



INDEX DIAGRAM

TOWNSHIP 24 SOUTH, RANGE 22 EAST,

		5	4		
6	5	4	8	3	2
		10	7	8	
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Subdivision of Section 3  
 Subdivision of Section 4  
 Subdivision of Section 9

pp. 11-13  
 pp. 13-15  
 pp. 15-18

T. 24 S., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the dependent resurvey of a portion of the north boundary and a portion of the subdivisional lines, and the subdivision of sections 3, 4 and 9, of Township 24 South, Range 22 East, Gila and Salt River Meridian, Arizona.

Philip Contzen surveyed the north boundary and the subdivisional lines in 1901.

Parcels 28, 37 and 38, as shown on the plat of survey entitled "Amended Plat Palominas Ranches Unit II" surveyed by Richard D. Riddell, Registered Land Surveyor No. 5015 and Registered Professional Engineer No. 1789, in 1982, were reacquired by the United States of America in consideration of the exchange of certain land and interests. After evaluation of Mr. Riddell's Plat of Survey and comparison to the dependent resurvey, it was determined that the aforementioned parcels are identical to their corresponding aliquot parts. Monumentation by Mr. Riddell was utilized in the course of this resurvey.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated November 19, 1997, for Group No. 821, Arizona.

Preliminary to the resurvey, the lines of the previous surveys were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The directions and distances of all lines were determined by use of the Trimble 4400 real time kinematic survey system, and refer to the true meridian.

The geographic position of the 1/4 section corner of sections 9 and 16, as determined from a relative global positioning vector made to Arizona Department of Transportation Triangulation station "GREEN 1982", with published latitude of 31°22'46.9241" N., and published longitude of 110°04'53.1204" W., NAD 83 (1992) is as follows:

Latitude: 31°21'03.24" N. Longitude: 110°06'49.81" W. NAD 83

The mean magnetic declination of 11 1/2° E., was derived from the U.S. Geological Survey computer program MAGPOINT, utilizing the Regional Magnetic Field Model for Epoch 1995 for the dates of survey.

Dependent Resurvey of a Portion of the North Boundary,  
T. 24 S., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">Restoring the survey executed by Philip Contzen, in 1901</p> <hr/>
	<p>Beginning at the cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., monumented by person(s) unknown, with a rebar, 5/8 in. diam., firmly set, 1/2 in. below the surface of pavement, with an affixed but illegible plastic cap. Cor. is located in the center line of Az. State Highway 92, 40 ft. wide, bears E. and W., which was identical with the township line as far back as 1924, according to Cochise County Highway Dept. maps, and at the intersection with the center line of Fox Hollow road, 25 ft. wide, improved dirt, bears N. and S. This is accepted as the best available evidence of the original cor. position. Not remonumented.</p> <p>S. 89°59' W., bet. secs. 3 and 34, on the N. bdy. of the Tp., along the center line of Az. State Highway 92.</p>
40.08	<p>The 1/4 sec. cor. of secs. 3 and 34, reestablished at proportionate dist., by Richard D. Riddell, R.L.S. 5015 and P.E. 1789, in 1982, as depicted on the Amended Plat of Palominas Ranches, Unit II, recorded at the Cochise County Clerk and Recorder in Bisbee, Az., monumented with a rebar, 5/8 in. diam., firmly set, 3 ins. below the surface of pavement, with an affixed but illegible plastic cap. This cor. is located in the center line of Az. State Highway 92, paved, 40 ft. wide, bears E. and W., which was identical with the township line as far back as 1924, according to Cochise County Highway Dept. maps. This is accepted as a careful and faithful reestablishment of the cor. position. Not remonumented.</p> <hr/>
20.04	<p>S. 89°59' W., beginning new measurement.</p> <p>The W. 1/16 sec. cor. of secs. 3 and 34, established by Richard D. Riddell, R.L.S. 5015 and P.E. 1789, in 1982, monumented with a rebar, 5/8 in. diam., firmly set, 3 ins. below pavement, with an affixed but illegible plastic cap, as depicted on the Amended Plat of Palominas Ranches, Unit II, recorded at the Cochise County Clerk and Recorder in Bisbee, Az. This is accepted as a careful and faithful establishment of the cor. position, from which</p>

Dependent Resurvey of a Portion of the North Boundary,  
T. 24 S., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 22 ins. in the ground, for a reference monument, bears S. 15°55' W., 57.8 ft. dist., with brass cap mkd. RM T24S R22E S3 57.8 FT TO W 1/16 COR. 1998, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post. Cor. is located 4 lks. N. of the S. R.O.W. fence of Az. State Highway 92, 4 strand barbed wire, bears E. and W.</p> <p>Cor. is located in the center line of Az. State Highway 92, paved, 40 ft. wide, bears E. and W.</p>
20.04	<p>S. 89°59' W., beginning new measurement.</p> <p>The cor. of secs. 3, 4, 33 and 34, remonumented by the Az. State Dept. of Highways, circa 1967, with a brass tablet, 3 ins. diam., firmly set, in concrete, and in a cast iron hand hole, with a 10 ins. diam. cast iron lid, 6 ins. below the surface of pavement, with brass cap mkd. ARIZONA HIGHWAY DEPT. The Az. State Highway Dept. remonumented a bolt at this cor. position around 1967, according to the Right-of-Way Plan of the Nogales-Lowell State Highway Project No. F-012-1-819, dated January 25, 1967. Cor. is located in the center line of Az. State Highway 92, 40 ft. wide, bears E. and W., which was identical with the township line as far back as 1924, according to Cochise County Highway Dept. maps. This is accepted as the best available evidence of the original cor. position. Not remonumented.</p>
40.205	<p>S. 89°56' W., bet. secs. 4 and 33, on the N. bdy. of the Tp., along the center line of Az. State Highway 92.</p> <p>The 1/4 sec. cor. of secs. 4 and 33, reestablished at proportionate dist., by Richard D. Riddell, R.L.S. 5015 and P.E. 1789, in 1982, monumented with a rebar, 1/2 in. diam., firmly set, 1 in. below pavement, as depicted on the Amended Plat of Palominas Ranches, Unit II, recorded at the Cochise County Clerk and Recorder in Bisbee, Az. Cor. is located in the center line of Az. State Highway 92, 40 ft. wide, bears E. and W., which was identical with the township line as far back as 1924, according to Cochise County Highway Dept. maps. This is accepted as a careful and faithful reestablishment of the cor. position, from which</p>

Dependent Resurvey of a Portion of the North Boundary,  
T. 24 S., R. 22 E., Gila and Salt River Meridian, Arizona

<p>CHAINS</p> <p>40.205</p>	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 23 ins. in the ground, for a reference monument, bears S. 37°35' E., 124.4 ft. dist., with brass cap mkd. RM T24S R22E S4 124.4 FT TO 1/4 COR. 1998, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post. Cor. is located 1 1/2 lks. N. of the S. R.O.W. fence of Az. State Highway 92, 4 strand barbed wire, bears E. and W.</p> <hr/> <p>S. 89°56' W., beginning new measurement.</p> <p>The cor. of secs. 4, 5, 32 and 33, remonumented by the Az. State Dept. of Highways, circa 1967, with a brass tablet, 3 ins. diam., firmly set, in concrete, and in a cast iron hand hole, with a 10 ins. diam. cast iron lid, 6 ins. below the surface of pavement, with brass cap mkd. ARIZONA HIGHWAY DEPT. The Az. State Highway Dept. remonumented a bolt at this cor. position around 1967, according to the Right-of-Way Plan of the Nogales-Lowell State Highway Project No. F-012-1-819, dated January 25, 1967. Cor. is located in the center line of Az. State Highway 92, 40 ft. wide, bears E. and W., which was identical with the township line as far back as 1924, according to Cochise County Highway Dept. maps, and at intersection with Palominas Road, paved to the N., improved dirt to the S., bears N. and S., This is accepted as the best available evidence of the original cor. position. Not remonumented.</p> <hr/> <p>Dependent Resurvey of a Portion of the Subdivisional Lines, T. 24 S., R. 22 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>Restoring the survey executed by Philip Contzen, in 1901</p> <hr/> <p>From the cor. of secs. 2, 3, 10 and 11, monumented with a redwood post, 4 x 4 ins., firmly set, projecting 15 ins. above ground, with illegible scribe marks on the N. and E. faces. Not remonumented.</p> <p>N. 0°04' E., bet. secs. 2 and 3.</p>
-----------------------------	--

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 24 S., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.09	<p>The 1/4 sec. cor. of secs. 2 and 3, reestablished at proportionate dist., by Richard D. Riddell, R.L.S. 5015 and P.E. 1789, in 1982, monumented with a rebar, 1/2 in. diam., firmly set, projecting 2 ins. above ground, with an affixed but illegible yellow plastic cap, as depicted on the Amended Plat of Palominas Ranches, Unit II, recorded at the Cochise County Clerk and Recorder in Bisbee, Az.; there is no remaining evidence of the original mkd. stone recovered around 1967. This is accepted as a careful and faithful reestablishment of the original cor. position. Not remonumented.</p> <p>Cor. is located 1/2 lk. N. of a cor. of fences, which is a wood post, 6 x 8 ins., projecting 5 ft. above ground, with barbed wire fences, 4 strand, extending N., S. and W.</p> <hr/> <p>N. 0°04' E., beginning new measurement.</p>
40.09	<p>The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 9 and 10, reestablished by proportionate measurement, by Richard D. Riddell, R.L.S. 5015 and P.E. 1789, in 1982, monumented with a rebar, 1/2 in. diam., firmly set, projecting 1 in. above ground, with affixed yellow plastic cap mkd. PE 1789, as depicted on the Amended Plat of Palominas Ranches, Unit II, recorded at the Cochise County Clerk and Recorder in Bisbee, Az. This is accepted as a careful and faithful reestablishment of the original cor. position. Not remonumented.</p> <p>Cor. is located approximately 50 lks. S. of a wash, drains NW.</p> <p>N. 0°06' E., bet. secs. 9 and 10.</p>
20.04	<p>The N. 1/16 sec. cor. of secs. 9 and 10, established by Richard D. Riddell, R.L.S. 5015 and P.E. 1789, in 1982, monumented with a rebar, 1/2 in. diam., firmly set, projecting 1 in. above ground, with affixed yellow plastic cap mkd. PE 1789, as depicted on the Amended Plat of Palominas Ranches, Unit II, recorded at the Cochise County Clerk and Recorder in Bisbee, Az. This is accepted as a careful and faithful establishment of the cor. position. Not remonumented.</p> <hr/> <p>N. 0°06' E., beginning new measurement.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 24 S., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS									
20.04	<p>The cor. of secs. 3, 4, 9 and 10, reestablished at proportionate dist., by Richard D. Riddell, R.L.S. 5015 and P.E. 1789, in 1982, monumented with a rebar, 1/2 in. diam., 15 ins. long, firmly set, in concrete, projecting 3 ins. above ground, as depicted on the Amended Plat of Palominas Ranches, Unit II, recorded at the Cochise County Clerk and Recorder in Bisbee, Az. This cor. position is identical with the SE cor. of Parcel 37, as shown on the above described plat. This is accepted as a careful and faithful reestablishment of the cor. position.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="855 778 1004 938"> <tr> <td>T24S</td> <td>R22E</td> </tr> <tr> <td>S 4</td> <td>S 3</td> </tr> <tr> <td>S 9</td> <td>S10</td> </tr> <tr> <td colspan="2">1998</td> </tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post and deposit the local rebar inside of the stainless steel post.</p> <p>Cor. is located 2 lks. S. of a barbed wire fence, 4 strand, bears E. and W.</p>	T24S	R22E	S 4	S 3	S 9	S10	1998	
T24S	R22E								
S 4	S 3								
S 9	S10								
1998									
40.065	<p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>West, bet. secs. 3 and 10.</p> <p>The 1/4 sec. cor. of secs. 3 and 10, reestablished at proportionate dist., by Richard D. Riddell, R.L.S. 5015 and P.E. 1789, in 1982, monumented with a rebar, 1/2 in. diam., firmly set, projecting 2 ins. above ground, with affixed yellow plastic cap mkd. PE 1789, as depicted on the Amended Plat of Palominas Ranches, Unit II, recorded at the Cochise County Clerk and Recorder in Bisbee, Az. This is accepted as a careful and faithful reestablishment of the cor. position. Not remonumented.</p> <p>Cor. is located in a barbed wire fence, 4 strand, bears E. and W.</p> <p>West, beginning new measurement.</p>								
40.065	<p>The cor. of secs. 3, 4, 9 and 10.</p> <p>N. 0°02' E., bet. secs. 3 and 4.</p>								

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 24 S., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS	
20.04	<p>The S. 1/16 sec. cor. of secs. 3 and 4, established by Richard D. Riddell, R.L.S. 5015 and P.E. 1789, in 1982, monumented with a rebar, 1/2 in. diam., 16 ins. long, firmly set, 3 ins. below the surface of ground, as depicted on the Amended Plat of Palominas Ranches, Unit II, recorded at the Cochise County Clerk and Recorder in Bisbee, Az. This cor. position is identical with the SE cor. of Parcel 28 and the NE cor. of Parcel 37, as shown on the above described plat. This is accepted as a careful and faithful establishment of the cor. position.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T24S R22E S 1/16 S 4   S 3 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post and deposit the local rebar inside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°02' E., beginning new measurement.</p>
20.04	<p>The 1/4 sec. cor. of secs. 3 and 4, reestablished at proportionate dist., by Richard D. Riddell, R.L.S. 5015 and P.E. 1789, in 1982, monumented with a rebar, 1/2 in. diam, 15 ins. long, firmly set, projecting 3 ins. above ground, with affixed yellow plastic cap mkd. PE 1789, in a well embedded collar of stone, as depicted on the Amended Plat of Palominas Ranches, Unit II, recorded at the Cochise County Clerk and Recorder in Bisbee, Az. This cor. position is identical with the NE cor. of Parcel 28, as shown on the above described plat. This is accepted as a careful and faithful reestablishment of the cor. position.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T24S R22E 1/4 S 4   S 3 1998</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 24 S., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.08	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post and deposit the local rebar inside the stainless steel post.</p> <hr/> <p>N. 0°02' E., beginning new measurement.</p> <p>The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., hereinbefore described.</p> <hr/>
20.04	<p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>N. 89°58' W. bet. secs. 4 and 9.</p> <p>The E. 1/16 sec. cor. of secs. 4 and 9, established by Richard D. Riddell, R.L.S. 5015 and P.E. 1789, in 1982, monumented with a rebar, 1/2 in. diam., 16 ins. long, firmly set, projecting 4 ins. above ground, with affixed yellow plastic cap mkd. PE 1789, as depicted on the Amended Plat of Palominas Ranches, Unit II, recorded at the Cochise County Clerk and Recorder in Bisbee, Az. This cor. position is identical with the SW cor. of Parcel 37 and the NE cor. of Parcel 38, as shown on the above described plat. This is accepted as a careful and faithful establishment of the cor. position.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T24S R22E</p> <p>S 4</p> <p>E 1/16 —</p> <p>S 9</p> <p>1998</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post and deposit the local rebar inside the stainless steel post.</p> <p>Cor. is located 30 lks. south of a track road, 9 ft. wide, bears E. and W.</p> <hr/> <p>N. 89°58' W., beginning new measurement.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 24 S., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS	
20.04	<p>The 1/4 sec. cor. of secs. 4 and 9, perpetuated by Richard D. Riddell, R.L.S. 5015 and P.E. 1789, in 1982, monumented with a rebar, 1/2 in. diam., 15 ins. long, firmly set, projecting 3 ins. above ground, as depicted on the Amended Plat of Palominas Ranches, Unit II, recorded at the Cochise County Clerk and Recorder in Bisbee, Az. The original redwood post, 36 x 4 x 2 ins., split in half, with no visible scribe marks, was found lying loosely on the surface of the ground near this position. This cor. position is identical with the NW cor. of Parcel 38, as shown on the above described plat. This is accepted as a careful and faithful perpetuation of the original cor. position.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T24S R22E S 4 1/4 — S 9 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post and deposit the local rebar inside the stainless steel post.</p> <p>Remove the original redwood post from the area.</p>
<p>Subdivision of Section 3, T. 24 S., R. 22 E., Gila and Salt River Meridian, Az.</p>	
40.08	<p>From the 1/4 sec. cor. of secs. 3 and 10.</p> <p>N. 0°03' E., on the N. and S. center line of sec. 3.</p> <p>The center 1/4 sec. cor. of sec. 3, established at intersection with the E. and W. center line of sec. 3, by Richard D. Riddell, R.L.S. 5015 and P.E. 1789, in 1982, monumented with a rebar, 1/2 in. diam., firmly set, projecting 2 ins. above ground, as depicted on the Amended Plat of Palominas Ranches, Unit II, recorded at the Cochise County Clerk and Recorder in Bisbee, Az. This is accepted as a careful and faithful establishment of the cor. position. Not remonumented.</p> <p>Cor. is located 1/2 lk. N. of a cor. of fences, which is a wood post, 6 x 8 ins., projecting 5 ft. above ground, with barbed wire fences, 4 strand, extending N. and E.</p>

Subdivision of Section 3,  
T. 24 S., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS	
	N. 0°03' E., beginning new measurement.
40.09	The 1/4 sec. cor. of secs. 3 and 34, on the N. bdy. of the Tp.
	From the 1/4 sec. cor. of secs. 2 and 3.
	West, on the E. and W. center line of sec. 3.
40.07	The center 1/4 sec. cor. of sec. 3.
	West, beginning new measurement.
20.04	<p>The center W. 1/16 sec. cor. of sec. 3, established by Richard D. Riddell, R.L.S. 5015 and P.E. 1789, in 1982, monumented with a rebar, 1/2 in. diam., 16 ins. long, firmly set, projecting 1 in. above ground, with an affixed but illegible yellow plastic cap, as depicted on the Amended Plat of Palominas Ranches, Unit II, recorded at the Cochise County Clerk and Recorder in Bisbee, Az. This is accepted as a careful and faithful establishment of the cor. position.</p>
	At the cor. point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, encircled with a collar of stone, with brass cap mkd.
	<p style="text-align: center;">T24S R22E W 1/16 C ————— C S 3 1998</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post and deposit the local rebar inside the stainless steel post.
	Cor. is located 20 lks. E. of the center of an improved dirt road, 12 ft. wide, bears N. and S.
	West, beginning new measurement.
20.04	The 1/4 sec. cor. of secs. 3 and 4.

Subdivision of Section 3,  
T. 24 S., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>NW 1/4</p> <hr style="width: 10%; margin: auto;"/>
	<p>From the center W. 1/16 sec. cor. of sec. 3.</p> <p>N. 0°02' E. on the N. and S. center line of the NW 1/4 of sec. 3, along a meandering dirt road.</p>
40.08	<p>The W. 1/16 sec. cor. of secs. 3 and 10, on the N. bdy. of the Tp.</p> <hr/>
	<p>Subdivision of Section 4, T. 24 S., R. 22 E., Gila and Salt River Meridian, Az.</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 4 and 9.</p> <p>N. 0°03' W., on the N. and S. center line of sec. 4.</p>
20.02	<p>Point for the center S. 1/16 sec. cor. of sec. 4. Not monumented.</p>
40.04	<p>Point for the center 1/4 sec. cor. of sec. 4, at intersection with the E. and W. center line of sec. 4</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T24S R22E C 1/4 S4 1998</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
80.08	<p>The 1/4 sec. cor. of secs. 4 and 33, on the N. bdy. of the Tp.</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 3 and 4.</p> <p>S. 89°59' W., on the E. and W. center line of sec. 4.</p>

Subdivision of Section 4,  
T. 24 S., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS	
20.07	<p>The center E. 1/16 sec. cor. of sec. 4, established by Richard D. Riddell, R.L.S. 5015 and P.E. 1789, in 1982, monumented with a rebar, 1/2 in. diam., firmly set, projecting 3 ins. above ground, as depicted on the Amended Plat of Palominas Ranches, Unit II, recorded at the Cochise County Clerk and Recorder in Bisbee, Az. This cor. position is identical with the NW cor. of Parcel 28, as shown on the above described plat. This is accepted as a careful and faithful establishment of the cor. position. Not remonumented.</p>
20.07	<p>S. 89°59' W., beginning new measurement.</p>
20.07	<p>The center 1/4 sec. cor. of sec. 4.</p>
60.22	<p>The 1/4 sec. cor. of secs. 4 and 5, monumented by Richard D. Riddell, R.L.S. 5015 and P.E. 1789, unknown date, with an iron pipe, 1 1/2 ins. diam., firmly set, flush with ground, with affixed iron end cap mkd. PE 1789. This is accepted as the best available evidence of the original cor. position. Not remonumented.</p> <p>Cor. is located 2 lks. S. of a cor. of fences, which is a wooden post, 6 x 8 ins., projecting 4 ft. above ground, with barbed wire fences, 4 strand, extending S. and W.</p> <p>From this cor. point, the cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., bears N. 0°08' W., 40.005 chs dist.</p>
20.03	<p style="text-align: center;">SE 1/4</p> <hr/> <p>From the E. 1/16 sec. cor. of secs. 4 and 9.</p> <p>N. 0°01' W., on the N. and S. center line of the SE 1/4 of sec. 4.</p> <p>The SE 1/16 sec. cor. of sec. 4, established at intersection with the E. and W. center line of the SE 1/4 of sec. 4, by Richard D. Riddell, R.L.S. 5015 and P.E. 1789, in 1982, monumented with a rebar, 1/2 in. diam., firmly set, projecting 4 ins. above ground, as depicted on the Amended Plat of Palominas Ranches, Unit II, recorded at the Cochise County Clerk and Recorder in Bisbee, Az. This cor. position is identical with the SW cor. of Parcel 28 and the NW cor. of Parcel 37, as shown on the above described plat. This is accepted as a careful and faithful establishment of the cor. position. Not remonumented.</p> <hr/> <p>N. 0°01' W., beginning new measurement.</p>

Subdivision of Section 4,  
T. 24 S., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS	
20.03	The center E. 1/16 sec. cor. of sec. 4.
	<p>From the S. 1/16 sec. cor. of secs. 3 and 4.</p> <p>N. 89°59' W., on the E. and W. center line of the SE 1/4 of sec. 4.</p>
20.06	<p>The SE 1/16 sec. cor. of sec. 4.</p> <hr/> <p>N. 89°59' W., beginning new measurement.</p>
20.06	The point for the center S. 1/16 sec. cor. of sec. 4.
	<p style="text-align: center;">Subdivision of Section 9, T. 24 S., R. 22 E., Gila and Salt River Meridian, Az.</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 9 and 16, monumented with the decayed remains of the original redwood post, at the center of a hole, 1 ft. diam., 1 1/2 ft. deep, with a steel fence post set alongside.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T24S R22E S 9 1/4 — S16 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>N. 0°04' E., on the N. and S. center line of sec. 9.</p>
40.06	<p>The center 1/4 sec. cor. of sec. 9, established at intersection with the E. and W. center line of sec. 9, by Richard D. Riddell, R.L.S. 5015 and P.E. 1789, in 1982, monumented with a rebar, 1/2 in. diam., 15 ins. long, firmly set, 4 ins. below the surface of ground, with a steel fence post set nearby, as depicted on the Amended Plat of Palominas Ranches, Unit II, recorded at the Cochise County Clerk and Recorder in Bisbee, Az. This is accepted as a careful and faithful establishment of the cor. position.</p>

Subdivision of Section 9,  
T. 24 S., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T24S R22E C 1/4 S9 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post and deposit the local rebar inside the stainless steel post.</p> <hr/> <p>N. 0°04' E., beginning new measurement.</p>
20.03	<p>The center N. 1/16 sec. cor. of sec. 9, established by Richard D. Riddell, R.L.S. 5015 and P.E. 1789, in 1982, monumented with a rebar, 1/2 in. diam., 16 ins. long, firmly set, projecting 2 ins. above ground, with an affixed but illegible cracked yellow plastic cap, as depicted on the Amended Plat of Palominas Ranches, Unit II, recorded at the Cochise County Clerk and Recorder in Bisbee, Az. This cor. position is identical with the SW cor. of Parcel 38, as shown on the above described plat. This is accepted as a careful and faithful establishment of the cor. position.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T24S R22E C N 1/16   S9 C 199</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post and deposit the local rebar inside the stainless steel post.</p> <hr/> <p>N. 0°04' E., beginning new measurement.</p>
20.03	<p>The 1/4 sec. cor. of secs. 4 and 9.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 9 and 10.</p> <p>N. 89°56' W., on the E. and W. center line of sec. 9.</p>

Subdivision of Section 9,  
T. 24 S., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS	
20.035	<p>The center E. 1/16 sec. cor. of sec. 9, established by Richard D. Riddell, R.L.S. 5015 and P.E. 1789, in 1982, monumented with a rebar, 1/2 in. diam., firmly set, projecting 2 ins. above ground, with a steel fence post set nearby, as depicted on the Amended Plat of Palominas Ranches, Unit II, recorded at the Cochise County Clerk and Recorder in Bisbee, Az. This is accepted as a careful and faithful establishment of the cor. position. Not remonumented.</p> <hr/> <p>N. 89°56' W., beginning new measurement.</p>
20.035	<p>The center 1/4 sec. cor. of sec. 9.</p> <hr/> <p>N. 89°56' W., beginning new measurement.</p>
40.11	<p>The 1/4 sec. cor of secs. 8 and 9, monumented by Richard D. Riddell, R.L.S. 5015 and P.E. 1789, in 1982, with a rebar, 1/2 in. diam., 15 ins. long, firmly set, projecting 3 ins. above ground, with a steel fence post set nearby, as depicted on the Amended Plat of Palominas Ranches, Unit II, recorded at the Cochise County Clerk and Recorder in Bisbee, Az. This is accepted as the best available evidence of the orig. cor. position.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T24S R22E 1/4 S 8   S 9 1998</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post and deposit the local rebar inside the stainless steel post.</p> <hr/>
	<div style="text-align: center;"> <p>NE 1/4</p> <hr/> </div> <p>From the center E. 1/16 sec. cor. of sec. 9.</p> <p>N. 0°05' E., on the N. and S. center line of the NE 1/4 of sec. 9.</p>

Subdivision of Section 9,  
T. 24 S., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS	
20.03	<p>The NE 1/16 sec. cor. of sec. 9, established at intersection with the E. and W. center line of the NE 1/4 of sec. 9, by Richard D. Riddell, R.L.S. 5015 and P.E. 1789, in 1982, monumented with a rebar, 1/2 in. diam., 16 ins. long, firmly set, projecting 2 ins. above ground, with a broken but affixed and illegible yellow plastic cap, with a steel fence post set nearby, as depicted on the Amended Plat of Palominas Ranches, Unit II, recorded at the Cochise County Clerk and Recorder in Bisbee, Az. This cor. position is identical with the SE cor. of Parcel 38, as shown on the above described plat. This is accepted as a careful and faithful establishment of the cor. position.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T24S R22E NE 1/16 S9 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post and deposit the local rebar inside the stainless steel post.</p> <hr/> <p>N. 0°05' E., beginning new measurement.</p>
20.03	<p>The E. 1/16 sec. cor. of secs. 4 and 9.</p> <hr/> <p>From the N. 1/16 sec. cor. of secs. 9 and 10.</p> <p>N. 89°57' W., on the E. and W. center line of the NE 1/4 of sec. 9.</p>
20.04	<p>The NE 1/16 sec. cor. of sec. 9.</p> <hr/> <p>N. 89°57' W., beginning new measurement.</p>
20.04	<p>The center N. 1/16 sec. cor. of sec. 9.</p> <hr/>

T. 24 S., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS	GENERAL DESCRIPTION
	<p>The area of the survey is near the town of Palominas, Arizona. Access is by way of Arizona State Highway 92.</p> <p>Elevation is about 4500 feet above sea level.</p> <p>Vegetation consists of mesquite, creosote, and catclaw, as well as various grasses in the lower and wetter areas.</p> <p>Principal uses of the area are cattle grazing, farming, and recreational activities.</p>

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

## FIELD ASSISTANTS

NAMES	CAPACITY
W. William Foster	Surveying Technician
Geoffrey A. Graham	Surveying Technician
Cheryl A. Hansen	Surveying Technician
Robert J. Lyle	Surveying Technician
Mark S. Searles	Surveying Technician

CERTIFICATE OF SURVEY

I, Stephen K. Hansen, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 19th day of November, 1997, I have dependently resurveyed a portion of the north boundary and a portion of the subdivisional lines, and subdivided sections 3, 4 and 9, of Township 24 South, Range 22 East, of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

3/04/98  
(Date)

Stephen K. Hansen  
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Arizona State Office  
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of a portion of the north boundary and a portion of the subdivisional lines, and the subdivision of sections 3, 4 and 9, of Township 24 South, Range 22 East, Gila and Salt River Meridian, Arizona, executed by Stephen K. Hansen, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

MAR 13 1998  
(Date)

Henry D. Rowntree  
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in T. 24 S., R. 22 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~\_\_\_\_\_  
(Date)~~

~~\_\_\_\_\_  
(Chief Cadastral Surveyor of Arizona)~~