

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTES  
OF THE

---

SURVEY OF

---

THE NINTH STANDARD PARALLEL NORTH,

---

(SOUTH BOUNDARY),

---

THE EAST AND NORTH BOUNDARIES

---

AND

---

A PORTION OF THE SUBDIVISIONAL LINES,

---

TOWNSHIP 37 NORTH, RANGE 20 EAST,

---

Of the Gila and Salt River Meridian,  
In the State of Arizona

EXECUTED BY

Leonard R. Sandoval, Cadastral Surveyor

---

Under Special Instructions dated and approved June 6, 1996, and Amended Special Instructions dated and approved August 13, 1997, which provided for the surveys included under Group Number 802 and assignment instructions dated June 6, 1996.

Survey Commenced July 22, 1997

Survey Completed March 31, 1998

## INDEX DIAGRAM

TOWNSHIP 37 NORTH, RANGE 20 EAST,

GILA AND SALT RIVER MERIDIAN, ARIZONA

21 6 59	20 5 52	19 4 46	18 3 38	17 2 29	16 1 15
58 7 57	58 8 51	52 9 45	46 10 36	37 11 28	29 12 14
56 18 55	56 17 49	50 16 43	44 15 35	36 14 26	27 13 13
54 19	53 20 48	49 21 42	43 22 33	34 23 25	26 24 12
30	29	47 28 40	41 27 32	33 26 23	24 25 11
31 4	32 5	33 38 6	39 34 30 7	31 35 21 8	22 36 10 9

## T. 37 N., R. 20 E., Gila and Salt River Meridian, Arizona

## CHAINS

The following field notes describe the survey of the Ninth Standard Parallel North, (south boundary), the east and north boundaries and a portion of the subdivisional lines, Township 37 North, Range 20 East, Gila and Salt River Meridian, Arizona.

The standard corner of Tps. 37 N., Rs. 19 and 20 E. was established, and the west boundary surveyed, by Jones Curtiss in 1997-98, concurrently under this same group.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, Special Instructions dated June 6, 1996, and Amended Special Instructions dated August 13, 1997, for Group No. 802, Arizona.

The directions of all lines were determined by the technique of differential positioning using the Ashtech M-Series Geodetic Positioning System and direct hour angle observations on the sun, and refer to the true meridian. Distances and angles were measured with Sokkia SET2BII, Topcon GTS3B and Lietz SET4A total station instruments.

The geographic position of the southeast corner of the township was determined by the technique of differential positioning using the Ashtech M-Series Geodetic Positioning System. First order National Geodetic Survey triangulation stations "COAL MINE 1951" and "KAYENTA 1951" were used as control stations. The geographic position is as follows:

Lat.: 36°33'48.839" N. Long.: 110°07'41.003" W. NAD83 (1992)

The mean magnetic declination is 12 1/2° E.

Survey of the Ninth Standard Parallel North, (South Boundary),  
T. 37 N., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Beginning at the stan. cor. of Tps. 37 N., Rs. 19 and 20 E., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set, and mkd. as described in the field notes of the survey of the Ninth Standard Parallel North, (south boundary), T. 37 N., R. 19 E., executed concurrently under this same group.</p> <p>Cor. is located in Moenkopi Canyon, 2.10 chs. W. of a graded road, 15 ft. wide, and 2.30 chs. W. of a power line, both bear NE and SW.</p> <p>East, on the S. bdy. of sec. 31.</p> <p>Over rolling land in Moenkopi Canyon.</p>
6.60	<p>Moenkopi Wash, 40 ft. wide, 12 ft. deep, drains WSW; thence ascend from Moenkopi Canyon and over top of mesa, over broken and rolling land.</p>
40.00	<p>Point for the stan. 1/4 sec. cor. of sec. 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T37N R20E 1/4 S31 ----- 1997</p> <p>from which</p> <p style="padding-left: 40px;">A piñon, 11 ins. diam., bears N. 40 3/4° W., 77 lks. dist., mkd. 1/4 S31 SC BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the stan. cor. of secs. 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T37N R20E S31   S32 ----- 1997</p>

Survey of the Ninth Standard Parallel North, (South Boundary),  
T. 37 N., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>from which</p> <p>A juniper, 11 ins. diam., bears N. 21 1/4° E., 68 1/2 lks. dist., mkd. T37N R20E S32 SC BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, broken and rolling. Soil, sandy and rocky clay with rock outcrops. Timber, piñon, juniper and ponderosa pine; undergrowth, brush and native grasses.</p> <hr/> <p>East, on the S. bdy. of sec. 32.</p> <p>Over rolling land atop a mesa.</p> <p>Point for the stan. 1/4 sec. cor. of sec. 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T37N R20E 1/4 S32</p> <hr style="width: 20%; margin: auto;"/> <p style="text-align: center;">1997</p>
80.00	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Point for the stan. cor. of secs. 32 and 33, falls on the face of a high cliff; where it is impracticable to establish a permanent monument.</p> <p>From this cor. point, the point selected for the witness cor. to the stan. cor. of secs. 32 and 33, bears N. 45°00' E., 1.50 chs. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">WC SC T37N R20E S32   S33</p> <hr style="width: 20%; margin: auto;"/> <p style="text-align: center;">1997</p> <p style="text-align: center;">↙</p>

Survey of the Ninth Standard Parallel North, (South Boundary),  
T. 37 N., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Witness cor. is located 70 lks. N. of high cliff at S. rim of a spur of Black Mesa, bears E. and W.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay with rock outcrops. Timber, piñon, juniper and ponderosa pine; undergrowth, brush and native grasses.</p>
	<p>East, on the S. bdy. of sec. 33.</p> <p>Over rugged land below high cliff.</p>
36.70	<p>W. rim of a spur of Black Mesa, bears N. and S.; thence over rolling land across spur of Black Mesa.</p>
40.00	<p>Point for the stan. 1/4 sec. cor. of sec. 33.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T37N R20E 1/4 S33</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">1997</p>
	<p>from which</p> <p style="padding-left: 40px;">The mks. X B0, chiseled on the face of a sandstone boulder, 8 x 5 x 3 1/2 ft., bear N. 5 1/2° E., 15 lks. dist.</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
56.80	<p>NE rim of a spur of Black Mesa, atop high cliff, bears ESE and WNW; thence descend abruptly over rugged slope of Black Mesa.</p>
80.00	<p>Point for the stan. cor. of secs. 33 and 34.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the Ninth Standard Parallel North, (South Boundary),  
T. 37 N., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">SC T37N R20E S33   S34 ----- 1997</p> <p>from which</p> <p style="padding-left: 40px;">The mks. X B0, chiseled on the face of a sandstone boulder, 30 x 20 x 15 ft., bear N. 76 1/4° E., 81 lks. dist.</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located on rugged slope of Black Mesa, bears ESE and WNW.</p> <p>Land, rugged to rolling to rugged. Soil, sandy and rocky clay with rock outcrops. Timber, piñon, juniper and ponderosa pine; undergrowth, brush and native grasses.</p>
	<p>East, on the S. bdy. of sec. 34.</p> <p>Over rugged and broken land, on descent of E. slope of Black Mesa.</p>
40.00	<p>Point for the stan. 1/4 sec. cor. of sec. 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">SC T37N R20E 1/4 S34 ----- 1997</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Thence over rolling land.</p>
80.00	<p>Point for the stan. cor. of secs. 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the Ninth Standard Parallel North, (South Boundary),  
T. 37 N., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">SC T37N R20E S34   S35 <hr/>1997</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rugged and broken to rolling. Soil, sandy and rocky clay with rock outcrops. Timber, piñon and juniper; undergrowth, scattered brush and native grasses.</p>
40.00	<p>East, on the S. bdy. of sec. 35</p> <p>Over rolling land.</p> <p>Point for the stan. 1/4 sec. cor. of sec. 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.</p>
80.00	<p style="text-align: center;">SC T37N R20E 1/4 S35 <hr/>1997</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located on E. edge of a trail road, bears N. and S.</p> <p>Point for the stan. cor. of secs. 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">SC T37N R20E S35   S36 <hr/>1997</p> <p>from which</p> <p style="text-align: center;">A piñon, 7 ins. diam., bears N. 72 1/4° W., 1.435 chs. dist., mkd. T37N R20E S35 SC BT.</p>

Survey of the Ninth Standard Parallel North, (South Boundary),  
T. 37 N., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy and rocky clay. Timber, scattered piñon and juniper; undergrowth, scattered brush and native grasses.</p>
40.00	<p>East, on the S. bdy. of sec. 36.</p> <p>Over rolling land.</p> <p>Point for the stan. 1/4 sec. cor. of sec. 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T37N R20E 1/4 S36 ----- 1997</p>
80.00	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Point for the stan. cor. of Tps. 37 N., Rs. 20 and 21 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T37N R20E   R21E S36   S31 ----- 1997</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy and rocky clay. Timber, scattered piñon and juniper; undergrowth, scattered brush and native grasses.</p>

Survey of the East Boundary,  
T. 37 N., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the stan. cor. of Tps. 37 N., Rs. 20 and 21 E., on the Ninth Standard Parallel North, hereinbefore described.</p> <p>North, bet. secs. 31 and 36.</p> <p>Over rolling land.</p>
16.20	Cane Wash, 60 ft. wide, 3 ft. deep, drains ESE.
40.00	<p>Point for the 1/4 sec. cor. of secs. 31 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T37N R20E R21E 1/4 S36   S31 1997</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
62.91	Intersect the S. side of a wood frame house, 40 x 25 ft., the SE cor. bears East, 27 lks. dist., long side bears N.
74.77	Southernmost cor. of a stuccoed house, 24 x 18 ft., bears East, 3.35 chs. dist., long side bears NE.
80.00	<p>Point for the cor. of secs. 25, 30, 31, and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T37N R20E   R21E S25   S30 ----- S36   S31 1997</p> </div> <p>from which</p> <p>A piñon, 12 ins. diam., bears N. 67 3/4° E., 1.125 chs. dist., mkd. T37N R21E S30 BT.</p> <p>A forked piñon, 13 ins. diam. at base, bears N. 12 1/4° W., 1.47 chs. dist., mkd. T37N R20E S25 BT.</p>

Survey of the East Boundary,  
T. 37 N., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, scattered brush and native grasses.</p>
	<p>North, bet. secs. 25 and 30.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T37N R20E R21E 1/4 S25   S30 1997</p> </div>
66.20	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Graded road, 25 ft. wide, bears E. in curve to right.</p>
74.60	<p>Underground water line, bears SE and NW.</p>
75.20	<p>Power line, bears ESE and WNW.</p>
80.00	<p>Point for the cor. of secs. 19, 24, 25, and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T37N R20E   R21E S24   S19 ----- S25   S30 1997</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>

Survey of the East Boundary,  
T. 37 N., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, gently rolling. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, scattered brush and native grasses.</p>
	<p>North, bet. secs. 19 and 24.</p> <p>Over gently rolling land.</p>
37.10	Trail road, bears E. and W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T37N R20E R21E 1/4 S24   S19 1997</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
59.70	Power line, bears ENE and WSW.
77.60	Graded road, 25 ft. wide, bears NE and SW.
80.00	<p>Point for the cor. of secs. 13, 18, 19, and 24.</p> <p>Set a magnet in a 1 x 1 x 2 ins. white colored plastic case, 24 ins. below the surface of ground.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 50°00' E., 60.0 ft. dist., with brass cap mkd. T37N R21E S19 RM 60.0 FT. TO COR. 1997 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 50°00' W., 80.0 ft. dist., with brass cap mkd. T37N R20E S13 RM 80.0 FT. TO COR. 1997 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>

Survey of the East Boundary,  
T. 37 N., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS													
	<p>Cor. is located in a wash, 12 ft. wide, 3 ft. deep, drains NNE.</p> <p>Land, gently rolling. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, scattered brush and native grasses.</p>												
	<p>North, bet. secs. 13 and 18.</p>												
	<p>Over gently rolling land.</p>												
8.40	<p>Navajo Route 59A, a graded road, 25 ft. wide, bears SSE and NNW.</p>												
28.80	<p>Power line, bears SSE and NNW.</p>												
34.30	<p>Graded road, 25 ft. wide, bears NE and SW.</p>												
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 18.</p>												
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>												
	<table border="0" style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T37N</td></tr> <tr><td style="text-align: center;">R20E</td><td style="text-align: center;">R21E</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td style="text-align: center;">S13</td><td style="text-align: center;">S18</td></tr> <tr><td colspan="2" style="text-align: center;">1997</td></tr> </table>	T37N		R20E	R21E	1/4		S13	S18	1997			
T37N													
R20E	R21E												
1/4													
S13	S18												
1997													
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>												
80.00	<p>Point for the cor. of secs. 7, 12, 13, and 18.</p>												
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>												
	<table border="0" style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T37N</td></tr> <tr><td style="text-align: center;">R20E</td><td style="text-align: center;">R21E</td></tr> <tr><td style="text-align: center;">S12</td><td style="text-align: center;">S 7</td></tr> <tr><td colspan="2" style="text-align: center;">-----</td></tr> <tr><td style="text-align: center;">S13</td><td style="text-align: center;">S18</td></tr> <tr><td colspan="2" style="text-align: center;">1997</td></tr> </table>	T37N		R20E	R21E	S12	S 7	-----		S13	S18	1997	
T37N													
R20E	R21E												
S12	S 7												
-----													
S13	S18												
1997													
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>												

Survey of the East Boundary,  
T. 37 N., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, gently rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p> <hr/> <p>North, bet. secs. 7 and 12.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T37N R20E R21E 1/4 S12   S 7 1997</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 1, 6, 7, and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T37N R20E   R21E S 1   S 6 <hr/>S12   S 7 1997</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p> <hr/> <p>North, bet. secs. 1 and 6.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 6.</p>

Survey of the East Boundary,  
T. 37 N., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T37N R20E   R21E 1/4 S 1   S 6 1997</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
44.55	Trail road, bears ENE and WSW.
80.00	<p>Point for the cor. of Tps. 37 and 38 N., Rs. 20 and 21 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T38N R20E   R21E S36   S31 ----- S 1   S 6 T37N 1997</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 45 lks. W. and 1.65 chs. S. of a trail road, bears SSE and NNW.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p>

Survey of the North Boundary,  
T. 37 N., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the cor. of Tps. 37 and 38 N., Rs. 20 and 21 E., hereinbefore described.</p> <p>West, bet. secs. 1 and 36.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T38N R20E S36 1/4 — S 1 T37N 1997</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
47.30	<p>W. rim of a mesa, atop sandstone cliff, bears NE and SW; thence descend abruptly into Church Rock Valley and nearly level land.</p>
80.00	<p>Point for the cor. of secs. 1, 2, 35, and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T38N R20E S35   S36 —   — S 2   S 1 T37N 1997</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 2.32 chs. E. of a woven wire and barbed wire fence, bears NE and SW.</p>

CHAINS	
	Land, rolling to nearly level. Soil, sandy and rocky clay with rock outcrops. No timber; scattered brush and native grasses.
	West, bet. secs. 2 and 35.  Over nearly level land.
9.56	Woven wire and barbed wire fence, bears NE and SW.
23.80	Trail road, bears N. and S.
40.00	Point for the 1/4 sec. cor. of secs. 2 and 35.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T38N R20E S35 1/4 — S 2 T37N 1997
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
45.70	Wash, 10 ft. wide, 6 ft. deep, drains NNE.
80.00	Point for the cor. of secs. 2, 3, 34, and 35.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T38N R20E S34   S35 ———— S 3   S 2 T37N 1997
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.

CHAINS											
	<p>Land, nearly level. Soil, sandy clay. No timber; scattered brush and native grasses.</p> <hr/> <p>West, bet. secs. 3 and 34. Over nearly level land.</p>										
18.05	Trail road, bears NNE and SSW.										
38.35	Trail road, bears NE and SW.										
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T38N R2OE S34 1/4 — S 3 T37N 1997</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>										
49.10	Navajo Route 59A, a graded road, 25 ft. wide, bears SE and NW.										
80.00	<p>Point for the cor. of secs. 3, 4, 33, and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. below the surface of the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td colspan="2" style="text-align: center;">T38N R2OE</td> </tr> <tr> <td style="text-align: center; border-right: 1px solid black;">S33</td> <td style="text-align: center;">S34</td> </tr> <tr> <td colspan="2" style="text-align: center;">—</td> </tr> <tr> <td style="text-align: center; border-right: 1px solid black;">S 4</td> <td style="text-align: center;">S 3</td> </tr> <tr> <td colspan="2" style="text-align: center;">T37N 1997</td> </tr> </table> </div> <p>from which</p> <p style="margin-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 45°00' E., 50.0 ft. dist., with brass cap mkd. T37N R2OE S3 RM 50.0 FT. TO COR. 1997 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>	T38N R2OE		S33	S34	—		S 4	S 3	T37N 1997	
T38N R2OE											
S33	S34										
—											
S 4	S 3										
T37N 1997											