

ORIGINAL

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES
OF THE

SURVEY OF

THE SIXTH GUIDE MERIDIAN EAST,

(WEST BOUNDARY),

THE EAST AND NORTH BOUNDARIES,

AND

THE SUBDIVISIONAL LINES,

TOWNSHIP 33 NORTH, RANGE 25 EAST,

Of the Gila and Salt River Meridian,
In the State of Arizona

EXECUTED BY

Leonard R. Sandoval, Cadastral Surveyor

Under Special Instructions dated and approved February 17, 1998, which provided for the surveys included under Group Number 822 and assignment instructions dated February 17, 1998.

Survey Commenced October 26, 1998
Survey Completed January 7, 1999

INDEX DIAGRAM

TOWNSHIP 33 NORTH, RANGE 25 EAST,

GILA AND SALT RIVER MERIDIAN, ARIZONA

8	22 6	21 5	20 4	19 3	18 2	17 1	16
7	66 7	66 8	55 9	47 10	39 11	30 12	15
6	64 18	64 17	54 16	46 15	38 14	28 13	14
5	62 19	62 20	52 21	44 22	36 23	27 24	12
4	60 30	59 29	51 28	43 27	35 26	25 25	11
4	58 31	57 32	50 33	42 34	33 35	23 36	9

T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>The following field notes describe the survey of the Sixth Guide Meridian East, (west boundary), the east and north boundaries, and the subdivisional lines, Township 33 North, Range 25 East, Gila and Salt River Meridian, Arizona.</p> <p>The west boundary of the Navajo Indian Reservation was originally surveyed by Ehud N. Darling in 1869 and dependently resurveyed by Loyd E. Sechrist in 1919-20 and is identified, where possible, for historical purposes only. The Eighth Standard Parallel North, (south boundary), was surveyed by Leonard R. Sandoval in 1989-90.</p> <p>The survey was executed in accordance with the specifications as set forth in the <u>Manual of Instructions for the Survey of the Public Lands of the United States, 1973</u>, and the Special Instructions dated February 17, 1998, for Group No. 822, Arizona.</p> <p>The directions of all lines were determined, and distances measured by the technique of differential positioning using Trimble Navigation 4400 and 4700 Series Global Positioning System receivers utilizing the Real-Time Kinematic technique.</p> <p>The geographic position of the southeast corner of the township was determined by the technique of differential positioning using the Trimble Navigation 4400 and 4700 Series Global Positioning System receivers. First order National Geodetic Survey triangulation stations "BEAUTIFUL 1951" and "LOHALI 1951" were used as control stations. The geographic position is as follows:</p> <p>Lat.: 36°12'56.217" N. Long.: 109°35'42.372" W. NAD83(1992)</p> <p>The mean magnetic declination is 12 1/4° E.</p>
--------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Survey of the Sixth Guide Meridian East, (West Boundary),
T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Beginning at the stan. cor. of Tps. 33 N., Rs. 24 and 25 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. SC T33N R24E R25E S31 S36 1990.</p> <p>Add the marks 1998 to the brass cap.</p> <p>North, bet. secs. 31 and 36.</p> <p>Over rolling land atop Carson Mesa.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 31 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T33N R24E R25E 1/4 S36 S31 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
65.70	<p>Apache County Road C554, a graded road, 20 ft. wide, bears NNE and SSW.</p>
80.00	<p>Point for the cor. of secs. 25, 30, 31, and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T33N R24E R25E S25 S30 ----- S36 S31 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p> <hr/> <p>North, bet. secs. 25 and 30.</p>

Survey of the Sixth Guide Meridian East, (West Boundary),
T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Over rolling land atop Carson Mesa.</p> <p>Point for the 1/4 sec. cor. of secs. 25 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T33N R24E R25E 1/4 S25 S30 1998</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 19, 24, 25, and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T33N R24E R25E S24 S19 ----- S25 S30 1998</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p>
	<p>North, bet. secs. 19 and 24.</p> <p>Over rolling land atop Carson Mesa.</p>
22.60	<p>Apache County Road C554, a graded road, 20 ft. wide, bears SE and NW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in sandstone bedrock, with brass cap mkd.</p>

Survey of the Sixth Guide Meridian East, (West Boundary),
T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T33N R24E R25E 1/4 S24 S19 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Thence over rolling and broken land.</p>
80.00	<p>Point for the cor. of secs. 13, 18, 19, and 24.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole, in sandstone bedrock, with top mkd.</p> <p style="text-align: center;">T33N R24E R25E S13 S18 ----- S24 S19 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case, in the drill hole beneath the brass tablet.</p> <p>Land, rolling and broken. Soil, sandy clay with sandstone outcrops. No timber; scattered brush and native grasses.</p>
	<p>North, bet. secs. 13 and 18.</p> <p>Over rolling and broken land across canyons and spur ridges of Carson Mesa.</p>
39.60	<p>N. rim of a canyon, atop sandstone cliff, bears E. and W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 18.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole, in sandstone bedrock, with top mkd.</p> <p style="text-align: center;">T33N R24E R25E 1/4 S13 S18 1998</p>

Survey of the Sixth Guide Meridian East, (West Boundary),
T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS											
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case in the drill hole beneath the brass tablet.										
	Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.										
69.30	Top of sandstone cliff, identical with S. bank of Black Mountain Wash, bears ESE and WNW; thence descend abruptly into valley.										
77.00	N. bank of Black Mountain Wash, 20 ft. high, bears E. and W.										
80.00	Point for the cor. of secs. 7, 12, 13, and 18.										
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.										
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T33N</td> </tr> <tr> <td style="text-align: center;">R24E</td> <td style="text-align: center;">R25E</td> </tr> <tr> <td style="text-align: center;">S12</td> <td style="text-align: center;">S 7</td> </tr> <tr> <td style="text-align: center;">S13</td> <td style="text-align: center;">S18</td> </tr> <tr> <td colspan="2" style="text-align: center;">1998</td> </tr> </table>	T33N		R24E	R25E	S12	S 7	S13	S18	1998	
T33N											
R24E	R25E										
S12	S 7										
S13	S18										
1998											
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.										
	Cor. is located 70 lks. S. of Navajo Route 8083, a graded road, 22 ft. wide, bears E. and W.										
	Land, rolling and broken. Soil, sandstone outcrops transitioning to sandy clay and sand. No timber; scattered brush and native grasses.										
	North, bet. secs. 7 and 12.										
	Over gently rolling to broken land, on ascent from Black Mountain Wash valley into a narrow canyon.										
30.80	Top of sandstone cliff, at head of a narrow canyon, bears SE and NW; thence over rolling land atop Carson Mesa.										
40.00	Point for the 1/4 sec. cor. of secs. 7 and 12.										
	Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole, in sandstone bedrock, with top mkd.										

Survey of the Sixth Guide Meridian East, (West Boundary),
T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p style="text-align: center;">T33N R24E R25E 1/4 S12 S 7 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case in the drill hole beneath the brass tablet.</p> <p>Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, W. of cor.</p> <p>Point for the cor. of secs. 1, 6, 7, and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
40.00	<p style="text-align: center;">T33N R24E R25E S 1 S 6 ----- S12 S 7 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located in a flat area between sand dunes.</p> <p>Land, rolling to broken to rolling. Soil, sandy clay, sand and sandstone outcrops. No timber; scattered brush and native grasses.</p> <hr/> <p>North, bet. secs. 1 and 6.</p> <p>Over rolling land atop Carson Mesa.</p> <p>Point for the 1/4 sec. cor. of secs. 1 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, atop a steel fence post, 6 ft. long, with brass cap mkd.</p>
	<p style="text-align: center;">T33N R24E R25E 1/4 S 1 S 6 1998</p> <p>Cor. is located on a bare sand dune.</p>

Survey of the Sixth Guide Meridian East, (West Boundary),
T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS															
48.60	N. edge of sand dunes, bears NE and SW.														
80.00	Point for the cor. of Tps. 33 and 34 N., Rs. 24 and 25 E.														
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.														
	<table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td colspan="2" style="text-align: center;">T34N</td> </tr> <tr> <td style="text-align: center;">R24E</td> <td style="text-align: center;">R25E</td> </tr> <tr> <td style="text-align: center;">S36</td> <td style="text-align: center;">S31</td> </tr> <tr> <td colspan="2" style="text-align: center;">-----</td> </tr> <tr> <td style="text-align: center;">S 1</td> <td style="text-align: center;">S 6</td> </tr> <tr> <td colspan="2" style="text-align: center;">T33N</td> </tr> <tr> <td colspan="2" style="text-align: center;">1998</td> </tr> </table>	T34N		R24E	R25E	S36	S31	-----		S 1	S 6	T33N		1998	
T34N															
R24E	R25E														
S36	S31														

S 1	S 6														
T33N															
1998															
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.														
	Land, rolling. Soil, sand dunes and some sandy clay. No timber; sparse brush and native grasses.														
<hr/> <p>Survey of the East Boundary, T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona</p> <hr/>															
	From the stan. cor. of Tps. 33 N., Rs. 25 and 26 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. SC T33N R25E R26E S31 S36 1990.														
	Add the marks 1998 to the brass cap.														
	From this cor. point, a rebar, 5/8 in. diam., set flush with the surface of the ground, bears S. 81°10' W., 33.10 chs. dist., with aluminum cap mkd. NAVAJO LAND DEVELOPMENT 36.13 109.36.														
	North, bet. secs. 31 and 36.														
	Over nearly level land in Chinle Valley.														
32.45	Graded road, 20 ft. wide, bears E. and W.														
40.00	Point for the 1/4 sec. cor. of secs. 31 and 36.														
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. below the surface of ground, with brass cap mkd.														

Survey of the East Boundary,
T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	<p style="text-align: center;">T33N R25E R26E 1/4 S36 S31 1998</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 45°00' E., 146.0 ft. dist., with brass cap mkd. T33N R26E 1/4 S31 RM 146.0 FT TO COR 1998 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 45°00' W., 129.0 ft. dist., with brass cap mkd. T33N R25E 1/4 S36 RM 129.0 FT TO COR 1998 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post at the 1/4 sec. cor.</p> <p>Cor. is located in a cultivated field.</p> <p>80.00 Point for the cor. of secs. 25, 30, 31, and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. below the surface of ground, with brass cap mkd.</p> <p style="text-align: center;">T33N R25E R26E S25 S30 ----- S36 S31 1998</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 45°00' E., 98.0 ft. dist., with brass cap mkd. T33N R26E S30 RM 98.0 FT TO COR 1998 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
--------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Survey of the East Boundary,
T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 45°00' W., 86.0 ft. dist., with brass cap mkd. T33N R25E S25 RM 86.0 FT TO COR 1998 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post at the sec. cor.</p> <p>Cor. is located in a cultivated field.</p> <p>Land, nearly level. Soil, sandy clay. Timber, scattered cottonwood, Russian Olive and saltcedar; undergrowth, thick brush and native grasses.</p>
	<hr/>
	<p>North, bet. secs. 25 and 30.</p>
	<p>Over nearly level land in Chinle Valley.</p>
9.45	<p>Graded road, 20 ft. wide, bears E. and W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 30.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. below the surface of ground, with brass cap mkd.</p>
	<p style="text-align: center;">T33N R25E R26E 1/4 S25 S30 1998</p>
	<p>from which</p>
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 45°00' E., 100.0 ft. dist., with brass cap mkd. T33N R26E 1/4 S30 RM 100.0 FT TO COR 1998 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 45°00' E., 140.0 ft. dist., with brass cap mkd. T33N R26E 1/4 S30 RM 140.0 FT TO COR 1998 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>

Survey of the East Boundary,
T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS													
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post at the 1/4 sec. cor.</p> <p>Cor. is located in a cultivated field.</p>												
71.15	Apache County Road C552, a graded road, 20 ft. wide, bears ENE and WSW.												
77.85	Graded road, 20 ft. wide, bears SE and NW.												
80.00	<p>Point for the cor. of secs. 19, 24, 25, and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td colspan="2">T33N</td></tr> <tr><td>R25E</td><td>R26E</td></tr> <tr><td>S24</td><td>S19</td></tr> <tr><td colspan="2">— —</td></tr> <tr><td>S25</td><td>S30</td></tr> <tr><td colspan="2">1998</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, nearly level. Soil, sandy clay. Timber, scattered cottonwood, Russian olive and saltcedar; undergrowth, thick brush and native grasses.</p>	T33N		R25E	R26E	S24	S19	— —		S25	S30	1998	
T33N													
R25E	R26E												
S24	S19												
— —													
S25	S30												
1998													
	<p>North, bet. secs. 19 and 24.</p> <p>Over nearly level land in Chinle Valley.</p>												
14.00	High voltage transmission line, bears NE and SW.												
14.45	Graded road, 20 ft. wide, bears NE and SW.												
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. below the surface of ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td colspan="2">T33N</td></tr> <tr><td>R25E</td><td>R26E</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>S24</td><td>S19</td></tr> <tr><td colspan="2">1998</td></tr> </table> </div>	T33N		R25E	R26E	1/4		S24	S19	1998			
T33N													
R25E	R26E												
1/4													
S24	S19												
1998													

Survey of the East Boundary,
T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 45°00' E., 400.0 ft. dist., with brass cap mkd. T33N R26E 1/4 S19 RM 400.0 FT TO COR 1998 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 45°00' W., 340.0 ft. dist., with brass cap mkd. T33N R25E 1/4 S24 RM 340.0 FT TO COR 1998 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post at the 1/4 sec. cor.</p> <p>Cor. is located in a cultivated field.</p>
45.50	Trail road, with a barbed wire and woven fence on S. edge, both bear E. and W.
65.20	Left bank of Chinle Wash, 4 ft. high, bears SSE and NNW; thence continue down the bed of Chinle Wash.
80.00	Point for the cor. of secs. 13, 18, 19, and 24.
	<p>Set a magnet in a 1 x 1 x 2 ins. white colored plastic case, 24 ins. below the surface of ground.</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in ground, for a reference monument, bears N. 70°00' E., 350.0 ft. dist., with brass cap mkd. T33N R26E S18 RM 350.0 FT TO COR 1998 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in ground, for a reference monument, bears S. 70°00' W., 260.0 ft. dist., with brass cap mkd. T33N R25E S24 RM 260.0 FT TO COR 1998 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located in Chinle Wash, 460 ft. wide, 5 ft. deep, drains N.</p>

Survey of the East Boundary,
T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, nearly level. Soil, sand and sandy clay. Timber, cottonwood, Russian olive and saltcedar; undergrowth, thick brush and native grasses.</p>
40.00	<p>North, bet. secs. 13 and 18.</p> <p>Over nearly level land down the bed of Chinle Wash.</p> <p>Point for the 1/4 sec. cor. of secs. 13 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T33N R25E R26E 1/4 S13 S18 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located on a vegetated island between channels of Chinle Wash.</p>
80.00	<p>Point for the cor. of secs. 7, 12, 13, and 18.</p> <p>Set a magnet in a 1 x 1 x 2 ins. white colored plastic case, 24 ins. below the surface of ground.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in ground, for a reference monument, bears S. 35°00' E., 70.0 ft. dist., with brass cap mkd. T33N R26E S18 RM 70.0 FT TO COR 1998 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in ground, for a reference monument, bears S. 55°00' W., 215.0 ft. dist., with brass cap mkd. T33N R25E S13 RM 215.0 FT TO COR 1998 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located in the middle channel of Chinle Wash, 66 ft. wide, 3 ft. deep, drains N.</p>

Survey of the East Boundary,
T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, nearly level. Soil, sand and sandy clay. Timber, cottonwood, Russian olive and saltcedar; undergrowth, thick brush and native grasses.</p>
	<p>North, bet. secs. 7 and 12.</p>
	<p>Over nearly level land down the bed of Chinle Wash.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 12.</p>
	<p>Set a magnet in a 1 x 1 x 2 ins. white colored plastic case, 24 ins. below the surface of ground.</p>
	<p>from which</p>
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in ground, for a reference monument, bears N. 45°00' E., 90.0 ft. dist., with brass cap mkd. T33N R26E 1/4 S7 RM 90.0 FT TO COR 1998 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in ground, for a reference monument, bears N. 45°00' W., 265.0 ft. dist., with brass cap mkd. T33N R25E 1/4 S12 RM 265.0 FT TO COR 1998 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
	<p>Cor. is located in the W. channel of Chinle Wash, 200 ft. wide, 4 ft. deep, drains N.</p>
48.70	<p>Left bank of Chinle Wash, 5 ft. high, bears NNE and SSW.</p>
51.90	<p>Left bank of Chinle Wash, 5 ft. deep, bears SSE and NNW; thence continue down the bed of Chinle Wash.</p>
80.00	<p>Point for the cor. of secs. 1, 6, 7, and 12.</p>
	<p>Set a magnet in a 1 x 1 x 2 ins. white colored plastic case, 24 ins. below the surface of ground.</p>

Survey of the East Boundary,
T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

<p>CHAINS</p>	<p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in ground, for a reference monument, bears S. 45°00' W., 200.0 ft. dist., with brass cap mkd. T33N R25E S12 RM 200.0 FT TO COR 1998 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in ground, for a reference monument, bears N. 45°00' W., 220.0 ft. dist., with brass cap mkd. T33N R25E S1 RM 220.0 FT TO COR 1998 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located in Chinle Wash, 1.50 chs. E. of the left bank, 5 ft. high, bears N. and S.</p> <p>Land, nearly level. Soil, sand. Timber, cottonwood, Russian olive and saltcedar; undergrowth, thick brush and native grasses.</p>
<p>40.00</p>	<p>North, bet. secs. 1 and 6.</p> <p>Over nearly level land down the bed of Chinle Wash.</p> <p>Point for the 1/4 sec. cor. of secs. 1 and 6.</p> <p>Set a magnet in a 1 x 1 x 2 ins. white colored plastic case, 24 ins. below the surface of ground.</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in ground, for a reference monument, bears N. 70°00' E., 330.0 ft. dist., with brass cap mkd. T33N R26E 1/4 S6 RM 330.0 FT TO COR 1998 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in ground, for a reference monument, bears S. 70°00' W., 265.0 ft. dist., with brass cap mkd. T33N R25E 1/4 S1 RM 265.0 FT TO COR 1998 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>

Survey of the East Boundary,
T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS													
	Cor. is located in Chinle Wash, 500 ft. wide, 5 ft. deep, drains N.												
77.60	Right bank of Chinle Wash, 10 ft. high, bears SE and NW.												
80.00	Point for the cor. of Tps. 33 and 34 N., Rs. 25 and 26 E.												
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.												
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T34N</td></tr> <tr><td style="text-align: center;">R25E</td><td style="text-align: center;">R26E</td></tr> <tr><td style="text-align: center;">S36</td><td style="text-align: center;">S31</td></tr> <tr><td style="text-align: center;">S 1</td><td style="text-align: center;">S 6</td></tr> <tr><td colspan="2" style="text-align: center;">T33N</td></tr> <tr><td colspan="2" style="text-align: center;">1998</td></tr> </table>	T34N		R25E	R26E	S36	S31	S 1	S 6	T33N		1998	
T34N													
R25E	R26E												
S36	S31												
S 1	S 6												
T33N													
1998													
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.												
	Cor. is located 1.00 ch. E. of the right bank of Chinle Wash, 10 ft. high, bears SSE and NNW.												
	Land, nearly level. Soil, sand and sandy clay. Timber, cottonwood, Russian olive and saltcedar; undergrowth, thick brush and native grasses.												
<p style="margin: 0;">Survey of the North Boundary, T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona</p>													
	From the cor. of Tps. 33 and 34 N., Rs. 25 and 26 E., hereinbefore described.												
	West, bet. secs. 1 and 36.												
	Over nearly level land across Chinle Wash.												
9.00	Left bank of Chinle Wash, 4 ft. high, bears N. and S.; thence continue through Chinle Valley.												
40.00	Point for the 1/4 sec. cor. of secs. 1 and 36.												
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.												

Survey of the North Boundary,
T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T34N R25E S36 1/4 — S 1 T33N 1998
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
55.58	E. right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway.
56.75	Center of U. S. Highway 191, asphalt pavement, 28 ft. wide, bears SSE and NNW.
57.90	W. right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway.
80.00	Point for the cor. of secs. 1, 2, 35, and 36.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T34N R25E S35 S36 ———— S 2 S 1 T33N 1998
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
	Land, nearly level. Soil, sand and sandy clay. Timber, cottonwood, Russian olive and saltcedar near Chinle Wash; undergrowth, brush and native grasses.
	West, bet. secs. 2 and 35.
	Over nearly level land in Chinle Valley.
36.20	Power line, bears N. and S.
36.80	Underground gas pipeline, bears N. and S.
40.00	Point for the 1/4 sec. cor. of secs. 2 and 35.

Survey of the North Boundary,
T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T34N R25E S35 1/4 — S 2 T33N 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 2, 3, 34, and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T34N R25E S34 S35 — — S 3 S 2 T33N 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, nearly level. Soil, sandy clay. No timber; scattered brush and native grasses.</p>
40.00	<p>West, bet. secs. 3 and 34.</p> <p>Over nearly level land in Chinle Valley.</p> <p>Point for the 1/4 sec. cor. of secs. 3 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T34N R25E S34 1/4 — S 3 T33N 1998</p>

Survey of the North Boundary,
T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS																					
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.																				
70.90	Base of Ventana Mesa, bears NNE and SSW; thence ascend abruptly over rocky E. slope.																				
79.10	E. rim of Ventana Mesa, bears NNE and SSW; thence descend gradually over rolling and broken land.																				
79.55	Trail road, bears NNE and SSW.																				
80.00	Point for the cor. of secs. 3, 4, 33, and 34.																				
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.																				
	<table border="0" style="margin-left: auto; margin-right: auto;"> <tr><td>T34N</td><td>R25E</td></tr> <tr><td>S33</td><td> </td><td>S34</td></tr> <tr><td colspan="3" style="border-top: 1px solid black;"></td></tr> <tr><td>S 4</td><td> </td><td>S 3</td></tr> <tr><td colspan="3" style="border-top: 1px solid black;"></td></tr> <tr><td colspan="3" style="text-align: center;">T33N</td></tr> <tr><td colspan="3" style="text-align: center;">1998</td></tr> </table>	T34N	R25E	S33		S34				S 4		S 3				T33N			1998		
T34N	R25E																				
S33		S34																			
S 4		S 3																			
T33N																					
1998																					
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.																				
	Land, nearly level to broken and rolling. Soil, sandy, gravelly and rocky clay. No timber; scattered brush and native grasses.																				
	West, bet. secs. 4 and 33.																				
	Over rolling and broken land on descent of W. slope of Ventana Mesa.																				
40.00	Point for the 1/4 sec. cor. of secs. 4 and 33.																				
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.																				
	<table border="0" style="margin-left: auto; margin-right: auto;"> <tr><td>T34N</td><td>R25E</td></tr> <tr><td colspan="2" style="text-align: center;">S33</td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td colspan="2" style="text-align: center;">S 4</td></tr> <tr><td colspan="2" style="text-align: center;">T33N</td></tr> <tr><td colspan="2" style="text-align: center;">1998</td></tr> </table>	T34N	R25E	S33		1/4	—	S 4		T33N		1998									
T34N	R25E																				
S33																					
1/4	—																				
S 4																					
T33N																					
1998																					

Survey of the North Boundary,
T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS													
80.00	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 4, 5, 32, and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T34N</td><td>R25E</td></tr> <tr><td>S32</td><td>S33</td></tr> <tr><td>S 5</td><td>S 4</td></tr> <tr><td colspan="2">T33N</td></tr> <tr><td colspan="2">1998</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy and gravelly clay. No timber; scattered brush and native grasses.</p>	T34N	R25E	S32	S33	S 5	S 4	T33N		1998			
T34N	R25E												
S32	S33												
S 5	S 4												
T33N													
1998													
27.50	<p>West, bet. secs. 5 and 32.</p> <p>Over rolling land on descent of W. slope of Ventana Mesa.</p> <p>Navajo Route 8083, a graded road, 20 ft. wide, bears NNE and SSW; thence over nearly level land in Black Mountain Wash valley.</p>												
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T34N</td><td>R25E</td></tr> <tr><td>S32</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 5</td><td></td></tr> <tr><td colspan="2">T33N</td></tr> <tr><td colspan="2">1998</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>	T34N	R25E	S32		1/4	—	S 5		T33N		1998	
T34N	R25E												
S32													
1/4	—												
S 5													
T33N													
1998													
71.85	<p>Black Mountain Wash, 160 ft. wide, 30 ft. deep, drains N.</p>												
80.00	<p>Point for the cor. of secs. 5, 6, 31, and 32.</p>												

Survey of the North Boundary,
T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS													
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="857 401 1008 583"> <tr><td>T34N</td><td>R25E</td></tr> <tr><td>S31</td><td>S32</td></tr> <tr><td>S 6</td><td>S 5</td></tr> <tr><td colspan="2">T33N</td></tr> <tr><td colspan="2">1998</td></tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling to nearly level. Soil, sandy clay. No timber; scattered brush and native grasses.</p>	T34N	R25E	S31	S32	S 6	S 5	T33N		1998			
T34N	R25E												
S31	S32												
S 6	S 5												
T33N													
1998													
17.00	<p>West, bet. secs. 6 and 31.</p> <p>Over nearly level land in Black Mountain Wash valley.</p> <p>E. rim of Carson Mesa, atop sandstone cliff, bears SSE and NNW; thence over rolling land atop Carson Mesa.</p>												
40.00	<p>Point for the 1/4 sec. cor. of secs. 6 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in sandstone bedrock, with brass cap mkd.</p> <table border="1" data-bbox="857 1255 1008 1438"> <tr><td>T34N</td><td>R25E</td></tr> <tr><td colspan="2">S31</td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td colspan="2">S 6</td></tr> <tr><td colspan="2">T33N</td></tr> <tr><td colspan="2">1998</td></tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>	T34N	R25E	S31		1/4	—	S 6		T33N		1998	
T34N	R25E												
S31													
1/4	—												
S 6													
T33N													
1998													
79.46	<p>The cor. of Tps. 33 and 34 N., Rs. 24 and 25 E., hereinbefore described.</p> <p>Land, nearly level to broken to rolling. Soil, sandy clay to sandstone outcrops to sand. No timber; scattered brush and native grasses.</p>												

Survey of the Subdivisional Lines,
T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the stan. cor. of secs. 35 and 36, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. SC T33N R25E S35 S36 1990.</p> <p>Add the marks 1998 to the brass cap.</p> <p>N. 0°01' W., bet. secs. 35 and 36.</p> <p>Over nearly level land in Chinle Valley.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T33N R25E 1/4 S35 S36 1998</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 25, 26, 35, and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T33N R25E S26 S25 ----- S35 S36 1998</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, nearly level. Soil, sandy clay. No timber; scattered brush and native grasses.</p>
	<p>From the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 25 and 36.</p> <p>Over nearly level land in Chinle Valley.</p>

Survey of the Subdivisional Lines,
T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
23.31	E. right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway.
24.07	Center of U. S. Highway 191, asphalt pavement, 30 ft. wide, bears NNE and SSW.
25.26	W. right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway.
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T33N R25E S25 1/4 — S36 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
59.20	Power line, bears SSE and NNW.
59.70	Underground gas pipeline, bears SSE and NNW.
80.00	<p>The cor. of secs. 25, 26, 35, and 36.</p> <p>Land, nearly level. Soil, sandy clay. Timber, scattered cottonwood, Russian olive and saltcedar; undergrowth, scattered brush and native grasses.</p>
	<p>N. 0°01' W., bet. secs. 25 and 26.</p> <p>Over nearly level land in Chinle Valley.</p>
37.90	High voltage transmission line, bears NE and SW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T33N R25E 1/4 S26 S25 1998</p>

Survey of the Subdivisional Lines,
T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS									
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.								
80.00	Point for the cor. of secs. 23, 24, 25, and 26.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.								
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T33N R25E</td> </tr> <tr> <td style="text-align: center;">S23</td> <td style="text-align: center;">S24</td> </tr> <tr> <td style="text-align: center;">S26</td> <td style="text-align: center;">S25</td> </tr> <tr> <td colspan="2" style="text-align: center;">1998</td> </tr> </table>	T33N R25E		S23	S24	S26	S25	1998	
T33N R25E									
S23	S24								
S26	S25								
1998									
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.								
	<p>Land, nearly level. Soil, sandy clay. No timber; scattered brush and native grasses.</p>								
	From the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp., hereinbefore described.								
	West, bet. secs. 24 and 25.								
	Over nearly level land in Chinle Valley.								
4.20	Graded road, 20 ft. wide, bears N. and S.								
20.10	High voltage transmission line, bears NE and SW.								
35.03	E. right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway.								
35.83	Center of U. S. Highway 191, asphalt pavement, 30 ft. wide, bears SSE and NNW.								
37.00	W. right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway.								
40.00	Point for the 1/4 sec. cor. of secs. 24 and 25.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.								

Survey of the Subdivisional Lines,
T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T33N R25E S24 1/4 — S25 1998
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
43.58	Intersect the SE side of a stuccoed house, 35 x 25 ft., the southernmost cor. bears SW, 15 lks. dist., long side bears NE.
43.85	SW cor. of a wood frame house, 40 x 16 ft., bears North, 1.02 chs. dist., long side bears NNW.
73.80	Power line, bears SSE and NNW.
74.30	Underground gas pipeline, bears SSE and NNW.
80.00	The cor. of secs. 23, 24, 25, and 26.
	Land, nearly level. Soil, sandy clay. Timber, scattered cottonwood, Russian olive and saltcedar; undergrowth, brush and native grasses.
	N. 0°01' W., bet. secs. 23 and 24.
	Over nearly level land in Chinle Valley.
40.00	Point for the 1/4 sec. cor. of secs. 23 and 24.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T33N R25E 1/4 S23 S24 1998
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
42.50	Underground gas pipeline, bears SSE and NNW.
46.60	Power line, bears SSE and NNW.
80.00	Point for the cor. of secs. 13, 14, 23, and 24.

Survey of the Subdivisional Lines,
T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="857 369 1008 527"> <tr> <td>T33N</td> <td>R25E</td> </tr> <tr> <td>S14</td> <td>S13</td> </tr> <tr> <td>S23</td> <td>S24</td> </tr> <tr> <td colspan="2">1998</td> </tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, nearly level. Soil, sandy clay. No timber; scattered brush and native grasses.</p>	T33N	R25E	S14	S13	S23	S24	1998			
T33N	R25E										
S14	S13										
S23	S24										
1998											
<p>3.80</p> <p>35.73</p> <p>36.90</p> <p>38.10</p> <p>40.00</p>	<p>From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 13 and 24.</p> <p>Over nearly level land in Chinle Wash.</p> <p>Left bank of Chinle Wash, 3 ft. high, bears N. and S.; thence over nearly level land in Chinle Valley.</p> <p>E. right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway.</p> <p>Center of U. S. Highway 191, asphalt pavement, 28 ft. wide, bears NNE and SSW.</p> <p>W. right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway.</p> <p>Point for the 1/4 sec. cor. of secs. 13 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="857 1583 1008 1740"> <tr> <td>T33N</td> <td>R25E</td> </tr> <tr> <td></td> <td>S13</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S24</td> </tr> <tr> <td colspan="2">1998</td> </tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>	T33N	R25E		S13	1/4	—		S24	1998	
T33N	R25E										
	S13										
1/4	—										
	S24										
1998											

Survey of the Subdivisional Lines,
T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p>From this cor. point, a rebar, 5/8 in. diam., set flush with the surface of the ground, bears N. 34°00' E., 14.04 chs. dist., with aluminum cap mkd. NAVAJO LAND DEVELOPMENT 36.16 109.36.</p> <p>The cor. of secs. 13, 14, 23, and 24.</p> <p>Land, nearly level. Soil, sandy clay. Timber, scattered cottonwood, Russian olive and saltcedar near Chinle Wash; undergrowth, scattered brush and native grasses.</p>
40.00	<p>N. 0°01' W., bet. secs. 13 and 14.</p> <p>Over nearly level land in Chinle Valley.</p> <p>Point for the 1/4 sec. cor. of secs. 13 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T33N R25E 1/4 S14 S13 1998</p> </div>
80.00	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 11, 12, 13, and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T33N R25E S11 S12 ----- S14 S13 1998</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, nearly level. Soil, sandy clay. No timber; scattered brush and native.</p>
	<p>From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., hereinbefore described.</p>

Survey of the Subdivisional Lines,
T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	West, bet. secs. 12 and 13.
	Over nearly level land in Chinle Wash.
16.10	Left bank of Chinle Wash, 3 ft. high, bears NNE and SSW; thence over gently rolling land in Chinle Valley.
22.83	E. right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway.
23.99	Center of U. S. Highway 191, asphalt pavement, 30 ft. wide, bears SSE and NNW.
25.16	W. right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway.
40.00	Point for the 1/4 sec. cor. of secs. 12 and 13.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T33N R25E S12 1/4 — S13 1998</p>
80.00	The cor. of secs. 11, 12, 13, and 14.
	Land, nearly level.
	Soil, sand and sandy clay.
	Timber, scattered cottonwood, Russian olive and saltcedar near Chinle Wash; undergrowth, scattered brush and native grasses.
	N. 0°01' W., bet. secs. 11 and 12.
	Over nearly level land of Chinle Valley.
40.00	Point for the 1/4 sec. cor. of secs. 11 and 12.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T33N R25E 1/4 S11 S12 1998</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
77.45	<p>Barbed wire fence, 4 strands, bears E. and W., on S. edge of a cultivated field.</p>
80.00	<p>Point for the cor. of secs. 1, 2, 11, and 12.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. below the surface of ground, with brass cap mkd.</p>
	<p style="text-align: center;">T33N R25E S 2 S 1 ----- S11 S12 1998</p>
	<p>from which</p>
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in ground, for a reference monument, bears S. 45°00' E., 300.0 ft. dist., with brass cap mkd. T33N R25E S12 RM 300.0 FT TO COR 1998 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in ground, for a reference monument, bears S. 45°00' W., 196.0 ft. dist., with brass cap mkd. T33N R25E S11 RM 196.0 FT TO COR 1998 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post at the sec. cor.</p>
	<p>Cor. is located in a cultivated field.</p>
	<p>Land, nearly level. Soil, sandy clay. No timber; scattered brush and native grasses.</p>
	<p>From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp., hereinbefore described.</p>

Survey of the Subdivisional Lines,
T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	West, bet. secs. 1 and 12.
	Over nearly level land in Chinle Valley.
39.21	E. right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, bears SSE and NNW.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 12.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T33N R25E S 1 1/4 — S12 1998</p>
	from which
	<p style="text-align: center;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in ground, for a reference monument, bears S. 45°00' E., 95.0 ft. dist., with brass cap mkd. T33N R25E 1/4 S12 RM 95.0 FT TO COR 1998 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
	<p style="text-align: center;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in ground, for a reference monument, bears N. 45°00' W., 185.0 ft. dist., with brass cap mkd. T33N R25E 1/4 S1 RM 185.0 FT TO COR 1998 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post at the 1/4 sec. cor.
	Cor. is located 37 lks. E. of center of U. S. Highway 191, asphalt pavement, 30 ft. wide, and 1.54 chs. E. of W. right-of-way fence of U. S. Highway 191, both bear SSE and NNW.
74.43	Barbed wire, 4 strands, bears N. and S., on E. edge of a cultivated field.
80.00	The cor. of secs. 1, 2, 11, and 12.

Survey of the Subdivisional Lines,
T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, nearly level. Soil, sandy clay. Timber, scattered Russian olive and saltcedar near Chinle Wash; undergrowth, scattered brush and native grasses.</p>
	<p>N. 0°01' W., bet. secs. 1 and 2.</p>
	<p>Over nearly level land in Chinle Valley.</p>
9.56	<p>Barbed wire, 4 strands, bears E. and W., on N. edge of a cultivated field.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 2.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T33N R25E 1/4 S 2 S 1 1998</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
79.99	<p>The cor. of secs. 1, 2, 35, and 36, on the N. bdy. of the Tp., hereinbefore described.</p>
	<p>Land, nearly level. Soil, sandy clay. No timber; scattered brush and native grasses.</p>
	<p>From the stan. cor. of secs. 34 and 35, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. SC T33N R25E S34 S35 1990.</p>
	<p>Add the marks 1998 to the brass cap.</p>
	<p>N. 0°01' W., bet. secs. 34 and 35.</p>
	<p>Over rolling land atop Ventana Mesa.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 34 and 35.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T33N R25E 1/4 S34 S35 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>From this cor. point, the 32 Mile Cor. of the 1920 resurvey of the W. bdy. of the 1868 Executive Order Navajo Indian Reservation, bears S. 51°24' E., 24.03 chs. dist., monumented with an iron post, 3 ins. diam., firmly set, projecting 11 ins. above ground, with brass cap mkd. NIR 32M 1920. Remove and destroy the iron post and the memorial stone from beneath.</p>
61.70	High voltage transmission line, bears NE and SW.
80.00	<p>Point for the cor. of secs. 26, 27, 34, and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T33N R25E S27 S26 ----- S34 S35 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p>
	<p>From the cor. of secs. 25, 26, 35, and 36.</p> <p>West, bet. secs. 26 and 35.</p> <p>Over gently rolling land in Chinle Valley.</p>
8.70	Base of Ventana Mesa, bears NNE and SSW.
20.60	E. rim of Ventana Mesa, bears NNE and SSW; thence over gently rolling land atop Ventana Mesa.
40.00	Point for the 1/4 sec. cor. of secs. 26 and 35.

Survey of the Subdivisional Lines,
T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T33N R25E S26 1/4 — S35 1998</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
53.90	<p>High voltage transmission line, bears NE and SW.</p>
80.00	<p>The cor. of secs. 26, 27, 34, and 35.</p> <p>Land, gently rolling to broken to gently rolling. Soil, sandy, gravelly and rocky clay. No timber; scattered brush and native grasses.</p>
	<p>N. 0°01' W., bet. secs. 26 and 27.</p>
	<p>Over rolling land atop Ventana Mesa.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 26 and 27.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T33N R25E 1/4 S27 S26 1998</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 22, 23, 26, and 27.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T33N R25E S22 S23 — — S27 S26 1998</p>

Survey of the Subdivisional Lines,
T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p>
	<p>From the cor. of secs. 23, 24, 25, and 26.</p> <p>West, bet. secs. 23 and 26.</p> <p>Over gently rolling land in Chinle Valley.</p>
14.00	<p>Base of Ventana Mesa, bears SE and NW; thence across NE slope of Ventana Mesa.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 23 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T33N R25E S23 1/4 — S26 1998</p>
80.00	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located on E. slope of Ventana Mesa, bears SSE and NNW, 1.50 chs. E. of E. rim; thence over rolling land atop Ventana Mesa.</p> <p>The cor. of secs. 22, 23, 26, and 27.</p> <p>Land, gently rolling to broken to rolling. Soil, sandy, gravelly and rocky clay. No timber; scattered brush and native grasses.</p>
40.00	<p>N. 0°01' W., bet. secs. 22 and 23.</p> <p>Over rolling land atop Ventana Mesa.</p> <p>Point for the 1/4 sec. cor. of secs. 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T33N R25E 1/4 S22 S23 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>From this cor. point, the 34 Mile Cor. of the 1920 resurvey of the W. bdy. of the 1868 Executive Order Navajo Indian Reservation, bears S. 55°16' E., 22.46 chs. dist., monumented with an iron post, 3 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. NIR 34M 1920. Remove and destroy the iron post and the memorial stone from beneath.</p>
80.00	<p>Point for the cor. of secs. 14, 15, 22, and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T33N R25E S15 S14 ----- S22 S23 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p>
4.50 5.00 40.00	<p>From the cor. of secs. 13, 14, 23, and 24.</p> <p>West, bet. secs. 14 and 23.</p> <p>Over gently rolling land in Chinle Valley.</p> <p>Power line, bears SSE and NNW.</p> <p>Underground gas pipeline, bears SSE and NNW.</p> <p>Point for the 1/4 sec. cor. of secs. 14 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T33N R25E S14 1/4 — S23 1998</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
51.30	<p>Base of Ventana Mesa, bears NNE and SSW; thence ascend over E. slope.</p>
61.90	<p>E. rim of Ventana Mesa, bears NNE and SSW; thence over gently rolling land atop Ventana Mesa.</p>
80.00	<p>The cor. of secs. 14, 15, 22, and 23.</p> <p>Land, gently rolling to broken to gently rolling. Soil, sandy, gravelly and rocky clay. No timber; scattered brush and native grasses.</p>
	<p>N. 0°01' W., bet. secs. 14 and 15.</p> <p>Over rolling land atop Ventana Mesa.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 14 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T33N R25E 1/4 S15 S14 1998</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
	<p>Cor. is located 60 lks. S. of NW rim of a spur of Ventana Mesa, bears NE and SW.</p>
	<p>From this cor. point, the 35 Mile Cor. of the 1920 resurvey of the W. bdy. of the 1868 Executive Order Navajo Indian Reservation, bears S. 52°33' E., 23.12 chs. dist., monumented with an iron post, 3 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. NIR 35M 1920. Remove and destroy the iron post and the memorial stone from beneath.</p>
	<p>Thence over broken land on descent from spur of Ventana Mesa.</p>

Survey of the Subdivisional Lines,
T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS											
56.60	Foot of NW slope of spur of Ventana Mesa, bears ENE and WSW; thence over gently rolling land in Chinle Valley.										
80.00	Point for the cor. of secs. 10, 11, 14, and 15.										
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T33N R25E</td> </tr> <tr> <td style="text-align: center;">S10</td> <td style="text-align: center;">S11</td> </tr> <tr> <td style="text-align: center;">S15</td> <td style="text-align: center;">S14</td> </tr> <tr> <td colspan="2" style="text-align: center;">1998</td> </tr> </table>	T33N R25E		S10	S11	S15	S14	1998			
T33N R25E											
S10	S11										
S15	S14										
1998											
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.										
	Land, rolling to broken to gently rolling. Soil, sandy, gravelly and rocky clay. No timber; scattered brush and native grasses.										
	From the cor. of secs. 11, 12, 13, and 14.										
	West, bet. secs. 11 and 14.										
	Over nearly level land in Chinle Valley.										
15.10	Power line, bears SSE and NNW.										
15.60	Underground gas pipeline, bears SSE and NNW.										
40.00	Point for the 1/4 sec. cor. of secs. 11 and 14.										
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T33N R25E</td> </tr> <tr> <td colspan="2" style="text-align: center;">S11</td> </tr> <tr> <td style="text-align: center;">1/4</td> <td style="text-align: center;">—</td> </tr> <tr> <td colspan="2" style="text-align: center;">S14</td> </tr> <tr> <td colspan="2" style="text-align: center;">1998</td> </tr> </table>	T33N R25E		S11		1/4	—	S14		1998	
T33N R25E											
S11											
1/4	—										
S14											
1998											
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.										
80.00	The cor. of secs. 10, 11, 14, and 15.										

Survey of the Subdivisional Lines,
T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, nearly level. Soil, sandy clay. No timber; scattered brush and native grasses.</p>
	<p>N. 0°01' W., bet. secs. 10 and 11.</p>
	<p>Over nearly level land in Chinle Valley.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 10 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T33N R25E 1/4 S10 S11 1998</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 2, 3, 10, and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T33N R25E S 3 S 2 ----- S10 S11 1998</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
	<p>Land, nearly level. Soil, sandy clay. No timber; scattered brush and native grasses.</p>
	<p>From the cor. of secs. 1, 2, 11, and 12.</p>
	<p>West, bet. secs. 2 and 11.</p>
	<p>Over nearly level land in Chinle Valley.</p>
25.70	<p>Power line, bears SSE and NNW.</p>
26.20	<p>Underground gas pipeline, bears SSE and NNW.</p>

Survey of the Subdivisional Lines,
T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T33N R25E S 2 1/4 — S11 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>The cor. of secs. 2, 3, 10, and 11.</p> <p>Land, nearly level. Soil, sandy clay. No timber; scattered brush and native grasses.</p>
	<p>N. 0°01' W., bet. secs. 2 and 3.</p> <p>Over nearly level land in Chinle Valley.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T33N R25E 1/4 S 3 S 2 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>From this cor. point, the 37 Mile Cor. of the 1920 resurvey of the W. bdy. of the 1868 Executive Order Navajo Indian Reservation, bears S. 68°06' E., 19.41 chs. dist., monumented with an iron post, 3 ins. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd. NIR 37M 1920. Remove and destroy the iron post and the memorial stone from beneath.</p>
79.99	<p>The cor. of secs. 2, 3, 34, and 35, on the N. bdy. of the Tp., hereinbefore described.</p>

Survey of the Subdivisional Lines,
T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, nearly level. Soil, sandy clay. No timber; scattered brush and native grasses.</p>
	<p>From the stan. cor. of secs. 33 and 34, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, flush with a mound of stone, 3 ft. base, 16 ins. high, with brass cap mkd. SC T33N R25E S33 S34 1990.</p> <p>Add the marks 1998 to the brass cap.</p> <p>N. 0°02' W., bet. secs. 33 and 34.</p> <p>Over rolling land across W. slope of Ventana Mesa.</p>
5.35	High voltage transmission line, bears NE and SW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 33 and 34.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole, in sandstone bedrock, with top mkd.</p> <p style="text-align: center;">T33N R25E 1/4 S33 S34 1998</p>
80.00	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case in the drill hole beneath the brass tablet.</p> <p>Point for the cor. of secs. 27, 28, 33, and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T33N R25E S28 S27 ----- S33 S34 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>

Survey of the Subdivisional Lines,
T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy clay with sandstone outcrops. No timber; scattered brush and native grasses.</p>
	<p>From the cor. of secs. 26, 27, 34, and 35. West, bet. secs. 27 and 34. Over rolling land atop Ventana Mesa.</p>
26.30	Trail road, bears NNE and SSW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 27 and 34. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T33N R25E S27 1/4 — S34 1998</p>
80.00	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 27, 28, 33, and 34.</p> <p>Land, rolling. Soil, sandy and gravelly clay. No timber; scattered brush and native grasses.</p>
40.00	<p>N. 0°02' W., bet. secs. 27 and 28. Over rolling land across W. slope of Ventana Mesa.</p> <p>Point for the 1/4 sec. cor. of secs. 27 and 28. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">T33N R25E 1/4 S28 S27 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>

Survey of the Subdivisional Lines,
T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS											
	Cor. is located in an abandoned trail road, bears ENE and WSW.										
74.10	Trail road, bears ENE and WSW.										
80.00	Point for the cor. of secs. 21, 22, 27, and 28.										
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T33N R25E</td> </tr> <tr> <td style="text-align: center;">S21</td> <td style="text-align: center;">S22</td> </tr> <tr> <td colspan="2" style="text-align: center;">-----</td> </tr> <tr> <td style="text-align: center;">S28</td> <td style="text-align: center;">S27</td> </tr> <tr> <td colspan="2" style="text-align: center;">1998</td> </tr> </table>	T33N R25E		S21	S22	-----		S28	S27	1998	
T33N R25E											
S21	S22										

S28	S27										
1998											
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.										
	Land, rolling.										
	Soil, sandy clay.										
	No timber; scattered brush and native grasses.										
	From the cor. of secs. 22, 23, 26, and 27.										
	West, bet. secs. 22 and 27.										
	Over rolling land atop Ventana Mesa.										
28.00	Trail road, bears SE and NW.										
40.00	Point for the 1/4 sec. cor. of secs. 22 and 27.										
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T33N R25E</td> </tr> <tr> <td colspan="2" style="text-align: center;">S22</td> </tr> <tr> <td style="text-align: center;">1/4</td> <td style="text-align: center;">-----</td> </tr> <tr> <td colspan="2" style="text-align: center;">S27</td> </tr> <tr> <td colspan="2" style="text-align: center;">1998</td> </tr> </table>	T33N R25E		S22		1/4	-----	S27		1998	
T33N R25E											
S22											
1/4	-----										
S27											
1998											
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.										
53.50	Trail road, bears ENE and WSW.										
80.00	The cor. of secs. 21, 22, 27, and 28.										

Survey of the Subdivisional Lines,
T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p>
	<p>N. 0°02' W., bet. secs. 21 and 22.</p>
	<p>Over rolling land across W. slope of Ventana Mesa.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 21 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T33N R25E 1/4 S21 S22 1998</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 15, 16, 21, and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T33N R25E S16 S15 ----- S21 S22 1998</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
	<p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p>
	<p>From the cor. of secs. 14, 15, 22, and 23.</p>
	<p>West, bet. secs. 15 and 22.</p>
	<p>Over rolling land on descent of W. slope of Ventana Mesa.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 15 and 22.</p>

Survey of the Subdivisional Lines,
T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

<p>CHAINS</p> <p>80.00</p>	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T33N R25E S15 1/4 — S22 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 5 lks. E. of SE bank of a wash, 3 ft. wide, 3 ft. deep, drains NE.</p> <p>The cor. of secs. 15, 16, 21, and 22.</p> <p>Land, rolling. Soil, sandy, gravelly and rocky clay. No timber; scattered brush and native grasses.</p>
<p>40.00</p>	<p>N. 0°02' W., bet. secs. 15 and 16.</p> <p>Over rolling and broken land across W. slope of Ventana Mesa.</p> <p>Point for the 1/4 sec. cor. of secs. 15 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T33N R25E 1/4 S16 S15 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
<p>80.00</p>	<p>Point for the cor. of secs. 9, 10, 15, and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T33N R25E S 9 S10 — — S16 S15 1998</p>

Survey of the Subdivisional Lines,
T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy and gravelly clay. No timber; scattered brush and native grasses.</p>
	<p>From the cor. of secs. 10, 11, 14, and 15.</p> <p>West, bet. secs. 10 and 15.</p> <p>Over rolling land in Chinle Valley.</p>
36.00	Foot of E. slope of Ventana Mesa, bears N. and S.; thence over broken land on ascent of E. slope.
40.00	<p>Point for the 1/4 sec. cor. of secs. 10 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T33N R25E S10 1/4 — S15 1998</p>
64.70	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>E. rim of Ventana Mesa, bears N. and S.; thence over rolling land atop Ventana Mesa.</p>
80.00	<p>The cor. of secs. 9, 10, 15, and 16.</p> <p>Land, rolling to broken to rolling. Soil, sandy, gravelly and rocky clay. No timber; scattered brush and native grasses.</p>
40.00	<p>N. 0°02' W., bet. secs. 9 and 10.</p> <p>Over rolling and broken land atop Ventana Mesa.</p> <p>Point for the 1/4 sec. cor. of secs. 9 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p style="text-align: center;">T33N R25E 1/4 S 9 S10 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 3, 4, 9, and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T33N R25E S 4 S 3 ----- S 9 S10 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located near the top of W. slope of a small spur ridge.</p> <p>Land, rolling and broken. Soil, sandy, gravelly and rocky clay. No timber; scattered brush and native grasses.</p>
40.00	<p>From the cor. of secs. 2, 3, 10, and 11.</p> <p>West, bet. secs. 3 and 10.</p> <p>Over nearly level land in Chinle Valley.</p> <p>Point for the 1/4 sec. cor. of secs. 3 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T33N R25E S 3 1/4 — S10 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>

Survey of the Subdivisional Lines,
T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From this cor. point, second order National Geodetic Survey triangulation station, "DOG 1949", bears S. 29°49.0' W., 28.327 chs. dist., monumented with a standard U. S. Geological Survey Benchmark brass tablet, 3 1/2 ins. diam., cemented in place, in a sandstone outcrop, with top mkd. DOG 1949 and a triangle.</p>
53.80	<p>Foot of E. slope of Ventana Mesa, bears N. and S.; thence over broken land on ascent of E. slope.</p>
66.60	<p>E. rim of Ventana Mesa, bears N. and S.; thence over rolling land atop Ventana Mesa.</p>
80.00	<p>The cor. of secs. 3, 4, 9, and 10.</p> <p>Land, nearly level to broken to rolling. Soil, sandy, gravelly and rocky clay. No timber; scattered brush and native grasses.</p>
	<p>N. 0°02' W., bet. secs. 3 and 4.</p> <p>Over rolling and broken land atop crest of Ventana Mesa.</p>
38.60	<p>E. rim of Ventana Mesa, bears ESE and WNW; thence over broken land along E. slope of Ventana Mesa.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T33N R25E 1/4 S 4 S 3 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 60 lks. E. of E. rim of Ventana Mesa; thence continue along E. slope of Ventana Mesa.</p>
77.25	<p>E. rim of Ventana Mesa, bears NNE and SSW; thence over rolling land atop crest of Ventana Mesa.</p>
79.99	<p>The cor. of secs. 3, 4, 33, and 34, on the N. bdy. of the Tp., hereinbefore described.</p>

Survey of the Subdivisional Lines,
T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling and broken. Soil, sandy, gravelly and rocky clay. No timber; scattered brush and native grasses.</p>
	<p>From the true point for the stan. cor. of secs. 32 and 33, which falls on steep slope of large clay ridge, impracticable to monument. From this cor. point, the witness cor. to the stan. cor. of secs. 32 and 33, bears N. 34°16' W., 0.22 ch. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. WC SC T33N R25E S32 S33 1990 and an arrow pointing to the true point.</p> <p>Encircle the stainless steel post with a collar of stone, and add the marks 1998 to the brass cap.</p> <p>N. 0°03' W., bet. secs. 32 and 33.</p> <p>Over rugged and broken land across badlands.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T33N R25E 1/4 S32 S33 1998</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
48.00	<p>SE rim of sandstone ridge at N. edge of badlands, bears NE and SW; thence over rolling land across E. slope of Carson Mesa.</p>
80.00	<p>Point for the cor. of secs. 28, 29, 32, and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T33N R25E S29 S28 ----- S32 S33 1998</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>

Survey of the Subdivisional Lines,
T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rugged and broken to rolling. Soil, clay with sandstone outcrops to sand and sandy clay. No timber; scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 27, 28, 33, and 34. West, bet. secs. 28 and 33. Over rolling and broken land across badlands.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 28 and 33. Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole, in sandstone bedrock, with top mkd.</p> <p style="text-align: center;">T33N R25E S28 1/4 — S33 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case in the drill hole beneath the brass tablet. Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor. Cor. is located at foot of clay slope on W. edge of badlands; thence ascend E. slope of Carson Mesa.</p>
80.00	<p>The cor. of secs. 28, 29, 32, and 33. Land, rolling and broken. Soil, clay with sandstone outcrops to sand and sandy clay. No timber; scattered brush and native grasses.</p> <hr/> <p>N. 0°03' W., bet. secs. 28 and 29. Over rolling land across E. slope of Carson Mesa.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 28 and 29. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T33N R25E 1/4 S29 S28 1998</p>

Survey of the Subdivisional Lines,
T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS											
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.										
58.75	Trail road, bears E. and W.										
61.10	Pump shaft of a windmill, bears East, 18.75 chs. dist., mkd. 10T-514A.										
80.00	<p>Point for the cor. of secs. 20, 21, 28, and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table data-bbox="868 682 1015 850" style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T33N R25E</td></tr> <tr><td style="text-align: center;">S20</td><td style="text-align: center;">S21</td></tr> <tr><td style="border-top: 1px solid black; text-align: center;">S29</td><td style="border-top: 1px solid black; text-align: center;">S28</td></tr> <tr><td colspan="2" style="text-align: center;">1998</td></tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p>	T33N R25E		S20	S21	S29	S28	1998			
T33N R25E											
S20	S21										
S29	S28										
1998											
	<p>From the cor. of secs. 21, 22, 27, and 28.</p> <p>West, bet. secs. 21 and 28.</p> <p>Over rolling land.</p>										
40.00	<p>Point for the 1/4 sec. cor. of secs. 21 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table data-bbox="868 1480 1015 1648" style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T33N R25E</td></tr> <tr><td colspan="2" style="text-align: center;">S21</td></tr> <tr><td colspan="2" style="text-align: center;">1/4 —</td></tr> <tr><td colspan="2" style="text-align: center;">S28</td></tr> <tr><td colspan="2" style="text-align: center;">1998</td></tr> </table>	T33N R25E		S21		1/4 —		S28		1998	
T33N R25E											
S21											
1/4 —											
S28											
1998											
80.00	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 20, 21, 28, and 29.</p>										

Survey of the Subdivisional Lines,
T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p>										
40.00	<p>N. 0°03' W., bet. secs. 20 and 21. Over rolling land on descent from Carson Mesa. Point for the 1/4 sec. cor. of secs. 20 and 21. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table border="0" style="margin-left: auto; margin-right: auto;"> <tr><td>T33N</td><td>R25E</td></tr> <tr><td></td><td>1/4</td></tr> <tr><td>S20</td><td> S21</td></tr> <tr><td></td><td>1998</td></tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>	T33N	R25E		1/4	S20	S21		1998		
T33N	R25E										
	1/4										
S20	S21										
	1998										
80.00	<p>Point for the cor. of secs. 16, 17, 20, and 21. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table border="0" style="margin-left: auto; margin-right: auto;"> <tr><td>T33N</td><td>R25E</td></tr> <tr><td>S17</td><td> S16</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td>S20</td><td> S21</td></tr> <tr><td></td><td>1998</td></tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>	T33N	R25E	S17	S16			S20	S21		1998
T33N	R25E										
S17	S16										
S20	S21										
	1998										
40.00	<p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 15, 16, 21, and 22. West, bet. secs. 16 and 21. Over rolling and broken land on descent from Ventana Mesa into badlands. Point for the 1/4 sec. cor. of secs. 16 and 21.</p>										

Survey of the Subdivisional Lines,
T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to bedrock, supported in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T33N R25E S16 1/4 — S21 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located in badlands between two clay ridges, bear N. and S.</p> <p>63.40 W. edge of badlands, bears NNE and SSW; thence over rolling land.</p> <p>80.00 The cor. of secs. 16, 17, 20, and 21.</p> <p>Land, rolling and broken. Soil, clay to sandy clay. No timber; scattered brush and native grasses.</p>
	<p>N. 0°03' W., bet. secs. 16 and 17.</p> <p>Over rolling and broken land.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 16 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T33N R25E 1/4 S17 S16 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located between two spur ridges, bear ENE and WSW.</p> <p>80.00 Point for the cor. of secs. 8, 9, 16, and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<div style="text-align: center;"> <table border="1"> <tr><td>T33N</td><td>R25E</td></tr> <tr><td>S 8</td><td>S 9</td></tr> <tr><td>S17</td><td>S16</td></tr> <tr><td colspan="2">1998</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy and gravelly clay. No timber; scattered brush and native grasses.</p>	T33N	R25E	S 8	S 9	S17	S16	1998			
T33N	R25E										
S 8	S 9										
S17	S16										
1998											
	<p>From the cor. of secs. 9, 10, 15, and 16.</p> <p>West, bet. secs. 9 and 16.</p> <p>Over rolling and broken land on descent of W. slope of Ventana Mesa.</p>										
40.00	<p>Point for the 1/4 sec. cor. of secs. 9 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T33N</td><td>R25E</td></tr> <tr><td>S 9</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S16</td><td></td></tr> <tr><td colspan="2">1998</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located on a bare red clay outcrop.</p>	T33N	R25E	S 9		1/4	—	S16		1998	
T33N	R25E										
S 9											
1/4	—										
S16											
1998											
80.00	<p>The cor. of secs. 8, 9, 16, and 17.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay with some bare clay outcrops. No timber; scattered brush and native grasses.</p>										
40.00	<p>N. 0°03' W., bet. secs. 8 and 9.</p> <p>Over rolling and broken land.</p> <p>Point for the 1/4 sec. cor. of secs. 8 and 9.</p>										

Survey of the Subdivisional Lines,
T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T33N R25E 1/4 S 8 S 9 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located halfway up the E. slope of a small spur ridge, bears NNE and SSW.</p>
80.00	<p>Point for the cor. of secs. 4, 5, 8, and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T33N R25E S 5 S 4 ----- S 8 S 9 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy and gravelly clay. No timber; scattered brush and native grasses.</p>
40.00	<p>From the cor. of secs. 3, 4, 9, and 10.</p> <p>West, bet. secs. 4 and 9.</p> <p>Over rolling and broken land, on descent of W. slope of Ventana Mesa.</p> <p>Point for the 1/4 sec. cor. of secs. 4 and 9.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole, in limestone bedrock, with top mkd.</p> <p style="text-align: center;">T33N R25E S 4 1/4 — S 9 1998</p>

Survey of the Subdivisional Lines,
T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case in the drill hole beneath the brass tablet.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of the cor.</p> <p>Cor. is located on NE edge of a wash, 8 ft. wide, 2 ft. deep, drains NW.</p> <p>Thence over rolling land on continued descent.</p>
76.40	Wash, 36 ft. wide, 8 ft. deep, drains NE.
80.00	<p>The cor. of secs. 4, 5, 8, and 9.</p> <p>Land, rolling and broken. Soil, sandy, gravelly and rocky clay with sandstone and limestone outcrops. No timber; scattered brush and native grasses.</p>
	<p>N. 0°03' W., bet. secs. 4 and 5.</p> <p>Over rolling land.</p>
30.10	Wash, 30 ft. wide, 3 ft. deep, drains SW.
39.10	Wash, 30 ft. wide, 4 ft. deep, drains NE.
40.00	<p>Point for the 1/4 sec. cor. of secs. 4 and 5.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T33N R25E 1/4 S 5 S 4 1998</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
43.20	Wash, 24 ft. wide, 6 ft. deep, drains WSW.
79.99	The cor. of secs. 4, 5, 32, and 33, on the N. bdy. of the Tp., hereinbefore described.

Survey of the Subdivisional Lines,
T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy and gravelly clay. No timber; scattered brush and native grasses.</p> <hr/> <p>From the stan. cor. of secs. 31 and 32, on the S. bdy. of the Tp., monumented with stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. SC T33N R25E S31 S32 1990.</p> <p>Add the marks 1998 to the brass cap.</p> <p>N. 0°03' W., bet. secs. 31 and 32.</p> <p>Over rolling land across E. slope of Carson Mesa.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T33N R25E 1/4 S31 S32 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 29, 30, 31, and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T33N R25E S30 S29 ----- S31 S32 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 28, 29, 32, and 33.</p>

Survey of the Subdivisional Lines,
T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>West, bet. secs. 29 and 32.</p> <p>Over rolling land on gradual ascent of E. slope of Carson Mesa.</p> <p>Point for the 1/4 sec. cor. of secs. 29 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T33N R25E S29 1/4 — S32 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>The cor. of secs. 29, 30, 31, and 32.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p> <hr/> <p>West, bet. secs. 30 and 31.</p> <p>Over rolling land on gradual ascent of E. slope of Carson Mesa.</p> <p>Point for the 1/4 sec. cor. of secs. 30 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T33N R25E S30 1/4 — S31 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
76.10	<p>Apache County Road C554, a graded road, 20 ft. wide, bears NNE and SSW.</p>
79.91	<p>The cor. of secs. 25, 30, 31, and 36, on the W. bdy. of the Tp., hereinbefore described.</p>

Survey of the Subdivisional Lines,
T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 29, 30, 31, and 32. N. 0°03' W., bet. secs. 29 and 30. Over rolling land across E. slope of Carson Mesa.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 29 and 30. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T33N R25E 1/4 S30 S29 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 19, 20, 29, and 30. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T33N R25E S19 S20 ----- S30 S29 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p> <hr/> <p>From the cor. of sec. 20, 21, 28, and 29. West, bet. secs. 20 and 29. Over rolling and broken land across N. slope of Carson Mesa.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 20 and 29.</p>

Survey of the Subdivisional Lines,
T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T33N R25E S20 1/4 — S29 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>The cor. of secs. 19, 20, 29, and 30.</p> <p>Land, rolling and broken. Soil, sandy and gravelly clay. No timber; scattered brush and native grasses.</p>
	<p>West, bet. secs. 19 and 30.</p> <p>Over rolling land atop Carson Mesa.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T33N R25E S19 1/4 — S30 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
65.70	<p>Cor. is located 1.25 chs. E. of a trail road, bears NNE and SSW.</p> <p>Apache County Road C554, a graded road, 20 ft. wide, bears SSE and NNW.</p>
79.82	<p>The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp., hereinbefore described.</p>

Survey of the Subdivisional Lines,
T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 19, 20, 29, and 30. N. 0°03' W., bet. secs. 19 and 20. Over rolling and broken land on descent of N. slope of Carson Mesa.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 19 and 20. Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole, in sandstone bedrock, with top mkd.</p> <p style="text-align: center;">T33N R25E 1/4 S19 S20 1998</p> <p>from which</p> <p style="text-align: center;">The marks X B0, chiseled on sandstone bedrock, bear N. 37° W., 16 1/2 lks. dist.</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case in the drill hole beneath the brass tablet.</p>
80.00	<p>Point for the cor. of secs. 17, 18, 19, and 20. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T33N R25E S18 S17 ----- S19 S20 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located on spur ridge on NW edge of a trail road, bears NE and SW.</p>

Survey of the Subdivisional Lines,
T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling and broken. Soil, sandy and gravelly clay with sandstone outcrops. No timber; scattered brush and native grasses.</p>
	<hr/>
	<p>From the cor. of secs. 16, 17, 20, and 21.</p>
	<p>West, bet. secs. 17 and 20.</p>
	<p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 17 and 20.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T33N R25E</p>
	<p style="text-align: center;">S17</p>
	<p style="text-align: center;">1/4 —</p>
	<p style="text-align: center;">S20</p>
	<p style="text-align: center;">1998</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>The cor. of secs. 17, 18, 19, and 20.</p>
	<p>Land, rolling and broken.</p>
	<p>Soil, sandy, gravelly and rocky clay.</p>
	<p>No timber; scattered brush and native grasses.</p>
	<hr/>
	<p>West, bet. secs. 18 and 19.</p>
	<p>Over rolling and broken land.</p>
40.00	<p>True point for the 1/4 sec. cor. of secs. 18 and 19, falls on precipitous steep sandstone cliff, on W. wall of a narrow canyon, drains NNE; where it is impracticable to establish a permanent monument.</p>
	<p>From this cor. point, the point selected for a witness cor. to the 1/4 sec. cor. of secs. 18 and 19, bears S. 18°00' W., 7.20 chs. dist.</p>
	<p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole, in sandstone bedrock, with top mkd.</p>

Survey of the Subdivisional Lines,
T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
79.73	<p style="text-align: center;"> WC T33N R25E ↗ S18 1/4 — S19 1998 </p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case in the drill hole beneath the brass tablet.</p> <p>The cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling and broken. Soil, sandy and gravelly clay with sandstone outcrops. No timber; scattered brush and native grasses.</p>
40.00	<p>From the cor. of secs. 17, 18, 19, and 20.</p> <p>N. 0°03' W., bet. secs. 17 and 18.</p> <p>Over rolling and broken land on descent.</p> <p>Point for the 1/4 sec. cor. of secs. 17 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> T33N R25E 1/4 S18 S17 1998 </p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located at foot of N. end of a spur ridge, extends S.</p>
80.00	<p>Point for the cor. of secs. 7, 8, 17, and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, atop a steel fence post, 6 ft. long, with brass cap mkd.</p> <p style="text-align: center;"> T33N R25E S 7 S 8 ———— S18 S17 1998 </p>

Survey of the Subdivisional Lines,
T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Cor. is located on a lone bare sand dune.</p> <p>Land, rolling and broken. Soil, sand and sandy clay. No timber; scattered brush and native grasses.</p>
	<p>From the cor. of secs. 8, 9, 16, and 17.</p> <p>West, bet. secs. 8 and 17.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 8 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T33N R25E S 8 1/4 — S17 1998</p>
80.00	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 7, 8, 17, and 18.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; scattered brush and native grasses.</p>
40.00	<p>West, bet. secs. 7 and 18.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 7 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T33N R25E S 7 1/4 — S18 1998</p>

Survey of the Subdivisional Lines,
T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, N. of cor.</p>
43.50	Foot of high sandstone cliff, bears N. and S.; thence over prominent sandstone ridge.
53.90	Foot of high sandstone cliff, bears SE and NW; thence over nearly level land in Black Mountain Wash valley.
61.90	Navajo Route 8083, a graded road, 22 ft. wide, bears NNE and SSW.
66.80	Black Mountain Wash, 165 ft. wide, 25 ft. deep, drains N.
74.90	Navajo Route 8083, a graded road, 22 ft. wide, bears ESE and WNW.
79.65	<p>The cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling and broken. Soil, sand, sandy and gravelly clay and prominent sandstone outcrops. No timber; scattered brush and native grasses.</p>
	<p>From the cor. of secs. 7, 8, 17, and 18.</p> <p>N. 0°03' W., bet. secs. 7 and 8.</p> <p>Over rolling land on gradual descent into Black Mountain Wash valley.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T33N R25E 1/4 S 7 S 8 1998</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
72.60	Navajo Route 8083, a graded road, 22 ft. wide, bears ENE and WSW.
80.00	Point for the cor. of secs. 5, 6, 7, and 8.

Survey of the Subdivisional Lines,
T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T33N</td><td>R25E</td></tr> <tr><td>S 6</td><td>S 5</td></tr> <tr><td>S 7</td><td>S 8</td></tr> <tr><td colspan="2">1998</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy and gravelly clay. No timber; scattered brush and native grasses.</p>	T33N	R25E	S 6	S 5	S 7	S 8	1998			
T33N	R25E										
S 6	S 5										
S 7	S 8										
1998											
	<p>From the cor. of secs. 4, 5, 8, and 9.</p> <p>West, bet. secs. 5 and 8.</p> <p>Over rolling land.</p>										
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T33N</td><td>R25E</td></tr> <tr><td colspan="2">S 5</td></tr> <tr><td colspan="2">1/4 —</td></tr> <tr><td colspan="2">S 8</td></tr> <tr><td colspan="2">1998</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>	T33N	R25E	S 5		1/4 —		S 8		1998	
T33N	R25E										
S 5											
1/4 —											
S 8											
1998											
69.20	<p>Navajo Route 8083, a graded road, 20 ft. wide, bears NE and SW; thence over nearly level land in Black Mountain Wash valley.</p>										
80.00	<p>The cor. of secs. 5, 6, 7, and 8.</p> <p>Land, rolling to nearly level. Soil, sandy and gravelly clay. No timber; scattered brush and native grasses.</p>										
	<p>West, bet. secs. 6 and 7.</p> <p>Over nearly level land in Black Mountain Wash valley.</p>										

Survey of the Subdivisional Lines,
T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
9.90	Black Mountain Wash, 210 ft. wide, 30 ft. deep, drains NE.
40.00	<p>Point for the 1/4 sec. cor. of secs. 6 and 7.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T33N R25E S 6 1/4 — S 7 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
45.70	Foot of E. slope of Carson Mesa, bears N. and S.; thence ascend abruptly.
48.50	E. rim of Carson Mesa, atop high sandstone cliff, bears N. and S.; thence over rolling land atop Carson Mesa.
79.56	<p>The cor. of secs. 1, 6, 7, and 12, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, nearly level to broken to rolling. Soil, sandy clay to sandstone outcrops to sand and sandy clay. No timber; scattered brush and native grasses.</p>
	<p>From the cor. of secs. 5, 6, 7, and 8.</p> <p>N. 0°03' W., bet. secs. 5 and 6.</p> <p>Over nearly level land in Black Mountain Wash valley.</p>
14.50	Right bank of Black Mountain Wash, 30 ft. high, bears NNE and SSW.
22.10	Left bank of Black Mountain Wash, 30 ft. high, bears NNE and SSW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T33N R25E 1/4 S 6 S 5 1998</p>

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

- FIELD ASSISTANTS

NAMES	CAPACITY
William F. Olver	Cadastral Surveyor
James L. Werdel	Cadastral Surveyor
Daniel Bryan	Engineering Technician
Wilfred Chee	Engineering Technician
Edward Clarke	Engineering Technician
Reuben Mason	Engineering Technician
Barney Woodie	Engineering Technician
Patti Cruz	BLM Volunteer

CERTIFICATE OF SURVEY

I, Leonard R. Sandoval, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 17th day of February, 1998, I have surveyed the Sixth Guide Meridian East, (west boundary), the east and north boundaries, and the subdivisional lines, Township 33 North, Range 25 East, of the Gila and Salt River Meridian, in the state of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said Special Instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

March 23, 2000
(Date)

Leonard R. Sandoval
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Arizona State Office
Phoenix, Arizona

The foregoing field notes of the survey of the Sixth Guide Meridian East, (west boundary), the east and north boundaries, and the subdivisional lines, Township 33 North, Range 25 East, Gila and Salt River Meridian, Arizona, executed by Leonard R. Sandoval, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

July 27, 2000
(Date)

Kenny D. Ravnikar
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in T. 33 N., R. 25 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~_____
(Date)~~

~~_____
(Chief Cadastral Surveyor of Arizona)~~