

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTES  
OF THE

SURVEY

OF

THE EAST AND

NORTH BOUNDARIES,

AND

THE SUBDIVISIONAL LINES,

TOWNSHIP 35 NORTH, RANGE 26 EAST,

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Jones Curtiss, Cadastral Surveyor

Under Special Instructions dated and approved February 17, 1998, which provided for the surveys included under Group Number 822 and assignment instructions dated February 17, 1998.

Survey Commenced April 14, 1999

Survey Completed June 22, 1999

INDEX DIAGRAM

TOWNSHIP 35 NORTH, RANGE 26 EAST,

GILA AND SALT RIVER MERIDIAN, ARIZONA

|             |             |             |             |             |            |
|-------------|-------------|-------------|-------------|-------------|------------|
| 14<br>6 57  | 13<br>5 45  | 12<br>4 37  | 11<br>3 29  | 10<br>2 22  | 9<br>1 8   |
| 56<br>7 55  | 56<br>8 44  | 45<br>9 36  | 37<br>10 28 | 29<br>11 21 | 21<br>12 7 |
| 54<br>18 53 | 54<br>17 42 | 43<br>16 35 | 35<br>15 27 | 28<br>14 19 | 20<br>13 6 |
| 52<br>19 50 | 51<br>20 41 | 42<br>21 33 | 34<br>22 25 | 26<br>23 18 | 18<br>24 5 |
| 49<br>30 48 | 49<br>29 40 | 40<br>28 32 | 33<br>27 24 | 25<br>26 16 | 17<br>25 4 |
| 47<br>31 46 | 47<br>32 38 | 39<br>33 30 | 31<br>34 23 | 24<br>35 15 | 16<br>36 4 |

## T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

## CHAINS

The following field notes describe the survey of the east and north boundaries, and the subdivisional lines, Township 35 North, Range 26 East, Gila and Salt River Meridian, Arizona.

The south boundary was surveyed by Jones Curtiss and Leonard R. Sandoval concurrently under this same group. The west boundary was surveyed by Jones Curtiss concurrently under this same group.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated February 17, 1998, for Group No. 822, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic and static global positioning system observations using Trimble 4400 and 4700 model receivers.

Geodetic control was derived from first order U.S. Coast and Geodetic Survey triangulation stations "BEAUTIFUL 1951" and "LOHALI 1951", as published by the National Geodetic Survey, NAD83(1992). The geographic position of the southeast corner of the township is as follows:

Latitude: 36°23'22.58" N.

Longitude: 109°29'15.88" W.

The mean magnetic declination is 12 1/4° E.

Survey of the East Boundary,  
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS |   |
|--------|---|
|        | <p>Beginning at the cor. of Tps. 34 and 35 N., Rs. 26 and 27 E., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set, mkd. and witnessed as described in the field notes of the survey of the east boundary, T. 34 N., R. 26 E., executed concurrently under this same group.</p> <p>North, bet. secs. 31 and 36.</p> <p>Over rolling land.</p>   |
| 40.00  | <p>Point for the 1/4 sec. cor. of secs. 31 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T35N<br/>R26E R27E<br/>1/4<br/>S36   S31<br/>1999</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>   |
| 80.00  | <p>Point for the cor. of secs. 25, 30, 31, and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T35N<br/>R26E   R27E<br/>S25   S30<br/>-----<br/>S36   S31<br/>1999</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling.<br/>Soil, sandy and rocky clay.<br/>Timber, scattered juniper; undergrowth, scattered brush and native grasses.</p> <hr/> <p>North, bet. secs. 25 and 30.</p> <p>Over rolling land.</p> |

Survey of the East Boundary,  
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS |   |
|--------|---|
| 14.90  | Apache County Road C492, a graded road, 20 ft. wide, bears SE and NW.   |
| 40.00  | <p>Point for the 1/4 sec. cor. of secs. 25 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T35N<br/>R26E R27E<br/>1/4<br/>S25   S30<br/>1999</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located on S. edge of a trail road, bears ENE and WSW.</p>   |
| 80.00  | <p>Point for the cor. of secs. 19, 24, 25, and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T35N<br/>R26E   R27E<br/>S24   S19<br/>-----<br/>S25   S30<br/>1999</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling.<br/>Soil, sandy and rocky clay.<br/>Timber, scattered juniper; undergrowth, scattered brush and native grasses.</p> <hr/> <p>North, bet. secs. 19 and 24.</p> <p>Over rolling land.</p> |
| 40.00  | <p>Point for the 1/4 sec. cor. of secs. 19 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>  |

Survey of the East Boundary,  
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS |   |
|--------|---|
| 80.00  | <p style="text-align: center;">T35N<br/>R26E R27E<br/>1/4<br/>S24   S19<br/>1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 13, 18, 19, and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>  |
| 40.00  | <p style="text-align: center;">T35N<br/>R26E   R27E<br/>S13   S18<br/>-----<br/>S24   S19<br/>1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling.<br/>Soil, sandy and rocky clay.<br/>No timber; scattered brush and native grasses.</p> <hr/> <p>North, bet. secs. 13 and 18.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 13 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> |
| 80.00  | <p style="text-align: center;">T35N<br/>R26E R27E<br/>1/4<br/>S13   S18<br/>1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 7, 12, 13, and 18.</p>   |

Survey of the East Boundary,  
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS |   |      |  |      |      |     |     |       |     |      |     |      |  |
|--------|---|------|--|------|------|-----|-----|-------|-----|------|-----|------|--|
|        | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,<br/>24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T35N</td></tr> <tr><td style="text-align: center;">R26E</td><td style="text-align: center;">R27E</td></tr> <tr><td style="text-align: center;">S12</td><td style="text-align: center;">S 7</td></tr> <tr><td colspan="2" style="text-align: center;">-----</td></tr> <tr><td style="text-align: center;">S13</td><td style="text-align: center;">S18</td></tr> <tr><td colspan="2" style="text-align: center;">1999</td></tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case<br/>beneath the stainless steel post.</p> <p>Land, rolling.<br/>Soil, sandy clay.<br/>No timber; scattered brush and native grasses.</p> | T35N |  | R26E | R27E | S12 | S 7 | ----- |     | S13  | S18 | 1999 |  |
| T35N   |   |      |  |      |      |     |     |       |     |      |     |      |  |
| R26E   | R27E  |      |  |      |      |     |     |       |     |      |     |      |  |
| S12    | S 7   |      |  |      |      |     |     |       |     |      |     |      |  |
| -----  |   |      |  |      |      |     |     |       |     |      |     |      |  |
| S13    | S18   |      |  |      |      |     |     |       |     |      |     |      |  |
| 1999   |   |      |  |      |      |     |     |       |     |      |     |      |  |
|        | <p>North, bet. secs. 7 and 12.</p> <p>Over rolling land.</p>  |      |  |      |      |     |     |       |     |      |     |      |  |
| 40.00  | <p>Point for the 1/4 sec. cor. of secs. 7 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,<br/>26 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T35N</td></tr> <tr><td style="text-align: center;">R26E</td><td style="text-align: center;">R27E</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td style="text-align: center;">S12</td><td style="text-align: center;">S 7</td></tr> <tr><td colspan="2" style="text-align: center;">1999</td></tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case<br/>beneath the stainless steel post.</p>  | T35N |  | R26E | R27E | 1/4 |     | S12   | S 7 | 1999 |     |      |  |
| T35N   |   |      |  |      |      |     |     |       |     |      |     |      |  |
| R26E   | R27E  |      |  |      |      |     |     |       |     |      |     |      |  |
| 1/4    |   |      |  |      |      |     |     |       |     |      |     |      |  |
| S12    | S 7   |      |  |      |      |     |     |       |     |      |     |      |  |
| 1999   |   |      |  |      |      |     |     |       |     |      |     |      |  |
| 63.00  | <p>Navajo Route 171, a graded road, 20 ft. wide, bears NE and SW.</p>   |      |  |      |      |     |     |       |     |      |     |      |  |
| 80.00  | <p>Point for the cor. of secs. 1, 6, 7, and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,<br/>26 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T35N</td></tr> <tr><td style="text-align: center;">R26E</td><td style="text-align: center;">R27E</td></tr> <tr><td style="text-align: center;">S 1</td><td style="text-align: center;">S 6</td></tr> <tr><td colspan="2" style="text-align: center;">-----</td></tr> <tr><td style="text-align: center;">S12</td><td style="text-align: center;">S 7</td></tr> <tr><td colspan="2" style="text-align: center;">1999</td></tr> </table>   | T35N |  | R26E | R27E | S 1 | S 6 | ----- |     | S12  | S 7 | 1999 |  |
| T35N   |   |      |  |      |      |     |     |       |     |      |     |      |  |
| R26E   | R27E  |      |  |      |      |     |     |       |     |      |     |      |  |
| S 1    | S 6   |      |  |      |      |     |     |       |     |      |     |      |  |
| -----  |   |      |  |      |      |     |     |       |     |      |     |      |  |
| S12    | S 7   |      |  |      |      |     |     |       |     |      |     |      |  |
| 1999   |   |      |  |      |      |     |     |       |     |      |     |      |  |

Survey of the East Boundary,  
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS |   |
|--------|---|
|        | <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling.<br/>Soil, sandy clay.<br/>No timber; scattered brush and native grasses.</p> |
|        | <p>North, bet. secs. 1 and 6.</p> <p>Over gently rolling land.</p>  |
| 14.10  | Wash, 20 ft. wide, 3 ft. deep, drains E.  |
| 40.00  | Point for the 1/4 sec. cor. of secs. 1 and 6.   |
|        | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>   |
|        | <p style="text-align: center;">T35N<br/>R26E R27E<br/>1/4<br/>S 1   S 6<br/>1999</p>  |
|        | <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>  |
| 60.90  | Agua Sal Wash, 95 ft. wide, 3 ft. deep, drains WSW.   |
| 80.00  | Point for the cor. of Tps. 35 and 36 N., Rs. 26 and 27 E.   |
|        | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>   |
|        | <p style="text-align: center;">T36N<br/>R26E   R27E<br/>S36   S31<br/>-----<br/>S 1   S 6<br/>T35N<br/>1999</p>   |
|        | <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>  |

Survey of the East Boundary,  
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS |   |
|--------|---|
|        | <p>Land, gently rolling.<br/>Soil, sand and sandy clay.<br/>No timber; scattered brush and native grasses.</p> <hr/> <p style="text-align: center;">Survey of the North Boundary,<br/>T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>West, bet. secs. 1 and 36.</p> <p>Over gently rolling land.</p>  |
| 6.90   | <p>Agua Sal Wash, 60 ft. wide, 5 ft. deep, drains NNE.</p>  |
| 40.00  | <p>Point for the 1/4 sec. cor. of secs. 1 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,<br/>26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R26E<br/>S36<br/>1/4 —<br/>S 1<br/>T35N<br/>1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case<br/>beneath the stainless steel post.</p> <p>Cor. is located 2.60 chs. E. of Apache County Road C492, a graded<br/>road, bears NNE and SSW.</p> |
| 80.00  | <p>Point for the cor. of secs. 1, 2, 35, and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,<br/>24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R26E<br/>S35   S36<br/>—   —<br/>S 2   S 1<br/>T35N<br/>1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case<br/>beneath the stainless steel post.</p>  |

Survey of the North Boundary,  
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS |  |
|--------|--|
|        | <p>Land, gently rolling.<br/>Soil, sand, clay and sandy clay.<br/>No timber; scattered brush and native grasses.</p> <hr/> <p>West, bet. secs. 2 and 35.<br/>Over rolling land.</p>  |
| 37.50  | Power line, bears NE and SW.   |
| 39.58  | SE right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, bears NE and SW.   |
| 40.00  | <p>Point for the 1/4 sec. cor. of secs. 2 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R26E<br/>S35<br/>1/4 —<br/>S 2<br/>T35N<br/>1999</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 44°00' E., 19.7 ft. dist., with brass cap mkd. T35N R26E 1/4 S2 RM 19.7 FT TO COR 1999 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 45°00' W., 84.0 ft. dist., with brass cap mkd. T36N R26E 1/4 S35 RM 84.0 FT TO COR 1999 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post at the 1/4 sec. cor.</p> <p>Cor. is located 70 lks. E. of center of U. S. Highway 191, and 1.83 chs. E. of NW right-of-way fence, barbed wire, 5 strands, both bear NE and SW.</p> |
| 80.00  | Point for the cor. of secs. 2, 3, 34, and 35.  |

Survey of the North Boundary,  
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS |   |
|--------|---|
|        | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R26E<br/>S34   S35<br/>-----<br/>S 3   S 2<br/>T35N<br/>1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling.<br/>Soil, sandy clay.<br/>No timber; scattered brush and native grasses.</p>          |
|        | <p>West, bet. secs. 3 and 34.</p> <p>Over rolling land.</p>   |
| 13.20  | Base of E. slope of a mesa, bears SSE and NNW; thence over broken land on ascent.   |
| 26.90  | E. rim of a mesa, atop rock ledge, bears NNE and SSW; thence over nearly level land atop a mesa.  |
| 30.10  | W. rim of a mesa, atop rock ledge, bears NNE and SSW; thence over broken land on descent.   |
| 40.00  | <p>Point for the 1/4 sec. cor. of secs. 3 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in sandstone bedrock, supported in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T36N R26E<br/>S34<br/>1/4 —<br/>S 3<br/>T35N<br/>1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> |

Survey of the North Boundary,  
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS |  |      |      |     |     |       |     |      |  |      |  |      |  |
|--------|--|------|------|-----|-----|-------|-----|------|--|------|--|------|--|
|        | <p>From this cor. point, third order U. S. Geological Survey triangulation station "HADES 2", bears S. 36°34.4' E., 12.427 chs. dist., monumented with a rebar, 5/8 in. diam., set 3 ins. below the surface of the ground, and referenced as described in the published recovery sheet.</p>  |      |      |     |     |       |     |      |  |      |  |      |  |
| 45.40  | <p>Base of W. slope of a mesa, bears ESE and WNW; thence over rolling land.</p>  |      |      |     |     |       |     |      |  |      |  |      |  |
| 80.00  | <p>Point for the cor. of secs. 3, 4, 33, and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, to bedrock, encircled with a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T36N</td><td>R26E</td></tr> <tr><td>S33</td><td>S34</td></tr> <tr><td>S 4</td><td>S 3</td></tr> <tr><td colspan="2">T35N</td></tr> <tr><td colspan="2">1999</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located on SE slope of a ridge.</p> <p>Land, broken and rolling with nearly level mesa top. Soil, sandy and rocky clay, and sandstone outcrops. No timber; sparse brush and native grasses.</p> <hr/> <p>West, bet. secs. 4 and 33.</p> <p>Over rolling and broken land.</p> | T36N | R26E | S33 | S34 | S 4   | S 3 | T35N |  | 1999 |  |      |  |
| T36N   | R26E   |      |      |     |     |       |     |      |  |      |  |      |  |
| S33    | S34  |      |      |     |     |       |     |      |  |      |  |      |  |
| S 4    | S 3  |      |      |     |     |       |     |      |  |      |  |      |  |
| T35N   |  |      |      |     |     |       |     |      |  |      |  |      |  |
| 1999   |  |      |      |     |     |       |     |      |  |      |  |      |  |
| 40.00  | <p>Point for the 1/4 sec. cor. of secs. 4 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T36N</td><td>R26E</td></tr> <tr><td colspan="2">S33</td></tr> <tr><td colspan="2">1/4 —</td></tr> <tr><td colspan="2">S 4</td></tr> <tr><td colspan="2">T35N</td></tr> <tr><td colspan="2">1999</td></tr> </table> </div>  | T36N | R26E | S33 |     | 1/4 — |     | S 4  |  | T35N |  | 1999 |  |
| T36N   | R26E   |      |      |     |     |       |     |      |  |      |  |      |  |
| S33    |  |      |      |     |     |       |     |      |  |      |  |      |  |
| 1/4 —  |  |      |      |     |     |       |     |      |  |      |  |      |  |
| S 4    |  |      |      |     |     |       |     |      |  |      |  |      |  |
| T35N   |  |      |      |     |     |       |     |      |  |      |  |      |  |
| 1999   |  |      |      |     |     |       |     |      |  |      |  |      |  |

Survey of the North Boundary,  
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS |   |      |      |     |     |       |  |     |     |      |  |      |  |
|--------|---|------|------|-----|-----|-------|--|-----|-----|------|--|------|--|
|        | <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located on E. slope of a ridge.</p>   |      |      |     |     |       |  |     |     |      |  |      |  |
| 80.00  | <p>Point for the cor. of secs. 4, 5, 32, and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T36N</td><td>R26E</td></tr> <tr><td>S32</td><td>S33</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 5</td><td>S 4</td></tr> <tr><td colspan="2">T35N</td></tr> <tr><td colspan="2">1999</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, broken and rolling.<br/>Soil, sandy and rocky clay.<br/>No timber; sparse brush and native grasses.</p> | T36N | R26E | S32 | S33 | <hr/> |  | S 5 | S 4 | T35N |  | 1999 |  |
| T36N   | R26E  |      |      |     |     |       |  |     |     |      |  |      |  |
| S32    | S33   |      |      |     |     |       |  |     |     |      |  |      |  |
| <hr/>  |   |      |      |     |     |       |  |     |     |      |  |      |  |
| S 5    | S 4   |      |      |     |     |       |  |     |     |      |  |      |  |
| T35N   |   |      |      |     |     |       |  |     |     |      |  |      |  |
| 1999   |   |      |      |     |     |       |  |     |     |      |  |      |  |
|        | <p>West, bet. secs. 5 and 32.</p> <p>Over rolling and broken land.</p>  |      |      |     |     |       |  |     |     |      |  |      |  |
| 40.00  | <p>Point for the 1/4 sec. cor. of secs. 5 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T36N</td><td>R26E</td></tr> <tr><td colspan="2">S32</td></tr> <tr><td colspan="2">1/4 —</td></tr> <tr><td colspan="2">S 5</td></tr> <tr><td colspan="2">T35N</td></tr> <tr><td colspan="2">1999</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>   | T36N | R26E | S32 |     | 1/4 — |  | S 5 |     | T35N |  | 1999 |  |
| T36N   | R26E  |      |      |     |     |       |  |     |     |      |  |      |  |
| S32    |   |      |      |     |     |       |  |     |     |      |  |      |  |
| 1/4 —  |   |      |      |     |     |       |  |     |     |      |  |      |  |
| S 5    |   |      |      |     |     |       |  |     |     |      |  |      |  |
| T35N   |   |      |      |     |     |       |  |     |     |      |  |      |  |
| 1999   |   |      |      |     |     |       |  |     |     |      |  |      |  |
| 80.00  | <p>Point for the cor. of secs. 5, 6, 31, and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>  |      |      |     |     |       |  |     |     |      |  |      |  |

Survey of the North Boundary,  
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS    |   |           |  |     |     |     |   |     |     |      |  |      |  |
|-----------|---|-----------|--|-----|-----|-----|---|-----|-----|------|--|------|--|
|           | <table border="1" style="margin: auto;"> <tr><td colspan="2">T36N R26E</td></tr> <tr><td>S31</td><td>S32</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td>S 6</td><td>S 5</td></tr> <tr><td colspan="2">T35N</td></tr> <tr><td colspan="2">1999</td></tr> </table> | T36N R26E |  | S31 | S32 |     |   | S 6 | S 5 | T35N |  | 1999 |  |
| T36N R26E |   |           |  |     |     |     |   |     |     |      |  |      |  |
| S31       | S32   |           |  |     |     |     |   |     |     |      |  |      |  |
|           |   |           |  |     |     |     |   |     |     |      |  |      |  |
| S 6       | S 5   |           |  |     |     |     |   |     |     |      |  |      |  |
| T35N      |   |           |  |     |     |     |   |     |     |      |  |      |  |
| 1999      |   |           |  |     |     |     |   |     |     |      |  |      |  |
|           | <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling and broken.<br/>Soil, sandy and rocky clay.<br/>No timber; sparse brush and native grasses.</p>   |           |  |     |     |     |   |     |     |      |  |      |  |
|           | <p>West, bet. secs. 6 and 31.</p> <p>Over rolling and broken land.</p>  |           |  |     |     |     |   |     |     |      |  |      |  |
| 5.50      | Base of E. slope of a ridge, bears N. and S.; thence over broken land over ridge.   |           |  |     |     |     |   |     |     |      |  |      |  |
| 31.20     | Bottom of W. slope of a ridge, bears NE and SW; thence over nearly level land.  |           |  |     |     |     |   |     |     |      |  |      |  |
| 40.00     | Point for the 1/4 sec. cor. of secs. 6 and 31.  |           |  |     |     |     |   |     |     |      |  |      |  |
|           | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>   |           |  |     |     |     |   |     |     |      |  |      |  |
|           | <table border="1" style="margin: auto;"> <tr><td colspan="2">T36N R26E</td></tr> <tr><td colspan="2">S31</td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td colspan="2">S 6</td></tr> <tr><td colspan="2">T35N</td></tr> <tr><td colspan="2">1999</td></tr> </table>                                     | T36N R26E |  | S31 |     | 1/4 | — | S 6 |     | T35N |  | 1999 |  |
| T36N R26E |   |           |  |     |     |     |   |     |     |      |  |      |  |
| S31       |   |           |  |     |     |     |   |     |     |      |  |      |  |
| 1/4       | —   |           |  |     |     |     |   |     |     |      |  |      |  |
| S 6       |   |           |  |     |     |     |   |     |     |      |  |      |  |
| T35N      |   |           |  |     |     |     |   |     |     |      |  |      |  |
| 1999      |   |           |  |     |     |     |   |     |     |      |  |      |  |
|           | <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>  |           |  |     |     |     |   |     |     |      |  |      |  |
| 48.30     | Chinle Wash, 30 ft. wide, 3 ft. deep, drains NW.  |           |  |     |     |     |   |     |     |      |  |      |  |
| 78.40     | The cor. of Tps. 35 and 36 N., Rs. 25 and 26 E., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the east boundary, T. 35 N., R. 25 E., executed concurrently under this same group.                            |           |  |     |     |     |   |     |     |      |  |      |  |

Survey of the North Boundary,  
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS |   |
|--------|---|
|        | <p>Cor. is located 2.10 chs. N. of a trail road, bears ESE and WNW; and 2.30 chs. E. of another trail road, bears N. and S.</p> <p>Land, rolling and broken to nearly level.<br/>Soil, sandy and rocky clay.<br/>Timber, cottonwood, Russian olive and saltcedar near Chinle Wash; undergrowth, sparse brush and native grasses.</p>  |
|        | <p>Survey of the Subdivisional Lines,<br/>T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona</p>   |
|        | <p>From the cor. of secs. 1, 2, 35, and 36, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the north boundary, T. 34 N., R. 26 E., executed concurrently under this same group.</p> <p>N. 0°01' W., bet. secs. 35 and 36.</p> <p>Over rolling land.</p>   |
| 40.00  | <p>Point for the 1/4 sec. cor. of secs. 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E<br/>1/4<br/>S35   S36<br/>1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 90 lks. S. of a trail road, bears NE and SW.</p> |
| 80.00  | <p>Point for the cor. of secs. 25, 26, 35, and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E<br/>S26   S25<br/>-----<br/>S35   S36<br/>1999</p>  |

Survey of the Subdivisional Lines,  
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS |  |
|--------|--|
|        | <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling.<br/>Soil, sandy clay.<br/>No timber; scattered brush and native grasses.</p>  |
|        | <p>From the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 25 and 36.</p> <p>Over rolling land.</p>  |
| 36.25  | Trail road, bears ENE and WSW.   |
| 40.00  | <p>Point for the 1/4 sec. cor. of secs. 25 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>   |
|        | <p style="text-align: center;">T35N R26E<br/>S25<br/>1/4 —<br/>S36<br/>1999</p>  |
| 80.00  | <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 25, 26, 35, and 36.</p> <p>Land, rolling.<br/>Soil, sandy clay.<br/>No timber; scattered brush and native grasses.</p> |
| 40.00  | <p>N. 0°01' W., bet. secs. 25 and 26.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 25 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>             |

Survey of the Subdivisional Lines,  
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS |   |
|--------|---|
| 80.00  | <p style="text-align: center;">T35N R26E<br/>1/4<br/>S26   S25<br/>1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 23, 24, 25, and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E<br/>S23   S24<br/>-----<br/>S26   S25<br/>1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling.<br/>Soil, sandy clay.<br/>No timber; scattered brush and native grasses.</p> |
| 40.00  | <p>From the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 24 and 25.</p> <p>Over rolling and broken land.</p> <p>Point for the 1/4 sec. cor. of secs. 24 and 25.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>   |
| 43.60  | <p style="text-align: center;">T35N R26E<br/>S24<br/>1/4 —<br/>S25<br/>1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Apache County Road C492, a graded road, 22 ft. wide, bears SE and NW.</p>   |

Survey of the Subdivisional Lines,  
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS |  |
|--------|--|
| 80.00  | <p>The cor. of secs. 23, 24, 25, and 26.</p> <p>Land, rolling and broken.<br/>Soil, sandy and rocky clay.<br/>Timber, scattered juniper; undergrowth, scattered brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 23 and 24.</p> <p>Over rolling land.</p>  |
| 33.40  | <p>Apache County Road C492, a graded road, 20 ft. wide, bears SSE and NNW.</p>   |
| 40.00  | <p>Point for the 1/4 sec. cor. of secs. 23 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T35N R26E<br/>1/4<br/>S23   S24<br/>1999</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>   |
| 80.00  | <p>Point for the cor. of secs. 13, 14, 23, and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T35N R26E<br/>S14   S13<br/><hr/>S23   S24<br/>1999</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located near top of W. slope of a hill.</p> <p>Land, rolling and broken.<br/>Soil, sandy and rocky clay.<br/>No timber; scattered brush and native grasses.</p> <hr/> |

Survey of the Subdivisional Lines,  
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS |   |
|--------|---|
|        | <p>From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 13 and 24.</p> <p>Over rolling land.</p>   |
| 40.00  | <p>Point for the 1/4 sec. cor. of secs. 13 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E<br/>S13<br/>1/4 —<br/>S24<br/>1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> |
| 80.00  | <p>The cor. of secs. 13, 14, 23, and 24.</p> <p>Land, rolling.<br/>Soil, sandy and rocky clay.<br/>No timber; sparse brush and native grasses.</p>  |
|        | <p>N. 0°01' W., bet. secs. 13 and 14.</p> <p>Over rolling land.</p>   |
| 40.00  | <p>Point for the 1/4 sec. cor. of secs. 13 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E<br/>1/4<br/>S14   S13<br/>1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>     |
| 63.50  | <p>Cor. is located 1.60 chs. S. of a power line, bears ESE and WNW.</p> <p>Apache County Road C492, a graded road, 15 ft. wide, bears NNE and SSW.</p>  |

Survey of the Subdivisional Lines,  
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS    |   |           |  |     |     |     |     |      |     |      |  |
|-----------|---|-----------|--|-----|-----|-----|-----|------|-----|------|--|
| 80.00     | <p>Point for the cor. of secs. 11, 12, 13, and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td colspan="2">T35N R26E</td> </tr> <tr> <td>S11</td> <td>S12</td> </tr> <tr> <td>S14</td> <td>S13</td> </tr> <tr> <td colspan="2">1999</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling.<br/>Soil, sandy clay.<br/>No timber; scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 12 and 13.</p> <p>Over rolling land.</p> | T35N R26E |  | S11 | S12 | S14 | S13 | 1999 |     |      |  |
| T35N R26E |   |           |  |     |     |     |     |      |     |      |  |
| S11       | S12   |           |  |     |     |     |     |      |     |      |  |
| S14       | S13   |           |  |     |     |     |     |      |     |      |  |
| 1999      |   |           |  |     |     |     |     |      |     |      |  |
| 40.00     | <p>Point for the 1/4 sec. cor. of secs. 12 and 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td colspan="2">T35N R26E</td> </tr> <tr> <td></td> <td>S12</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S13</td> </tr> <tr> <td colspan="2">1999</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located atop a bare clay ridge, bears E. and W.</p>   | T35N R26E |  |     | S12 | 1/4 | —   |      | S13 | 1999 |  |
| T35N R26E |   |           |  |     |     |     |     |      |     |      |  |
|           | S12   |           |  |     |     |     |     |      |     |      |  |
| 1/4       | —   |           |  |     |     |     |     |      |     |      |  |
|           | S13   |           |  |     |     |     |     |      |     |      |  |
| 1999      |   |           |  |     |     |     |     |      |     |      |  |
| 72.20     | <p>Apache County Road C492, a graded road, 18 ft. wide, bears NNE and SSW.</p>  |           |  |     |     |     |     |      |     |      |  |
| 80.00     | <p>The cor. of secs. 11, 12, 13, and 14.</p>  |           |  |     |     |     |     |      |     |      |  |

Survey of the Subdivisional Lines,  
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS |   |
|--------|---|
|        | <p>Land, rolling.<br/>Soil, sandy and rocky clay.<br/>No timber; sparse brush and native grasses.</p>             |
|        | <hr/>   |
|        | <p>N. 0°01' W., bet. secs. 11 and 12.</p>   |
|        | <p>Over rolling and broken land.</p>  |
| 40.00  | <p>Point for the 1/4 sec. cor. of secs. 11 and 12.</p>  |
|        | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,<br/>24 ins. in the ground, with brass cap mkd.</p> |
|        | <p style="text-align: center;">T35N R26E<br/>1/4<br/>S11   S12<br/>1999</p>                                       |
|        | <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case<br/>beneath the stainless steel post.</p>      |
|        | <p>Cor. is located on the S. slope of a bare clay hill.</p>   |
| 80.00  | <p>Point for the cor. of secs. 1, 2, 11, and 12.</p>  |
|        | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,<br/>24 ins. in the ground, with brass cap mkd.</p> |
|        | <p style="text-align: center;">T35N R26E<br/>S 2   S 1<br/><hr/>S11   S12<br/>1999</p>                            |
|        | <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case<br/>beneath the stainless steel post.</p>      |
|        | <p>Land, rolling and broken.<br/>Soil, sandy and rocky clay.<br/>No timber; sparse brush and native grasses.</p>  |
|        | <hr/>   |
|        | <p>From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the<br/>Tp., hereinbefore described.</p>             |
|        | <p>West, bet. secs. 1 and 12.</p>   |
|        | <p>Over rolling land.</p>   |

Survey of the Subdivisional Lines,  
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS |  |
|--------|--|
| 9.90   | Wash, 25 ft. wide, 3 ft. deep, drains NNW.   |
| 18.80  | Navajo Route 171, a graded road, 20 ft. wide, bears NNW and SSE.   |
| 31.20  | Apache County Road C492, a graded road, 20 ft. wide, bears NNE and SSW.                                    |
| 40.00  | Point for the 1/4 sec. cor. of secs. 1 and 12.   |
|        | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.     |
|        | <p style="text-align: center;">T35N R26E<br/>S 1<br/>1/4 —<br/>S12<br/>1999</p>                            |
|        | Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.          |
|        | Thence over rolling and broken land.   |
| 80.00  | The cor. of secs. 1, 2, 11, and 12.  |
|        | Land, rolling and broken.<br>Soil, sandy and rocky clay.<br>No timber; scattered brush and native grasses. |
|        | N. 0°01' W., bet. secs. 1 and 2.   |
|        | Over rolling land.   |
| 40.00  | Point for the 1/4 sec. cor. of secs. 1 and 2.  |
|        | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.     |
|        | <p style="text-align: center;">T35N R26E<br/>1/4<br/>S 2   S 1<br/>1999</p>                                |
|        | Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.          |
|        | Cor. is located on N. slope of a hill.   |

Survey of the Subdivisional Lines,  
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS |   |
|--------|---|
| 80.00  | <p>The cor. of secs. 1, 2, 35, and 36, on the N. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling.<br/>Soil, sandy and rocky clay.<br/>No timber; scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the north boundary, T. 34 N., R. 26 E., executed concurrently under this same group.</p> <p>N. 0°01' W., bet. secs. 34 and 35.</p> <p>Over rolling and broken land.</p> |
| 40.00  | <p>Point for the 1/4 sec. cor. of secs. 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T35N R26E<br/>1/4<br/>S34   S35<br/>1999</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>  |
| 80.00  | <p>Point for the cor. of secs. 26, 27, 34, and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T35N R26E<br/>S27   S26<br/>-----<br/>S34   S35<br/>1999</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>  |

Survey of the Subdivisional Lines,  
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS |  |
|--------|--|
|        | <p>Land, rolling and broken.<br/>Soil, sandy and rocky clay.<br/>No timber; sparse brush and native grasses.</p> <hr/> <p>From the cor. of secs. 25, 26, 35, and 36.<br/>West, bet. secs. 26 and 35.<br/>Over rolling and broken land.</p>   |
| 40.00  | <p>Point for the 1/4 sec. cor. of secs. 26 and 35.<br/>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,<br/>26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E<br/>S26<br/>1/4 —<br/>S35<br/>1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case<br/>beneath the stainless steel post.</p> |
| 80.00  | <p>The cor. of secs. 26, 27, 34, and 35.<br/>Land, rolling.<br/>Soil, sandy and rocky clay.<br/>No timber; sparse brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 26 and 27.<br/>Over rolling land.</p>   |
| 40.00  | <p>Point for the 1/4 sec. cor. of secs. 26 and 27.<br/>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,<br/>26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E<br/>1/4<br/>S27   S26<br/>1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case<br/>beneath the stainless steel post.</p>     |
| 80.00  | <p>Point for the cor. of secs. 22, 23, 26, and 27.</p>   |

Survey of the Subdivisional Lines,  
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS |  |      |      |     |     |     |     |      |     |      |  |
|--------|--|------|------|-----|-----|-----|-----|------|-----|------|--|
|        | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="867 373 1013 527"> <tr> <td>T35N</td> <td>R26E</td> </tr> <tr> <td>S22</td> <td>S23</td> </tr> <tr> <td>S27</td> <td>S26</td> </tr> <tr> <td colspan="2">1999</td> </tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling.<br/>Soil, sandy clay.<br/>No timber; scattered brush and native grasses.</p> | T35N | R26E | S22 | S23 | S27 | S26 | 1999 |     |      |  |
| T35N   | R26E   |      |      |     |     |     |     |      |     |      |  |
| S22    | S23  |      |      |     |     |     |     |      |     |      |  |
| S27    | S26  |      |      |     |     |     |     |      |     |      |  |
| 1999   |  |      |      |     |     |     |     |      |     |      |  |
|        | <p>From the cor. of secs. 23, 24, 25, and 26.</p> <p>West, bet. secs. 23 and 26.</p> <p>Over rolling land.</p>   |      |      |     |     |     |     |      |     |      |  |
| 40.00  | <p>Point for the 1/4 sec. cor. of secs. 23 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="867 1167 1013 1320"> <tr> <td>T35N</td> <td>R26E</td> </tr> <tr> <td></td> <td>S23</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S26</td> </tr> <tr> <td colspan="2">1999</td> </tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>          | T35N | R26E |     | S23 | 1/4 | —   |      | S26 | 1999 |  |
| T35N   | R26E   |      |      |     |     |     |     |      |     |      |  |
|        | S23  |      |      |     |     |     |     |      |     |      |  |
| 1/4    | —  |      |      |     |     |     |     |      |     |      |  |
|        | S26  |      |      |     |     |     |     |      |     |      |  |
| 1999   |  |      |      |     |     |     |     |      |     |      |  |
| 80.00  | <p>The cor. of secs. 22, 23, 26, and 27.</p> <p>Land, rolling.<br/>Soil, sandy clay.<br/>No timber; scattered brush and native grasses.</p>  |      |      |     |     |     |     |      |     |      |  |
|        | <p>N. 0°01' W., bet. secs. 22 and 23.</p> <p>Over rolling and broken land.</p>   |      |      |     |     |     |     |      |     |      |  |
| 40.00  | <p>Point for the 1/4 sec. cor. of secs. 22 and 23.</p>   |      |      |     |     |     |     |      |     |      |  |

Survey of the Subdivisional Lines,  
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS |  |
|--------|--|
|        | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E<br/>1/4<br/>S22   S23<br/>1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>   |
| 80.00  | <p>Point for the cor. of secs. 14, 15, 22, and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E<br/>S15   S14<br/>-----<br/>S22   S23<br/>1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located on N. slope of a small clay ridge.</p> <p>Land, rolling and broken.<br/>Soil, sandy and rocky clay.<br/>No timber; sparse brush and native grasses.</p> |
|        | <p>From the cor. of secs. 13, 14, 23, and 24.</p> <p>West, bet. secs. 14 and 23.</p> <p>Over rolling land.</p>   |
| 17.00  | <p>Apache County Road C492, a graded road, 20 ft. wide, bears N. and S.</p>  |
| 40.00  | <p>Point for the 1/4 sec. cor. of secs. 14 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>   |

Survey of the Subdivisional Lines,  
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS |  |
|--------|--|
|        | T35N R26E<br>S14<br>1/4 —<br>S23<br>1999   |
| 80.00  | Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.<br><br>The cor. of secs. 14, 15, 22, and 23.<br><br>Land, rolling.<br>Soil, sandy and rocky clay.<br>No timber; sparse brush and native grasses. |
| 40.00  | N. 0°01' W., bet. secs. 14 and 15.<br><br>Over rolling and broken land.<br><br>Point for the 1/4 sec. cor. of secs. 14 and 15.<br><br>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.       |
|        | T35N R26E<br>1/4<br>S15   S14<br>1999  |
| 72.70  | Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.<br><br>Cor. is located atop a small clay hill.<br><br>Apache County Road C590, a graded road, 20 ft. wide, bears ESE and WNW.                    |
| 80.00  | Point for the cor. of secs. 10, 11, 14, and 15.<br><br>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, to bedrock, supported in a mound of stone, 3 ft. base, to top, with brass cap mkd.                       |
|        | T35N R26E<br>S10   S11<br>————<br>S15   S14<br>1999  |

Survey of the Subdivisional Lines,  
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS |  |
|--------|--|
|        | <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling and broken.<br/>Soil, sandy and rocky clay.<br/>No timber; sparse brush and native grasses.</p> <hr/> <p>From the cor. of secs. 11, 12, 13, and 14.</p> <p>West, bet. secs. 11 and 14.</p> <p>Over rolling land.</p> |
| 40.00  | <p>Point for the 1/4 sec. cor. of secs. 11 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E<br/>S11<br/>1/4 —<br/>S14<br/>1999</p>   |
| 80.00  | <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 10, 11, 14, and 15.</p> <p>Land, rolling.<br/>Soil, sandy and rocky clay.<br/>No timber; sparse brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 10 and 11.</p> <p>Over rolling land.</p>          |
| 40.00  | <p>Point for the 1/4 sec. cor. of secs. 10 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E<br/>1/4<br/>S10   S11<br/>1999</p>   |

Survey of the Subdivisional Lines,  
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS |  |      |      |     |     |     |     |      |  |      |  |
|--------|--|------|------|-----|-----|-----|-----|------|--|------|--|
| 80.00  | <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 2, 3, 10, and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T35N</td><td>R26E</td></tr> <tr><td>S 3</td><td>S 2</td></tr> <tr><td>S10</td><td>S11</td></tr> <tr><td colspan="2">1999</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling.<br/>Soil, sandy and rocky clay.<br/>No timber; sparse brush and native grasses.</p> <hr/> <p>From the cor. of secs. 1, 2, 11, and 12.</p> <p>West, bet. secs. 2 and 11.</p> <p>Over rolling land.</p> | T35N | R26E | S 3 | S 2 | S10 | S11 | 1999 |  |      |  |
| T35N   | R26E   |      |      |     |     |     |     |      |  |      |  |
| S 3    | S 2  |      |      |     |     |     |     |      |  |      |  |
| S10    | S11  |      |      |     |     |     |     |      |  |      |  |
| 1999   |  |      |      |     |     |     |     |      |  |      |  |
| 40.00  | <p>Point for the 1/4 sec. cor. of secs. 2 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T35N</td><td>R26E</td></tr> <tr><td>S 2</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S11</td><td></td></tr> <tr><td colspan="2">1999</td></tr> </table> </div>  | T35N | R26E | S 2 |     | 1/4 | —   | S11  |  | 1999 |  |
| T35N   | R26E   |      |      |     |     |     |     |      |  |      |  |
| S 2    |  |      |      |     |     |     |     |      |  |      |  |
| 1/4    | —  |      |      |     |     |     |     |      |  |      |  |
| S11    |  |      |      |     |     |     |     |      |  |      |  |
| 1999   |  |      |      |     |     |     |     |      |  |      |  |
| 80.00  | <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 2, 3, 10, and 11.</p> <p>Land, rolling.<br/>Soil, sandy clay.<br/>No timber; scattered brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 2 and 3.</p>   |      |      |     |     |     |     |      |  |      |  |

Survey of the Subdivisional Lines,  
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS |   |
|--------|---|
|        | Over rolling land.  |
| 39.70  | Power line, bears NE and SW.  |
| 40.00  | Point for the 1/4 sec. cor. of secs. 2 and 3.<br><br>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,<br>26 ins. in the ground, with brass cap mkd.<br><br><div style="text-align: center;">           T35N R26E<br/>           1/4<br/>           S 3   S 2<br/>           1999         </div>  |
|        | Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case<br>beneath the stainless steel post.  |
| 44.92  | S. right-of-way fence of U. S. Highway 191, barbed wire,<br>5 strands, parallels highway.   |
| 45.83  | Center of U. S. Highway 191, asphalt pavement, 25 ft. wide, bears<br>ENE in curve to left.  |
| 46.64  | N. right-of-way fence of U. S. Highway 191, barbed wire,<br>5 strands, parallels highway.   |
| 80.00  | The cor. of secs. 2, 3, 34, and 35, on the N. bdy. of the Tp.,<br>hereinbefore described,<br><br>Land, rolling.<br>Soil, sandy clay.<br>No timber; scattered brush and native grasses.  |
|        | From the cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the<br>Tp., monumented with a stainless steel post, 2 1/2 ins. diam.,<br>with brass cap, set and mkd. as described in the field notes of<br>the survey of the north boundary, T. 34 N., R. 26 E., executed<br>concurrently under this same group.<br><br>N. 0°02' W., bet. secs. 33 and 34.<br><br>Over rolling and broken land. |
| 40.00  | Point for the 1/4 sec. cor. of secs. 33 and 34.<br><br>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,<br>26 ins. in the ground, with brass cap mkd.  |

Survey of the Subdivisional Lines,  
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS |   |
|--------|---|
| 80.00  | <p style="text-align: center;">T35N R26E<br/>1/4<br/>S33   S34<br/>1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 27, 28, 33, and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E<br/>S28   S27<br/>-----<br/>S33   S34<br/>1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling and broken.<br/>Soil, sandy and rocky clay.<br/>No timber; sparse brush and native grasses.</p> |
| 40.00  | <p>From the cor. of secs. 26, 27, 34, and 35.</p> <p>West, bet. secs. 27 and 34.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 27 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E<br/>S27<br/>1/4 —<br/>S34<br/>1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 1.72 chs. E. of a barbed wire fence, 5 strands, bears NNE and SSW.</p>  |

Survey of the Subdivisional Lines,  
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS |   |
|--------|---|
| 80.00  | <p>The cor. of secs. 27, 28, 33, and 34.</p> <p>Land, rolling.<br/>Soil, sandy and rocky clay.<br/>No timber; sparse brush and native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 27 and 28.</p> <p>Over rolling and broken land.</p>   |
| 8.50   | White Water Wash, 20 ft. wide, 5 ft. deep, drains WNW.  |
| 18.00  | Base of S. slope of a mesa, bears NE and SW.  |
| 35.80  | S. rim of a mesa, atop rock ledge, bears ESE and WNW; thence over rolling land atop mesa.   |
| 40.00  | <p>Point for the 1/4 sec. cor. of secs. 27 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E<br/>1/4<br/>S28   S27<br/>1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Thence gradually descend N. slope of a mesa.</p> |
| 80.00  | <p>Point for the cor. of secs. 21, 22, 27, and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E<br/>S21   S22<br/>-----<br/>S28   S27<br/>1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>                                     |

Survey of the Subdivisional Lines,  
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS |   |
|--------|---|
|        | <p>Land, rolling and broken.<br/>Soil, sandy and rocky clay.<br/>No timber; scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 22, 23, 26, and 27.<br/>West, bet. secs. 22 and 27.<br/>Over rolling and broken land.</p>   |
| 40.00  | <p>Point for the 1/4 sec. cor. of secs. 22 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,<br/>26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E<br/>S22<br/>1/4 —<br/>S27<br/>1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case<br/>beneath the stainless steel post.</p> |
| 80.00  | <p>The cor. of secs. 21, 22, 27, and 28.</p> <p>Land, rolling and broken.<br/>Soil, sandy and rocky clay.<br/>No timber; sparse brush and native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 21 and 22.<br/>Over rolling and broken land.</p>   |
| 40.00  | <p>Point for the 1/4 sec. cor. of secs. 21 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,<br/>26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E<br/>1/4<br/>S21   S22<br/>1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case<br/>beneath the stainless steel post.</p>     |
| 70.80  | <p>Wash, 30 ft. wide, 2 ft. deep, drains NW.</p>  |

Survey of the Subdivisional Lines,  
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS    |  |           |  |     |     |       |  |     |     |      |  |
|-----------|--|-----------|--|-----|-----|-------|--|-----|-----|------|--|
| 74.30     | Wash, 10 ft. wide, 1 ft. deep, drains WSW.   |           |  |     |     |       |  |     |     |      |  |
| 80.00     | <p>Point for the cor. of secs. 15, 16, 21, and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T35N R26E</td></tr> <tr><td>S16</td><td>S15</td></tr> <tr><td colspan="2">—</td></tr> <tr><td>S21</td><td>S22</td></tr> <tr><td colspan="2">1999</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling and broken.<br/>Soil, sandy and rocky clay.<br/>No timber; sparse brush and native grasses.</p> | T35N R26E |  | S16 | S15 | —     |  | S21 | S22 | 1999 |  |
| T35N R26E |  |           |  |     |     |       |  |     |     |      |  |
| S16       | S15  |           |  |     |     |       |  |     |     |      |  |
| —         |  |           |  |     |     |       |  |     |     |      |  |
| S21       | S22  |           |  |     |     |       |  |     |     |      |  |
| 1999      |  |           |  |     |     |       |  |     |     |      |  |
|           | <p>From the cor. of secs. 14, 15, 22, and 23.</p> <p>West, bet. secs. 15 and 22.</p> <p>Over rolling and broken land.</p>  |           |  |     |     |       |  |     |     |      |  |
| 40.00     | <p>Point for the 1/4 sec. cor. of secs. 15 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T35N R26E</td></tr> <tr><td colspan="2">S15</td></tr> <tr><td colspan="2">1/4 —</td></tr> <tr><td colspan="2">S22</td></tr> <tr><td colspan="2">1999</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located at the base of a bare clay hill.</p>  | T35N R26E |  | S15 |     | 1/4 — |  | S22 |     | 1999 |  |
| T35N R26E |  |           |  |     |     |       |  |     |     |      |  |
| S15       |  |           |  |     |     |       |  |     |     |      |  |
| 1/4 —     |  |           |  |     |     |       |  |     |     |      |  |
| S22       |  |           |  |     |     |       |  |     |     |      |  |
| 1999      |  |           |  |     |     |       |  |     |     |      |  |
| 80.00     | The cor. of secs. 15, 16, 21, and 22.  |           |  |     |     |       |  |     |     |      |  |

Survey of the Subdivisional Lines,  
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS |   |
|--------|---|
|        | <p>Land, rolling and broken land.<br/>Soil, sandy and rocky clay.<br/>No timber; sparse brush and native grasses.</p> |
|        | <p>N. 0°02' W., bet. secs. 15 and 16.</p>   |
|        | <p>Over rolling and broken land.</p>  |
| 40.00  | <p>Point for the 1/4 sec. cor. of secs. 15 and 16.</p>  |
|        | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,<br/>24 ins. in the ground, with brass cap mkd.</p>     |
|        | <p style="text-align: center;">T35N R26E<br/>1/4<br/>S16   S15<br/>1999</p>   |
|        | <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case<br/>beneath the stainless steel post.</p>          |
| 80.00  | <p>Point for the cor. of secs. 9, 10, 15, and 16.</p>   |
|        | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,<br/>22 ins. in the ground, with brass cap mkd.</p>     |
|        | <p style="text-align: center;">T35N R26E<br/>S 9   S10<br/>-----<br/>S16   S15<br/>1999</p>                           |
|        | <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case<br/>beneath the stainless steel post.</p>          |
|        | <p>Cor. is located on the NE edge of a wash, 3 ft. wide, 1 ft. deep,<br/>drains NW.</p>                               |
|        | <p>Land, rolling and broken.<br/>Soil, sandy and rocky clay.<br/>No timber; sparse brush and native grasses.</p>      |
|        | <p>From the cor. of secs. 10, 11, 14, and 15.</p>   |
|        | <p>West, bet. secs. 10 and 15.</p>  |
|        | <p>Over rolling land.</p>   |

Survey of the Subdivisional Lines,  
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS |  |
|--------|--|
| 11.30  | Apache County Road C590, a graded road, 20 ft. wide, bears N. and S.   |
| 40.00  | Point for the 1/4 sec. cor. of secs. 10 and 15.<br><br>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.<br><br>T35N R26E<br>S10<br>1/4 —<br>S15<br>1999<br><br>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post. |
| 80.00  | The cor. of secs. 9, 10, 15, and 16.<br><br>Land, rolling.<br>Soil, sandy and rocky clay.<br>No timber; sparse brush and native grasses.   |
|        | N. 0°02' W., bet. secs. 9 and 10.<br><br>Over rolling land.  |
| 40.00  | Point for the 1/4 sec. cor. of secs. 9 and 10.<br><br>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.<br><br>T35N R26E<br>1/4<br>S 9   S10<br>1999<br><br>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.     |
| 54.80  | Power line, bears NE and SW.   |
| 63.30  | Red Water Wash, 20 ft. wide, 3 ft. deep, drains W.   |
| 80.00  | Point for the cor. of secs. 3, 4, 9, and 10.<br><br>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.   |

Survey of the Subdivisional Lines,  
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS |   |      |      |     |     |     |       |      |     |      |  |
|--------|---|------|------|-----|-----|-----|-------|------|-----|------|--|
|        | <table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td>T35N</td> <td>R26E</td> </tr> <tr> <td>S 4</td> <td>S 3</td> </tr> <tr> <td>S 9</td> <td>S10</td> </tr> <tr> <td colspan="2" style="text-align: center;">1999</td> </tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling.<br/>Soil, sandy and rocky clay.<br/>No timber; sparse brush and native grasses.</p>   | T35N | R26E | S 4 | S 3 | S 9 | S10   | 1999 |     |      |  |
| T35N   | R26E  |      |      |     |     |     |       |      |     |      |  |
| S 4    | S 3   |      |      |     |     |     |       |      |     |      |  |
| S 9    | S10   |      |      |     |     |     |       |      |     |      |  |
| 1999   |   |      |      |     |     |     |       |      |     |      |  |
|        | <p>From the cor. of secs. 2, 3, 10, and 11.</p> <p>West, bet. secs. 3 and 10.</p> <p>Over rolling land.</p>   |      |      |     |     |     |       |      |     |      |  |
| 3.90   | Apache County Road C590, a graded road, 20 ft. wide, bears N. and S.  |      |      |     |     |     |       |      |     |      |  |
| 40.00  | <p>Point for the 1/4 sec. cor. of secs. 3 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td>T35N</td> <td>R26E</td> </tr> <tr> <td></td> <td>S 3</td> </tr> <tr> <td></td> <td>1/4 —</td> </tr> <tr> <td></td> <td>S10</td> </tr> <tr> <td colspan="2" style="text-align: center;">1999</td> </tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 1.30 chs. E. of a trail road, bears NNE and SSW.</p> | T35N | R26E |     | S 3 |     | 1/4 — |      | S10 | 1999 |  |
| T35N   | R26E  |      |      |     |     |     |       |      |     |      |  |
|        | S 3   |      |      |     |     |     |       |      |     |      |  |
|        | 1/4 —   |      |      |     |     |     |       |      |     |      |  |
|        | S10   |      |      |     |     |     |       |      |     |      |  |
| 1999   |   |      |      |     |     |     |       |      |     |      |  |
| 48.30  | Power line, bears NE and SW.  |      |      |     |     |     |       |      |     |      |  |
| 80.00  | <p>The cor. of secs. 3, 4, 9, and 10.</p> <p>Land, rolling.<br/>Soil, sandy clay.<br/>No timber; sparse brush and native grasses.</p>   |      |      |     |     |     |       |      |     |      |  |
|        | <p>N. 0°02' W., bet. secs. 3 and 4.</p>   |      |      |     |     |     |       |      |     |      |  |

Survey of the Subdivisional Lines,  
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS |   |
|--------|---|
|        | Over rolling land.  |
| 33.95  | S. right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway.  |
| 35.85  | Center of U. S. Highway 191, asphalt pavement, 25 ft. wide, bears E. and W.   |
| 37.75  | N. right-of-way fence of Arizona State Highway 191, barbed wire, 5 strands, parallels highway.  |
| 40.00  | Point for the 1/4 sec. cor. of secs. 3 and 4.<br><br>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.<br><br><div style="text-align: center;">           T35N R26E<br/>           1/4<br/>           S 4   S 3<br/>           1999         </div><br>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.<br><br>Thence ascend over rolling and broken land. |
| 80.00  | The cor. of secs. 3, 4, 33, and 34, on the N. bdy. of the Tp., hereinbefore described.<br><br>Land, rolling and broken.<br>Soil, sandy and rocky clay.<br>No timber; sparse brush and native grasses.   |
|        | From the cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the north boundary, T. 34 N., R. 26 E., executed concurrently under this same group.<br><br>N. 0°03' W., bet. secs. 32 and 33.<br><br>Over rolling and broken land.   |
| 40.00  | Point for the 1/4 sec. cor. of secs. 32 and 33.<br><br>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.   |

Survey of the Subdivisional Lines,  
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS |  |
|--------|--|
|        | <p style="text-align: center;">T35N R26E<br/>1/4<br/>S32   S33<br/>1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>   |
| 63.80  | White Water Wash, 20 ft. wide, 2 ft. deep, drains NW.  |
| 80.00  | <p>Point for the cor. of secs. 28, 29, 32, and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p>   |
|        | <p style="text-align: center;">T35N R26E<br/>S29   S28<br/>-----<br/>S32   S33<br/>1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located atop a rocky ridge, 25 lks. N. and 45 lks. E. of S. rim, ridge bears SE and NW.</p> <p>Land, rolling and broken.<br/>Soil, sandy and rocky clay.<br/>No timber; sparse brush and native grasses.</p> |
|        | <p>From the cor. of secs. 27, 28, 33, and 34.</p> <p>West, bet. secs. 28 and 33.</p> <p>Over rolling and broken land.</p>  |
| 36.00  | White Water Wash, 20 ft. wide, 1 ft. deep, drains WSW.   |
| 40.00  | <p>Point for the 1/4 sec. cor. of secs. 28 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>   |
|        | <p style="text-align: center;">T35N R26E<br/>S28<br/>1/4 —<br/>S33<br/>1999</p>  |

Survey of the Subdivisional Lines,  
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS |  |
|--------|--|
| 80.00  | <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 28, 29, 32, and 33.</p> <p>Land, rolling and broken.<br/>Soil, sandy and rocky clay.<br/>No timber; sparse brush and native grasses.</p>   |
| 40.00  | <p>N. 0°03' W., bet. secs. 28 and 29.</p> <p>Over rolling and broken land.</p> <p>Point for the 1/4 sec. cor. of secs. 28 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T35N R26E<br/>1/4<br/>S29   S28<br/>1999</p> </div>   |
| 80.00  | <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 20, 21, 28, and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T35N R26E<br/>S20   S21<br/>-----<br/>S29   S28<br/>1999</p> </div> |
|        | <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling and broken.<br/>Soil, sandy and rocky clay.<br/>No timber; sparse brush and native grasses.</p> <hr/> <p>From the cor. of secs. 21, 22, 27, and 28.</p> <p>West, bet. secs. 21 and 28.</p>   |

Survey of the Subdivisional Lines,  
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS |  |
|--------|--|
|        | Over rolling land.   |
| 40.00  | Point for the 1/4 sec. cor. of secs. 21 and 28.<br><br>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,<br>26 ins. in the ground, with brass cap mkd.<br><br><div style="text-align: center;">           T35N R26E<br/>                 S21<br/>           1/4 —<br/>                 S28<br/>           1999         </div>  |
| 80.00  | Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case<br>beneath the stainless steel post.<br><br>The cor. of secs. 20, 21, 28, and 29.<br><br>Land, rolling.<br>Soil, sandy and rocky clay.<br>No timber; sparse brush and native grasses.  |
|        | N. 0°03' W., bet. secs. 20 and 21.   |
|        | Over rolling land.   |
| 40.00  | Point for the 1/4 sec. cor. of secs. 20 and 21.<br><br>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,<br>24 ins. in the ground, with brass cap mkd.<br><br><div style="text-align: center;">           T35N R26E<br/>                 1/4<br/>           S20   S21<br/>           1999         </div>   |
| 80.00  | Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case<br>beneath the stainless steel post.<br><br>Point for the cor. of secs. 16, 17, 20, and 21.<br><br>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,<br>24 ins. in the ground, with brass cap mkd.<br><br><div style="text-align: center;">           T35N R26E<br/>           S17   S16<br/>           ————<br/>           S20   S21<br/>           1999         </div> |

Survey of the Subdivisional Lines,  
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS |  |
|--------|--|
|        | <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling.<br/>Soil, sandy and rocky clay.<br/>No timber; sparse brush and native grasses.</p>                                       |
|        | <p>From the cor. of secs. 15, 16, 21, and 22.</p> <p>West, bet. secs. 16 and 21.</p> <p>Over rolling land.</p>   |
| 40.00  | <p>Point for the 1/4 sec. cor. of secs. 16 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E<br/>S16<br/>1/4 —<br/>S21<br/>1999</p> |
| 71.70  | <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Wash, 60 ft. wide, 3 ft. deep, drains N.</p>   |
| 80.00  | <p>The cor. of secs. 16, 17, 20, and 21.</p> <p>Land, rolling.<br/>Soil, sandy and rocky clay.<br/>No timber; sparse brush and native grasses.</p>   |
|        | <p>N. 0°03' W., bet. secs. 16 and 17.</p> <p>Over rolling land.</p>  |
| 11.50  | <p>Wash, 55 ft. wide, 3 ft. deep, drains WNW.</p>  |
| 40.00  | <p>Point for the 1/4 sec. cor. of secs. 16 and 17.</p> <p>Set a magnet enclosed in a 1 x 1 x 2 ins. white plastic case, 24 ins. below the surface of the ground.</p>   |

Survey of the Subdivisional Lines,  
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS |  |      |      |     |     |  |  |     |     |      |  |
|--------|--|------|------|-----|-----|--|--|-----|-----|------|--|
|        | <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 80°00' E., 180.0 ft. dist., with brass cap mkd. T35N R26E 1/4 S16 RM 180.0 FT TO COR 1999 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 10°00' W., 160.0 ft. dist., with brass cap mkd. T35N R26E 1/4 S17 RM 160.0 FT TO COR 1999 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located in Red Water Wash, 60 ft. wide, 6 ft. deep; 30 lks. W. of left bank, and 2.00 chs. S. of right bank, drains SSW in curve to left.</p> |      |      |     |     |  |  |     |     |      |  |
| 57.30  | Power line, bears NNE and SSW.   |      |      |     |     |  |  |     |     |      |  |
| 80.00  | <p>Point for the cor. of secs. 8, 9, 16, and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table data-bbox="857 1136 1008 1289" style="margin-left: auto; margin-right: auto;"> <tr> <td>T35N</td> <td>R26E</td> </tr> <tr> <td>S 8</td> <td>S 9</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black;"></td> </tr> <tr> <td>S17</td> <td>S16</td> </tr> <tr> <td colspan="2" style="text-align: center;">1999</td> </tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling.<br/>Soil, sandy clay.<br/>No timber; sparse brush and native grasses.</p>   | T35N | R26E | S 8 | S 9 |  |  | S17 | S16 | 1999 |  |
| T35N   | R26E   |      |      |     |     |  |  |     |     |      |  |
| S 8    | S 9  |      |      |     |     |  |  |     |     |      |  |
|        |  |      |      |     |     |  |  |     |     |      |  |
| S17    | S16  |      |      |     |     |  |  |     |     |      |  |
| 1999   |  |      |      |     |     |  |  |     |     |      |  |
| 40.00  | <p>From the cor. of secs. 9, 10, 15, and 16.</p> <p>West, bet. secs. 9 and 16.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 9 and 16.</p>   |      |      |     |     |  |  |     |     |      |  |

Survey of the Subdivisional Lines,  
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS |   |
|--------|---|
|        | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E<br/>S 9<br/>1/4 —<br/>S16<br/>1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>  |
| 52.60  | Red Water Wash, 70 ft. wide, 3 ft. deep, drains SSW.  |
| 68.20  | Power line, bears NNE and SSW.  |
| 80.00  | <p>The cor. of secs. 8, 9, 16, and 17.</p> <p>Land, rolling.<br/>Soil, sandy and rocky clay.<br/>No timber; sparse brush and native grasses.</p>  |
| 40.00  | <p>N. 0°03' W., bet. secs. 8 and 9.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 8 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E<br/>1/4<br/>S 8   S 9<br/>1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> |
| 80.00  | <p>Point for the cor. of secs. 4, 5, 8, and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E<br/>S 5   S 4<br/>—   —<br/>S 8   S 9<br/>1999</p>  |

Survey of the Subdivisional Lines,  
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS |  |
|--------|--|
|        | <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling.<br/>Soil, sandy and rocky clay.<br/>No timber; sparse brush and native grasses.</p> <hr/> <p>From the cor. of secs. 3, 4, 9, and 10.</p> <p>West, bet. secs. 4 and 9.</p> <p>Over rolling land.</p>             |
| 40.00  | <p>Point for the 1/4 sec. cor. of secs. 4 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E<br/>S 4<br/>1/4 —<br/>S 9<br/>1999</p>   |
| 80.00  | <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 4, 5, 8, and 9.</p> <p>Land, rolling.<br/>Soil, sandy and rocky clay.<br/>No timber; sparse brush and native grasses.</p> <hr/> <p>N. 0°03' W., bet. secs. 4 and 5.</p> <p>Over rolling and broken land.</p> |
| 40.00  | <p>Point for the 1/4 sec. cor. of secs. 4 and 5.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E<br/>1/4<br/>S 5   S 4<br/>1999</p>   |

Survey of the Subdivisional Lines,  
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS |  |
|--------|--|
|        | Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.  |
| 51.30  | Center of U. S. Highway 191, asphalt pavement, 25 ft. wide, bears ESE in curve to right.   |
| 80.00  | <p>The cor. of secs. 4, 5, 32, and 33, on the N. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling and broken.<br/>Soil, sandy and rocky clay.<br/>No timber; sparse brush and native grasses.</p>   |
|        | <p>From the cor. of secs. 5, 6, 31, and 32, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set, mkd. and witnessed as described in the field notes of the survey of the north boundary, T. 34 N., R. 26 E., executed concurrently under this same group.</p> <p>N. 0°03' W., bet. secs. 31 and 32.</p> <p>Over rolling land.</p> |
| 18.15  | Trail road, bears ENE and WSW.   |
| 40.00  | <p>Point for the 1/4 sec. cor. of secs. 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E<br/>1/4<br/>S31   S32<br/>1999</p>   |
| 51.85  | Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.  |
| 51.85  | Trail road, bears NE and SW.   |
| 77.40  | White Water Wash, 70 ft. wide, 2 ft. deep, drains WNW.   |
| 80.00  | <p>Point for the cor. of secs. 29, 30, 31, and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>   |

Survey of the Subdivisional Lines,  
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS |  |      |      |     |     |     |       |      |     |      |  |
|--------|--|------|------|-----|-----|-----|-------|------|-----|------|--|
|        | <table border="1" data-bbox="860 273 1015 430"> <tr> <td>T35N</td> <td>R26E</td> </tr> <tr> <td>S30</td> <td>S29</td> </tr> <tr> <td>S31</td> <td>S32</td> </tr> <tr> <td colspan="2">1999</td> </tr> </table> <p data-bbox="414 462 1421 535">Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p data-bbox="414 556 1144 661">Land, rolling.<br/>Soil, sandy and rocky clay.<br/>No timber; scattered brush and native grasses.</p> | T35N | R26E | S30 | S29 | S31 | S32   | 1999 |     |      |  |
| T35N   | R26E   |      |      |     |     |     |       |      |     |      |  |
| S30    | S29  |      |      |     |     |     |       |      |     |      |  |
| S31    | S32  |      |      |     |     |     |       |      |     |      |  |
| 1999   |  |      |      |     |     |     |       |      |     |      |  |
|        | <p data-bbox="414 714 1079 745">From the cor. of secs. 28, 29, 32, and 33.</p> <p data-bbox="414 777 844 808">West, bet. secs. 29 and 32.</p> <p data-bbox="414 840 698 871">Over rolling land.</p>  |      |      |     |     |     |       |      |     |      |  |
| 40.00  | <p data-bbox="414 903 1161 934">Point for the 1/4 sec. cor. of secs. 29 and 32.</p> <p data-bbox="414 966 1356 1029">Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>  |      |      |     |     |     |       |      |     |      |  |
|        | <table border="1" data-bbox="860 1060 1015 1228"> <tr> <td>T35N</td> <td>R26E</td> </tr> <tr> <td></td> <td>S29</td> </tr> <tr> <td></td> <td>1/4 —</td> </tr> <tr> <td></td> <td>S32</td> </tr> <tr> <td colspan="2">1999</td> </tr> </table> <p data-bbox="414 1249 1421 1312">Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>   | T35N | R26E |     | S29 |     | 1/4 — |      | S32 | 1999 |  |
| T35N   | R26E   |      |      |     |     |     |       |      |     |      |  |
|        | S29  |      |      |     |     |     |       |      |     |      |  |
|        | 1/4 —  |      |      |     |     |     |       |      |     |      |  |
|        | S32  |      |      |     |     |     |       |      |     |      |  |
| 1999   |  |      |      |     |     |     |       |      |     |      |  |
| 80.00  | <p data-bbox="414 1344 1006 1375">The cor. of secs. 29, 30, 31, and 32.</p> <p data-bbox="414 1407 1144 1512">Land, rolling.<br/>Soil, sandy and rocky clay.<br/>No timber; scattered brush and native grasses.</p>  |      |      |     |     |     |       |      |     |      |  |
|        | <p data-bbox="414 1564 844 1596">West, bet. secs. 30 and 31.</p> <p data-bbox="414 1627 1437 1659">Over gently rolling land across flood plain of White Water Wash.</p>  |      |      |     |     |     |       |      |     |      |  |
| 32.50  | <p data-bbox="414 1690 893 1722">Power line, bears NNE and SSW.</p>  |      |      |     |     |     |       |      |     |      |  |
| 40.00  | <p data-bbox="414 1753 1161 1785">Point for the 1/4 sec. cor. of secs. 30 and 31.</p>  |      |      |     |     |     |       |      |     |      |  |

Survey of the Subdivisional Lines,  
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS |  |
|--------|--|
|        | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E<br/>S30<br/>1/4 —<br/>S31<br/>1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>   |
| 71.80  | Chinle Wash, 200 ft. wide, 4 ft. deep, drains NNW.   |
| 78.84  | <p>The cor. of secs. 25, 30, 31, and 36, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set, mkd. and witnessed as described in the field notes of the survey of the east boundary, T. 35 N., R. 25 E., executed concurrently under this same group.</p> <p>Cor. is located in the flood plain of Chinle Wash, 2.40 chs. N. of left bank of Chinle Wash, 1 ft. high, bears NNE and SSW.</p> <p>Land, gently rolling.<br/>Soil, sand and sandy clay.<br/>Timber, Russian olive and saltcedar near Chinle Wash; undergrowth, scattered brush and native grasses.</p> |
| 40.00  | <p>From the cor. of secs. 29, 30, 31, and 32.</p> <p>N. 0°03' W., bet. secs. 29 and 30.</p> <p>Over gently rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 29 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E<br/>1/4<br/>S30   S29<br/>1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>   |
| 62.70  | Power line, bears NNE and SSW.   |

Survey of the Subdivisional Lines,  
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS    |   |           |  |     |     |       |     |      |  |      |  |
|-----------|---|-----------|--|-----|-----|-------|-----|------|--|------|--|
| 80.00     | <p>Point for the cor. of secs. 19, 20, 29, and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T35N R26E</td> </tr> <tr> <td style="text-align: center;">S19</td> <td style="text-align: center;">S20</td> </tr> <tr> <td style="text-align: center;">S30</td> <td style="text-align: center;">S29</td> </tr> <tr> <td colspan="2" style="text-align: center;">1999</td> </tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, gently rolling.<br/>Soil, sandy clay.<br/>No timber; scattered brush and native grasses.</p>                  | T35N R26E |  | S19 | S20 | S30   | S29 | 1999 |  |      |  |
| T35N R26E |   |           |  |     |     |       |     |      |  |      |  |
| S19       | S20   |           |  |     |     |       |     |      |  |      |  |
| S30       | S29   |           |  |     |     |       |     |      |  |      |  |
| 1999      |   |           |  |     |     |       |     |      |  |      |  |
| 40.00     | <p>From the cor. of secs. 20, 21, 28, and 29.</p> <p>West, bet. secs. 20 and 29.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 20 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T35N R26E</td> </tr> <tr> <td colspan="2" style="text-align: center;">S20</td> </tr> <tr> <td colspan="2" style="text-align: center;">1/4 —</td> </tr> <tr> <td colspan="2" style="text-align: center;">S29</td> </tr> <tr> <td colspan="2" style="text-align: center;">1999</td> </tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> | T35N R26E |  | S20 |     | 1/4 — |     | S29  |  | 1999 |  |
| T35N R26E |   |           |  |     |     |       |     |      |  |      |  |
| S20       |   |           |  |     |     |       |     |      |  |      |  |
| 1/4 —     |   |           |  |     |     |       |     |      |  |      |  |
| S29       |   |           |  |     |     |       |     |      |  |      |  |
| 1999      |   |           |  |     |     |       |     |      |  |      |  |
| 71.00     | <p>Power line, bears NNE and SSW.</p>   |           |  |     |     |       |     |      |  |      |  |
| 80.00     | <p>The cor. of secs. 19, 20, 29, and 30.</p> <p>Land, rolling.<br/>Soil, sandy and rocky clay.<br/>No timber; scattered brush and native grasses.</p>   |           |  |     |     |       |     |      |  |      |  |
|           | <p>West, bet. secs. 19 and 30.</p>  |           |  |     |     |       |     |      |  |      |  |

Survey of the Subdivisional Lines,  
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS |  |
|--------|--|
|        | Over gently rolling land.  |
| 24.35  | Trail road, bears SSE and NNW.   |
| 26.60  | White Water Wash, 30 ft. wide, 10 ft. deep, drains NNE.  |
| 40.00  | Point for the 1/4 sec. cor. of secs. 19 and 30.<br><br>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,<br>26 ins. in the ground, with brass cap mkd.<br><br>T35N R26E<br>S19<br>1/4 —<br>S30<br>1999<br><br>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case<br>beneath the stainless steel post.   |
| 68.40  | Chinle Wash, 430 ft. wide, 2 ft. deep, drains N.   |
| 75.60  | W. bank of flood plain of Chinle Wash, 8 ft. high, bears NE and SW.  |
| 78.76  | The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp.,<br>monumented with a stainless steel post, 2 1/2 ins. diam., with<br>brass cap, set and mkd. as described in the field notes of the<br>survey of the east boundary, T. 35 N., R. 25 E., executed<br>concurrently under this same group.<br><br>Cor. is located 2.70 chs. N. of W. bank of flood plain of Chinle<br>Wash, 10 ft. high, bears ENE and WSW; and 1.10 chs. E. and<br>1.20 chs. S. of a graded road, 20 ft. wide, bears NE and SW.<br><br>Land, gently rolling.<br>Soil, sand and sandy clay.<br>Timber, cottonwood, Russian olive and saltcedar near Chinle Wash;<br>undergrowth, scattered brush and native grasses. |
|        | From the cor. of secs. 19, 20, 29, and 30.<br><br>N. 0°03' W., bet. secs. 19 and 20.<br><br>Over gently rolling land.  |
| 40.00  | Point for the 1/4 sec. cor. of secs. 19 and 20.  |

Survey of the Subdivisional Lines,  
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS |  |
|--------|--|
|        | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E<br/>1/4<br/>S19   S20<br/>1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>   |
| 56.10  | Red Water Wash, 120 ft. wide, 4 ft. deep, drains SW.   |
| 80.00  | Point for the cor. of secs. 17, 18, 19, and 20.  |
|        | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E<br/>S18   S17<br/>-----<br/>S19   S20<br/>1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling.<br/>Soil, sandy clay.<br/>No timber; sparse brush and native grasses.</p> |
|        | <p>From the cor. of secs. 16, 17, 20, and 21.</p> <p>West, bet. secs. 17 and 20.</p> <p>Over gently rolling land.</p>  |
| 24.30  | Left bank of Red Water Wash, 3 ft. high, bears SSW in curve to right; thence along bed of Red Water Wash.  |
| 29.70  | Power line, bears NNE and SSW.   |
| 40.00  | Point for the 1/4 sec. cor. of secs. 17 and 20.  |
|        | <p>Set a magnet enclosed in a 1 x 1 x 2 ins. white plastic case, 24 ins. below the surface of the ground.</p>  |

Survey of the Subdivisional Lines,  
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS |   |
|--------|---|
|        | <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 30°00' E., 300.0 ft. dist., with brass cap mkd. T35N R26E 1/4 S20 RM 300.0 FT TO COR 1999 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 35°00' W., 200.0 ft. dist., with brass cap mkd. T36N R26E 1/4 S20 RM 200.0 FT TO COR 1999 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located on a low island in Red Water Wash, 1.60 chs. N. of left channel, 72 ft. wide, 2 ft. deep, drains WNW; and 90 lks. S. of right channel, 100 ft. wide, 2 ft. deep, drains WNW.</p> |
| 50.80  | Right bank of Red Water Wash, 2 ft. high, bears ENE and WSW; thence leave Red Water Wash.   |
| 80.00  | <p>The cor. of secs. 17, 18, 19, and 20.</p> <p>Land, gently rolling.<br/>Soil, sandy clay.<br/>No timber; sparse brush and native grasses.</p>   |
|        | <p>West, bet. secs. 18 and 19.</p> <p>Over rolling land.</p>  |
| 40.00  | <p>Point for the 1/4 sec. cor, of secs. 18 and 19.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E<br/>S18<br/>1/4 —<br/>S19<br/>1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>   |

Survey of the Subdivisional Lines,  
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS |   |
|--------|---|
| 78.67  | <p>The cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the east boundary, T. 35 N., R. 25 E., executed concurrently under this same group.</p> <p>Land, rolling.<br/>Soil, sandy and rocky clay.<br/>No timber; scattered brush and native grasses.</p>  |
|        | <p>From the cor. of secs. 17, 18, 19, and 20.<br/>N. 0°03' W., bet. secs. 17 and 18.<br/>Over rolling and broken land.</p>  |
| 40.00  | <p>Point for the 1/4 sec. cor. of secs. 17 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E<br/>1/4<br/>S18   S17<br/>1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>   |
| 80.00  | <p>Point for the cor. of secs. 7, 8, 17, and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E<br/>S 7   S 8<br/>-----<br/>S18   S17<br/>1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located near base of W. slope of Round Top Ridge.</p> |

Survey of the Subdivisional Lines,  
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS |   |
|--------|---|
|        | <p>Land, rolling and broken.<br/>Soil, sandy and rocky clay.<br/>No timber; sparse brush and native grasses.</p> <hr/> <p>From the cor. of secs. 8, 9, 16, and 17.</p> <p>West, bet. secs. 8 and 17.</p> <p>Over rolling land.</p>  |
| 35.40  | Base of E. slope of Round Top Ridge, bears NNE and SSW; thence over broken land on ascent.  |
| 40.00  | <p>Point for the 1/4 sec. cor. of secs. 8 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E<br/>S 8<br/>1/4 —<br/>S17<br/>1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located on steep E. slope of Round Top Ridge, bears N. and S.; thence over Round Top Ridge.</p> |
| 80.00  | <p>The cor. of secs. 7, 8, 17, and 18.</p> <p>Land, rolling and broken.<br/>Soil, sandy and rocky clay.<br/>No timber; sparse brush and native grasses.</p> <hr/> <p>West, bet. secs. 7 and 18.</p> <p>Over rolling land on descent into Chinle Valley.</p>   |
| 40.00  | <p>Point for the 1/4 sec. cor. of secs. 7 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>   |

Survey of the Subdivisional Lines,  
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS |   |
|--------|---|
|        | T35N R26E<br>S 7<br>1/4 —<br>S18<br>1999  |
|        | Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.   |
| 78.58  | The cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the east boundary, T. 35 N., R. 25 E., executed concurrently under this same group.<br><br>Land, rolling.<br>Soil, sandy and rocky clay.<br>Timber, cottonwood, Russian olive and saltcedar at west end; undergrowth, scattered brush and native grasses. |
|        | From the cor. of secs. 7, 8, 17, and 18.<br><br>N. 0°03' W., bet. secs. 7 and 8.<br><br>Over rolling and broken land over spur ridge of Round Top Ridge.  |
| 40.00  | Point for the 1/4 sec. cor. of secs. 7 and 8.<br><br>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to bedrock, supported in a mound of stone, 3 ft. base, to top, with brass cap mkd.  |
|        | T35N R26E<br>1/4<br>S 7   S 8<br>1999   |
|        | Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.   |
| 47.60  | Base of N. slope of spur ridge of Round Top Ridge, bears E. and W.; thence over rolling land.   |
| 80.00  | Point for the cor. of secs. 5, 6, 7, and 8.<br><br>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.   |

Survey of the Subdivisional Lines,  
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS    |  |           |  |     |     |       |  |     |     |      |  |
|-----------|--|-----------|--|-----|-----|-------|--|-----|-----|------|--|
|           | <div style="text-align: center;"> <table border="1"> <tr><td colspan="2">T35N R26E</td></tr> <tr><td>S 6</td><td>S 5</td></tr> <tr><td colspan="2">—</td></tr> <tr><td>S 7</td><td>S 8</td></tr> <tr><td colspan="2">1999</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling and broken.<br/>Soil, sandy and rocky clay.<br/>No timber; sparse brush and native grasses.</p>  | T35N R26E |  | S 6 | S 5 | —     |  | S 7 | S 8 | 1999 |  |
| T35N R26E |  |           |  |     |     |       |  |     |     |      |  |
| S 6       | S 5  |           |  |     |     |       |  |     |     |      |  |
| —         |  |           |  |     |     |       |  |     |     |      |  |
| S 7       | S 8  |           |  |     |     |       |  |     |     |      |  |
| 1999      |  |           |  |     |     |       |  |     |     |      |  |
| 40.00     | <p>From the cor. of secs. 4, 5, 8, and 9.</p> <p>West, bet. secs. 5 and 8.</p> <p>Over rolling and broken land over Round Top Ridge.</p> <p>Point for the 1/4 sec. cor. of secs. 5 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p>  |           |  |     |     |       |  |     |     |      |  |
| 80.00     | <div style="text-align: center;"> <table border="1"> <tr><td colspan="2">T35N R26E</td></tr> <tr><td colspan="2">S 5</td></tr> <tr><td colspan="2">1/4 —</td></tr> <tr><td colspan="2">S 8</td></tr> <tr><td colspan="2">1999</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 5, 6, 7, and 8.</p> <p>Land, rolling and broken.<br/>Soil, sandy and rocky clay.<br/>No timber; sparse brush and native grasses.</p> | T35N R26E |  | S 5 |     | 1/4 — |  | S 8 |     | 1999 |  |
| T35N R26E |  |           |  |     |     |       |  |     |     |      |  |
| S 5       |  |           |  |     |     |       |  |     |     |      |  |
| 1/4 —     |  |           |  |     |     |       |  |     |     |      |  |
| S 8       |  |           |  |     |     |       |  |     |     |      |  |
| 1999      |  |           |  |     |     |       |  |     |     |      |  |
| 40.00     | <p>West, bet. secs. 6 and 7.</p> <p>Over gently rolling land on descent into Chinle Valley.</p> <p>Point for the 1/4 sec. cor. of secs. 6 and 7.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>   |           |  |     |     |       |  |     |     |      |  |

Survey of the Subdivisional Lines,  
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS |  |
|--------|--|
|        | <p style="text-align: center;">T35N R26E<br/>S 6<br/>1/4 —<br/>S 7<br/>1999</p>  |
|        | <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>   |
| 58.00  | <p>Chinle Wash, 120 ft. wide, 5 ft. deep, drains NNE.</p>  |
| 78.49  | <p>The cor. of secs. 1, 6, 7, and 12, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the east boundary, T. 35 N., R. 25 E., executed concurrently under this same group.</p> |
|        | <p>Cor. is located in the flood plain of Chinle Wash, 65 lks. E. and 1.35 chs. S. of W. bank of flood plain, 6 ft. high, bears NNE and SSW.</p>  |
|        | <p>Land, gently rolling.<br/>Soil, sand and sandy clay.<br/>Timber, cottonwood, Russian olive and saltcedar near Chinle Wash; undergrowth, scattered brush and native grasses.</p>   |
|        | <p>From the cor. of secs. 5, 6, 7, and 8.</p>  |
|        | <p>N. 0°03' W., bet. secs. 5 and 6.</p>  |
|        | <p>Over gently rolling land.</p>   |
| 22.86  | <p>S. right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway.</p>  |
| 23.19  | <p>A brass tablet, 3 ins. diam., set flush in a concrete collar, 6 ins. diam., firmly set, projecting 6 ins. above ground, bears East, 81 lks. dist., with top mkd. ARIZONA HIGHWAY DEPT. 1961; with an angle iron to the E., with marks 113+86.43 HWY RW visible on a face.</p>                 |
| 24.91  | <p>Center of U. S. Highway 191, asphalt pavement, 28 ft. wide, bears ENE in curve to left.</p>   |
| 26.69  | <p>A brass tablet, 3 ins. diam., set flush in a concrete collar, 6 ins. diam., firmly set, projecting 6 ins. above ground, bears West, 61 1/2 lks. dist., with top mkd. ARIZONA HIGHWAY DEPT. 1961; with an angle iron to the E., with marks 113+86.43 visible on a face.</p>                    |

Survey of the Subdivisional Lines,  
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS |  |
|--------|--|
| 26.94  | N. right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway.   |
| 40.00  | Point for the 1/4 sec. cor. of secs. 5 and 6.<br><br>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.<br><br><div style="text-align: center;">           T35N R26E<br/>           1/4<br/>           S 6   S 5<br/>           1999         </div><br>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post. |
| 62.80  | Base of S. slope of a ridge, bears E. and W.; thence over broken land over ridge.  |
| 72.30  | Base of N. slope of a ridge, bears NE and SW; thence over rolling land.  |
| 80.00  | The cor. of secs. 5, 6, 31, and 32, on the N. bdy. of the Tp., hereinbefore described.<br><br>Land, rolling and broken.<br>Soil, sandy and rocky clay.<br>No timber; sparse brush and native grasses.  |

T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS | GENERAL DESCRIPTION   |
|--------|---|
|        | <p>The area surveyed is within the Navajo Indian Reservation, approximately six miles northeast of the community of Many Farms, Arizona and six miles southwest of the community of Round Rock. The extreme western portion of the township is in Chinle Valley. The central portion of the township is primarily clay badlands dominated by Round Top Ridge, which extends from section 4 southwesterly into section 17. Red Water Wash and White Water Wash drain westerly into Chinle Wash, which drains northerly along the west boundary of the township. Drainage in the northeastern portion of the township is northeasterly into Agua Sal Wash, which drains northerly through section 1.</p> <p>The elevation varies from 5200 to 5800 feet above sea level. The soil is mostly sandy and rocky clay. The only significant timber, which is cottonwood, Russian olive and saltcedar, is in the flood plains of Chinle Wash and Agua Sal Wash. The majority of the township is vegetated with sparse or scattered brush and native grasses.</p> <p>Principal access to the township is provided by U. S. Highway 191, which enters the township in section 6 and exits in section 2. There are three major graded roads and numerous trail roads providing additional access. Much of the area is used for grazing livestock. There is no mining activity in the township.</p> <p>The mean magnetic declination is 12 1/4° E., as derived from the United States Geological Survey computer program GEOMAGIX utilizing the Regional Magnetic Field Model for Epoch 1995 for the dates of survey.</p> |

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

## FIELD ASSISTANTS

| NAMES            | CAPACITY               |
|------------------|------------------------|
| William F. Olver | Cadastral Surveyor     |
| Daniel Bryan     | Engineering Technician |
| Wilfred Chee     | Engineering Technician |
| Edward Clarke    | Engineering Technician |
| Reuben Mason     | Engineering Technician |
| Barney Woodie    | Engineering Technician |
|                  |                        |
|                  |                        |
|                  |                        |
|                  |                        |
|                  |                        |
|                  |                        |
|                  |                        |
|                  |                        |
|                  |                        |

## CERTIFICATE OF SURVEY

I, Jones Curtiss, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 17th day of February 1998, I have surveyed the east and north boundaries, and the subdivisional lines, Township 35 North, Range 26 East, of the Gila and Salt River Meridian, in the state of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said Special Instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and in specific manner described in the foregoing field notes.

January 31, 2001  
(Date)

Jones Curtiss  
(Cadastral Surveyor)

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Arizona State Office  
Phoenix, Arizona

The foregoing field notes of the survey of the east and north boundaries, and the subdivisional lines, Township 35 North, Range 26 East, Gila and Salt River Meridian, Arizona, executed by Jones Curtiss, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

February 20, 2001  
(Date)

Lenny D. Rawmka  
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~\_\_\_\_\_~~  
~~(Date)~~

~~\_\_\_\_\_~~  
~~(Chief Cadastral Surveyor of Arizona)~~