

ORIGINAL

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

**FIELD NOTES  
OF THE  
DEPENDENT RESURVEY  
OF A PORTION OF THE NORTH BOUNDARY  
AND A PORTION OF THE SUBDIVISIONAL LINES  
AND  
THE SUBDIVISION OF SECTIONS 3 AND 9,  
TOWNSHIP 23 SOUTH, RANGE 20 EAST,  
OF THE GILA AND SALT RIVER MERIDIAN,  
IN THE STATE OF ARIZONA.**

**EXECUTED BY**

Gordon R. Bubel, Cadastral Surveyor

Under Special Instructions dated July 31, 2000, approved July 31, 2000,  
which provided for the surveys included under Group No. 854, and  
assignment instructions dated July 31, 2000.

Survey commenced August 8, 2000

Survey completed September 21, 2000

# INDEX DIAGRAM

TOWNSHIP 23 SOUTH      RANGE 20 EAST

2

6	5	4 16	13 3 10	4 2	1
7	8	15 9 13	7 10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Subdivision of Section 3 ..... Pages 17-26  
 Subdivision of Section 9. .... Pages 26-31

## T. 23 S., R. 20 E., Gila and Salt River Meridian, Arizona

## CHAINS

The following field notes describe the dependent resurvey of a portion of the north boundary and a portion of the subdivisional lines and the subdivision of sections 3 and 9, Township 23 South, Range 20 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this resurvey is as follows:

Portions of the north and east boundaries and a portion of the subdivisional lines were surveyed by Philip Contzen in 1901. In 1906 Philip Contzen surveyed the south boundary, portions of the north and east boundaries, and a portion of the subdivisional lines.

In 1901, Contzen surveyed the E.  $\frac{1}{2}$  of the N. bdy. of sec. 3 and the line bet. secs. 2 and 3, thus allowing for entry in the NE $\frac{1}{4}$  of sec. 3. In 1904 a patent was issued for the SE $\frac{1}{4}$  of the NE $\frac{1}{4}$  of sec. 3. In 1906 the remainder of sec. 3 was surveyed and lots 1 and 2 in the NW quarter of the sec. were created. To protect the 1904 patent the center 1/4 sec. cor. of sec. 3 was established by intersecting a line from the 1/4 sec. cor. of secs. 3 and 34, parallel with the N.  $\frac{1}{2}$  of the line bet. secs. 2 and 3, with a line from the 1/4 sec. cor. of secs. 2 and 3 parallel with the E.  $\frac{1}{2}$  of the line bet. secs. 3 and 34.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated July 31, 2000, for Group No. 854, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation 4400 model receivers.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from first order U. S. Coast and Geodetic Survey triangulation station HEREFORD 1938, as published by the National Geodetic Survey, NAD 83 (1992). The geographic position of the cor. of secs. 2, 3, 10 and 11, is as follows:

Latitude: 31° 27' 10.33" N.      Longitude: 110° 17' 28.53" W.

The mean magnetic declination is 11 $\frac{1}{2}$ ° E.

Dependent Resurvey of a Portion of the North Boundary,  
T. 23 S., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Restoring the survey executed by Philip Contzen, in 1901</p>
	<p>Beginning at the cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., reestablished by proportionate distance by Raymond T. Jones, Arizona Registered Land Surveyor No. 5713, in 1964, and remonumented by Tallak Daniel Maakestad, Arizona Registered Land Surveyor No. 13012, in 1984, monumented with an iron rod, 5/8 in. diam., firmly set in a concrete cylinder, 6 1/4 ins. diam., projecting 6 ins. above ground, with aluminum cap, 3 1/4 ins. diam., mkd. CLEAVE-LUNDGREN &amp; ASSOC. PROPERTY BOUNDARY BARACHAS RANCH 34 35 3 2 1984 RLS 13012. This is accepted as a careful and faithful reestablishment of the position of the original corner.</p>
	<p>Not remonumented.</p>
	<p>Cor. is located 10 lks. W. of the west edge of pavement of Calle Matate, 38 lks. wide, bears N. and S., curving easterly.</p>
	<p>From this cor. point, the cor. of secs. 1, 2, 35 and 36, bears East, 80.14 chs. dist., perpetuated by person(s) unknown, monumented with a brass cap, 2 ins. diam., set flush in concrete, on the N. edge of Ramsey Canyon Road, bears E. and W., and at the intersection of Stafford Lane, bears S., with brass cap mkd. PL 789 35 36 2 1 ASA 1664 SEC COR.</p>
	<p>from which the remains of the original bearing tree.</p>
	<p>A mesquite stump cluster, 30 ins. diam., with partially rotted evidence of four major trunks, 5 ins. diam., bears S. 26 1/2° W., 337 lks. dist., no marks remaining. (Record, S. 26° W., 324 lks. dist.)</p>
	<p>N. 89°59' W., bet. secs. 3 and 34.</p>
	<p>Over gently rolling land, through native grasses and scattered oak and mesquite timber.</p>
0.14	<p>Four strand barbed wire fence, bears N. and S.</p>
20.03	<p>The E. 1/16 sec. cor. of secs. 3 and 34, established by Tallak Daniel Maakestad, Arizona Registered Land Surveyor No. 13012, in 1984, monumented with an iron rod, 5/8 in. diam., firmly set in a concrete cylinder, 6 1/4 ins. diam., projecting 1 in. above ground, with aluminum cap, 3 1/4 ins. diam., mkd. CLEAVE-LUNDGREN &amp; ASSOC PROPERTY BOUNDARY BARACHAS RANCH E 1/16 S34 S3 1984 RLS 13012. This is accepted as a careful and faithful determination of the position of the corner.</p>
	<p>Not remonumented</p>

Dependent Resurvey of a Portion of the North Boundary,  
T. 23 S., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
20.03	<p>Cor. is located at the cor. of fences, with four strand barbed wire fences extending N. and E.</p> <hr/> <p>N. 89°59' W., beginning new measurement.</p> <p>The 1/4 sec. cor. of secs. 3 and 34, monumented with an X chiseled on the top N. side of a granite boulder, 3 X 2 X 3 ft. high, with a mound of stone, 3 ft. base, 3 ft. high to the N.</p> <p>from which the remaining original bearing tree</p> <p style="padding-left: 40px;">A stump hole, bears N. 43¼° W., 88 lks. dist., with a rotted oak, 17 ins. diam., lying loose alongside, no marks visible.</p> <p>At the cor. point</p> <p>Set a brass tablet, 3¼ ins. diam., 3¼ ins. stem, in a drill hole cemented in place, flush with the face of granite boulder, with brass tablet mkd.</p> <div style="text-align: center;"> <p>T22S R20E S34 1/4 ——— S3 T23S 2000</p> </div> <p>Deposit a magnet at the bottom of the drill hole.</p> <p>From this cor. point, an X chiseled in the same granite boulder, bears N. 51°09' W., 1.0 lk. dist., established by Tallak Daniel Maakestad, Arizona Registered Land Surveyor No. 13012 in 1984.</p> <hr/> <p style="text-align: center;">Restoring the survey executed by Philip Contzen, in 1906</p> <hr/> <p>S. 89°48' W., beginning new measurement.</p> <p>Over rolling and mountainous land, through native grasses and scattered oak and mesquite timber.</p>
39.72	<p>The cor. of secs. 3, 4, 33 and 34, monumented with a limestone, 18 x 9 x 6 ins., loosely set, projecting 4 ins. above ground, mkd. with 3 notches on the E. and 3 notches on the W. edges, with a scattered mound of stone to the W.</p> <p>from which the remaining original bearing tree</p>

**Dependent Resurvey of a Portion of the North Boundary,  
T. 23 S., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS

An oak, 18 ins. diam., bears N.  $61\frac{1}{4}^{\circ}$  W., 170 lks. dist.,  
with healed blaze.

At the cor. point

Set a stainless steel post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 13 ins.  
in the ground, in a mound of stone, 3 ft. base, to top, with  
brass cap mkd.

T22S R20E	
S33	S34
S 4	S 3
T23S	
2000	

Deposit a magnet in a white plastic case at the base of the  
stainless steel post.

Rebuild the scattered mound of stone, 3 ft. base, 1 ft. high, W.  
of cor.

From this cor. point, the center of an abandoned mine shaft  
8 x 8 x 20 ft. deep, bears S.  $13^{\circ}44'$  W., 104 lks. dist.

---

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 20 E., Gila and Salt River Meridian, Arizona**

---

Restoring the survey executed by  
Philip Contzen, in 1901

---

From the cor. of secs. 2, 3, 10 and 11, perpetuated by Kevin P.  
Gilbert, Arizona Registered Land Surveyor No. 14181, in 1990,  
monumented with an aluminum post,  $2\frac{1}{2}$  ins. diam., firmly set,  
projecting 12 ins. above ground, in a mound of stone, 3 ft. base  
to top, with aluminum cap,  $3\frac{1}{4}$  ins. diam., mkd. U.S. DEPT. OF  
AGRICULTURE T23S R20E S3 S2 S10 S11 LS 14181 1990 CADASTRAL  
SURVEY FOREST SERVICE. This is accepted as a careful and  
faithful perpetuation of the original corner position.

from which bearing trees marked by Gilbert

An oak, 8 ins. diam., bears N.  $65\frac{1}{2}^{\circ}$  E., 40 lks. dist.,  
with illegible scribe marks visible on partially opened  
blaze.

An oak, 12 ins. diam., bears S.  $80\frac{1}{4}^{\circ}$  E., 43 lks. dist.,  
with no marks visible on partially healed blaze.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS

An oak, 9 ins. diam., bears S.  $49\frac{1}{2}^{\circ}$  W., 52 lks. dist., with illegible scribe marks visible on partially opened blaze.

An alligator juniper, 7 ins. diam., bears N.  $41^{\circ}$  W., 19 lks. dist., with scribe marks BT4 visible on partially opened blaze.

Not remonumented.

Cor. is located at the intersection of 4 strand barbed wire fences, bearing N. and E.

From this cor. point, U. S. Coast and Geodetic Survey triangulation station HEREFORD 1938, bears N.  $87^{\circ}39'$  E., 655.51 chs. dist., monumented with a standard brass disk,  $3\frac{1}{2}$  ins. diam., cemented in a concrete post, 12 ins. square, firmly set, projecting 6 ins. above ground, with top mkd. HEREFORD ASA 262 1938 and a triangle.

N.  $0^{\circ}30'$  W., bet. secs. 2 and 3.

Over rolling and mountainous land.

19.735

The S.  $1/16$  sec. cor. of secs. 2 and 3, established by Michael R. Pine, Arizona Registered Land Surveyor No. 28737, in 1998, monumented with a rebar, 18 ins. long,  $5/8$  in. diam., firmly set, projecting 3 ins. above ground, with aluminum cap, 2 ins. diam., mkd. G.P.S. LAND SURVEY S  $1/16$  S3 S2 1998 R.L.S. 28737. This is accepted as a careful and faithful determination of the position of the cor.

At the corner point

Set a stainless steel post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 25 ins. in the ground, in a collar of stone, with brass cap mkd.

T23S R20E  
S  $1/16$   
S3 | S2  
2000

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Deposit the rebar inside the stainless steel post.

Cor. located 2 lks. N. of a fence cor., with 4 strand barbed wire fences bearing S. and WSW for 47 lks., thence N. and S.

---

N.  $0^{\circ}30'$  W., beginning new measurement.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
19.735	<p>The 1/4 sec. cor. of secs. 2 and 3, perpetuated by Raymond L. Jones, Arizona Registered Land Surveyor No. 5713, in 1964, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 5 ins. above ground, with attached lead cap mkd. 1/4 3 2. This is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <p>Not remonumented.</p> <p>Cor. is located in a four strand barbed wire fence, bears E. and W.</p> <p>The original granite stone, 14 x 11 x 9 ins., mkd. 1/4 3 on a face and 2 on the opposite face was found lying loose nearby.</p>
	<p>N. 0°05' E., beginning new measurement.</p>
19.62	<p>Southerly edge of pavement, Ramsey Canyon road, 27 lks. wide, bears NE and SW.</p>
20.03	<p>Point for the N. 1/16 sec. cor. of secs. 2 and 3.</p>
	<p>Set a railroad spike, 6½ ins. long, 1½ ins. wide, flush with the pavement of Ramsey Canyon Road.</p>
	<p>from which</p>
	<p>A stainless steel post, 28 ins. long, 2½ ins. diam., set</p>
	<p>24 ins. in the ground for a reference monument, bears</p>
	<p>N. 89°49' W., 55.9 ft. dist., with brass cap mkd. RM T23S</p>
	<p>R20E N1/16 55.9 FT TO COR S3 2000 and an arrow pointing</p>
	<p>to the corner.</p>
	<p>A stainless steel post, 28 ins. long, 2½ ins. diam., set</p>
	<p>21 ins. in the ground for a reference monument, bears</p>
	<p>N. 13°56' W., 41.6 ft. dist., with brass cap mkd. RM T23S</p>
	<p>R20E N1/16 41.6 FT TO COR S3 2000 and an arrow pointing</p>
	<p>to the corner.</p>
	<p>From this cor. point, a rebar, ½ in. diam., firmly set, 2 ins.</p>
	<p>below the pavement of Ramsey Canyon Road, bears S. 2°02' E.,</p>
	<p>3.5 lks. dist., established by Raymond T. Jones, Arizona</p>
	<p>Registered Land Surveyor No. 5713 in 1964, marking the SW cor.</p>
	<p>of the INDIADA platted subdivision.</p>
	<p>From this same cor. point, an open end iron pipe, firmly set,</p>
	<p>flush with the northerly edge of pavement of Ramsey Canyon Road,</p>
	<p>bears S. 70°19' W., 12.5 lks. dist., origin unknown.</p>
20.13	<p>Northerly edge of pavement, Ramsey Canyon Road, 27 lks. wide,</p>
	<p>bears NE and SW.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS	
20.65	Woven wire fence, 4½ ft. high, bears N. 46¾° E. and S. 46¾° W., for 16 lks., thence N. 0°22' E.
24.39	Woven wire fence, 4½ ft. high, bears N. 58½° E and S. 58½° W., for 11 lks., thence N. 2°11' E. and S. 0°22' W.
26.93	Woven wire fence, 4½ ft. high, bears N. 2°11' E. and S. 2°11' W.
27.34	Cor. of woven wire fences, bears E., 1.5 lks dist., with fences extending N. 0°51' E., N. 46°06' E. and S. 2°11' W.
29.50	Cor. of woven wire fences, bears E., 4.5 lks dist., with fences extending N. 83°48' E., and S. 0°51' W.
40.06	The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp.
<hr/> <p>Restoring the survey executed by Philip Contzen, in 1906</p> <hr/>	
<p>From the cor. of secs. 9, 10, 15 and 16, perpetuated by Kevin P. Gilbert, Arizona Registered Land Surveyor No. 14181, in 1990, monumented with an aluminum post, 2¼ ins. diam., firmly set, projecting 6 ins. above ground, in a mound of stone, 2½ ft. base, to top, with an aluminum cap, 3¼ in. diam., mkd. U.S. DEPT. OF AGRICULTURE T23S R20E S9 S10 S16 S15 LS14181 1990 CADASTRAL SURVEY FOREST SERVICE. This is accepted as a careful and faithful perpetuation of the original cor. position.</p>	
<p>from which the remaining original bearing tree</p>	
<p style="padding-left: 40px;">An oak snag, 13 ins. diam., bears N. 5° W., 87 lks. dist., with a rotted out blaze.</p>	
<p>and bearing trees marked by Gilbert</p>	
<p style="padding-left: 40px;">A pine, 10 ins. diam., bears N. 64° E., 14 lks. dist., with illegible scribe marks visible on partially opened blaze.</p>	
<p style="padding-left: 40px;">A pine, 7 ins. diam., bears S. 26° E., 20 lks. dist., with scribe marks BT2 visible on partially opened blaze.</p>	
<p style="padding-left: 40px;">A pine, 12 ins. diam., bears S. 61° W., 20.5 lks. dist., with illegible scribe marks visible on partially opened blaze.</p>	
<p style="padding-left: 40px;">A pine, 10 ins. diam., bears N. 4° W., 4 lks. dist., with scribe marks BT4 visible on partially opened blaze.</p>	

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>The original syenite stone, 16 x 8 x 7 ins., with 3 notches on an edge and 4 notches on the opposite edge was found within the mound of stone.</p> <p>Not remonumented.</p> <p>N. 0°05' W., bet. secs. 9 and 10.</p> <p>Over mountainous land, descending through pine timber.</p>
19.79	<p>The S. 1/16 sec. cor. of secs. 9 and 10, established by Kevin P. Gilbert, Arizona Registered Land Surveyor No. 14181, in 1990, monumented with an aluminum rod, 3/4 in. diam., firmly set, projecting 16 ins. above ground, in a mound of stone, 2 1/2 ft. base, 1 ft. high, with aluminum cap, 3 1/4 ins. diam., mkd. U.S. DEPT. OF AGRICULTURE S 1/16 LS 14181 1990 CADASTRAL SURVEY FOREST SERVICE. This is accepted as a careful and faithful determination of the cor. position.</p> <p>from which bearing trees marked by Gilbert</p> <p style="padding-left: 40px;">A pine, 8 ins. diam., bears S. 29° W., 28 lks. dist., with illegible scribe marks visible on partially opened blaze.</p> <p style="padding-left: 40px;">An oak, 6 ins. diam., bears N. 79° W., 16 lks. dist., with scribe marks BT2 visible on partially opened blaze.</p> <p>Not remonumented.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°05' W., beginning new measurement.</p>
19.79	<p>The 1/4 sec. cor. of secs. 9 and 10, perpetuated by Kevin P. Gilbert, Arizona Registered Land Surveyor No. 14181, in 1990, monumented with an aluminum post, 2 1/4 ins. diam., firmly set, projecting 12 ins. above ground, in a mound of stone, 3 ft. base, 1 ft. high, with aluminum cap, 3 1/4 ins. diam., mkd. U.S. DEPT. OF AGRICULTURE S9 S10 1/4 LS14181 1990 CADASTRAL SURVEY FOREST SERVICE. This is accepted as a careful and faithful perpetuation of the original cor. position.</p> <p>from which the remaining original bearing tree</p> <p style="padding-left: 40px;">An oak, 15 ins. diam., bears S. 31 1/4° E., 92 lks. dist., with healed blaze.</p> <p>and bearing tree marked by Gilbert</p> <p style="padding-left: 40px;">A pine, 14 ins. diam., bears S. 56° W., 64 lks. dist., with healed blaze.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
19.995	<p>Cor. is located in a dilapidated 4 strand barbed wire fence, bears irregularly N. and S.</p> <p>Not remonumented.</p> <hr/> <p>N. 0°04' W., beginning new measurement.</p> <p>Descending through oak timber.</p> <p>The N. 1/16 sec. cor. of secs. 9 and 10, established by Kevin P. Gilbert, Arizona Registered Land Surveyor No. 14181, in 1990, monumented with an aluminum rod, 30 ins. long, <math>\frac{3}{4}</math> in. diam., firmly set, projecting 1 in. above ground, encircled with a collar of stone, with aluminum cap mkd. U.S. DEPT. OF AGRICULTURE N 1/16 LS 14181 1990 CADASTRAL SURVEY FOREST SERVICE. This is accepted as a careful and faithful determination of the cor. position.</p> <p>from which bearing trees marked by Gilbert</p> <p style="padding-left: 40px;">An oak, 7 ins. diam., bears N. 25° E., 24 lks. dist., with healed over blaze.</p> <p style="padding-left: 40px;">An oak, 6 ins. diam., bears S. 78° E., 43 lks. dist., with scribe marks BT2 visible on partially opened blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T23S R20E N 1/16 S 9   S10 2000</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Invert and deposit the aluminum rod inside the stainless steel post.</p> <p>Cor. is located in a three strand barbed wire fence, bears S. and N. for 15 lks., to cor. of fences, bearing N., E. and SE.</p> <p>From this cor. point, a rebar, <math>\frac{1}{2}</math> in. diam., firmly set, projecting, 3 ins. above ground, with 1 in. diam. yellow plastic cap, mkd. LS 14181, bears N. 89°23' E., 48.5 lks. dist.</p> <hr/> <p>N. 0°04' W., beginning new measurement.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
19.995	<p>Ascending through dense oak brush.</p> <p>The cor. of secs. 3, 4, 9 and 10, perpetuated by Kevin P. Gilbert, Arizona Registered Land Surveyor No. 14181, in 1990, monumented with an aluminum post, 2½ ins. diam., firmly set, projecting 8 ins. above ground, in the remains of the original mound of stone, 3 ft. base, to top, with aluminum cap mkd. U.S. DEPT. OF AGRICULTURE T23S R20E S4 S3 S9 S10 LS14181 1990 CADASTRAL SURVEY FOREST SERVICE. This is accepted as a careful and faithful perpetuation of the original cor. position.</p> <p>from which bearing trees marked by Gilbert</p> <p>An oak, 7 ins. diam., bears N. 34° E., 21 lks. dist., with illegible scribe marks visible on partially opened blaze.</p> <p>An oak, 12 ins. diam., bears S. 19° E., 52 lks. dist., with scribe marks BT visible on partially opened blaze.</p> <p>An oak, 9 ins. diam., bears S. 33° W., 39 lks. dist., with scribe mark T visible on partially opened blaze.</p> <p>A forked oak, 36 ins. diam., at base, bears N. 48° W., 36 lks. dist., with healed over blaze, on an 8 ins. diam. limb.</p> <p>Not remonumented.</p>
20.03	<hr/> <p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>S. 89°51' W., bet. sec. 3 and 10.</p> <p>Descending through oak and manzanita brush.</p> <p>The E. 1/16 sec. cor. of secs. 3 and 10, established by Kevin P. Gilbert, Arizona Registered Land Surveyor No. 14181, in 1990, monumented with an aluminum rod, ¾ in. diam., firmly set, projecting 7 ins. above ground, in a mound of stone, 3 ft. base, to top, with aluminum cap mkd. U.S. DEPT. OF AGRICULTURE E 1/16 S3 S10 LS14181 1990 CADASTRAL SURVEY FOREST SERVICE. This is accepted as a careful and faithful determination of the cor. position.</p> <p>from which bearing trees marked by Gilbert</p> <p>An oak, 9 ins. diam., bears N. 28° E., 78.5 lks. dist., with healed blaze.</p> <p>An oak, 8 ins. diam., bears S. 60° E., 46 lks. dist., with illegible scribe marks visible on partially opened blaze.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Cor. is located at the intersection of four strand barbed wire fences, bearing N. and W.</p> <p>An open end iron pipe, 18 ins. long, 1 in. diam., was found lying loose nearby, unknown origin.</p> <p>Not remonumented.</p> <hr/> <p>S. 89°51' W., beginning new measurement.</p> <p>Along four strand barbed wire fence.</p>
20.03	<p>The 1/4 sec. cor. of secs. 3 and 10, perpetuated by Kevin P. Gilbert, Arizona Registered Land Surveyor No. 14181, in 1990, monumented with an aluminum post, 2½ ins. diam., firmly set, projecting 12 ins. above ground, in a mound of stone, 3 ft. base, 1 ft. high, with aluminum cap mkd. U.S. DEPT. OF AGRICULTURE S3 1/4 S10 LS14181 1990 CADASTRAL SURVEY FOREST SERVICE. This is accepted as a careful and faithful perpetuation of the original cor. position.</p> <p>from which an original bearing tree</p> <p style="padding-left: 40px;">A dead oak, 9 ins. diam., bears S. 21½° E., 19 lks. dist., with a rotted blaze.</p> <p>and bearing trees marked by Gilbert</p> <p style="padding-left: 40px;">An alligator juniper, 15 ins. diam., bears N. 88° E., 66 lks. dist., with scribe marks BT1 visible on partially opened blaze.</p> <p style="padding-left: 40px;">An alligator juniper, 7 ins. diam., bears S. 53° W., 27 lks. dist., with scribe marks BT2 visible on partially opened blaze.</p> <p>Not remonumented.</p> <hr/> <p>S. 89°54' W., beginning new measurement.</p>
18.20	<p>Center of pavement, Ramsey Canyon road, 27 lks. wide, bears NNE and SSW.</p>
19.98	<p>Point for the W. 1/16 sec. cor. of secs. 3 and 10.</p> <p>Not monumented.</p>
27.00	<p>A rebar, ½ in. diam., firmly set, projecting 2 ins. above ground, with 1 in. diam. yellow plastic cap mkd. LS 4181.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
29.97	<p>The W-W 1/64 sec. cor. of secs. 3 and 10, established by Kevin P. Gilbert, Arizona Registered Land Surveyor No. 14181, in 1990, monumented with an aluminum rod, <math>\frac{3}{4}</math> in. diam., firmly set, projecting 1 in. above ground, encircled with a collar of stone, with aluminum cap mkd. U.S. DEPT. OF AGRICULTURE WW LS 14181 1/64 1990 CADASTRAL SURVEY FOREST SERVICE. This is accepted as a careful and faithful determination of the cor. position.</p> <p>from which bearing trees marked by Gilbert</p> <p>An oak, 8 ins. diam., bears N. 77° E., 36.5 lks. dist., with illegible scribe marks visible on partially healed blaze.</p> <p>An oak, 10 ins. diam., bears N. 70° W., 35 lks. dist., with scribe mark B visible on partially healed blaze.</p> <p>Cor. is located 12 lks. N. of a 4 strand barbed wire fence, bears irregularly E. and W.</p> <p>Not remonumented.</p> <hr/> <p>S. 89°54' W., beginning new measurement.</p>
4.995	<p>The W-W-W 1/256 sec. cor. of secs. 3 and 10, established by Kevin P. Gilbert, Arizona Registered Land Surveyor No. 14181, in 1990, monumented with an aluminum rod, <math>\frac{3}{4}</math> in. diam., firmly set, projecting 7 ins. above ground, in a mound of stone, 4 ft. base, to top, with aluminum cap mkd. U.S. DEPT. OF AGRICULTURE WWW 1/256 LS 14181 1990 CADASTRAL SURVEY FOREST SERVICE. This is accepted as a careful and faithful determination of the cor. position.</p> <p>from which bearing trees marked by Gilbert</p> <p>An oak, 9 ins. diam., bears N. 76° E., 39 lks. dist., with illegible scribe marks visible on partially healed blaze.</p> <p>An oak, 9 ins. diam., bears N. 77° W., 29 lks. dist., with illegible scribe marks visible on partially healed blaze.</p> <p>Cor. is located 1.5 lks. N. of a four strand barbed wire fence, bears irregularly E. and W. for 4 lks., thence irregularly S.</p> <p>Not remonumented.</p> <hr/> <p>S. 89°54' W., beginning new measurement.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
4.995	The cor. of secs. 3, 4, 9 and 10.
	<hr/>
	N. 0°02' W., bet. secs. 3 and 4.
	Over mountainous land.
19.89	Point for the S. 1/16 sec. cor. of secs. 3 and 4.
	Not monumented.
39.78	The 1/4 sec. cor. of secs. 3 and 4, monumented with a quartz
	stone, 14 X 13 X 6 ins., firmly set, projecting 6 ins. above
	ground, mkd. 1/4 on the W. face, with a mound of stone, 3 ft.
	base, 2 ft. high to the W.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins.
	in the ground, with brass cap mkd.
	<div style="text-align: center;">           T23S R20E            1/4            S 4   S 3            2000         </div>
	Deposit a magnet in a white plastic case at the base of the
	stainless steel post.
	Bury the original stone alongside the stainless steel post.
	<hr/>
	N. 0°04' W., beginning new measurement.
39.80	The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp.
	<hr/>
	From the cor. of secs. 9, 10, 15 and 16.
	N. 89°29' W., bet. secs. 9 and 16.
	Over mountainous land, through dense pine, oak and fir timber.
39.76	The 1/4 sec. cor. of secs. 9 and 16, monumented with a granite
	stone, 19 X 12 X 7 ins., firmly set, projecting 13 ins. above
	ground, mkd. 1/4 on the N. face.
	from which
	<div style="text-align: center;">           An oak, 13 ins. diam., bears N. 30¼° W., 17 lks. dist.,            with healed blaze.         </div>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
	At the cor. point
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins.
	in the ground, in a mound of stone, 2 ft. base, to top, with
	brass cap mkd.
	<div style="text-align: center;">           T23S R20E            S 9            1/4 ———            S16            2000         </div>
	Deposit a magnet in a white plastic case at the base of the
	stainless steel post.
	Bury the original stone alongside the stainless steel post.
	Cor. is located 45 lks. S. of the center of the abandoned road
	to the Hamburg Mine, 22 lks. wide, bears ENE and WSW.
	N. 89°31' W., beginning new measurement.
19.83	Point for the W. 1/16 sec. cor. of secs. 9 and 16.
	Not monumented.
39.66	The cor. of secs. 8, 9, 16 and 17, monumented with an X chiseled
	in a granite slab, with four grooves E. of the X and four
	grooves S. of the X.
	from which the remaining original bearing trees
	A rotted pine stump, 18 ins. diam., bears N. 54½° E.,
	71 lks. dist., with healed blaze. (Record species:
	balsam)
	A pine snag, 14 ins. diam., bears S. 89¼° E., 64 lks.
	dist., with scribe marks T23S R20E S16 BT visible on
	partially opened blaze. (Record species: balsam)
	A rotted fir stump, 23 ins. diam., bears N. 6½° W., 88 lks.
	dist., with scribe marks 3 T S8 BT visible on partially
	opened blaze.
	At the cor. point
	Set a brass tablet, 3½ ins. diam., 3½ ins. stem, in a drill
	hole, cemented in place, flush with the face of granite slab,
	with brass tablet mkd.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T23S R20E</td></tr> <tr><td>S 8</td><td>S 9</td></tr> <tr><td colspan="2" style="text-align: center;"> </td></tr> <tr><td>S17</td><td>S16</td></tr> <tr><td colspan="2" style="text-align: center;">2000</td></tr> </table>	T23S R20E		S 8	S 9			S17	S16	2000	
T23S R20E											
S 8	S 9										
S17	S16										
2000											
	<hr/>										
	<p>N. 0°15' W., bet. secs. 8 and 9.</p>										
	<p>Over mountainous land, through dense pine, oak and fir timber.</p>										
19.67	<p>Point for the S. 1/16 sec. cor. of secs. 8 and 9.</p>										
	<p>Not monumented.</p>										
39.34	<p>Point for the 1/4 sec. cor. of secs. 8 and 9, at proportionate dist.; there is no remaining evidence of the original cor.</p>										
	<p>Set a brass tablet, 3½ ins. diam., 3½ ins. stem, in a drill hole, cemented in place, flush with the face of limestone slab, 24 x 8 ins., with brass tablet mkd.</p>										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T23S R20E</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td>S 8</td><td>S 9</td></tr> <tr><td colspan="2" style="text-align: center;"> </td></tr> <tr><td colspan="2" style="text-align: center;">2000</td></tr> </table>	T23S R20E		1/4		S 8	S 9			2000	
T23S R20E											
1/4											
S 8	S 9										
2000											
	<p>from which</p>										
	<p style="padding-left: 40px;">A limestone outcropping, 16 X 16 ins., bears N. 38° E., 8 lks. dist., mkd. X.</p>										
	<p style="padding-left: 40px;">A 60 D spike, driven in the W. side of an 8 in. diam. oak, bears N. 15° W., 14 lks. dist.</p>										
	<p>Cor. is located on steep E. facing slope.</p>										
59.01	<p>Point for the N. 1/16 sec. cor. of secs. 8 and 9.</p>										
	<p>Not monumented.</p>										
78.68	<p>The cor. of secs. 4, 5, 8 and 9, perpetuated by Wallace L. Craig, Arizona Registered Land Surveyor No. 20354, in 2000, monumented with an aluminum post, 2½ ins. diam., firmly set, projecting 16 ins. above ground, in a mound of stone, 3 ft. base, 1 ft. high, with a mound of stone, 4 ft. base, 2 ft. high to the W., with aluminum cap mkd. U.S. DEPT. OF AGRICULTURE T23S R20E S5 S4 S8 S9 LS20354 2000 CADASTRAL SURVEY FOREST SERVICE. This is accepted as a careful and faithful perpetuation of the original cor. position.</p>										
	<p>from which the remaining original bearing trees</p>										

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>An oak, 12 ins. diam., bears N. <math>78\frac{1}{4}^{\circ}</math> E., 97 lks. dist., with a healed blaze.</p> <p>A juniper, 13 ins. diam., bears S. <math>11^{\circ}</math> E., 123 lks. dist., with scribe marks T23S R20E S9 BT visible on partially opened blaze. (Record species: pine)</p> <p>and bearing trees marked by Craig</p> <p>A twin trunk juniper, 4 ins. diam., bears N. <math>85^{\circ}</math> E., 25.5 lks. dist., with <math>1\frac{1}{2}</math> in. diam. metal washer, marked PLS 20354, nailed to the S. limb.</p> <p>A juniper, 8 ins. diam., bears S. <math>89^{\circ}</math> W., 79 lks. dist., with scribe marks BT visible on partially opened blaze.</p> <p>Not remonumented.</p>
19.91	<p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>S. <math>89^{\circ}52'</math> W., bet. secs. 4 and 9.</p> <p>Over mountainous land, through oak timber.</p> <p>Point for the E. <math>1/16</math> sec. cor. of secs. 4 and 9.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 23 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T23S R20E S 4 E <math>1/16</math> ——— S 9 2000</p> </div> <p>from which</p> <p>An oak, 4 ins. diam., bears S. <math>6^{\circ}</math> W., 18 lks. dist., mkd. X at breast height and BT at base.</p> <p>An oak, 4 ins. diam., bears N. <math>17^{\circ}</math> W., 13.5 lks. dist., mkd. X at breast height and BT at base.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
39.82	<p>Point for the <math>1/4</math> sec. cor. of secs. 4 and 9, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 25 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T23S R20E S 4 1/4 ——— S 9 2000</p>
	<p>from which</p> <p style="padding-left: 40px;">A pine, 9 ins. diam., bears N. 28° E., 32.5 lks. dist., mkd. 1/4 S4 BT.</p> <p style="padding-left: 40px;">An oak, 6 ins. diam., bears S. 31° W., 27 lks. dist., mkd. X at breast height and BT at base.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located on a steep, precipitous N. facing slope.</p>
59.73	<p>Point for the W. 1/16 sec. cor. of secs. 4 and 9.</p>
	<p>Not monumented.</p>
79.64	<p>The cor. of secs. 4, 5, 8 and 9.</p>
<p>Subdivision of Section 3, T. 23 S., R. 20 E., Gila and Salt River Meridian, Arizona</p>	
	<p>From the 1/4 sec. cor. of secs. 3 and 10.</p>
	<p>N. 0°30' W., on the N. and S. center line of sec. 3.</p>
	<p>Descending, over rolling land, through dense oak and manzanita.</p>
19.80	<p>Point for the center S. 1/16 sec. cor. of sec. 3.</p>
	<p>Not monumented.</p>
29.47	<p>Intersect the S. side of a wooden horse stall, 27 x 13 x 7 ft. high, the long side bears E. and W., the SE cor. bears E., 21 lks. dist.</p>
29.66	<p>Intersect the N. side of same horse stall.</p>
29.70	<p>Point for the center N-S 1/64 sec. cor.</p>
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>

Subdivision of Section 3,  
T. 23 S., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T23S R20E C N-S 1/64   S 3 C 2000
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Cor. is located 21 lks. W. of a woven wire fence, 7 ft. high, bears N. and S.
	From this cor. point, a rebar, ½ in. diam., firmly set, projecting 3 ins. above ground, with 1 in. diam. yellow plastic cap mkd. LS 17565, bears N. 64°43' E., 29.5 lks. dist.
	From this same cor. point, a wooden power pole, bears N. 81°56' E., 24 lks. dist.
30.28	Woven wire fence, 7 ft. high, bears N. 89½° W. and S. 89½° E. for 22 lks., thence S.
30.39	Barbed wire fence, four strand, bears irregularly E. and W.
39.60	Point for the center 1/4 sec. cor. of sec. 3, at intersection with a line from the 1/4 sec. cor. of secs. 3 and 34, on the N. bdy. of the Tp., parallel with N. ½ of the line bet. secs. 2 and 3 and a line from the 1/4 sec. cor. of secs. 2 and 3, parallel with E. ¼ of the line bet. secs. 3 and 34.
	Set a brass tablet, 3¼ ins. diam., 3¼ ins. stem, in a drill hole cemented in place, flush with the face of 20 x 20 ft. granite slab, with brass tablet mkd.
	T23S R20E C 1/4 S 3 2000
	Cor. is located on a steep, rocky, S. facing slope.
	<hr style="width: 20%; margin: auto;"/>
	N. 0°05' E., beginning new measurement.
10.015	Point for the center S-N 1/64 sec. cor. for the NE 1/4 of sec. 3 only.
	Set a brass tablet, 3¼ ins. diam., 3¼ ins. stem, in a drill hole cemented in place, flush with the face of a granite outcropping, with brass tablet mkd.

Subdivision of Section 3,  
T. 23 S., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T23S R20E C S 3  S-N 1/64 C 2000
	Deposit 5 U.S. one cent pieces at the base of the drill hole.
11.80	Four strand barbed wire fence, bears irregularly SSE and NNW.
20.03	Point for the center N. 1/16 sec. cor. for the NE 1/4 of sec. 3 only.
	Not monumented.
40.06	The 1/4 sec. cor. of secs. 3 and 34, on the N. bdy. of the Tp.
	<hr/>
	From the 1/4 sec. cor. of secs. 2 and 3.
	N. 89°59' W., on the E. and W. center line of sec. 3.
18.85	Center of pavement, Ramsey Canyon Road, 27 lks. wide, bears NNE and SSW.
20.03	Point for the center E. 1/16 sec. cor. of sec. 3.
	Not monumented.
40.06	The center 1/4 sec. cor. of sec. 3
	<hr/>
	N. 89°50' W., beginning new measurement.
0.50	Four strand barbed wire fence, bears irregularly N. and S.
19.81	Point for the center W. 1/16 sec. cor. of sec. 3.
	Not monumented.
39.62	The 1/4 sec. cor. of secs. 3 and 4.
	<hr/>
	NE 1/4
	<hr/>
	From the point for the center E. 1/16 sec. cor. of sec. 3.
	N. 0°05' E., on the N. and S. center line of the NE 1/4 of sec. 3.
	Over rolling and mountainous land, through medium oak timber.

Subdivision of Section 3,  
T. 23 S., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
10.015	<p>Point for the center S-NE 1/64 sec. cor. of sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T23S R20E S 3 C-S-NE 1/64 2000</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
10.04	<p>Four strand barbed wire fence, bears N. 60° E., for 24 lks., thence N. and S. and S. 60° W., for 11 lks., thence S.</p>
19.84	<p>Four strand barbed wire fence, bears N. 86° E., and S. 86° W.</p>
20.03	<p>Point for the NE 1/16 sec. cor. of sec. 3, at intersection with the E. and W. center line of the NE 1/4 of sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 17 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T23S R20E NE 1/16 S 3 2000</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, a rebar of unknown origin, 5/8 in. diam., firmly set, projecting 10 ins. above ground, bears S. 42°52' E., 24.5 lks. dist.</p>
40.06	<p>The E. 1/16 sec. cor. of secs. 3 and 34, on the N. bdy. of the Tp.</p> <hr/> <p>From the N. 1/16 sec. cor. of secs. 2 and 3.</p> <p>N. 89°59' W., on the E. and W. center line of the NE 1/4 of sec. 3.</p>
0.09	<p>Westerly edge of pavement, Ramsey Canyon Road, 27 lks. wide, bears NE and SW.</p>
0.55	<p>From this point, the cor. of 4 strand barbed wire fences, extending NE, SW, and W, bears S., 2 lks. dist.</p>

Subdivision of Section 3,  
T. 23 S., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
10.81	From this point, a $\frac{1}{2}$ in. diam. rebar firmly set, projecting 6 ins. above ground, located in a 4 strand barbed wire fence, bearing E. and W., bears S., 5 lks. dist.
19.67	From this point, a fence cor. with 4 strand barbed wire fences extending E., S. and W., bears S., 17 lks. dist.
20.03	The NE $\frac{1}{16}$ sec. cor. of sec. 3
40.06	The point for the center N. $\frac{1}{16}$ sec. cor. for the NE $\frac{1}{4}$ of sec. 3 only.
	<hr/> <p>From the center S-NE <math>\frac{1}{64}</math> sec. cor. of sec. 3.</p> <p>N. <math>89^{\circ}59'</math> W., on the E. and W. center line of the SE <math>\frac{1}{4}</math> of the NE <math>\frac{1}{4}</math> of sec. 3.</p> <p>Over mountainous land, ascending.</p>
6.95	Barbed wire fence, 4 strand, bears irregularly E. and W.
20.03	The center S-N $\frac{1}{64}$ sec. cor. for the NE $\frac{1}{4}$ of sec. 3 only.
	<hr/> <p style="text-align: center;">SE <math>\frac{1}{4}</math></p> <hr/>
	<p>From the E. <math>\frac{1}{16}</math> sec. cor. of secs. 3 and 10.</p> <p>N. <math>0^{\circ}30'</math> W., on the N. and S. center line of the SE <math>\frac{1}{4}</math> of sec. 3.</p> <p>Over rolling land, through dense oak and manzanita brush.</p>
19.765	Point for the SE $\frac{1}{16}$ sec. cor. of sec. 3, at intersection with the E. and W. center line of the SE $\frac{1}{4}$ of sec. 3.
	<p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 20 ins. in the ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T23S R20E SE <math>\frac{1}{16}</math> S3 2000</p>
38.05	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	<p>Center of pavement, Ramsey Canyon Road, 27 lks. wide, bears NNE and SSW.</p>

Subdivision of Section 3,  
T. 23 S., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
39.53	<p>The point for the center E. 1/16 sec. cor. of sec. 3.</p> <hr/> <p>From the S. 1/16 sec. cor. of secs. 2 and 3.</p> <p>S. 89°56' W., on the E. and W. center line of the SE 1/4 of sec. 3.</p> <p>Over rolling and mountainous land.</p>
19.65	Dilapidated barbed wire fence, 4 strand, bears irregularly N. and S.
20.03	The SE 1/16 sec. cor. of sec. 3.
40.06	<p>The point for the center S. 1/16 sec. cor. of sec. 3.</p> <hr/> <p style="text-align: center;">SW 1/4</p> <hr/> <p>From the point for the W. 1/16 sec. cor. of secs. 3 and 10.</p> <p>N. 0°16' W., on the N. and S. center line of the SW 1/4 of sec. 3.</p> <p>Over rolling and mountainous land.</p>
19.84	<p>Point for the SW 1/16 sec. cor. of sec. 3, at intersection with the E. and W. center line of the SW 1/4 of sec. 3.</p> <p>Not monumented.</p>
29.22	Intersect the S. side, of the westerly wing of an irregular shaped brick house, the long side bears E. and W., the SW cor. bears W., 17 lks. dist.
29.52	Intersect the N. side, of same building.
29.76	<p>Point for the center N-SW 1/64 sec. cor. of sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T23S R20E S3 C-N-SW 1/64 2000</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

Subdivision of Section 3,  
T. 23 S., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
31.22	Oak tree fence corner, with 4 strand barbed wire fences bearing SSE and W.
34.72	<p>Point for the center N-N-SW 1/256 sec. cor. of sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T23S R20E S3 C-N-N-SW 1/256 2000</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, an open end galvanized iron pipe, 1 in. diam., firmly set, projecting 5 ins. above ground, origin unknown, bears N. 75°35' E., 13 lks. dist.</p>
35.43	Four strand barbed wire fence, bears irregularly E. and W.
39.68	The point for the center W. 1/16 sec. cor. of sec. 3.
	<hr/> <p>From the point for the center S. 1/16 sec. cor. of sec. 3. N. 89°58' W., on the E. and W. center line of the SW 1/4 of sec. 3. 3. Over rolling land.</p>
19.89	The point for the SW 1/16 sec. cor. of sec. 3.
29.835	<p>Point for the center W-SW 1/64 sec. cor. of sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T23S R20E S3 C-W-SW 1/256 2000</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

Subdivision of Section 3,  
T. 23 S., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Cor. is located in a dilapidated, 3 strand barbed wire fence, bears irregularly N. and S.</p> <p>From this cor. point, a rebar, <math>\frac{1}{2}</math> ins. diam., firmly set, projecting 2 ins. above ground, with 1 in. yellow plastic cap mkd. LS 17565, bears S. <math>4^{\circ}49'</math> E., 52 lks. dist.</p>
39.78	<p>The point for the S. <math>\frac{1}{16}</math> sec. cor. of sec. 3 and 4.</p> <hr/> <p>From the center N-S <math>\frac{1}{64}</math> sec. cor. of sec. 3.</p> <p>N. <math>89^{\circ}54'</math> W., on the E. and W. center line of the NE <math>\frac{1}{4}</math> of the SW <math>\frac{1}{4}</math> of sec. 3.</p> <p>Along 4 wire over head power line, across fenced yard of private residence.</p>
6.05	<p>Woven wire fence, bears S. <math>0^{\circ}45'</math> W. and N. <math>0^{\circ}45'</math> E., for 69 lks. to a cor. of woven wire fence, bearing S. <math>89^{\circ}32'</math> E. and barbed wire fence bearing N <math>0^{\circ}45'</math> E., for 7.5 lks., thence irregularly E. and W.</p> <p>From this same point, a <math>\frac{1}{2}</math> in. diam., rebar, firmly set, projecting 2 ins. above ground, bears N. <math>0^{\circ}45'</math> E., 5 lks., dist., located in same woven wire fence, origin unknown, thence across fenced yard of private residence.</p>
12.41	<p>Woven wire fence, bears S. <math>0^{\circ}46'</math> W. and N. <math>0^{\circ}46'</math> E., for 85 lks., to a cor. of woven wire fences bearing irregularly E. and W.</p> <p>From this same point, an open end iron pipe, <math>1\frac{1}{2}</math> ins. diam., firmly set, projecting 11 ins. above ground, bears N. <math>0^{\circ}46'</math> E., 3 lks. dist., located in same woven wire fence, origin unknown, thence across junk storage area.</p>
18.86	<p>From this point, the SE cor. of a concrete staircase landing, 9 x 8 ft., bears N., 4 lks. dist., the long side bears N.</p>
18.89	<p>Intersect the east side of a wooden staircase, the most northeastern point bears N., 5.5 lks. dist.</p>
18.95	<p>Intersect the west side of same wooden staircase, the most northwestern point bears N., 5.5 lks. dist.</p>
19.36	<p>Intersect the east side of a wood enclosure on a block foundation, 28.5 x 10.5 ft., the long side bears W., the NE cor. bears N., 3 lks. dist.</p>
19.79	<p>Intersect the west side of same wood enclosure, the NW cor. bears N., 3 lks. dist.</p>

Subdivision of Section 3,  
T. 23 S., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
19.85	The center N-SW 1/64 sec. cor.
	<hr/> <p>From the W-W 1/64 sec. cor. of secs. 3 and 10.</p> <p>N. 0°09' W., on the N. and S. center line of the SW 1/4 of the SW 1/4 of sec. 3.</p> <p>Over E. facing slope, through dense oak and manzanita brush.</p>
5.82	<p>From this point, a rebar, ½ in. diam., firmly set, projecting 2 ins. above ground, with 1 in. diam. yellow plastic cap mkd. LS 17565, bears E., 6.5 lks. dist.</p> <p>From this same point, a dilapidated 4 strand barbed wire fence, bearing irregularly N. and S., bears W., 65 1/2 lks. dist.</p>
12.16	<p>From this point, a rebar, ½ in. diam., firmly set, projecting 2 ins. above ground, with 1 in. diam. yellow plastic cap mkd. LS 17565, bears E., 5.5 lks. dist.</p> <p>From this same point, a dilapidated 4 strand barbed wire fence, bearing irregularly N. and S., bears W., 38 lks. dist.</p>
19.87	The center W-SW 1/64 sec. cor. of sec. 3.
	<hr/> <p>N. 0°09' W., on a portion of the N. and S. center line of the NW 1/4 of the SW 1/4 of sec. 3.</p>
1.19	From this point, the terminus of a dilapidated 4 strand barbed wire fence, bearing irregularly S., bears E., 8 lks. dist.
4.05	Road to Brown Canyon, graded, 12 lks. wide, bears NE and SW.
14.90	Point for the center N-NW-SW 1/256 sec. cor. of sec. 3.
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T23S R20E S3 C-N-NW-SW 1/256 2000</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

Subdivision of Section 3,  
T. 23 S., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From this cor. point, a galvanized iron pipe, 1 in. diam., firmly set, projecting 6 ins. above ground, origin unknown, bears N. 79°17' E., 6.5 lks. dist.</p> <hr/> <p>S. 89°52' E., on the E. and W. center line of the NE 1/4 of the NW 1/4 of the SW 1/4 of sec. 3.</p>
1.89	<p>Four strand barbed wire fence, bears SW and N. 40° E., for 42 lks., thence irregularly E.</p>
7.99	<p>Intersect a four strand barbed wire fence, bears N. and S., with a rebar, ½ in. diam., firmly set, projecting 6 ins. above ground, with 1½ ins. aluminum cap mkd. 1789, bearing N. 3 lks. dist.</p>
9.915	<p>The center N-N-SW 1/256 sec. cor. of sec. 3.</p> <hr/> <p style="text-align: center;">Subdivision of Section 9, T. 23 S., R. 20 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 9 and 16.</p> <p>N. 0°08' W., on the N. and S. center line of sec. 9.</p> <p>Through dense pine and oak timber, descending into Ramsey Canyon.</p>
19.725	<p>Point for the center S. 1/16 sec. cor. of sec. 9.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T23S R20E</p> <p style="margin: 0 10px;">C</p> <p style="margin: 0 10px;">S 1/16   S9</p> <p style="margin: 0 10px;">C</p> <p style="margin: 0 10px;">2000</p> </div> <p>from which</p> <p style="margin-left: 40px;">A fir, 8 ins. diam., bears N. 65° E., 41 lks. dist., mkd. C-S 1/16 S9 BT.</p> <p style="margin-left: 40px;">A pine, 8 ins. diam., bears N. 63° W., 23.5 lks. dist., mkd. C-S 1/16 S9 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

Subdivision of Section 9,  
T. 23 S., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Cor. is located within Ramsey Canyon on a steep W. facing slope.
39.45	Point for the center 1/4 sec. cor. of sec. 9, at intersection with the E. and W. center line of sec. 9.  Not monumented.
59.28	Point for the center N. 1/16 sec. cor. of sec. 9.  Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, in a collar of stone, with brass cap mkd.  <div style="text-align: center;">           T23S R20E                  C            N 1/16   S9                  C            2000         </div> from which  <div style="text-align: center;">           A granite boulder, 4 x 2 x 2 ft. high, bears N. 8° E.,            10 lks. dist., mkd. XBO.         </div> Deposit a magnet in a white plastic case at the base of the stainless steel post.
79.11	The 1/4 sec. cor. of secs. 4 and 9. <hr/>
	From the 1/4 sec. cor. of secs. 9 and 10.  N. 89°40' W., on the E. and W. center line of sec. 9.  Over mountainous land, through medium pine and oak timber.
19.89	Point for the center E. 1/16 sec. cor. of sec. 9.  Not monumented.
39.78	The point for the center 1/4 sec. cor. of sec. 9.
59.65	Point for the center W. 1/16 sec. cor. of sec. 9.  Set a stainless steel post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, in a collar of stone, with brass cap mkd.  <div style="text-align: center;">           T23S R20E                  W 1/16            C ——— C                  S9            2000         </div>

Subdivision of Section 9,  
T. 23 S., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
79.52	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located on SW facing slope, within dense manzanita brush.</p> <p>The 1/4 sec. cor. of secs. 8 and 9.</p> <hr/> <p style="text-align: center;">NE 1/4</p> <hr/> <p>From the point for the center E. 1/16 sec. cor. of sec. 9.</p> <p>N. 0°06' W., on the N. and S. center line of the NE 1/4 of sec. 9.</p> <p>Over easterly facing slope, through dense oak and manzanita brush.</p>
19.915	<p>Point for the NE 1/16 sec. cor. of sec. 9, at intersection with the E. and W. center line of the NE 1/4 of sec. 9.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T23S R20E NE 1/16 S9 2000</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 6 ins. diam., bears N. 67° W., 25.5 lks. dist., mkd. NE 1/16 S9 BT.</p>
39.83	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located on a steep rocky ESE facing slope.</p> <p>The E. 1/16 sec. cor. of secs. 4 and 9.</p> <hr/>
19.90	<p>From the N. 1/16 sec. cor. of secs. 9 and 10.</p> <p>N. 89°54' W., on the E. and W. center line of the NE 1/4 of sec. 9.</p> <p>Over mountainous land, through dense oak and manzanita brush.</p> <p>The NE 1/16 sec. cor. of sec. 9.</p>

Subdivision of Section 9,  
T. 23 S., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
39.80	<p>The center N. 1/16 sec. cor. of sec. 9.</p> <hr/> <p style="text-align: center;">SE 1/4</p> <hr/> <p>From the S. 1/16 sec. cor. of secs. 9 and 10.</p> <p>N. 89°35' W., on the E. and W. center line of the SE 1/4 of sec. 9.</p> <p>Descending over S. facing slope, through dense pine and oak timber.</p>
39.77	<p>The center S. 1/16 sec. cor. of sec. 9.</p> <hr/> <p style="text-align: center;">SW 1/4</p> <hr/> <p>From the point for the W. 1/16 sec. cor. of secs. 9 and 16.</p> <p>N. 0°11' W., on the N. and S. center line of the SW 1/4 of sec. 9.</p> <p>Descending over E. facing slope, through dense pine and oak timber.</p>
19.70	<p>Point for the SW 1/16 sec. cor. of sec. 9, at intersection with the E. and W. center line of the SW 1/4 of sec. 9.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T23S R20E SW 1/16 S9 2000</p> <p>from which</p> <p style="padding-left: 40px;">An oak, 4 ins. diam., bears N. 17½° E., 36.5 lks. dist. mkd. X at breast height and BT at base.</p> <p style="padding-left: 40px;">A pine, 9 ins. diam., bears N. 78° E., 27.5 lks. dist. mkd. SW 1/16 S9 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
39.40	<p>The center W. 1/16 sec. cor. of sec. 9.</p> <hr/>

Subdivision of Section 9,  
T. 23 S., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the center S. 1/16 sec. cor. of sec. 9.</p> <p>N. 89°36' W., on the E. and W. center line of the SW 1/4 of sec. 9.</p> <p>Ascending across Ramsey Canyon, through dense pine and oak timber.</p>
19.85	The SW 1/16 sec. cor. of sec. 9.
39.70	The point for the S. 1/16 sec. cor. of secs. 8 and 9.
	<hr/> <p>NW 1/4</p> <hr/>
	<p>From the center W. 1/16 sec. cor. of sec. 9.</p> <p>N. 0°11' W., on the N. and S. center line of the NW 1/4 of sec. 9.</p> <p>Over mountainous land, through dense oak and pine timber.</p>
19.75	<p>Point for the NW 1/16 sec. cor. of sec. 9, at intersection with the E. and W. center line of sec. 9.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T23S R20E NW 1/16 S9 2000</p> <p>from which</p> <p style="padding-left: 40px;">An oak, 4 ins. diam., bears S. 58° E., 16.5 lks. dist., mkd. X at breast height and BT at base.</p> <p style="padding-left: 40px;">A juniper, 9 ins. diam., bears S. 16° E., 22 lks. dist., mkd. NW 1/16 S9 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
39.50	The point for the W. 1/16 sec. cor. of secs. 4 and 9.
	<hr/> <p>From the center N. 1/16 sec. cor. of sec. 9.</p> <p>N. 89°54' W., on the E. and W. center line of the NW 1/4 of sec. 9.</p>

**Subdivision of Section 9,  
T. 23 S., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Over mountainous land.</p> <p>19.89 The NW 1/16 sec. cor. of sec. 9.</p> <p>39.78 The point for the N. 1/16 sec. cor. of secs. 8 and 9.</p> <hr/> <p style="text-align: center;"><b>GENERAL DESCRIPTION</b></p> <hr/> <p>The land encompassed in this resurvey varies from mountainous in sec. 9, to the rolling foot hills of the Huachuca Mountains in sec. 3. Elevations range from about 5000 ft. to 7000 ft. above sea level. Ramsey Canyon is the principal geological feature, located in the S ½ of sec. 9.</p> <p>Rolling grasslands with scattered oak and mesquite are found in sec. 3, changing to pinyon pine, emory oak, juniper and fir at the higher elevations in sec. 9.</p> <p>Access is by way of Ramsey Canyon road, Brown Canyon road and numerous Forest Service hiking trails.</p> <p>The mean magnetic declination of 11½° E., was derived from the United States Geological Survey computer program GEOMAG, utilizing the World Magnetic Model for Epoch 2000 for the dates of survey.</p> <hr/>
--------	---



## CERTIFICATE OF SURVEY

I, Gordon R. Bubel, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 31<sup>st</sup> day of July, 2000, I have dependently resurveyed a portion of the north boundary and a portion of the subdivisional lines and subdivided sections 3 and 9, T. 23 S., R. 20 E., Gila and Salt River Meridian, Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

Aug. 22, 2001

(Date)

Gordon R. Bubel

(Cadastral Surveyor)

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of a portion of the north boundary and a portion of the subdivisional lines and the subdivision of sections 3 and 9, T. 23 S., R. 20 E., Gila and Salt River Meridian, Arizona, executed by Gordon R. Bubel, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

November 30, 2001

(Date)

Kenny D. Runkler

(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 23 S., R. 20 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor of Arizona)~~