

U. S. DEPARTMENT OF AGRICULTURE
FOREST SERVICE

JUN 2 - 1916

99

FIELD NOTES

OF

HOMESTEAD ENTRY SURVEY NO. 157

SITUATED IN THE

TONTO NATIONAL FOREST

ADMINISTRATIVE DISTRICT NO. 3

in

Section 24, - surveyed, Township 9 N., Range 10 E.

Section 19, - surveyed, Township 9 N., Range 11 E.

of the

Gila and Salt River Base and Meridian.

ARIZONA

Survey executed by Walter G. Turley, Surveyor - Forest Service

Under special instructions dated November 29, 1913 ✓

Survey commenced May 17, 1914

Survey completed May 18, 1914

Under Acts of June 11, 1906 and March 4, 1913. ✓

Applicant for listing Ellen J. Neal, ✓

Residence Payson, Arizona

Application No. 51 ✓, dated May 16, 1907 ✓


List No. 918 ✓, dated January 23, 1908 ✓

Applicant for survey Ellen J. Neal, ✓

Residence Payson, Arizona.

H. E. No. 02001 ✓, dated August 8, 1908 ✓

Land district Phoenix, Arizona.



100

187

OATH OF ASSISTANTS

We hereby certify that we assisted Walter G. Turley,
Surveyor - Forest Service in surveying all those
parts or portions of Homestead Entry Survey No. 157, in
- surveyed Section 24, Township 9 N., Range 10 E.,
- surveyed Section 19, Township 9 N., Range 10 E.,

of the G. & S.R.B. & meridian, State of Arizona, which
are represented in the following field notes as having been
surveyed by him and under his direction; and that said sur-
vey has been in all respects, to the best of our knowledge
and belief, well and faithfully surveyed, and the corner
monuments established, according to the instructions fur-
nished by the United States Surveyor General for Arizona.

Note: It would have been
very expensive and incon-
venient to appear before an
officer to administer oaths
to Assistants; hence, they
were taken by the Surveyor.

Charles D. Hudson, Chainman
Charles S. Baecht, Chainman

Subscribed and sworn to before me this 26th day of
May, 1914.

Walter G. Turley
Forest Service Surveyor

OATH OF SURVEYOR

I, Walter G. Turley, Surveyor - Forest Service, do solemnly swear
that, in strict conformity with the special instructions of
the United States Surveyor General for Arizona, dated
November 29 1913, and the laws of the United States, I have
well, faithfully, and truly, in my own proper person, sur-
veyed a tract of land ~~upon the application of~~ embraced in
List, No. 918, dated Jan. 23, 1908, for
Patent, under the Act of June 11, 1906,
the same to be known as Homestead Entry Survey No. 157,
situated within the TONTON National Forest, in
- surveyed Section 24, Township 9 N., Range 10 E., and
- surveyed Section 19, Township 9 N., Range 11 E.,

of the G. & S.R.B. & meridian, Arizona, and the
related retracements and resurveys and section subdivisions,
which are represented in the following field notes as having
been surveyed by me; and I further solemnly swear that all
the corners of said survey have been established and perpet-
uated in strict accordance with the stated special instruc-
tions, and in the specific manner described in the field
notes, and that the following are the original field notes
of such survey.

Walter G. Turley
Forest Service Surveyor

Subscribed and sworn to before me this second day of
June, 1914.

Henry A. Randall
Notary Public



Commission Expires
February 21 1916

8-2249

TONTO NATIONAL FOREST

STATE OF ARIZONA

Chains Applicant for listing, Ellen J. Neal; Application No. 51, dated May 16, 1907; List No. 918, dated January 23, 1908; H. E. No. 02001, made in the Phoenix Land Office on August 8, 1908.

Surveyed under special instructions from the Surveyor General for Arizona, dated November 29, 1913, and designated as Homestead Entry Survey No. 157.

Situated in sec. 24, T. 9 N., R. 10 E., and sec. 19, T. 9 N., R. 11 E., Gila and Salt River Base and Meridian, within the Tonto National Forest, Arizona. Surveyed under the Acts of June 11, 1906 and March 4, 1913.

Survey commenced May 17, 1914, and executed with a W. and L. E. Gurley light mountain transit No. 12953

with vertical circle and Burt solar attachment.

I test the adjustments of the transit and solar attachment and make necessary corrections. The stadia is adjusted to read 1:132.

All distances are horizontal and were reduced from measurements made on the slope with a 400 link steel tape and a Philadelphia stadia rod graduated to feet and hundredths with target verniers reading to thousandths.

The slope angles are determined with a clinometer.

May 17, 1914.

At 8h. 39m. p.m., l.m.t., I observe Polaris with telescope direct at cor. No. 3 of this survey, identical with the position of the list survey corner, no trace of which is found, and mark the direction thus determined with a tack in a stake set 4.00 chs. N. of my station.

Chains

Astron. l.m.t., obsn., May 16, 1914, 32h. 39.0m.

Astron. l.m.t. U.C. Pol., May 16, 1914, 21h. 49.5m.

Hour angle Pol. at obsn., 10h. 49.5m.

Azimuth of Pol. at obsn., $0^{\circ} 24' 18''$ W.

Lat. $34^{\circ} 06' 30''$ N., Long. $111^{\circ} 16' 46''$ W.

May 17, 1914.

May 18, 1914.

At 3h. 50m. a.m., l.m.t., I observe Polaris at Eastern elongation. Azimuth of Polaris at E. elong., $1^{\circ} 23' 28''$ E.

I turn off $1^{\circ} 23-1/2'$ to the W. and mark the line upon the ground with a tack in a stake set 4.00 chs. N. of my station.

I also turn off $0^{\circ} 24'$ to the E. from my line of last night's obsn. which defines a line that differs from the line determined by this morning's observation by $0^{\circ} 00' 12''$ of measured arc. I mark the mean of these two lines with a tack in a stake set 4.00 chs. N. of my station, and to the corresponding meridian all the courses of this survey were referred.

May 18, 1914.

At 7h. 00m. a.m., l.m.t., I set off $19^{\circ} 28'$ N. on the decl. arc, and $34^{\circ} 06-1/2'$ on the lat. arc, and determine a meridian with the solar at cor. No. 3, and my line of sight falls upon the tack in the stake set 4.00 chs. N. of my station. Therefore, I conclude that my transit is in satisfactory adjustment.

HOMESTEAD ENTRY SURVEY NO. 157

TONTON NATIONAL FOREST

STATE OF ARIZONA

Chains

Thence North. From the W. C. to cor. of secs. 19, 24, 25 and 30, which is a granite stone 10 x 8 x 5 ins. above ground, marked and witnessed as described by the Surveyor General. This W. C. is 1.00 ch. S. of true point for cor.

41.02 Fall 5 lks. W. of 1/4 sec. cor. to secs. 19 and 24, which is a granite stone 10 x 6 x 5 ins. above ground, marked and witnessed as described by the Surveyor General.

81.00 Fall 10 lks. W. of cor. of secs. 13, 18, 19 and 24, which is a granite stone 9 x 5 x 4 ins. above ground, marked and witnessed as described by the Surveyor General.

Return course S. 0° 04' W.

Cor. No. 1, and closing cor. on line bet. secs. 19 and 24.

Identical with cor. No. 6, H. E. S. No. 124, which is a quartzite stone 12 x 5 x 10 ins. above ground, marked C C on the W. face and 6 - H E S 124 on the S. face, with a mound of stone 2 ft. base, 1-1/2 ft. high, W. of cor. I mark C C on the E. face and 1 - H E S 157 on the N. face of the same stone, from which:

1/4 sec. cor. between secs. 24 and 19,

T. 9 N., Rs. 10 and 11 E., heretofore described, bears N. 0° 04' E., 1.77 chs. dist.

The W. C. to cor. of secs. 19, 24, 25 and 30,

T. 9 N., Rs. 10 and 11 E., heretofore described, bears S. 0° 04' W., 39.25 chs. dist.

Pits impracticable. No bearings available.

Chains Mag. decl. at 8.00 a.m., 14° 35' E. • Mean Mag. decl.
14° 32' E.
Lat. 34° 06' 30" N., Long. 111° 16' 30" W., from special
instructions of the Surveyor General.

Thence N. 80° 30' W.

Along fence in cultivated land, and line 6-5 of
H. E. S. No. 124.

- 3.95 Fence cor., from which fence bears E., W., and N.
- 10.45 Irrigating ditch, 6 lks. wide, course S.
- 10.55 Fence, bears N. and S.
- 11.60 To cor. No. 2.

Identical with position for the list survey corner,
no trace of which is found, and cor. No. 5 of H. E. S.
No. 124, also a cor. of unsurveyed H. E. S. No. 177.

I mark 2 - H E S 157 on the N. face of the quartzite
stone 10 x 8 x 10 ins. above ground, which is marked
5 - H E S 124 on the SE. face, with a mound of stone
2 ft. base, 1-1/2 ft. high, SE. of cor., from which:

A cottonwood, 36 ins. dia., bears N. 31° E.,
137 lks. dist., marked 5 H E S 124 B T,
2 H E S 157 B T.

A willow, 12 ins. dia., bears S. 86° E.,
92 lks. dist., marked 2 H E S 157 B T.

Thence N. 57° 25' W.

Ascend 10 ft. to cor.

- 1.00 Road, bears N. and S.
- 1.85 Irrigating ditch, 10 lks. wide, course S.
- 8.91 To cor. No. 3.

Identical with position of the list survey corner, also

TERRITORY NATIONAL FOREST

STATE OF ARIZONA

Chains

cor. H-2 of List 3-3170 of John Fox Booth, no trace
of which is found. At this point I set a quartzite
stone 28 x 15 x 7 ins., 18 ins. in the ground, over
a small stone marked with a cross, marked 3 - H E S 157
on the E. face; and raise a mound of stone 2 ft. base,
1-1/2 ft. high, E. of cor., from which:

A mesquit, 4 ins. dia., bears S. 86° E.,
35 lks. dist., marked 3 H E S 157 B T.

A mesquit, 6 ins. dia., bears N. 22° 30' W.,
68 lks. dist., marked 3 H E S 157 B T.

Thence N. 2° 44' W.

Ascend SW. slope 10 ft.

13.79

To cor. No. 4.

Identical with the position of the list survey corner,
no trace of which is found. At this point I set a
quartzite stone 26 x 10 x 7 ins., 16 ins. in the ground,
over a small stone marked with a cross, marked
4 - H E S 157 on the SE. face; and raise a mound of
stone 2 ft. base, 1-1/2 ft. high, SE. of cor., from
which:

A palo verde, 5 ins. dia., bears S. 81° 15' W.,
79 lks. dist., marked 4 H E S 157 B T.

A mesquit, 6 ins. dia., bears S. 61° 35' W.,
149 lks. dist., marked 4 H E S 157 B T.

Thence N. 87° 16' E.

Ascend SW. slope of mesa 5 ft.

3.00

To cor. No. 5.

Identical with the position of the list survey corner,
no trace of which is found. At this point I set a

Chains
 basalt stone 24 x 10 x 8 ins., 14 ins. in the ground,
 over a small stone marked with a cross, marked
 5 - H E S 157 on the SE. face; and raise a mound of
 stone 2 ft. base, 1-1/2 ft. high, SE. of cor., from
 which:
 A mesquit, 4 ins. dia., bears S. 74° 20' W.,
 189 lks. dist., marked 5 H E S 157 B T.
 Pits impracticable. No other bearings
 available;

Thence N. 2° 44' W.

5.00 To cor. No. 6.

Over mesa.
 Identical with the position for list survey corner,
 no trace of which is found. At this point I set a
 quartzite stone 26 x 9 x 8 ins., 16 ins. in the
 ground, over a small stone marked with a cross, marked
 6 - H E S 157 on the NE. face; and raise a mound of
 stone 2 ft. base, 1-1/2 ft. high, NE. of cor., from
 which:

- A catclaw, 4 ins. dia., bears N. 5° W.,
 45 lks. dist., marked 6 H E S 157 B T.
- A catclaw 5 ins. dia., bears N. 41° 55' W.,
 192 lks. dist., marked 6 H E S 157 B T.

Thence S. 87° 16' W.

3.00 To cor. No. 7.

Over mesa.
 Identical with the position for list survey corner, no
 trace of which is found. At this point I set a gran-
 ite stone 24 x 10 x 9 ins., 14 ins. in the ground, over

TONTON NATIONAL FOREST

STATE OF ARIZONA

Chains	<p>a small stone marked with a cross, marked 7 - H E S 157 on the NE. face; and raise a mound of stone 2 ft. base, 1-1/2 ft. high, NE. of cor., from which:</p> <p>A mesquit, 4 ins. dia., bears S. 67° 30' W., 89 lks. dist., marked 7 H E S 157 B T.</p> <p>A mesquit, 4 ins. dia., bears N. 81° 15' E., 175 lks. dist., marked 7 H E S 157 B T.</p> <p>The NW. gable end of frame school house, 32 x 24 ft., the long side of which bears NW. and SE., bears S. 2° 44' E., 3.52 chs. dist.</p> <hr/> <p>Thence N. 2° 44' W.</p> <p>Over mesa.</p> <p>3.00 To cor. No. 8.</p> <p>Identical with the position for list survey corner, no trace of which is found. I mark 8 - H E S 157 on the SE. face of the quartzite stone 7 x 6 x 10 ins. above ground, which is marked 9 - H E S 56 on the NE. face; and raise a mound of stone 2 ft. base, 1-1/2 ft. high, SE. of cor., from which:</p> <p>A mesquit, 5 ins. dia., bears N. 64° W., 78 lks. dist., marked 8 H E S 157 B T.</p> <p>A mesquit, 5 ins. dia., bears S. 37° 30' E., 58 lks. dist., marked 8 H E S 157 B T.</p> <hr/> <p>Thence S. 81° 30' E.</p> <p>Along line 9-8 of H. E. S. No. 56. Over mesa.</p> <p>12.75 Edge of mesa, bears NE. and SW. Descend 20 ft. to bottom.</p> <p>13.50 Irrigating ditch, 6 lks. wide, course SW.</p> <p>14.25 Fence cor., from which fence bears NE., SW., W. and WNW.</p>
--------	---

Chains Enter cultivated land.

20.28 To cor. No. 9, and a closing cor.

At this point I intersect the line between secs. 24 and 19, T. 9 N., Rs. 10 and 11 E., at a point 23.72 chs. N. 0° 04' E. of the 1/4 sec. cor. to secs. 19 and 24, heretofore described, and 16.26 chs. S. 0° 04' W. of the cor. of secs. 13, 18, 19 and 24, heretofore described. I mark C C on the W. face and 9 - H E S 157 on the S. face of the quartzite stone 12 x 12 x 10 ins. above ground, which is marked C C on the S. face and 8 - H E S 56 on the N. face; and raise a mound of stone 2 ft. base, 1-1/2 ft. high, W. of cor., from which:

An elderberry, 18 ins. dia., bears S. 67° 30' E., 184 lks. dist., marked 9 H E S 157 B T.

Pits impracticable. No other bearings available.

Thence S. 81° 30' E.

Along line 8-7 of H. E. S. No. 56 and fence in cultivated land.

1.44 Fence cor., from which fence bears N., S., E. and W. Leave cultivated land and continue in undergrowth.

10.70 Fence cor., from which fence bears N., S., and W.

13.94 Right bank of Tonto Creek, 3.50 chs. wide, right bank 3 ft. high, left bank 20 ft. high, course S. Ascend 30 ft. from creek.

20.16 To cor. No. 10.

Identical with the position for list survey corner, no trace of which is found. I mark 10 - H E S 157 on the SW. face of the quartzite boulder 10 x 8 x 10 ins. above ground, marked 7 - H E S 56 on the NW. face, with a mound of stone 2 ft. base, 1-1/2 ft. high, NW.

Chains

of cor., from which:
A palo verde, 4 ins. dia., bears S. 19° E.,
55 lks. dist., marked 10 H E S 157 B T.
A mesquit, 4 ins. dia., bears N. 49° 15' W.,
59 lks. dist., marked 10 H E S 157 B T.

Thence S. 4° 21' E.

Ascend along E. slope 20 ft.

4.50 Spur, bears E. and W.

Descend rolling E. slope 15 ft.

25.28 To W. C. No. 11.

A point on the bank of an arroyo in which the point for
cor. No. 11 falls. At this point I set a quartzite
stone 26 x 9 x 5 ins., 16 ins. in the ground, over a
small stone marked with a cross, marked W C - 11 -

H E S 157 on the NW. face; and raise a mound of stone
2 ft. base, 1-1/2 ft. high, NW. of cor., from which:

A cedar, 5 ins. dia., bears N. 10° E.,
8 lks. dist., marked W C 11 H E S 157 B T.

A cedar, 10 ins. dia., bears N. 88° 45' E.,
112 lks. dist., marked W C 11 H E S 157 B T.

Descend 15 ft. to arroyo.

26.22 To point for cor. No. 11, identical with point for cor.
No. 7 of H. E. S. 124.

Thence N. 80° 30' W.

Along line 7-6 of H. E. S. No. 124. Ascend 10 ft.
to arroyo bank.

0.81 To W. C. No. 11.

Identical with W. C. 7 of H. E. S. 124, which is a ba-
salt stone 9 x 8 x 10 ins. above ground, marked W C - 7
- H E S 124 on the SW. face, with a mound of stone 2 ft.
base, 1-1/2 ft. high to the SW. I mark W C - 11 -
H E S 157 on the NW. face of the same stone, whence:

Chains
 A cedar, 24 ins. dia., bears S. 84° 10' W.,
 150 lks. dist., marked W C 7 H E S 124 B T
 and W C 11 H E S 157 B T.
 A cedar, 5 ins. dia., bears N. 44° 10' E.,
 154 lks. dist., marked W C 11 H E S 157 B T.
 3.00 Spur, bears NE. and SW. Descend 40 ft.
 6.25 Left bank of Tonto Creek, 2.50 chs. wide, banks 3 ft.
 high, course S. Ascend 5 ft. to cor.
 10.10 Irrigating ditch, 6 lks. wide, course South.
 10.86 Fence, bears N. and S. Continue in cultivated land.
 22.26 To cor. No. 1, the place of beginning.

AREA

Area in Sec. 24, - - - - - 46.37 acres
 Area in Sec. 19, - - - - - 53.75 acres
 Total Area - - - - - 100.12 acres

IMPROVEMENTS

The improvements made upon and for the benefits of this
 homestead, and belonging to the claimant, consist of

the following:

A frame hay barn, 42 x 30 ft., the long side of which
 bears E. and W. and the NW. cor. bears S. 31° E.,
 14.60 chs. dist. from cor. No. 5.

Value ----- \$300.00

A frame hay shed, 24 x 14 ft., the long side of which
 bears E. and W., and the NW. cor. bears S. 33° 25' E.,
 14.20 chs. dist. from cor. No. 5.

Value ----- \$100.00

A frame dwelling, 36 x 24 ft., the long side of which
 bears N. and S., and the NW. cor. bears S. 45° E.,
 13.60 chs. dist. from cor. No. 5.

Value ----- \$500.00

TONTONATIONAL FOREST

STATE OF ARIZONA

Chains A frame barn, 18 x 14 ft., the long side of which bears E. and W., and the NW. cor. bears S. 76° 30' E., 7.40 chs. dist. from cor. No. 5.

Value ----- \$100.00

A frame dwelling, 35 x 24 ft., the long side of which bears N. and S., and the NW. cor. bears S. 83° 40' E., 8.20 chs. dist. from cor. No. 5.

Value ----- \$400.00

There is approximately one mile of fencing.

Value ----- \$100.00

A bearing orchard.

Value ----- \$500.00

DESCRIPTION

This claim is situated in the Gisela Valley on Tonto Creek which runs south and furnishes sufficient water for irrigation. There is some sycamore along the creek and catsclaw and mesquit on the slopes. The soil is fertile where water is applied. This claim appears to be non-mineral in character.

CONFLICTS AND ADJOINING CLAIMS

This claim is joined on the North by H. E. S. No. 56, Albert Booth, and on the south by H. E. S. No. 124, D. Hale, and List 3-3170 of John Fox Booth (unsurveyed H. E. S. No. 177). I was unable to find any of the list survey corners and no record is made of any corners having been set. Their position is very well established by the fact that a homestead entry survey has been made of the claims immediately north and south of this claim; and by the improvements of the claimant.

Chains

Payson post office is 12 miles in a northerly direction and is reached by wagon road. Globe railway station is 70 miles in a southeasterly direction and is reached by 90 miles of wagon road.

May 18, 1914.

TRAVERSE - Sec. 19.

Cor.	Course	Dist.	N	S	E	W
1-9	N. 0° 04' E.	25.49	25.49		0.03	
9-10	S. 81° 30' E.	20.16		2.98	19.94	
10-11	S. 4° 21' E.	26.22		26.14	1.99	
11-1	N. 80° 30' W.	22.26	3.67			21.95
		94.13	29.16	29.12	21.96	21.95
			29.12		21.95	
Error in Lat. and Dep.			.04		.01	

Closing error 1:2283.

TRAVERSE - Sec. 24.

Cor.	Course	Dist.	N	S	E	W
1-2	N. 80° 30' W.	11.60	1.91			11.44
2-3	N. 57° 25' W.	8.91	4.80			7.51
3-4	N. 2° 44' W.	13.79	13.77			0.66
4-5	N. 87° 16' E.	3.00	0.14		3.00	
5-6	N. 2° 44' W.	5.00	5.00			0.24
6-7	S. 87° 16' W.	3.00		0.14		3.00
7-8	N. 2° 44' W.	3.00	3.00			0.14
8-9	S. 81° 30' E.	20.28		3.00	20.06	
9-1	S. 0° 04' W.	25.49		25.49		0.03
		94.07	28.62	28.63	23.06	23.02
				28.62	23.02	
Error in Lat. and Dep.				.01	.04	

Closing error 1:2282.

TRAVERSE - ENTIRE TRACT

Cor.	Course	Dist.	N	S	E	W
1-2	N. 80° 30' W.	11.60	1.91			11.44
2-3	N. 57° 25' W.	8.91	4.80			7.51
3-4	N. 2° 44' W.	13.79	13.77			0.66
4-5	N. 87° 16' E.	3.00	0.14		3.00	
5-6	N. 2° 44' W.	5.00	5.00			0.24
6-7	S. 87° 16' W.	3.00		0.14		3.00
7-8	N. 2° 44' W.	3.00	3.00			0.14
8-9	S. 81° 30' E.	20.28		3.00	20.06	
9-10	S. 81° 30' E.	20.16		2.98	19.94	
10-11	S. 4° 21' E.	26.22		26.14	1.99	
11-1	N. 80° 30' W.	22.26	3.67			21.95
		137.22	32.29	32.26	44.99	44.94
			32.26		44.94	
Error in Lat. and Dep.			.03		.05	

Closing error 1:2353.

Walter J. Turley
Surveyor - Forest Service

DIRECTIONS.—1. Carry out calculations to two decimals only.
2. In balancing Latitudes and Departures do not obliterate or change the original figures. Do not change the footing of the original figures, but put below them the corrected footing in red ink. Put the corrected figure or figures above in red ink. Do not change the footing of the original figures, but put below them the corrected footing in red ink. The corrections for balancing fallings should be proportional to the lengths of the lines.
3. In calculations of fallings take result to nearest link. In calculations of N. and S. areas drop all after second decimal. Surveyors are required to use the Standard Field Tables issued by the G. L. O.
4. Only three copies of this tabulation are necessary, for the District Office, the Surveyor General, and the Commissioner.

TABLING AND CALCULATIONS OF HOMESTEAD ENTRY SURVEY NO. 157, STATE OF ARIZONA, Tonto, Ellen J. Neal.

CORNERS.	BEARING.	DISTANCE.	LATITUDES.		DEPARTURES.		DOUBLE M. D.	N. AREAS.		S. AREAS.	
			NORTH.	SOUTH.	EAST.	WEST.					
Sec. 24. 1-2	N. 80° 30' W.	11.60	1 91			11 44 ⁵	28 57	54 57 ✓			
2-3	N. 57° 25' W.	8.91	4 80			n7 51 ⁷	9 61	46 13 ✓			
3-4	N. 2° 44' W.	13.79	13 77			0 66	1 43	19 69 ✓			
4-5	N. 87° 16' E.	3.00	0 14		3 00		3 76	0 53 ✓			
5-6	N. 2° 44' W.	5.00	5 00			0 24	6 52	32 60 ✓			
6-7	S. 87° 16' W.	3.00		0 14		3 00	3 28			0 46 ✓	
7-8	N. 2° 44' W.	3.00	3 00		3 00	0 14	0 14	0 42 ✓			
8-9	S. 81° 30' E.	20.28		3 00	20 06		20 05			60 15 ✓	
9-1	S. 0° 04' W.	25.49		25 49		0 03	40 06			1020 73 ✓	
		94.07	28 62	28 63	23 06	23 02		153 94		1081 34	
			28 62	28 62	23 05	23 05				153 94	
										927 40	
										46 37 acres.	
	Closing error 1:2282.										
Sec. 19. 1-9	N. 0° 08' E.	25.49	25 49		0 03		0 03	0 76 ✓			
9-10	S. 81° 30' E.	20.16		2 98	19 94		20 00			59 80 ✓	
10-11	S. 4° 21' E.	26.22		26 14	1 99		41 92			1096 21 ✓	
11-1	N. 80° 30' W.	22.26	3 67			21 95		80 34 ✓			
		94.13	29 16	29 12	21 96	21 95		81 10		1156 01	
			29 14	29 14	21 95	21 95				81 10	
										1074 91	
	Closing error, 1:2283									53 75 acres.	

APPROVAL


Office of the United States Surveyor General,

Phoenix, Arizona, March 8 , 1917

The foregoing field notes of Homestead Entry Survey No.

157

executed by **Walter G. Turley, Surveyor Forest Service**
[Forest Service Title.]
under his special instructions, dated **November 29** , 191**3** having
been critically examined, and the necessary corrections and explanations
made, the said field notes, and the surveys they describe, are hereby
approved.


U. S. Surveyor General.

I certify that the foregoing transcript of the field notes of the
above-described survey in the State of **Arizona** , has been
correctly copied from the original notes on file in this office.

Frank P. Trott.
U. S. Surveyor General.