

43

MAY 1 - 1916

U. S. DEPARTMENT OF AGRICULTURE  
FOREST SERVICE

**FIELD NOTES**

OF

HOMESTEAD ENTRY SURVEY NO. 206

SITUATED IN THE

SITGREAVES NATIONAL FOREST

ADMINISTRATIVE DISTRICT NO. 3

in

Section 13, surveyed, Township 9 N., Range 22 E.

-----  
-----  
-----

of the

Gila and Salt River Base and Meridian.

**ARIZONA**

Survey executed by C. A. Long, Surveyor - Forest Service

Under special instructions dated June 17, 1914

and supplemental special instructions dated July 22, 1914

Survey commenced September 2, 1914

Survey completed September 7, 1914

Under Acts of June 11, 1906 and June 30, 1914

Applicant for listing Andrew P. Holland,

Residence Lakeside, Arizona

Application No. 394 ✓, dated November 9, 1912 ✓


List No. 3-2232 ✓, dated January 20, 1913 ✓

Applicant for survey Andrew P. Holland,

Residence Lakeside, Arizona

H. E. No. 022394 ✓, dated May 26, 1913 ✓

Land district Phoenix, Arizona





44

OATH OF ASSISTANTS

We hereby certify that we assisted C. A. Long,  
Surveyor - Forest Service in surveying all those  
parts or portions of Homestead Entry Survey No. 206, in  
- surveyed Section 13, Township 9 N., Range 22 E.,  
- surveyed Section - - -, Township - - -, Range - - -,  
- - - - -  
of the G. & S.R.B.& meridian, State of ARIZONA, which  
are represented in the following field notes as having been  
surveyed by him and under his direction; and that said sur-  
vey has been in all respects, to the best of our knowledge  
and belief, well and faithfully surveyed, and the corner  
monuments established, according to the instructions fur-  
nished by the United States Surveyor General for ARIZONA.

Note: It would have been  
very expensive and incon-  
venient to appear before  
an officer to administer  
the oaths to Assistants;  
hence, they were taken  
by the Surveyor.

Wm. Warner Chainman

Frank Farley Chainman

Subscribed and sworn to before me this 7th day of  
September, 1914.

C. A. Long  
Surveyor - Forest Service

OATH OF SURVEYOR

I, C. A. Long, Surveyor-Forest Service, do solemnly swear  
that, in strict conformity with the special instructions of  
the United States Surveyor General for ARIZONA dated June 17, 1914 & supp'l  
instrs. dated July 22, 1914, and the laws of the United States, I have  
well, faithfully, and truly, in my own proper person, sur-  
veyed a tract of land ~~upon the application of~~ embraced in  
List, No 3-2232, dated Jan. 20, 1913, for  
PATENT, under the Act of June 11, 1906,  
the same to be known as Homestead Entry Survey No. 206,  
situated within the SITGREAVES National Forest, in  
- surveyed Section 13, Township 9 N., Range 22 E., and  
- surveyed Section - - -, Township - - -, Range - - -,  
- - - - -  
of the G. & S.R.B.& meridian, ARIZONA, and the  
related retracements and resurveys and section subdivisions,  
which are represented in the following field notes as having  
been surveyed by me; and I further solemnly swear that all  
the corners of said survey have been established and perpet-  
uated in strict accordance with the stated special instruc-  
tions, and in the specific manner described in the field  
notes, and that the following are the original field notes  
of such survey.

C. A. Long  
Surveyor-Forest Service

Subscribed and sworn to before me this 23rd day of  
April, 1915.

Elmer C. Myers  
Notary Public





SITGREAVES NATIONAL FOREST

STATE OF ARIZONA

Chains

Applicant for listing, Andrew P. Holland. Application No. 394, dated November 9, 1912. List No. 3-2232, dated January 20, 1913. H. E. No. 022394, made at Phoenix, Arizona, by Andrew P. Holland, dated May 26, 1913.

Surveyed under Special Instructions from the Surveyor General for Arizona, dated June 17, 1914 and supplemental special instructions dated July 22, 1914 and designated as Homestead Entry Survey No. 206.

Situated in Sec. 13, T. 9 N., R. 22 E., Gila and Salt River Base and Meridian, Sitgreaves National Forest, Arizona.

Surveyed under the Acts of June 11, 1906 and June 30, 1914.

---

Survey commenced September 2, 1914 and executed with a W. and L. E. Gurley light mountain transit No. 11920 provided with a full vertical circle and a horizontal limb having two double verniers placed opposite each other and reading to single minutes of arc, which is also the least count of the vernier on the vertical circle.

I examine the adjustments of the transit and make necessary corrections.

All measurements were made on the slopes with a 500 link steel tape and the slope angles determined with a clinometer. The horizontal distances alone appearing in these notes.

---

September 2, 1914.

At the cor. to Secs. 13, 14, 23 and 24, T. 9 N., R. 22 E., which is a malpais stone marked and witnessed



Chains

as described by the Surveyor General. Latitude  $34^{\circ} 10' 20''$  N. Longitude  $109^{\circ} 58' 30''$  W. by account from Land Office map. At 8h. 48.7m., p.m., by my watch which is set for local mean time, I observe Polaris at eastern elongation with telescope direct and reversed in accordance with instructions in the Manual and mark a point in the line thus determined by a tack in a wooden peg driven in the ground 5 chs. N. of my station.

September 3, 1914.

At 7h. 00m., a.m., I turn off the azimuth of Polaris  $1^{\circ} 23' 32''$  to the west, and mark the meridian thus determined by a tack in a stake 5 chs. N. of my station.

The magnetic bearing of the stated meridian at 8h. 30m., a.m., is N.  $14^{\circ} 12'$  W., which corrected for diurnal variation, gives a mean magnetic declination of  $14^{\circ} 10'$  E.

September 3, 1914.

I begin at the cor. to Secs. 13, 14, 23 and 24, heretofore described, and run North.

On a random line bet. Secs. 13 and 14.

40.00 Make search for 1/4 cor.

78.88 Fall, 106 lks. W. of the Cor. to Secs. 11, 12, 13 and 14, which is a malpais stone marked and witnessed as described by the Surveyor General. I return on a true

course S.  $0^{\circ} 46'$  W. on line bet. Secs. 13 and 14 and at 19.72 Set temp. point for 1/16 sec. cor. on W. bdy. NW/4.

39.44 Again make search for 1/4 cor. finding no trace of it.

I re-establish it as follows:

Set a malpais stone 18 x 12 x 9 ins., 10 ins. in the ground for 1/4 sec. cor. marked 1/4 on W. face and a



SITGREAVES NATIONAL FOREST

STATE OF ARIZONA

Chains

cross on top. No bearings, therefore dig pits 18 x 18 x 12 ins. N. and S. of cor. 3 ft. dist. and raise a mound of stone 3 ft. base, 2 ft. high, W. of cor. (No larger stone available for cor.). I continue on course measuring from the sec. cor.

59.16 Set temp. point for 1/16 sec. cor. on W. bdy. SW/4.

69.48 Cross Porter Creek, 20 lks. wide, 1 ft. deep, course W.

78.88 The cor. to Secs. 13, 14, 23 and 24, the place of beginning.

Thence East

On a random line bet. Secs. 13 and 24.

40.32 Fall, 12 lks. N. of the 1/4 cor. on S. bdy. Sec. 13, which is a basalt stone, marked and witnessed as described by the Surveyor General.

I return on a true course N. 89° 50' W. bet. Secs. 13 and 24.

20.16 Set temp. 1/16 cor. on S. bdy. SW/4.

40.32 The Cor. to Secs. 13, 14, 23 and 24, the place of beginning.

September 4, 1914.

I begin at the cor. to Secs. 11, 12, 13 and 14, heretofore described and run east on a random line bet. Secs. 12 and 13.

39.91 Make search for 1/4 sec. cor.

77.47 Fall, 268 lks. S. of the cor. to Secs. 7, 12, 13 and 18, on township line, which is a stone marked and witnessed as described by the Surveyor General.

Thence S. 88° 01' W.

On a true line bet. Secs. 12 and 13.



Chains

19.38 Set temp. 1/16 cor. on N. bdy. NE/4.

38.76 Again make search for 1/4 cor. finding no trace of it.

I reestablish the cor. as follows:- Set a malpais stone 26 x 14 x 8 ins., 16 ins. in the ground, over a stone marked with a cross for 1/4 sec. cor. marked 1/4 on N. face. Dig pits 18 x 18 x 12 ins. E. and W. of cor. 3 ft. dist. and raise a mound of stone 3 ft. base, 2 ft. high N. of cor. whence:

A nail in a juniper 12 ins. dia., bears S. 51°

25' W., 38 lks. dist. marked 1/4 S B T.

No other trees within limits.

Thence South

On a random line through Sec. 13.

80.32 Fall, 51 lks. W. of the 1/4 cor. on S. bdy., Sec. 13.

Thence N. 0° 22' W.

On a true line along the meridional 1/4 sec. line.

40.16 Set temp. point for center 1/4 sec. cor.

80.32 The 1/4 cor. on N. bdy. sec. 13, heretofore described, the place of beginning.

I return to the 1/4 sec. cor. on W. bdy. Sec. 13, and run east.

On a random line through Sec. 13.

77.98 Fall 172 lks. S. of the 1/4 cor. on E. bdy. Sec. 13,

which is a stone marked and witnessed as described by the Surveyor General.

Thence S. 88° 44' W.

On a true line.

Along the latitudinal 1/4 sec. line.

38.51 Intersect the meridional 1/4 sec. line S. 00° 22' E.,

39.83 chs. from the 1/4 cor. on N. bdy., Sec. 13. At



SITGREAVES NATIONAL FOREST

STATE OF ARIZONA

Chains	<p>this point, I set a temp. stake for center 1/4 sec. cor. I continue on course measuring from 1/4 cor. on E. bdy., Sec. 13.</p> <p>48.38 Set temp. point for cor. of the claim.</p> <p>58.25 Set temp. 1/16 cor. on N. bdy. SW/4.</p> <p>78.00 1/4 cor. on W. bdy. Sec. 13, the place of beginning.</p>
	<p>I return to the temp. 1/16 cor. on N. bdy. SW/4 and run South on a random line through the SW/4 Sec.</p> <p>40.00 Fall 13 lks. east of the temp. 1/16 cor. on S. bdy. SW/4.</p> <p>Thence N. 0° 11' E.</p>
	<p>On a true line along the meridional 1/16 sec. line through the SW/4.</p> <p>20.00 Set temp. point for center of SW/4.</p> <p>40.00 The temp. 1/16 cor. on N. bdy. SW/4, the place of beginning.</p>
	<p>I return to the 1/4 cor. on S. bdy. Sec. 13, and run N. 00° 22' W. on the meridional 1/4 sec. line.</p> <p>20.24 Set temp. 1/16 cor. on E. bdy. SW/4.</p> <p>Thence West.</p> <p>On a random line through SW/4.</p> <p>39.93 Fall, 38 lks. N. of the temp. 1/16 cor. on W. bdy. SW/4.</p> <p>Thence N. 89° 27' E.</p>
	<p>On a true line on the latitudinal 1/16 sec. line through SW/4.</p> <p>0.50 Set temp. point for cor. of the claim.</p>



Chains

- 19.96 Intersect the meridional 1/16 sec. line through SW/4  
N. 0° 11' E. 20.00 chs. from the temp. 1/16 cor. on  
S. bdy. SW/4. Set a temp. stake for a cor. of the  
claim and center of the SW/4.
- 29.95 Set temp. point.
- 39.93 The temp. 1/16 cor. on E. bdy. SW/4.

- Thence N. 00° 22' W.  
On the meridional 1/4 sec. line.
- 10.13 Set temp. 1/64 cor. on E. bdy. NE/4 SW/4.
- 20.25 The temp. center 1/4 sec. cor.

- Thence N. 88° 44' E.  
On the latitudinal 1/4 sec. line.
- 14.44 Set temp. stake for cor. of the claim.
- 19.25 Set temp. 1/16 cor. on S. bdy. NE/4.

- Thence North  
On a random line through NE/4.
- 40.09 Fall, 11½ lks. E. of the temp. 1/16 cor. on N. bdy. NE/4,  
I return on a true course S. 0° 10' E. on the meridion-  
al 1/16 sec. line through NE/4.

- 20.04 Set temp. point for center of NE/4.
- 40.09 The temp. 1/16 cor. on S. bdy. NE/4, the place of begin-  
ning.

- September 5, 1914.  
I return to the 1/4 cor. on the E. bdy. of Sec. 13,  
and run North on a random line bet. Secs. 13 and 18.
- 40.36 Fall, 8½ lks. west of the cor. to Secs. 7, 12, 13 and  
18, previously described. I return on a true course



SITGREAVES NATIONAL FOREST

STATE OF ARIZONA

Chains

S. 0° 07' W. bet. Secs. 13 and 18. - 1  
 20.18 Set temp. 1/16 cor. on E. bdy. NE/4.  
 40.36 The 1/4 cor. on E. bdy. Sec. 13, the place of beginning.

I return to the 1/4 cor. on N. bdy. Sec. 13 and run  
 S. 0° 22' E.  
 On a true line along the meridional 1/4 sec. line.  
 19.92 Set temp. 1/16 cor. on W. bdy. NE/4.

Thence N. 88° 20' E.  
 On a true line through NE/4, the temp. 1/16 cor. on  
 E. bdy. NE/4 being plainly visible.

14.47 Set temp. stake opposite point for cor. of the claim.

19.30 Intersect the meridional 1/16 sec. line through NE/4,  
 S. 0° 10' E., 20.08 chs. from the temp. 1/16 cor. on  
 N. bdy. NE/4. Set temp. stake for center of NE/4.

38.60 The temp. 1/16 cor. on E. bdy. NE/4.

From the temp. 1/16 cor. on W. bdy. NE/4, I run S. 88°  
 28' W., on a true line through NW/4. The temp. 1/16  
 cor. on W. bdy. NW/4 being plainly visible.

39.18 The temp. 1/16 cor. on W. bdy. NW/4.

Boundaries of H. E. S. No. 206.

I establish cor. No. 1 on the E. side of road exception  
 and 50 lks. E. of the temp. 1/16 sec. cor. on W. bdy.

SW/4, Sec. 13 as follows:

Set a basalt stone 24 x 6 x 6 ins., 14 ins. in the  
 ground, over a stone marked with a cross for cor. No. 1,



Chains

marked 1 - H E S 206 on side facing claim and a cross on top. Dig pits 24 x 24 x 12 ins. crosswise on this and the succeeding course 7 ft. dist. and raise a mound of stone 3 ft. base, 2 ft. high, 3-1/2 ft. dist.

within claim, whence,

The cor. to Secs. 13 and 14, 23 and 24, bears

S. 02° 13' W., 19.72 chs. dist.

Fence cor. bears N. 75° 00' W., 28 lks. dist.

No bearing trees within limits.

Thence N. 0° 46' E.

Over open level land covered with malpais stone along E. side of 3 wire fence, and E. side of road, except-

ion from W. bdy. NW/4 SW/4 and SW/4 NW/4.

19.72 The 1/4 cor. on W. bdy. Sec. 13, bears west 50 lks.

20.00 Cross wire fence, continue along W. side.

38.00 Cor. of wire fence bears E. 20 lks. from which fences bear E. and S.

38.94 To Cor. No. 2 on South and East sides of road exceptions.

Set a malpais stone 19 x 9 x 7 ins., 9 ins. in the

ground, over a stone marked with a cross for cor. No.

2 marked 2 - H E S 206 on side facing claim and a cross

on top. No bearings, therefore, dig pits 24 x 24 x

12 ins. crosswise on this and the succeeding course

7 ft. dist. and raise a mound of stone 4 ft. base,

3 ft. high, 3-1/2 ft. dist. within claim.

Fence cor. bears S. 12° 08' W., 35 lks. dist.

from which fences bear N. and E.

Fence cor. bears S. 21° 48' E., 93 lks. dist.

from which fences bear E. and S.

Fence cor. bears S. 62° 05' W., 80 lks. dist.

from which fences bear N. and W.

(No larger stone available for cor.)



SITGREAVES NATIONAL FOREST

STATE OF ARIZONA

Chains

Thence N. 88° 28' E. 308.25 chs. - A  
Over open level land along S. side of road exception  
from N. bdy. S/2 NW/4. The patented claim of James  
E. Porter, extends to the latitudinal 1/16 sec. line  
through NW/4, and 50 lks. N. of the N. bdy. of this  
claim. Wire fence is 20 lks. S. and bears with line.

38.68 To Cor. No. 3.  
On S. side of road exception.  
Set a basalt stone 20 x 6 x 4 ins., 10 ins. in the  
ground, over a stone marked with a cross for cor. No. 3  
marked 3 - H E S 206 on side facing claim and a  
cross on top. No bearings, therefore dig pits 24 x 24  
x 12 ins. crosswise on this and the succeeding course,  
7 ft. dist. and raise a mound of earth 4 ft. base, 2  
ft. high, 3-1/2 ft. dist. within claim.  
The 1/4 cor. on N. bdy. Sec. 13 bears  
N. 0° 22' W., 20.42 chs. dist.  
(No larger stone available for cor).

---

Thence N. 88° 20' E.  
Over open level land.  
Along S. side of road exception and N. side of wire  
fence 20 lks. dist. which bears with line. The patent-  
ed claim of James E. Porter is 50 lks. N. of the N.  
bdy. of this claim.

14.47 To Cor. No. 4.  
On S. side of road exception.  
Set a red iron stone 24 x 16 x 3 ins., 14 ins. in the  
ground, over a stone marked with a cross for cor.



Chains

No. 4 marked 4 - H E S 206 on side facing claim and a cross on top. No bearings, therefore, dig pits 24 x 24 x 12 ins. crosswise on this and the succeeding course, 7 ft. dist. and raise a mound of earth 3 ft. base, 2 ft. high, 3-1/2 ft. dist. within claim.

I adopt mean courses and distances within the SW/4 NE/4. Thence S. 0° 13' E.

Over open level land.

0.65 Sheep proof wire fence, bears E. and W.

1.25 3 wire fence bears E. and W. Continue along W. side of fence, 10 lks. dist.

19.49 To Cor. No. 5 on the latitudinal 1/4 sec. line.

Set a malpais stone 25 x 12 x 9 ins., 15 ins. in the ground, over a stone marked with a cross for cor. No. 5, marked 5 - H E S 206 on side facing claim and a cross on top. Dig pits 24 x 24 x 12 ins. crosswise on this and the succeeding course, 7 ft. dist. and raise a mound of stone 3 ft. base, 2 ft. high, 3-1/2 ft. dist. within claim, whence:

A nail in a yellow pine 17 ins. dia., bears

N. 77° 49' E., 70 lks. dist.

A nail in a yellow pine 12 ins. dia., bears

S. 34° 35' W., 80 lks. dist.

A nail in a white oak 7 ins. dia., bears

N. 16° 35' W., 48 lks. dist.

Each blazed and scribed 5 H E S 206 B T.

Fence cor. bears S. 02° 20' E., 160 lks. dist.

The 1/4 cor. on E. bdy. Sec. 13, bears N. 88°

44' E., 24.07 chs. dist.



SITGREAVES NATIONAL FOREST

STATE OF ARIZONA

Chains	September 6, 1914.
24.31	Thence S. 88° 44' W. 8 marked 8 - H E S 206 on side facing claim and a cross on top. No bearings, therefore, dig pits 24 x 24 x 12 ins. crosswise on this and the succeeding course, 7 ft. dist. and raise a mound of stone 3 ft. base, 2 ft. high, 3-1/2 ft. dist. within claim.
	Over open level land, along latitudinal 1/4 sec. line.
	To Cor. No. 6.
	Set a malpais stone 19 x 12 x 5 ins., 10 ins. in the ground, over a stone marked with a cross for cor. No. 6 marked 6 - H E S 206 on side facing claim and a cross on top. No bearings, therefore, dig pits 24 x 24 x 12 ins. crosswise on this and the succeeding course, 7 ft. dist. and raise a mound of stone 3 ft. base, 2 ft. high, 3-1/2 ft. dist. within claim.
	(No larger stone available for cor.)
	I adopt mean courses and distances within NE/4. SW/4.
	Thence S. 0° 06' E. 84 x 84 x 18 line crosswise on this and the succeeding course, 7 ft. dist. and raise a mound of stone 3 ft. base, 2 ft. high, 3-1/2 ft. dist. within claim.
	Over open level land.
10.06	To Cor. No. 7.
	Set a malpais stone 24 x 10 x 5 ins., 14 ins. in the ground, over a stone marked with a cross for cor. No. 7 marked 7 - H E S 206 on side facing claim and a cross on top. No bearings, therefore dig pits 24 x 24 x 12 ins. crosswise on this and the succeeding course, 7 ft. dist. and raise a mound of stone 3 ft. base, 2 ft. high, 3-1/2 ft. dist. within claim.
	Thence S. 89° 05' W.
	On a mean course.
	Over open level land.
9.93	To Cor. No. 8.
	Set a malpais stone 20 x 12 x 5 ins., 10 ins. in the



Chains

ground, over a stone marked with a cross for cor. No. 8 marked 8 - H E S 206 on side facing claim and a cross on top. No bearings, therefore, dig pits 24 x 24 x 12 ins. crosswise on this and the succeeding course 7 ft. dist. and raise a mound of stone 3 ft. base, 2 ft. high, 3-1/2 ft. dist. within claim. (No larger stone available for cor.) -

---

10.00 Thence S. 0° 11' W. along E. bdy. SE/4 NW/4 SW/4. Over open level land.

10.00 To Cor. No. 9. Set a malpais stone 24 x 8 x 4 ins., 14 ins. in the ground, over a stone marked with a cross for cor. No. 9 marked 9 - H E S 206 on side facing claim and a cross on top. No bearings, therefore, dig pits 24 x 24 x 12 ins. crosswise on this and the succeeding course, 7 ft. dist. and raise a mound of stone 3 ft. base, 2 ft. high, 3-1/2 ft. dist. within claim.

---

10.00 Thence S. 89° 27' W. Over open level land along latitudinal 1/16 sec. line, through SW/4. Wire fence is 5 lks. S. and bears with line.

10.00 Cross wire fence. Continue along S. side.

19.46 To Cor. No. 1, the place of beginning.

AREA

Area H. E. S. No. 206

151.37 acres



SITGREAVES NATIONAL FOREST

STATE OF ARIZONA

Chains

IMPROVEMENTS

The improvements made upon this claim and belonging to

the claimant herein, consist of the following:-

A frame shack, 12 x 12 ft., course of side N. and S.,  
the SE. cor. of which bears from Cor. No. 5, N. 78°  
12' W. 120 lks. dist.

Value \$50.00

Two and one-fourth miles of wire fence.

Value \$125.00

Total value of improvements. \$175.00

DESCRIPTION

This claim is located on a level mesa covered with mal-  
pais stone. The soil is a brown adobe and very fer-  
tile. None has been under cultivation heretofore.

There is no water, timber or mineral on the claim, but  
it is susceptible of irrigation from Porter Creek,  
which flows near the claim.

Lakeside, an inland village, is the nearest postoffice  
and trading center, and is two miles south of the  
claim and is reached by a rough wagon road.

CONFLICTS AND ADJOINING CLAIMS

There are no conflicts. The patented claim of James E.  
Porter joins the road exception on the north and the  
patented claim of Harrison W. Alstadt joins the claim  
on the south.



Chains

TRAVERSE

Cor.	Course	Dist.	N.	S.	E.	W.
1-2	N. 0° 46' E.	38.94	38.94		52	
2-3	N. 88° 28' E.	38.68	1.04		38.67	
3-4	N. 88° 20' E.	14.47	.42		14.46	
4-5	S. 0° 13' E.	19.49		19.49	.07	
5-6	S. 88° 44' W.	24.31		.54		24.30
6-7	S. 0° 06' E.	10.06		10.06	.02	
7-8	S. 89° 05' W.	9.93		.16		9.93
8-9	S. 0° 11' W.	10.00		10.00		.03
9-1	S. 89° 27' W.	19.46		.19		19.46
			40.40	40.44	53.74	53.72
Error in Lat. and Dep.				40.40	53.72	
				.04	.02	

Error of closure 1:4340.

Survey completed September 7, 1914.

DESCRIPTION

This claim is located on a level mesa covered with malpais stone. The soil is a brown silt and very fertile. There is no water, timber or mineral on the claim, but it is susceptible of irrigation from Porter Creek, which flows near the claim. Lakeside, an inland village, is the nearest postoffice and trading center, and is two miles south of the claim and is reached by a rough wagon road.

*C. Long*  
Surveyor - Forest Service.

CONFLICTS AND ADJOINING CLAIMS

There are no conflicts. The patented claim of James H. Porter joins the road exception on the north and the patented claim of Harrison W. Alstead joins the claim on the south.



DIRECTIONS.—1. Carry out calculations to two decimals only.

2. In balancing Latitudes and Departures do not obliterate or change the original figures.

Put the corrected figure or figures above in red ink. Do not change the footing of the original figures, but put below them the corrected footing in red ink.

The corrections for balancing fallings should be proportional to the lengths of the lines.

3. In calculations of fallings take result to nearest link. In calculations of N. and S. areas drop all after second decimal. Surveyors are required to use the Standard Field Tables issued by the G. L. O.

4. Only three copies of this tabulation are necessary, for the District Office, the Surveyor General, and the Commissioner.

TABLING AND CALCULATIONS OF HOMESTEAD ENTRY SURVEY NO. 206, STATE OF ARIZONA

CORNERS.	BEARING.	DISTANCE.	LATITUDES.		DEPARTURES.		DOUBLE M. D.	N. AREAS.	S. AREAS.
			NORTH.	SOUTH.	EAST.	WEST.			
	N. 0° 46' E.	38.94	38.94 <sup>45</sup>		.52 <sup>51</sup>		51	19.86 <sup>✓</sup>	
	N. 88° 28' E.	38.68	1.04 <sup>86</sup>		38.67		39.69	41.67 <sup>✓</sup>	
	N. 88° 20' E.	14.47	.42		14.46		92.82	38.98 <sup>✓</sup>	
	S. 0° 13' E.	19.49		19.49 <sup>48</sup>	.07		107.35		2091.18 <sup>✓</sup>
	S. 88° 44' W.	24.21		.54 <sup>53</sup>	.02	24.20	83.11		44.05 <sup>✓</sup>
	S. 0° 06' E.	10.06		10.06			58.82		591.73 <sup>✓</sup>
	S. 89° 05' W.	9.93		.16		9.93	48.91		7.83 <sup>✓</sup>
	S. 0° 11' W.	10.00		10.00		.03	38.95		389.50 <sup>✓</sup>
	S. 89° 27' W.	19.46		.19		19.46	19.46		3.70 <sup>✓</sup>
		185.34	40.40	40.44	53.74	53.72		100.51	3127.99
			40.42	40.42	53.73	53.73			100.51
			Closing error 1.4340						20/3027.48
									151.37 acres

59

2711



COUNTY	BEARING	DISTANCE	TALMAGES			DEBITABLES		DOUBLES W. D.	N. ACREA	S. ACREA
			Moran	South	Frank	Frank	Frank			
CLOSING DISTRICT J. 1240			50.50	50.50	50.50	50.50	100.00		100.00	
		22.85	22.85	22.85	22.85	22.85	22.85	22.85	22.85	22.85
	2. 25. 00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00
	2. 00. 11	00.00	00.00	00.00	00.00	00.00	00.00	00.00	00.00	00.00
	2. 25. 00	3. 25	3. 25	3. 25	3. 25	3. 25	3. 25	3. 25	3. 25	3. 25
	2. 00. 11	00.00	00.00	00.00	00.00	00.00	00.00	00.00	00.00	00.00
	2. 25. 00	13.43	13.43	13.43	13.43	13.43	13.43	13.43	13.43	13.43
	2. 00. 11	00.00	00.00	00.00	00.00	00.00	00.00	00.00	00.00	00.00
	2. 25. 00	13.43	13.43	13.43	13.43	13.43	13.43	13.43	13.43	13.43
	2. 00. 11	00.00	00.00	00.00	00.00	00.00	00.00	00.00	00.00	00.00
	2. 25. 00	13.43	13.43	13.43	13.43	13.43	13.43	13.43	13.43	13.43
	2. 00. 11	00.00	00.00	00.00	00.00	00.00	00.00	00.00	00.00	00.00
	2. 25. 00	13.43	13.43	13.43	13.43	13.43	13.43	13.43	13.43	13.43
	2. 00. 11	00.00	00.00	00.00	00.00	00.00	00.00	00.00	00.00	00.00
	2. 25. 00	13.43	13.43	13.43	13.43	13.43	13.43	13.43	13.43	13.43
	2. 00. 11	00.00	00.00	00.00	00.00	00.00	00.00	00.00	00.00	00.00
	2. 25. 00	13.43	13.43	13.43	13.43	13.43	13.43	13.43	13.43	13.43
	2. 00. 11	00.00	00.00	00.00	00.00	00.00	00.00	00.00	00.00	00.00
	2. 25. 00	13.43	13.43	13.43	13.43	13.43	13.43	13.43	13.43	13.43

STATE OF VERMONT

DEPARTMENT OF LANDS AND FORESTRY

OFFICE OF THE REGISTER

1. All the copies of this report for the year 1900, for the District Office, the State Office, and the Commission. 2. In consideration of which the land is sold to the State, and 3. There shall be no further claims against the land. All the proceeds of the sale of the land shall be paid to the State. The land is sold to the State for the purpose of raising money for the improvement of the land. The land is sold to the State for the purpose of raising money for the improvement of the land. The land is sold to the State for the purpose of raising money for the improvement of the land.

RECORDED



APPROVAL

Office of the United States Surveyor General,

Phoenix, Arizona, March 8, 1917


The foregoing field notes of Homestead Entry Survey No.

206

executed by C. A. Long, Surveyor Forest Service

[Forest Service Title.]

under his special instructions, dated June 17, 1914, having  
and supplemental instructions dated July 22, 1914, having  
been critically examined, and the necessary corrections and explanations  
made, the said field notes, and the surveys they describe, are hereby  
approved.



U. S. Surveyor General.

I certify that the foregoing transcript of the field notes of the  
above-described survey in the State of Arizona, , has been  
correctly copied from the original notes on file in this office.

Frank P. Trott.

U. S. Surveyor General.