

U. S. DEPARTMENT OF AGRICULTURE
FOREST SERVICE

63
MAY 1914

FIELD NOTES

OF

HOMESTEAD ENTRY SURVEY NO. 207

SITUATED IN THE

SITGREAVES NATIONAL FOREST

ADMINISTRATIVE DISTRICT NO. 3

in

Section 8, surveyed, Township 9 N., Range 22 E.

of the

Gila and Salt River Base and Meridian.

ARIZONA

Survey executed by C. A. Long, Surveyor - Forest Service

Under special instructions dated June 16, 1914

and supplemental special instructions dated July 22, 1914

Survey commenced August 26, 1914

Survey completed August 31, 1914

Under Acts of June 11, 1906 and June 30, 1914.

Applicant for listing H. H. Whipple,

Residence Show Low, Arizona

Application No. 383, dated August 15, 1912


List No. 3-2461, dated April 10, 1913

Applicant for survey H. H. Whipple,

Residence Show Low, Arizona

H. E. No. _____, dated _____

Land district Phoenix, Arizona



64

OATH OF ASSISTANTS

We hereby certify that we assisted C. A. Long,
Surveyor - Forest Service in surveying all those
parts or portions of Homestead Entry Survey No. 207, in
surveyed Section 8, Township 9 N., Range 22 E.,
surveyed Section ---, Township ---, Range ---,

of the G. & S. R. B. & --- meridian, State of ARIZONA, which
are represented in the following field notes as having been
surveyed by him and under his direction; and that said sur-
vey has been in all respects, to the best of our knowledge
and belief, well and faithfully surveyed, and the corner
monuments established, according to the instructions fur-
nished by the United States Surveyor General for ARIZONA

Note: It would have been
very expensive and incon-
venient to appear before
an officer to administer
the oaths to Assistants;
hence, they were taken
by the Surveyor.

Wm Wanner Chainman

Fred Burley Chainman

Subscribed and sworn to before me this 31st day of
August, 1914.

C. A. Long
Surveyor - Forest Service

OATH OF SURVEYOR

I, C. A. Long, Surveyor-Forest Service, do solemnly swear
that, in strict conformity with the special instructions of
the United States Surveyor General for ARIZONA dated June 16, 1914 & supp'l
instrs. dated July 22 1914, and the laws of the United States, I have
well, faithfully, and truly, in my own proper person, sur-
veyed a tract of land ~~upon the application of~~ embraced in
List, No. 3-2461 dated April 10, 1913, for
PATENT, under the Act of June 11, 1906,
the same to be known as Homestead Entry Survey No. 207,
situated within the SITGREAVES National Forest, in
surveyed Section 8, Township 9 N., Range 22 E., and
surveyed Section ---, Township ---, Range ---,

of the G. & S. R. B. & --- meridian, ARIZONA, and the
related retracements and resurveys and section subdivisions,
which are represented in the following field notes as having
been surveyed by me; and I further solemnly swear that all
the corners of said survey have been established and perpet-
uated in strict accordance with the stated special instruc-
tions, and in the specific manner described in the field
notes, and that the following are the original field notes
of such survey.

C. A. Long
Surveyor-Forest Service

Subscribed and sworn to before me this 23rd day of

April, 1915.

Elsie C. Myers
Notary Public



SITGREAVES NATIONAL FOREST

STATE OF ARIZONA

Chains

Applicant for listing H. H. Whipple; Application No. 383, dated August 15, 1912; List No. 3-2461, dated April 10, 1913. Entry not yet made.

Surveyed under special instructions from the Surveyor General for Arizona, dated June 16, 1914 and supplemental special instructions dated July 22, 1914 and designated as Homestead Entry Survey No. 207.

Situated in Section 8, T. 9 N., R. 22 E., G. and S. R. B. and M., Sitgreaves National Forest, Arizona.

Surveyed under the Acts of June 11, 1906 and June 30, 1914.

Survey commenced August 26, 1914 and executed with a W. and L. E. Gurley light mountain transit No. 11920, provided with a full vertical circle and a horizontal

limb having two double verniers, placed opposite each other and reading to single minutes of arc, which is also the least reading of the verniers, on the vertical circle.

I test the adjustments of the transit and make necessary corrections.

All measurements were made on the slopes with a 500 link steel tape, and the slope angles determined with a clinometer, the horizontal distances alone appearing in these notes.

August 26, 1914.

At the 1/4 sec. cor. bet. secs. 8 and 9, T. 9 N., R. 22 E., which is an oak post, marked and witnessed as described by the Surveyor General; in latitude 34° 12' N., longitude 110° 01' 30" W., by account from a Land Office map. At 9h. 16.m., p.m., by my watch

Chains

which is set for local mean time, I observe Polaris at Eastern elongation, in accordance with instructions in the Manual, and mark a point in the line thus determined, by a tack in a stake, driven in the ground, 5 chs. N. of my station.

August 27, 1914.

At 7h. 00m., a.m., I turn off the Azimuth of Polaris $1^{\circ} 23' 38''$ to the West, and mark the meridian thus determined by a tack in a wooden stake driven in the ground, 5 chs. N. of my station.

The Magnetic bearing of the stated meridian at 8h. 30m. a.m., is N. $14^{\circ} 30' W.$, corrected for diurnal variation gives the mean magnetic declination $14^{\circ} 26' E.$

From the $1/4$ sec. cor. bet. secs. 8 and 9, heretofore described, I run south on a random line bet. secs. 8 and 9.

39.30 Fall 31 lks. West of the cor. to secs. 8, 9, 16 and 17, which is a stone, marked and witnessed as described by the Surveyor General. Therefore the bearing of the line bet. secs. 8 and 9 is S. $0^{\circ} 27' E.$, 39.30 chs. I move to section cor.

Thence West.

On a random line bet. secs. 8 and 17.

39.30 Fall $18-1/2$ lks. south of this $1/4$ cor. bet. secs. 8 and 17, which is a stone marked and witnessed as described by the Surveyor General. Therefore the bearing of line bet. secs. 8 and 17 is N. $89^{\circ} 44' W.$ 39.30 chs. I move to the $1/4$ sec. cor.

Thence North.

On a random line through Section 8.

SITGREAVES NATIONAL FOREST

STATE OF ARIZONA

Chains	
79.36	Fall 175 lks. East of the 1/4 cor. bet. secs. 5 and 8, which is a stone, marked and witnessed as described by the Surveyor General.
	I return on a true course S. 1° 16' E., on the meridional 1/4 sec. line, and at
39.69	Set temp. point for center of sec.
79.38	The 1/4 sec. cor. on S. bdy. sec. 8.
<hr/>	
	Thence S. 89° 44' E.
	On a true line bet. secs. 8 and 17.
19.65	Set temp. 1/16 cor. on S. bdy. SE/4.
39.30	The cor. to secs. 8, 9, 16 and 17, heretofore described.
<hr/>	
	Thence N. 0° 27' W.
	On a true line bet. secs. 8 and 9.
19.65	Set temp. 1/16 cor. on E. bdy., SE/4.
34.39	Set temp. point.
39.30	The 1/4 cor. bet. secs. 8 and 9, the place of beginning.
<hr/>	
	August 28, 1914.
	I begin at the cor. to secs. 5, 6, 7 and 8, T. 9 N., R. 22 E., which is a stone firmly set, marked and witnessed as described by the Surveyor General.
	Thence South.
	On a random line, bet. secs. 7 and 8.
40.00	Make careful search for the 1/4 cor. bet. secs. 7 and 8.
79.15	Fall 164 lks. West of the cor. to secs. 7, 8, 17 and 18, which is a stone, firmly set, marked and witnessed as described by the Surveyor General.
	I return on a true course, N. 1° 11' W., bet. secs. 7 and 8.

Temp. pt. in sec. 8, SE/4. 9/15/14
Set 1/8.

Chains

39.58 Again make search for 1/4 cor., finding no trace of it;

I reestablish it as follows: Set a sandstone

24 x 14 x 5 ins., 14 ins. in the ground, for 1/4

sec. cor., marked 1/4 on W. face, from which:

A nail in a white oak, 16 ins. dia., bears

S. 79° 13' W., 56 lks. dist.

A nail in a white oak, 16 ins. dia., bears

N. 42° 02' W., 46 lks. dist.

A nail in a white oak, 24 ins. dia., bears

N. 46° 45' E., 51 lks. dist.

Each blazed and scribed 1/4 S B T.

Thence East.

On a random line through sec. 8.

79.58 Fall 65 lks. North of the 1/4 cor. bet. secs. 8 and 9,
heretofore described.

I return on a true course N. 89° 32' W. on the lati-
tudinal 1/4 sec. line, and at

39.81 Intersect the meridional 1/4 sec. line S. 1° 16' E.,

39.82 chs. from the 1/4 sec. cor. on N. bdy. Sec. 8,

and N. 1° 16' W., 39.56 chs. from the 1/4 sec. cor.

on S. bdy. Sec. 8. Set a temp. stake for center
of sec.

Thence S. 1° 16' E.

On the meridional 1/4 sec. line.

19.78 Set temp. 1/16 cor. on W. bdy. SE/4.

Thence East.

On a random line through SE/4.

39.48 Fall 24 lks. North of the temp. 1/16 cor. on E. bdy.

SE/4.

SITGREAVES NATIONAL FOREST

STATE OF ARIZONA

Chains

Thence N. 89° 39' W.

On a true line on the latitudinal 1/16 sec. line,
through SE/4.

9.87 Set temp. 1/64 cor. on S. bdy. NE/4 SE/4 and what will
be a corner of the claim.

19.74 Set temp. point for center of SE/4.

39.48 The temp. 1/16 cor. on W. bdy. SE/4 and place of
beginning.

From the 1/4 cor. bet. secs. 8 and 9, heretofore de-
scribed, I run N. 89° 32' W.

On a true line on the latitudinal 1/4 sec. line.

9.95 Set temp. 1/64 cor. on N. bdy. NE/4 SE/4.

19.90 Set temp. 1/16 cor. on N. bdy. SE/4.

Thence South.

On a random line through SE/4.

39.44 Fall 64 lks. West of the temp. 1/16 cor. on S. bdy.
SE/4.

Thence N. 0° 55' W.

On a true course, on the meridional 1/16 sec. line
through SE/4.

19.67 Intersect the latitudinal 1/16 sec. line through SE/4,
N. 89° 39' W., 19.74 chs. from the temp. 1/16 cor.
on E. bdy. SE/4.

34.50 Set temp. point for a cor. of the claim.

39.44 The temp. 1/16 cor. on N. bdy. SE/4, the place of
beginning.

From the temp. 1/64 cor. on N. bdy. NE/4 SE/4 I run
south on a random line through NE/4 SE/4.

SITGREAVES NATIONAL FOREST

STATE OF ARIZONA

Chains	
19.71	<p>Fall 22-1/2 lks. West of the temp. 1/64 cor. on S. bdy. NE/4 SE/4.</p> <p>Thence N. 0° 39' W. On a true line on the meridional 1/64 sec. line through NE/4 SE/4.</p>
19.71	<p>The temp. 1/64 cor. on N. bdy. NE/4 SE/4, the place of beginning.</p>
<p>From the temp. point set S. 0° 27' E., 4.91 chs. from the 1/4 cor. bet. Secs. 8 and 9, I run West on a random line.</p>	
19.86	<p>Fall 15 lks. south of the temp. point, set S. 0° 55' E. 4.94 chs. from the temp. 1/16 cor. on N. bdy. SE/4. Thence S. 89° 34' E.</p>
<p>On a true line.</p>	
9.93	<p>Intersect the meridional 1/64 line through the NE/4 SE/4 at S. 0° 39' E. 4.93 chs. from temp. 1/64 cor. on N. bdy. NE/4 SE/4. Set a temp. point for cor. No. 9 of the claim.</p>
<p>August 29, 1914.</p>	
<p>Bdys. of H. E. S. 207.</p>	
<p>I proceed to the cor. to secs. 8, 9, 16 and 17, heretofore described, and set a brown sandstone 24 x 14 x 8 ins., 14 ins. in the ground over a stone marked with a + along side the sec. cor. for Cor. No. 1 of this survey, marked 1 - H E S 207 on side facing the claim and a + on top. Dig pits 24 x 24 x 12 ins.</p>	
<p>crosswise on this and the succeeding course 7 ft. dist. and raise a mound of earth and stone 3 ft. base, 2 ft. high, 3-1/2 ft. dist. within the claim, whence:</p>	

SITGREAVES NATIONAL FOREST

STATE OF ARIZONA

Chains

A nail in a yellow pine 12' ins. dia., bears

N. 13° 00' W., 50 lks. dist.

A nail in a juniper 16 ins. dia., bears S. 0°
20' E., 26 lks. dist.

Each blazed and scribed 1 H E S 207 B.T.

A yellow pine 14 ins. dia., bears N. 75° 18' W.,
55 lks. dist. marked T 9 N R 22 E S 8 B T.

A yellow pine 13 ins. dia., bears S. 35° 10' W.,
48 lks. dist. marked T 9 N R 22 E S 17 B T.

A yellow pine 8 ins. dia., bears S. 82° 25' E.
38 lks. dist., marked T 9 N R 22 E S 16 B T.

Thence N. 89° 44' W.

Over level land through heavy pine timber bet. secs.

8 and 17.

1.42 To Cor. No. 2.

Set a brown sandstone 24 x 14 x 8 ins., 14 ins. in
the ground, over a stone marked with a + for cor.

No. 2 of this survey, marked 2 - H E S 207 on side

facing the claim and a + on top. Dig pits 24 x 24 x 12
ins. crosswise on this and the succeeding course 7

ft. dist. and raise a mound of earth and stone 3 ft.

base, 2 ft. high, 3-1/2 ft. dist., within the claim,

whence:

A nail in a yellow pine 12 ins. dia., bears

North 37 lks. dist.

A nail in a yellow pine 14 ins. dia., bears

N. 77° 35' E., 72 lks. dist.

Each blazed and scribed 2 H E S 207 B.T.

The above cor. is set alongside a brown sandstone 14 x

12 x 5 ins. above ground, marked I. R. on W. face

and CC. on E. face, being the closing cor. of the

North bdy. of the White Mountain Indian Reservation

with the line bet. secs. 8 and 17.

Chains

Thence, N. 31° 46' W.

Along the North bdy. White Mountain Indian Reserva-
tion. Over level land through heavy stand of yellow
pine.

1.81 To Cor. No. 3.

Set a brown sandstone 24 x 12 x 8 ins., 14 ins. in
the ground, over a stone marked with a + for Cor. No.
of this survey, marked 3 - H E S 207 on side facing
the claim and a + on top. Dig pits 24 x 24 x 12 ins.
crosswise on this and the succeeding course, 7 ft.
dist. and raise a mound of earth and stone 3 ft.
base, 2 ft. high, 3-1/2 ft. dist. within the claim,
whence:

A nail in a yellow pine 20 ins. dia., bears

S. 53° 42' E., 34 lks. dist.

A nail in a yellow pine, 16 ins. dia., bears

N. 43° 16' E., 128 lks. dist.

Each blazed and scribed 3 H E S 207 B T

A yellow pine 20 ins. dia., bears S. 41° 45' E.,

31 lks., marked A P 372 B T.

A yellow pine 14 ins. dia., bears N. 81° 32' W.

69 lks., marked A P 372 B T.

Cor. No. 3 is set alongside a sandstone showing 6 x 12
x 5 ins. above ground and marked A P N B W M I R 372
on W. face and B M F R on E. face, being Cor. No. 372
of the White Mountain Apache Indian Reservation.

Thence N. 10° 45' W.

Along the North bdy. of the White Mountain Indian
Reservation, over level land, through heavy stand
of yellow pine. Cor. No. 4 will fall in irrigation
ditch, therefore set witness corner.

SITGREAVES NATIONAL FOREST

STATE OF ARIZONA

Chains

2.02

W. C. to Cor. No. 4.

Set a sandstone 22 x 10 x 10 ins., 12 ins. in the ground, over a stone marked with a + for witness cor. to Cor. No. 4, marked WC - 4 H E S 207 on side facing the claim and a + on top. Pits and mounds impracticable. (No larger stone available for cor). Whence:

A nail in a yellow pine 12 ins. dia., bears N. 9° 28' W., 26 lks. dist.

A nail in a yellow pine 14 ins. dia., bears S. 73° 30' E., 26 lks. dist.

Each blazed and scribed W C 4 H E S 207 B T.

3.16

True point for cor. No. 4 falls in center of pine stump

on edge of irrigation ditch, the tree was felled in constructing ditch, the side visible is marked

A P N B W M I R 373.

Thence N. 51° 38' W.

Along N. bdy. White Mountain Indian Reservation, over level land, through heavy stand of yellow pine.

0.76

W. C. to Cor. No. 4.

Set a sandstone 22 x 14 x 4 ins., 12 ins. in the ground, over a stone marked with a + for witness cor. to cor. No. 4, marked WC-4- H E S 207 on side facing the claim and a + on top. Dig pits 24 x 24 x 12 ins.

crosswise on this and the succeeding course, 7 ft. dist. and raise a mound of earth and stone 3 ft. base, 2 ft. high, 3-1/2 ft. dist., within the claim, (no larger stone available for cor.) whence:

A nail in a yellow pine 18 ins. dia., bears N. 25° 29' W., 76 lks. dist.

A nail in a yellow pine 12 ins. dia., bears S. 29° 09' W., 52 lks. dist.

Each blazed and scribed W C 4 H E S 207 B T

SITGREAVES NATIONAL FOREST

STATE OF ARIZONA

Chains	
1.00	Reservation wire fence bears NW. and SE.
6.65	Reservation wire fence bears N. 55° 00' W. and S. 55° 00' E.
7.30	Leave pine, enter juniper timber.
12.00	To Cor. No. 5. Set a sandstone 22 x 12 x 6 ins., 12 ins. in the ground, over a stone marked with a + for Cor. No. 5 of this survey, marked 5 - H E S 207 on side facing the claim and a + on top. Dig pits 24 x 24 x 12 ins., crosswise on this and the succeeding course, 7 ft. dist. and raise a mound of earth and stone, 3 ft. base, 2 ft. high, 3-1/2 ft. dist. within the claim, whence: A nail in a blackjack 8 ins. dia., bears S. 82° 00' E., 50 lks. dist. A nail in a pinon, 6 ins. dia., bears N. 04° 10' E., 62 lks. dist. Each blazed and scribed 5 H E S 207 B T. (No larger stone available for cor). Cor. No. 5 of this claim is set alongside a juniper 12 ins. dia., marked B M F R on N. face and A P N B W M I R 374 on S. face, being an angle point in the North bdy. of the White Mountain Apache Indian Reservation. Thence N. 37° 27' W. Over level land, through thick juniper and buck brush, leave Indian Reservation bdy.
5.00	Ascend 15 ft.
13.69	Top of slope. Leave buck brush and juniper, enter scattering pine reproduction, continue over level land.

SITGREAVES NATIONAL FOREST

STATE OF ARIZONA

Chains

15.00 Ascend 10 ft., through heavy pine timber.

24.39 To Cor. No. 6.

Identical with list cor. No. 6, which is a sandstone

12 x 6 x 5 ins. above ground, marked and witnessed

as described by the Forest Service. I destroy it

and witnesses thereto, and set a sandstone 24 x 16

x 10 ins., 14 ins. in the ground, over a stone marked

with a + for cor. No. 6 of this survey, marked

6 - H E S 207 on side facing the claim, and a + on top.

Dig pits 24 x 24 x 12 ins., crosswise on this and

the succeeding course 7 ft. dist. and raise a mound

of earth 3 ft. base, 2 ft. high, 3-1/2 ft. dist.

within the claim, whence:

A nail in a yellow pine 16 ins. dia. bears

S. 24° 04' E., 83 lks. dist.

A nail in a juniper 8 ins. dia., bears

S. 67° 17' E., 45 lks. dist.

Each blazed and scribed 6 H E S 207 B T.

Thence N. 40° 56' E.

Through scattering juniper, oak and large yellow

pine. Descend 35 ft.

10.65 To Cor. No. 7.

Identical with the temp. 1/16 cor. on N. bdy. SE/4,

set a sandstone 20 x 16 x 6 ins., 10 ins. in the

ground, over a stone marked with a + for cor. No. 7,

and 1/16 sec. cor., marked 1/16 on N. face and

7 - H E S 207 on side facing the claim and a + on top,

whence:

A nail in a yellow pine 16 ins. dia. bears

S. 88° 17' W. 120 lks. dist.

Chains

A nail in a yellow pine 16 ins. dia., bears
N. 89° 05' W., 28 lks. dist.

A nail in a yellow pine 22 ins. dia., bears
S. 45° 07' W., 57 lks. dist.

Each blazed and scribed 7 H E S 207 B T

Fence cor. bears N. 28° 03' W., 21 lks. dist.

from which 3 wire fence bears N. and E.

List cor. No. 5, which is a sandstone 12 x 5 x 4 ins.

above ground, marked and witnessed as described

by the Forest Service, bears N. 64° 00' E., 32 lks.

dist. I destroy it and all witnesses thereto.

(No larger stone available for cor.)

August 30, 1914.

Thence S. 0° 55' E.

Along the meridional 1/16 sec. line through the SE/4.

Over level land, through large pine timber, between

Lists 3-1614 and List 3-2461.

4.94 To Cor. No. 8.

Identical with the temp. point previously set by

me in subdividing the SE/4. Set a sandstone 24 x

8 x 3 ins., 14 ins. in the ground over a stone

marked with a cross for Cor. No. 8 of this survey,

marked 8 - H E S 207 on side facing the claim and

a + on top. Dig pits 24 x 24 x 12 ins. crosswise on

this and the succeeding course, 7 ft. dist. and

raise a mound of earth 3 ft. base, 2 ft. high, 3-1/2

ft. dist. within the claim, whence:

A nail in a juniper 30 ins. dia., bears

S. 14° 51' E., 79 lks. dist.

A nail in a yellow pine 33 ins. dia., bears

S. 88° 17' W., 120 lks. dist.

SITGREAVES NATIONAL FOREST

STATE OF ARIZONA

Chains

Each blazed and scribed 8 H E S 207 B T
List cor. No. 4, which is a sandstone 15 x 10 x 8 ins.
above ground, marked and witnessed as described by
the Forest Service bears N. 55° 50' E., 25 lks.
dist. I destroy it and all witnesses thereto.

Thence S. 89° 34' E.

Bet. List 3-1614 and List 3-2461, along N. and S/2
NW/4 NE/4 SE/4. Through heavy pine timber and re-

production. Descend 5 ft.
4.33 Bottom of slope.

4.40 Cross main irrigation ditch, 5 lks. wide, 1 ft. deep,
course NW. and SE.

7.00 Cross main irrigation ditch, 5 lks. wide, 1 ft. deep,
course SW. and N. 80° 00' E.

9.00 Cross main irrigation ditch, 5 lks. wide, 1 ft. deep,
course N. 80° 00' W. and SE.

9.93 To Cor. No. 9.

Identical with the temp. point set by me in subdividing
the SE/4. Set a sandstone 18 x 14 x 8 ins. 10 ins.
in the ground, over a stone marked with a + for cor.
No. 9 of this survey, marked 9 - H E S 207 on side
facing the claim and a + on top. Dig pits 24 x 24
x 12 ins., crosswise on this land the succeeding course,
7 ft. dist. and raise a mound of earth and stone
3 ft. base, 2 ft. high, 3-1/2 ft. dist. within the
claim, whence:

A nail in a yellow pine 25 ins. dia., bears
S. 10° 00' W., 62 lks. dist.

A nail in a yellow pine 23 ins. dia., bears
N. 88° 38' E., 23 lks. dist.

Each blazed and scribed 9 H E S 207 B T.

Chains	
	List cor. No. 3, which is a sandstone 10 x 8 x 8 ins. above ground, marked and witnessed as described by the Forest Service bears N. 50° 00' E., 31 lks. dist. I destroy it and all witnesses thereto. (No larger stone available for cor.)
	Thence S. 0° 39' E.
	Bet. list 3-1614 and List 3-2461, along line bet. E. and W/2 NE/4 SE/4. Through good stand of yellow pine and scattering juniper and oak. Over level land.
0.63	Main irrigation ditch, 5 lks. wide, 1 ft. deep. Course NW. and SE.
1.00	Ascend 15 ft.
8.78	Top of slope, thence over level land.
10.00	Descend 12 ft.
12.00	Bottom of slope.
12.78	Cross main irrigation ditch, 5 lks. wide, 1 ft. deep. Course N. 25° 00' E. and S. 25° 00' W.
14.78	To Cor. No. 10. Identical with the temp. 1/64 cor. previously set by me. Set a sandstone 22 x 16 x 4 ins., 12 ins. in the ground, over a stone marked with a + for cor. No. 10 of this survey, marked 10 - H E S 207 on side facing the claim and a + on top. Dig pits 24 x 24 x 12 ins. crosswise on this and the succeeding course 7 ft. dist. and raise a mound of earth and stone 3 ft. base, 2 ft. high, 3-1/2 ft. dist. within the claim, whence: A nail in a yellow pine 16 ins. dia., bears S. 73° 13' E., 25 lks. dist.

SITGREAVES NATIONAL FOREST

STATE OF ARIZONA

Chains

A nail in a yellow pine 22 ins. dia., bears
 N. 20° 30' E., 61 lks. dist.
 Each blazed and scribed 10 H E S 207 B T
 Irrigation ditch is 70 lks. west of cor.
 List cor. No. 2, which is a sandstone 15 x 8 x 5 ins.
 above ground, marked and witnessed as described
 by the Forest Service, bears S. 45° 00' W., 5 lks. dist.
 I destroy it, and all witnesses thereto.

(No larger stone available for cor.)

Thence S. 89° 39' E.

On the latitudinal 1/16 sec. line through the SE/4
 bet. list 3-1614 and list 3-2461. Over level land
 through heavy stand of yellow pine.

2.87 Claimant's ditch 3 lks. wide, 1 ft. deep. Course
 N. 60° 00' E.

9.87 To Cor. No. 11 and closing cor. on line bet. Secs. 8
 and 9, and identical with the temp. 1/16 sec. cor.
 on E. bdy. SE/4. Set a sandstone 28 x 14 x 5 ins.
 18 ins. in the ground, over a stone marked with a +
 for cor. No. 11 and closing cor. marked CC on W.
 face and 11 - H E S 207 on side facing the claim. Dig
 pits 24 x 18 x 12 ins., N. and S. 3 ft. dist. and
 West 7 ft. dist. and raise a mound of earth 4 ft.
 base, 2 ft. high, 3-1/2 ft. dist. on closing line;
 whence:

A nail in a yellow pine 18 ins. dia., bears
 S. 85° 26' W., 65 lks. dist.

A nail in a yellow pine 14 ins. dia., bears
 S. 25° 16' W., 51 lks. dist.

80

Chains

Each blazed and scribed CC 11 H E S 207 B T
 Fence cor. bears East, 5 lks. dist. from which
 fences bear N., S. and E.
 List cor. No. 1, which is a sandstone 15 x 8 x 5 ins.
 above ground, marked and witnessed as described by
 the Forest Service, bears W. 5 lks. dist. which I
 destroy and all witnesses thereto.

Thence S. 0° 27' E.

On line bet. secs. 8 and 9, and bet. List 3-2418 and
 List 3-2461. Over level land through heavy stand
 of yellow pine. Wire fence is 5 lks. E. and bears
 with line.

18.35 Cross main irrigation ditch, 5 lks. wide, 1 ft. deep.

Course SE.

19.65 To Cor. No. 1, the place of beginning.

AREA

Area H. E. S. 207 39.00 acres

IMPROVEMENTS

The only improvements made upon the claim is about
 4 chs. of irrigation ditch.
 Value \$ 5.00

DESCRIPTION

This claim is located on gently rolling land at an
 elevation of 6350 ft. above sea level. The claim
 is covered with a good stand of yellow pine, the
 soil is a brown sticky adobe, very fertile, the
 claim is unfenced and no part of it has been under
 cultivation heretofore. A main irrigation ditch
 owned by the community runs through a part of the

SITGREAVES NATIONAL FOREST

STATE OF ARIZONA

Chains

claim and will furnish sufficient water for all purposes.

There is no evidence of mineral deposits on the claim. Show Low, an inland village, postoffice and trading center lies about 4-1/2 miles dist. in a northerly direction and is reached by a fair wagon road.

CONFLICTS AND ADJOINING CLAIMS.

There are no conflicts. This claim is joined on the south and west by the White Mountain Apache Indian Reservation, on the north and east by list 3-1614 and list 3-2418.

TRAVERSE

Cor.	Course	Dist.	N.	S.	E.	W.	
1-2	N. 89° 44' W.	1.42	0.01			1.42	
2-3	N. 31° 46' W.	1.81	1.54			0.95	
3-4	N. 10° 45' W.	3.16	3.10			0.59	
4-5	N. 51° 38' W.	12.00	7.45			9.41	
5-6	N. 37° 27' W.	24.39	19.36			14.83	
6-7	N. 40° 56' E.	10.65	8.04		6.98		
7-8	S. 0° 55' E.	4.94		4.93	0.08		
8-9	S. 89° 34' E.	9.93		0.07	9.93		
9-10	S. 0° 39' E.	14.78		14.78	0.17		
10-11	S. 89° 39' E.	9.87		0.06	9.87		
11-1	S. 0° 27' E.	19.65		19.65	0.15		
			112.60	39.50	39.49	27.18	27.20
				39.49			27.18
Error in Lat. and Dep.				.01			.02

Error of closure 1:5035.

Survey completed August 31, 1914.

C. A. Long
Surveyor - Forest Service.

Chains

Chains

claim and will furnish sufficient water for all purposes. There is no evidence of mineral deposits on the claim. Show low, an inland village, postoffice and trading center lies about 4-1/2 miles dist. in a northerly direction and is reached by a fair wagon road.

CONFLICTS AND ADJOINING CLAIMS.

There are no conflicts. This claim is joined on the south and west by the White Mountain Apache Indian Reservation, on the north and east by list 3-1814 and list 3-2418.

TRAVELER

Cor.	Course	Dist.	N.	S.	E.	W.
1-3	N. 89° 44' W.	1.42	0.01			1.42
2-3	N. 21° 48' W.	1.81	1.84			0.95
3-4	N. 10° 45' W.	2.16	2.10			0.89
4-5	N. 51° 28' W.	12.00	7.48			9.41
5-6	N. 37° 27' W.	24.39	12.36			14.88
6-7	N. 40° 56' E.	10.65	8.04		6.98	
7-8	S. 0° 55' E.	4.94		4.93	0.08	
8-9	S. 89° 34' E.	9.93		0.07	9.93	
9-10	S. 0° 33' E.	14.78		14.78	0.17	
10-11	S. 89° 39' E.	9.87		0.08	9.87	
11-1	S. 0° 27' E.	19.65		19.65	0.15	
Total			32.50	32.49	37.18	37.50
Error in lat. and dep.			0.01			0.02
Error of closure 1:5055.						

Survey completed August 31, 1914.

[Signature]
Surveyor - Forest Service

- DIRECTIONS.—1. Carry out calculations to two decimals only.
2. In balancing Latitudes and Departures do not obliterate or change the original figures. Put the corrected figure or figures above in red ink. Do not change the footing of the original figures, but put below them the corrected footing in red ink. The corrections for balancing fallings should be proportional to the lengths of the lines.
3. In calculations of fallings take result to nearest link. In calculations of N. and S. areas drop all after second decimal. Surveyors are required to use the Standard Field Tables issued by the G. L. O.
4. Only three copies of this tabulation are necessary, for the District Office, the Surveyor General, and the Commissioner.

TABLING AND CALCULATIONS OF HOMESTEAD ENTRY SURVEY NO. 207, STATE OF ARIZONA

8-2349

CORNERS.	BEARING.	DISTANCE.	LATITUDES.		DEPARTURES.		DOUBLE M. D.	N. AREAS.	S. AREAS.
			North.	South.	East.	West.			
Sec. 8 1-2	N. 89° 44' W.	1.42	.01			1.42	52.96	.53 ✓	
2-3	N. 31° 46' W.	1.81	1.54			.95	50.59	77.91 ✓	
3-4	N. 10° 45' W.	3.16	3.10			.59	42.05	152.06 ✓	
4-5	N. 51° 38' W.	12.00	7.45		9.41	32.05	32.05	220.92 ✓	
5-6	N. 37° 27' W.	24.39	19.36		14.83	14.82	14.82	286.92 ✓	
6-7	N. 40° 56' E.	10.65	8.04	4.94	6.98	6.99	6.99	56.20 ✓	
7-8	S. 0° 55' E.	4.94	4.93		.08	14.06	14.06	69.46 ✓	
8-9	S. 89° 34' E.	9.23	.07		9.93	24.07	24.07	1.68 ✓	
9-10	S. 0° 39' E.	14.78	14.78		.17	34.17	34.17	505.03 ✓	
10-11	S. 89° 39' E.	9.87	.06		9.87	44.21	44.21	2.65 ✓	
11-1	S. 0° 27' E.	19.65	19.65		.15	54.23	54.23	1065.62 ✓	
		112.60	39.50	39.49	27.18	27.20		864.54	1644.44
			39.50	39.50	27.19	27.19			864.54
									20/779.90
	Closing error	1:5035							39.00
									Acres

83

EMH

APPROVAL

Office of the United States Surveyor General,

Phoenix, Arizona, March 8 , 1917.


The foregoing field notes of Homestead Entry Survey No.

207

executed by

C. A. Long, Surveyor Forest Service
[Forest Service Title.]

under his special instructions, dated June 16, 1914, having
and supplemental instructions dated July 22, 1914,
been critically examined, and the necessary corrections and explanations
made, the said field notes, and the surveys they describe, are hereby
approved.


U. S. Surveyor General.

I certify that the foregoing transcript of the field notes of the
above-described survey in the State of **Arizona** , has been
correctly copied from the original notes on file in this office.

Frank P. Trott

U. S. Surveyor General.