

U. S. DEPARTMENT OF AGRICULTURE
FOREST SERVICE

MAY 1 - 1916

FIELD NOTES

OF

HOMESTEAD ENTRY SURVEY NO. 210 ✓

SITUATED IN THE

SITGREAVES NATIONAL FOREST

ADMINISTRATIVE DISTRICT NO. 3 ✓

in

Section 30, surveyed, Township 10 N., Range 24 E.

Section 25, unsurveyed, Township 10 N., Range 23 E.

of the

Gila and Salt River Base and Meridian.

ARIZONA

Survey executed by C. A. Long, Surveyor - Forest Service

Under special instructions dated June 16, 1914 ✓

and supplemental special instructions dated July 22, 1914 ✓

Survey commenced September 17, 1914

Survey completed September 20, 1914

Under Acts of June 11, 1906 and June 30, 1914. ✓

Applicant for listing Albert Penrod,

Residence Pinetop, Arizona.

Application No. 346 ✓, dated August 13, 1912 ✓

List No. 3-2188 ✓, dated December 30, 1912 ✓

Applicant for survey Albert Penrod,

Residence Pinetop, Arizona.

H. E. No. 023461 ✓, dated October 1, 1913. ✓

Land district Phoenix, Arizona.

124

OATH OF ASSISTANTS

We hereby certify that we assisted C. A. Long,
Surveyor - Forest Service in surveying all those
parts or portions of Homestead Entry Survey No. 210, in
surveyed Section 30, Township 10 N., Range 24 E.,
unsurveyed Section 25, Township 10 N., Range 23 E.,

of the G. & S.R.B. & meridian, State of Arizona, which
are represented in the following field notes as having been
surveyed by him and under his direction; and that said sur-
vey has been in all respects, to the best of our knowledge
and belief, well and faithfully surveyed, and the corner
monuments established, according to the instructions fur-
nished by the United States Surveyor General for Arizona.

Note: It would have been
very expensive and incon-
venient to appear before an
officer to administer oaths
to Assistants; hence, they
were taken by the Surveyor.

Wm. Warner, Chainman

Frank Taylor, Chainman

Subscribed and sworn to before me this 20th day of
September, 1914

C. A. Long

Surveyor - Forest Service

OATH OF SURVEYOR

I, C. A. Long, Surveyor-Forest Service, do solemnly swear
that, in strict conformity with the special instructions of
the United States Surveyor General for Arizona, dated June 16, 1914 and
suppl. instrs. dated July 22, 1914, and the laws of the United States, I have
well, faithfully, and truly, in my own proper person, sur-
veyed a tract of land ~~upon the application of~~ embraced in
List, No. 3-2188, dated Dec. 30, 1912, for
Patent, under the Act of June 11, 1906,
the same to be known as Homestead Entry Survey No. 210,
situated within the SITGREAVES National Forest, in
surveyed Section 30, Township 10 N., Range 24 E., and
unsurveyed Section 25, Township 10 N., Range 23 E.,

of the G. & S.R.B. & meridian, Arizona, and the
related retracements and resurveys and section subdivisions,
which are represented in the following field notes as having
been surveyed by me; and I further solemnly swear that all
the corners of said survey have been established and perpet-
uated in strict accordance with the stated special instruc-
tions, and in the specific manner described in the field
notes, and that the following are the original field notes
of such survey.

C. A. Long

Surveyor - Forest Service

Subscribed and sworn to before me this 23rd day of
April, 1915.

Elsie C. Meyer
Notary Public



SITGREAVES NATIONAL FOREST

STATE OF ARIZONA

Chains Applicant for listing, Albert Penrod; Application No. 346, dated August 13, 1912; List No. 3-2188, dated December 30, 1912; H. E. No. 023461, made at Phoenix, Arizona by Albert Penrod, dated October 1, 1913.

Surveyed under special instructions from the Surveyor General for Arizona, dated June 16, 1914, and supplemental special instructions dated July 22, 1914, and designated as Homestead Entry Survey, No. 210.

Situated in sec. 30, T. 10 N., R. 24 E., and in unsurveyed sec. 25, T. 10 N., R. 23 E., Gila and Salt River Base and Meridian, Sitgreaves National Forest, Arizona.

Surveyed under the Acts of June 11, 1906 and June 30, 1914.

Survey commenced September 17, 1914 and executed with a W. and L. E. Gurley light mountain transit No. 11920, provided with a full vertical circle and a horizontal limb having two double verniers placed opposite each other and reading to single minutes of arc, which is also the least reading of the vernier on the vertical circle.

I test the adjustments of my instrument and make necessary corrections.

All measurements were made on the slopes with a 500 link steel tape and the slope angles determined with a clinometer, the horizontal distances alone appearing in these notes.

September 17, 1914.

At the 1/4 sec. cor. on the Tp. line bet. secs. 25 and 30, which is a basalt stone in a mound of stone, marked and witnessed as described by the Surveyor General.

Chains Latitude $34^{\circ}15'$ N., Long. $109^{\circ}51'20''$ W., by account from Land office map. At 7h. 50m., p.m., l.m.t., I observe Polaris at eastern elongation, in accordance with instructions in the Manual, and mark a point in the line thus determined by a tack in a stake driven in the ground 5.00 chs. N. of my station. September 18, 1914.

At 7h. a.m., I turn off the azimuth of Polaris $1^{\circ}23'30''$ to the west, and mark the meridian thus determined by a tack in a peg driven in the ground 5.00 chs. N. of my station.

The magnetic bearing of the stated meridian at 8h. 30m., a.m., is N. $14^{\circ}15'$ W., which corrected for diurnal variation gives the mean magnetic declination $14^{\circ}13'$ E.

September 18, 1914.

I begin at the $1/4$ sec. cor. to secs. 25 and 30, heretofore described, and as this cor. is unwitnessed, I witness as follows:

A juniper 6 ins. dia., bears N. $36^{\circ}04'$ E., 53 lks. dist.

A yellow pine, 14 ins. dia., bears N. $47^{\circ}07'$ E., 241 lks. dist.

Each blazed and scribed $1/4$ S. B T.

Thence North

On a random line bet. secs. 25 and 30.

39.73 Fall 63- $1/2$ lks. east of the remains of old cor. to secs. 19, 24, 25 and 30, which is a stone in a mound of stone and marks nearly obliterated. I destroy the old cor. and set a basalt stone 19 x 10 x 6 ins., in a mound of stone for cor. to secs. 19, 24, 25 and 30, marked with 2 notches on S. face and 4 notches on N. face. Pits impracticable. No bearing trees. The bearing of

SITGREAVES NATIONAL FOREST

STATE OF ARIZONA

Chains	<p>this line is N. 0° 55' W., 39.73 chs.</p>
	<p>Thence East. On a random line bet. secs. 19 and 30.</p>
39.60	<p>Make search for 1/4 sec. cor. bet. secs. 19 and 30.</p>
78.57	<p>Fall 60 lks. S. of the cor. of secs. 19, 20, 29 and 30, which is a stone firmly set in a mound of stone, marked and witnessed as described by the Surveyor General. Thence S. 89° 34' W. On a true line bet. secs. 19 and 30.</p>
39.48	<p>The proportionate point for 1/4 sec. cor. I re-establish it as follows:- Set a malpais stone 17 x 14 x 12 ins., in a mound of stone for 1/4 cor. marked 1/4 on N. face, whence: A juniper, 6 ins. dia., bears S. 25° 46' W., 128 lks. dist. A juniper 8 ins. dia., bears N. 33° 00' W., 166 lks. dist. Each blazed and scribed 1/4 S.B.T. (No larger stone available for 1/4 cor.)</p>
	<p>Thence South. On a random line through sec. 30.</p>
40.00	<p>Set temp. point for center 1/4 sec. cor.</p>
80.40	<p>Fall 161 lks. west of the 1/4 sec. cor. on S. bdy. sec. 30, which is a stone marked as described by the Survey- or General. The witness tree described by the Surveyor General, which is a yellow pine, 24 ins. dia., bears S. 29° 30' W., 50 lks. dist., but there is no evidence of it having been marked in the past. Therefore, I witness the 1/4 cor. as follows: A juniper, 22 ins. dia., bears S. 26° 52' W., 72 lks. dist., marked 1/4 S.B.T.</p>

Chains

The bearing of the meridional 1/4 sec. line is
S. 1° 09' E., 80.42[✓] chs.

I move to 1/4 sec. cor. on S. bdy. sec. 30.

Thence West

On a random line bet. secs. 30 and 31.
40.37 Fall 13 lks. S. of the cor. of secs. 25, 30, 31 and 36,
which is a stone marked and witnessed as described by
the Surveyor General. Therefore, the bearing of this
line is N. 89° 49' W., 40.37 chs. dist.

From the cor. of secs. 25, 30, 31 and 36, heretofore
described, I run North.

On a random line bet. secs. 25 and 30.

40.32 Fall 18 lks. W. of the 1/4 sec. cor. bet. secs. 25 and
30, heretofore described, therefore the bearing of this
line is N. 0° 16' E., 40.32 chs. dist.

Thence East.

On a random line through sec. 30.

5.00 Sponsler Lake on line. I run S. 11.00 chs., thence
east 22.00 chs. on offset, thence N. 11.00 chs. to
line at

27.00 On true line.

77.91 Fall 11 lks. south of the 1/4 sec. cor. bet. secs. 29
and 30, which is a malpais stone set in mound of stone,
marked and witnessed as described by the Surveyor

Thence S. 89° 55' W.

I run on a true line, along latitudinal 1/4 sec. line.

38.56 Intersect the meridional 1/4 sec. line, N. 1° 09' W.,
40.48 chs. from the 1/4 sec. cor. on S. bdy. sec. 30,
set a temp. point for true center sec.

SITGREAVES NATIONAL FOREST

STATE OF ARIZONA

Chains 50.91	Sponsler Lake on line. Water being shallow, I send chainmen in lake and at
58.37	Set temp. 1/16 cor. on N. bdy. SW/4, I determine the above point by the following proportion: $39.60 + 39.86$: $39.35 = 20.00 : X$. That is, the point should be set S. $89^{\circ} 55'$ W., 19.81 chs. from the center of sec.
<hr/>	
	September 19, 1914.
	I return to the 1/4 sec. cor. on W. bdy. sec. 30, and run S. $0^{\circ} 16'$ W. on a true line bet. secs. 25 and 30.
20.16	Set temp. 1/16 cor. on W. bdy. SW/4, and what will be a cor. to the claim.
39.82	Set temp. point for cor. No. 2 of the claim.
40.32	The cor. of secs. 25, 30, 31 and 36, heretofore described.
<hr/>	
	Thence S. $89^{\circ} 49'$ E.
	On a true line bet. secs. 30 and 31, I determine the position for the 1/16 cor. on S. bdy. SW/4 by the following proportion: $39.86 : 40.37 = 20.00 : X$. That is, it should be set N. $89^{\circ} 49'$ W., 20.26 chs. from the 1/4 sec. cor. on S. bdy. sec. 30, or
20.11	Set temp. 1/16 cor. on S. bdy. SW/4.
40.37	The 1/4 cor. to secs. 30 and 31, heretofore described.
<hr/>	
	Thence N. $1^{\circ} 09'$ W.
	On a true line along the meridional 1/4 sec. line.
20.24	Set temp. 1/16 cor. on E. bdy. SW/4.
<hr/>	
	Thence West.
	On a random line through SW/4.
39.90	Fall 1 lk. S. of the temp. 1/16 cor. on W. bdy. SW/4,

Chains Thence S. 89° 59' E.
On a true line, along latitudinal 1/16 sec. line through SW/4.

19.95 Set temp. point for center 1/16 cor. of SW/4.

39.90 The temp. 1/16 cor. on E. bdy. SW/4, the place of beginning.

I return to the temp. 1/16 cor. on S. bdy. SW/4, and run North
On a random line through SW/4.

40.39 Fall 37 lks. east of the temp. 1/16 cor. on N. bdy. SW/4.

Thence S. 0° 32' E.
On a true line along meridional 1/16 sec. line through SW/4.

20.20 Intersect the latitudinal 1/16 sec. line S. 89° 59' E., 19.83 chs. from the temp. 1/16 cor. on W. bdy. SW/4 set a temp. point for true center 1/16 sec. cor. of the SW/4, and what will be a cor. No. 4 of the claim.

39.89 Set temp. point for cor. No. 3 of the claim, on N. side of road exception.

40.39 The temp. 1/16 cor. on S. bdy. SW/4, and place of beginning.

September 20, 1914.

Boundaries of H. E. S. No. 210.

I begin at the cor. of secs. 25, 30, 31 and 36, heretofore described, and set a malpais stone 24 x 14 x 10 ins., 14 ins. in the ground, over a stone marked with a cross on the NW. side of the same stone for cor. No. 1 of the claim, and closing cor. on line bet. secs. 25 and 30, marked C C on W. face and 1 - H E S 210 on side facing claim and a cross on top. No bearings, there-

SITGREAVES NATIONAL FOREST

STATE OF ARIZONA

Chains fore dig pits 24 x 24 x 12 ins., N. and S. 3 ft. dist. and West 7 ft. dist.; and raise a mound of earth 4 ft. base, 2 ft. high, 3-1/2 ft. W. of cor.

Thence N. 0° 16' E.

Over open level land, covered with malpais stone, along line bet. secs. 25 and 30.

0.25 Cross wire fence, bears E. and W.

0.50 To cor. No. 2.

Set a malpais stone 22 x 10 x 5 ins., 12 ins. in the ground, over a stone marked with a cross for cor. No. 2, marked 2 - H E S 210 on side facing claim and a cross on top. No bearings, therefore dig pits 24 x 24 x 12 ins. crosswise on this and the succeeding course 7 ft. dist.; and raise a mound of earth and stone 3 ft. base, 2 ft. high, 3-1/2 ft. dist. within the claim. (No larger stone available for cor.)

Thence S. 89° 49' E.

Along N. side of road exception and 50 lks. N. of line bet. secs. 30 and 31, over open level land.

10.00 Cross wire fence, bearing N. 89° 30' E. and S. 89° 30' W.

20.11 To cor. No. 3 on N. bdy. road exception.

Set a basalt stone 26 x 10 x 8 ins., 16 ins. in the ground, over a stone marked with a cross for cor. No. 3, marked 3 - H E S 210 on side facing the claim and a cross on top. Dig pits 24 x 24 x 12 ins. crosswise on this and the succeeding course 7 ft. dist.; and raise a mound of earth and stone 3 ft. base, 2 ft. high, 3-1/2 ft. dist. within claim, whence:

A nail in a yellow pine, 17 ins. dia., bears S. 9° 26' E., 190 lks. dist.

A nail in a white oak, 14 ins. dia., bears N. 85° 33' E., 236 lks. dist.

Chains . . . Each blazed and scribed 3 H E S 210 B T.

Thence N. 0° 32' W.

Along the meridional 1/16 sec. line through SW/4,
 over level land covered with malpais stone.

0.20 Cross wire fence, bears N. 89° 30' E. and S. 89° 30' W.

3.70 Dry wash, 10 lks. wide, 5 ft. deep, course NW.

15.00 Cross wire fence, bearing S. 22° 00' E. and N. 22° 00' W.

19.69 To cor. No. 4.

Identical with the center of the SW/4 sec. Set a
 basalt stone 24 x 13 x 5 ins., 14 ins. in the ground,
 over a stone marked with a cross for cor. No. 4, and
 1/16 sec. cor., marked 1/16 on E. face, 4 - H E S 210
 on side facing claim, and a cross on top. No bearings,
 therefore dig pits 24 x 24 x 12 ins. crosswise on this
 and the succeeding course 7 ft. dist.; and raise a
 mound of earth and stone 3 ft. base, 2 ft. high, 3-1/2
 ft. dist. within claim.

Thence N. 89° 59' W.

Along the latitudinal 1/16 sec. line through SW/4,
 over open, gently rolling land, covered with malpais
 stone.

6.33 Cross wash, 15 lks. wide, 5 ft. deep, course NW.

14.00 Cross wire fence, bearing N. 89° 30' W. and S. 89° 00' E.

19.83 To cor. No. 5 and closing corner on line bet. secs. 25
 and 30.

Set a basalt stone 25 x 14 x 12 ins., 15 ins. in the
 ground, over a stone marked with a cross for closing
 cor. and cor. No. 5, marked C C on E. face, 1/16 on W.
 face and 5 - H E S 210 on side facing claim, and a
 cross on top. Dig pits N. and S. 3 ft. dist. and E.
 7 ft. dist.; and raise a mound of earth and stone 3 ft.

SITGREAVES NATIONAL FOREST

STATE OF ARIZONA

Chains. base, 2 ft. high, 3-1/2 ft. dist. on closing line.
 No bearing trees.
 Cor. No. 2 bears S. 0° 16' W., 19.66 chs. dist.
 The 1/4 cor. to secs. 25 and 30 bears
 N. 0° 16' E., 20.16 chs. dist.

Thence West.
 In unsurveyed sec. 25, over open, gently rolling land
 covered with malpais stone.
 0.70 Wire fence bears NE. and SW.
 1.00 Wire fence 30 lks. S. and bears with line.
 20.00 To cor. No. 6.
 Set a malpais stone 24 x 12 x 8 ins., 14 ins. in the
 ground, over a stone marked with a cross for cor. No.
 6, marked 6 - H E S 210 on side facing claim and a
 cross on top. Dig pits 24 x 24 x 12 ins. crosswise
 on this and the succeeding course 7 ft. dist.; and
 raise a mound of earth and stone 3 ft. base, 2 ft. high,
 3-1/2 ft. dist. within claim, whence:
 A juniper 6 ins. dia., bears S. 15° 48' E.,
 219 lks. dist., marked 6 H E S 210 B T.
 No other bearing trees within prescribed
 limits.
 Fence cor. bears S. 64° 18' W., 183 lks. dist.,
 from which fences bear S. and E.

Thence South.
 Over open level grassland, covered with malpais stone.
 1.00 Wire fence, bears E. and W.
 10.00 Wire fence is 70 lks. W. and bears with line.
 20.16 To cor. No. 7.
 Set a basalt stone 24 x 13 x 8 ins., 14 ins. in the

Chains ground, over a stone marked with a cross for cor. No. 7, marked 7 - H E S 210 on side facing claim and a cross on top. No bearings, therefore dig pits 24 x 24 x 12 ins. crosswise on this and the succeeding course, 7 ft. dist.; and raise a mound of earth and stone 3 ft. base, 2 ft. high, 3-1/2 ft. dist. within claim.

Fence cor. bears S. 18° 45' W., 40 lks. dist. from which fences bear N. and E.

Thence East. Over open level land, along N. side of fence.

10.00 Cross wire fence, bears S. 89° 30' W. and N. 89° 30' E.

19.91 To cor. No. 1, the place of beginning.

Area in sec. 30 ----- 39.29 acres
 Area in sec. 25 ----- 40.23 acres
 Total area ----- 79.52 acres

IMPROVEMENTS

The only improvements upon that portion of Entry No. 023461 included in the metes and bounds survey consists of about 1-1/2 mile of barbed wire fencing.

Value ----- \$120.00

Claimant's residence, barns, and out-houses are located on that portion of his claim lying in sec. 31, embracing Lot 1, W/2 NE/4 NW/4, and N/2 Lot 2.

DESCRIPTION

This claim is located on an open level flat at an elevation of 6,800 ft. above sea level. The entire area

135

SITGREAVES NATIONAL FOREST

STATE OF ARIZONA

Chains

is covered with malpais stone, but when cleared will produce good crops of grain, potatoes, and vegetables under modern dry farming methods.

The soil is a brown adobe, very fertile, about 10 acres have been under cultivation.

There is no water, timber or mineral on the claim.

Water for domestic use is obtained from Sponsler Lake, one mile north of claimant's house.

Pinetop, an inland village, post office and trading place, is about 7 miles SW. of claim and is reached by a fair wagon road.

CONFLICTS AND ADJOINING CLAIMS.

There are no conflicts. The pre-emption claim of Joseph Sponsler, Lots 2 and 3, sec. 30, joins the claim on the north. No other adjoining claims known.

TRAVERSE SEC. 30.

Cor.	Course	Dist.	N	S	E	W
2-3	S. 89° 49' E.	20.11		0.06	20.11	
3-4	N. 0° 32' W.	19.69	19.69			0.18
4-5	N. 89° 59' W.	19.83	0.01			19.83
5-2	S. 0° 16' W.	19.66		19.66		0.09
			79.29	19.70	19.72	20.11
					19.70	20.10
Error in Lat. and Dep.				.02	.01	

Closing error 1:3555.

TRAVERSE SEC. 25.

Cor.	Course	Dist.	N	S	E	W
1-5	N. 0° 16' E.	20.16	20.16		0.09	
5-6	West	20.00				20.00
6-7	South	20.16		20.16		
7-1	East	19.91			19.91	
			80.23	20.16	20.16	20.00
					20.00	20.00

Closing error 0:00

Survey completed September 20, 1914.

Cal Long
Surveyor - Forest Service.

HOMESTEAD ENTRY SURVEY NO. 101

NATIONAL FOREST

STATE OF ARIZONA

Chains is covered with malpais stone, but when elevated produce good crops of grain, potatoes, and vegetables under modern dry farming methods. The soil is a brown silt, very fertile, about 10 acres have been under cultivation. There is no water, timber or mineral on the claim. Water for domestic use is obtained from Spangler Lake, one mile north of claimant's house. Tinotop, an Indian village, post office and trading place, is about 7 miles SW. of claim and is reached by a dirt wagon road.

COMPLICATED AND ADJOINING CLAIMS. There are no conflicts. The pre-emption claim of Joseph Spangler, lots 2 and 3, sec. 30, joins the claim on the north. No other adjoining claims known.

GRAVINE SEC. 30.

Cor.	Course	Dist.	N	S	E	W
2-3	S. 89° 49' E.	20.11		0.08	20.11	
3-4	N. 0° 33' W.	19.88	19.88			0.18
4-5	N. 89° 39' W.	19.88	0.01			19.82
5-2	S. 0° 16' W.	19.66		19.66		0.09
<hr/>						
		79.29	19.70	19.73	20.11	20.10
			19.70	20.10		
			0.08			0.01

Error in Dist. and Dep. Closing error 1:3882.

TRAVINER SEC. 28.

Cor.	Course	Dist.	N	S	E	W
1-2	N. 0° 16' E.	20.16		20.16		
2-3	West	20.00			0.09	20.00
3-4	South	20.16		20.16		
4-1	East	19.91	19.91			
<hr/>						
		80.23	20.16	20.16	20.00	20.00

Closing error 0:00. Survey completed September 20, 1914.

[Signature]
 Surveyor - Forest Service.

DIRECTIONS.—1. Carry out calculations to two decimals only.
2. In balancing Latitudes and Departures do not obliterate or change the original figures. Put the corrected figure or figures above in red ink. Do not change the footing of the original figures, but put below them the corrected footing in red ink. The corrections for balancing fallings should be proportional to the lengths of the lines.
3. In calculations of fallings take result to nearest link. In calculations of N. and S. areas drop all after second decimal. Surveyors are required to use the Standard Field Tables issued by the G. L. O.
4. Only three copies of this tabulation are necessary, for the District Office, the Surveyor General, and the Commissioner.

8-2349 **TABLING AND CALCULATIONS OF HOMESTEAD ENTRY SURVEY NO. 210, STATE OF Arizona - Sitgreaves**

CORNERS.	BEARING.	DISTANCE.	LATITUDES.		DEPARTURES.		DOUBLE M. D.	N. AREAS.	S. AREAS.
			NORTH.	SOUTH.	EAST.	WEST.			
Sec. 30 2-3	S. 89° 49' E.	20.11		0 06	20 11		20 11		1 21 ✓
3-4	N. 0° 32' W.	19.69	19 59			0 18	40 03	788 59 ✓	
4-5	N. 89° 59' W.	19.83	0 01			19 83	20 01	0 20 ✓	
5-2	S. 0° 16' W.	19.66		19 66		0 09	0 09		1 77 ✓
		79.29	19 70	19 72	20 11	20 10		788 79	2 98
	Closing error 1:3555		19 71	19 71	20 11	20 11		2 98	
								785 81	
								39 29 ✓ acres.	
Sec. 25 1-5	N. 0° 16' E.	20.16	20 16		0 09		39 91	804 59 ✓	
5-6	West	20.00				20 00	20 00		
6-7	South	20.16		20 16			0 00		
7-1	East	19.91			19 91		19 91		
		80.23	20 16	20 16	20 00	20 00		20) 804 59	
	Closing error 0:00		20 16	20 16	20 00	20 00		40 23 ✓ acres.	

137

APPROVAL

Office of the United States Surveyor General,

Phoenix, Arizona, March 8, 1917.


The foregoing field notes of Homestead Entry Survey No.

210

executed by **C. A. Long, Surveyor Forest Service**

[Forest Service Title.]

under his special instructions, dated **June 16** 1914, having
and supplemental instructions dated July 22, 1914,
been critically examined, and the necessary corrections and explanations
made, the said field notes, and the surveys they describe, are hereby
approved.


U. S. Surveyor General.

I certify that the foregoing transcript of the field notes of the
above-described survey in the State of **Arizona**, has been
correctly copied from the original notes on file in this office.

Frank P. Trott,
U. S. Surveyor General.