

75

JUN 20 1917

U. S. DEPARTMENT OF AGRICULTURE
FOREST SERVICE

FIELD NOTES

OF

HOMESTEAD ENTRY SURVEY NO. 365

SITUATED IN THE **PRESCOTT** NATIONAL FOREST

ADMINISTRATIVE DISTRICT NO. 3

In Section 17 , unsurveyed, Township 11 N., Range 2 W.

In Section 20 , unsurveyed, Township 11 N., Range 2 W.

of the

Gila and Salt River Base and Meridian.


State of

ARIZONA

Applicant for listing **Emmaline Agee,**
Residence **Kirkland, Arizona.**
Application No. **228** , dated **July 7** , 19**14**
List No. **3-3582** , dated **May 11** , 19**15**

Applicant for survey **Emmaline Agee,**
Residence **Kirkland, Arizona.**
H. E. No. , dated , 19
Land District **Phoenix, Arizona.**

Survey executed by **Charles D. Hodson, Surveyor - Draftsman**
[Forest Service Title.]
Under special instructions dated **June 4** , 19**15**
Survey commenced **June 18** , 19**15**
Survey completed **June 18** , 19**15**
Under Acts of **June 11, 1906 and June 30, 1914.**



76

OATH OF ASSISTANTS

We hereby certify that we assisted **Charles D. Hodson,**
Surveyor - Draftsman in surveying all those
[Forest Service Title.]
parts or portions of Homestead Entry Survey No. **365**, in the State
of **Arizona**, which are represented in the following field notes
as having been surveyed by him and under his direction; and that said
survey has been in all respects, to the best of our knowledge and
belief, well and faithfully surveyed, and the corner monuments estab-
lished, according to the instructions furnished by the United States
Surveyor General for **Arizona.**

Note: It would have been
very expensive and incon-
venient to appear before an
officer to administer oaths
to Assistants; hence, they
were taken by the Surveyor.

C. S. Baechle, Chairman
D. E. Meister, Chairman

Subscribed and sworn to before me this **first** day of
October, 19**15**.

Charles D. Hodson
Surveyor - Draftsman

OATH OF SURVEYOR

I, **Charles D. Hodson,** **Surveyor - Draftsman**
[Forest Service Title.]

do solemnly swear that, in strict conformity with the special instruc-
tions of the United States Surveyor General for **Arizona**, dated
June 4, 19**15**, and the laws of the United States, I have
well, faithfully, and truly, in my own proper person, surveyed a tract
of land embraced in

List, No. **3-3582**, dated **May 11**, 19**15**, for
Patent, under the Act of **June 11**, 19**06**,
the same to be known as Homestead Entry Survey No. **365**,
situated within the **Prescott** National Forest, in
unsurveyed Section **17**, Township **11 N.**, Range **2 W.**, and
unsurveyed Section **20**, Township **11 N.**, Range **2 W.**,

of the **G. and S. R. B. and** meridian, **Arizona**, and the
related retracements and resurveys and section subdivisions, which are
represented in the following field notes as having been surveyed by me;
and I further solemnly swear that all the corners of said survey have been
established and perpetuated in strict accordance with the stated special
instructions, and in the specific manner described in the field notes,
and that the following are the original field notes of such survey.

Charles D. Hodson
Surveyor - Draftsman
[Forest Service Title.]

Subscribed and sworn to before me this **eight** day of
October, 19**15**.

Elsie C. Meyer
Notary Public



8-2349

My Commission expires April 20, 1918.

PRESCOTT NATIONAL FOREST

STATE OF ARIZONA

Chains Applicant for listing, Emmaline Agee; Application No. 228, dated July 7, 1914; List No. 3-3582, dated May 11, 1915.

Surveyed under special instructions from the Surveyor General for Arizona, dated June 4, 1915 and designated as Homestead Entry Survey No. 365.

Situated in what will probably be, when surveyed, Secs. 17 and 20, T. 11 N., R. 2 W., Gila and Salt River Base and Meridian, Prescott National Forest, Arizona.

Surveyed under the Acts of June 11, 1906 and June 30, 1914.

Survey commenced June 18, 1915, and executed with a Buff and Buff transit No. 9700-6.

I test the adjustments of the transit and make necessary corrections.

All measurements were made directly on the slope with a 500 link steel tape. The slope angles were determined with a clinometer.

All the courses of this survey were deflected from the meridian established by me by obsn. of Pol. at Eastern elongation June 13, 1915, in connection with H. E. S. No. 337.

Diligent search for corner of the public survey in this vicinity was made by me on June 14 and 15 in connection with the execution of H. E. S. No. 337, and no corner was found.

Chains June 18, 1915.
Beginning at cor. No. 1.
Identical with cor. H-1 of the list survey, a granite stone 24 x 12 x 12 ins. above ground, marked and witnessed as described by the Forest Service. I destroy all trace of this list cor. At this point I previously established cor. No. 4 of H. E. S. 338, which is a granite stone 12 x 10 x 10 ins. above ground, marked 4 - H E S 338 on the N. face, with mound of stone 3 ft. base, 2 ft. high, N. of cor. I chisel 1 - H E S 365 on the SE. face of same stone; and raise a mound of stone 3 ft. base, 2 ft. high SE. of cor., whence:

A juniper, 6 ins. dia., blazed and scribed
4 H E S 338 + B T, bears N. 82° 47' W.,
113 lks. dist. I scribe this tree
1 H E S 365.

A juniper, 12 ins. dia., blazed and scribed
4 H E S 338 + B T, bears S. 34° 10' W., 176
lks. dist. I scribe this tree 1 H E S 365.

U. S. L. M. No. 337, H. E. S., a malpais stone
in place, 24 x 24 x 18 ins. above ground,
marked U S L M No 337 H E S on SE. face,
with mound of stone 8 ft. base, 6 ft. high
North 18 lks. dist., bears N. 47° 45' W.,
41.61 chs. dist., by direct measurement.

Lat. 34° 18' 30" N., by obsn. on Pol. made by me on
June 13, 1915 in connection with H. E. S. 337. Long.
112° 28' 54" W., from U. S. G. S. Topographic sheet,
Bradshaw Mountain quadrangle.
Mag. decl. at 7h. 00m. a.m., 14° 51' E. Mean mag.

PRESCOTT NATIONAL FOREST

STATE OF ARIZONA

Chains

decl. 14° 47' E.

Thence N. 70° 14' E.

Along line 4-3 of H. E. S. No. 338. Over level
agricultural land.

0.09 Fence cor. bears N. 2 lks. dist., fences bear ENE.,
NNW. and S. along claim lines.

6.39 Irrigation ditch, 5 lks. wide, 1 ft. deep, course S.

6.49 Foot of hill, bears N. and S. Asc. 35 ft.

8.89 Top of hill, bears N. and S.

9.82 To cor. No. 2.

Identical with cor. H-4 of the list survey, a granite
stone 20 x 10 x 10 ins. above ground, marked and wit-
nessed as described by the Forest Service. I destroy
all trace of the list cor. and at this point I set a
granite stone 26 x 14 x 10 ins., 16 ins. in the ground,
over a small stone marked with a cross. I chisel a
cross at the point and 2 - H E S 365 on the SW. face;
and raise a mound of stone 3 ft. base, 2 ft. high, SW.
of cor., whence:

A juniper, 10 ins. dia., blazed and scribed
2 H E S 365 + B T, bears S. 40° 12' E.,
56 lks. dist.

A juniper, 10 ins. dia., blazed and scribed
2 H E S 365 + B T, bears S. 14° 42' W.,
55 lks. dist.

Cor. No. 3 of H. E. S. No. 338 bears N. 70°
14' E., 11.07 chs. dist.

Fence cor. bears N., 3 lks. dist., fences bear
ENE., WSW. and SSE. along claim line.

Thence S. 22° 46' E.

Asc. 40 ft. over NNW. slope. Fence along line.

Chains 3.00	Edge of mesa, bears ENE. and WSW. Proceed over brushy mesa.
14.70	Edge of mesa, bears E. and W. Desc. 50 ft. over S. slope.
21.30	Right bank dry wash, 1 ft. deep, course W.
22.60	Left bank dry wash, 1 ft. deep, course W. Asc. 75 ft. over NNW. slope.
30.80	Enter mesa, edge bears WSW. and E. Slopes N. Asc. 10 ft. over mesa.
33.78	To cor. No. 3. Identical with cor. H-3 of the list survey, a granite stone 20 x 10 x 10 ins. above ground, marked and wit- nessed as described by the Forest Service. I destroy all trace of the list cor. and at this point I set a diorite stone 24 x 7 x 5 ins., 14 ins. in the ground, over a small stone marked with a cross. I chisel a cross at the point and 3 - H E S 365 on the W. face; and raise a mound of stone 3 ft. base, 2 ft. high, W. of cor., whence: A juniper, 10 ins. dia., blazed and scribed 3 H E S 365 + B T, bears N. 57° 26' W., 55 lks. dist. A juniper 14 ins. dia., blazed and scribed 3 H E S 365 + B T, bears S. 9° 04' W., 47 lks. dist.
17.00	Thence S. 45° 20' W. Desc. 50 ft. along NW. edge of flat topped ridge. Fence along line. To edge of hill. Desc. 70 ft. over WNW. slope.
25.00	Foot of hill, bears SSW. and NNE. Proceed over level agricultural land.

PRESCOTT NATIONAL FOREST

STATE OF ARIZONA

Chains
30.10

To cor. No. 4.
 Identical with cor. H-2 of the list survey, a malpais stone 20 x 10 x 8 ins. above ground, marked and witnessed as described by the Forest Service. I destroy all trace of the list cor. and at this point I set a granite stone 26 x 12 x 10 ins., 16 ins. in the ground, over a small stone marked with a cross. I chisel a cross at the point and 4 - H E S 365 on the NNE. face; and raise a mound of stone 3 ft. base, 2 ft. high,

NNE. of cor., whence:

A desert willow, 8 ins. dia., blazed and scribed
 4 H E S 365 + B T, bears N. 54° 37' E., 154
 lks. dist.

An ash, 6 ins. dia., blazed and scribed
 4 H E S 365 + B T, bears S. 37° 00' E.,
 159 lks. dist.

Cor. No. 1 of H. E. S. No. 337 bears S. 66°
 06' E., 17.40 chs. dist.

Thence N. 1° 03' W. Fence along line.

4.60 Left bank Milk Creek, banks 2 ft. high, course SSW.
 Asc. 5 ft. in creek bed. Cor. fence. Fence bears NNE.

32.25 Right bank Milk Creek, banks 2 ft. high, course SSW.
 Asc. 20 ft. over gentle SE. slope.

40.00 Top of ridge, slopes E. Right bank Milk Creek, 100
 lks. wide, bears E. 3 chs. dist. Desc. 15 ft.

46.00 Right bank Milk Creek, banks 2 ft. high, course SE.

48.50 Left bank Milk Creek, banks 1 ft. high, course SE.

49.10 To cor. No. 1, the place of beginning.

AREA.

Total Area - - - - - 70.04 acres

PRESCOTT NATIONAL FOREST

STATE OF ARIZONA

Chains

IMPROVEMENTS

The improvements made upon and for the benefit of this claim, and belonging to the claimant, consist of the following:

Approximately 1-1/2 miles of wire fence, following very closely the lines of this survey.

Value ----- \$150.00

Approximately 1/2 mile of irrigation ditch.

Value ----- \$ 50.00

DESCRIPTION

This claim is located on Milk Creek between the junctions of Ash Creek and Crook Creek with that creek. The claim is approximately one-half bottom and one-half hillside and mesa land. The latter has no agricultural value and is covered with scrub oak and scattering juniper of no commercial value. The bottom land is a rich sandy loam and will produce corn, grain hay, and garden truck..

Water for all purposes is obtained from the irrigation ditch on the claim.

I saw no indication of mineral on the claim.

CONFLICTS AND ADJOINING CLAIMS

There are no conflicts.

The homestead of James McNary, H. E. S. 338, joins this claim on the North. The homestead of A. C. Baldwin, H. E. S. 337, is approximately 1/4 mile SE.

Kirkland, the nearest post office and railroad point, is 25 miles by wagon road in a Northwesterly direction.

Five miles of this road are very poor while the remainder is good.

PRESCOTT NATIONAL FOREST

STATE OF ARIZONA

Chains

TRAVERSE

Course	Dist.	N	S	E	W
N. 70° 14' E.	9.82	3.32		9.24	
S. 22° 46' E.	33.78		31.15	13.07	
S. 45° 20' W.	30.10		21.16		21.41
N. 1° 03' W.	49.10	49.09			0.90
	122.80	52.41	52.31	22.31	22.31
		<u>52.31</u>		<u>22.31</u>	

Error in Lat. and Dep. .10 .00

Closing error 1:1228.

Survey completed June 18, 1915.

Charles D. Hobson

Surveyor - Draftsman

84

Chains

TRAVEL

Chains

Course Dist. N S E W

N. 70° 14' E. 9.82 3.32 9.34

S. 23° 46' E. 33.78 31.15 13.07

S. 45° 30' W. 30.10 31.15 14.41

N. 1° 03' W. 49.10 49.09 0.90

122.80 52.41 52.31 22.31

52.31 52.31

Error in Lat. and Dep. 10.00

Closing error 1:228.

Survey completed June 18, 1915.

Charles H. ...

Surveyor - Draftsman

DIRECTIONS.—1. Carry out calculations to two decimals only.
 2. In balancing Latitudes and Departures do not obliterate or change the original figures, but put below them the corrected footing in red ink.
 Put the corrected figure or figures above in red ink. Do not change the footing of the original figures, but put below them the corrected footing in red ink.
 The corrections for balancing fallings should be proportional to the lengths of the lines.
 3. In calculations of fallings take result to nearest link. In calculations of N. and S. areas drop all after second decimal. Surveyors are required to use the Standard Field Tables issued by the G. L. O.
 4. Only three copies of this tabulation are necessary, for the District Office, the Surveyor General, and the Commissioner.

TABLING AND CALCULATIONS OF HOMESTEAD ENTRY SURVEY NO. 365, STATE OF Arizona - Prescott.

CORNERS.	BEARING.	DISTANCE.	LATITUDES.		DEPARTURES.		DOUBLE M. D.	N. AREAS.	S. AREAS.
			NORTH.	SOUTH.	EAST.	WEST.			
1-2	N. 70° 14' E.	9.82	3 32		9 24		9 24	30 68	
2-3	S. 22° 46' E.	33.78		31 15	13 07		31 55		983 73
3-4	S. 45° 20' W.	30.10		21 16			23 21		491 82
4-1	N. 1° 03' W.	49.10	49 09				0 90	44 15	
		122.80	52 41	52 31	22 31	22 31		74 83	1475 55
			52 37	52 37	22 31	22 31			74 83
									201 1400 72
									Area = 70 04 acres
									T. P.

Closing error 1:1228

85

APPROVAL


Office of the United States Surveyor General,

Phoenix, Arizona, August 14 , 1917

The foregoing field notes of Homestead Entry Survey No.

365

executed by **Charles D. Hodson, Surveyor-Draftsman**
[Forest Service Title.]
under his special instructions, dated **June 4 , 1915**, having
been critically examined, and the necessary corrections and explanations
made, the said field notes, and the surveys they describe, are hereby
approved.



U. S. Surveyor General.

I certify that the foregoing transcript of the field notes of the
above-described survey in the State of **Arizona** , has been
correctly copied from the original notes on file in this office.

Frank P. Trott

U. S. Surveyor General.