

**ORIGINAL**

97 page 5-4  
11-13-16 tie course  
21-16  
11-2-1916  
MAR 15 1920  
APR-8 1920

**U. S. DEPARTMENT OF AGRICULTURE  
FOREST SERVICE**

**FIELD NOTES**

OF

HOMESTEAD ENTRY SURVEY NO. **374**

SITUATED IN THE **COCONINO** NATIONAL FOREST

ADMINISTRATIVE DISTRICT NO. **3**

In Section **15** , - surveyed, Township **22 N.**, Range **8 E.**

of the

**Gila and Salt River Base and Meridian.**

State of **ARIZONA**

Applicant for listing **Jacob Stamm,**

Residence **Cliffs, Arizona**

Application No. **375** ✓ , dated **September 25** , 19**12** ✓

List No. **3-2250** ✓ , dated **January 8** , 19**13** ✓

Applicant for survey **Jacob Stamm,** ✓

Residence **Cliffs, Arizona**

H. E. No. **022717** ✓ , dated **June 13** , 19 **13** ✓

Office  
Land District **Phoenix, Arizona.**

Survey executed by **Charles D. Hodson, Surveyor - Draftsman, Forest Service**  
and **A. W. Hendrix, Surveyor - Draftsman, Forest Service,**

Under special instructions dated **July 9** , 19**15** ✓

Survey commenced **September 23** , 19**15**

Survey completed **June 11,** , 19**19**

Under Acts of **June 11, 1906 and March 4, 1915, & Oct. 1, 1918.**

98

370

OATH OF ASSISTANTS

We hereby certify that we assisted **Charles D. Hodson,**  
**Surveyor - Draftsman** in surveying all those  
[Forest Service Title.]

parts or portions of Homestead Entry Survey No. **374**, in the State  
of **ARIZONA**, which are represented in the following field notes  
as having been surveyed by him and under his direction; and that said  
survey has been in all respects, to the best of our knowledge and  
belief, well and faithfully surveyed, and the corner monuments estab-  
lished, according to the instructions furnished by the United States  
Surveyor General for **ARIZONA**.

**Note: It would have been  
very expensive and incon-  
venient to appear before  
an officer to administer  
the oaths to Assistants;  
hence, they were taken  
by the Surveyor.**

-----  
*Bud Owens* Chainman  
-----  
*Douglas E. Foster* Chainman  
-----

Subscribed and sworn to before me this **28th** day of  
**September**, 19 **15**.

*Charles D. Hodson*  
-----  
**Surveyor - Draftsman**

OATH OF SURVEYOR

I, **Charles D. Hodson, Surveyor - Draftsman**  
[Forest Service Title.]

do solemnly swear that, in strict conformity with the special instruc-  
tions of the United States Surveyor General for **ARIZONA**, dated  
**July 9**, 19 **15**, and the laws of the United States, I have  
well, faithfully, and truly, in my own proper person, surveyed a tract  
of land embraced in

List **PATENT**, No. **3-2250**, dated **January 8**, 19 **13**, for  
under the Act of **June 11**, 19 **06**,  
the same to be known as Homestead Entry Survey No. **374**,  
situated within the **COCONINO** National Forest, in  
- surveyed Section **15**, Township **22 N.**, Range **8 E.**, and  
- surveyed Section - - - , Township - - - , Range - - - ,

of the **G. & S.R.B. &** meridian, **ARIZONA**, and the  
related retracements and resurveys and section subdivisions, which are  
represented in the following field notes as having been surveyed by me;  
and I further solemnly swear that all the corners of said survey have been  
established and perpetuated in strict accordance with the stated special  
instructions, and in the specific manner described in the field notes,  
and that the following are the original field notes of such survey.

*Charles D. Hodson*  
-----  
**Surveyor - Draftsman**  
[Forest Service Title.]

Subscribed and sworn to before me this *eight* day of  
*October*, 19 **15**.

*Ursie C. Myers*  
-----  
*Notary Public*



8-2349

*My Commission expires April 20, 1918.*

U. S. DEPARTMENT OF AGRICULTURE  
FOREST SERVICE

**FIELD NOTES**

OF

HOMESTEAD ENTRY SURVEY NO.

SITUATED IN THE NATIONAL FOREST

ADMINISTRATIVE DISTRICT NO.

In Section , surveyed, Township Range

of the

Meridian.

State of

Applicant for listing

Residence

Application No. , dated , 19

List No. , dated , 19

Applicant for survey

Residence

H. E. No. , dated , 19

Land Office

Survey executed by


[Forest Service Title]

Under special instructions dated , 19

Survey commenced , 19

Survey completed , 19

Under Acts of



OATH OF ASSISTANTS

We hereby certify that we assisted **A. W. Hendrix, Sr.,**  
**Surveyor - Draftsman, Forest Service,** in surveying all those  
[Forest Service Title.]

parts or portions of Homestead Entry Survey No. **374**, in the State  
of **ARIZONA** which are represented in the following field notes  
as having been surveyed by him and under his direction; and that said  
survey has been in all respects, to the best of our knowledge and  
belief, well and faithfully surveyed, and the corner monuments estab-  
lished, according to the instructions furnished by the United States  
Surveyor General for **ARIZONA.**

Note: It would have been  
very expensive and incon-  
venient to appear before an  
officer to administer the  
oath to Assistant; hence, it  
was taken by the Surveyor.

*Donald Garbison*  
Chairman

Subscribed and sworn to before me this **11th** day of

**June**, 19 **19**.

*aw hendrix*  
Surveyor-Draftsman Forest Service

OATH OF SURVEYOR

I, **A. W. Hendrix, Surveyor - Draftsman, Forest Service,**  
[Forest Service Title.]

do solemnly swear that, in strict conformity with the special instruc-  
tions of the United States Surveyor General for **ARIZONA**, dated  
**July 9**, 19**15**, and the laws of the United States, I have  
well, faithfully, and truly, in my own proper person, surveyed a tract  
of land **embraced in**

**List**, No. **3-2250**, dated **January 8 19 13**, for  
**Patent**, under the Act of **June 11**, 19 **06**,  
the same to be known as Homestead Entry Survey No. **374**,  
situated within the **COCONINO** National Forest, in  
--surveyed Section **15**, Township **22 N.**, Range **8 E.**, and  
--surveyed Section **---**, Township **---**, Range **---**,

of the **GILA AND SALT RIVER BASE &** meridian, **ARIZONA**, and the  
related retracements and resurveys and section subdivisions, which are  
represented in the following field notes as having been surveyed by me;  
and I further solemnly swear that all the corners of said survey have  
been established and perpetuated in strict accordance with the stated  
special instructions, and in the specific manner described in the field  
notes, and that the following are the original field notes of such  
survey.

*aw hendrix*  
~~Surveyor-Draftsman Forest Service~~  
[Forest Service Title.]

Subscribed and sworn to before me this **21<sup>st</sup>** day of

*Feb*, 19 **20**

*Law. R. Holdeman*

*my com*  
*affirms Feb 11, 1923*

*Natary Public*



COCONINO NATIONAL FOREST

STATE OF ARIZONA

Chains

Applicant for listing, Jacob Stamm; Application No. 375, dated September 25, 1912; List No. 3-2250 dated January 8, 1913; H. E. 022717 made in the Phoenix Land Office on June 13, 1913 by Jacob Stamm.

Surveyed under special instructions from the Surveyor General for Arizona dated July 9, 1915 and designated as Homestead Entry Survey No. 374.

Situated in Sec. 15, T. 22 N., R. 8 E., Gila and Salt River Base and Meridian within the Coconino National Forest, Arizona.

Surveyed under the Acts of June 11, 1906 and March 4, 1915, and October 1, 1918.

Survey commenced September 23, 1915 and executed with a Buff and Buff transit No. 9700-6, equipped with Smith solar attachment.

I test the adjustments of the transit and make necessary corrections.

All measurements were made directly on the slope with an 800 link steel tape. The slope angles were determined with a clinometer.

September 24, 1915.  
Near point for cor. No. 1 of this survey at 7h. 22.9m., 1 p.m., l.m.t., I observe Polaris at E. elong. with telescope direct and reverse, and mark the lines of sight with a tack driven in a stake set firmly in the ground 8.00 chs. N. of my station. Lat. 35° 17' 30" N., Long. 111° 32' 37" W. from special instructions from Surveyor General and later verified. September 24, 1915.

Chains

September 25, 1915.

With my transit over my station of last night's Pol. obsn., I lay off  $1^{\circ} 24'$  to the W. of my line of sight of last night's obsn., and mark my line of sight with a tack in a stake driven in the ground 8.00 chs. N. of my station. To this meridian all courses of this survey are referred.

September 25, 1915.

*Retracement & Subdivision*

September 25, 1915.

Beginning at the cor. to Secs. 15, 16, 21 and 22, a malpais stone 10 x 8 x 10 ins. above ground, marked with 3 notches on S. and 3 notches on E. edges, with mound of stones W. of cor.; and witnessed by trees as described by the Surveyor General.

Thence N.  $1^{\circ} 30'$  W.

On a random line bet. Secs. 15 and 16.

40.00 I make careful search and find no trace of the  $1/4$  cor.

79.20 Fall 9 lks. E. of the point for cor. Secs. 9, 10, 15 and 16 which I determine by running N.  $65^{\circ} 00'$  E., 46 lks. from a pine tree, 52 ins. dia., blazed and scribed as described by the Surveyor General. At this point, I set an iron pipe 36 ins. long, 2 ins. dia., 30 ins. in the ground over broken glass, marked with 4 notches on S. and 3 notches on E. sides, and take the following new witness trees:

A pine 42 ins. dia., blazed and scribed T 22 N. R 8 E, S 15 B T bears S.  $70^{\circ} 05'$  E., 218 lks. dist.

A pine 36 ins. dia., blazed and scribed T 22 N R 8 E S 9 B T bears N.  $83^{\circ} 08'$  W., 23 lks. dist.

No other witnesses available.

COCONINO NATIONAL FOREST

STATE OF ARIZONA

Chains	Thence S. 1° 34' E.
	On a true line bet. Secs. 15 and 16.
39.60	Point for 1/4 sec. cor. in main road, Flagstaff to Grand Canyon. To perpetuate this point, I drive iron bar 24 ins. long, 1 in. dia. flush with surface of ground. From the point S. 89° 54' E., 40 lks., set an iron pipe, 36 ins. long, 1 in. dia., 24 ins. in the ground, over broken glass, marked WC 1/4 S on W. side. Dig pits 24 x 24 x 12 ins. N. and S. 3 ft. and raise a mound of earth, 4 ft. base, 2 ft. high W. of cor.
	Note: The road follows along line bet. Secs. 15 and 16. It was therefore impracticable to set the WC for 1/4 sec. cor. on sec. line.
59.40	Set temporary point for 1/16 Sec. Cor. on W. bdy. SW/4.
79.20	Cor. to Secs. 15, 16, 21 and 22.
<hr/>	
	Thence East.
	On a random line bet. Secs. 15 and 22.
40.13	Fall 8 lks. N. of the 1/4 cor. bet. Secs. 15 and 22, a post, 3 x 3 x 18 ins., above ground, marked and witnessed as described by the Surveyor General.
	Thence N. 89° 53' W.
	On a true line bet. Secs. 15 and 22.
20.06	Set temp. point for 1/16 sec. cor. on S. bdy. SW/4.
30.09	Set temp. point for 1/64 sec. cor. on S. bdy. SW/4 SW/4.
40.13	Cor. to Secs. 15, 16, 21 and 22, heretofore described.
<hr/>	
	Return to point for 1/4 cor. bet. Secs. 15 and 16, heretofore described.
	Thence East.
	On a random latitudinal 1/4 sec. line.
80.37	Fall 14 lks. N. of the 1/4 cor. bet. Secs. 14 and 15 which is a malpais stone 16 x 12 x 10 ins. above ground marked 1/4 on W. face with pits N. and S., 3-1/2 ft.

Chains

dist. and mound 4 ft. base, 2 ft. high W. of cor.

whence:

A yellow pine, 8 ins. dia., blazed and scribed

1/4 S B T bears N. 78° 52' E., 111 lks. dist.

A yellow pine, 6 ins. dia., blazed and scribed

1/4 S B T bears N. 21° 58' W., 24 lks. dist.

Thence N. 89° 54' W.

On a true latitudinal 1/4 sec. line.

79.97 WC to 1/4 sec. cor. bet. Secs. 15 and 16, heretofore described.

80.37 The point for the 1/4 cor. bet. Secs. 15 and 16.

Return to 1/4 cor. bet. Secs. 15 and 22, heretofore described.

Thence North.

On a random meridional 1/4 sec. line.

79.39 Fall 192 lks. E. of the 1/4 cor. bet. Secs. 10 and 15, a pine post, 3 x 3 x 18 ins. above ground, marked and witnessed as described by the Surveyor General.

Thence S. 1° 23' E.

On a true meridional 1/4 sec. line.

39.84 Intersect latitudinal 1/4 sec. line at 40.30 chs. S. 89° 54' E. of the point for 1/4 cor. bet. Secs. 15 and 16 and at 40.07 chs. N. 89° 54' W. of the 1/4 cor. bet. Secs. 14 and 15 set temporary point for center of Sec. 15.

49.73 Set temporary point for 1/64 cor. at center N/2 S/2, Sec. 15.

59.62 Set temporary point for 1/16 cor. at center S/2, Sec. 15.

79.41 The 1/4 cor. bet. Secs. 15 and 22.

Return to temporary point for center, Sec. 15.

Thence N. 89° 54' W.

Along the latitudinal 1/4 sec. line.



COCONINO NATIONAL FOREST

STATE OF ARIZONA

Chains

- 15.11 Set temporary point for 1/256 sec. cor.
- 20.15 Set temporary point for 1/16 cor. at center W/2, Sec. 15.  
September 25, 1915.

September 27, 1915.

Return to temporary point for 1/16 cor. at center W/2, Sec. 15.

Thence S. 1° 28' E.

On true meridional 1/16 sec. line through SW/4, Sec. 15, for flag on temporary point for 1/16 cor. on S. bdy. of SW/4 which is plainly visible.

- 39.58 The temporary point for 1/16 sec. cor.

Return to temporary point for 1/16 cor. on W. bdy. SW/4, Sec. 15.

Thence S. 89° 54' E.

On a true latitudinal 1/16 sec. line through SW/4 for flag on temporary 1/16 cor. at center S/2, Sec. 15 which is plainly visible.

- 20.11 Intersect meridional 1/16 sec. line at 19.79 chs. N. 1° 28' W. of the temporary point for 1/16 cor. on S. bdy. SW/4 Sec., and at 19.79 chs. S. 1° 28' E. of the temporary point for 1/16 cor. at center of W/2 Sec. and set temporary point.

- 40.21 The temporary point for 1/16 cor. at center of S/2, Sec. 15.

Charles D. Hodson, Surveyor - Draftsman,  
Forest Service,

September 27, 1915.

June 11, 1919.

In accordance with letter from Surveyor General dated December 12, 1917, I, A. W. Hendrix, Surveyor - Drafts-

Chains

man, Forest Service, together with Donald E. Harbison, Assistant, return to this claim for the purpose of making necessary retracement of the remaining boundaries of Sec. 15, T. 22 N., R. 8 E.,

The retracement was executed with a Buff and Buff transit No. 10530, equipped with Smith solar attachment. I test the adjustments of the instrument and make necessary corrections.

All distances are horizontal and were reduced from measurements made directly on the slope with a 400 link steel tape. The slope angles were determined with a clinometer.

The courses of this retracement were deflected from the meridian established by me on June 7, 1919 at the Cor. of Secs. 3, 4, 33 and 34, Ts. 22 and 23 N., R. 8 E. in connection with H. E. S. No. 376.

June 11, 1919.

From the cor. of Secs. 9, 10, 15 and 16, heretofore described,

Thence S. 89° 56' E.

Retracing line bet. Secs. 10 and 15, W/2.

40.35 Fall 11 lks. S. 0° 04' W. of 1/4 cor., which is a post 3 x 3 x 18 ins. above ground marked and witnessed as described by the Surveyor General.

True line is N. 89° 55' E., 40.35 chs.

Thence S. 89° 56' E.

Retracing line bet. Secs. 10 and 15, E/2.

40.41 Fall 30 lks. N. 0° 04' E. of cor. of Secs. 10, 11, 14 and 15, heretofore described,

True line is S. 89° 30' E., 40.41 chs.

COCONINO NATIONAL FOREST

STATE OF ARIZONA

Chains From the cor. of Secs. 14, 15, 22 and 23, which is a malpais stone 8 x 10 x 10 ins. above ground, marked and witnessed as described by the Surveyor General.

Thence N. 89° 51' W.

Retracing line bet. Secs. 15 and 22, E/2.

39.81 Fall 2 lks. S. 0° 09' W. of 1/4 cor. heretofore described.

True line is N. 89° 49' W., 39.81 chs.

June 11, 1919.

A. W. Hendrix, Surveyor - Draftsman, Forest Service,

BOUNDARIES OF CLAIM

Charles D. Hodson, Surveyor - Draftsman, Forest Service,  
September 27, 1915.

I adopt mean courses and distances for claim boundaries conformable to legal subdivisions within the quarter-quarter sections invaded.

TRACT A.

Beginning at Cor. No. 1, and C.C. on line bet. Secs. 15 and 22, identical with point for 1/64 cor. on S. bdy. SW/4 SW/4, Sec. 15.

Set a malpais stone 20 x 12 x 6 ins., (no longer stone available), 12 ins. in the ground, over a small stone marked with a cross. I chisel a cross at the point, 1 - H E S 374 on the NE. face, C.C. on N. face; dig pits 24 x 24 x 12 ins., E. and W., 3-1/2 ft. dist. and N. 8 ft. dist. and raise a mound of earth 6 ft. base, 2 ft. high, on closing line N. of cor., whence:

A pine 24 ins. dia., blazed and scribed

1 H E S 374 + B T bears N. 86° 24' W.,  
58 lks. dist.

A pine 12 ins. dia., blazed and scribed

1 H E S 374 + B T bears S. 22° 43' E.,  
177 lks. dist.

COCONINO NATIONAL FOREST

STATE OF ARIZONA.

Chains Cor. of Secs. 15, 16, 21 and 22, brs. N. 89°  
53' W., 10.04 chs. dist.  
1/4 cor. bet. Secs. 15 and 22 brs. S. 89° 53' E.,  
30.09 chs. dist.  
Lat. 35° 17' 30" N., Long. 111° 32' 37" W., obtained  
from the Special Instructions of the Surveyor General  
and later verified.  
Mag. decl. at 11h. Om., a.m., 14° 39' E. Mean Mag.  
decl. 14° 39' 19" E.  
Thence N. 1° 31' W.  
On mean course, through center SW/4 SW/4, Sec. 15.  
17.80 Wire fence, E. and W.  
19.80 To Cor. No. 2.  
Set a pine post 42 x 6 x 6 ins., 30 ins. in the ground  
over broken glass. I drive a nail in the top for the  
point, scribe 2 H E S 374 on the SE. face, dig pits  
24 x 24 x 12 ins. corsswise on this and the succeeding  
course 7 ft. dist. and raise a mound of earth 4 ft.  
base, 2 ft. high SE. of cor., whence:  
A pine 20 ins. dia., blazed and scribed  
2 H E S 374 + B T bears N. 20° 46' W.,  
164 lks. dist.  
A pine 20 ins. dia., blazed and scribed  
2 H E S 374 + B T bears S. 81° 00' W.,  
196 lks. dist.  
Thence S. 89° 54' E.  
Along latitudinal 1/16 sec. line through SW/4 sec. 15,  
over level land.  
10.05 To Cor. No. 3.  
Identical with the point for 1/16 cor. at center  
SW/4, Sec. 15. Set a malpais stone 22 x 10 x 8 ins.,

COCONINO NATIONAL FOREST

STATE OF ARIZONA

Chains (no longer stone available), 14 ins. in the ground  
 over a small stone marked with a cross. I chisel a  
 cross at the point, 3 - H E S 374 on the SE. face, 1/16  
 on NW. face, dig pits 24 x 24 x 12 ins. crosswise on  
 this and the succeeding course 3-1/2 ft. dist. and  
 raise a mound of earth 4 ft. base, 2 ft. high, SE.  
 of cor., whence:

A pine 22 ins. dia., blazed and scribed  
 1/16 - 3 H E S 374 + B T, bears  
 S. 44° 00' E., 208 lks. dist.

A pine 24 ins. dia., blazed and scribed  
 1/16 - 3 H E S 374 + B T, bears  
 S. 70° 00' E., 234 lks. dist.

Thence N. 1° 28' W.

Along meridional 1/16 sec. line through SW/4, Sec. 15.

19.73 Wire fence, E. and W.

19.79 To Cor. No. 4.

Identical with the 1/16 cor. at center of W/2, Sec. 15.

Set a pine post 36 x 6 x 6 ins., 24 ins. in the ground  
 over a charred stake. I drive a nail at the point,

scribe 4 - H E S 374 on the SE. face, 1/16 on NW.

face, dig pits 24 x 24 x 12 ins. crosswise on this

and the succeeding course, 7 ft. dist. and raise a

mound of earth, 4 ft. base, 2 ft. high SE. of cor.,

No bearings available.

Thence S. 89° 54' E.

Along latitudinal 1/4 sec. line through Sec. 15.

1.45 Wire fence, N. and S.

5.04 To Cor. No. 5.

Set a pine post 36 x 6 x 6 ins., 24 ins. in the ground

COCONINO NATIONAL FOREST

STATE OF ARIZONA

Chains over a charred stake. I drive a nail at the point,  
 scribe 5 - H E S 374 on SW. face, dig pits 24 x 24 x  
 12 ins. crosswise on this and the succeeding course,  
 7 ft. dist. and raise a mound of earth 4 ft. base,  
 2 ft. high, SW. of cor.  
 No bearings available.

Thence S. 1° 27' E.

On a mean course over level land.

4.95 To Cor. No. 6.

Set a pine post 36 x 7 x 5 ins., 24 ins. in the ground  
 over a charred stake. I drive a nail at the point,  
 scribe 6 - H E S 374 on the SW. face, dig pits 24 x  
 24 x 12 ins. crosswise on this and the succeeding  
 course 3-1/2 ft. dist. and raise a mound of earth 4 ft.  
 base, 2 ft. high SW. of cor.,

No bearings available.

Thence S. 89° 54' E.

On a mean course over level land.

10.07 To Cor. No. 7.

Set a pine post 36 x 8 x 8 ins., 24 ins. in the ground  
 over a charred stake. I drive a nail at the point,  
 scribe 7 - H E S 374 on the SW. face, dig pits 24 x  
 24 x 12 ins. crosswise on this and the succeeding  
 course 7 ft. dist. and raise a mound of earth 4 ft.

base, 2 ft. high, SW. of cor., whence:

A pine 24 ins. dia., blazed and scribed

7 H E S 374 + B T, bears N. 21° 42' E.,

252 lks. dist.

A pine 30 ins. dia., blazed and scribed

7 H E S 374 + B T, bears N. 10° 55' E.,

240 lks. dist.

COCONINO NATIONAL FOREST

STATE OF ARIZONA

Chains

Thence S. 1° 24' E.

On mean course over level land.

4.95

To Cor. No. 8.

Set a pine post 42 x 8 x 8 ins., 30 ins. in the ground over a charred stake. I drive a nail at the point, scribe 8 - H E S 374 on the SW. face, dig pits 24 x 24 x 12 ins. crosswise on this and the succeeding course 3-1/2 ft. dist. and raise a mound of earth 4 ft. base, 2 ft. high, SW. of cor.,

No bearings available.

Thence S. 89° 54' E.

On mean course over level land.

4.21

To Cor. No. 9 on N. bdy. road exception 82 lks. west of temp. 1/64 cor. center N/2 S/2, Sec. 15.

Set a pine post 42 x 6 x 6 ins., 30 ins. in the ground over a charred stake. I drive a nail at the point, scribe 9 - H E S 374 on the WSW. face, dig pits 24 x 24 x 12 ins. crosswise on this and the succeeding course 10 ft. dist. and raise a mound of earth 4 ft. base, 2 ft. high, WSW. of cor., whence:

A pine 18 ins. dia., blazed and scribed

9 H E S 374 + B T, bears N. 31° 00' E.,  
264 lks. dist.

A pine 36 ins. dia., blazed and scribed

9 H E S 374 + B T, bears N. 8° 30' W.,  
288 lks. dist.

September 27, 1915.

The center line method of laying down the boundaries of the Road Exception was not used in this survey.

COCONINO NATIONAL FOREST

STATE OF ARIZONA

Chains

September 28, 1915.

Thence S. 62° 24' W.

Over level land along NW. bdy. road exception.

11.55 To Cor. No. 10.

Set a pine post 36 x 6 x 6 ins., 24 ins. in the ground

over a charred stake. I drive a nail at the point,

scribe 10 - H E S 374 on NW. face, dig pits 24 x 24 x

12 ins. crosswise on this and the succeeding course

3-1/2 ft. dist. and raise a mound of earth 4 ft. base,

2 ft. high, NW. of cor.,

No bearings available.

Thence S. 48° 00' W.

Over level land along NW. bdy. road exception.

8.72 To Cor. No. 11.

Set a malpais stone 18 x 14 x 10 ins., (no longer

stone available), 12 ins. in the ground over a

small stone marked with a cross. I chisel a

cross at the point, 11 - H E S 374 on the NW. face,

dig pits 24 x 24 x 12 ins. crosswise on this and

the succeeding course 3-1/2 ft. dist. and raise a

mound of earth 4 ft. base, 2 ft. high, NW. of cor.,

whence:

A pine 24 ins. dia., blazed and scribed

11 H E S 374 + B T, bears

N. 45° 58' W., 38 lks. dist.

A pine 12 ins. dia., blazed and scribed

11 H E S 374 + B T, bears

S. 64° 12' W., 53 lks. dist.

Thence S. 37° 02' W.



COCONINO NATIONAL FOREST

STATE OF ARIZONA

Chains

Over level land along NW. bdy. road exception.

7.40

To Cor. No. 12.

Set a malpais stone 18 x 8 x 8 ins., (no longer stone available) 12 ins. in the ground over broken glass,

I chisel a cross at the point, 12 - H E S 374 on NW. face, and raise a mound of stone 2 ft. base, 1-1/2 ft. high NW. of cor., whence:

A pine 30 ins. dia., blazed and scribed  
12 H E S 374 + B T, bears S. 49° 45' E.,  
291 lks. dist.

A pine 30 ins. dia., blazed and scribed  
12 H E S 374 + B T, bears S. 84° 30' E.,  
232 lks. dist.

Thence S. 18° 45' W.

Over level land along NW. bdy. of road exception.

13.18

To Corner No. 13 and Closing Corner.

On line bet. Sections 15 and 24. Set a malpais stone 22 x 10 x 8 ins., (no longer stone available), 14 ins. in the ground over broken glass.

I chisel a cross at the point, 13 - H E S 374

on NW. face, C. C on NNE. face, and dig pits 24

x 24 x 12 ins., E. and W., 4 ft. distant and

NNE. on closing line 8 ft. distant and raise a

mound of earth 6 ft. base, 2 ft. high on closing

line NNE. of cor., whence:

A pine 36 ins. dia., blazed and

scribed 13 H E S 374 + B T

bears N. 9° 36' E., 133 lks.

distant.

COCONINO NATIONAL FOREST

STATE OF ARIZONA

Chains

A pine 48 ins. dia., blazed and

scribed 13 H E S 374 + B T,

Bears N. 37° 02' W., 139 lks.

distant.

Cor. Sections 15, 16, 21 and 22,

bears N. 89° 53' W., 13.20 chs.

distant.

1/4 corner between Sections 15 and

22 bears S. 89° 53' E., 26.93

chs. distant.

Thence N. 89° 53' W.

Over level land along line between Sections 15 and 22.

3.16 To Cor. No. 1, the place of beginning.

Beginning at Corner No., 14.

On meridional 1/4 section line. 43 links, South of temporary 1/64 corner center N/2 S/2, Section 15.

Set a pine post 36 x 6 x 6 ins., 24 ins. in the ground over a charred stake. Drive a nail at the point,

scribe 14 - H E S 374 on SSW. face, dig pits 24 x

24 x 12 ins. crosswise on each course 8 feet distant

and raise a mound of earth 4 ft. base, 2 feet high SSW. of corner, whence:

A pine 36 ins. dia., blazed and

scribed 14 H E S 374 + B T,

bears N. 21° 12' W., 350 lks.

distant.

A pine 24 ins. dia., blazed and

COCONINO NATIONAL FOREST

STATE OF ARIZONA

Chains

scribed 14 H E S 374 + B T, bears

S. 35° 48' W., 116 lks. distant.

Cor. No. 9 heretofore described,

bears N. 62° 37' W., 93 links dis-

tant.

---

Thence S. 1° 23' E.

Over level land along meridional 1/4 section line.

9.46 To Corner No. 15 and 1/16 Section corner.

Set a charred post 36 x 6 x 6 ins., 24 ins. in the ground over a charred stake. I drive a nail at the

point, scribe 15 - H E S 374 on NW. face, 1/16 on

NE. face, dig pits 24 x 24 x 12 ins. crosswise on

this and the succeeding course 7 ft. distant and

raise a mound of earth 4 ft. base, 2 ft. high, NW.

of corner, whence:

A pine 24 ins. dia., blazed and

scribed 1/16 - 15 H E S 374

+ B T, bears N. 66° 00' W.,

127 lks. dist.

A pine 22 ins. dia., blazed and

scribed 1/16 - 15 H E S 374

+ B T bears S. 18° 00' E.,

42 lks. dist.

---

Thence N. 89° 54' W.

Over level land along latitudinal 1/16 sec. line in SW/4, Sec. 15.

10.35 Wire fence, N. 60° E. and S. 60° W.

14.50 Wire fence, N. 60° E. and S. 60° W.

15.08 To Cor. No. 16.

Chains

Set a malpais stone 24 x 12 x 8 ins., 14 ins. in the ground over a small stone marked with a cross. I chisel a cross at the point, 16 - H E S 374 on NW. face, dig pits 24 x 24 x 12 ins. crosswise on this and the succeeding course 3-1/2 ft. dist. and raise a mound of earth 4 ft. base, 2 ft. high NW. of cor., whence:

A pine 48 ins. dia., blazed and scribed

16 H E S 374 + B T bears S. 19° 40' W.,

125 lks. dist.

A pine 60 ins. dia., blazed and scribed

16 H E S 374 + B T bears S. 30° 00' E.,

159 lks. dist.

Thence S. 1° 27' E.

On mean course over level land.

2.45 The east cor. of a dug out 14 x 16 ft., long side bearing NW.

4.94 To Cor. No. 17.

Set a malpais stone 24 x 8 x 8 ins., 14 ins. in the ground over a small stone marked with a cross, I chisel a cross at the point, 17 - H E S 374 on NW. face and raise a mound of stone 2 ft. base, 1-1/2 ft. high NW. of cor., whence:

A pine 16 ins. dia., blazed and scribed

17 H E S 374 + B T bears S. 19° 00' E.,

72 lks. dist.

A pine 20 ins. dia., blazed and scribed

17 H E S 374 + B T bears East, 117 lks.

dist.

Thence N. 89° 54' W. on mean course.

Over level land.

4.54 To Cor. No. 18 on SE. bdy. road exception.

Set a malpais stone 18 x 12 x 6 ins., (no longer stone

COCONINO NATIONAL FOREST

STATE OF ARIZONA

Chains

available), 12 ins. in the ground over a small stone marked with a cross. I chisel a cross at the point, 18 - H E S 374 on ENE. face and raise a mound of stones 2 ft. base, 1-1/2 ft. high, ENE. of cor. whence:

A pine 24 ins. dia., blazed and scribed 18 H E S 374 + B T bears S. 15° 06' E., 104 lks. dist.

A pine 36 ins. dia., blazed and scribed 18 H E S 374 + B T bears N. 78° 35' E., 39 lks. dist.

Thence N. 37° 02' E. Over level land along SE. bdy. road exception. To Cor. No. 19.

3.79

Set a malpais stone 22 x 10 x 6 ins., ( no longer stone available) 14 ins. in the ground over a small stone marked with a cross. I chisel a cross at the point, 19 - H E S 374 on the SE. face and raise a mound of stone 2 ft. base, 1-1/2 ft. high SE. of cor. whence:

A pine 6 ins. dia., blazed and scribed 19 H E S 374 + B T bears N. 60° 25' E., 50 lks. dist.

A pine 12 ins. dia., blazed and scribed 19 H E S 374 + B T bears S. 49° 55' E., 63 lks. dist.

Cor. No. 11 previously described bears N. 47° 29' W., 76 lks. dist.

Thence N. 48° 00' E. Over level land along NE. bdy. road exception.

Chains

8.54 To Cor. No. 20.

Set a pine post 42 x 6 x 6 ins., 30 ins. in the ground over a charred stake. I drive a nail at the point, scribe 20 - H E S 374 on SE. face, dig pits 24 x 24 x 12 ins. crosswise on this and the succeeding course 7 ft. dist. and raise a mound of earth 4 ft. base, 2 ft. high SE. of cor. whence:

Cor. No. 10, previously described bears

N. 34° 48' W., 46 lks. dist.

No other bearings available.

Thence N. 62° 24' E.

Over level land along SE. bdy. road exception.

11.98 To Cor. No. 14, the place of beginning.

Beginning at Cor. No. 21.

On meridional 1/16 sec. line through center SW/4, Sec. 15.

Set a malpais stone 30 x 16 x 8 ins., 20 ins. in the ground over a small stone marked with a cross. I chisel a cross at the point, 21 - H E S 374 on SSW. face, and raise a mound of stone 2 ft. base, 1-1/2 ft. high SSW. of cor. whence:

A pine 36 ins. dia., blazed and scribed

21 H E S 374 + B T bears N. 50° 30' E.,

109 lks. dist.

A pine 12 ins. dia., blazed and scribed

21 H E S 374 + B T bears S. 12° 45' E.,

60 lks. dist.

Cor. No. 18 previously described bears N.

37° 02' E., 76 lks. dist.

COCONINO NATIONAL FOREST

STATE OF ARIZONA

Chains

Thence S. 1° 28' E.

Over level land along meridional 1/16 line in SW/4,

Sec. 15.

14.23 To Cor. No. 22 and CC. on line bet. Secs. 15 and 22 also  
1/16 Sec. Cor. on S. bdy. SW/4, Sec. 15.

Set a pine post 36 x 6 x 6 ins., 24 ins. in the ground  
over a charred stake. I drive a nail at the point,  
scribe 22 - H E S 374 on NW. face, CC. 1/16 on N. face,  
dig pits 24 x 24 x 12 ins., E. and W. 4 ft. dist. and  
N. 8 ft. dist. and raise a mound of earth 6 ft. base,  
2 ft. high on closing line N. of cor. whence:

A pine 10 ins. dia., blazed and scribed

1/16 - 22 H E S 374 + B T bears N. 11° 01' E.,

350 lks. dist.

A pine 12 ins. dia., blazed and scribed

1/16 - 22 H E S 374 + B T bears N. 48° 09' W.,

239 lks. dist.

1/4 cor. bet. Secs. 15 and 22 heretofore de-  
scribed bears S. 89° 53' E., 20.06 chs. dist.

Cor. Secs. 15, 16, 21 and 22 heretofore de-

scribed bears N. 89° 53' W., 20.07 chs. dist.

Thence N. 89° 53' W.

Over level land.

6.07 To cor. No. 23 and CC. on line bet. Secs. 15, and 22.

Set a malpais stone 18 x 8 x 8 ins., (no longer stone  
available) 12 ins. in the ground over broken glass.

I chisel a cross at the point, 23 - H E S 374 on ENE.  
face, CC. on NNE. side, dig pits 24 x 24 x 12 ins.

crosswise on line E. and W., 4 ft. dist. and NNE. 8 ft.  
dist. and raise a mound of earth 6 ft. base, 2 ft.

high on closing line NNE. of cor. whence:

A pine 24 ins. dia., blazed and scribed

COCONINO NATIONAL FOREST

STATE OF ARIZONA

Chains

23 - H E S 374 + B T bears N. 68° 32' E.,

115 lks. dist.

A pine 24 ins. dia., blazed and scribed

23 H E S 374 + B T bears S. 6° 47' W., 268

lks. dist.

Cor. Secs. 15, 16, 21 and 22 heretofore described

bears N. 89° 53' W., 14.00 chs. dist.

Cor. No. 13 heretofore described bears

N. 89° 53' W., 80 lks. dist.

1/4 cor. bet. Secs. 15 and 22 heretofore de-

scribed bears S. 89° 53' E., 26.13 chs. dist.

Thence N. 18° 45' E.

Over level land along SE. bdy. road exception.

12.82 To Cor. No. 24.

Set a malpais stone 22 x 6 x 4 ins., (no longer stone available), 14 ins. in the ground over broken glass.

Chisel a cross at the point, 24 - H E S 374 on SE.

face and raise a mound of stone 2 ft. base, 1-1/2 ft.

high SE. of cor. whence;

A pine 30 ins. dia., blazed and scribed

24 H E S 374 + B T bears N. 82° 30' E.,

163 lks. dist.

A pine 30 ins. dia., blazed and scribed

24 H E S 374 + B T bears S. 47° 49' E.,

216 lks. dist.

Cor. No. 12, heretofore described, bears N. 62°

07' W., 77 lks. dist.

Thence N. 37° 02' E.

Over level land along SE. bdy. road exception.



COCONINO NATIONAL FOREST

STATE OF ARIZONA

121

Chains

2.66

To Cor. No. 21 and place of beginning.

AREA

Area in Tract A. 34.98 acres

Area in Tract B. 9.23 acres

Area in Tract C. 4.86 acres

Total Area 49.07 acres

Tract D, (Unlisted area in Road Exception,) 3.13 acres.

3.13

IMPROVEMENTS

The improvements made upon this claim and belonging to the claimant consist of the following:

A dug out with board roof, 16 x 14 ft., the long side extending NW. and SE. and the E. cor. of which bears from Cor. No. 17 N. 1° 27' W., 249 lks. dist.

Value \$25.00

Approximately 10.00 chs. of wire fence.

Value \$8.00

DESCRIPTION

This claim is situated in the S. end of Black Bill Park with a very gentle slope to the N. The north end is less than 5 ft. lower than the south end.

The soil is a sandy loam with cinders covering approximately 50 per cent of the entire area.

Approximately 1/2 acre, enclosed within the wire fence, has been cultivated but the crop was a failure.

There is no water on the claim and water for all purposes has to be hauled 5 miles.

There is no timber of commercial value on the claim.

I saw no indication of mineral on this claim.

Chains

CONFLICTS AND ADJOINING CLAIMS.

There are no conflicts.

H. E. 0259, Benjamin Doney, entryman, joins this claim on the N. and W. along lines 2-3 and 3-4.

The legal subdivisional portion of this claim, more fully described as follows:- W/2 W/2 SE/4 NW/4, Sec. 15 joins this claim on the north along line 4-5.

Cliffs, the nearest postoffice is 5 miles in a southerly direction. Flagstaff, the nearest railroad and market point is 10 miles in a southwesterly direction and is reached by good wagon road.

TRAVERSE - TRACT A.

Course	Dist.	N.	S.	E.	W.
N. 1° 31' W.	19.80	19.79			.52
S. 89° 54' E.	10.05		.02	10.05	
N. 1° 28' W.	19.79	19.78			.51
S. 89° 54' E.	5.04		5.01	5.04	
S. 1° 27' E.	4.95		4.95	.13	
S. 89° 54' E.	10.07		.02	10.07	
S. 1° 24' E.	4.95		4.95	.12	
S. 89° 54' E.	4.21		.01	4.21	
S. 62° 24' W.	11.55		5.35		10.24
S. 48° 00' W.	8.72		5.83		6.48
S. 37° 02' W.	7.40		5.91		4.46
S. 18° 45' W.	13.18		12.48		4.24
N. 89° 53' W.	3.16	.00			3.16
	122.87	39.57	39.53	29.62	29.61

Error in Lat. and Dep.  $\frac{39.53}{10} = .04$

Closing error: 1:2980.

Approximately 1/3 acre enclosed within the wire fence has been cultivated but the crop was a failure. There is no water on the claim and water for all purposes has to be hauled 5 miles. There is no timber of commercial value on the claim. I saw no indication of mineral on this claim.

123

COCONINO NATIONAL FOREST

STATE OF ARIZONA

Chains

TRAVERSE - TRACT B.

Course	Dist.	N.	S.	E.	W.
S. 1° 23' E.	9.46		9.46	.23	
N. 89° 54' W.	15.08	.03			15.08
S. 1° 27' E.	4.94		4.94	.13	
N. 89° 54' W.	4.54	.00			4.54
N. 37° 02' E.	3.79	3.03		2.28	
N. 48° 00' E.	8.54	5.71		6.35	
N. 62° 24' E.	11.98	5.55		10.62	
	<u>58.35</u>	14.32	14.40	19.61	19.62
			<u>14.32</u>		<u>19.61</u>
Error in Lat. and Dep.			.08		.01

Closing error 1:724

TRAVERSE - TRACT C.

Course	Dist.	N.	S.	E.	W.
S. 1° 28' E.	14.23		14.23	.36	
N. 89° 53' W.	6.07	.01			6.07
N. 18° 45' E.	12.82	12.14		4.12	
N. 37° 02' E.	2.66	2.12		1.60	
	<u>35.78</u>	14.27	14.23	6.08	6.07
		<u>14.23</u>		<u>6.07</u>	
Error in Lat. and Dep.		.04		.01	

Closing error 1:868

Survey completed June 11, 1919.

*Charles D. Hodson*

Surveyor - Draftsman,  
Forest Service,

*Augustus*

Surveyor - Draftsman,  
Forest Service,

NATIONAL FOREST

STATE OF ARIZONA

174

Traverse - Tract B.		Traverse - Tract C.	
Course	Dist.	Course	Dist.
S. 1° 23' N.	9.46	S. 1° 28' E.	14.23
N. 89° 54' W.	16.08	N. 89° 53' W.	6.07
S. 1° 27' E.	4.94	N. 18° 45' E.	12.82
N. 89° 54' W.	4.84	N. 37° 02' E.	2.36
N. 37° 02' E.	2.79	S. 7° 08' W.	32.78
N. 48° 00' E.	8.24		
N. 69° 34' E.	11.98		
	58.34		
Error in Lat. and Dep.		Error in Lat. and Dep.	
Closing error 1:784		Closing error 1:888	
Survey completed June 12, 1912.			

*Charles C. Johnson*  
 Surveyor - District  
 Forest Service

*William J. ...*  
 Surveyor - District  
 Forest Service

DIRECTIONS.—1. Carry out calculations to two decimals only.

2. In balancing Latitudes and Departures do not obliterate or change the original figures.

Put the corrected figure or figures above in red ink. Do not change the footing of the original figures, but put below them the corrected footing in red ink.

The corrections for balancing fallings should be proportional to the lengths of the lines.

3. In calculations of fallings take result to nearest link. In calculations of N. and S. areas drop all after second decimal. Surveyors are required to use the Standard Field Tables issued by the G. L. O.

4. Only three copies of this tabulation are necessary, for the District Office, the Surveyor General, and the Commissioner.

**TABLING AND CALCULATIONS OF HOMESTEAD ENTRY SURVEY NO. 374**, STATE OF **ARIZONA**  
**Tract A.** **Jacob Stamm - Coconino**

CORNERS.	BEARING.	DISTANCE.	LATITUDES.			DEPARTURES.		DOUBLE M. D.		N. AREAS.	S. AREAS.
			NORTH.	SOUTH.	EAST.	WEST.					
1-2	N. 1° 31' W.	19.80	19 79				3	53	10 48		20
2-3	S. 89° 54' E.	10.05		02	10 05		52	10 05			24
3-4	N. 1° 28' W.	19.79	19 78				51	19 59	387 29		99
4-5	S. 89° 54' E.	5.04		01	5 04			24 12			79
5-6	S. 1° 27' E.	4.95		4 95	13			29 29		144	92
6-7	S. 89° 54' E.	10.07		02	10 07			39 49			17
7-8	S. 1° 24' E.	4.95		4 95	12			49 68		245	54
8-9	S. 89° 54' E.	4.21		01	4 21			54 01			17
9-10	S. 62° 24' W.	11.55		5 35		10 24		47 98		257	25
10-11	S. 48° 00' W.	8.72		5 83		6 48		31 26		182	09
11-12	S. 37° 02' W.	7.40		5 91		4 46		20 32		120	13
12-13	S. 18° 45' W.	13.18		12 48		4 24		11 62	00	145	
13-1	N. 89° 53' W.	3.16	00			3 16		4 22			
		122.87	39 57	39 53	29 62	29 61		397	77	1097	32
			39 65	39 55	29 62	29 62				397	77
										20 ) 699	55
										Area	34 98
	Closing error 1:2980										

125

e. g. m. ft

**DIRECTIONS.**—1. Carry out calculations to two decimals only.

2. In balancing Latitudes and Departures do not obliterate or change the original figures.

Put the corrected figure or figures above in red ink. Do not change the footing of the original figures, but put below them the corrected footing in red ink.

The corrections for balancing fallings should be proportional to the lengths of the lines.

3. In calculations of fallings take result to nearest link. In calculations of N. and S. areas drop all after second decimal. Surveyors are required to use the Standard Field Tables issued by the G. L. O.

4. Only three copies of this tabulation are necessary, for the District Office, the Surveyor General, and the Commissioner.

**TABLING AND CALCULATIONS OF HOMESTEAD ENTRY SURVEY NO. 374, STATE OF ARIZONA**

**Tract B. Jacob Stamm - Coconino**

CORNERS.	BEARING.	DISTANCE.	LATITUDES.		DEPARTURES.		DOUBLE M. D.		N. AREAS.	S. AREAS.		
			NORTH.	SOUTH.	EAST.	WEST.						
14-15	S. 1° 23' E.	9.46		9		23		38	73			
15-16	N. 89° 54' W.	15.08	5 03	46	15	08		23	89	1	19	
16-17	S. 1° 27' E.	4.94		3 94	13			8	95		44	
17-18	N. 89° 54' W.	4.54		00	4	54		4	54		05	
18-19	N. 37° 02' E.	3.79	3 03		2	28		2	28	6	95	
19-20	N. 48° 00' E.	8.54	5 71		6	35		10	91	62	41	
20-14	N. 62° 24' E.	11.98	5 55		10	62		27	88	155	01	
		58.33	14 32	14 40	19 61	19 62		225	59	225	59	
			14 38	14 38	19 61	19 61		20	184	53	53	
<b>Closing error 1:724</b>											Area	92 26
											92 26	8 ft

410.12  
225.59  
184.53  
92.26

127

DIRECTIONS.—1. Carry out calculations to two decimals only.

2. In balancing Latitudes and Departures do not obliterate or change the original figures.

Put the corrected figure or figures above in red ink. Do not change the footing of the original figures, but put below them the corrected footing in red ink.

The corrections for balancing fallings should be proportional to the lengths of the lines.

3. In calculations of fallings take result to nearest link. In calculations of N. and S. areas drop all after second decimal. Surveyors are required to use the Standard Field Tables issued by the G. L. O.

4. Only three copies of this tabulation are necessary, for the District Office, the Surveyor General, and the Commissioner.

Tract C. Jacob Stamm - Coconino

TABLING AND CALCULATIONS OF HOMESTEAD ENTRY SURVEY NO. 374, STATE OF ARIZONA

CORNERS.	BEARING.	DISTANCE.	LATITUDES.		DEPARTURES.		DOUBLE M. D.		N. AREAS.	S. AREAS.
			NORTH.	SOUTH.	EAST.	WEST.				
21 - 22	S. 1° 28' E.	14.23	14	23	36	5	11	79	168	01
22 - 23	N. 89° 53' W.	6.07					6	07	06	
23 - 24	N. 18° 45' E.	12.82	12	14	4	12	4	12	49	93
24 - 21	N. 37° 02' E.	2.66	2	12	1	60	9	84	20	86
		35.78	14	27	6	08			70	85
			14	25	6	07			70	85
Closing error 1:868									97	16
									Area	4 86 acres

8 m Ft

129

DIRECTIONS.—1. Carry out calculations to two decimals only.

2. In balancing Latitudes and Departures do not obliterate or change the original figures.

Put the corrected figure or figures above in red ink. Do not change the footing of the original figures, but put below them the corrected footing in red ink.

The corrections for balancing fallings should be proportional to the lengths of the lines.

3. In calculations of fallings take result to nearest link. In calculations of N. and S. areas drop all after second decimal. Surveyors are required to use the Standard Field Tables issued by the G. L. O.

4. Only three copies of this tabulation are necessary, for the District Office, the Surveyor General, and the Commissioner.

TABLING AND CALCULATIONS OF HOMESTEAD ENTRY SURVEY NO. 374, STATE OF ARIZONA, COCONINO

8-2349

CORNERS.	BEARING.	DISTANCE.	LATITUDES.		DEPARTURES.		DOUBLE M. D.	N. AREAS.	S. AREAS.
			NORTH.	SOUTH.	EAST.	West.			
X X	N. 1-34 W.	79.20'	SECTION 79 17	15.		2 17			
	N. 89-55 E.	40.35'	06		40 35				
	S. 89-30 E.	40.41'		35	40 41				
X	S. 1-01 E.	79.23'		79 22	1 41				
	N. 89-49 W.	39.81'	13			39 81			
	N. 89-53 W.	40.13'	08			40 13			
		<u>319.15</u>	79 46	79 57	82 17	82 17			
			4			11			
			13	13		06			
	Closing error	1/2255							

131



DIRECTIONS.—1. Carry out calculations to two decimals only.  
 2. In balancing Latitudes and Departures do not obliterate or change the original figures.  
 Put the corrected figure or figures above in red ink. Do not change the footing of the original figures, but put below them the corrected footing in red ink.  
 The corrections for balancing fallings should be proportional to the lengths of the lines.  
 3. In calculations of fallings take result to nearest link. In calculations of N. and S. areas drop all after second decimal. Surveyors are required to use the Standard Field Tables issued by the G. L. O.  
 4. Only three copies of this tabulation are necessary, for the District Office, the Surveyor General, and the Commissioner.

TABLING AND CALCULATIONS OF HOMESTEAD ENTRY SURVEY NO. 374, STATE OF ARIZONA.

CORNERS.	BEARING.	DISTANCE.	LATITUDES.		DEPARTURES.		DOUBLE M. D.	N. AREAS.		S. AREAS.
			NORTH.	SOUTH.	EAST.	WEST.				
23-13	N. 89°53' W.	.80	00		80	80	00			
13-12	N. 18-45 E.	13.18	12 48		4 24	4 23	52 53			
12-11	N. 37-02 E.	7.40	5 91		4 46	12 92	76 36			
11-10	N. 48-00 E.	8.72	5 83		6 48	23 86	139 10			
10-9	N. 62-24 E.	11.55	5 35		10 24	40 58	217 10			
9-pt 1/64	S. 89-54 E.	.82		00	82	51 64			8 00	
pt 1/64-14	S. 1-23 E.	.43		43	01	52 47			22 56	
14-20	S. 62-24 W.	11.98		5 55		41 86			232 32	
20-19	S. 48-00' W.	8.54		5 71		24 89			142 12	
19-18	S. 37-02 W.	3.79		3 03		16 26			49 27	
18-pt	N. 89-54 W.	.48	00			13 50			00	
pt-21	S. 1-28 E.	.61		61		13 04			7 95	
21-24	S. 37-02 W.	2.66		2 12		11 46			24 30	
24-23	S. 18-45 W.	12.82		12 14		5 73			69 50	
		63.78	29 57	29 59	26 27		485 39		548 02	
			29 58	29 57	26 25				485 39	
	Error in Lat. and Dep.			02	02				20/ 62 63	
	Closing error 1/2962		Tract D - Unlisted Area in Road Exception						3 13 Acres	

133

APPROVAL

Office of the United States Surveyor General,

Phoenix, Arizona, June 7, 1920

The foregoing field notes of Homestead Entry Survey No.

374

executed by *Charles D. Hodson & A. H. Hendrix, Surveyors-Draftsmen* [Forest Service Title.]  
under his special instructions, dated *July 9*, 1915, having  
been critically examined, and the necessary corrections and explanations  
made, the said field notes, and the surveys they describe, are hereby  
approved.

*Frank P. Trott*  
-----  
U. S. Surveyor General.

I certify that the foregoing transcript of the field notes of the  
above-described survey in the State of *Arizona*, has been  
correctly copied from the original notes on file in this office.

FRANK P. TROTT

-----  
U. S. Surveyor General.