

ORIGINAL

33

U. S. DEPARTMENT OF AGRICULTURE FOREST SERVICE

SEP-4-1917
NOV-2-1918
MAR-2-1918

FIELD NOTES

OF

HOMESTEAD ENTRY SURVEY NO. 453

SITUATED IN THE SITGREAVES NATIONAL FOREST

ADMINISTRATIVE DISTRICT NO. 3

In Section 31 , unsurveyed, Township 10 N., Range 23 E.

In Section 32 , unsurveyed, Township 10 N., Range 23 E.

of the

Gila and Salt River Base and Meridian.

State of

ARIZONA

Applicant for listing C. H. Frost,

Residence		Showlow, Arizona	
Application No.	216 ✓	, dated	July 22 , 1910 ✓
Application No.	415 ✓	, dated	November 25 , 1912 ✓
List No.	3-1281 ✓	, dated	May 5 , 1911 ✓
List No.	3-2355 ✓	, dated	March 7 , 1913 ✓

Applicant for survey ^{1e5} Charles H. Frost,

Residence		Showlow, Arizona	
H. E. No.	016573 ✓	, dated	January 31 , 1912 ✓
H. E. No.	024517 ✓	, dated	March 2 , 1914 ✓

Office

Land District Phoenix, Arizona

Survey executed by R. P. A. Johnson, Surveyor - Draftsman
[Forest Service Title.]

Under special instructions dated April 17 , 1916 ✓

Survey commenced August 7 , 1916

Survey completed August 9 , 1916

Under Acts of June 11, 1906 and July 31, 1916

1

OATH OF ASSISTANTS

We hereby certify that we assisted R. P. A. Johnson
Surveyor Craftsman [Forest Service Title.] in surveying all those
 parts or portions of Homestead Entry Survey No. 453, in the State
 of Arizona which are represented in the following field notes
 as having been surveyed by him and under his direction; and that said
 survey has been in all respects, to the best of our knowledge and
 belief, well and faithfully surveyed, and the corner monuments estab-
 lished, according to the instructions furnished by the United States
 Surveyor General for Arizona

Note: It would have been very expensive and inconvenient to appear before an officer to administer oaths to Assistants; hence, they were taken by the Surveyor.

Nelson Newman, Chainman

Chester A. Lee, Chainman

Subscribed and sworn to before me this fourteenth day of
August, 1916.

R. P. A. Johnson
Surveyor Craftsman

OATH OF SURVEYOR

I, R. P. A. Johnson, *Surveyor Craftsman*
 [Forest Service Title.]

do solemnly swear that, in strict conformity with the special instruc-
 tions of the United States Surveyor General for Arizona, dated
April 17, 1916, and the laws of the United States, I have
 well, faithfully, and truly, in my own proper person, surveyed a tract
 of land embraced in

List, No. 3-1281 dated May 5, 1911
List, No. 3-2355, dated March 7, 1914, for
patent, under the Act of June 11, 1906,
 the same to be known as Homestead Entry Survey No. 453,
 situated within the Sitgreaves National Forest, in
unsurveyed Section 31, Township 10N, Range 23E, and
unsurveyed Section 32, Township 10N, Range 23E,

of the Gila and Salt River Basins meridian, Arizona, and the
 related retracements and resurveys and section subdivisions, which are
 represented in the following field notes as having been surveyed by me;
 and I further solemnly swear that all the corners of said survey have
 been established and perpetuated in strict accordance with the stated
 special instructions, and in the specific manner described in the field
 notes, and that the following are the original field notes of such
 survey.

DISTRICT OF COLUMBIA
 CITY OF WASHINGTON

R. P. A. Johnson
Surveyor Craftsman
 [Forest Service Title.]

Subscribed and sworn to before me this 9th day of
March, 1917.

Sylvester L. McLaughlin



SITGREAVES NATIONAL FOREST

STATE OF ARIZONA

Chains

Applicant for listing, C. H. Frost; Application Nos. 216 ✓
and 415, ✓ dated July 22, 1910 ✓ and November 25, 1912 ✓; List
Nos. 3-1281 ✓ and 3-2355, ✓ dated May 5, 1911 ✓ and March 7,
1913 ✓; H. E. Nos. 016573 ✓ and 024517, ✓ made in the Phoenix
Land Office on January 31, 1912 ✓ and March 2, 1914 ✓ by
Charles H. Frost.

The listing in this case was erroneously made by legal
subdivisions in a Township which was never legally
surveyed, and no attempt was made to locate original
list lines on ground. This survey is in the nature
of a cooperative survey and will be used as a basis for
supplemental and amendatory listing and entry.

Surveyed under special instructions from the Surveyor
General for Arizona, dated April 17, 1916 ✓ and desig-
nated as Homestead Entry Survey No. 453.

Situated in what will probably be, when surveyed, Secs.
31 and 32, T. 10 N., R. 23 E., Gila and Salt River Base
and Meridian, within the Sitgreaves National Forest,
Arizona.

Surveyed under the Acts of June 11, 1906 and July 31,
1916.

Survey commenced August 7, 1916 and executed with a Buff
and Buff transit equipped with Smith solar attachment.

I test the adjustments of the transit and make necessary
corrections.

All distances are horizontal and were reduced from meas-
urements made directly on the slope with a 500 link
steel tape. The slope angles were determined with a
clinometer.

August 7, 1916, p.m.

I observe Polaris for azimuth at cor. No. 1 of this survey

Chains

hereinafter described. The reading on the reference object is set at zero. My watch is set for local mean time. Lat. $34^{\circ} 13' N.$, Long. $109^{\circ} 56' 20'' W.$, from special instructions from the Surveyor General.

Telescope	Time	Horizontal Angle W. of Star
-----------	------	--------------------------------

Direct	8h. 49m. 00s.	$12^{\circ} 59' 30''$
--------	---------------	-----------------------

Reversed	8h. 51m. 12s.	$12^{\circ} 58' 00''$
----------	---------------	-----------------------

	2)17h. 40m. 12s.	$25^{\circ} 57' 30''$
--	------------------	-----------------------

Mean	8h. 50m. 06s.	$12^{\circ} 58' 45''$
------	---------------	-----------------------

l.m.t. obsn., August 7, 1916, p.m., 8h. 50.1m.

l.m.t. U.C.Pol., August 8, a.m., 4h. 24.9m.

Uncorrected Hour Angle, 7h. 34.8m.

Long. Correction, 01.2m.

Hour Angle of Pol. at obsn., 7h. 33.6m.

Azimuth of Polaris, $1^{\circ} 15' 18'' E.$

Bearing of reference object, N. $11^{\circ} 43' 27'' W.$

August 8, 1916, p.m.

I again observe Polaris for azimuth at same station. The reading on the reference object is set at zero.

Telescope	Time	Horizontal Angle W. of Star.
-----------	------	---------------------------------

Direct	7h. 57m. 25s.	$12^{\circ} 51' 00''$
--------	---------------	-----------------------

Reversed	8h. 00m. 11s.	$12^{\circ} 50' 00''$
----------	---------------	-----------------------

	2)15h. 57m. 36s.	$25^{\circ} 41' 00''$
--	------------------	-----------------------

Mean	7h. 58m. 48s.	$12^{\circ} 50' 30''$
------	---------------	-----------------------

l.m.t. obsn., August 8, 1916, p.m., 7h. 58.8m.

l.m.t. U.C.Pol., August 9, 1916, a.m., 4h. 21.0m.

Uncorrected Hour Angle, 8h. 22.2m.

Long. Correction, 01.2m.

Hour Angle of Pol. at obsn., 8h. 21.0m.

Azimuth of Polaris, $1^{\circ} 07' E.$

Bearing of reference object, N. $11^{\circ} 43' 30'' W.$

SITGREAVES NATIONAL FOREST

STATE OF ARIZONA

Chains

The mean of these is N. 11° 43' 29" W. and to the corresponding meridian all the courses of this survey are referred.

RETRACEMENT

August 8, 1916.

From cor. for secs. 5, 6, 31 and 32, Ts. 9 and 10 N., R. 23 E., a post marked as described by the Surveyor General. No witnesses. Post is decayed, I therefore restore cor. as follows:

Deposit a lava stone 4 x 4 x 3 ins., 10 ins. in the ground, over which set a lava stone 18 x 8 x 6 ins., marked with 5 notches on E. face and 1 notch on W. face; and raise a mound of stone 3 ft. base, 2 ft. high N. of cor., whence:

An oak, 10 ins. dia., bears N. 30° E., 57 lks. dist., scribed T 10 N R 23 E S 32 B T.

A yellow pine, 10 ins. dia., bears N. 3° 05' W., 107 lks. dist., scribed T 10 N R 23 E S 31 B T.

A yellow pine, 6 ins. dia., bears S. 43° 16' W., 56 lks. dist., scribed T 9 N R 23 E S 6 B T.

A yellow pine, 10 ins. dia., bears S. 17° 45' E., 106 lks. dist., scribed T 9 N R 23 E S 5 B T.

Thence West.

On random line bet. secs. 6 and 31.

40.43 Fall 8 lks. N. of the 1/4 sec. cor. bet. secs. 31 and 6, which is a lava stone 12 x 9 x 10 ins. above ground, marked and witnessed as described by the Surveyor General.

Thence N. 89° 53' E.

On true line bet. secs. 6 and 31.

5.05 Set temp. 1/256 sec. cor. on S. line SW/4 SW/4 SE/4, Sec. 31.

SITGREAVES NATIONAL FOREST

STATE OF ARIZONA

Chains
40.43

Cor. for secs. 5, 6, 31 and 32, heretofore described.

BOUNDARIES OF CLAIM

Beginning at cor. No. 1.

Identical with cor. for secs. 5, 6, 31 and 32, heretofore described. I mark + on top of sec. cor. for point and alongside set an oak post 48 x 8 x 8 ins., 36 ins. in the ground, marked 1 - H E S 453 on NW. face, whence:

A yellow pine, 8 ins. dia., bears N. 13° 34' E.,
48 lks. dist., scribed 1 H E S 453 + B T.

A yellow pine, 8 ins. dia., bears S. 55° 38' E.,
99 lks. dist., scribed 1 H E S 453 + B T.

Lat. 34° 13' N., Long. 109° 56' 20" W., from special instructions from the Surveyor General, and later verified.

Mag. decl. at 8:00 a.m., 13° 30' E. Mean mag. decl.,
13° 26' E.

Thence S. 89° 53' W.

Descend gentle NW. slope 20 ft. to arroyo, through scattering pine and oak.

24.40 Road bears NNE. and SSW.

32.70 Arroyo, 8 lks. wide, 1 ft. deep, course NE. Thence over level land, through pine and oak timber.

35.38 To cor. No. 2 and C. C. on line bet. secs. 6 and 31.

Identical with temp. 1/256 sec. cor. on S. bdy. SW/4 SW/4 SE/4, Sec. 31. Deposit a lava stone 6 x 4 x 2 ins. marked with a +, 14 ins. in the ground, over which set a lava stone 24 x 8 x 8 ins., chiseled + for the point, 2 - H E S 453 on NE. face and C C on N. face; and raise a mound of stone 3 ft. base, 2 ft. high N. of cor., whence:

A yellow pine, 28 ins. dia., bears N. 80° 15' W.,
66 lks. dist., scribed 2 H E S 453 + B T.

SITGRAVES NATIONAL FOREST

STATE OF ARIZONA

Chains

An oak, 10 ins. dia., bears N. 15° E., 62 lks. dist., scribed 2 H E S 453 + B T.

Cor. for secs. 5, 6, 31 and 32, heretofore described, bears N. 89° 53' E., 35.38 chs. dist. 1/4 sec. cor. bet. secs. 6 and 31, heretofore described, bears S. 89° 53' W., 5.05 chs. dist.

Thence North.

Over level land in pine and oak timber.

5.00 To cor. No. 3.

Deposit a lava stone 4 x 4 x 2 ins. marked with a +, 16 ins. in the ground, over which set a lava stone 26 x 10 x 8 ins., chiseled + for the point and 3, - H E S 453 on SE. face; and raise a mound of stone 3 ft. base, 2 ft. high SE. of cor., whence:

An oak, 12 ins. dia., bears N. 23° 26' E., 61 lks. dist., scribed 3 H E S 453 + B T.

A yellow pine, 32 ins. dia., bears N. 89° 55' E., 75 lks. dist., scribed 3 H E S 453 + B T.

Thence East.

Over level land in pine and oak timber.

5.00 To cor. No. 4.

Deposit a lava stone 2 x 2 x 1 ins. marked with a +, 14 ins. in the ground, over which set a lava stone 24 x 8 x 8 ins., chiseled + for the point and 4 - H E S 453 on SE. face. No stone available for mound, therefore dig pits 24 x 24 x 12 ins. crosswise on chain lines 3 ft. dist.; and raise a mound of earth 4 ft. base, 2 ft. high, 3-1/2 ft. dist. SE. of cor., whence:

An oak, 12 ins. dia., bears South, 45 lks. dist., scribed 4 H E S 453 + B T.

Chains

A yellow pine, 16 ins. dia., bears N. 87° 15' E.,
59 lks. dist., scribed 4 H E S 453 + B T.

Thence North.

Over level land in pine and oak timber.

10.00

To cor. No. 5.

Deposit a lava stone 4 x 4 x 2 ins. marked with a +, 14 ins. in the ground, over which set a lava stone 24 x 10 x 10 ins. chiseled + for the point and 5 - H E S 453 on SE. face. No stone available for mound, therefore dig pits 24 x 24 x 12 ins. crosswise on claim lines 8 ft. dist.; and raise a mound of earth 4 ft. base, 2 ft. high, 3-1/2 ft. dist. SE. of cor., whence:

A yellow pine, 18 ins. dia., bears S. 20° 26' W.,
109 lks. dist., scribed 5 H E S 453 + B T.

A yellow pine, 26 ins. dia., bears S. 74° 04' E.,
50 lks. dist., scribed 5 H E S 453 + B T.

Thence East.

Over level land, through pine and oak timber.

7.40

To cor. No. 6.

Deposit a lava stone 5 x 4 x 2 ins. marked with a +, 14 ins. in the ground, over which set a lava stone 24 x 8 x 5 ins., chiseled + for the point and 6 - H E S 453 on SE. face. No stone available for mound, therefore dig pits 24 x 24 x 12 ins. crosswise on claim lines 3 ft. dist.; and raise a mound of earth 4 ft. base, 2 ft. high, 3-1/2 ft. dist. SE. of cor., whence:

A yellow pine, 20 ins. dia., bears S. 89° 09' W.,
191 lks. dist., scribed 6 H E S 453 + B T.

A yellow pine, 18 ins. dia., bears N. 7° 14' W.,
140 lks. dist., scribed 6 H E S 453 + B T.

SITGREAVES NATIONAL FOREST

STATE OF ARIZONA

Chains

Thence N. 5° 22' E.

In open, over level land. Fence on line.

13.90 Foot ascent. Ascend 30 ft. to rocky ridge.

19.80 Fence cor. Fence bears NE. Leave fence.

23.10 Rocky ridge bears E. and W. Enter timber. Descend
30 ft. to cor.

27.81 To cor. No. 7.

Point for cor. falls on a lava stone in place,
showing 24 x 18 x 7 ins. above ground. I mark
+ on top for point and 7 - H E S 453 on the SE.
face; and raise a mound of stone 3 ft. base, 2
ft. high SE. of cor., whence:

An oak, 8 ins. dia., bears S. 51° 12' W.,

40 lks. dist., scribed 7 H E S 453 + B T.

A pine, 18 ins. dia., bears N. 21° 22' W.,

53 lks. dist., scribed 7 H E S 453 + B T.

August 8, 1916.

August 9, 1916.

Thence S. 89° 58' E.

Descend 10 ft. in oak and pine timber to flat.

1.50 Foot descent. Leave timber, bears N. and S.

4.65 Road bears NW. and SE.

5.50 Fence bears NNW. and SSE.

23.59 To cor. No. 8

Deposit a lava stone 6 x 3 x 2 ins. marked with a
+, 14 ins. in the ground, over which set a lava
stone 24 x 10 x 8 ins., chiseled + for the point
and 8 H E S 453 on SW. face; and raise a mound of
stone 3 ft. base, 2 ft. high SW. of cor. whence;

SITGREAVES NATIONAL FOREST

STATE OF ARIZONA

Chains	Description	Chains
	and 8 - H E S 453 on SW. face	
	An oak, 4 ins. dia., bears S. 53° 14' E., 28 lks. dist., scribed 8 H E S 453 + B T.	
	An oak, 6 ins. dia., bears N. 29° 14' E., 71 lks. dist., scribed 8 H E S 453 + B T.	
	Thence S. 4° 16' W.	
	Ascend along gentle NW. slope in pine and oak timber 30 ft. to cor. Fence on line.	
8.20	Fence cor. Fence bears W. and along line.	
29.20	Fence cor. Fence bears W. Leave fence.	
42.75	To cor. No. 1, the place of beginning.	

AREA

Total Area - - - - - 114.84 acres

IMPROVEMENTS.

The improvements made upon this claim and belonging to claimant, consist of the following:

A frame dwelling 30 x 15 ft., the long side of which bears N. and S. and the NE. cor. of which bears S. 59° 32' E., 8.54 chs. dist. from cor. No. 7.

Value - - - - - \$250.00

A frame barn, 35 x 18 ft., the long side of which bears N. and S. and the NE. cor. of which bears S. 54° 08' E., 4.32 chs. dist. from cor. No. 7.

Value - - - - - \$200.00

There is approximately 1-1/4 mile of wire fence.

Value - - - - - \$150.00

There are three pole corrals, one 150 ft. dia., one 100 ft. dia. and one 150 ft. square.

Value - - - - - \$100.00

SITGREAVES NATIONAL FOREST

STATE OF ARIZONA

Chains

A tank 150 ft. dia.,

Value ----- \$ 50.00

DESCRIPTION

This claim lies at base of Porter Mountain, which rises to SE. The claim is part of a large mesa and lies across a shallow draw. The elevation is 6700 ft. and the general slope is to the North.

The timber consists of a mixed stand of oak and yellow pine, which occurs along S., E. and West boundaries. The soil, with exception of ridge in NW., is a clayey loam of good depth and fertile. The soil on ridge in NW. is rocky and non-tillable.

Water for domestic use is hauled from spring one mile dist. Stock water is obtained from tank on claim. There is no water for irrigation.

I saw no indications of mineral upon the claim.

There are approximately 20 acres in cultivation.

CONFLICTS AND ADJOINING CLAIMS

There are no conflicting or adjoining claims.

Showlow, Arizona, the nearest post office, is 8 miles to West over poor road. Holbrook, Arizona, the nearest railroad point is 50 miles to North over fair road.

TRAVERSE

Cor.	Course	Dist.	N	S	E	W
1-2	S. 89° 53' W.	35.38 ✓		0.07 ✓		35.38 ✓
2-3	North	5.00 ✓	5.00 ✓			
3-4	East	5.00 ✓			5.00 ✓	
4-5	North	10.00 ✓	10.00 ✓			
5-6	East	7.40 ✓			7.40 ✓	
6-7	N. 5° 22' E.	27.81 ✓	27.69 ✓		2.60 ✓	
7-8	S. 89° 58' E.	23.59 ✓		0.01 ✓	23.59 ✓	
8-1	S. 4° 16' W.	42.75 ✓		42.63 ✓		3.18 ✓
		156.93 ✓	42.69 ✓	42.71 ✓	38.59 ✓	38.56 ✓
				42.69 ✓	38.56 ✓	
Error in Lat. and Dep.				.02	.03	

SITGREAVES NATIONAL FOREST

STATE OF ARIZONA

Chains

Closing error, 1:4353.

Survey completed August 9, 1916.

R. L. Johnson

Surveyor - Draftsman

Line	Course	Distance	Angle	Area
1-1	North	10.00	90.00	0.00
1-2	East	10.00	0.00	0.00
1-3	South	10.00	90.00	0.00
1-4	West	10.00	180.00	0.00
1-5	North	10.00	90.00	0.00
1-6	East	10.00	0.00	0.00
1-7	South	10.00	90.00	0.00
1-8	West	10.00	180.00	0.00
1-9	North	10.00	90.00	0.00
1-10	East	10.00	0.00	0.00
1-11	South	10.00	90.00	0.00
1-12	West	10.00	180.00	0.00
1-13	North	10.00	90.00	0.00
1-14	East	10.00	0.00	0.00
1-15	South	10.00	90.00	0.00
1-16	West	10.00	180.00	0.00
1-17	North	10.00	90.00	0.00
1-18	East	10.00	0.00	0.00
1-19	South	10.00	90.00	0.00
1-20	West	10.00	180.00	0.00
1-21	North	10.00	90.00	0.00
1-22	East	10.00	0.00	0.00
1-23	South	10.00	90.00	0.00
1-24	West	10.00	180.00	0.00
1-25	North	10.00	90.00	0.00
1-26	East	10.00	0.00	0.00
1-27	South	10.00	90.00	0.00
1-28	West	10.00	180.00	0.00
1-29	North	10.00	90.00	0.00
1-30	East	10.00	0.00	0.00
1-31	South	10.00	90.00	0.00
1-32	West	10.00	180.00	0.00
1-33	North	10.00	90.00	0.00
1-34	East	10.00	0.00	0.00
1-35	South	10.00	90.00	0.00
1-36	West	10.00	180.00	0.00
1-37	North	10.00	90.00	0.00
1-38	East	10.00	0.00	0.00
1-39	South	10.00	90.00	0.00
1-40	West	10.00	180.00	0.00
1-41	North	10.00	90.00	0.00
1-42	East	10.00	0.00	0.00
1-43	South	10.00	90.00	0.00
1-44	West	10.00	180.00	0.00
1-45	North	10.00	90.00	0.00
1-46	East	10.00	0.00	0.00
1-47	South	10.00	90.00	0.00
1-48	West	10.00	180.00	0.00
1-49	North	10.00	90.00	0.00
1-50	East	10.00	0.00	0.00
1-51	South	10.00	90.00	0.00
1-52	West	10.00	180.00	0.00
1-53	North	10.00	90.00	0.00
1-54	East	10.00	0.00	0.00
1-55	South	10.00	90.00	0.00
1-56	West	10.00	180.00	0.00
1-57	North	10.00	90.00	0.00
1-58	East	10.00	0.00	0.00
1-59	South	10.00	90.00	0.00
1-60	West	10.00	180.00	0.00
1-61	North	10.00	90.00	0.00
1-62	East	10.00	0.00	0.00
1-63	South	10.00	90.00	0.00
1-64	West	10.00	180.00	0.00
1-65	North	10.00	90.00	0.00
1-66	East	10.00	0.00	0.00
1-67	South	10.00	90.00	0.00
1-68	West	10.00	180.00	0.00
1-69	North	10.00	90.00	0.00
1-70	East	10.00	0.00	0.00
1-71	South	10.00	90.00	0.00
1-72	West	10.00	180.00	0.00
1-73	North	10.00	90.00	0.00
1-74	East	10.00	0.00	0.00
1-75	South	10.00	90.00	0.00
1-76	West	10.00	180.00	0.00
1-77	North	10.00	90.00	0.00
1-78	East	10.00	0.00	0.00
1-79	South	10.00	90.00	0.00
1-80	West	10.00	180.00	0.00
1-81	North	10.00	90.00	0.00
1-82	East	10.00	0.00	0.00
1-83	South	10.00	90.00	0.00
1-84	West	10.00	180.00	0.00
1-85	North	10.00	90.00	0.00
1-86	East	10.00	0.00	0.00
1-87	South	10.00	90.00	0.00
1-88	West	10.00	180.00	0.00
1-89	North	10.00	90.00	0.00
1-90	East	10.00	0.00	0.00
1-91	South	10.00	90.00	0.00
1-92	West	10.00	180.00	0.00
1-93	North	10.00	90.00	0.00
1-94	East	10.00	0.00	0.00
1-95	South	10.00	90.00	0.00
1-96	West	10.00	180.00	0.00
1-97	North	10.00	90.00	0.00
1-98	East	10.00	0.00	0.00
1-99	South	10.00	90.00	0.00
1-100	West	10.00	180.00	0.00

DIRECTIONS.—1. Carry out calculations to two decimals only.

2. In balancing Latitudes and Departures do not obliterate or change the original figures.

Put the corrected figure or figures above in red ink. Do not change the footing of the original figures, but put below them the corrected footing in red ink.

The corrections for balancing fallings should be proportional to the lengths of the lines.

3. In calculations of fallings take result to nearest link. In calculations of N. and S. areas drop all after second decimal. Surveyors are required to use the Standard Field Tables issued by the G. L. O.

4. Only three copies of this tabulation are necessary, for the District Office, the Surveyor General, and the Commissioner.

TABLING AND CALCULATIONS OF HOMESTEAD ENTRY SURVEY NO. 453, STATE OF ARIZONA.

CORNERS.	BEARING.	DISTANCE.	LATITUDES.		DEPARTURES.		DOUBLE M. D.	N. AREAS.	S. AREAS.
			NORTH.	SOUTH.	EAST.	WEST.			
1-2	S. 89° 53' W.	35.38		06 07		35 38	35 39		2 12
2-3	North	5.00	5 00				0 00		
3-4	East	5.00			5 00		5 00		
4-5	North	10.00	10 00				10 00	100 00	
5-6	East	7.40			7 40		17 40		
6-7	N. 5° 22' E.	27.81	27 69		2 60		27 39	758 43	
7-8	S. 89° 58' E.	23.59		01 62			53 57		54
8-1	S. 4° 16' W.	42.75	42 69	42 63		3 18	73 97	3152 60	60
		156.93	42 69	42 71	38 59	38 56		858 43	3155 26
			42 69	42 69	38 58	38 58			858 43
								20/2296 83	
								114 84	Acres.

45

EMH

APPROVAL


Office of the United States Surveyor General,

Phoenix, Arizona, *May 22*, 1918

The foregoing field notes of Homestead Entry Survey No.

453

executed by *R. P. A. Johnson, Surveyor-Draftsman*
under his special instructions, dated *April 17*, 1916, having
been critically examined, and the necessary corrections and explanations
made, the said field notes, and the surveys they describe, are hereby
approved.



U. S. Surveyor General.

I certify that the foregoing transcript of the field notes of the
above-described survey in the State of *Arizona*, has been
correctly copied from the original notes on file in this office.

FRANK P. TROTT

U. S. Surveyor General.