

HES

0

0

5

9

0

ORIGINAL

149

DEC-8 1919

MAY 13 1920

Form 85
Sheet No. 1
(Revised July 1, 1914.)

U. S. DEPARTMENT OF AGRICULTURE
FOREST SERVICE

FIELD NOTES

OF

HOMESTEAD ENTRY SURVEY NO. 590

SITUATED IN THE TONTO NATIONAL FOREST

ADMINISTRATIVE DISTRICT NO. 3

In Section 21 , unsurveyed, Township 10 N., Range 14 E.
In Section 28 , unsurveyed, Township 10 N., Range 14 E.
In Section 29 , unsurveyed, Township 10 N., Range 14 E.

of the

GILA AND SALT RIVER BASE & Meridian.

State of

ARIZONA.

Applicant for listing Wm. Shrigley,
Residence Young, Arizona.
Application No. 581 , dated August 5 , 19 15
List No. 3-3891 , dated September 30, 1916.

Applicant for survey Charles S. Erskine,
Residence Young, Arizona.
H. E. No. 041027 , dated December 26 19 18
Land Office Phoenix, Arizona.

Survey executed by Frank D. Yost, Surveyor - Forest Service,
[Forest Service Title.]
Under special instructions dated March 12 , 19 19
Survey commenced June 3 19 19
Survey completed June 4 19 19
Under Acts of June 11, 1906, and October 1, 1918.

150

OATH OF ASSISTANTS

We hereby certify that we assisted **Frank D. Yost,**
Surveyor - Forest Service, in surveying all those
[Forest Service Title.]

parts or portions of Homestead Entry Survey No. **590**, in the State
of **ARIZONA** which are represented in the following field notes
as having been surveyed by him and under his direction; and that said
survey has been in all respects, to the best of our knowledge and
belief, well and faithfully surveyed, and the corner monuments estab-
lished, according to the instructions furnished by the United States
Surveyor General for **ARIZONA**

Note: It would have been
very expensive and incon-
venient to appear before an
officer to administer oaths
to Assistants; hence, they
were taken by the Surveyor.

H. E. Brandebury
Chainman

H. H. Langfellow
Chainman

Subscribed and sworn to before me this **sixth** day of
August, 19**19**

Frank D. Yost
Surveyor - Forest Service,

OATH OF SURVEYOR

I, **Frank D. Yost,** Surveyor - Forest Service,
[Forest Service Title.]

do solemnly swear that, in strict conformity with the special instruc-
tions of the United States Surveyor General for **ARIZONA**, dated
March 12, 19**19**, and the laws of the United States, I have
well, faithfully, and truly, in my own proper person, surveyed a tract
of land embraced in

List No. **3-3891**, dated **September 30 1916**, for
Patent, under the Act of **June 11**, 19**06**,
the same to be known as Homestead Entry Survey No. **590**,
situated within the **TONTO** National Forest, in
un surveyed Section **21**, Township **10 N.**, Range **14 E.**, and
un surveyed Section **28**, Township **10 N.**, Range **14 E.**,
un surveyed section **29**, Township **10 N.**, Range **14 E.**

of the **GILA AND SALT RIVER BASE &** meridian, **ARIZONA**, and the
related retracements and resurveys and section subdivisions, which are
represented in the following field notes as having been surveyed by me;
and I further solemnly swear that all the corners of said survey have
been established and perpetuated in strict accordance with the stated
special instructions, and in the specific manner-described in the field
notes, and that the following are the original field notes of such
survey.

Frank D. Yost
Surveyor - Forest Service,
[Forest Service Title.]

Subscribed and sworn to before me this **fifth** day of
November, 19**19**.

Echel G. Myers
Notary Public,



My commission expires **March 17, 1921**.

TONTO NATIONAL FOREST

STATE OF ARIZONA.

Chains

Applicant for listing, Wm. Shrigley; Application No. 581, dated August 5, 1915; List No. 3-3891, dated September 30, 1916; H. E. 041027 made in the Phoenix Land Office on December 26, 1918, by Charles S. Erskine.

Surveyed under special instructions from the Surveyor General for Arizona, dated March 12, 1919, and designated as Homestead Entry Survey No. 590.

Situated in what will probably be when surveyed Secs. 21, 28 and 29, T. 10 N., R. 14 E., Gila and Salt River Base and Meridian, Tonto National Forest, Arizona.

Surveyed under the Acts of June 11, 1906 and October 1, 1918.

Survey commenced June 3, 1919, and executed with a Buff and Buff transit No. 10019, equipped with Smith solar attachment.

I test the adjustments of the transit and make necessary corrections.

All distances are horizontal, and were reduced from measurements made directly on the slope with a 500 link steel tape. The slope angles were determined with a clinometer.

All courses of this survey were deflected from the meridian established by me at Cor. No. 4 of H.E.S. 587, by direct solar observation on May 30, 1919, in connection with the survey of H. E. S. 587.

BOUNDARIES OF CLAIM

June 3, 1919.

Beginning at Cor. No. 1, which is also Cor. No. 2 of H.E.S. 587.

Identical with Cor. H-9 of the list survey, which is a sandstone 12 x 6 x 2 ins. above ground, marked and witnessed as described by the Forest Service. I destroy

Chains

all trace of this list corner.

Deposit a sandstone 3 x 2 x 2 ins. marked with a + 18 ins. in the ground, over which set a red sandstone 24 x 12 x 10 ins. chiseled + for the point and 1 H E S 590 on NW. face; and 2 H E S 587 on East face; raise a mound of stone 3 ft. base, 2 ft. high, NW. and E. of cor., whence:

An oak 15 ins. dia., brs. N. 2° 59' W.,

28 lks. dist.

A juniper 40 ins. dia., brs. N. 85° 10' W.,

84 lks. dist.

Each blazed and scribed 1 H E S 590 + B T

An oak 12 ins. dia., brs. N. 66° 47' E.,

37 lks. dist.

An oak 10 ins. dia., brs. S. 20° 01' E.,

44 lks. dist.

Each blazed and scribed 2 H E S 587 + B T

The cor. of Secs. 4, 5, 32 and 33, Ts. 9 and

10 N., R. 14 E., a granite porphyry stone

10 x 8 x 8 ins. above ground, firmly set,

marked and witnessed as described by the

Surveyor General, brs. S. 4° 28' 22" E.,

125.15 chs. dist. by traverse which appears

at the end of these notes.

Lat. 34° 10' 53" N., Long. 110° 55' 39" W., from Special Instructions from the Surveyor General and later verified.

Magnetic declination at 8 a.m., 14° 30' E. Mean

Magnetic declination, 14° 26' E.

(Note: The above cor. was set and mkd. for both surveys May 30, 1919, in connection with H. E. S. 587.

Thence S. 87° 56' W.

Descend 60 ft., over steep rocky NW. slope, thru dense

TONTON NATIONAL FOREST

STATE OF ARIZONA

Chains brush.

2.71 Wash, 25 lks. wide, banks 3 ft. high, (dry) course SW.
Bottom of desc. Ascend 60 ft. over steep rocky SE.
slope, thru dense brush.

.6.07 Top of ascent, on edge of mesa, thence over level grassy
mesa, thru scattering juniper and oak.

20.69 To Cor. No. 2.
Identical with Cor. H-8 of the list survey, which is a
sandstone 12 x 7 x 3 ins. above ground, marked and wit-
nessed as described by the Forest Service. I destroy
all trace of this list corner.
Deposit a sandstone 5 x 3 x 1 ins. marked with a + 18
ins. in the ground, on solid rock, over which set an
iron post 36 ins. long, 2 ins. dia., with brass cap
marked 1919 on S. rim, and 2 H E S 590 in NE. quadrant,
surrounded by a mound of stone 3 ft. base, 1-1/2 ft.
high, whence:
A juniper 16 ins. dia., brs. S. 86° 40' W.,
221 lks. dist.
A juniper 20 ins. dia., brs. S. 1° 10' E.,
214 lks. dist.
Each blazed and scribed 2 H E S. 590 + B T.

Thence N. 0° 39' E.
Across level grassy mesa,
22.41 Edge of mesa. Begin descent of 60 ft., over steep
rocky NW. slope, thru dense brush.

24.07 Wash, 30 lks. wide, banks 3 ft. high, (dry), course SW.
Bottom of descent, thence over gravel bar.

24.93 To Cor. No. 3.
Identical with Cor. H-7 of the list survey, which is
a sandstone 10 x 8 x 3 ins. above ground, marked and
witnessed as described by the Forest Service. I des-

Chains

troy all trace of this list corner.

Deposit a sandstone 5 x 4 x 3 ins. marked with a + 26 ins. in the ground, over which set a sandstone 30 x 14 x 5 ins. chiseled + for the point and 3 H E S 590 on SE. face, surrounded by a mound of stone 4 ft. base, 2 ft. high; raise a mound of stone 3 ft. base, 2 ft. high, SE. of cor., whence:

A pine 26 ins. dia., brs. N. 64° 45' E.,

36 lks. dist.

An oak 15 ins. dia., brs. S. 85° 07' E.,

20 lks. dist.

An oak 24 ins. dia., brs. S. 5° 47' E.,

19 lks. dist.

Each blazed and scribed 3 H E S 590 + B T

Cor. No. 2 of H.E.S. 591, a sandstone 12 x 6

x 14 ins. above ground marked + on top and

2 H E S 591 on NW. face, brs. N. 41° 18' 40" W.,

45.17 chs. dist. by traverse which appears at

the end of these notes.

Note: Cor. No. 3 is set near the bed of dry wash and was surrounded by mound of stone to prevent its being washed out.

Thence N. 89° 08' E.

Over gravel bar.

0.61 Wash, 30 lks. wide, banks 3 ft. high, course SW. Ascend

60 ft. over steep rocky NW. slope, thru dense brush.

4.07 Top of ascent, on edge of mesa, thence over level grassy

mesa, thru scattering juniper.

29.36 To Cor. No. 4.

Identical with Cor. H-6 of the list survey, which is a sandstone 8 x 6 x 5 ins. above ground, marked and witnessed as described by the Forest Service. I destroy

TONTO NATIONAL FOREST

STATE OF ARIZONA

Chains

all trace of this list cor.

Deposit a sandstone 5 x 4 x 2 ins. marked with a + 18 ins. in the ground, over which set a red sandstone 24 x 6 x 5 ins. chiseled + for the point and 4 H E S 590 on SE. face; raise a mound of stone 3 ft. base, 2 ft. high, SE. of cor., whence:

A juniper 40 ins. dia., brs. N. 56° 48' W.,

439 lks. dist.

A juniper 30 ins. dia., brs. N. 56° 40' E.,

399 lks. dist.

Each blazed and scribed 4 H E S 590 + B T

Thence N. 0° 52' E.

Across level grassy mesa; thru scattering juniper and oak.

7.09 Edge of mesa. Begin desc. of 60 ft.; over steep rocky NW. slope; thru dense brush.

9.41 Bottom of descent, thence over gravel bar.

9.96 To Cor. No. 5.

Identical with Cor. H-5 of the list survey, which is a sandstone 14 x 10 x 5 ins. above ground; marked and witnessed as described by the Forest Service. I destroy all trace of this list cor.

Deposit a sandstone 4 x 3 x 2 ins. marked with a + 18 ins. in the ground; over which set a sandstone 24 x 12 x 8 ins. chiseled + for the point and 5 H E S 590 on SE. face; raise a mound of stone 3 ft. base, 2 ft. high, SE. of cor., whence:

An oak 6 ins. dia., brs. N. 7° 59' W.,

23 lks. dist.

An oak 8 ins. dia., brs. S. 74° 15' W.,

28 lks. dist.

Each blazed and scribed 5 H E S 590 + B T

June 3, 1919.

156

HOMESTEAD ENTRY SURVEY NO. 590

TONTON NATIONAL FOREST

STATE OF ARIZONA

Chains June 4, 1919.
 Thence N. 87° 51' E.
 Over level grassy mesa, thru scattering juniper and oak.
 10.67 To Cor. No. 6.
 Identical with Cor. H-4 of the list survey, which is a sandstone 13 x 9 x 2 ins. above ground, marked and witnessed as described by the Forest Service. I destroy all trace of this list cor.
 Deposit a sandstone 3 x 3 x 1 ins. marked with a + 16 ins. in the ground, over which set a sandstone 24 x 10 x 6 ins. chiseled + for the point and 6 H E S 590 on SE. face; raise a mound of stone 3 ft. base, 2 ft. high, SE. of cor., whence:
 A juniper 30 ins. dia., brs. S. 83° 30' E.,
 332 lks. dist.
 A pine 15 ins. dia., brs. N. 2° 47' E.,
 294 lks. dist.
 Each blazed and scribed 6 H E S 590 + B T

Thence N. 0° 42' E.
 Over level grassy mesa, thru scattering juniper and oak.
 9.94 To Cor. No. 7.
 Identical with Cor. H-3 of the list survey, which is a sandstone 16 x 7 x 4 ins. above ground, marked and witnessed as described by the Forest Service. I destroy all trace of this list cor.
 Deposit a sandstone 3 x 3 x 1 ins. marked with a + 20 ins. in the ground, over which set a sandstone 28 x 12 x 6 ins. chiseled + for the point and 7 H E S 590 on SE. face; raise a mound of stone 3 ft. base, 2 ft. high, SE. of cor., whence:
 A juniper 36 ins. dia., brs. S. 29° 15' W.,
 158 lks. dist.
 A juniper 12 ins. dia., brs. S. 74° 51' E.,
 70 lks. dist.

TONTON NATIONAL FOREST

STATE OF ARIZONA

Chains

Each blazed and scribed 7 H E S 590 + B T

Thence N. $89^{\circ} 13'$ E.

Over rolling grassy mesa, thru scattering juniper and oak.

22.27 Enter heavy brush.

24.83 To Cor. No. 8, which is also Cor. No. 2, H.E.S. 588, Identical with Cor. H-2 of List 3-3891 and also Cor. H-4 of List 3-3890, which is a sandstone 12 x 6 x 4 ins. above ground, marked and witnessed as described by the Forest Service. I destroy all trace of this list cor. Deposit a sandstone 4 x 3 x 2 ins. marked with a + 20 ins. in the ground, (impracticable to set cor. deeper), over which set an iron post 36 ins. long, 2 ins. dia., with brass cap marked 1919 on S. rim, 8 H E S 590 in SW. quadrant, and 2 H E S 588 in SE. quadrant; surrounded by a mound of stone 3 ft. base, 1 ft. high to protect cor.; raise a mound of stone 3 ft. base, 2 ft. high, SW. and SE. of cor., whence:

A juniper 40 ins. dia., brs. S. $23^{\circ} 38'$ W.,

80 lks. dist.

A juniper 24 ins. dia., brs. S. $78^{\circ} 35'$ E.,

16 lks. dist.

Each blazed and scribed 8 H E S 590 + B T

An oak 30 ins. dia., brs. N. $32^{\circ} 07'$ W.,

61 lks. dist.

A juniper 24 ins. dia., brs. S. $55^{\circ} 57'$ W.,

77 lks. dist.

Each blazed and scribed 2 H E S 588 + B T

(Note: The above cor. was set and mkd. for both surveys on May 31, 1919 in connection with H. E. S. 588.)

Thence S. $0^{\circ} 44'$ E..

Desc. 20 ft. over a gentle S. slope, thru heavy scrub oak and dense brush, along line 2-1 of H. E. S. 588.

TONTON NATIONAL FOREST

STATE OF ARIZONA

Chains 30.20	<p>To Cor. No. 9, which is also Cor. No. 1, H.E.S. 588.</p> <p>Identical with Cor. H-1 of List 3-3891, and also Cor. H-1 of List 3-3890, which is a sandstone 18 x 9 x 7 ins. above ground, marked and witnessed as described by the Forest Service. I destroy all trace of this list cor.</p> <p>Deposit a sandstone 3 x 2 x 1 ins. marked with a + 24 ins. in the ground, over which set an iron post 36 ins. long, 2 ins. dia., with brass cap marked 1919 on S. rim, 9 H E S 590 in NW. quadrant, and 1 H E S 588 in NE. quadrant; raise mounds of stone 3 ft. base, 2 ft. high, NW. and NE. of cor., whence:</p> <p>An oak 8 ins. dia., brs. N. 36° 09' W., 40 lks. dist.</p> <p>An oak 8 ins. dia., brs. S. 84° 31' W., 10 lks. dist.</p> <p>Each blazed and scribed 9 H E S 590 + B T</p> <p>A pinon 14 ins. dia., brs. S. 23° 01' E., 20 lks. dist.</p> <p>An oak 12 ins. dia., brs. N. 71° 47' E., 21 lks. dist.</p> <p>Each blazed and scribed 1 H E S 588 + B T (Note: The above cor. was set and mkd. for both surveys on May 31, 1919, in connection with H. E. S. 588.)</p> <hr/> <p>Thence West, descending 25 ft., thru dense underbrush and timber, over rocky west slope.</p> <p>2.07 Wash, 25 lks. wide, banks 3 ft. high, (dry) course South. Ascend 20 ft. over rocky east slope, thru dense underbrush and timber</p> <p>4.95 To Cor. No. 10, which is also Cor. No. 4, H.E.S. 587. Identical with Cor. H-1 of List 3-3893 which is a sandstone 15 x 10 x 6 ins. above ground, marked and witnessed as described by the Forest Service. I de-</p>
-----------------	---

TONTON NATIONAL FOREST

STATE OF ARIZONA

Chains

Destroy all trace of this list cor.
Deposit a sandstone 3 x 3 x 2 ins. marked with a + 18 ins. in the ground, over which set a sandstone 24 x 10 x 5 ins. chiseled + for the point, 10 H E S 590 on N. face, and 4 H E S 587 on the SW. face; raise a mound of stone 3 ft. base, 2 ft. high, N. and SW. of cor.,

whence:

An oak 24 ins. dia., brs. N. 12° 11' E.,

30 lks. dist.

A pine 10 ins. dia., brs. S. 38° 01' E.,

74 lks. dist.

Each blazed and scribed 10 H E S 590 + B T

An oak 16 ins. dia., brs. S. 58° 01' W.,

21 lks. dist.

An oak 15 ins. dia., brs. S. 41° 57' E.,

71 lks. dist.

Each blazed and scribed 4 H E S 587 + B T

(Note: The above cor. was set and mkd. for both surveys on May 30, 1919, in connection with H.E.S. 587.)

Thence S. 89° 57' W, along line 4-3 of H. E. S. 587.

Thru dense brush, ascend 15 ft. over east slope.

36.35 Top of ascent, on edge of mesa.

Thence across level grassy mesa.

40.10 To Cor. No. 11, which is also Cor. No. 3, H.E.S. 587.

Identical with Cor. H-10 of List 3-3891, and also Cor. H-2 of List 3-3893, which is a sandstone 11 x 8 x 2 ins.

above ground, marked and witnessed as described by the

Forest Service. I destroy all trace of this list cor.

Deposit a granite stone 3 x 2 x 2 ins. marked with a +

26 ins. in the ground, over which set an iron post 36

ins. long, 2 ins. dia., with brass cap marked 1919 on

S. rim, 11 H E S 590 in portion of circle facing this

claim, and 3 H E S 587 in SE. quadrant; raise a mound

of stone 3 ft. base, 2 ft. high, NW. and SE. of cor.,

Chains

whence:

A juniper 35 ins. dia., brs. S. 52° 15' W., 202 lks. dist.

A juniper 24 ins. dia., brs., N. 30° 27' W., 326 lks. dist.

Each blazed and scribed 11 H E S. 590 + B E

A juniper 30 ins. dia., brs. N. 44° 19' E., 440 lks. dist.

A juniper 14 ins. dia., brs. S. 40° 05' E., 508 lks. dist.

Each blazed and scribed 2 H E S. 587 + B E

(Note: The above cor. was set and mkd. for both surveys on May 30, 1919, in connection with H. E. S. 587.)

Thence S. 0° 09' E.

Over level grassy mesa, thru scattering juniper and oak, along line 5-2 of H. E. S. 587.

Edge of mesa. Begin descent of 60 feet, over steep

rocky SE. slope, thru dense oak brush.

Wash, 25 lks. wide, banks 3 ft. high, (dry) course SW.

Bottom of desc. Ascend 60 ft. over steep rocky NW

slope, thru dense oak brush.

15.02

To cor. No. 1, place of beginning.

AREA

Total Area, --- Acres.

IMPROVEMENTS

The improvements made upon and for the benefit of this

claim consist of the following:

An adobe cowshed 18 x 25 ft., the long sides ex-

tending E. and W., the NE. cor. of which brs.

S. 24° 07' W., 5.81 chs. dist. from cor. No.

8. (shed is in poor condition).

Value --- \$ 10.00

160

161

TONTO NATIONAL FOREST

STATE OF ARIZONA

Chains

Approximately 1/4 mile of brush fencing,

Value - - - - - \$ 10.00

DESCRIPTION

The claim is located on a high flat mesa, with a very gradual slope to the South.

The soil is a light loam, rather gravelly in places.

There is no water on the claim. Water for domestic use might be had by sinking a well in the dry wash which crosses the SE. portion of the claim. About 75% of the claim can be cultivated.

The claim showed no signs of occupancy or cultivation at the time of survey.

I saw no indications of mineral on the claim.

There is no timber of commercial value on the claim.

CONFLICTS AND ADJOINING CLAIMS.

There are no conflicts. H. E. S. 587 adjoins this survey on the South; line 4-3 thereof being identical with line 10-11 of this survey. H.E.S. 588 adjoins on the East, line 2-1 thereof being identical with line 8-9 of this survey; H.E.S. 589 lies about 3/8 mile to the South, and H.E.S. No. 591 lies about 1/2 mile to NW. Note: H.E.S. 588 has been cancelled.

Young, Arizona, the nearest settlement and postoffice, is about 7 miles in a southerly direction.

TONTON NATIONAL FOREST

STATE OF ARIZONA

Chains

TRAVERSES

Course	Dist.	N.	S.	E.	W.
S. 87° 56' W.	20.69		.75		20.68
N. 0° 39' E.	24.93	24.93		.28	
N. 89° 08' E.	29.36	.44		29.36	
N. 0° 52' E.	9.96	9.96		.15	
N. 87° 51' E.	10.67	.40		10.66	
N. 0° 42' E.	9.94	9.94		.12	
N. 89° 13' E.	24.83	.34		24.83	
S. 0° 44' E.	30.20		30.20	.39	
West	4.95				4.95
S. 89° 57' W.	40.10		.03		40.10
S. 0° 09' E.	15.02		15.02	.04	
<u>220.65</u>		46.01	46.00	65.83	65.73
		46.00		65.73	
Error in Lat. and Dep.		.01		.10	
Closing Error, 1:2196.					

TIE FROM COR. NO. 1, H.E.S. 590 TO COR. OF SECS. 4, 5, 32 and 33, TS. 9 and 10 N., R. 14 E.

Course	Dist.	N.	S.	E.	W.
S. 0° 12' E.	24.68		24.68	.09	
S. 89° 38' E.	40.02		.26	40.02	
S. 0° 52' W.	20.74		20.74		.31
N. 18° 10' E.	.77	.73		.24	
S. 65° 00' W.	3.14		1.33		2.85
S. 37° 00' E.	18.75		14.97	11.28	
S. 0° 41' E.	64.54		64.54	.77	
S. 88° 01' W.	17.37		.60		17.36
S. 85° 39' W.	10.05		.76		10.02
N. 78° 53' W.	12.33	2.38			12.10
		3.11	127.88	52.40	42.64
			3.11	42.64	
			124.77	9.76	

Resultant course S. 4° 28' 22" E., 125.15 chs.

TIE FROM COR. NO. 2, H.E.S. 591 TO COR. NO. 3, H.E.S. 590.

Course	Dist.	N.	S.	E.	W.
N. 82° 16' W.	9.67	1.30			9.58
S. 6° 01' W.	7.97		7.93		.84
S. 3° 08' W.	20.11		20.08		1.10
S. 16° 53' E.	4.28		4.10	1.24	
S. 85° 33' E.	40.22		3.12	40.10	
		1.30	35.23	41.34	11.52
			1.30	11.52	
			33.93	29.82	

Resultant course S. 41° 18' 40" E., 45.17 chs.

Survey completed June 4, 1919, by setting corners.

Frank J. Coe
Surveyor - Forest Service,

- DIRECTIONS.—1. Carry out calculations to two decimals only.
 2. In balancing Latitudes and Departures do not obliterate or change the original figures.
 Put the corrected figure or figures above in red ink. Do not change the footing of the original figures, but put below them the corrected footing in red ink.
 The corrections for balancing fallings should be proportional to the lengths of the lines.
 3. In calculations of fallings take result to nearest link. In calculations of N. and S. areas drop all after second decimal. Surveyors are required to use the Standard Field Tables issued by the G. L. O.
 4. Only three copies of this tabulation are necessary, for the District Office, the Surveyor General, and the Commissioner.

TABLING AND CALCULATIONS OF HOMESTEAD ENTRY SURVEY NO. 590, STATE OF Arizona

8-2349

CORNERS.	BEARING.	DISTANCE.	LATITUDES.		DEPARTURES.		DOUBLE M. D.	N. AREAS.		S. AREAS.	
			NORTH.	SOUTH.	EAST.	WEST.					
1 - 2	S. 87-56 W.	20.69		75		20 68	20 69			15 52	
2 - 3	N. 0-39 E.	24.93	24 93		27 28		27	6 73			
3 - 4	N. 89-08 E.	29.36	44		29 36		29 88	13 15			
4 - 5	N. 0-52' E.	9.96	9 96		15		59 37	591 33			
5 - 6	N. 87-51 E.	10.67	40		10 66		70 18	28 07			
6 - 7	N. 0-42 E.	9.94	9 94		12		80 96	804 74			
7 - 8	N. 89-13 E.	24.83	34		24 83		105 90	36 01			
8 - 9	S. 0-44 E.	30.20		30 20	39		131 09			3958 92	
9 - 10	West	4.95					4 95	126 51			
10 - 11	S. 89-57 W.	40.10		03			40 10	81 44		3 26	
11 - 1	S. 0-09 E.	15.02		15 02	04		41 35			621 08	
		220.65	46 01	46 00	65 83	65 73		1480 03		4598 78	
			46 00	46 01	65 76	65 76				1480 03	
	Error in Lat. and Dep.		01		10					20/3118 75	
	Closing Error, 1:2196									155 94	Acres

163

APPROVAL

Office of the United States Surveyor General,

Phoenix, Arizona, May 18, 1920

The foregoing field notes of Homestead Entry Survey No.

590

executed by *Frank D. Gost, Surveyor* [Forest Service Title.]
under his special instructions, dated *March 12*, 1919, having
been critically examined, and the necessary corrections and explanations
made, the said field notes, and the surveys they describe, are hereby
approved.

FRANK P. TROTT

U. S. Surveyor General.

I certify that the foregoing transcript of the field notes of the
above-described survey in the State of **Arizona**, has been
correctly copied from the original notes on file in this office.

Frank D. Gost

U. S. Surveyor General.