

ELLS

0

0

6

3

8

U. S. DEPARTMENT OF AGRICULTURE
FOREST SERVICE

ORIGINAL

FIELD NOTES

OF

HOMESTEAD ENTRY SURVEY NO. 638

SITUATED IN THE COCONINO NATIONAL FOREST

ADMINISTRATIVE DISTRICT NO. 3

In Section 6 , - surveyed, Township 19 N., Range 9 E.

of the

Gila and Salt River Base and Meridian.

State of
Arizona

Applicant for listing

Residence

Application No. , dated , 19

List No. 3-4435 , dated April 21 , 19 21

Applicant for survey Peter L. Zion,

Residence Flagstaff, Arizona

H. E. No. 054761 , dated December 26 , 19 22

Land Office Phoenix, Arizona


Survey executed by Thomas F. Myers, Surveyor - Forest Service
[Forest Service Title]

Under special instructions dated June 25 , 19 23

Survey commenced July 2 , 19 23

Survey completed July 8 , 19 23

Under Acts of June 11, 1906, and February 26, 1923.



OATH OF ASSISTANTS

We hereby certify that we assisted **Thomas F. Myers,**
Surveyor - Forest Service in surveying all those
[Forest Service Title.]

parts or portions of Homestead Entry Survey No. **638**, in the State
of **Arizona** which are represented in the following field notes
as having been surveyed by him and under his direction; and that said
survey has been in all respects, to the best of our knowledge and
belief, well and faithfully surveyed, and the corner monuments estab-
lished, according to the instructions furnished by the United States
Surveyor General for **Arizona**.

Note: It would have been
very expensive and incon-
venient to appear before an
officer to administer Oaths
to Assistants; hence they
were taken by the Surveyor.

H. C. Olander Chairman
Geo W Cook Chairman

Subscribed and sworn to before me this **8th** day of
July, 19**23**.

Thomas F. Myers

Surveyor - Forest Service.

OATH OF SURVEYOR

I, **Thomas F. Myers, Surveyor - Forest Service,**
[Forest Service Title.]

do solemnly swear that, in strict conformity with the special instruc-
tions of the United States Surveyor General for **Arizona**, dated
June 25, 19**23**, and the laws of the United States, I have
well, faithfully, and truly, in my own proper person, surveyed a tract
of land embraced in

List patent, No. **3-4435**, dated **April 21**, 19**21**, for
the same to be known as Homestead Entry Survey No. **638**,
situated within the **Coconino** National Forest, in
- surveyed Section **6**, Township **19 N.**, Range **9 E.**, and
- surveyed Section **-----**, Township **-----**, Range **-----**,

of the **Gila and Salt River Base &** meridian, **Arizona**, and the
related retracements and resurveys and section subdivisions, which are
represented in the following field notes as having been surveyed by me;
and I further solemnly swear that all the corners of said survey have
been established and perpetuated in strict accordance with the stated
special instructions, and in the specific manner described in the field
notes, and that the following are the original field notes of such

Thomas F. Myers

Surveyor - Forest Service.

[Forest Service Title.]

Subscribed and sworn to before me this **17th** day of
December, 19**23**.

Ethel G. Myers

Notary Public.



N-2349

My commission expires April 12, 1925.

COCONINO NATIONAL FOREST

STATE OF ARIZONA

Chains

Surveyed a tract of land embraced in List 3-4435, dated April 21, 1921; H. E. No. 054761, made in the Phoenix Land Office on December 26, 1922, by Peter L. Zion. Surveyed under special instructions from the Surveyor General for Arizona, dated June 25, 1923, and designated as Homestead Entry Survey No. 638. Situated in Sec. 6, T. 19.N., R. 9.E., surveyed and accepted, Gila and Salt River Base and Meridian, Coconino National Forest, Arizona. Surveyed under the Acts of June 11, 1906, and February 26, 1923.

Survey commenced July 2, 1923, and executed with a Buff and Buff transit No. 14631, equipped with Smith solar attachment.

I test the adjustments of the transit and make necessary corrections.

All distances are horizontal and were reduced from measurements made directly on the slope with a 400 link steel tape. The slope angles were determined with a clinometer.

July 2, 1923.

At my station near Cor. No. 5 of this survey, hereinafter described, in Latitude $35^{\circ}03'26''$ N., Longitude $111^{\circ}28'55''$ W. from Forest Service Base Map, at 5h. 55m. 22s. p.m. l.m.t., I observe Polaris with telescope direct, reading an angle of $0^{\circ}24'$ from star to right to reference mark about 10 chs. northwardly of my station. Greenwich m.t. U. C. Polaris, July 2, 1923, 6h 56.4m a.m.
Corr. for Long. 1.2

l.m.t. U. C. Polaris, July 2, 1923,	6h 55.2m a.m.
l.m.t. Obsn. Polaris, July 2, 1923,	5h 55.4m p.m.
Hour angle	11h 00.2m.

Chains

Azimuth of Polaris 0°20' W.

Bearing of Reference Mark N. 0°04'00" E.

At same station at 5h. 56m. 37s. p.m., l.m.t., I again observe Polaris with telescope reversed, reading an angle of 0°23'30" from star to right to same reference mark.

l.m.t. U. C. Polaris, July 2, 1923, 6h 55.2m a.m.

l.m.t. Obsn. Polaris, July 2, 1923, 5h 56.6m p.m.

Hour angle 11h 01.4m

Azimuth of Polaris 0°19.6'00" W.

Bearing of reference mark N. 0°03.9' E.

The bearing of reference mark as determined from the mean of the two observations is N. 0°03'57" E.

I accept bearing of reference mark as N. 0°04'00" E.

and from the corresponding meridian all the courses of this survey were deflected by sustained angulation.

RETRACEMENTS AND RESURVEYS

July 2, 1923.

Beginning at the Cor. of Ts. 19 and 20 N., Rs. 8 and 9 E., an old wooden stake in mound of stone, Old stake is badly decayed but a portion of the markings, as described by the Surveyor General, are still legible.

I restore Cor. at same point as follows: Set a malpais stone 24x10x10 ins. 14 ins. in ground, chiseled + on top, 6 notches on N., S., E. and W. edges, T 20 N on NW. face, R 8 E on SW. face, T 19 N on SE. face and R 9 E on NE face; set piece of old Cor. post alongside of Cor. and raise mound of stone 2 ft. base 1-1/2 ft. high south of Cor.

No witnesses available.

Thence South.

Retracing line between Secs. 1 and 6, T. 19 N., Rs. 8 and 9 E.

40.00 Make careful search for 1/4 Cor. but find no evidence of same.

Chains
80.23

Fall 231 lks. W. of Cor. of Secs. 1, 6, 7 and 12, a pine post, 4 ins. square, 2 ft. long, marked and witnessed as described by the Surveyor General. Post is badly decayed. I therefore restore Cor. as follows: Set a malpais stone 24x12x6 ins. 16 ins. in ground, chiseled + on top, 1 notch on N. and 5 notches on S. Set original stake alongside, and raise a mound of stone 2 ft. base 1-1/2 ft. high W. of Cor.

Thence N. 1°39' W.

On true line between Secs. 1 and 6.

40.13

I again make careful search for 1/4 Cor. but find no evidence of same. At this point, I reestablish 1/4 Cor. as follows: Set a malpais stone 20x8x10 ins. 15 ins. in ground, chiseled + on top and 1/4 on W. face; raise mound of stone 2 ft. base 1-1/2 ft. high W. of Cor., whence:

A pine 8 ins. dia. brs. S. 29°30' W. 7 lks.
marked 1/4 S 1 + BT.

A pine 9 ins. dia. brs. N. 67°40' E. 33 lks.
marked 1/4 S 6 + BT.

60.195

Set temporary point for 1/16 Sec. Cor.

80.26

The Cor. Ts. 19 and 20 N., Rs. 8 and 9 E., previously described.

From the Cor. of Secs. 1, 6, 7 and 12, previously described.

Thence East.

On random line between Secs. 6 and 7.

38.82

Make careful search for 1/4 Cor. but fail to find any evidence of same.

80.54

Fall 52 links N. of point for Cor. of Secs. 5, 6, 7 and 8, which I determine from call of witness tree for Sec. 6, recorded as a pine 34 ins. dia. N. 20° W. 120

Chains

lks. I restore Cor. as follows: Set a malpais stone 24x12x10 ins., 10 ins. in ground to solid rock, marked + on top and 5 notches on East and South faces; raise a mound of stone 3 ft. base, 2 ft. high W. of Cor., whence:

A pine 35 ins. dia. brs. N. 20° W. 120 lks., marked T XIX N R IX E S VI BT. (Old bearing tree).

The tree recorded as S. 45° W. 100 lks. has been cut.

Thence N. 89°38' W.

On true line between Secs. 6 and 7.

40.87

Proportionate point for 1/4 Cor. between Secs. 6 and 7, determined from the following proportionate measurements: 78.82 : 80.54 :: 40.00 : X = 40.87. I again make careful search but find no evidence of same. I therefore reestablish 1/4 Cor. as follows: Set a malpais stone 16x10x7 ins. 11 ins. in ground, chiseled + on top and 1/4 on N. face; raise mound of stone 2 ft. base 1-1/2 ft. high N. of Cor., whence:

A pine 12 ins. dia. brs. N. 39°50' W. 159 lks., marked 1/4 S. 6 + BT.

No other witnesses in limits.

80.54

The Cor. of Secs. 1, 6, 7 and 12, previously described.

July 2, 1923.

July 3, 1923.

Return to Cor. Ts. 19 and 20 N., Rs. 8 and 9 E., previously described.

Thence East.

Retracing line between Secs. 6 and 31.

38.84

Fall 11 lks. N. of 1/4 Cor. between Secs. 6 and 31, an embedded malpais showing 24x15x24 ins. above ground, marked 1/4 on top with small mound of stone S. of Cor.

Chains	(recorded as sandstone 24x24x15 ins. set 18 ins. in ground, marked 1/4, on N. face). Thence N. 89°51' W. On true line between Secs. 1 and 36.
20.19	Proportionate point for temporary 1/16 Cor., determined from the following proportionate measurement: 38.47 : 38.84 :: 20.00 : X = 20.19.
38.84	To Cor. Ts. 19 and 20 N., Rs. 9 and 10 E., previously described.
	Return to 1/4 Cor. between Secs. 1 and 6, previously described. Thence East. On random latitudinal 1/4 Sec. line through Sec. 6.
82.00	Fall 10 lks. N. of 1/4 Cor. between Secs. 5 and 6, a malpais stone 20x10x9 ins. in mound of stone, marked 1/4 on W. face. True line is S. 89°56'00" E. 82.00 chs. July 3, 1923.
	July 5, 1923. Return to 1/4 Cor. between Secs. 6 and 7, previously described. Thence North. On a random meridional 1/4 Sec. line through Sec. 6.
40.32	Intersect latitudinal 1/4 Sec. line S. 89°56'00" E. 40.80 from 1/4 Cor. between Secs. 1 and 6, previously described.
80.34	Fall 309 lks. East of 1/4 Cor. between Secs. 6 and 31, previously described. Thence S. 2°12'00" E. On true meridional 1/4 Sec. line through Sec. 6.
20.025	Set temporary 1/16 Cor. center N/2.
40.05	Intersect latitudinal 1/4 Sec. line.

Chains. Set temporary point for center 1/4 Sec. Cor.
 1/4 Cor. between Secs. 1 and 6, previously
 described, brs. N. 89°56'00" W. 39.24 chs.
 1/4 Cor. between Secs. 5 and 6, previously
 described, bears S. 89°56'00" E. 42.76 chs.
 80.40 The 1/4 Cor. between Secs. 6 and 7, previously described.

From the temporary point for center 1/4 Sec. Cor.
 Thence N. 89°56' W.

On true latitudinal 1/4 Sec. line through W/2.
 20.31 Proportionate point for temporary 1/16 Cor. center W/2,
 determined from the following proportionate measurement:
 38.645 : 39.24 :: 20.00 : X = 20.31.

Set temporary stake for 1/16 Cor.
 39.24 1/4 Cor. between Secs. 1 and 6, previously described.

From the temporary 1/16 Sec. Cor. on latitudinal 1/4
 Sec. line, center W/2.

Thence N. 1°56' W.
 On a random meridional 1/16 Sec. line through center
 NW/4.

20.05 Set temporary point for 1/16 Cor. center NW/4.
 40.09 Fall 2 lks. E. of temporary 1/16 Cor. on line between
 Secs. 6 and 31 W/2.

True line is S. 1°58' E. 40.09 chs.
 I move temporary 1/16 point center NW/4 West 1 link
 and South 1/2 link.

July 5, 1923.

July 6, 1923,
 Rain.

July 7, 1923.
 From the temporary 1/16 Cor. between Secs. 1 and 6 N/2.

Chains

Thence S. $89^{\circ}53'$ E.On random latitudinal $1/16$ Sec. line through NW/4.

39.07

Fall $2-1/2$ lks. south of temporary $1/16$ Cor. on meridional $1/4$ Sec. line center N/2.Thence N. $89^{\circ}55'$ W.On true latitudinal $1/16$ line through NW/4.

20.22

Intersect meridional $1/16$ line N. $1^{\circ}58'$ W. 1 link from temporary $1/16$ Cor. on meridional $1/16$ line center NW/4.I move temporary point for $1/16$ Cor. to point of intersection.

39.07

The temporary $1/16$ Cor. between Secs. 1 and 6 N/2.

BOUNDARIES OF CLAIM

TRACT A.

July 7, 1923.

Beginning at Cor. No. 1, also $1/16$ Cor. Center W/2.

Deposit a malpais stone $2x6x8$ ins., marked with a + 14 ins. in ground, over which set a malpais stone $24x10x8$ ins., marked + on top, 1 HES 638 on NE. and $1/16$ on SW. faces; raise a mound of stone 2 ft. base $1-1/2$ ft. high NE. of Cor., whence:

A pine 9 ins. dia. brs. S. $68^{\circ}12'$ W. 209 lks.

A pine 30 ins. dia. brs. S. $13^{\circ}46'$ E. 608 lks.

Each blazed and scribed $1/16$ - 1 HES 638 + BT.

$1/4$ Cor. between Secs. 1 and 6, previously described; brs. N. $89^{\circ}56'$ W. 18.93 chs.

Latitude $35^{\circ}03'24''$ N., Longitude $111^{\circ}29'06''$ W. from

Forest Service Base Map.

Mag. decl. at 8 a.m. $15^{\circ}05'$ E., mean mag. decl. $15^{\circ}01'$ E.

Thence N. $1^{\circ}58'$ W.

Along meridional $1/16$ Sec. line through NW/4. Descend 15 ft. gradually over open North slope covered with loose malpais rock.

Chains

14.49

To Cor. No. 2 on S. boundary of exemption for logging railway on south edge of Flagstaff-Mormon Lake wagon road.

Deposit a malpais stone 2x2x3 ins., marked with a + 18 ins. in the ground, over which set a malpais stone 18x12x10 ins., chiseled + on top and 2 HES 638 on SE. face; raise a mound of stone 3 ft. base 2 ft. high SE. of Cor. 10 ft. dist.

No witnesses available. Pits impracticable.

Thence S. 65°00' E.

On S. boundary of exemption for logging railway over open land.

.50

Flagstaff-Mormon Lake road bears NNW. and SSE.

22.74

To Cor. No. 3 on S. boundary of exemption for logging railway.

Deposit a malpais stone 2x2x4 ins., marked with a + 16 ins. in ground, over which set a malpais stone 24x16x9 ins., chiseled + on top and 3 HES 638 on SW. face.

No witnesses available. Pits and mound impracticable.

July 7, 1923.

July 8, 1923.

Thence S. 2°12' E.

Along meridional 1/4 Sec. line.

Over open level land.

4.88

To Cor. No. 4, also center 1/4 Sec. Cor.

Deposit a malpais stone 2x3x3 ins., marked with a + 14 ins. in ground, over which set a malpais stone 24x8x8 ins., chiseled + on top, 4 HES 638 on NW. and C 1/4 S on SE. faces.

No witnesses available. Pits and mound impracticable.

Chains Thence N. $89^{\circ}56'00''$ W.
 Along latitudinal $1/4$ Sec. line over open level land.
 9.00 Flagstaff-Mormon Lake road bears NW. and SE. Ascend
 gradually 10 ft. over gentle North slope covered with
 loose malpais.
 20.31 To Cor. No. 1, the place of beginning.

TRACT B.

Beginning at Cor. No. 5.

On North boundary of exemption for logging railway.

Deposit a malpais stone $2 \times 2 \times 3$ ins., marked with a + 16
 ins. in ground, over which set a malpais stone $26 \times 14 \times 8$
 ins., chiseled + on top and 5 HES 638 on NW. face.

No witnesses available. Pits and mound

impracticable.

Cor. No. 3, previously described, bears S. $2^{\circ}12'$ E.

1.12 chs.

Thence N. $65^{\circ}00'$ W.

North

Along boundary of exemption for logging railway.

22.74 To Cor. No. 6.

On N. boundary of exemption for logging railway.

Deposit a malpais stone $1 \times 3 \times 4$ ins., marked with a + 16
 ins. in ground, over which set a malpais stone $24 \times 16 \times 8$
 ins., chiseled + on top and 6 HES 638 on NE. face;
 raise a mound of stone 2 ft. base, $1-1/2$ ft. high NE.
 of Cor.

No witnesses available. Pits impracticable.

Cor. No. 2, previously described, bears S.

 $1^{\circ}58'$ E. 1.12 chs.Thence N. $1^{\circ}58'$ W.Along meridional $1/16$ Sec. line over open level land.

3.52 Fence bears NW. and SE.

4.45 To Cor. No. 7, also $1/16$ Cor. center NW/4.Deposit a malpais stone $2 \times 3 \times 6$ ins., marked with a + 14

COCONINO NATIONAL FOREST

10.

STATE OF ARIZONA

Chains

ins. in ground, over which set a malpais stone 24x10x8 ins., chiseled + on top, 7 HES 638 on SE. and 1/16 on NW. faces.

No witnesses available. Pits and mound impracticable.

Thence S. 89°55' E.

Along latitudinal 1/16 Sec. line over open level land.

4.90 Arroyo 20 lks. wide, 4 ft. deep, course NW.

9.20 Dim road bears NW. and SE. Ascend 40 ft. over rocky S. slope.

20.22 To Cor. No. 8, also 1/16 Cor. center N/2.

Deposit a malpais stone 3x6x6 ins., marked with a + 14 ins. in ground, over which set a malpais stone 24x12x10 ins., chiseled + on top, 8 HES 638 on SW. and 1/16 on NE. faces; raise a mound of stone 2 ft. base 1-1/2 ft. high SW. of Cor., whence:

An embedded malpais boulder, showing 7x5x2 ft. above ground, marked + 1/16 8 HES 638 B0 on W. face, bears S. 77°51' E. 24 lks.

An embedded malpais boulder showing 5x4x2 ft. above ground, marked + 1/16 8 HES 638 B0 bears N. 10°08' W. 43 lks.

Thence S. 2°12' E.

Along meridional 1/4 Sec. line. Descend 50 ft. over rocky South slope.

6.50 Bottom of descent, thence over level bottom land.

12.25 Fence bears N. 66° W. and S. 66° E.

13.30 Arroyo 30 lks. wide, 4 ft. deep, course N. 66° W.

14.03 To Cor. No. 5, the place of beginning.

Chains

AREA

Tract A. - - - - -	19.64 acres
Tract B. - - - - -	18.69 "
Total Area - - - - -	38.33 acres
Tract C. (Unlisted area in exemption for logging railway)	2.35 acres

IMPROVEMENTS

The improvements made upon and for the benefit of this claim and belonging to the claimant herein consist of the following:

A frame house 24x16 ft., the long sides extending NW. and SE., the W. Cor. of which bears S. 61°38' E. 249 lks. from Cor. No. 2.

Value - - - - - \$400.00

A frame shed 12x6 ft., the long sides extending N. and S., the NW. Cor. of which bears S. 54°42' E. 273 lks. from Cor. No. 2.

Value - - - - - \$ 20.00

A frame outhouse 5x4 ft., the long sides extending N. and S., the SW. Cor. of which bears S. 50° E. 332 lks. from Cor. No. 2.

Value - - - - - \$ 10.00

GENERAL DESCRIPTION

The claim is comprised mainly of open bottom land bordered by low hills on the N. and S., lying about two miles southeasterly from the SE. end of Lake Mary. The area has a general drainage to the NW. The soil in the bottom land is a rich black loam of good depth and very fertile. The hillsides are rocky and suitable for grazing lands only. About 20 acres of the area are suitable for agricultural purposes, of which possibly 7 acres show signs of having been under cultivation in the past. None of the area, however,

Chains

was under cultivation at the time of survey.

Water for domestic use is obtained from Flagstaff, being hauled in tank car on the logging railway. It is believed water could be obtained at a shallow depth on the claim.

There is no timber on the claim.

There are no indications of mineral on the claim.

CONFLICTS AND ADJOINING CLAIMS

There are no conflicts. The claim is joined on the north and west by H. E. 423, patented by D. Chisholm on October 20, 1897; on the east by H. E. 077, patented by Donald Chisholm on April 7, 1914; and on the south by legal subdivisions, portion of claimants entry described as the N/2 NE/4 SW/4 Sec. 6.

Flagstaff, Arizona, the nearest postoffice and trading point lies about 15 miles in a northwesterly direction and is reached by a good wagon road.

Survey completed July 8, 1923.

Thomas J. Myler

Surveyor - Forest Service.

- DIRECTIONS.—1. Carry out calculations to two decimals only.
 2. In balancing Latitudes and Departures do not obliterate or change the original figures. Put the corrected figure or figures above in red ink. Do not change the footing of the original figures, but put below them the corrected footing in red ink. The corrections for balancing fallings should be proportional to the lengths of the lines.
 3. In calculations of fallings take result to nearest link. In calculations of N. and S. areas drop all after second decimal. Surveyors are required to use the Standard Field Tables issued by the G. L. O.
 4. Only three copies of this tabulation are necessary, for the District Office, the Surveyor General, and the Commissioner.

TABLING AND CALCULATIONS OF HOMESTEAD ENTRY SURVEY NO. 638, STATE OF ARIZONA

8-2349

CORNERS.	BEARING.	DISTANCE.	LATITUDES.		DEPARTURES.		DOUBLE M. D.	N. AREAS.		S. AREAS.	
			NORTH.	SOUTH.	EAST.	WEST.					
1 - 2	N. 1°58' W.	14.49	14 48		TRACT A.		50		7 24		
2 - 3	S. 65°00' E.	22.74		9 61		20 61		20 62			198.36
3 - 4	S. 2°12' E.	4.88		4 88		19		41 43			202 18
4 - 1	N. 89°56' W.	20.31		02			20 31	21 31		43	
		62.42	14 50	14 49		20 80			7 67		400 54
			14 49				20 80				7 67
			01				01				20/392 87
Error in Lat. & Dep.			14 50	14 50		20 81	20 81				
Closing error 1/4414											19 64 acres
					TRACT B.						
5 - 6	N. 65°00' W.	22.74	9 61				20 61	20 91	200 74		
6 - 7	N. 1°58' W.	4.45	4 45				15	15	67		
7 - 8	S. 89°55' E.	20.22		03		20 22		20 22			61
8 - 5	S. 2°12' E.	14.03		14 02		54		40 98			574 54
		61.46	14 06	14 05		20 76			201 41		575 15
			14 05			20 76					201 41
Error in Lat. & Dep.			01			00					20/ 373 74
Closing error 1/6146			14 05	14 05		20 76	20 76				18 69 acres

37

- DIRECTIONS.—1. Carry out calculations to two decimals only.
 2. In balancing Latitudes and Departures do not obliterate or change the original figures. Put the corrected figure or figures above in red ink. Do not change the footing of the original figures, but put below them the corrected footing in red ink. The corrections for balancing fallings should be proportional to the lengths of the lines.
 3. In calculations of fallings take result to nearest link. In calculations of N. and S. areas drop all after second decimal. Surveyors are required to use the Standard Field Tables issued by the G. L. O.
 4. Only three copies of this tabulation are necessary, for the District Office, the Surveyor General, and the Commissioner.

TABLING AND CALCULATIONS OF HOMESTEAD ENTRY SURVEY NO. 638, STATE OF ARIZONA

8-2349

CORNERS.	BEARING.	DISTANCE.	LATITUDES.		DEPARTURES.		DOUBLE M. D.		N. AREAS.		S. AREAS.	
			NORTH. '	SOUTH.	EAST.	WEST.						
2 - 3	S. 65°00' E.	22.74		9 61	20 61		20 61			198 06		
3 - 5	N. 2°12' E.	1.12	1 12		04		41 25	46 21				
5 - 6	N. 65°00' W.	22.74	9 61			20 61	20 69	198 83				
6 - 2	S. 1°58' W.	1.12		1 12		04	04				04	
		47.72	10 73	10 73	20 65	20 65		245 04		198 10		
			10 73		20 65			198 10				
Error in Lat. & Dep			00		00			20 / 46 94				
Closing error: None								2 35 acres				
TRACT C. (Unlisted Area in Exemption)												
Closing W ² Sec. 6												
	S 89° 51' E	38.84		10	38 84			S 89° 51' E	38.84	10	38.84	
	S 2° 12' E	20.40		20 34	3 09			S 2° 12' E	40.00	40.02	1.54	
	N 89° 38' W	39.67	25			39 67		N 89° 56' W	39.24	25	39.24	
	N 1° 39' W	20.26	20 23			2 31		N 1° 39' W	40.13	40.11	1.16	
		239.17	80 48	80 44	41 93	41 98				40.16 40.12 40.88	40.40	
			80 44			41 93						
			04			00						
Closing error 1:37 37												

45

APPROVAL

Office of the United States Surveyor General,

Phoenix, Arizona, April 4, 1924

The foregoing field notes of Homestead Entry Survey No.

638

executed by **Thomas F. Myers, Surveyor,**

[Forest Service Title]

under his special instructions, dated **June 25**, 1923, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.

Charles M. Donohoe

U. S. Surveyor General.

I certify that the foregoing transcript of the field notes of the above-described survey in the State of **Arizona**, has been correctly copied from the original notes on file in this office.

-----**Charles M. Donohoe**-----

U. S. Surveyor General.