

**ELLS**

**0**

**0**

**6**

**6**

**8**

# POOR QUALITY

**The following pages are scanned at the best possible quality setting. The original pages are of poor quality and this is the best possible reproduction.**

101

May 26 1941  
Aug. 14 "  
Oct. 9, "  
Feb. 16, 1942

U. S. DEPARTMENT OF AGRICULTURE  
FOREST SERVICE

**FIELD NOTES**

**FOREST SERVICE**  
Prescott National Forest  
PRESCOTT, ARIZONA  
MAY - 3 1941  
**RECEIVED**

OF  
EXCHANGE  
~~XXXXXXXXXX~~ SURVEY NO. 668

SITUATED IN THE **PRESCOTT** NATIONAL FOREST

ADMINISTRATIVE DISTRICT NO.

In Tract 44 which is within

~~in~~ Section 3 surveyed  
and Section 34 " "

Township 13 N. , Range 3 W.,  
" 14 N. , " 3 W.

and

Retracement of the West half of the South Boundary of Section 34,  
T. 14 N., R. 3 W. and line 3-4, Tract 44.

of the

Gila and Salt River Base and Meridian.

State of

Arizona

State of

Applicant for Exchange ~~XXXXXXXXXX~~ Phelps Dodge Corporation

Residence

Application No. , dated , 19

List No. , dated , 19

Applicant for survey

Residence

H. E. No. , dated , 19

Land Office

Survey executed by Edwin R. Sievers, Associate C.E., In Charge of Surveys  
[Forest Service Title.]

Under special instructions dated July 23 , 19 40

Survey commenced April 14 , 19 41

Survey completed April 19 , 19 41

Under Acts of March 20, 1922 and June 30, 1940.

102

OATH OF ASSISTANTS

We hereby certify that we assisted **Edwin R. Sievers, Associate C.E.**,  
In Charge of Surveys, in surveying all those

[Forest Service Title.]  
~~Exchange~~  
parts or portions of ~~Homestead Entry~~ Survey No. 668, in the State  
of **Arizona** which are represented in the following field notes  
as having been surveyed by him and under his direction; and that said  
survey has been in all respects, to the best of our knowledge and  
belief, well and faithfully surveyed, and the corner monuments estab-  
lished, according to the instructions furnished by the United States  
Surveyor General for

NOTE: It would have been very  
expensive and inconvenient to  
appear before an officer to ad-  
minister oath to assistants.  
Hence, they were taken by the  
Associate C.E., In Charge of  
Surveys.

*Aaron F. Jones*  
AARON F. JONES  
Sr. Engr. Aid.

*Frank Ciochetti*  
Enrollee CCC F19A.

Subscribed and sworn to before me this 19th day of

April, 1941

*Edwin R. Sievers*  
EDWIN R. SIEVERS  
Associate Civil Engineer,  
In Charge of Surveys

OATH OF SURVEYOR

I, **Edwin R. Sievers, Associate C.E., In Charge of Surveys**  
[Forest Service Title.]

do solemnly swear that, in strict conformity with the special instruc-  
tions of the ~~United States Surveyor General~~ <sup>Public Survey Office</sup> for **Arizona**, dated  
**July 23**, 19**40**, and the laws of the United States, I have  
well, faithfully, and truly, in my own proper person, surveyed a tract  
of land

, No. , dated , 19 , for  
the same to be known as ~~Homestead Entry~~ <sup>Exchange</sup> under the Act of **March 20**, 1922 & **June 30, 1940.**  
situated within the ~~Homestead Entry~~ <sup>Exchange</sup> Survey No. **668**,  
Prescott National Forest, in **Tract 44**  
in surveyed Section **s 3 & 4**, Township **13 N.**, Range **3 W.**, and  
surveyed Section **34**, Township **14 N.**, Range **3 W.**,

of the **Gila and Salt River Base & meridian**, **Arizona**, and the  
related retracements and resurveys and section subdivisions, which are  
represented in the following field notes as having been surveyed by me;  
and I further solemnly swear that all the corners of said survey have  
been established and perpetuated in strict accordance with the stated  
special instructions, and in the specific manner described in the field  
notes, and that the following are the original field notes of such  
survey.

*Edwin R. Sievers*  
EDWIN R. SIEVERS  
Associate C.E., In Charge of Surveys  
[Forest Service Title.]

Subscribed and sworn to before me this **Eighth** day of

May, 1941

*B. R. Bretton*



S-2349

Notary Public

EXCHANGE  
~~HOME/STEAD/ENTRY~~ SURVEY NO. 668

PRESCOTT NATIONAL FOREST

STATE OF ARIZONA

Chains: The tract of land embraced in this survey is in private ownership and was surveyed as said Tract 44, excepting this area of 5 acres, has been offered in exchange by Phelps Dodge Corp. for acquisition by the United States under the Acts of March 20, 1922 and June 30, 1940.

Applicant for Exchange, Phelps Dodge Corp. and 4, Situated in surveyed Tract 44 which is within Secs. 3, T. 13 N., R. 3 W., and surveyed Sec. 34, T. 14 N., R. 3 W. of the Gila and Salt River Base and Meridian, Prescott National Forest, Arizona.

Surveyed under special instructions from the Public Survey Office for Arizona, dated July 23, 1940, and designated as Exchange Survey No. 668.

Note: A thorough search was made for mounds of stone and cross on rock described in deed which is referred to in special instructions. The cross on rock was found and was used to determine the location of this tract of land. No evidence of any mounds of stone was found. Survey commenced April 14, 1941 and executed with a Gurley transit No. 12731 which is graduated to read direct to 1 minute of arc. The adjustments of the transit were tested and necessary adjustments made before commencing the survey.

All distances are horizontal and were reduced from measurements made directly on the slope with a 400 link steel tape. The slope angles were determined with a clinometer.

April 17, 1941.

At Cor. No. 3, Exchange Survey No. 668, hereinafter described, to stake approximately 5 chains Westerly.

Latitude 34° 32' 40" Longitude 112° 34'

from Forest Service Base Map, I observe Polaris at elongation as follows:

East Elongation, April 17, 1941 6 h. 06.1 m. - A.M.

Correction for Longitude 1.2 m.

April 17, 1941 Polaris at E. Elongation 6 h. 04.9 m. - A.M.

PRESCOTT NATIONAL FOREST

STATE OF ARIZONA

Chains Watch Time Telescope Angle from Mark to Star  
 6 h. 05 m. Direct 91° 04' 30" R.  
 6 h. 06 m. Reversed 91° 04' 30" R.  
 6 h. 05.5 m. Mean 91° 04' 30" Right  
 Azimuth of Polaris 1° 14' East  
 Angle Mark to Star 91° 04' 30" Right  
 Azimuth of Polaris 1° 14' East  
 Bearing Cor. No. 3 to Mark N. 89° 50' 30" W.

A CHECK POLARIS OBSERVATION.  
 April 18, 1941.  
 At Cor. No. 4, Exchange Survey No. 668, hereinafter described in  
 Latitude 34° 32' 40" Longitude 112° 34'  
 From Forest Service Base Map, I observe Polaris as follows:

Reference Mark Cor. No. 5, Exchange Survey No. 668.  
 Watch Time Telescope Angle from Mark to Star  
 6 h. 32 m. - P.M. Direct 1° 13' 30"  
 6 h. 37 m. - P.M. Reversed 1° 13' 00"  
 Mean 6 h. 34 m. 30" 1° 13' 15"  
 - 30 m.  
 6 h. 04.5 m. - Corr. to l.m.t.

Checked the watch against Western Union time, today and found it  
 correct for 105th Meridian Standard Time, which by difference of  
 longitude at this point is 30 m. fast of l.m.t.

Greenwich M.T. U.C. April 18, 1941 11 h. 57.8 m. - A.M.  
 Correction for longitude 1.2 m.  
 11 h. 56.6 m. - A.M.  
 l.m.t. U.C. Polaris April 18, 1941 11 h. 56.6 m. - A.M.  
 l.m.t. obsv. " April 18, 1941 6 h. 04.5 m. - P.M.  
 Hour Angle 6 h. 07.9 m.  
 Azimuth of Polaris 1° 14'  
 Bearing of Reference Mark N. 0° 0' 45" W.  
 Watch Time Telescope Angle from Mark to Star  
 6 h. 40 m. Direct 6:40-P.M. 1° 13' 00"

PRESCOTT NATIONAL FOREST

STATE OF ARIZONA

Chains 6 h. 41 m. Reverse 6:41-P.M. 1° 13' 00"

Mean 6 h. 40.5 m. 1° 13' 00"

- 30.0 m. Corr. to l.m.t.

6 h. 10.5 m. l.m.t. obsv.

l.m.t. U.C. Polaris April 18, 1941. 11 h. 56.6 m. A.M.

l.m.t. obsv. " April 18, 1941. 6 h. 10.5 m. - P.M.

Hour Angle 6 h. 13.9 m.

Azimuth of Polaris 1° 13' 54"

Bearing of Reference Mark N. 0° 0' 54" W.

The bearing of Reference Mark as determined from the mean of the observation is N. 0° 01' W.

RETRACEMENT OF THE WEST HALF OF THE SOUTH BOUNDARY OF SECTION 34, T. 14 N., R. 3 W. AND LINE 3-4, TRACT 44.

April 14, 1941.

Beginning at the 1/4 Cor. on the S. boundary of Sec. 34, T. 14 N., R. 3 W., an iron post, 1 in. in diameter, 20 in. above ground in mound of stone with brass cap marked and witnessed as described by the Public Survey Office.

Thence N. 89° 48' W.

Retracing line between Sec. 34, T. 14 N., R. 3 W., and Secs. 3 and 4, T. 13 N., R. 3 W. for flag on Cor. Secs. 33-34.

Descending west slope of mountain thru heavy pine timber and brush.

8.48 East bank of Creek.

9.42 Center of Wash and Stream, 30 links wide, bears N. 5° E.

9.78 North 7 links to Fence Corner.

10.59 West bank of Creek - across open field.

11.80 Center of Road. Course N. 10° E.

12.01 Cross Fence. Course N. 10° E.

16.19 Cross Fence. Course N. 10° E.

16.30 Cross small Drain. Bears N. 8° 30' E.

17.00 Enter heavily timbered area and begin ascending E. slope.

29.93 Closing corner to Secs. 3 and 4, T. 13 N., R. 3 W. An iron post, 2 in. in diameter, with brass cap, 9" above ground and set in mound of

106

EXCHANGE  
HOMESTEAD/ENTRY SURVEY NO. 668

PRESCOTT NATIONAL FOREST  
STATE OF ARIZONA

Chains stone, marked and witnessed as described by the Public Survey Office.

Across mountainous rolling country thru heavy timber and brush.

34.34 Cross small Drain. Bears N. 45° E.  
Ascend slope.

40.22 Cor. Secs. 33 and 34, T. 14 N., R. 3 W. An iron post, 2 in. in diameter, 18 in. above ground and set in mound of stone, with brass cap marked and witnessed as described by the Public Survey Office.

\*\*\*-----\*\*

RETRACEMENT LINE 4-3 TRACT 44.

Beginning at Cor. No. 4 of Tract 44 which is an iron post 1 in. in diameter, 18 in. above ground, also Cor. No. 1, Tract 37, with brass cap. Post is set in mound of stone and is marked and witnessed as described by the Public Survey Office.

N. 89° 50' W. Retracing line 4-3 for flag on Cor. No. 3.

39.91 Cor. No. 3 of Tract 44, also Cor. No. 2 of Tract 37, which is an iron post 1 in. in diameter, with brass cap, 10 in. above ground, set in mound of rocks and marked and witnessed as described by the Public Survey Office.

BOUNDARIES EXCHANGE SURVEY NO. 668

April 17, 1941.

Beginning at Cor. No. 1 and closing corner which was established on the section line common to Secs. 3 and 34, Ts. 13 & 14 N., R. 3 W., set an iron post, 12 in. above ground, 3 ft. long, 1 in. in diameter,

with brass cap marked: CC:S 34 TR 44

1:S 30

ES 668:T 13 N

R 3 W  
1941

Raised a mound of rock around the post.

South 1/4 Cor. of Sec. 34, T. 14 N., R. 3 W., bears S. 89° 48' E.,

8.01 chains.

Whence from corner a Pine 11 in. in diameter bears S. 58° 20' W.,

0.17 chains. Blazed and scribed AP 1 ES 668 B.T.

A Pine 5 in. in diameter bears N. 10° 17' W., 0.29 chains. Blazed

and scribed AP 1 ES 668 B.T.



EXCHANGE SURVEY NO. 668  
 PRESCOTT NATIONAL FOREST  
 STATE OF ARIZONA

Thence South	
	Along timbered hillside.
0.90	Wash, bears N. 55° W.
3.84	Cor. No. 2. Intersects south boundary Tract 44, at N. 89° 50' W. 9.33 chains from Cor. No. 4, Tract 44, previously described. Set an iron post 1 in. in diameter, 3 ft. long, 12 in. above ground, with brass cap marked: AP 2: TR <u>ES 668: 44</u> TR 37 1941 Raised mound of rock around post. Whence from corner a pine 6 in. in diameter bears N. 10° 16' W. 0.34 chains, blazed and scribed AP 2 ES 668 B.T. An oak 9 in. in diameter bears N. 49° 18' W. 0.65 chains, blazed and scribed AP 2 ES 668 B.T.
----- Thence N. 89° 50' W. Descend thru heavy timber.	
2.70	East bank of creek, leave timber.
3.00	Fall south 0.69 chains from cross on granite bed rock on west bank of creek.
3.06	Center of wash and stream, 30 links wide, bears N. 15° E.
3.42	Fall south 1.57 chains of barn 20 x 12 ft.
3.51	West bank of creek.
3.87	Center of road, bears S. 20° E.
4.03	Cross yard fence, course NE and SW.
4.82	N. W. corner of house, 30 x 20 ft.
5.25	Cross yard fence, course NE and SW.
6.17	Center of road, bears N. 70° E.
7.19	Cor. No. 3. Set an iron post 1 in. in diameter, 3 ft. long, 12 in. above ground, with brass cap. Raised mound of rock around post. Cor. No. 3, Tract 44 bears N. 89° 50' W. 23.39 chains. Marked cap: :AP 3 :ES <u>TR 44 :668</u> TR 37 1941 Whence from corner a box elder 17 in. in diameter bears N. 84° 48' E. 2.36 chains. Blazed and scribed AP 3 ES 668 B.T. A pine 13 in. in diameter bears S. 53° 59' W., 1.62 chains. Blazed

EXCHANGE SURVEY NO. 668  
 PRESCOTT NATIONAL FOREST  
 STATE OF ARIZONA

Chains

and scribed AP 3 ES 668 B.T.

-----  
 Thence North

Over slightly rolling, open land.

0.21 Cross fence, bears N.  $83^{\circ} 30'$  E.3.81 Cross small drain, bears N.  $53^{\circ} 30'$  E.

3.84 Cor. No.4 and closing corner on line between Secs. 3 and 34, Ts. 13 and 14 N., R. 3 W. Set an iron post 1 in. in diameter, 3 ft. long, 12 in. above ground, with brass cap. Raised mound of rock around post.

Marked cap:

S 34 : 4

TR PLAN:ES 668

44 T 13 N

S 3 : CC

R 3 W

1941

Corner to Secs. 33 and 34, T. 14 N., R. 3 W. bears N.  $89^{\circ} 48'$  W. 25.03chains. C. C. Secs. 3 and 4, T. 13 N., R. 3 W. bears N.  $89^{\circ} 48'$  W.14.74 chains. Corner No.1, this survey, bears S.  $89^{\circ} 48'$  E. 7.18 chains.Whence from corner a pine 7 in. in diameter bears N.  $80^{\circ} 30'$  W. 1.89 chains, blazed and scribed AP 4 ES 668 B.T.

No other bearing trees available.

-----  
 Thence North

Over slightly rolling, open land.

3.33 Cor. No. 5. Set an iron post 1 in. in diameter, 3 ft. long, 12 in. above ground, with brass cap. Raised mound of rock around post.

Marked cap:

TR

44: AP 5

: ES 668

1941

Whence from corner a pine 12 in. in diameter bears N.  $45^{\circ} 30'$  W. 0.17 chains, blazed and scribed AP 5 ES 668 B.T.A box elder 14 in. in diameter bears S.  $88^{\circ} 23'$  E. 2.23 chains, blazed and scribed AP 5 ES 668 B.T.:-----  
 Thence S.  $89^{\circ} 50'$  E.

Over slightly rolling, open country.

1.65 Center of spring, 9 links south.

2.13 Center of pond, 11 links south, 25 x 12 ft.

EXCHANGE  
HOMESTEAD/ENTRY SURVEY NO. 668

PRESCOTT NATIONAL FOREST

STATE OF ARIZONA

Chains

- 3.63 Fence. Bears S. 10° W.
- 3.84 Road. Bears S. 10° W.
- 4.80 Fence. Bears S. 30° E. - Enter timber.
- 5.16 West bank of Creek. - Descend into Wash.
- 6.06 Center of Wash and Stream, 30 links wide. Bears N. 10° E.
- 6.65 East bank of Creek.
- 7.18 Cor. No. 6. Set an iron post, 1 in. in diameter, 3 ft. long, 12 in. above ground, with brass cap. Raised mound of rock around post.

Marked cap: \_\_\_\_\_ : TR 44  
 AP 6 :  
 ES 668 :  
 1941

Whence from corner a Pine 18 in. in diameter bears S. 33° 36' W.,  
 0.20 chains. Blazed and scribed AP 6 ES 668 B.T.

A Pine 9 in. in diameter bears S. 87° 02' W., 0.35 chains. Blazed  
 and scribed AP 6 ES 668 B.T.

Thence South

along West slope of heavily timbered mountain.

- 3.33 Fall 0.9 links West of Cor. No. 1 and closing corner previously described.

True Course S. 0° 9' E.

	Area in Sec. 34, T. 14 N., R. 3 W.	2.39 Acres
Total Area 5.15 acres -	3, T. 13 N., R. 3 W.	2.76 "

Survey completed April 19, 1941.

*E. R. Sievers*  
 E. R. SIEVERS  
 Associate Civil Engineer  
 In Charge of Surveys



*suggest this edge be bound*

- DIRECTIONS.—1. Carry out calculations to two decimals only.  
 2. In balancing Latitudes and Departures do not obliterate or change the original figures.  
 Put the corrected figure or figures above in red ink. Do not change the footing of the original figures, but put below them the corrected footing in red ink.  
 The corrections for balancing fallings should be proportional to the lengths of the lines.  
 3. In calculations of fallings take result to nearest link. In calculations of N. and S. areas drop all after second decimal. Surveyors are required to use the Standard Field Tables issued by the G. L. O.  
 4. Only three copies of this tabulation are necessary, for the District Office, the Surveyor General, and the Commissioner.

EXCHANGE

TABLING AND CALCULATIONS OF ~~HOMESTEAD~~ ~~ENTRY~~ SURVEY NO. 668, STATE OF ARIZONA

8-2349

CORNERS.	BEARING.	DISTANCE. Chains	LATITUDES.		DEPARTURES.		DOUBLE M. D.	N. AREAS.		S. AREAS.	
			NORTH.	SOUTH.	EAST.	WEST.					
1 - 2	South	3.84		3 84'			0 00				
2 - 3	N. 89° 50' W.	7.19	02'			7 19	- 7 19	-	14'		
3 - 4	North	3.84	3 84'				- 14 38'	-	55 22'		
4 - 5	North	3.33	3 33'				- 14 38'	-	47 89'		
5 - 6	S. 89° 50' E.	7.18		02'	7 18'		- 7 20'			+	14'
6 - 1	S. 0° 09' E.	3.33		3 33'	01'		- 01'			+	03'
			7 19	7 19	7 19	7 19			- 103 25'	+	17'
									+ 17		
									20 / 103 08'		
									5 15		
		Closing error 0/1									
Area in Sec. 34, T. 14 N., R. 3 W											
4-5	North	3.33	3 33				00				
5-6	S. 89° 50' E.	7.18		02	7 18		- 7 18			+	14
6-1	S. 0° 9' E.	3.33		3 33	01		- 14 37			+	47 78
1-4	N. 89° 48' W.	7.18	02		7 18		- 7 19		14		
Area in Sec. 3, T. 13 N., R. 3 W											
			3 35	3 35	7 19	7 18					20 / 47 78
											2.39 Acres
1-2	South	3.84		3 84			00				
2-3	N. 89° 50' W.	7.19	02			7 19	- 7 19		14		
3-4	North	3.84	3 84				- 14 38		55 22		
4-1	S. 89° 48' E.	7.18		02	7 18		- 7 19			+	14
			2 86	3 86	7 18	7 19			20 / 55 22		2.76 Acres

2.76

112

No.	NAME	RESIDENCE	RELATION	STATUS	REMARKS	DATE	INITIALS
1							
2							
3							
4							
5							
6							
7							
8							
9							
10							
11							
12							
13							
14							
15							
16							
17							
18							
19							
20							

SO	10	10	10
10	10	10	10
10	10	10	10

CROCIUS CLAZ. O. I.

1000

1000

1000

THIS COPY IS FOR THE...  
 THE...  
 THE...  
 THE...  
 THE...

DIRECTIONS.—1. Carry out calculations to two decimals only.

2. In balancing Latitudes and Departures do not obliterate or change the original figures.

Put the corrected figure or figures above in red ink. Do not change the footing of the original figures, but put below them the corrected footing in red ink.

The corrections for balancing fallings should be proportional to the lengths of the lines.

3. In calculations of fallings take result to nearest link. In calculations of N. and S. areas drop all after second decimal. Surveyors are required to use the Standard Field Tables issued by the G. L. O.

4. Only three copies of this tabulation are necessary, for the District Office, the Surveyor General, and the Commissioner.

EXCHANGE

TABLING AND CALCULATIONS OF ~~HOMESTEAD ENTRY~~ SURVEY NO. 663, STATE OF ARIZONA (Tract 44 Closure)

8-2349

CORNERS. (Tr. 44 Closure)	BEARING.	DISTANCE. Chains	LATITUDES.		DEPARTURES.		DOUBLE M. D.	N. AREAS.		S. AREAS.	
			NORTH.	SOUTH.	EAST.	WEST.					
Tr. 44 4-3 (Retraced)	N. 89° 50' W.	39.91	12			39 91					
Tr. 44 3-2 (Record)	North	40.00	40 00								
Tr. 44 2-1 (Record)	S. 89° 34' E.	40.04		30	40 04						
Tr. 44 1-4 (Record)	South	40.00		40 00							
			40 12	40 30	40 04	39 91					
				40 12	39 91						
				18	13						
	Closure error.	1/901									

113

4/14

CHANGE ERROR 1/1

(50000) 4-1 44 44

(50000) 1-3 44 44

(50000) 2-1 44 44

(50000) 1-1 44 44

(50000) 44 44

00.04

40.04

00.04

40.04

00.04

IS	00	04	40	IS	00	04	40
SI	00	04	40	SI	00	04	40
IS	00	04	40	IS	00	04	40
SI	00	04	40	SI	00	04	40

UNITED STATES GOVERNMENT (mirrored text)



DIRECTIONS.—1. Carry out calculations to two decimals only.

2. In balancing Latitudes and Departures do not obliterate or change the original figures.

Put the corrected figure or figures above in red ink. Do not change the footing of the original figures, but put below them the corrected footing in red ink.

The corrections for balancing fallings should be proportional to the lengths of the lines.

3. In calculations of fallings take result to nearest link. In calculations of N. and S. areas drop all after second decimal. Surveyors are required to use the Standard Field Tables issued by the G. L. O.

4. Only three copies of this tabulation are necessary, for the District Office, the Surveyor General, and the Commissioner.

EXCHANGE

TABLING AND CALCULATIONS OF ~~HOMESTEAD ENTRY~~ SURVEY NO. 668, STATE OF ARIZONA (Sec. 34 closure)

S-2349

CORNERS. (Sec. 34 closure)	BEARING.	DISTANCE. Chains	LATITUDES.		DEPARTURES.		DOUBLE M. D.	N. AREAS.	S. AREAS.
			NORTH.	SOUTH.	EAST.	WEST.			
S $\frac{1}{2}$ , S34 SC 33 & 34 (Retraced)	N. 89° 48' W.	40.22	14		40	22			
SC 33 & 34-SC 28, 27, 33 & 34 (Record)	N. 0° 01' W.	80.00	80	00		02			
SC 28, 27, 33 & 34-SC 27, 26, 34 & 35 (Record)	East	80.06			80	06			
SC 27, 26, 34 & 35-SC 34 & 35 (Record)	S. 0° 01' E.	80.00		80	00	02			
SC 34 & 35-S $\frac{1}{2}$ S34	S. 89° 58' W.	40.00		02		40	00		
			80	14	80	08			
			80	02		80	08		
			12			16			
		Closing error	1/1601						

1/15

116

(grupos de .002) ANONIMA DO BRASIL

350 ON 28/08/1964

(grupos de .002)

55 04

41

32.04

1.121.00 R 41.8.77.02 1.412.13 (50055394)

50

00.08

00.08

1.110.00 R 35.05.77.03 (50055394)

30 03

30.08

1.081.00 R 32.14.79.05.03 (50055394)

50

00.08

1.150.00 R 35.05.77.03.15.02 (50055394)

00 04

50

00.04

1.137.00 R 35.05.77.03.15.02 (50055394)

15 03

00 03

80 03

50 08

41 05

00.04

1.137.00 R 35.05.77.03.15.02 (50055394)

1001/1 TORRE ANTONIO

APPROVAL

PUBLIC SURVEY OFFICE

~~Office of the United States Surveyor General,~~

Phoenix, Arizona, February 16, 1942, 191

The foregoing field notes of ~~Homestead Entry Survey No.~~

EXCHANGE SURVEY NO. 668

executed by Edwin R. Sievers, Associate C.E., In Charge of Surveys,  
Forest Service, [Forest Service Title.]  
under his special instructions, dated July 23, 1940, 191, having  
been critically examined, and the necessary corrections and explanations  
made, the said field notes, and the surveys they describe, are hereby  
approved.

*Sherman C. Fiske*  
~~U. S. Surveyor General.~~  
Office Cadastral Engineer

I certify that the foregoing transcript of the field notes of the  
above-described survey in the State of Arizona has been  
correctly copied from the original notes on file in this office.

5-2349

Sherman C. Fiske  
~~U. S. Surveyor General.~~  
Office Cadastral Engineer

APPROVAL

Office of the United States Attorney General

191

The foregoing field notes of Robert [Name] have been

APPROVED

executed by [Name], [Title], [Date], and the necessary corrections and explanations have been critically examined, and the survey is hereby approved.

Special Agent in Charge, [Department]

U.S. Department of Justice