

filed

NOV. 24 1913

JAN 26 1914

(4-683.)

Mineral Survey No. 3084

Lot No. _____

ARIZONA Land District.

FIELD NOTES

OF THE SURVEY OF THE MINING CLAIM OF

John C. Gillespie and Mrs. M. F. Sims

KNOWN AS THE

"BULL DOG" "OMAHA"

MARTINEZ Mining District,

YAVAPAI County, ARIZONA

Section 23 & 24, Township 10 N., Range 6 W.

Surveyed under instructions dated Nov. 5, 1913.

by J. WILLIAM WAARA,

U. S. Deputy Mineral Surveyor

Claim located See location notices, 1

Survey commenced November 10, 1913.

Survey completed November 13, 1913.

Address o 6-190

H. H. Linney Atty.,

Prescott Arizona.

SURVEY NO. 3084BULL DOG

Beginning at Cor.No.1 identical with Cor. No.1 of OMAHA Lode of this survey, a granite stone 5 x 12 x 30 inches long set twelve inches in the ground with a substantial mound of stone alongside; chiseled O-1, B D-1-3084 on north face with cross on top for exact corner point, from which point, the location monument being a mound of stone 3 foot base and 3 feet high, brs. S.26°-17'W. 26.0 ft.

The 1/4 corner between sections 23-24, of T.10 N. R.6 W. of the Gila and Salt River Base and meridian, brs. N.16°-09'E. 207.8 ft.

A rock in place 4 x 3 x 2 ft. exposed and chiseled BxR-0 1, B D-1-3084, brs. S.11°-46'W. 69.4 ft.

A projecting boulder 3 x 2 x 2 ft. exposed, and chiseled BxR-0 1, B D-1-3084, brs. S.22-30'E. 64.5 ft.

No other bearings available.

Feet

Thence N.26°-17'E.

130.6 Intersect the section line between sections 23-24, S.0°-01'E. 82.5 ft. from the 1/4 corner, ~~and S.0°-01'E. 443.5 feet from its intersection with line 3-4 of this lode.~~

339.8 EAST CENTER END, identical with West center End Omaha Lode Of this survey, a mound of stone.

702.2 TO.COR.No.2, identical with Cor. No.4 Omaha Lode of this survey, a granite boulder 18" x 14" x 12" exposed, with a substantial mound of stone alongside; chiseled B D-2 on southwest face and O-4-3084 on southeast face with cross on top for exact corner point, from which point,

A projecting granite slab, 10 x 12 x 3 ft. exposed and chiseled BxR-0-4, B D-2 3084 on top, brs. S.3°-48'E. 65.5 ft.

The location monument, being a mound of stone three foot base and three feet high brs. N.26°-17'E.18.0 ft.

No other bearings available.

Thence S.74°-46'W.

262.46 Intersect the section line between sections 23-24, N.0°-01'W. 361.0 ft. from the 1/4 corner, ~~and N.0° 01'W. 443.5 feet from its intersection with line 1-2 of this lode.~~

717.49 TO COR. No.3, a granite stone 5 x 12 x 30 inches long set twelve inches in the ground with a substantial mound of stone alongside, chiseled B D-3-3084 with cross on top for exact corner point, from which point,

A granite outcropping 6 x 8 x 6 ft. exposed and chiseled BxR-B D-3-3084 on north face , brs. S.44°-08'W. 57.9 ft.

The location monument, being a mound of stone three foot base and three feet high, brs. N.5°-59'E. 39.3 feet.

No other bearings available.

Thence N.34°-47'W.

576.87 TO COR. No.4, a granite boulder 4x3x3 ft. exposed, with a substantial mound of stone alongside; and chiseled B D 4-3084 with cross on top for exact corner point.

No bearings available.

Thence S.26°-17'W.

85.6 Cor.No.1, Last Chance Lode, ^{Sur.No.3085/} a rock in place, being a granite outcropping 6 x 3 x 3 ft. exposed, with a substantial mound of stone alongside, chiseled L C-1-3085 on west face with cross on top for exact corner point.

332.1 Cross trail course northwest to southeast.

335.4 WEST CENTER END, mound of stone.

468.4 South Center End Last Chance Lode Sur. No 3084, a mound of stone.

676.0 TO COR. NO.5, on line 4 - 1 Last Chance Lode, Survey No. 3085, being, a granite stone, 5 x 8 x 30 inches long, set twelve inches in the ground with a substantial mound of stone alongside, chiseled B D-5-3084 with cross on top for exact corner point, from which point,

A rock in place being a granite outcropping 12 feet high on lower side, and chiseled BxR- B D-5-3084, brs. S.57°-26'W. 9.3 ft.

A granite boulder 2 x 3 x 2 ft. exposed and

chiseled BxR, B D-5-3084, brs. S.46°-56'E. 24.9 ft.
 Cor, No. 4 Last Chance Lode Sur. No. 3085, being a granite boulder 3x4x3 ft. exposed and chiseled L C-4-3085, with cross on top brs. S.26°-17'W. 175.1 ft.
 Thence S.40°-58'E.

542.20 TO COR. No. 6, a rock in place, on granite dyke, chiseled B D-6-3084, with cross for exact corner point and substantial mound of stone alongside, from which point,

A granite boulder 4 x 5 x 4 ft. exposed and chiseled BxR-B D-6-3084, brs. S.13°-04'W. 95.5 ft.

The location monument, being a mound of stone three feet high and three foot base, brs. S.20°-00'W. 53.0 feet

No other bearings available.

Thence N.81°-18'E.

638.0 Cross trail course north to south.

662.68 To the place of beginning, Cor. No. 1.

All corners are identical with their respective locations except where otherwise mentioned. Variation at all corners 14°-00'E.

OMAHA

Beginning at Cor. No. 1, identical with Cor. No. 1 Bull Dog Lode of this survey, previously described, from which point, the location monument, being a mound of stone 3 foot base and 3 feet high, brs. S.26°-17'W. 26.0 ft.
 The 1/4 cor. between sections 23-24 of T.10 N. R.6 W. of the Gila and Salt River Base and Meridian, brs. N.16°-09'E. 207.8 ft.

Thence N, 82°-17'E.

58.37 Intersect the section line between sections 23-24, S.0°-01'E. 191.8 ft. from the 1/4 cor. ~~and 109.3 ft. from its intersection with line 4-1 of this lode.~~

1485.05 TO COR. No. 2, a granite boulder 27 x 6 x 12 inches exposed with a substantial mound of stone alongside; chiseled O-2 3084 on top with cross for exact corner point, from which point,

A rock in place, being a large granite dyke, chiseled BxR-O-2-3084 on east face, brs. S.75°-47'W. 42.8

feet

The Location monument, being a mound of stone three foot base and three feet high, brs. N.87°-59'E. 28.2 feet.

No other bearings available.

Thence N.26°-17'E.

50.0 Cross small wash flows west to east.

365.5 EAST CENTER END, a mound of stone, from which point, the location monument being a mound of stone three foot base and three feet high brs. N.81°-28'E. 29.5 feet.

728.9 TO COR. NO.3, a granite stone 4 x 10 x 24 inches long set twelve inches in the ground with a substantial mound of stone alongside; chiseled O-3-3084 on west face with cross on top for exact corner point, from which point,

A granite boulder 8 x 12 x 8 ft exposed and chiseled BxR-0-3-3084 on east face, brs. N.12°-59'W. 25.75 feet.

The location monument, being a mound of stone three foot base and three feet high, brs. N.81°-26'E. 31.2 feet.

No other bearings available.

Thence S. 81°26'W.

1000.0 Cross over cut of No.4 tunnel, S.58°-59'E. 4.0 feet from first set of timbers in tunnel.

1500.13-TO COR.No.4, identical with Cor. No.3 Bull Dog Lode of this survey and previously described.

Thence S.26°-17'W.

362.4 WEST CENTER END, identical with East center End Bull Dog Lode of this survey and previously described.

571.6 Intersect the section line between sections 23-24, S.0°-01'E. 82.5 feet from the 1/4 corner, and ~~N.0°-01'W. 100.3 feet from its intersection with line 1-2 of this lode.~~

702.2 To the place of beginning, Cor. No.1.

All corners are identical with their respective locations except where otherwise mentioned. Variation at all corners 14°-00'E.

LODE LINES

As near as can be determined from the present

developements, the veins on the respective lodes extend as follows from their discoveries;

Bull Dog Lode

N.36°-10'W. 555.3 feet, and N.78°-32'E. 695.2 ft.

Omaha Lode

S.81°-28'W. 19.6 feet, and N.81°-28'E. 1480.0 ft.

AREAS.

	Acres
Total area Bull Dog Lode - - - - -	15.499
Total area Omaha Lode - - - - -	20.223

LOCATION.

This survey is located in sections 23-24, T.10 N.E.6 W. of the Gila and Salt River Base and meridian, in the Martinez Mining District, Yavapai County, Arizona.

EXPENDITURE OF FIVE HUNDRED DOLLARS.

I hereby certify that the value of the labor and improvements made upon, or for the benefit of each location embraced in said mining claims, by the claimants or their grantors, is not less than five hundred dollars, and that said improvements consists of;

Bull Dog

No.1 Discovery monument, located on the ledge, S.36°-10'E. 555.3 ft. from West center End.

No.2 Incline Shaft, the center of which hrs. N.57°-49'E. 38.0 ft. from the West center end, 4x5' running N.32°-00'E. on an incline of 23° from the horizontal, 75.0 ft. to sta.1, thence same course 12.0 ft. to sta.2, thence same course 63.0 ft. to bottom. From sta. 1 runs a drift at right angles to shaft 5.0 ft. to south east. From Sta.2 runs a drift at right angles to shaft 33.0 ft. to center of winze 10 ft. deep. making a total of

Shaft 150.0 ft.	value	\$1500.00
Drifts 38.0 "	"	\$ 380.00
Winze 10.0 "	"	\$ 100.00

No.3 Trench, the northerly end of which brs. N.86°-46'E. 25.0 ft. from the West Center End, 3 x 4 ft. running S.21°-40'E. 60.0 ft.

value \$250.00

No.4 Incline shaft, the center of which brs. N.67°-55'E. 263.0 ft. from Cor. No.5; 4 x 6 ft. running N.33°-00'E., on an incline of 23° from the horizontal, 45.0 ft. to bottom.

Value \$450.00

No.5, Incline shaft, the center of which brs. S.85°-28'E. 285.0 ft. from Cor. No.5, 4 x 5 ft. running N.32°-00'E. , on an incline of 27°-30' from the horizontal 25.0 ft. to bottom.

Value \$250.00

No.6 Trench, the southwest end of which brs. S.88°-31'E. 372.0 ft. from Cor. No.5, ~~is~~ 5 x 10 ft. running N.64° E. 26.0 ft.

Value \$450.00

Omaha

No.1 Discovery cut, the south end of which brs. N.81°-28'E. 19.6 ft. from the West center end, six ft. wide running due north 24.0 ft. to breast being 10 ft. in height.

value \$ 250.00

No.2 Cut, the mouth of which brs. S.73°-52'E. 260.0 ft. from Cor. No.4, running northwesterly, 7.0 ft. wide, 15.0 ft. to 10 foot breast.

value \$175.00

No.3 Cut, the mouth of which brs. N.89°-18'E. 368.0 ft. from Cor. No.4, running northwesterly, 7.0 ft. wide, 12.0 ft. to 8.0 foot breast.

Value \$125.00

No.4 Tunnel, the mouth of which brs. N.82°-13'E. 508.0 ft. from Cor. No.4, 4x6 running N.58°-59'W. at 14.0 ft. first set at tunnel mouth proper, 74.0 ft. to point of cave-in, from which point access to deeper workings was impossible. This tunnel is considered to be in the neighborhood of 1100 feet in length, and the size of the waste dump verifies

the immense amount of work performed, as stated by disinterested parties.

Assumed Value \$10,000

OTHER IMPROVEMENTS

NONE

ADJOINING CLAIMS

This survey is bounded on the northwest by the Last Chance Lode Sur. No. 3085, John C. Gillespie and Dan Walsh, claimants.

There are no other adjoining claims.

INSTRUMENT

This survey was made with a Lietz Light Mountain transit-theodolite, No. 13-5929. The courses were deflected from the true meridian, as determined by observations by the use of the Saegmuller Solar attachment. The distances were measured with a 100 foot and 300 foot steel tapes.

REPORT

U.S.M.M. No. 1 cannot be tied to, as it is under the waste dump of one of the shafts of the Congress Consolidated Gold Mines Co. This was determined from the calls in the official records of the adjoining ⁱⁿ claims which were ^{tied/} to this monument.

The 1/4 cor. between sections 23-24, is a mound of stone as described in $\frac{1}{4}$ the field notes for same, but I was unable to distinguish positively any markings on stones near by, as called for in the notes. This corner bears N. 89° -55'E. 5286.4 ft. from the west 1/4 corner of section 23, so it agrees ~~as~~ exactly with the call for its true position according to the official records of subdivision of public lands.

Owing to the flatness of the veins passing through the above claims, topographical conditions have a great tendency to cause the outcropping to have a zigzag and irre-

gular course. This is very apparent on the Bull Dog Lode, where the vein passes through the west center end, and on ascending the mountain, has a southeasterly course to the discovery monument, which is located on the saddle of the range. As the ground slopes to the northeast from the saddle, this has a tendency to swing the outcropping of the vein to the north from the initial course. Thus the center line of the claim is caused to swing at the discovery, and take a course toward the discovery on the Omaha Lode, which is directly in line with the east center end of the Bull-Dog lode.

The discrepancies found existing between the claims as marked by location monuments and as described in the location notices, are due to errors in the location notices.

William Coara
U. S. MINERAL SURVEYOR.

ADDITIONAL REPORT

I was unable to find corners north and south, one half mile from the 1/4 corner between sections 33-34, T.10 N.R.6 W. so could not comply with section 15 page 11 of the Manual, and I assumed the course of said section line to be as of record. Improvement No. 4, a tunnel, was run on a vein outcropping on the Omaha lode, being the same vein which passes through improvements Nos 2 and 3. As the apex of this vein is on the Omaha Lode and the tunnel starts within its boundaries, I believe that the same is conclusive evidence of its developing the Omaha lode, and its value properly included in the estimate of expenditures for this claim.

FINAL OATHS FOR SURVEYS.

LIST OF NAMES.

A list of the names of the individuals employed by J. WILLIAM WAARA

United States ~~Deputy~~ Mineral Surveyor, to assist in running, measuring, and marking the lines, corners, and boundaries described in the foregoing field notes of the survey of the mining claim of

John C. Gillespie and Mrs. M. F. Sims

known as the "BULL DOG," "OMAHA"

and showing the respective capacities in which they acted.

Franklin Newhall, Chainman.

Chainman.

Axman.

Flagman.

FINAL OATHS OF ASSISTANTS.

We, I, Franklin Newhall

and _____, do solemnly swear that we assisted

J. WILLIAM WAARA, United States ~~Deputy~~ Mineral Surveyor, in marking the corners and surveying the boundaries of the mining claim of John C. Gillespie and Mrs. M. F. Sims

known as the "BULL DOG," "OMAHA"

represented in the foregoing field notes as having been surveyed by said ~~deputy~~ mineral surveyor and under his direction; and that said survey has been in all respects, to the best of our knowledge and belief, faithfully and correctly executed, and the corner and boundary monuments established according to law and the instructions furnished by the United States Surveyor-General for ARIZONA

Franklin Newhall Chainman.

Chainman.

Axman.

Flagman.

Subscribed and sworn to by the above-named persons before me this 18th

day of November, 1913

My commission expires Dec. 31, 1916.

John Luke
Notary Public

(4-686.)

FINAL OATH OF U. S. ~~DEPUTY~~ MINERAL SURVEYOR

I, J. WILLIAM WAARA, U. S. ~~Deputy~~ Mineral Surveyor, do solemnly swear that, in pursuance of instructions received from the United States Surveyor General for ARIZONA, dated November 5, 1913, I have, in strict conformity to the laws of the United States, the official regulations and instructions thereunder, and the instructions of said Surveyor General, faithfully and correctly executed the survey of the Mining Claim of John C. Gillespie and Mrs. M. F. Sims, known as the "BULL DOG" "OMAHA", situate in MARTINEZ Mining District, YAVAPAI County, ARIZONA, in Sections 23 & 24, Township No. 10 N., Range No. 6 W. --- G. & S. R. B. & M., and designated as Survey No. 3084, as represented in the foregoing field notes, which accurately show the boundaries of said mining claim as distinctly marked by monuments on the ground, and described in the attached copy of the location certificate, which was received by me from the Surveyor General with said instructions, and that all the corners of said survey have been established and perpetuated in strict accordance with the law, official regulations and instructions thereunder; and I do further solemnly swear that the foregoing are the true and original field notes of said survey and my report therein, and that the labor expended and improvements made upon said mining claim by claimants or their grantors are as therein fully stated, and that the character, extent, location and itemized value thereof are specified therein with particularity and full detail, and that no portion of said labor or improvements so credited to this claim has been included in the estimate of expenditures upon any other claim.

J. William Waara
 U. S. ~~Deputy~~ Mineral Surveyor.

Subscribed and sworn to by the said J. WILLIAM WAARA
 U. S. ~~Deputy~~ Mineral Surveyor, before me a NOTARY PUBLIC
 this 21st
 day of NOVEMBER, 1913

Richard Lamson
 Notary Public

My commission expires
March 3 - 1917

"Bull Dog"

Notice of Location.

12

AUG 12 1895

Know all Men by these Presents:

That ... the undersigned, have this day Located Fifteen Hundred (1,500) linear feet of this vein or lode, bearing precious metals, with all dips, spurs, angles and variations, with surface ground Three Hundred (300) feet on each side of the center of vein, with all Mineral Deposits contained therein, and all Timber growing within the limits of said claim, and all Water and Water Privileges thereon or appurtenant thereto, under and according to the provisions of the Mining Laws of the United States, under which it is Located.

This claim commences at this Monument and Notice placed upon the ledge, and runs Fifteen Hundred (1,500) feet in a Southerly direction along the ledge

The Exterior boundaries are as follows, viz:

Commencing at this Monument and Notice, and running Three Hundred (300) feet in an Easterly direction to monument of stone at N. E. corner of claim; thence in a Southerly direction parallel with the ledge Fifteen Hundred (1,500) feet to monument at S.E. corner of claim; thence at right angles across the ledge in a Westerly direction Six Hundred (600) feet to monument at S.W. corner of claim; thence parallel with the lode in a Northerly direction Fifteen Hundred (1,500) feet to monument at N.W. corner of claim; thence at right angles across the ledge in an Easterly direction Three Hundred (300) feet to monument upon the ledge and place of beginning.

This ledge may be more generally described as situated about half a mile from the Congress Mine and an extencen on the South East end of the Last Chance Mine. in Martines Mining District, Yavapai County, Arizona Territory, and shall be known as the Bull Dog Mining Claim.

DATED ON THE GROUND this 29 day of August 1895

Witchness

Ed Gillespie

J.C.Morgan.

Recorded at request of Ed Gillespie Nov 8" A.D. 1895, at 9 o'clock A.M., in Book 38 of Mines, Page 452 Records of Yavapai County, Arizona.

(Seal)

F.A.Tritle County Recorder.

By H.R.Tritle Deputy.

Territory of Arizona,)
:ss.
County of Yavapai.)

Know All Men by these Presents That Ed Gillep^{ie} of the County of Yavapai and Territory of Arizona the undersigned has this 28th day of May 1896 Amended, located, claimed and by these presents does amend locate and claim by right of discovery and amended location in compliance with the Mining Acts of Congress approved May 10th 1872 and all subsequent acts and with local customs, laws and regulations 1300 feet linear and horizontal measurement of the Bull Dog lode vein ledge or deposit, along the vein thereof with all its dips angles and variations as allowed by law, together with 300 feet on each side of the middle of said vein at the surface so far as can be determined from present developments and all veins lodes, ledges or deposits and surface ground within the lines of said claims 600 feet running S 35° E from location Monument at North end center of claim to Monument on vein, Thence N 78° 30' E 700 .. to Monument on center of vein at East center end of claim, said discovery and end Monuments being situated upon said lode vein ledge or deposit, and within the lines of said claim, in Martinez Mining District County of Yavapai and Territory of Arizona described by meets and bounds as follows to wit, Beginning at North center end Monuments N 26° E 137 feet from the South center end Monument of the Last Chance lode. Thence S 26° W 345 feet to Corner No 1. Thence S 35° E 600 feet to Cor. No 2 Thence N 78° 30' E 700 feet to Cor. No 3. Thence N 26° E 379.5 feet to East center end Mon. Thence N 26° E 379.5 feet to Cor. No 4. Thence S 78° 30' E 700 feet to Cor. No. 5. Thence N 35° W 600 feet to Cor No 6 Thence S 26° W 345 feet to North center end the place of beginning Magnetic Variation 14° 30' East. This claim is located about 2000 feet South East from the Congress Mill on unsurveyed land and joins the Last Chance Lode on the South end line. This being the same lode originally located on the 29 day of August 1895 and recorded on the 8th day of Nov 1895, in Book 38 pages 452 in the office of the Recorder of Yavapai County. This further and amended certificate of location is made without waiver of any previously acquired rights, but for the purpose of correcting errors in the original location, description or record.

Date of Location.....)
Date of Amended Certificate) Ed Gillep^{ie} (Seal)
28th day of May 1896)

Recorded at request of A Falco June 3rd A.D. 1896 at 10:15 O clock A.M. in
Book 44 of Mines pages 377 & 378 Records of Yavapai County Arizona.

(Seal)

F.A.Trittle

County Recorder.

Notice of Mining Location Quartz Claim.

To All Whom It May Concern:

This mining claim, the name of which is the Omaha Extension of Bull Dog Mining Claim, situate on lands belonging to the United States of America, and in which there are valuable mineral deposits, was entered upon and located for the purpose of exploration and purchase by Frank Nichols and Julius Warlop, the undersigned, on the first day of September, 1895.

The length of this claim is 1500 feet and ... claim 300 feet on each side of the discovery shaft (at which this notice is posted) lengthwise of the claim. The general course of the lode deposit and premises is from the N.W. to S.E.

The claim is situated and located in Martinez Mining District, in Yavapai County, in the Territory of Arizona, about half a mile in a N.W. direction from Congress Mine.

The surface boundaries of the claim are marked upon the ground as follows: Beginning at a point in a N.W. direction 200 feet from the discovery shaft, at which this notice is posted, being in the center of the West end line of said claim; thence 300 feet to a monument of stone being the S.W. corner of said claim; thence 750 .. to a monument of stone at the center of the South side line of said claim; thence 750 feet to a monument of stone, being at the S.E. corner of said claim; thence North 300 feet to a monument of .. at the center of the E.end of said claim; thence 300 feet to a monument of stone, being at the corner of said claim; thence 750 feet to a monument of stone being at the center of the N. side line of said claim; thence 750 feet to a monument at the N.W. corner of said claim; thence 300 feet to the place of beginning.

All done under the provisions of Chapter Six, of Title XXXI, of the Revised Statutes of the United States, and of an Act of the General Assembly of Arizona, entitled "An Act Concerning Mines, approved March 20th 1895, —

Dated and posted on the ground this first day of September, 1895.

Frank Nichols

Julius Warlop

Filed and recorded at request of F.H.Fall, Nov.29"A.D. 1895, at 9 o'clock A.M., in Book 42 of Mines, pages 382 et seq. Records of Yavapai County, Arizona.

(Seal)

F.A.Tritle

By M.O.Archibald

County Recorder.

Deputy.

Omaha (Amended)

Territory of Arizona)
 :ss.
 County of Yavapai)

Know all men by these Presents That Ed Gillepsie of the County of Yavapai and Territory of Arizona the undersigned, has this 28th day of May 1896 Amended, located and claimed, and by these presents, does Amend, locate and claim by right of discovery and amended location in compliance with the Mining Acts of congress approved May 10th 1872 and all subsequent acts, and with local customs, laws and regulations 1500 feet linear and horizontal measurement of the Omaha lode vein ledge, or deposits along the vein thereof with all its dips, angles and variations as allowed by law, together with 300 feet on each side of the middle of said vein, at the surface, so far as can be determined from present developments, and all veins, lodes ledges or deposits, and surface ground within the lines of said claim 20 feet running S.80° 15' W from discovery open cut to West center end monument and 1480 feet running N 81° 15' E to East center end monument. Said discovery Open Cut being situated upon said lode vein ledge or deposit, and within the lines of said claim in Martinez Mining District County of Yavapai and Territory of Arizona, described by meets and bounds as follows to wit Beginning at West center end Mon identical with East center end Monument of the Bull Dog lode. Thence S 26° W 379.5 feet to Cor No 1, Thence N 81° 15' E 1500 feet to Cor No 2 Thence N 26° W 366 feet to East center end monument 732 feet same ~~same~~ course to Cor. No 3 Thence S 81° 15' E 1500 feet to Cor No 4, Thence S 26° W 379.5 feet to West center end Monument to place of beginning. Magnetic Variation 14°30' E. This claim is located about 3000 feet South East from the Congress Mill on unsurveyed land and Joins the Bull Dog lode on the East end line, This being the same lode originally located on the 1st day of Sept.1895 and recorded on the 29 day of Nov 1895 in Book 42 page 382 in the office of the Recorder of Yavapai County. This further and Amended Certificate of location is made without waiver of any previously acquired rights but for the purpose of correcting errors in the original location, description or record.

Date of Location-

Date of Amended Certificate

28th day of May 1896

Ed Gillepsie (Seal)

Recorded at request of A Falco June 3rd A.D. 1896 at 10:15 O clock A.M. in Book 44 of Mines pages 375,376 & 377 Records of Yavapai County Arizona.

(Seal)

F.A.Tritle
 County Recorder.

Filed and recorded at request of _____

_____ A. D. 191 _____, at _____ o'clock

_____ M., Book _____ pages _____

Records of Yavapai County, Arizona.

{ SEAL }

L. S. COLWELL,
County Recorder,

By _____

Deputy Recorder.

STATE OF ARIZONA, }
COUNTY OF YAVAPAI. } ss.

I, L. S. Colwell, County Recorder in and for the County of Yavapai, State of

Arizona, and custodian of the records of such office, do hereby certify that I have compared the foregoing

~~copy with, and that the same is a full, true and correct copy of~~ ^{(Notices of Location of the} Bull Dog Mining Claim, filed ^{for record on Nov. 8, A. D. 1895, at 9: o'clock A.M. and recorded in Book 38 of} Mines, at page 452, and ^{the Amended Notice of Location of the (same) filed for} record on June 3rd A. D. 1896 at 10:15 o'clock A.M. and recorded in Book 44 of ^{Mines at pages 377 & 378; also the (Omaha Mining claim, filed for record on} Nov. 29th A. D. 1895, at 9:00 o'clock A.M. and recorded in Book 42 of Mines at ^{pages 382 et seq. and Amended Location Notice of same claim filed for} record on June 3rd A. D. 1896, at 10:15 o'clock A.M. and recorded in Book 44 of Mines ^{record in my office in Book _____ of _____}

at pages 375-377 and of the whole thereof.

IN WITNESS WHEREOF, I have hereunto set my
hand and affixed my Official Seal this 2nd day
of June, A. D. 1913

L. S. Colwell
County Recorder.



U. S. SURVEYOR GENERAL'S FINAL CERTIFICATE ON
FIELD NOTES.

DEPARTMENT OF THE INTERIOR,
OFFICE OF U. S. SURVEYOR GENERAL,

Phoenix, Arizona,

April 13, 1914.

I, U. S. Surveyor General for District of Arizona,
do hereby certify that the foregoing transcript of the Field Notes, return and approval
of the Survey of the mining claim of
JOHN C. GILLESPIE AND MRS. M. F. SIMS,
, known as the BULL DOG, OMAHA,
, situate in MARTINEZ
Mining District, YAVAPAI County,
ARIZONA, in Sections 23 & 24, Township No. 10 N.,
Range No. 6 W., and designated as Survey
No. 3084, has been correctly copied from the originals on
file in this office; that said Field Notes furnish such an accurate description of said
mining claim as will, if incorporated into a patent, serve fully to identify the premises,
and that such reference is made therein to natural objects or permanent monuments as
will perpetuate and fix the locus thereof.

And I further certify that five hundred dollars' worth of labor has been expended
each of
or improvements made upon said mining claim by claimants or their grantors, and
that said improvements consist of 3 shafts, 2 drifts, 1 winze, 2 trenches,
3 cuts and 1 tunnel, total value \$13930.00

and that no portion of said labor or improvements has been included in the estimate of
expenditures upon any other claim.

I further certify that the plat thereof, filed in the U. S. Land Office at Phoenix,
Arizona, is correct and in conformity with the foregoing Field Notes.

Frank S. Ingalls,

United States Surveyor General for Arizona.

4-687.

**SURVEYOR-GENERAL'S CERTIFICATE OF APPROVAL OF FIELD
NOTES AND SURVEY OF MINING CLAIM.**

Department of the Interior.

Office of U. S. Surveyor-General,

Phoenix, Arizona.

April 13, 1914.

I, U. S. Surveyor-General for District of Arizona

do hereby certify that the foregoing and hereto attached Field Notes and Return of the Survey of the
Mining Claim of

JOHN C. GILLESPIE AND MRS. M.E. SIMS.

, known as the

BULL DOG, OMAHA.

situate in MARTINEZ mining district,

YAVAPAI

County,

ARIZONA.

in Sections 23 & 24, Township No. 10 N., Range No. 6 W.,

, designated as Survey No. 3084

executed by J. William Waara, U. S. Deputy Mineral

Surveyor, November 10-13, 1913, 190, under my instructions dated

November 5, 1913, 190, have been critically examined and the necessary cor-
rections and explanations made, and the said Field Notes and Return, and the Survey they describe,

are hereby approved. A true copy of the copy of the location certificate filed by the applicant for
survey is included in the field notes.

Frank Ingalls

U. S. Surveyor-General for Arizona.