

MINERAL SURVEY No. 3557

ARIZONA Land District.

FIELD NOTES

OF THE SURVEY OF THE MINING CLAIM OF

MOHAVE MIDNIGHT MINING Company

KNOWN AS THE

MIDNIGHT lode

Wallapai Mining District,

Mohave County, Arizona

Section 10 8 11, Township 23 north, Range 18 west

Surveyed under instructions dated Dec. 23, 19 18

by Leon H. Foster U. S. Mineral Surveyor.

Claim located January 1st see location notice, 1896

Survey commenced Feb. 16, 19 19

Survey completed Feb. 17, 19 19

Address of claimant C. W. Herndon, Atty. Kingman, Arizona

DATES OF AMENDED LOCATIONS.

December 16 1918

Mineral Survey No. 3557

	Midnight lode.
feet	Beginning Cor. No. I.
	A pine post, 4 ft. long, 4 ins. square, with a nail at the exact corner, set in a mound of earth and stone, scribed M-I-3557.
	Identical with the location.
	The corner of sections 10-II-14-15, T. 23 N. R. 18 W. G. & S. R. B. & M. S. 2° 08' E. 276.30 ft.
	(Cor. No. 3. Pinkham lode, Sur. No. 525 bears N. 52° 06' W 1270.3)
	A granite boulder, 6 ft. long, 3 ft. wide and 4 ft. high, with a cross chiseled on the west face, marked B.R.-M-1-1389, bears N. 76° 23' E. 86.55 ft.
	Thence N. 23° 25' E.
282.13	Intersect line 3-A, Pinkham lode, Sur. No. 525 at N. 49° 35' E. 278.94 ft. and S. 49° 35' W. 321.06 ft. from corners No. 3 and 4, respectively.
299.00	To the southeast end center of the location.
	A pine post, 4 ft. long, 4 ins. square, with a nail at the exact point, set in a mound of earth and stone, scribed 3557.
	The discovery shaft bears N. 66° 35' W. 898.00 ft.
598.65	To Cor. No. 2.
	A pine post, 4 ft. long, 4 ins. square, with a nail at the exact corner, set in a mound of earth and stone, scribed M-2-3557.
	Identical with the location.
	A granite boulder, 4 ft. long, 3 ft. wide and 4 ft. above ground, with a cross chiseled on the north face, marked B.R.-M-2-1389, bears S. 8° 58' W. 113.70 ft.
	Thence N. 66° 34' W.
300.00	Cross <del>north and south</del> gulch. <i>course south</i>
334.41	Intersect line between sections 10 & 11, T. 23 N. R. 18 W. at N. 4° 43' W. 961.67 ft. and S. 4° 43' E. 1798.44 ft. from corner of sections 10-II-14-15 and quarter corner, <sup>bet. Secs 10 &amp; 11</sup> respectively.
559.40	To Cor. No. 1, Buckey O'Neil lode, Sur. No. 3375.
1498.00	To Cor. No. 3.

## Survey No. 3557.

Midnight lode, continued,

A pine post, 4 ft. long, 4 ins. square, with a nail at the exact corner, set in a mound of earth and stone, scribed M-3-3557.

Identical with the location and with Cor. No. 4 Little Midnight lode, Sur. No. 3375.

Thence S. 23° 25' W.

300.00 To the northwest end center of the location.

Identical with the southeast end center of Little Midnight lode, Sur. No. 3375.

A pine post, 4 ft. long, 4 ins. square, with a nail at the exact point, set in a mound of earth and stone, scribed 3557.

600.00 The discovery shaft bears S. 66° 35' E. 600 ft.

560.18 Intersect line 3-4, Towne lode, Sur. No. 2830 at S. 72° 55' E. 1388.25 ft. and N. 72° 55' W. 111.75 ft. from Cor. No. 3 and 4, respectively.

600.00 To Cor. No. 4.

A pine post, 4 ft. long, 4 ins. square, with a nail at the exact corner, set in a mound of earth and stone, scribed M-4-3557.

Identical with the location and with Cor. No. I, Little Midnight lode, Sur. No. 3375.

Cor. No. 4, Towne lode, Sur. No. 2830, bears N. 88° 16' E. 122.70 ft.

Thence S. 66° 37' E.

115.44 Intersect line 4-I, Towne lode, Sur. No. 2830 at S. 18° 37' W. 52.26 ft. and N. 18° 37' E. 547.74 ft. from Cor. No. 4 and I, respectively.

1439.73 Intersect line 2-3, Pinkham lode, Sur. No. 525 at N. 40° 25' W. 1417.87 ft. and S. 40° 25' E. 72.13 ft. from Cor. No. 2 and 3, respectively.

1483.85 Intersect line between sections 10 and 11, T. 23 N. R. 18 W. at N. 4° 43' W. 282.67 ft. and S. 4° 43' E. 2477.44 ft. from corner of sections 10-II-14-15 and quarter corner, respectively.

1498.00 To Cor. No. I, the place of beginning.

Variation at all corners - 14° 30' E.

Survey No. 3557.

Lode line. As near as can be determined from present developments, the lode line extends as follows-  
 N. 66° 35' W. 600 ft. and S. 66° 35' E. 898 ft.  
 from the discovery shaft.

\*\*\*\*\*

Location, This claim is located in the Wallapai Mining District, Mohave County, Arizona, in the southeast quarter of section 10 and the southwest quarter of section 11, T. 23 N. R. 18 W. G. & S. R. B. & M.-

\*\*\*\*\*

Area

Total area -----	20.611 acres
Area in conflict with Midnight lode, Sur. No. 1389 -----	20.611 "
Area in conflict with Towne lode, Sur. No. 2830 -----	0.120 "
Area in conflict with Pinkham lode, Sur. No. 525 -----	0.420 "

\*\*\*\*\*

Expenditure of Five Hundred Dollars

I certify that the value of the improvements and labor made upon and for the benefit of this claim by the claimant or his grantors is not less than Five Hundred dollars and are as follows.-

- No. 1 - The discovery shaft, two compartment on the lode line 600 ft. from the N.W.E.C. and timbered, 1/7 value ----- \$1290.00
- No. 2 - A shaft, 4 ft. wide, 8 ft. long and 60 ft. deep, on the lode line at 470 ft. from the northwest end center. ----- *Value* \$1500.00
- No. 3 - A shaft, 4 ft. wide, 8 ft. long and 5 ft. deep, on the lode line at 530 ft. from the northwest end center. ----- *Value* \$20.00
- No. 4.- A shaft, 4 ft. wide, 8 ft. long and 8 ft. deep, which bears S. 30° E. 595 ft. from Cor.

Survey No. 3557.

No. 5 - A shaft, 7 ft. wide, 9 ft. long and 10 ft. deep, on the lode line, at 640 ft. from the northwest end center. Value ----- \$60.00

No. 6 - A shaft, 7 ft, wide, 8 ft. long and 16 ft. deep, which bears N. 89° W. 1750 ft. from Cor. No. 2.

Value ----- \$125.00

No. 8 - An open cut, 12 ft. face, 4 ft. wide, running S. 66° E. 25 ft. to its mouth and a tunnel 4 ft. wide, 6 ft. high, running N. 30° W. 20 ft. from the face, which bears S. 82° W. <sup>640 ft.</sup> from Cor. No. 2.

Value ----- \$200.00

No. 7 - An open cut, 6 ft. face, 4 ft. wide, running South 20 ft. to its mouth. The center of the face bears S. 88° W. 645 ft. from Cor. No. 2.

Value ----- \$20.00

No. 9 - A shaft, 6 ft. wide, 8 ft. long and 35 ft. deep, which bears S. 81° 30' W. 610 ft. from Cor. No. 2.

Value ----- \$550.00

No. 10 - A shaft, 7 ft. wide, 9 ft. long and 5 ft. deep, which bears S. 75° 30' W. 387 ft. from Cor. No. 2.

Value ----- \$20.00

No. 11 - A shaft, 8 ft. wide, 9 ft. long and 8 ft. deep, which bears N. 86° W. 233 ft. from Cor. No. 2.

Value ----- \$50.00

No. 12 - A shaft, 7 ft. wide, 8 ft. long and 5 ft. deep, which bears N. 81° 30' W. 240 ft. from Cor. No. 2.

Value ----- \$20.00

\*\*\*\*\*

Instrument and Meridian.

This survey was made with a Berger & Sons Mining transit and a 500 and 100 ft. steel tape.

The Meridian was determined by direct observation on the sun.

\*\*\*\*\*

Survey No. 3557.

Report

This location is identical with the Midnight lode, Sur. No. 1389. and all corner posts are the original posts of said Survey.

The side and end lines and all other lines of this Survey were run direct on the ground.

The intersections with Survey No. 2830, Towne lode were made upon the ground and I find the records of said survey and Little Midnight lode, Sur. No. 3375, to be in error.

The course of line 4-1, Little Midnight lode, Sur. No. 3375 is in error 4 minutes.

In Buckey O'Neil lode, above survey, line I-2 is in error 3 minutes for course and 1 ft. in distance.

The intersections with Pinkham lode, Sur. No. 525 are calculated from the tie from Cor. No. 3 to the Section corner, there being nothing on the ground to define the corners.

The description of the bearing rocks in Midnight lode, Sur. No. 1389 are in error as to dimensions of rocks and the letter "M" was added to the markings by me for this survey.

The lack of topography in this survey is due to the fact that it lies in level country and there being no well defined ridges or gulches.

The No. 1 improvement is the main working shaft and is full of water. There being no maps of underground workings, I value it as per values given in Survey No. 3375, wherein it is described as 6x9ft, 301ft. deep, and distributed as a common improvement to the six lodes of Sur. 3375 and to this claim.

The section corner and quarter corner, tied to in this survey, are stones set in a mound of stones, and properly marked.

The corners of Survey No. 3375, tied to in this survey, are pine posts properly set and marked.

\*\*\*\*\*  
Adjoining and Conflicting Claims.

This survey is joined on the northwest end line

Survey No. 3557.

on the northeast side line by the Buckey O'Neil lode, Sur. by the Little Midnight lode, Sur. No. 3375, and, No. 3375, & by the Bay State lode, Unsurveyed, on the southwest side line.

Conflicts with Towne lode, Sur. No. 2830 on the southwest corner and with the Pinkham lode, Sur. No. 525, on the southeast corner.

*Robert H. Foster*

U. S. Mineral Surveyor.

Kingman, Arizona.

# FINAL OATHS FOR SURVEYS.

## LIST OF NAMES.

A list of the names of the individuals employed by Leon H. Foster  
 United States Mineral Surveyor, to assist in running, measuring, and marking the lines, corners, and  
 boundaries described in the foregoing field notes of the survey of the mining claim of \_\_\_\_\_  
 \_\_\_\_\_ ~~MOHAVE MIDNIGHT MINING~~ Company  
 known as the \_\_\_\_\_ MIDNIGHT Lode  
 and showing the respective capacities in which they acted.

\_\_\_\_\_ R. H. Hayward \_\_\_\_\_, *Chainman.*  
 \_\_\_\_\_ XXXXXXXXXXXXXXXXXXXXXXXXXXXX \_\_\_\_\_, *Chainman.*  
 \_\_\_\_\_ XXXXXXXXXXXXXXXXXXXXXXXXXXXX \_\_\_\_\_, *Asman.*  
 \_\_\_\_\_ XXXXXXXXXXXXXXXXXXXXXXXXXXXX \_\_\_\_\_, *Flagman.*

## FINAL OATHS OF ASSISTANTS.

~~Witness~~ I, \_\_\_\_\_ R. H. Hayward \_\_\_\_\_  
 and \_\_\_\_\_ XXXXXXXXXXXXXXXXXXXX \_\_\_\_\_, do solemnly swear that we assisted \_\_\_\_\_  
 \_\_\_\_\_ L. H. Foster \_\_\_\_\_, United States Mineral Surveyor, in marking the corners and surveying  
 the boundaries of the mining claim of \_\_\_\_\_  
 \_\_\_\_\_ Mohave Midnight Mining Company  
 known as the \_\_\_\_\_ MIDNIGHT Lode  
 represented in the foregoing field notes as having been surveyed by said mineral surveyor and under his  
 direction; and that said survey has been in all respects, to the best of our knowledge and belief, faithfully  
 and correctly executed, and the corner and boundary monuments established according to law and the instruc-  
 tions furnished by the United States Surveyor-General for \_\_\_\_\_ ARIZONA \_\_\_\_\_

\_\_\_\_\_ R. H. Hayward \_\_\_\_\_, *Chainman.*  
 \_\_\_\_\_ XXXXXXXXXXXXXXXXXXXX \_\_\_\_\_, *Chainman.*  
 \_\_\_\_\_ XXXXXXXXXXXXXXXXXXXX \_\_\_\_\_, *Asman.*  
 \_\_\_\_\_ XXXXXXXXXXXXXXXXXXXX \_\_\_\_\_, *Flagman*

Subscribed and sworn to by the above-named persons before me this \_\_\_\_\_ 18th  
 day of \_\_\_\_\_ July \_\_\_\_\_, 1919

\_\_\_\_\_ J. N. Van Meter \_\_\_\_\_  
 Clerk, Superior Court  
 Mohave County, Arizona \_\_\_\_\_



FINAL OATH OF U. S. MINERAL SURVEYOR.

I, Leon H. Foster, U. S. Mineral Surveyor,  
do solemnly swear that, in pursuance of instructions received from the United States  
Surveyor General for ARIZONA, dated  
Dec. 23 1918, I have, in strict conformity to the laws of the  
United States, the official regulations and instructions thereunder, and the instructions  
of said Surveyor General, faithfully and correctly executed the survey of the Mining  
Claim of Mohave Midnight Mining Comp<sup>pany</sup>, known as the  
Midnight lode,  
situate in Walla pai Mining District,  
Mohave County, ARIZONA, in Section  
10 1/2, Township No. 23 N., Range No. 18 West,  
and designated as Survey No. 3557, as represented  
in the foregoing field notes, which accurately show the boundaries of said mining claim  
as distinctly marked by monuments on the ground, and described in the attached copy  
of the location certificate, which was received by me from the Surveyor General with  
said instructions, and that all the corners of said survey have been established and per-  
petuated in strict accordance with the law, official regulations and instructions there-  
under; and I do further solemnly swear that the foregoing are the true and original  
field notes of said survey and my report therein, and that the labor expended and  
improvements made upon said mining claim by claimant or ~~their~~<sup>its</sup> grantors  
are as therein fully stated, and that the character, extent, location, and itemized value  
thereof are specified therein with particularity and full detail, and that no portion of  
said labor or improvements so credited to this claim has been included in the estimate  
of expenditures upon any other claim.

Leon H. Foster  
U. S. Mineral Surveyor.

Subscribed and sworn to by the said Leon H. Foster  
U. S. Mineral Surveyor, before me \_\_\_\_\_  
\_\_\_\_\_ this 18th  
day of July, 19 19

J. H. VanMaster  
Clerk, Superior Court.  
Mohave County  
Arizona.

U. S. SURVEYOR-GENERAL'S FINAL CERTIFICATE ON FIELD NOTES.

Department of the Interior,

OFFICE OF U. S. SURVEYOR-GENERAL,

Phoenix, Arizona,

March 23, 1920, 191

I, U. S. Surveyor-General for Arizona

do hereby certify that the foregoing transcript of the Field Notes, return and approval of the survey of the mining claim of Mohave Midnight Mining Company

known as the Midnight lode

situate in Wallapai

Mining District, Mohave County, Arizona

in Section 10 & 11, Township No. 23 N., Range No. 18 West, and

designated as Survey No. 3557, has been correctly copied from the originals on file in this office; that said Field Notes furnish such an accurate description of said mining claim as will, if incorporated into a patent, serve fully to identify the premises, and that such reference is made therein to natural objects or permanent monuments as will perpetuate and fix the locus thereof.

And I further certify that five hundred dollars' worth of labor has been expended or improvements made upon said mining claim by claimant or its grantors, and that said improvements consist of 10 shafts 2 cuts and 1 tunnel

Total value credited to this claim \$3895.

and that no portion of said labor or improvements has been included in the estimate of expenditures upon any other claim.

I further certify that the plat thereof, filed in the U. S. Land Office at Phoenix, Arizona is correct and in conformity with the foregoing Field Notes.

Frank P. Trott

United States Surveyor-General for Arizona.

SURVEYOR-GENERAL'S CERTIFICATE OF APPROVAL OF FIELD  
NOTES AND SURVEY OF MINING CLAIM.

Department of the Interior,

OFFICE OF U. S. SURVEYOR-GENERAL,

Phoenix, Arizona,

March 23, 1920, 191

I, U. S. Surveyor-General for Arizona

do hereby certify that the foregoing and hereto attached Field Notes and Return of the Survey of the  
Mining Claim of

Mohave Midnight Mining Company

, known as the

MIDNIGHT lode

situate in Wellapai mining district,

Mohave County, Arizona

in Section S 10 and 11, Township No. 23 N, Range No. 18 W.

, designated as Survey No. 3557

executed by Leon H. Foster, United States Mineral

Surveyor, Feb. 10 - 17, 1919, under my instructions dated

Dec. 23, 1918, have been critically examined and the necessary cor-

rections and explanations made, and the said Field Notes and Return, and the Survey they describe,

are hereby approved. A true copy of the copy of the location certificate filed by the applicant for

survey is included in the field notes.

  
U. S. Surveyor-General for Arizona.