

4-683

MINERAL SURVEY No. 3653

LOT No.

ARIZONA Land District.

FIELD NOTES

OF THE SURVEY OF THE MINING CLAIM OF

The Louis d'Or Mining and Milling Company

KNOWN AS THE

FAIRVIEW, DEMOCRAT, GOODENOUGH, BREIDLEY, BESSIE, HART,
and GOODNUF FRACTION Lodes, Globe Mining District,
Gila County, Arizona.

Sections 1 and 12, Township 1 N., Range 14 Unsur, and East
6 and 7 Unsur, 15

Surveyed under instructions dated July 19, 1920, 19

by Edwin T. Stewart
U. S. Mineral Surveyor.

Claim located See location notices, 19

Survey commenced July 21, 1920.

Survey completed July 31, 1920.

Address of claimant:

DATES OF AMENDED LOCATIONS.

See location notices

Charles I. Rawlins, Globe, Arizona,
Attorney for claimant.

MINERAL SURVEY NO. 3653

| Claims | M & B Desc. | Improvements | Loc. Notices |
|------------------|-------------|--------------|--------------|
| | Pg. | Pg. | Red Pg. |
| Bessie | 9 | 19 | 9 |
| Breidley | 7 | 18 | 7 |
| Democrat | 3 | 18 | 3 |
| Fairview | 1 | 17 | 1 |
| Goodenough | 5 | 18 | 5 |
| Goodnuf Fraction | 13 | 19 | 13 |
| Hart | 11 | 19 | 11 |

Feet.

MINERAL SURVEY NO. 3653.

FAIRVIEW Lode.

Beginning at Cor. No. 1, identical with N.E. Cor. of the location and Cor. No. 6, Bessie lode, this survey.

A standard 3 in. iron pipe, 3 ft. long, with iron cap divided in quadrants, and stamped 1-F-3653 in the quadrant facing this claim, set 22 ins. in concrete base, whence

The corner common to Townships 1 and 2 N., Ranges 14 and 15 E., G. & S.R.B. & M., bears N.14°-45'^{30"}W. 4495.9 ft.

A dacite boulder 7 x 7 x 3.5 ft. out of the ground, chiseled cross B.R.3653, bears N.06°-02'E. 30.6 ft.

No other bearings available.

Thence S.30°-51'E.

Along line 6-5 of said Bessie lode, this survey

227.9 To S.W.E.C. of said Bessie lode.

300.0 To N.E.E.C. monument of the location, from which the discovery shaft bears S.59°-36'W. 997.9 ft.

A pine post, 4 ft. long, 4 ins. sq., with nail at the exact point, set 12 ins. in the ground, on bed rock, scribed N.E.E.C.-F-3653.

514.7 To Cor. No. 2, identical with Cor. No. 5 of said Bessie lode, ^{this survey} from which the S.E. Cor. of the location, a monument of stone 3 ft. base, 3 ft. high. bears S.30°-51'E. 22.17 ft.

On line 4-1, Goodenough lode, this survey.

A redwood post, 4 ft. long, 4 ins. sq., with nail at the exact corner, set 24 ins. in the ground, scribed 2-F-3653 on the side facing this claim.

No bearings available.

Thence S.53°-37'W.

Along line 1-4 of said Goodenough lode.

356.2 To Cor. No. 3, identical with Cors. 4 and 1, respectively, of Goodenough and Democrat lodes, both of this survey, from which the S.E. Cor. of the location (previously

Feet. described) bears N.57°-11'E. 354.75 ft.

A redwood post, 4 ft. long, 4 ins. sq., with nail at the exact corner, set 18 ins. in the ground. with mound of stone, scribed 3-F-3653 on the side facing this claim, whence

An oak tree, 6 ins. in diameter, blazed and scribed cross B.T.3653, bears S.47°-12'W. 22.45 ft.
Cor. No. 1, Rosaline No. 7 lode, Sur. 2495, brs. N.40°34'W. 43.85 ft.
No other bearings available.

Thence S.57°-11'W.

Along line 1-5 of said Democrat lode.

50.54 Intersect line 1-2, Rosaline No. 7 lode, Sur. 2495, S.12°-57'W. 62.3 ft. from Cor. No. 1, from which corner, Cor. No. 4 of said Rosaline No. 7 lode bears N.76°-21'W. 558.8 ft.

129.0 Road, course northerly and southerly.

691.4 Bed of gulch, draining southerly.

861.34 Intersect line 3-4 of ~~said~~ Rosaline No. 7 lode, Sur. 2495, S.13°-33'W. 650.1 ft. from Cor. No. 4.

1143.9 To Cor. No. 4, identical with S.W. Cor. of the location. At the intersection of line 5-1, Democrat lode, this survey, with line 1-2, Little Chief lode, Sur. 3250, being N.30°-51'W. 19.4 ft. from Cor. No. 2 of said Little Chief lode.

A standard 3 in. iron pipe, 3 ft. long, with iron cap divided in quadrants and stamped 4-F-3653 in the quadrant facing this claim, set 21 ins. in concrete base, whence

A cross on monzonite in place, about which is chiseled B.R. 3653, bears N.55°-44'E. 24.5 ft.

No other bearings available.

Thence N.30°-51'W.

Along line 2-1 of said Little Chief lode.

290.3 To N.E.E.C. of said Little Chief lode.

299.8 To S.W.E.C. monument of the location.

A redwood post, 4 ft. long, 4 ins. sq., with nail at the exact point, set 22 ins. in the ground, scribed S.W.E.C.

Feet. F-3653.
 599.8 To Cor. No. 5, identical with N.W. Cor. of the location and Cor. No. 1 of said Little Chief lode.

A redwood post, 4 ft. long, 4 ins. sq. with nail at the exact corner, set 18 ins. in the ground, with mound of stone, scribed 1-L.C.-3250, to which I add 5-F-3653 for this claim.

A cross on monzonite in place, about which is chiseled B.R. 3250, to which I add 3653, bears N.24°-52'E, 43.8 ft.

No other bearings available.

Thence N.59°-36'E.

1497.90 To Cor. No. 1, the place of beginning.

DEMOCRAT lode.

Beginning at Cor. No. 1, identical with N.E. Cor. of the location and Cors. 3 and 4, respectively, of Fairview and Goodenough lodes, both of this survey.

A redwood post, previously described, to which I add 1-D on the side facing this claim.

The corner common to Townships 1 and 2 N., Ranges 14 and 15 E., G. & S.R.B. & M., bears N.12°-37'-20"W. 5125.4 ft.

Thence S.30°-15'E.

Along line 4-3 of said Goodenough lode.

300.30 To N.E.E.C. monument of the location, identical with S.W.E.C. of said Goodenough lode, from which the discovery cut bears S.57°-11'W. 65.0 ft.

A redwood post, 4 ft. long, 4 ins. sq., with nail at the exact point, set 18 ins. in the ground, with mound of stone, scribed N.E.E.C.-D-3653 on the side facing this claim.

600.30 To Cor. No. 2, identical with S.E. Cor. of the location and Cors. Nos. 3 and 5, respectively, of Goodenough and Bradley lodes, both of this survey.

A redwood post, 4 ft. long. 4 ins. sq., with nail at the exact corner, set 18 ins. in the ground, with mound of stone, scribed 2-D-3653, on the side facing this claim, whence

- Feet.** An oak tree, 11 inches in diameter, blazed and scribed cross B.T.-3653, bears N.28°-08'W. 42.2 ft.
- No other bearings available.
- Thence S.57°-10'W.
- Along line 5-4 of said Bradley lode.
- 465.70 Road, course northwesterly and southeasterly.
- 640.00 Intersect line 1-2, Rosaline No. 7 lode, Sur.2495, S.12°-57'W. 922.4 ft. from Cor. No. 1.
- 748.70 Bed of gulch, draining southerly.
- 763.70 To Cor. No. 3, identical with Cor. No. 4 of said Bradley lode, from which the S.W. Cor. of the location, a 4 x 4 post in monument of stone, bears S.57°-10'W. 733.8 ft.
- A standard 3 in. iron pipe, 3 ft. long, with iron cap divided in quadrants, and stamped 3-D-3653 in the quadrant facing this claim, set 21 ins. in concrete base.
- No bearings available.
- Thence S.72°-22'W.
- 564.70 Intersect lines 2-1 and 3-4, respectively, of Innes lode Sur. 1638 and Rosaline No. 7 lode, Sur. 2495, S.16°-00'E. 294.5 ft. from Cor. No. 2 of said Innes lode, and N.13°-33'E. 104.8 ft. from Cor. No. 3 of said Rosaline No. 7 lode.
- 751.20 To Cor. No. 4, from which the S.W. Cor. monument of the location, (previously described), bears S.30°-15'E. 197.2 ft.
- A dacite boulder, 2.5 x 3 x 4 ft., chiseled cross 4-D-3653 on the east face, with mound of stone alongside.
- No bearings available.
- Thence N.30°-15'W.
- 103.40 To S.W.E.C. monument of the location.
- A redwood post, 4 ft. long, 4 ins. sq., with nail at the exact point; set 20 ins. in the ground, scribed S.W.E.C.-D-3653.
- 307.40 Intersect lines 2-3 of each of the Innes lode, Sur. 1638 and the Little Chief lode, Sur. 3250, S.73°-35'W. 262.1

| | |
|---------|--|
| Feet. | ft. from Cor. No. 2 of said Innes lode and S.45°-03'W. 365.15 ft. from Cor. No. 2 of said Little Chief lode. |
| 403.70 | To Cor. No. 5, identical with N.W. Cor. of the location. A cross on monzonite in place, about which is chiseled 5-D-3653, with mound of stone alongside. |
| | No bearings available. |
| | Thence N.57°-11'E. |
| 353.50 | To Cor. No. 4, Fairview lode, this survey, and intersect line 1-2, Little Chief lode, Sur. 3250, N.30°-51'W. 19.4 ft. from Cor. No. 2. |
| | Along line 4-3 of said Fairview lode. |
| 636.06 | Intersect line 3-4, Rosaline No. 7 lode, Sur. 2495, N. 13°-33'E. 759.9 ft. from Cor. No. 3. |
| 806.00 | Bed of gulch, draining southerly. |
| 1368.40 | Road, course northerly and southerly. |
| 1446.86 | Intersect line 1-2, Rosaline No. 7 lode, Sur. 2495, S.12°- 57'W. 62.3 ft. from Cor. No. 1. |
| 1497.40 | To Cor. No. 1, the place of beginning. |
| | GOODENOUGH Lode. |
| | Beginning at Cor. No. 1, identical with N.E. Cor. of the location and Cor. No. 4, Goodnuf Fraction lode, this survey. |
| | On line 1-2, Starr No. 2 lode, Sur. 2699, S.53°-37'W. 15.0 ft. from Cor. No. 1. |
| | A redwood post, 4 ft. long, 4 ins. sq., with nail at the exact Cor., set 20 ins. in the ground. scribed 1-G-3653 on the side facing this claim, whence |
| | The south quarter corner of section 31, T. 2 N., R. 15 E., G. & S.R.B. & M., bears N.04°-02'E. 4147.3 ft. |
| | No other bearings available. |
| | Thence S.30°-15'E. |
| | Along line 4-3 of said Goodnuf Fraction lode. |
| 300.30 | To N.E.E.C. monument of the location, from which the discovery cut bears S.53°-37'W. 1260.0 ft. |
| | A pine post, 3 ft. long, 4 ins., sq., with nail at the |

Feet. exact point, set 18 ins. in the ground. scribed N.E.E.C.-G-3653.

346.74 Intersect line 3-4, Starr lode, Sur. 2494, N.55°-25'E. 67.65 ft. from Cor. No. 3.

347.20 To Cor. No. 3 of said Goodnuf Fraction lode, *this survey*

599.10 To Cor. No. 3, identical with S.E. Cor. of the location. A standard 3 in. iron pipe, 3 ft. long, with iron cap divided in quadrants, and stamped 2-G-3653 in the quadrant facing the claim, set 20 inches in concrete base.

No bearings available.

Thence S.53°-34'W.

157.20 To Cor. No. 4, Rosaline No. 10 lode, Sur. 2701 and intersect line 2-3, Starr lode, Sur. 2494, S.11°-38'E. 278.8 ft. from Cor. No. 3.

Along line 4-3 of said Rosaline No. 10 lode.

477.20 To N.W.E.C. of said Rosaline No. 10 lode.

776.60 To Cor. No. 3 of said Rosaline No. 10 lode and Cor. No. 1, Bradley lode, this survey.

Along line 1-5 of said Bradley lode.

1496.60 To Cor. No. 3, identical with S.W. Cor. of the location Cor. No. 5 of said Bradley lode and Cor. No. 2, Democrat lode, also of this survey.

A redwood post, previously described, to which I add 3-G on the side facing this claim.

Thence N.30°-15'W.

Along line 2-1 of said Democrat lode.

300.00 To S.W.E.C. monument of the location, identical with N.E.E.C. of said Democrat lode.

A redwood post, previously described. to which I add S.W.E.C.-G, on the side facing this claim.

600.30 To Cor. No. 4, identical with N.W. Cor. of the location, Cor. No. 1 of said Democrat lode, and Cor. No. 3, Fairview lode, also of this survey.

A redwood post, previously described, to which I add 4-G, on the side facing this claim.

| | |
|---------|---|
| Feet. | Thence N.53°-37'E. |
| | Along line 3-2 of said Fairview lode. |
| 356.20 | To Cor. No. 2 of said Fairview lode and Cor. No. 5, Bessie lode, also of this survey. |
| | Along line 5-4 of said Bessie lode. |
| 482.20 | To Cor. No. 4 of said Bessie lode, and Cor. No. 2, Starr No. 2 lode, Sur. 2699. |
| | Along line 2-1 of said Starr No. 2 lode. |
| 1496.50 | To Cor. No. 1, the place of beginning. |
| | BREIDLEY lode. |
| | Beginning at Cor. No. 1, identical with N.E. Cor. of the location and Cor. No. 3, Rosaline No. 10 lode, Sur. 2701. |
| | On line 2-3 Goodenough lode, this survey. |
| | The post at this corner of the Rosaline No. 10 lode, being badly rotted I removed it and set a standard 3 inch iron pipe, 3 ft. long, with iron cap divided in quadrants, stamped 3-2701-R 10 in the quadrant facing said Rosaline No. 10 claim and 1-B-3653 in the quadrant facing this claim, 22 inches in concrete base. |
| | The south quarter corner of section 31, T. 2 N., R. 15 E., G. & S.R.B. & M., bears N.06°-51'E. 5152.5 ft. |
| | A cross on monzonite in place, about which is chiseled B.R. 3653, bears S.81°-16'W.20.85 ft. |
| | No other bearings available. |
| | Thence S.24°-56'E. |
| | Along line 3-2 of said Rosaline No. 10 lode. |
| 280.00 | To N.E.E.C. monument of the location, from which the discovery cut bears S.55°-26'W. 1437.0 ft. |
| | A pine post, 4 ft. long. 4 ins. sq., with nail at the exact point, set 12 ins. in the ground, on bed rock, with mound of stone, scribed N.E.E.C.-B-3653. |
| 525.50 | To Cor. No. 2, identical with S.E. Cor. of the location and Cor. No. 1, Hart lode, this survey. |
| | On line 2-3 of said Rosaline No. 10 lode, Sur. 2701. |
| | A redwood post, 4 ft. long, 4 ins. sq., with nail at the exact corner, set 24 ins. in the ground. with mound of |

| Feet. | stone, scribed 2-B-3653 on the side facing this claim, whence An oak tree, 9 ins. in diameter, blazed and scribed cross B.T. 3653, bears S.20°-12'E. 47.6 ft. No other bearings available. Thence S.55°-26'W. Along line 1-4 of said Hart lode. |
|---------|--|
| 954.90 | To Cor. No. 4 of said Hart lode, and intersect line 3-4, Bonita lode, Sur. 1638, S.77°-09'W. 589.15 ft. from Cor. No. 3. |
| 1103.00 | Road, course northerly and southerly. |
| 1160.00 | Road, course northwesterly and southeasterly. |
| 1483.00 | To Cor. No. 3, identical with S.W. Cor. of the location. A standard 3 in. iron pipe, 3 ft. long, with iron cap divided in quadrants, and stamped 3-B-3653 in the quadrant facing the claim, set 19 inches in concrete base, whence An Oak tree, 12 ins. in diameter, blazed and scribed cross B.T. 3653, bears N.55°-26'E. 41.75 ft. No other bearings available. Thence N.24°-56'W. |
| 184.00 | Bed of gulch, draining southerly. |
| 199.80 | Intersect lines 3-4 and 1-2, respectively, of Bonita lode, Sur. 1638 and Rosaline No. 9 lode, Sur. 2732, S.77°-09'W. |
| 1121.60 | 1121.60 ft. from Cor. No. 3 of said Bonita lode and S.77°-09'W. 0.30 ft. from Cor. No. 1 of said Rosaline No. 9 lode. |
| 245.50 | To S.W.E.C. monument of the location. A redwood post, 4 ft. long, 4 ins. sq., with nail at the exact point, set 22 ins. in the ground. scribed S.W.E.C.-B-3653. |
| 306.00 | Bed of gulch, draining southeasterly. |
| 384.85 | To Cor. No. 5 of said Rosaline No. 9 lode (from which Cor. No. 1 of said Rosaline No. 9 lode bears S.25°-2'E. 185.1 ft.) and intersect line 1-2, Rosaline No. 7 lode, Sur. 2495, S.12°-57'W. 1121.9 ft. from Cor. No. 1. |

Feet.
421.00 Bed of gulch draining southwesterly.
525.30 To Cor. No. 4, identical with N.W. Cor. of the location
and Cor. No. 3, Democrat lode, this survey, from which the
N.E. Cor. of the location bears N.55°-25'E. 1483.0 ft.
An iron pipe with cap, previously described, to which I add
4-B-3653 in the quadrant facing this claim.
Thence N.57°-10'E.
Along line 3-2 of said Democrat lode.
15.00 Bed of gulch, draining southerly.
123.70 Intersect line 1-2, Rosaline No. 7 lode, Sur. 2495, S.12°-
57'W. 922.4 ft. from Cor. No. 1.
300.00 Road, course northwesterly and southeasterly.
763.70 To Cor. No. 5, identical with Cors. 2 and 3, respectively,
of Democrat and Goodenough lodes, both of this survey.
A redwood post, previously described, to which I add
5-B. on the side facing this claim.
Thence N.55°-34'E.
Along line 3-2 of said Goodenough lode.
720.00 To Cor. No. 1, the place of beginning.
BESSIE Lode.
Beginning at Cor. No. 1, identical with N.E. Cor. of the
Location.
A standard 3 in. iron pipe, 3 ft. long, with cap divided
in quadrants, stamped 1-B-3653 in the quadrant facing
the claim, set 22 ins. in concrete base, whence
The south quarter corner of section 31, T. 2 N., R. 15 E.,
G. & S.R.E. & M., bears N.09°-32'E. 3221.4 ft.
Cor. No. 3, May lode, Sur. 2699, bears S.45°-55'W. 176.15
ft.
No other bearings available.
Thence S.30°-51'E.
29.75 Intersect line 3-4, of said May lode N.55°-37'E. 171.8 ft.
from Cor. No. 3.
315.00 To N.E.E.C. monument of the location, from which the
discovery cut bears S.41°-20'W. 1313.6 ft.

| | |
|---------|---|
| Feet. | A monument of stone, 3.5 ft. base, 3 ft. high. |
| 483.50 | To Cor. No. 5, Pittsburg lode, Survey 2699, and intersect line 2-3, May lode, also of Sur. 2699, S.52°-00'E. 475.2 ft. from Cor. No. 3. |
| | Along line 5-4 of said Pittsburg lode. |
| 630.00 | To Cor. No. 2, identical with S.E. Cor. of the location and Cor. No. 4 of said Pittsburg lode, from which the S.W. corner of the location, a 4 x 4 post in monument of stone, bears S.41°-20'W. 1491.2 ft. |
| | The post at this corner of said Pittsburg lode being badly rotted, I removed it and set a standard 3 in. iron pipe, 3 ft. long, with iron cap divided in quadrants, stamped 4-2699-P in the quadrant facing said Pittsburg lode and 2-B-3653 in the quadrant facing this claim, 21 ins, in concrete base. |
| | No bearings available. |
| | Thence S.41°-25'W. |
| | Along line 4-3 of said Pittsburg lode. |
| 280.70 | To Cors. 3 and 4, respectively, of Pittsburg and Starr No. 2 lodes, both of Sur. 2699. |
| | Along line 4-3 of said Starr No. 2 lode. |
| 1358.90 | To Cor. No. 3, identical with Cor. No. 3 of said Starr No. 2 lode. |
| | A pine post, 4 ins. sq., with nail at the exact corner, showing 28 ins. out of the ground, scribed 3-2699-S 2, to which I add 3-B-3653, on the side facing this claim. |
| | No bearings available. |
| | Thence S.30°-13'E. |
| | Along line 3-2 of said Starr No. 2 lode. |
| 1.00 | To point for S.W.E.C. of said Starr No. 2 lode. |
| 2.00 | To Cor. No. 4, identical with Cor. No. 2 of said Starr No. 2 lode, from which the S.W. corner of the location (previously described) bears S.41°-20'W. 131.7 ft. |
| | On line 4-1, Goodenough lode, this survey. |
| | A redwood post, 4 ins., sq., with nail at the exact corner, showing 28 ins. out of the ground, scribed |

| | |
|---|---|
| <p>Feet.</p> <p>126.00</p> <p>214.70</p> <p>286.80</p> <p>514.70</p> <p>1345.75</p> <p>1421.05</p> <p>1520.20</p> | <p>2-2699-S 2, to which I add 4-B-3653 on the side facing this claim.</p> <p style="text-align: center;">No bearings available.</p> <p style="text-align: center;">Thence S.53°-37'W.</p> <p>Along line 1-4 of said Goodenough lode.</p> <p>To Cor. No. 5, identical with Cor. No. 2, Fairview lode, this survey, from which the S.W. corner of the location (previously described) bears S.30°-51'E. 28.16 ft.</p> <p>On line 4-1, Goodenough lode, this survey.</p> <p>A redwood post, previously described, to which I add 5-B on the side facing this claim.</p> <p style="text-align: center;">Thence N.30°-51'W.</p> <p>Along line 2-1 of said Fairview lode.</p> <p>To N.E.E.C. of said Fairview lode.</p> <p>To S.W.E.C. monument of the location.</p> <p>A monument of stone, 3.5 ft. base, 4 ft. high.</p> <p>To Cor. No. 6, identical with N.W. Cor. of the location and Cor. No. 1 of said Fairview lode.</p> <p>An iron pipe, with cap, previously described, to which I add 6-B-3653 in the quadrant facing this claim.</p> <p style="text-align: center;">Thence N.38°-12'E.</p> <p>Intersect line 2-3, May lode, Sur. 2699, S.52°-00'E. 23.65 ft. from Cor. No. 3.</p> <p>Intersect line 3-4 of said May lode, N.55°-37'E. 79.0 ft. from Cor. No. 3.</p> <p>To Cor. No. 1, the place of beginning.</p> <p style="text-align: center;">HART Lode.</p> <p>Beginning at Cor. No. 1, identical with N.E. Cor. of the location and Cor. No. 2, Bradley lode, this survey.</p> <p>On line 2-3, Rosaline No. 10 lode, Sur. 2701.</p> <p>A redwood post, previously described, to which I add 1-H for this claim.</p> <p>The south quarter corner of section 31, T. 2 N., R. 15 E., G & S.R.E. & M., bears N.04°-01'-20"E. 5606.1 ft.</p> <p style="text-align: center;">Thence S.24°-56'E.</p> <p>Along line 3-2 of said Rosaline No. 10 lode.</p> |
|---|---|

- Feet.
303.80 To N.E.E.C. monument of the location, from which the discovery cut bears S.55°-26'W. 19.0 ft.
A redwood post, 4 ft. long, 4 ins. sq., with nail at the exact point, set 18 ins. in the ground, with mound of stone, scribed N.E.E.C.-H-3653.
- 360.80 To Cor. No. 2, identical with S.E. Cor. of the location. At the intersection of line 2-3, Rosaline No. 10 lode, Sur. 2701 with line 6-1. Hamburg lode, Sur. 3491. being and N.77°04'E. 373.5 ft. from Cor. No. 6, S.77°-04'W. 112.3 ft. from Cor. No. 1, of said Hamburg lode and N.24°-56'W. 197.1 ft. from Cor. No. 2 of said Rosaline No 10 lode.
A standard 3 in. iron pipe. 3 ft. long, with iron cap divided in quadrants, and stamped 2-H-3653 in the quadrant facing the claim, set 22 ins, in concrete base.
No bearings available.
Thence S.55°-26'W.
- 436.40 Intersect lines 5-6 and 2-3, respectively, of Hamburg lode, Sur. 3491 and Bonita lode, Sur. 1638, S.01°-38'E. 164.05 ft. from Cors. 6. and 3.
- 806.00 Road, course northerly and southerly.
- 954.90 To Cor. No. 3, identical with S.W. Cor. of the location. A standard 3 in. iron pipe. 3 ft. long, with cap divided in quadrants, and stamped 3-H-3653 in the quadrant facing the claim, set 19 ins. in concrete base, whence an oak tree, 6 ins. in diameter, blazed and scribed cross B.T. 3653, bears S.46°-05'W. 25.05 ft.
No other bearings available.
Thence N.24°-56'W.
- 57.00 To S.W.E.C. monument of the location.
A pine post, 4 ft. long, 4 ins. sq., with nail at the exact point, set 24 ins. in the ground, with mound of stone, scribed S.W.E.C.-H-3653.
- 189.00 Road, course easterly and westerly.
- 360.80 To Cor. No. 4, identical with N.W. Cor. of the location. At the intersection of line 2-3, Bradley lode, this

Feet.

survey, with line 3-4, Bonita lode, Sur. 1638, being S. 77°-09'W. 589.15 ft. from Cor. No. 3 of said Bonita lode.

A redwood post, 4 ft. long, 4 ins. sq., with nail at the exact corner, set 18 ins. in the ground, with mound of stone, scribed 4-H-3653. whence

A cedar tree, 10 ins. in diameter, blazed and scribed cross B.T.-3653, bears S. 13°-53'E. 10.6 ft.

No other bearings available.

Thence N.55°-26'E.

Along line 3-2 of said Bradley lode.

954.90 To Cor. No. 1, the place of beginning.

GOODNUF FRACTION Lode.

Beginning at Cor. No. 1, identical with N. E. Cor. of the location and Cor. No. 1, Starr No. 2 lode, Sur. 2699.

On line 2-3, Pittsburg lode, Sur. 2699.

A redwood post, 4 ins. sq., with nail at the exact corner, showing 27 ins. out of the ground, with mound of stone, scribed 1-2699-S2, to which I add 1-G.Fr.-3653 for this claim, whence

The south quarter corner of section 31, T. 2 N., R. 15 E., G. & S.R.B. & M., bears N.03°-52'-30"E. 4137.6 ft.

An oak tree, 7 ins. in diameter, blazed and scribed cross B.T. 3653, bears N.01°-01'W. 65.55 ft.

No other bearings available.

Thence S.30°-15'E.

Along line 3-2 of said Pittsburg lode.

347.20 To Cor. No. 2, identical with S.E. Cor. of the location and Cor. No. 2 of said Pittsburg lode.

On line 3-4, Starr lode, Sur. 2494, N. 55°-25'E. 82.62 ft. from Cor. No. 3.

A redwood post, 4 ft. long, 4 ins. sq., with nail at the exact corner, set 24 ins. in the ground, with mound of stone,, scribed 2-2699-P, to which I add 2-G.Fr.-3653 on the side facing this claim, whence

A cedar tree, 9 ins. in diameter, blazed and scribed cross B.T.-3653, bears N. 32°-23'E. 49.1 ft.

Feet. No other bearings available.

Thence S.53°-37'W.

7.50 To S.E.E.C. monument of the location, from which the discovery cut bears N. 30°-15'W. 37.0 ft.
A monument of stone, 4 ft. base, 4 ft. high.

15.00 To Cor. No. 3, identical with S.W. Cor. of the location. On line 1-2, Goodenough lode, this survey.
A redwood post, 4 ft. long, 4 ins. sq., with nail at the exact corner, set 24 ins. in the ground. scribed 3-G.Fr.-5653.

No bearings available.

Thence N. 30°-15'W.

Along line 2-1 of said Goodenough lode.

0.46 Intersect line 3-4, Starr lode, Sur. 2494, N. 55°-25'E. 67.65 ft. from Cor. No. 3.

46.90 To N.E.E.C. monument of said Goodenough lode.

347.20 To Cor. No. 4, identical with N.W. Cor. of the location and Cor. No. 1 of said Goodenough lode.
On line 1-2, Starr No. 2 lode, Sur. 2699.
A redwood post, previously described. to which I add 4-G.Fr. on the side facing this claim.

Thence N.53°-37'E.

Along line 2-1 of said Starr No. 2 lode.

7.50 To N.W.E.C. monument of the location.
A monument of stone, 3.5 ft. base, 3.5 ft. high.

15.00 To Cor. No. 1, the place of beginning.

Mean magnetic variation at all corners 13°-45'E.

.....

Lode Lines.

As near as can be determined from present developments the veins of the several locations embraced in this survey extend as follows from their respective discovery points:

Fairview lode, N.59°-36'E. 997.9 ft. and S.59°-36'W. 500.0 ft.

Democrat lode, N.57°-11'E. 65.0 ft. and S.57°-11'W. 1432.4 ft.

15.

Feet. Goodenough lode, N.53°-37'E. 1260.0 ft. and S.53°-37'W.
 236.5 ft.
 Bradley lode, N.55°-26'E. 1437.0 ft. and S.55°-26'W.
 46.0 ft.
 Bessie lode, N.41°-20'E. 1313.6 ft. and S.41°-20'W.
 177.6 ft.
 Hart lode, N.55°-26'E. 19.0 ft. and S. 55°-26'W. 935.9
 ft.
 Goodnuf Fraction lode, N.30°-15'W. 310.2 ft. and S.
 30°-15'E. 37.0 ft.

oooooooooooooooooooo

AREAS.

| | Acres. |
|---|----------|
| Total area Fairview lode, | 19.452 ✓ |
| Area in conflict with Rosaline No. 7 lode, Sur. 2495., | 4.574 ✓ |
| Total area Democrat lode, | 20.678 ✓ |
| Area in conflict with: | |
| Innes lode, Sur. 1638, | 1.528 ✓ |
| Rosaline No. 7 lode, Sur. 2495, | 10.068 ✓ |
| Little Chief lode, Sur. 3250, | 0.469 ✓ |
| Total area Goodenough lode, | 20.484 ✓ |
| Area in conflict with Starr lode, Sur. 2494. | 0.652 ✓ |
| Total area Bradley lode, | 17.238 ✓ |
| Area in conflict with: | |
| Bonita lode, Sur. 1638, | 1.194 ✓ |
| Rosaline No. 7 lode, Sur. 2495, | 0.198 ✓ |
| Rosaline No. 9 lode, Sur. 2732 | 0.001 ✓ |
| Total area Bessie lode, | 19.042 ✓ |
| Area in conflict with May lode, Sur. 2699, | 0.873 ✓ |
| Total area Hart lode, | 7.797 ✓ |
| Area in conflict with: | |
| Bonita lode, Sur. 1638, | 3.205 ✓ |
| Hamburg lode, Sur. 3491, | 0.692 ✓ |
| Total area Goodnuf Fraction lode, | 0.119 ✓ |
| Area in conflict with Starr lode, sur. 2494. | 0.000 ✓ |

oooooooooooooooooooo

LOCATION.

This survey is located ~~approximately~~ in sections 1 and
 12, T. 1 N., R. 14 E., ^{Unsur.} and in sections 6 and 7, ^{Unsur.} T. 1 N.,
 R. 15 E., G. & S.R.B. & M., ~~unsurveyed~~, Globe Mining
 District, Gila County, Arizona, in the Crook National

Forest.

oooooooooooooooooooo

ADJOINING AND CONFLICTING CLAIMS.

The Butte, Sleeping Beauty, Lime Rock, Lime Rock No. 2, and Lime Rock No. 3 lodes, all unsurveyed, owned by Jacob Kleinfelder, on the north. The May, Pittsburg, and Starr No. 2 lodes, of Sur. 2699; the Starr lode, Sur. 2494; and the Rosaline No. 10 lode, Sur. 2701, all owned by Clara Kinney, on the east. The Hamburg lode, Sur. 3491, owned by Clara Kinney; the Bonita lode, of Sur. 1638, owned by the Inspiration Miami Copper Company, on the south. The Rosaline No. 7 lode, Sur. 2495 and the Rosaline No. 9 lode, Sur. 2732, owned by Clara Kinney; the Innes lode, of Sur. 1638, owned by Inspiration Miami Copper Company; and the Little Chief lode, of Sur. 3250, owned by the Warrior Copper Company, on the west.

oooooooooooooooooooo

DISCOVERY AND IMPROVEMENTS.

I certify that the value of the labor and improvements made upon, or for the benefit of, each of the locations embraced in this survey, by the claimant or its grantors, is not less than five hundred dollars (except for the Goodnuf Fraction lode, for which supplemental certificate covering work to be performed will be submitted) and that said improvements consist of:

COMMON IMPROVEMENTS.

Improvement No. 6, on the Fairview lode, a vertical diamond drill hole, $1\frac{1}{4}$ inches in diameter, 880 feet deep, value \$8000.00, the center of which bears N.89°-00'W. 100.5 ft. from a point on line 2-5 of said Fairview lode; 115.1 ft. from Cor. No. 3, and improvement No. 2 on the Bradley lode, a vertical diamond drill hole, $1\frac{1}{4}$ inches in diameter, 671.5 feet deep, value, \$7000.00, the center of which bears S.67°-31'E. 28.0 ft. from the S.W.E.C. of said Bradley lode, are two of a series of holes to be put down at intervals on the claims in the

~~in the survey~~ for the purpose of prospecting and determining the extent of and the values in the mineralized zone. The plan of prospecting and developing a group of claims by drill holes is quite generally carried out in this district, the Inspiration Consolidated Copper Company's mine and the Miami Copper Company's mine, both large properties operating in the near vicinity of this group, being successfully prospected by drill holes. The plan of developing the group by a system of drill holes being feasible, and advantageous, and the holes now down being so located that they not only develop the claims they are situated on, but also tend to develop the other claims in the group, their value is distributed equally to all the claims, except the Goodnuf Fraction. No portion of the value of the holes is credited to the Goodnuf Fraction lode on account of its having been located by the claimant subsequent to sinking the drill holes, and the value of the holes is, therefore, distributed equally between the other six claims of the survey, \$2500.00 being credited to each.

FAIRVIEW.

No. 1, the discovery shaft, 4 x 6 x 8 ft., the center of which is on the lode line 500.0 ft. from the S.W.E.C. Value, \$40.00.

No. 2, shaft, 4 x 6 x 65 feet. partially timbered, the N.E. Cor. of which bears S.04°-24'W. 75.9 ft. from a point on the lode line 504.3 ft. from the S.W.E.C. Value, \$1000.00.

No. 3, 46 ft. of cut and tunnel, 6 x 7 ft., the center of the toe of which bears S.23°-57'W. 304.6 ft. from the above described point, and which extends thence S.66°W. 38 ft.; thence N. 23°W. 8.0 ft. to face. Value \$400.00.

No. 4, 70 feet of cut and tunnel, 4 x 6 ft., the center of the toe of which bears S.10°-29'E. 188.5 ft. from a point on line 5-1, 91.7 ft. from Cor. No. 1, and which extends thence S.09°-50'E. 40.0 ft; thence S.36°W.

30.0 ft. to face. Value \$800.00

No. 5, 28 ft. of cut and tunnel, 4 x 6 ft., the center of the toe of which bears S.10°-10'W. 317.2 ft. from the above described point, and which extends thence S.11°-40' E. 20.0 ft.; thence S. 09°W. 8.0 ft. to face. Value \$200.00.

No. 6, diamond drill hole described under common improvements.

1/6th of the common improvement, which is credited to this claim. Value \$2500.00.

1/2 of the value of improvement No. 2 on the Bessie lode, which is credited to this claim, Value \$1350.00.

DEMOCRAT.

No. 1. the discovery, cut, 4 x 7 x 10 ft., the center of the face of which is on the lode line 65.0 ft. from the N.E.E.C., and which extends thence S.80°E to toe. Value \$45.00.

No. 2, 27 ft. of cut and tunnel, 4 x 6 ft., the center of the toe of which bears S.39°-05'W. 247.2 ft. from a point on line 5-1, 756.5 ft. from Cor. No. 5, and which extends thence N.80°W. to face. Value \$135.00.

1/6th of the common improvement which is credited to this claim, Value \$2500.00.

GOODENOUGH.

No. 1, the discovery, cut, 4 x 10 x 10^{lx}, the N.E. corner of which is on the lode line, 256.5 ft. from the S.W.E.C., and which extends thence S.44°W to toe. Value, \$45.00.

No. 2, 53 ft. of cut and tunnel, 4.5 x 6.5 ft., the center of the toe of which bears N.19°-04'W. 155.4 ft. from the S.W.E.C., and which extends thence N.36°W to face. Value, \$500.00.

1/6th of the common improvement which is credited to this claim. Value \$2500.00.

BREIDLEY.

No. 1, the discovery, 54 ft of cut and tunnel, 4 x 6 ft., which is intersected by the lode line, 46.0 ft. from

19.

the S.W.E.C., and which extends thence S.39°W. 31.0 ft. to toe, and N.50°E 23.0 ft. to face. Value \$350.00.

No. 2, diamond drill hole, described under common improvements.

1/6th of the common improvement which is credited to this claim, Value \$2500.00.

BESSIE.

No. 1, the discovery, 37.5 ft. of cut and tunnel, 3.5 x 5.5 ft., the center of the toe of which is on the lode line 177.6 ft. from the S.W.E.C., and which extends thence N.40°W. to face. Value \$200.00.

No. 2, 206 ft. of cut and tunnel, 4 x 6 ft., the center of the toe of which bears S.49°-41'E. 174.4 ft. from Cor. No. 6, and which extends thence S.30°-04'W. 150.0 ft. to face, And, from a point S.30°-04'W. 79.0 ft. from toe of cut a cross cut extends S.44°E 13.0 ft. to face. And, from a point, S.30°-04'W. 105.0 ft. from toe of cut, a cross cut extends N.52°W. 43.0 ft. to face. Value \$2700.00.

This improvement being partially on the Bessie lode and partially on the Fairview lode of the survey, the value thereof is distributed to these two claims, one-half being credited to each, Value credited to this claim, \$1350.00

1/6th of the common improvement which is credited to this claim, Value \$2500.00.

HART.

No. 1, the discovery, cut 4.5 x 10 x 13 ft., the S.E. corner of which is on the lode line 19.0 ft. from the N.E.E.C., and which extends thence S.76°W. to toe. Value \$45.00.

1/6th of the common improvement which is credited to this claim, Value \$2500.00.

GOODNUF FRACTION.

No. 1, the discovery, cut, 4 x 10 x 14 ft., the center of the face of which is on the lode line 37.0 ft. from the S.E.E.C., and which extends thence N.20°W. to toe. Value, \$40.00.

OTHER IMPROVEMENTS.

60.5 ft. of cut and tunnel, 4 x 6 ft., the center of the toe of which bears N. 70°-23'E. ^{204.2 ft.} from a point on the lode line of the Fairview lode, 504.3 ft. from the S.W.E.C., and which extends thence N. 31°E 17.0 ft.; thence N. 55°E 10.0 ft.; thence N. 64°E 23.5 ft.; thence S. 71°E 10.0 ft. to face.

A cut, 4.5 x 10 x 30 ft., the center of the toe of which bears S. 30°-51'E 69.2 ft. from the above described point, and which extends thence N. 41°W to face.

58 ft. of cut and tunnel, 4 x 6 ft., the center of the toe of which bears N. 79°-31'W. 436.4 ft. from a point on line 2-3 of the Democrat lode, 463.7 ft. from Cor. No. 2, and which extends thence S. 47°-30'W. 22.0 ft.; thence S. 15°W. 36 ft. to face.

56.5 ft. of cut and tunnel, 4.5 x 6.5 ft., the center of the toe of which bears N. 87°-50'W. 580.7 ft. from the above described point, and which extends thence S. 75°-30'W. 32.5 ft.; thence S. 48°W 24.0 ft to face.

A shaft, 4 x 6 x 5 ft. (caved) the S. E. corner of which bears S. 80°-48'W. 569.2 ft. from the above described point.

A churn drill hole, 10 ins, diameter, 655 feet deep, the center of which bears N. 23°-03'W. 337.8 ft. from a point on line 2-3, Democrat lode, 432.7 ft. from Cor. No. 2.

The above described improvements are not credited to the claims in the survey on account of either being on ground not held by the claims or not having been made by the claimant or its grantors.

oooooooooooooooooooo

INSTRUMENT AND DETERMINATION OF MERIDIAN.

This survey was made with a 6 $\frac{1}{2}$ inch Berger transit. The courses were deflected from the true meridian as determined by direct solar observation. The distances

were measured with a 660 foot steel tape.

oooooooooooooooooooo

REPORT.

The corner common to Township 1 and 2 North, Ranges 14 and 15 East, G. & S.R.B. & M., to which ties are given, is a quartzite stone, showing 10x 12 x 12 ins. out of the ground, chiseled 2N on the northeast face, 15 E. on the southeast face, 1 N. on the southwest face, 14E. on the northwest face and 6 grooves on each of the four corners, with mound of stone along side. The ties to this corner were computed from a traverse beginning at Cor. No. 5, Fairview lode and running thence S. 36°-40'W. 370.8 ft: thence N.20°-33'W. 2135.0 ft.: thence N.21°-07'E. 1661.5 ft.: thence N.17°-17'E. 1775.1 ft.: thence N.02°-08'W. 159.7 ft.

The south quarter corner of section 31, T. 2 N., R. 15E., G. & S.R.B. & M., to which ties are given, is a dacite boulder, showing 2 x 24 x 14 ins. out of the ground, chiseled cross and 1/4, with mound of stone alongside. The ties to this corner were computed from a traverse beginning at Cor. No. 1, Bessie lode, and running thence N.10°-35'E. 458.4 ft.: thence N.10°-30'E. 2403.8 ft.: thence N.03°-55'E. 361.1 ft.

Sur. 2699, May, Pittsburg and Starr No. 2 lodes:

Cors. 2, 3 and 4 of May lode; Cors. 2, 3 and 5 of Pittsburg lode; and Cors. 1, 2, 3 and 4 of Starr No. 2 lode are all 4 x 4 posts properly set and scribed. Cor.No. 4 of said Pittsburg lode was reset as reported herein. The disagreement between these notes and line 3-4 of said May lode, lines 2-3-4-5 of said Pittsburg lode and lines 1-2-3-4 of said Starr No. 2 lode, as approved, is due to errors in Sur. 2699. I find the bearing of line 2-3 of said May lode correct as approved.

Sur. 2494, Starr lode:

Cors. 2, 3 and 4 of said Starr lode are 4 x 4 posts properly set and scribed. The disagreement between these notes and the bearings of lines 2-3-4 of said Starr

lode, as approved, is due to errors in Sur. 2494.

Sur. 2701, Rosaline No. 10 lode:

Cors. 2 and 4 of said Rosaline No. 10 lode are 4 x 4 posts properly set and scribed. I removed Cor. No. 3 of said claim and reset it as reported herein. The disagreement between these notes and lines 2-3-4 of said Rosaline No 10 lode, as approved, is due to errors in Sur. 2701.

Sur. ~~2491~~³⁴⁹¹, Hamburg lode:

Cors. 1, 5 and 6 of said Hamburg lode are 4 x 4 posts properly set and scribed. The disagreement between these notes and lines 5-6-1, as approved, is due to errors in Sur. ~~2701~~³⁴⁹¹.

Sur. 1638, Bonita and Innes lodes:

Cors. 2, 3 and 4 of said Bonita lode and Cors. 2 and 3 of said Innes lode are 4 x 4 posts, properly set and scribed. I established the point for Cor. No 1 of said Innes lode by the bearing rock set for it. The disagreement between these notes and lines 2-3-4 of said Bonita lode and lines 1-2-3 of said Innes lode, as approved, is due to errors in Sur. 1638.

Sur. 2752, Rosaline No. 9 lode:

Cors. 1 and 5 of said Rosaline No. 9 lode are 4 x 4 posts properly set and scribed. The disagreement between these notes and line 5-1 of said Rosaline No. 9 lode, as approved, is nominal.

Sur. 2495, Rosaline No. 7 lode:

Cors. 1, 2, 3 and 4 of said Rosaline No. 7 lode are all 4 x 4 posts properly set and scribed. The disagreement between these notes and lines 3-4-1-2, as approved, is due to errors in Sur. 2495. In the execution of Sur. 2495, Mineral Surveyor H.C. Hopkins gives the bearings of line 1-2 Innes lode, Sur. 1638 as N.16°-58'W., while I determine this bearing to be N.16°-00'W. He also states the point of intersection of this line with line

3-4 of said Rosaline No. 7 lode, as being N.13°-58'E. 102.5 ft. from Cor No. 3 of said Rosaline No. 7 lode, and I determine this intersection point to be N.13°-33'E. 104.8'ft. from the same corner.

Sur. 3250, Little Chief lode:

Cors. 1, 2 and 3 of said Little Chief lode are 4 x 4 posts properly set and scribed.

There is a nominal disagreement between these notes and lines 1-2-3 of said Little Chief lode, as approved.

The disagreement between these notes and the location notices is due to errors in the latter.

Edwin P. Steward
United States Mineral Surveyor.

Globe, Arizona, December 1st, 1920.

FINAL OATHS FOR SURVEYS.

LIST OF NAMES.

A list of the names of the individuals employed by Edwin T. Stewart
 United States Mineral Surveyor, to assist in running, measuring, and marking the lines, corners, and
 boundaries described in the foregoing field notes of the survey of the mining claim of
The Louis d'Or Mining and Milling Company
 known as the FAIRVIEW, DEMOCRAT, GOODENOUGH, BREIDLEY, BESSIE, HART and
GOODNUF FRACTION lodes
 and showing the respective capacities in which they acted.

- Rudolph Wolf , Chainman.
- , Chainman.
- , Axman.
- , Flagman.

FINAL OATHS OF ASSISTANTS.

We,
~~and~~ I, Rudolph Wolf , do solemnly swear that we assisted
Edwin T. Stewart , United States Mineral Surveyor, in marking the corners and surveying
 the boundaries of the mining claim of The Louis d'Or Mining and Milling Company

 known as the FAIRVIEW, DEMOCRAT, GOODENOUGH, BREIDLEY, BESSIE, HART and
GOODNUF FRACTION lodes
 represented in the foregoing field notes as having been surveyed by said mineral surveyor and under his
 direction ; and that said survey has been in all respects, to the best of our knowledge and belief, faithfully
 and correctly executed, and the corner and boundary monuments established according to law and the instruc-
 tions furnished by the United States Surveyor-General for Arizona.

- Rudolph Wolf , Chainman.
- , Chainman.
- , Axman.
- , Flagman

Subscribed and sworn to by the above-named persons before me this 1st.
 day of December , 1920

*My Commission expires
 November 12 - 1924*

M. L. Harrison
 Notary Public

FINAL OATH OF U. S. MINERAL SURVEYOR.

I, Edwin T. Stewart, U. S. Mineral Surveyor, do solemnly swear that, in pursuance of instructions received from the United States Surveyor General for Arizona, dated July 19, 1920, I have, in strict conformity to the laws of the United States, the official regulations and instructions thereunder, and the instructions of said Surveyor General, faithfully and correctly executed the survey of the Mining Claim of The Louis d'Or Mining and Milling Company, known as the HART, GOODENOUGH, FAIRVIEW, DEMOCRAT, BREIDLEY, BESSIE and GOODNOUGH FRACTION Lodes, situate in Globe Mining District, Gila County, Arizona, in Section S 1 and 12 Township No. 1 N, Range No. 14 and 15 E, ^{E. Unsur.} _{5 E} and designated as Survey No. 3653, as represented in the foregoing field notes, which accurately show the boundaries of said mining claim as distinctly marked by monuments on the ground, and described in the attached copy of the location certificate, which was received by me from the Surveyor General with said instructions, and that all the corners of said survey have been established and perpetuated in strict accordance with the law, official regulations and instructions thereunder; and I do further solemnly swear that the foregoing are the true and original field notes of said survey and my report therein, and that the labor expended and improvements made upon said mining claim by claimant or its grantors are as therein fully stated, and that the character, extent, location, and itemized value thereof are specified therein with particularity and full detail, and that no portion of said labor or improvements so credited to this claim has been included in the estimate of expenditures upon any other claim.

Edwin T. Stewart
U. S. Mineral Surveyor.

Subscribed and sworn to by the said Edwin T. Stewart
U. S. Mineral Surveyor, before me, a notary public,
this 1st
day of December, 19 20.

M. L. Harrison
Notary Public, Gila
County, Arizona.

*My Commission expires
November 12 - 1924.*

U. S. SURVEYOR-GENERAL'S FINAL CERTIFICATE ON FIELD NOTES.

Department of the Interior,

OFFICE OF U. S. SURVEYOR-GENERAL,

Phoenix, Arizona,

February 1, 19 21

I, U. S. Surveyor-General for District of Arizona,

do hereby certify that the foregoing transcript of the Field Notes, return and approval of the survey of the mining claim of

The Louis d'Or Mining and Milling Company FAIRVIEW, DEMOCRAT, GOODENOUGH, BREIDLEY, BESSIE, HART, known as the and GOODNUF FRACTION Lodes situate in Globe

Mining District Gila County, Arizona, in Section 1 and 12 1 N. 14 E., Unsur., & 6 & 7 Unsur. Township No. 1 N., Range No. 15 E., and designated as Survey No. 3653

has been correctly copied from the originals on file in this office; that said Field Notes furnish such an accurate description of said mining claim as will, if incorporated into a patent, serve fully to identify the premises, and that such reference is made therein to natural objects or permanent monuments as will perpetuate and fix the locus thereof.

And I further certify that five hundred dollars' worth of labor has been expended or improvements made upon said mining claim by claimant or its grantors, and that said improvements consist of except the Goodnuf Fraction lode, by claimant or its grantors, and that said improvements consist of 2 shafts, 12 cuts, 8 tunnels, 2 crosscuts and 2 drill holes, total value \$21,500.

and that no portion of said labor or improvements has been included in the estimate of expenditures upon any other claim.

I further certify that the plat thereof, filed in the U. S. Land Office at Phoenix, Arizona, is correct and in conformity with the foregoing Field Notes.

Frank P. Trott

United States Surveyor-General for ARIZONA

SURVEYOR GENERAL'S CERTIFICATE OF APPROVAL OF FIELD NOTES AND SURVEY OF MINING CLAIM

DEPARTMENT OF THE INTERIOR OFFICE OF U. S. SURVEYOR GENERAL

Phoenix, Arizona,

February 1, 1921

I, U. S. Surveyor General for District of Arizona

do hereby certify that the foregoing and hereto attached Field Notes and Return of the Survey of the Mining Claim of

The Louis d'Or Mining and Milling Company

known as the FAIRVIEW, DEMOCRAT, GOODENOUGH, BREIDLEY, BESSIE, HART, and GOODNUF FRACTION Lodes

situate in Globe mining district,

Gila County, Arizona,

1 and 12 1 N. 14 E., Unsur., & in Section 6 & 7, Unsur., Township No. 1 N., Range No. 15 E.

designated as Survey No. 3653

executed by Edwin T. Stewart, U. S. Mineral

Surveyor, July 21 - 31, 1920, under my instructions dated

July 19, 1920, have been critically examined and the necessary cor-

rections and explanations made, and the said Field Notes and Return, and the Survey they describe,

are hereby approved. The certified copy of the location certificate filed by the applicant for survey is

on file in this office and a true copy of said certified copy of said location certificate is included and made

a part of the transcript of the field notes.

[Handwritten signature]

U. S. Surveyor General for Arizona

(4-691.)

Certificate of U. S. Surveyor General

AS TO


EXPENDITURES REPORTED AFTER RETURN OF SURVEY OF MINING CLAIM.

I, U. S. Surveyor General for..... District of Arizona,
do hereby certify that Five Hundred Dollars' worth of labor has been expended or
improvements made by claimant or... its grantors, upon ^{or for each of} the mining claims of
..... The Louis d'Or Mining and Milling Company

..... FAIRVIEW, DEMOCRAT, GOODENOUGH, BREIDLEY, BESSIE,
known as the HART, and GOODNUF FRACTION Lodes
situate in Globe mining district,
..... Gila County, Arizona

in Section s 1 & 12, Township No. 1 N., Range No. 14 E., Unsur., &
6 & 7 Unsur. 1 N. 15 E.
that said improvements consist of, in addition to those reported at
..... time of survey, 2 drill holes, value \$4305.

....., and that no portion of said labor or improvements has been
included in the estimate of expenditures upon any other claim. A copy of the report of
..... Edwin T. Stewart, U. S. Deputy Mineral Surveyor, dated
..... March 14, 1921, is hereto attached.



U. S. Surveyor General for..... Arizona

Office of U. S. Surveyor General,
..... Phoenix, Arizona,
..... March 16, 1921.

SUPPLEMENTAL REPORT OF IMPROVEMENTS MADE ON THE GOODENOUGH AND BRIDLEY LODES OF MINERAL SURVEY NO. 3653 FOR THE BENEFIT OF ALL THE CLAIMS OF SAID SURVEY AND SUBSEQUENT TO THE EXECUTION OF SURVEY.

I certify that the value of the labor and improvements made upon, or for the benefit of, each of the claims embraced in Mineral Survey No. 3653, by the claimant or its grantors, is not less than Five Hundred Dollars, and that said improvements, in addition to those reported in the returns of said Survey, dated December 1, 1920, consist of:

A vertical diamond drill hole, 1 1/4 inches in diameter, 335 feet deep, which bears S.78°-40'E. 96.1 feet from a point on line 4-1 of the Goodenough lode, 155.1 feet from Cor. No. 4.; value, \$2405.00.

A vertical diamond drill hole, 1 1/4 inches in diameter, 235 feet deep, which bears N.10°-17'W. 83.9 feet from a point on line 2-3 of the Briedley lode, 954.9 feet from Cor. No. 2; value, \$1900.00.

These are two holes in the system of holes planned by the claimant to prospect the claims in the survey, mentioned in my original returns of the survey, and, they having been drilled subsequent to the date of location of the Goodnuf Fraction lode of the survey, the value thereof is distributed equally to the seven claims, \$615.00 being credited to each.

Edwin P. Steward

United States Mineral Surveyor.

Subscribed and sworn to before me this 14th day of March, 1921. My commission expires November 12, 1924.

M. L. Harrison

Notary Public, Gila County, Ariz.

