

MINERAL SURVEY No. 3965

1

ARIZONA Land District.

FIELD NOTES

OF THE SURVEY OF THE MINING CLAIM OF

J. B. Jamison

KNOWN AS THE

BUCKEYE NOS. 1, 2, 3, 4, 5, 6, 7, 8, 9, and 10 lodes.

Globe Mining District,

Gila County, Arizona

Sections 22, 27, 28., Township 1 North., Range 14 East. G. & S.R. B. & M. (Unsurveyed).

Surveyed under instructions dated October 14th., 1924.

by Paul E. Fernald U. S. Mineral Surveyor.

Claim located (see notices attached), 19

Survey commenced October 16th., 19 24.

Survey completed November 15th., 19 24.

Address of claimant's Attorney:- W.E. SoRelle, Atty. Miami, Arizona.

DATES OF AMENDED LOCATIONS.

U. S. MINERAL SURVEY NO. 3965.

Feet.	<u>BUCKEYE NO. 1 Lode.</u>
	Beginning at Cor. No. 1, at top high rocky point.
	A 2" iron pipe 4 feet long, set 1½ foot in the ground in concrete and surrounded by monument of stones. 2" iron cap on pipe stamped U.S.M.S.No.3965, 1 BKY.1.
	Whence U.S.L.M.No. 2652 bears S 8° 3' 25"W, 652.94 feet.
	Cor. No.1, Hunt'sville Lode, Survey No. 2652, bears N 46° 6' 45"W, 175.80 feet.
	Thence N 78°41'E.
262.00	Crosses spur descending to north.
300.00	North end center - monument of stones 3 feet high with 4 foot base.
410.43	Intersects line 1-2, Hunt'sville Lode, Survey No. 2652, at point S 85° 32' E, 530.75 feet from its Cor. No. 1.
600.00	Cor. No. 2.
	A 2" iron pipe 4 feet long, set 1½ feet in the ground in concrete and surrounded by monument of stones. 2" iron cap on pipe stamped U.S.M.S.No. 3965, 2 BKY. 1.
	Whence:- Cor. No. 4, Santa Fe Lode, Survey No. 2652, bears S 10°15¼'E, 53.31 feet.
	Cor. No. 3, Santa Fe Lode, Survey No. 2652, bears S 80°44¼'E, 616.64 feet.
	Cor. No.2, Hunt'sville Lode, Survey No. 2652, bears S 81°41' 9"E, 768.42 feet.
	Thence S 10°22 3/4'E
53.34	Intersects line 1-2, Hunt'sville Lode, Survey No. 2652, at point S 85°32'E, 726.84 feet from its Cor. No. 1.
	Identically, intersects line 3-4, Santa Fe Lode, Survey No. 2652, at point S 85°32'E, 0.12 feet from its Cor.No.4.
838.00	Center of gully running E.- N.E.
1146.13	Intersects the north side line of Barney No. 27 Lode, unsurveyed, at point N 60°49½'E, 123.96 feet from its N.W.Corner.
1425.17	Intersects line 1-2, Santa Fe Lode, Survey No. 2652, at point S 85°32¼'E, 27.93 feet from its Cor. No.1. Cor. No.4 said Santa Fe lode brs. N.9° 15'W. 1364.96 ft. from Cor.No.1 thereof.
1500.00	Cor. No. 3.

A 2" pipe 4 feet long, set $1\frac{1}{2}$ feet in the ground in concrete and surrounded by monument of stones. 2" cap on pipe stamped U.S.M.S.No. 3965, 3-BKY.1.

Whence:- The N.W. Cor. of Barney No. 27 Lode, unsurveyed, bears N $30^{\circ}52\frac{1}{2}'W$, 335.15 feet.

The N.E. Cor. of Barney No. 27 Lode, unsurveyed, bears N $48^{\circ}9'E$, 1526.54 feet.

The S.E. Cor. of Barney No. 27 Lode, unsurveyed, bears N $70^{\circ}42\frac{3}{4}'E$, 1512.65 feet.

The S.W. Cor. of Barney No. 27 Lode, unsurveyed, bears S $26^{\circ}43\frac{3}{4}'E$, 261.52 feet.

Cor. No. 1, Santa Fe Lode, Survey No. 2652, bears N $28^{\circ}36\frac{1}{4}'W$, 86.31 feet.

Cor. No. 2, Santa Fe Lode, Survey No. 2652, bears N $87^{\circ}1\frac{1}{2}'E$, 558.68 feet.

This Corner is situated at point 603.66 on line 1-2, Barney No. 23 Lode, Survey No. 2880, whence its Cor. No. 2 bears N $78^{\circ}41'E$, 888.72 feet.

Thence S $78^{\circ}41'W$.

11.15 Intersects the West end line of Barney No. 27 Lode, unsurveyed, at point S $29^{\circ}3\frac{1}{2}'E$, 331.58 feet from its N.W. Corner.

42.00 Crosses small gully running South.

260.00 East edge of high ground.

300.00 South end center - monument of stones 3 feet high with 4 foot base.

600.00 Cor. No.4, at point 3.66 on line 1-2, Barney No 23 Lode, Survey No. 2880.

A 2" pipe 4 feet long, set $1\frac{1}{2}$ feet in the ground in concrete and surrounded by monument of stones. 2" Cap on pipe stamped U.S.M.S.No.3965. 4-BKY.1.

Whence:- a 9" Cedar with old blaze, scribed B.T. 2880, and true point marked by nail-head, bears N $50^{\circ}33'E$, 60.42 feet

a 7" Oak with old blaze, scribed B.T. 2880, and true point marked by nail head, bears S $21^{\circ}30'E$,

U.S. MINERAL SURVEY NO. 3965.

96.90 feet.

Thence N 10°22 3/4'E.

- 298.00 Crosses high point of ridge down from N.W. to S.E.
 654.00 Crosses small gulley running easterly.
 868.00 Crosses crest of spur running down easterly.
 1010.00 Crosses crest of spur running N.- N.E.
 1218.00 High point on ridge running north along line.
 1500.00 Cor. No.1, the point of beginning.

BUCKEYE NO. 2 Lode.

Beginning at Cor. No. 1, identical with Cor. No.1, Buckeye No.1 Lode, this survey, heretofore described. Cap on pipe monument additionally stamped "1-BKY.2" for this corner.

Whence:- U.S.L.M.No.2652 bears S 8° 3' 25"W, 652.94 feet.

Thence S 78°43'W.

- 300.00 North End Center - monument of stones 3 feet high with 4 foot base.
 310.00 Top crest running down northerly.
 600.00 Cor. No. 2.

A 2" iron pipe 4 feet long, set 1½ feet in the ground in concrete and surrounded by monument of stones. Cap on pipe stamped U.S.M.S.No.3965, 2-BKY.2.

Whence:- An 8" Oak, blazed and scribed "3965 X B.T!" bears N 5°37'E, 38.84 feet.

The S.¼ Cor. of Section 22, T.1 N, R.14 E, G.& S.R.B.& M. bears S 1°56 3/4'W, 310.40 feet.

Thence S 10°22 3/4'E.

- 328.00 Crosses spur running down from south.
 729.00 Crosses crest of main ridge running northeasterly.
 1500.00 Cor. No.3. being on line 4-1, Barney No.24 Lode, Survey No. 2880, N 78°43'E, 800.01 feet from its Cor. No.4.
 A 2" iron pipe, 4 feet long, set 1½ feet in the ground in concrete and surrounded by monument of stones. Cap on pipe stamped U.S.M.S.No.3965. 3-BKY.2. This corner is situated at the west side of small gulley running

from the north.
 Thence N 78°43'E.

136.00 Top spur running down from north.

290.00 Crosses small gulley from north.

300.00 South End Center - monument of stones 3 feet high with 4 foot base.

596.34 Cor. No.1, Barney No. 24 Lode, identical with Cor. No.1, Barney No. 23 Lode, both Survey No. 2880.

600.00 Cor. No. 4, identical with Cor. No. 4, Buckeye No.1 Lode, this survey, heretofore described.
 Cap on pipe monument additionally stamped "4-BKY.2" for this corner.
 Thence N 10°22 3/4'W.

298.00 Crosses high point of ridge down from N.W. to S.E.

654.00 Crosses small gulley running easterly.

868.00 Crosses crest of spur running down easterly.

1010.00 Crosses crest of spur running N.-N.E.

1218.00 High point on ridge running north along line.

1500.00 Cor. No.1, the point of beginning.

BUCKEYE NO. 3 Lode.
 Beginning at Cor. No.1, identical with Cor. No.2, Buckeye No. 2 Lode, this survey, heretofore described. Cap on pipe monument additionally stamped "1 BKY.3" for this corner.
 Whence:- U.S.L.M.No.2652 bears S 43°12' 5"E, 725.84 feet.
 1/4 Cor. between Secs. 22 & 27, T.14N., R.1 E. brs. S. 1°56 3/4' W. 310.40ft.
 Thence S 78°43'W

300.00 North End Center - monument of stones 3 feet high with 4 foot base.

317.00 Crest of spur running down N.- N.E.

600.00 Cor. No. 2.
 A 2" iron pipe 4 feet long, set 1 1/2 feet in the ground in concrete and surrounded by a monument of stones. Cap on pipe stamped U.S.M.S.No.3965, 2.BKY.3.
 Whence:- A 4x4 post 1 1/2 feet above ground in mound of

U.S. MINERAL SURVEY NO. 3965.

stones, marked "W.C.C.Ms", apparently an ^{unofficial} unidentified witness corner to the S.E. Cor. of Continental Millsite, Lot. No. 37 B, bears N 50° 4 3/4'E, 209.93 feet.
 Thence S 10°22 3/4'E
 318.00 Crosses spur running down N.- N.E.
 749.00 Main ridge running E.-N.E.
 1346.00 Crosses spur running down S.E.
 1500.00 Cor. No. 3.
 A 2" iron pipe 4 feet long, set 1 1/2 feet in the ground in concrete and surrounded by monument of stones. Cap on pipe stamped U.S.M.S.No.3965, 3.BKY.3. This corner is on line 4-1 of Barney No. 24 Lode, Survey No. 2880, N 78°43'E, 200.01 feet from its Cor. No.4.
 Thence N 78°43'E
 135.00 Crosses spur running down S.E.
 300.00 South End Center - monument of stones 3 feet high with 4 foot base.
 329.00 Crosses small gulley running southerly.
 487.00 Crosses spur running down S.-S.E.
 600.00 Cor. No.4, identical with Cor. No. 3, Buckeye No. 2 Lode, this survey, heretofore described.
 Cap on pipe additionally stamped "4.BKY.3" for this Cor.
 Thence N 10°22 3/4'W
 771.00 Crosses crest of main ridge running northeasterly.
 1172.00 Crosses spur running down from south.
 1500.00 Cor. No.1, the point of beginning.

BUCKEYE NO. 4 Lode.

Beginning at Cor. No.1, identical with Cor. No. 2, Buckeye No. 3 Lode, this survey, heretofore described.
 Cap on pipe additionally stamped "1.BKY.4" for this Cor.
 Whence:- U.S.L.M.No. 2652 bears S 69°13'33"E, 1160.75 ft.
 Thence S 78°46 1/4'W
 300.00 North End Center - a 4" oak post 4 feet above ground in monument of stones.
 600.00 Cor. No. 2.

U.S. MINERAL SURVEY NO. 3965

- A 2" iron pipe 4 feet long, set 1½ feet in the ground in concrete and surrounded by monument of stones. Cap on pipe stamped U.S.M.S.No.3965, 2.BKY.4.
Thence S 10°22 3/4'E.
- 604.00 Crosses main ridge running E.-N.E.
- 1431.00 Crosses spur running down southeasterly.
- 1500.00 Cor. No.3. on line 4-1, Barneya No.25 Lode, Survey No. 2880, S 78°48'W, 399.99 feet from Cor. No. 1.
A 2" iron pipe 4 feet long, set 1½ feet in the ground in concrete and surrounded by monument of stones, Cap on pipe stamped U.S.M.S.No.3965, 3.BKY.4.
Thence N 78°46¼'E
- 64.00 Crosses spur running down southeasterly.
- 212.00 Crosses small gulley running S.-S.E.
- 300.00 South End Center - monument of stones 3 feet high with 4 foot base.
- 436.00 Crest of spur running down southerly.
- 600.00 Cor. No. 4, identical with Cor. No.3, Buckeye No.3 Lode, this survey, heretofore described. Cap on pipe monument additionally stamped "4-BKY.4" for this corner.
Thence N 10°22 3/4'W.
- 154.00 Crosses spur running down S.E.
- 751.00 Crest main ridge running E.-N.E.
- 1182.00 Crosses spur running down N.-N.E.
- 1500.00 Cor. No.1, the point of beginning.

BUCKEYE NO. 5 Lode.

- Beginning at Cor. No.1, identical with Cor. No.2, Buckeye No. 4 Lode, this survey, heretofore described. Cap on pipe monument additionally stamped "1-BKY.5" for this corner.
- Whence:- U.S.L.M.No.2652 bears S 80° 0'33"E, 1699.57 ft.
Thence S 78°48'W
- 300.00 North End Center - monument of stones 3 feet high with 4 foot base.
- 348.00 Crosses crest of spur running down northerly.

U.S. MINERAL SURVEY NO. 3965.

- 545.00 East branch of small gulley running northerly.
 - 600.00 Cor. No. 2, at east side of west branch small gulley running northerly.
A 2" iron pipe 4 feet long, set 1½ feet in the ground in concrete and surrounded by monument of stones. Cap on pipe stamped U.S.M.S.No.3965. 2.BKY.5.
Whence:- a 10" oak, blazed and scribed 3965 X B.T., bears N 73°27'E, 20.12 feet.
Thence S 10°22 3/4'E.
 - 135.00 Crosses crest of small spur running down northerly.
 - 611.00 Top main ridge running E. and W.
 - 1206000 Crosses small gulley running to south.
 - 1500.00 Cor. No. 3, on line 4-1, Barney No. 25 Lode, Survey No. 2880, at point N 78°48'E, 500.17 feet from its Cor. No. 4.
A 2" iron pipe 4 feet long, set 1½ feet in the ground in concrete and surrounded by monument of stones. Cap on pipe stamped U.S.M.S.No.3965: 3.BKY.5.
Thence N 78°48'E.
 - 121.00 Crosses small spur running down S.W.
 - 300.00 South End Center - monument of stones 3 feet high with 4 foot base.
 - 600.00 Cor. No. 4, identical with Cor. No. 3, Buckeye No. 4 Lode, this survey, heretofore described. Cap on pipe monument additionally stamped for this corner "4.BKY.5"
This corner is on line 4-1, Barney No. 25 Lode, Survey No. 2880, N 78°48'E, 1100.17 feet from Cor. No. 4.
Thence N 10°22 3/4'W
 - 69.00 Crosses spur running down southeasterly.
 - 896.00 Crosses main ridge running E.- N.E.
 - 1500.00 Cor. No. 1, the point of beginning.
- BUCKEYE NO. 6 Lode.
Beginning at Cor. No. 1, identical with Cor. No. 2, buckeye No. 5 Lode, this survey, heretofore described. Cap on pipe monument additionally stamped "1.BKY.6" for this

corner.

Whence:- U.S.L.M.No.2652 bears S 85°29'33"E, 2269.38 ft.

Thence S 78°46¼'W

4300.00 North End Center - monument of stones 3 feet high with 4 foot base, on crest of spur running northerly.

600.00

Cor. No.2.

A 2" iron pipe 4 feet long, set 1½ feet in the ground in concrete and surrounded by monument of stones. Cap on pipe stamped U.S.M.S.No.3965. 2.BKY.6.

Whence:- the S.W.Cor. of Section 22, T 1 N, R 14 E, G.& S.R.B.& M., bears N 61°17½'W, 330.38 feet.

Thence S 10°22 3/4'E

471.00 Crosses crest of main ridge running E.& W.

924.00 Crosses crest of spur running down southerly.

1392.00 Crosses main gulch at bend from N.E. to S.E.

1500.00 Cor. No.3, on line 4-1, Barney No. 26 Lode, Survey No. 2880, at point S 78°37 3/4'W, 99.83 feet from its Cor.No.1
A 2" iron pipe, 4 feet long, set 1½ feet in the ground in concrete and surrounded by a monument of stones. Cap on pipe stamped U.S.M.S.No.3965. 3.BKY.6.

Whence:- Cor. No.2, Barney No.26 Lode, identical with

Cor. No.3, Barney No.25 Lode, both of Survey No.2880, bears S 20°13'45"E, 607.35 feet.

Thence N 78°46¼'E

99.83 Intersects line 1-2, Barney No.26 Lode, Survey No.2880, at point S 10°46¼'E, 0.25 feet from its Cor. No.1.

Identically, intersects line 3-4, Barney No.25 Lode, Survey No.2880, at point S 10°46¼'E, 0.25 feet from its Cor. No.4. This point is at center of main gulch running easterly.

245.00 Center main gulch running E.- N.E.

300.00 South End Center, at south edge main gulch, a monument of stones 3 feet high with 4 foot base.

317.00 Center main gulch running southeasterly.

414.00 Crest of spur running down from north.

U.S. MINERAL SURVEY NO. 3965.

- 456.00 Crosses small gulch running south.
- 600.00 Cor. No.4, identical with Cor. No.3, Buckeye No.5 Lode, this survey, heretofore described, being on line 4-1, Barney No.25 Lode, Survey No.2880, at point N 78°48'E, 500.17 feet from Cor. No.4. Cap on pipe monument additionally stamped "4.BKY.6" for this corner.
Thence N 10°22 3/4'W.
- 294.00 Crosses small gully running south.
- 389.00 Top main ridge running E. & W.
- 1355.00 Crosses crest of small spur running down northerly.
- 1500.00 Cor. No.1, the point of beginning.

BUCKEYE NO.7 Lode.

Beginning at Cor. No.1, identical with Cor. No.2, Buckeye No.6 Lode, this survey, heretofore described. Cap on pipe monument additionally stamped "1.BKY.7" for this corner.

Whence:- U.S.L.M.No.2652 bears S 88°45'51"E, 2851.57 ft.
Thence S 78°37 3/4'W

- 243.00 Crosses crest of spur running north.
- 300.00 North End Center - monument of stones 3 feet high with 4 foot base.
- 508.00 Crosses crest of spur running N.- N.W.
- 600.00 Cor. No.2.
A 2" iron pipe 4 feet long, set 1 1/2 feet in the ground in concrete and surrounded by monument of stones. Cap on pipe stamped U.S.M.S.No.3965. 2.BkY.7.
Thence S 10°22 3/4'E
- 468.00 Crosses main ridge running W.-S.W. to E.-N.E.
- 544.00 Crosses spur from main ridge running down S.-S.E.
- 1288.00 Crosses main gulch running easterly.
- 1500.00 Cor. No.3, on line 4-1; Barney No.26 Lode, Survey No. 2880, at point N 78°37 3/4'E, 739.97 feet from its Cor. No.4. A 2" iron pipe 4 feet long, set 1 1/2 feet in the ground in concrete and surrounded by monument of stones.

Cap on pipe stamped U.S.M.S.No.3965. 3.BKY.7.

Thence N 78°37 3/4'E

- 74.00 Crosses small spur running N.-N.E.
 300.00 South End Center - monument of stones 3 feet high with
 4 foot base.
 410.00 Crosses tip of spur running down from south.
 600.00 Cor. No.4, on line 4-1, Barney No.26 Lode, Survey No.
 2880, at point N 78°37 3/4'E, 1339.97 feet from Cor. No.4.
 Identical with Cor. No.3, Buckeye No.6 Lode, this survey,
 heretofore described. Cap on pipe monument additionally
 stamped "4.BKY.7" for this corner.

Thence N 10°22 3/4'W.

- 108.00 Crosses main gulch at bend from N.E. to S.E.
 576.00 Crosses crest of spur running down southerly.
 1029.00 Crosses crest of main ridge running E.& W.
 1500.00 Cor. No.1, the point of beginning.

BUCKEYE NO.8 Lode.

Beginning at Cor. No.1, identical with Cor. No.2, Buckeye
 No.7 Lode, this survey, heretofore described. Cap on
 pipe monument additionally stamped "1.BKY.8" for this
 corner.

Whence:- U.S.L.M.No.2652 bears N 89° 3'15"E, 3439.57 feet.

Thence S 78°37 3/4'W.

- 189.00 Crosses small gulley running north.
 300.00 North End Center - monument of stones 3 feet high with
 4 foot base.
 381.00 Crosses crest of spur running down northerly.
 600.00 Cor. No.2.
 A 2" iron pipe 4 feet long, set 1½ feet in the ground in
 concrete and surrounded by monument of stones. Cap on
 pipe stamped U.S.M.S.No.3965. 2.BKY.8.

Thence S 10°22 3/4'E

- 596.00 Crosses main ridge running W.-S.W. to E.-N.E.
 1174.00 Crosses main gulch running easterly.
 1500.00 Cor. No.3, on line 4-1, Barney No.26 Lode, Survey No.2880,

U.S. MINERAL SURVEY NO. 3965.

at point N 78°37 3/4'E, 139.97 feet from Cor. No. 4.

A 2" iron pipe 4 feet long, set 1 1/2 feet in the ground in concrete and surrounded by monument of stones. Cap on

pipe stamped U.S.M.S. No. 3965, 3.BKY.8.

Thence N 78°37 3/4'E

300.00 South End Center - monument of stones 3 feet high with 4 foot base.

445.00 Crosses tip of spur running down from south.

600.00 Cor. No. 4, on line 4-1 Barney No. 26 Lode, Survey No. 2880, at point N 78°37 3/4'E, 139.97 feet from Cor. No. 4.

Identical with Cor. No. 3, Buckeye No. 7 Lode, this survey, heretofore described. Cap on pipe monument additionally stamped "4.BKY.8" for this corner.

Thence N 10°22 3/4'W

212.00 Crosses main gulch running easterly.

956.00 Crosses spur from main ridge running down S.-S.E.

1032.00 Crosses main ridge running W.-S.W. to E.-N.E.

1500.00 Cor. No. 1, the point of beginning.

BUCKEYE, NO. 9 Lode.

Beginning at Cor. No. 1, identical with Cor. No. 2, Buckeye No. 8 Lode, this survey, heretofore described. Cap on

pipe monument additionally stamped "1.BKY.9" for this corner.

Whence:- U.S.L.M. No. 2652 bears N 87°30'38"E, 4031.14 ft.

Thence S 78°37 3/4'W

223.00 Crosses small spur running down northerly.

300.00 North End Center - a 4x4 post 4 feet above ground in monument of stones.

600.00 Cor. No. 2.

A 2" iron pipe 4 feet long, set 1 1/2 feet in the ground in concrete and surrounded by monument of stones. Cap on

pipe stamped U.S.M.S. No. 3965. 2.BKY.9.

Thence S 10°22 3/4'E.

346.00 Crest of small spur running down N 15°W.

- 690.00 Crosses main ridge running E.-N.E.
- 1307.00 Crosses main gulch at bend from S.E. to N.E.
- 1421.83 Intersects the east side line of Arizona No.8 Lode, unsurveyed, at point N $16^{\circ}27'28''$ W, .682.67 feet from the S.E. Corner.
- 1500.00 Cor. No.3.
A 2" iron pipe 4 feet long, set $1\frac{1}{2}$ feet in the ground in concrete and surrounded by monument of stones. Cap on pipe stamped U.S.M.S.No.3965. 3.BKY.9.
Whence:- the N.E.Cor. of Arizona No.8 Lode, unsurveyed, bears N $15^{\circ}56'46''$ W, 889.81 feet.
the S.E. Cor. of Arizona No.8 Lode, unsurveyed, bears S $17^{\circ}14\frac{1}{2}'$ E, 605.00 feet.
Thence N $78^{\circ}37\frac{3}{4}'$ E
- 8.31 Intersects the east sideline of Arizona No.8 Lode, unsurveyed, at point N $16^{\circ}27'28''$ W, 604.20 feet from the S.E. Corner.
- 300.00 South End Center -monument of stones 3 feet high with 4 foot base.
- 460.03 Cor. No.4, Barney No.26 Lode, Survey No.2880.
- 600.00 Cor. No.4 on line 4-1, Barney No.26 Lode, Survey No. 2880, at point 139.97, N $78^{\circ}37\frac{3}{4}'$ E, from Cor. No.4.
Identical with Cor. No.3, Buckeye No.8 Lode, this survey, heretofore described. Cap on pipe monument additionally stamped "4.BKY.9" for this corner.
Thence N $10^{\circ}22\frac{3}{4}'$ W
- 326.00 Crosses main gulch running easterly.
- 904.00 Crosses main ridge running W.-S.W. to E.-N.E.
- 1500.00 Cor. No.1, the point of beginning.
- BUCKEYE NO.10 Lode.
Beginning at Cor. No.1, identical with Cor. No.2, Buckeye No.9 Lode, this survey, heretofore described. Cap on pipe monument additionally stamped "1.BKY.10" for this corner.
Whence:- U.S.L.M.No.2652 bears N $86^{\circ}21'45''$ E, 4624.88 feet.

U.S. MINERAL SURVEY NO. 3965.

Thence S 79°24 3/4'W

300.00 North End Center - 4x4 post 4 feet above ground in monument of stones.

565.00 Crosses Miami road

600.00 Cor. No. 2, in main north gulch.

A 2" iron pipe 4 feet long, set 1 1/2 feet in the ground in concrete and surrounded by monument of stones. Cap on pipe stamped U.S.M.S.NO.3965. 2.Bky.10.

Thence S 10°22 3/4'E

40.00 Crosses Miami road.

617.72 Intersects the north end line of Arizona No.8 Lode, unsurveyed, at point S 79° 0' 5"W, 514.00 feet from its N.E. corner.

830.00 Crosses main ridge from W. to N.E.

1312.00 Crosses main south gulch at bend from west to northeast.

1428.61 Intersects the west side line of Arizona No.8 Lode, unsurveyed, at point N 16°26'30"W, 681.10 feet from its S.W. corner. Identically, intersects the east side line of Arizona No.7 Lode, unsurveyed, at point N 16°26'30"W, 681.10th from its S.E.Cor.

1500.00 Cor. No. 3.

A 2" iron pipe 4 feet long, set 1 1/2 feet in the ground in concrete and surrounded by monument of stones. Cap on pipe stamped U.S.M.S.NO.3965. 3.BKY.10.

Whence:- an 18" Cedar Stump, scribed 3965 X B.T. bears S 20° 2'E, 15.12 feet.

the N.E.Cor. of Arizona No.8 Lode, unsurveyed, bears N 19°41'15"E, 1025.87 feet:

the N.W.Cor. of Arizona No.8 Lode, unsurveyed, identical with the N.E.Cor. of Arizona No.7 Lode, unsurveyed, bears N 15°57'15"W, 885.53 feet.

the N.End Center of Arizona No.7 Lode, unsurveyed, bears N 33°55'15"W, 956.38 feet.

the S.W.Cor. of Arizona No.8 Lode, unsurveyed, identical with the S.E.Cor. of Arizona No.7 Lode, unsurveyed.

veyed, bears S 17° 9'E, 610.15 feet.

Thence N 79° 24 3/4'E

- 7.58 Intersects the east side line of Arizona No.7 Lode, unsurveyed, at point N 16° 26' 30"W, 609.33 feet from the S.E. corner. Identically, intersects the west side line of Arizona No.8 Lode, unsurveyed, at point N 16° 26' 30"W, 609.33 feet from the S.W. Corner.
- 300.00 South End Center - monument of stones 3 feet high with 4 foot base.
- 600.00 Cor. No.4, identical with Cor. No.3, Buckeye No.9 Lode, this survey, heretofore described. Cap on pipe monument additionally stamped "4 BKY.10" for this corner. Whence:- the S.E. Cor. of Arizona No.8 Lode, unsurveyed, bears S 17° 14 1/2'E, 605.00 feet.
the N.E. Cor. of Arizona No.8 Lode, unsurveyed, bears N 15° 56' 46"W, 889.81 feet.
- Thence N 10° 22 3/4'W
- 78.17 Intersects the east side line of Arizona No.8 Lode, unsurveyed, at point S 16° 27' 28"E, 812.05 feet from the N.E. corner.
- 193.00 Crosses main gulch at bend from S.E. to N.E.
- 810.00 Crosses main ridge running E.-N.E.
- 1154.00 Crest of small spur running down N 15°W.
- 1500.00 Cor. No.1, the point of beginning.

Magnetic Variation at all corners of this survey - 13° 50'E.

No suitable natural bearing objects available from corners of this survey, except where specifically noted herein.

The survey of each lode of this location is identical with the respective lode as staked upon the ground, and all survey corners are identical in position with the respective location monuments.

LODE LINES:- As near as can be determined from the present state of developement, the veins of the ten locations embraced in this survey, extend as follows from the respective discovery points:-

U.S. MINERAL SURVEYOR NO. 3965.

Buckeye No.1, N 10°22 3/4'W - 750.00 feet, and S 10°22 3/4'E
750.00 feet.

Buckeye No.2, N 10°22 3/4'W - 750.00 feet, and S 10°22 3/4'E
750.00 feet.

Buckeye No.3, N 10°22 3/4'W - 750.00 feet, and S 10°22 3/4'E
750.00 feet.

Buckeye No.4, N 10°22 3/4'W - 750.00 feet, and S 10°22 3/4'E
750.00 feet.

Buckeye No.5, N 10°22 3/4'W - 750.00 feet, and S 10°22 3/4'E
750.00 feet.

Buckeye No.6, N 10°22 3/4'W - 750.00 feet, and S 10°22 3/4'E
750.00 feet.

Buckeye No.7, N 10°22 3/4'W - 750.00 feet, and S 10°22 3/4'E
750.00 feet.

Buckeye No.8, N 10°22 3/4'W - 724.00 feet, and S 10°22 3/4'E
776.00 feet.

Buckeye No.9, N 10°22 3/4'W - 750.00 feet, and S 10°22 3/4'E
750.00 feet.

Buckeye No.10, N 10°22 3/4'W - 500.00 feet, and S 10°22 3/4'E
1000.00 feet.

LOCATION:- This survey is located in the S. 1/2 of the S. 1/2 of Section
22, the N. 1/2 of Section 27 and the N.E. 1/4 of Section 28,
T 1 N, R 14 E, G. & S.R.B. & M., in the Globe Mining District,
Gila County, Arizona, being partly within the Crook Natl.
Forest. Of the above sections, only the W. 1/2 of
Section 22 has been surveyed, which survey has not yet
been approved.

ADJOINING AND CONFLICTING CLAIMS:-
The claims adjoining or conflicting with the claims of

this survey are as follows:- On the North, Hunt^sville Lode, Survey No.2652; on the East, the Santa Fe Lode, Survey No. 2652, and Barney No. 27 Lode, unsurveyed, (a part of which conflict is also covered by conflict with Santa Fe Lode, Survey No.2652); on the South Barney No.23, Barney No.24, Barney No.25 and Barney No.26 Lodes, all of Survey No. 2880, and the Arizona No.8 Lode, unsurveyed; and on the West, Arizona No.8 and Arizona No.7 Lodes, unsurveyed.

AREAS:-	Buckeye No.1 Lode, total area	20.658 acres.	
	Conflict with Hunt ^s ville Lode, Survey No.2652.	0.116	"
	Conflict with Santa Fe Lode, Survey No.2652.	0.427	"
	Conflict with Barney No.27 Lode, unsurveyed.	0.517	"
	Conflict with Barney No.27 Lode, unsurveyed, exclusive of its conflict with Santa Fe Lode, Survey No.2652.	0.365	"
	Buckeye No.2 Lode, total area	20.659	"
	Buckeye No.3 Lode, " "	20.659	"
	Buckeye No.4 Lode, " "	20.659	"
	Buckeye No.5 Lode, " "	20.659	"
	Buckeye No.6 Lode, " "	20.659	"
	Conflict with Barney No.25 Lode, Survey No.2880.	0.001	"
	Conflict with Barney No.26 Lode, Survey No.2880.	0.000+	"
	Buckeye No.7 Lode, total area	20.658	"
	Buckeye No.8 Lode, " "	20.658	"
	Buckeye No.9 Lode, " "	20.658	"
	Conflict with Arizona No.8 Lode, unsurveyed.	0.007	"

U.S. MINERAL SURVEY NO. 3965.

Buckeye No.10 Lode, total area 20.661 acres.

Conflict with Arizona No.8 Lode, unsurveyed. 11.378 "

Conflict with Arizona No.7 Lode, unsurveyed. 0.006 "

EXPENDITURE OF FIVE HUNDRED DOLLARS:-

I certify that the value of labor and improvements made upon, or for the benefit of, each of the locations embraced in said mining claim, by the claimants or its grantors, is not less than Five Hundred Dollars, and that said improvements consist of:-

Buckeye No.1 Lode.

No.1, Discovery shaft 4x6x8 feet deep, center on center line 750. feet from the north end center.

Value \$40.00

No.2. Cut 4x19 x 10 foot face, running in N 70°W, the center of mouth of which bears N 11°58'E, 707.3 feet from Cor. No.4. Cut partly caved

Value \$75.00

No.3. Cut in N 67°W, 4x13 to 10 foot face, thence tunnel 4x6½ - 46 feet long. Center of mouth of cut bears N 5°22'E, 696.92 feet from Cor. No.4.

Value \$550.00

A ¼ interest in improvement No.3, Buckeye No.4 Lode, this survey, hereinafter described.

\$678.25

Buckeye No.2 Lode.

No.1. Discovery Shaft, 4x6-8 feet deep, on center line 750. feet from the north end center.

value \$40.00

No.2. Cut in N 73°E, 4x10 to 8 foot face, partly filled, the center of mouth of which bears N 6°54'E, 647. feet from Cor.No.3. Value \$33.00

A ¼ interest in Improvement No.3, Buckeye No.4 Lode, this survey, hereinafter described.

\$678.25

Buckeye No.3 Lode.

No.1.Discovery Cut in S 27°W, 4x12 to 10 feet face, the center of which is on center line 750. feet from the north end center. Value \$50.00

No.2. Cut in S 15°E, 4x12 to 8 foot face, partly filled, the center of mouth of which bears S 1°11'E, 796. feet from Cor. No.1. Value \$40.00

A 1/4 interest in improvement No.3, Buckeye No.4 Lode, this survey, hereinafter described. \$678.25

Buckeye No.4 Lode.

No.1.Discovery Shaft, 4x6 - 8 feet deep, the center of which is on center line 750 feet from the north end center. Value \$40.00

No.2. Cut in N 78°E, 4x11 to 8 foot face, partly filled, the center of mouth of which bears N 14°59'W, 689. feet from the south end center. Value \$35.00

No.3.Cut and tunnel, the center of mouth of cut bearing N 22° 4'W, 440.2 feet from the south end center. Cut runs in N 54°E, 5 feet wide at mouth, 9 feet wide at face, 21 feet long to 14 foot face. Thence 4x7 foot tunnel runs N 75°E - 91. feet, thence N 70°E - 27 feet, thence N 82°E - 21 feet, thence N 84 1/2°E - 24 feet to breast. Value of cut and 163. feet of tunnel \$2713.00

This tunnel, starting from a low point on the Buckeye No. 4 Lode, and driven in the general direction of the

Buckeye Nos.3, 2 and 1 Lodes, this survey, constitutes the main general working for those four lodes, as by continuing same in level and direction it will open up and develop at depth such lodes. It therefore

constitutes a common improvement of equal benefit to said four lodes, and an equal 1/4 interest in its value is

properly accredited herein to Buckeye No.1, No.2, No.3 and No.4 Lodes. No interest in this improvement is

accredited to Buckeye Nos. 5,6,7,8,9 or 10 Lodes, as

U.S. MINERAL SURVEY NO. 3965.

the direction of tunnel is opposite from same, and they are generally developed by tunnel improvement No. 4, Buckeye No. 4 Lode, hereinafter described.

1/4 interest in this improvement assigned to this lode. \$678.25

No. 4. Cut and tunnel, the center of mouth of cut bearing N 28° 7' W, 511.7 feet from the south end center. Cut runs in N 79° W, 5 feet wide, 15 feet long to 11 foot face. Thence 4x6 1/2 foot tunnel runs N 67° W - 82. feet, thence N 78° W - 20 feet, whence a crosscut runs N 12° E - 14 feet; thence N 87° W - 54 feet, thence west - 69 feet to breast. Value of cut and 239. feet of tunnel and crosscut -

\$3671.01 . This tunnel, starting from a low point on the Buckeye No. 4 Lode, and driven in the general direction of the Buckeye Nos. 5, 6, 7, 8, 9 and 10 Lodes, this survey, constitutes the main general working for those Lodes, as by continuing same in level and direction, it will open up and develop all of them at depth. It therefore constitutes a common improvement of equal benefit to the Buckeye Nos. 4, 5, 6, 7, 8, 9 and 10 Lodes of this survey, and an equal 1/7th. interest in its value is properly accredited herein to each of those lodes.

No interest in this improvement is accredited to Buckeye Nos. 3, 2 or 1 Lodes, as the direction of tunnel is opposite from same, and they are generally developed by tunnel improvement No. 3, this lode, heretofore described. 1/7th. interest in this improvement accredited to this lode. \$ 524.43

Buckeye No. 5 Lode.

No. 1. Discovery Cut in West, 4x12 to 10 foot face, the center of mouth of which is on center line 750. feet from the north end center. Value \$50.00

No. 2. Shaft 4 1/2 x 6 - 8 feet deep, partly filled, the center of which bears N 9° 45' E, 736.00 feet from Cor. No. 3. Value \$45.00

A 1/7th. interest in improvement No. 4, Buckeye No. 4 Lode,

this survey, heretofore described.

Value \$524.43

Buckeye No.6 Lode.

No.1. Discovery shaft 4x6 - 8 feet deep, the center of which is on center line 750. feet from the north end center.

Value \$40.00

No.2. Cut in northerly, 4x12 to 8 foot face, partly filled, the center of mouth of which bears N 3°22'E, 779.7 feet from Cor. No.3.

Value \$40.00

A 1/7th. interest in improvement No.4, Buckeye No.4 Lode, this survey, heretofore described.

Value \$524.43

Buckeye No.7 Lode.

No.1. Discovery Cut in N.W., 4x11 to 10 foot face, the center of which is on center line 750 feet from the north end center.

Value \$45.00

No.2. Cut in N 17°30'W, 4x10x8 feet, partly filled, the center of mouth of which bears N 2°51'E, 1001. feet from Cor. No.3.

Value \$33.00

A 1/7th. interest in improvement No.4, Buckeye No.4 Lode, this survey, heretofore described.

Value \$524.43

Buckeye No.8 Lode.

No.1. Discovery Cut in N 50°W, 4x14 to 10 foot face, the center of mouth of which is on center line 724. feet from the north end center.

Value \$58.00

A 1/7th. interest in improvement No.4, Buckeye No.4 Lode, this survey, heretofore described.

Value \$524.43

Buckeye No.9 Lode.

No.1. Discovery shaft, 4x6 - 8 feet deep, center of which is on center line 750. feet from the north end center.

Value \$40.00

No.2. Cut in north, 4x10 to 7 foot face, partly filled, the center of face of which bears N 30° 6'W, 714. feet from Cor. No.4.

Value \$29.00

U.S. MINERAL SURVEY NO. 3965.

A 1/7th. interest in improvement No.4, Buckeye No.4 Lode, this survey, heretofore described.

Value \$524.43

Buckeye No.10 Lode. No.1. Discovery Cut in S 55°E, 4x12 - 10 foot face, the center of mouth of which is on center line 500. feet from the north end center.

Value \$50.00

No.2. Cut in south, 4x9 to 7 foot face, caved, the center of mouth of which bears S 32°53'E, 639. feet from Cor.

No.2. Value \$26.50

A 1/7th. interest in improvement No.4, Buckeye No.4 Lode, this survey, heretofore described.

Value \$524.43

OTHER IMPROVEMENTS:-

Buckeye No.4 Lode. A frame and iron house, 12x16 feet, the N.E. Corner of which bears N. 41°16'W, 257.9 feet from the south end center.

INSTRUMENT:-

This survey was made with Dietzgen Transit No. 7256. Courses were deflected from the true meridian as determined by direct solar observations. Distances were measured with Chicago 50 and 350 foot steel tapes.

REPORT:-

The lines of this survey were run direct upon the ground. For all corners of this survey, pipe monuments were painted with red lead and caps with white enamel. Caps were then stamped with corner description and coated with spar varnish.

U.S.L.M.No.2652, Globe Mining District, Gila County, Arizona, is a 6x8" post 6 feet above ground at north side of a high flat hilltop. Post is surrounded by a 3 foot monument of stones and scribed on E. face "U.S.L.M.2652"

The S.W.Cor. and S. 1/4 Cor. of Section 22, T 1-N., R.14 E., G. & S.R.B. & M. are standard G.L.O. Corners - pipe with brass caps, which in addition to corner designation, bear year mark 1923. The S.W. Corner has a 4" Juniper B.T.

to the S.- S.W., and the S. $\frac{1}{4}$ Cor. has Oak bearing trees to west and south.

Survey No. 2652. Cor. No. 1 Huntsville Lode, is a 3" iron pipe with cap, painted white, extending $1\frac{1}{2}$ feet above the ground and set in a 1 foot square concrete base. Cap is stamped "1 Huntsville, 2652". From this monument, a 4x4 wooden post, 4 feet above ground in monument of stones, scribed "W.C. 1 - 2652 H" bears S $85^{\circ}32'E$, 51.36 feet. This W.C. is on the east side of a high boulder and is not visible from its true corner.

Cor. No. 2, Huntsville Lode - monument same as Cor. No. 1. Cap stamped 2 - 2652 Huntsville.
4 - 2652 Lucky Bill.

Santa Fe Lode, All corner monuments similar to Cor. No. 1 Huntsville Lode. Caps stamped with name, survey and corner numbers.

Barney No. 27 Lode, unsurveyed, Inspiration Consol. Copper Company, claimant. All reported corners are 4x4 posts, 4 feet above ground in monuments of stone. Posts marked with claim initial and number, and corner designation.

Survey No. 2880. All reported corners except Cor. No. 3, Barney No. 25, ident. Cor. No. 2, Barney No. 26 Lode, are 3" iron pipes with caps, painted white, extending $1\frac{1}{2}$ feet above ground and set in 1 foot square concrete base.

Caps are stamped with Lode name, survey and corner number.

From Cor. No. 1, Barney No. 26 Lode, a 4x4 post, 2 feet above ground, bears S $10^{\circ}46\frac{1}{4}'E$, 35.4 feet. Post is scribed respectively on 4 sides "2880", "True Cor. 35.4 ft.", "1 x B 26", and "4 x B 25 x WC".

Cor. No. 2, Barney No. 26 Lode, identical with Cor. No. 3, Barney No. 25 Lode, is a 4x4 post, 2 feet above ground in monument of stones, scribed on four sides respectively "2 - B 26", "3 - B 25", "4 - B 10", and "2880 1 - B 7".

Arizona Nos. 7 and 8 Lodes, unsurveyed, Dan. Williamson, Globe, Arizona, claimant. All corners are 4x4 posts 4 feet above ground in monuments of stones.

U.S. MINERAL SURVEY NO. 3965.

Continental Millsite, Lot No. 37 B. As per official notes of this survey, all corners were marked by three foot monuments of stones. After diligent search, I was unable to locate any such corners nor bearing trees called from the S.E. and S.W. Corners. The 4x4 post monument marked "W,C,C,Ms" as described herein with tie from Cor. No. 2, Buckeye No. 3 Lode, this survey, bears N 0°15'W, 22.93 feet from theoretical position of the S.E. Cor. of Continental Millsite, as determined by traverse W.C. to Cor. No. 2, Buckeye No. 3 Lode; thence to Cor. No. 1, Buckeye No. 2 Lode; thence to Cor. No. 1, Huntsville Lode, Survey No. 2652; thence by tie given with that survey (S 74°36'W - 922.1 feet) to S.E. Cor. Continental Millsite. I therefore conclude that such witness corner was set on the East sideline of Continental Millsite, 23. feet from its true S.E. Corner, to mark position of same when monument was destroyed during subsequent road construction.

The difference between the actual position of discovery work on Buckeye No. 3 Lode, this survey, and as described in location notice thereof, is due to error in said notice.

Valuation of improvements on lodes embraced in this survey is made on a basis of \$5.00 per 24 cubic feet for shallow surface workings, and \$10.00 per 24 cubic feet for underground work, except in case of tunnels Nos. 3 and 4, Buckeye No. 4 Lode. For these improvements, claimant has made affidavit to effect that work cost \$20.00 per linear foot, and I have herein valued same at \$15.00 per linear foot.

Respectfully submitted

Paul E. Fernald.
U.S. Mineral Surveyor.

Tucson, Arizona, February 7th. 1925.

FINAL OATHS FOR SURVEYS.

LIST OF NAMES.

A list of the names of the individuals employed by Paul E. Fernald

United States Mineral Surveyor, to assist in running, measuring, and marking the lines, corners, and boundaries described in the foregoing field notes of the survey of the mining claim of _____

J.B. Jamison

known as the BUCKEYE NOS. 1, 2, 3, 4, 5, 6, 7, 8, 9, and 10 lodes

and showing the respective capacities in which they acted.

J.D. Houston _____, *Chainman.*

_____, *Chainman.*

George Talkalia _____, *Asman.*

_____, *Flagman.*

FINAL OATHS OF ASSISTANTS.

We, J.D. Houston

and George Talkalia, do solemnly swear that we assisted Paul E.

Fernald, United States Mineral Surveyor, in marking the corners and surveying

the boundaries of the mining claim of J.B. Jamison

known as the BUCKEYE NOS. 1, 2, 3, 4, 5, 6, 7, 8, 9, and 10 lodes

represented in the foregoing field notes as having been surveyed by said mineral surveyor and under his

direction; and that said survey has been in all respects, to the best of our knowledge and belief, faithfully

and correctly executed, and the corner and boundary monuments established according to law and the instruc-

tions furnished by the United States Surveyor-General for Arizona.

J.D. Houston _____, *Chainman.*

G.T. Talkalia _____, *Chainman.*

George Talkalia _____, *Asman.*

_____, *Flagman*

Subscribed and sworn to by the above-named persons before me this 18th

day of November, 1934

*My Commission Expires
October 5th 1934*

J.H. Shaw
Notary Public

4-686.

FINAL OATH OF U. S. MINERAL SURVEYOR.

I, Paul E. Fernald, U. S. Mineral Surveyor, do solemnly swear that, in pursuance of instructions received from the United States Surveyor General for Arizona, dated October 14th. 1924., I have, in strict conformity to the laws of the United States, the official regulations and instructions thereunder, and the instructions of said Surveyor General, faithfully and correctly executed the survey of the Mining Claim of J.B. Jamison, known as the BUCKEYE NOS. 1, 2, 3, 4, 5, 6, 7, 8, 9, and 10 lodes, situate in Globe Mining District, Gila County, Arizona, in Sections 22, 27 & 28, Township No. 1 North, Range No. 14 East, G. & S. R. B. & M. Unsvd. and designated as Survey No. 3965, as represented in the foregoing field notes, which accurately show the boundaries of said mining claim as distinctly marked by monuments on the ground, and described in the attached copy of the location certificate, which was received by me from the Surveyor General with said instructions, and that all the corners of said survey have been established and perpetuated in strict accordance with the law, official regulations and instructions thereunder; and I do further solemnly swear that the foregoing are the true and original field notes of said survey and my report therein, and that the labor expended and improvements made upon said mining claim by claimant or its grantors are as therein fully stated, and that the character, extent, location, and itemized value thereof are specified therein with particularity and full detail, and that no portion of said labor or improvements so credited to this claim has been included in the estimate of expenditures upon any other claim.

Paul E. Fernald

U. S. Mineral Surveyor.

Subscribed and sworn to by the said

U. S. Mineral Surveyor, before me

Public, at Tucson, Arizona, this sixt
day of February, 1925

O. J. Richy
Notary Public

My Commission expires Nov. 30, 1927.

U. S. SURVEYOR-GENERAL'S FINAL CERTIFICATE ON FIELD NOTES.

Department of the Interior,

OFFICE OF U. S. SURVEYOR-GENERAL,

Phoenix, Arizona,

March 20, 1925.

I, U. S. Surveyor-General for Arizona

do hereby certify that the foregoing transcript of the Field Notes, return and approval of the survey of the mining claim of

J. B. Jamison

known as the BUCKEYE NOS. 1, 2, 3, 4, 5, 6, 7, 8, 9 and 10 lodes

situate in Globe

Mining District, Gila County, Arizona

in Section 22, 27, 28, Township No. 1 N., Range No. 14 E., Unsur., and

designated as Survey No. 3965, has been correctly copied from the originals on file in

this office; that said Field Notes furnish such an accurate description of said mining claim as will, if incorporated into a patent, serve fully to identify the premises, and that such reference is made therein to natural objects or permanent monuments as will perpetuate and fix the locus thereof.

And I further certify that five hundred dollars' worth of labor has been expended or improved or for each of improvements made upon said mining claim by claimant or his grantors, and that said improvements consist of 16 cuts, 3 tunnels, 6 shafts and 1 crosscut, total value \$7743.51

and that no portion of said labor or improvements has been included in the estimate of expenditures upon any other claim.

I further certify that the plat thereof, filed in the U. S. Land Office at Phoenix, Arizona, is correct and in conformity with the foregoing Field Notes.

Charles M. Donohoe

United States Surveyor-General for Arizona.

**SURVEYOR GENERAL'S CERTIFICATE OF APPROVAL OF FIELD NOTES
AND SURVEY OF MINING CLAIM**

**DEPARTMENT OF THE INTERIOR
OFFICE OF U. S. SURVEYOR GENERAL**

Phoenix, Arizona.

March 20, 1925

I, U. S. Surveyor General for Arizona

do hereby certify that the foregoing and hereto attached Field Notes and Return of the Survey of the Mining Claim of

J. B. Jamison

, known as the

BUCKEYE NOS. 1, 2, 3, 4, 5, 6, 7, 8, 9, and 10 lodes

situate in Globe mining district,

Gila County, Arizona

in Sections 22, 27, 28, Township No. 1 N., Range No. 14 E., Unsur.

, designated as Survey No. 3965

executed by Paul E. Fernald, U. S. Mineral

Surveyor, October 16 - November 15, 1924, under my instructions dated

October 14, 1924, have been critically examined and the necessary

corrections and explanations made, and the said Field Notes and Return, and the survey they describe,

are hereby approved. The certified copy of the location certificate filed by the applicant for survey is

on file in this office and a true copy of said certified copy of said location certificate is included and

made a part of the transcript of the field notes.

Charles M. Donohoe

U. S. Surveyor General for Arizona.

UNITED STATES DEPARTMENT OF THE INTERIOR 9605 (942)
BUREAU OF LAND MANAGEMENT M.S. 3965
ARIZONA STATE OFFICE

NOTICE OF CANCELLATION OF MINERAL SURVEY

The Buckeye No's. 3, 4, 5, 6, 7, 8, 9 and 10 lodes, Mineral Survey No. 3965, located in Township 1 North, Range 14 East, Gila and Salt River Meridian, Arizona, are hereby canceled. As of this date, this notice of cancellation will become part of the field notes for Mineral Survey No. 3965, page 50.


These claims have not been filed with the Arizona State Office, Bureau of Land Management, in accordance with Section 314, 90 STAT. 2769, (43 U.S.C. 1744).

This cancellation was necessitated to clear the record.

The Mineral Survey Plat should be noted as follows:

"Buckeye No's. 3, 4, 5, 6, 7, 8, 9 and 10 lodes, M.S. 3965 were canceled November 6, 1995, by memo 9605 (942) M.S. 3965 which is now a part of the original field notes."

November 6, 1995
Date


Acting Chief Cadastral Surveyor of Arizona