

MINERAL SURVEY No. 4047

ARIZONA Land District.

FIELD NOTES

OF THE SURVEY OF THE MINING CLAIM OF

HENRY T. BAILEY

KNOWN AS THE

EDNA, ETHEL, FLORENCE, IGO, PLUTUS, PLUTUS #2, RICO and UGO Lodes

WINIFRED Mining District,

MARICOPA County, ARIZONA

Section s 3 and 34, Townships 2 and 3 N., Range 3 East

Surveyed under instructions dated June 28th., 1927.

by Harry E. Jones, U. S. Mineral Surveyor.

Claim located See location notices, 19

Survey commenced June 30th., 1927.

Survey completed July 14th., 1927.

Address of claimant Henry T. Bailey, 323 Ellis Bldg. Phoenix, Arizona.

DATES OF AMENDED LOCATIONS.

See location notices.

## MINERAL SURVEY NO. 4047

Feet

Edna Lode

- Beginning at Cor. No. 1, identical with location monument and Cor. 1 Florence and Cor. 1 Plutus ~~No. 2~~ <sup>##</sup> lodes, both of this survey, a 3½ft. ½in. pipe with a 2in. brass cap marked U.S. MINERAL SURVEY NO. 4047-E-1; F-1; P No. 2-1; set 24 ins. in ground and surrounded with a substantial mound of earth and rock.
- The ¼ corner common to Section 3, T. 2 N. R. 3 E. and Section 34, T. 3 N. R. 3 E. G&SRB&M. bears S. 53° 13' E. 235.65 ft. No other suitable bearings available.
- Thence S. 24° 34' W.
- Along line 1-4 Florence lode this survey.
- 157.42 Intersect the line common to Sections 3 and 34, T. 2 and 3 N. R. 3 E. at S. 89° 32' W. 254.19 ft. from the ¼ corner common to said sections.
- 320.00 Cross center of 10 ft. wash, course Southerly.
- 480.00 Cross center of 10 ft. wash, course Southwesterly.
- 730.00 Cross center of 10 ft. wash, course Southwesterly.
- 950.00 Cross center of 10 ft. wash, course Southwesterly.
- 1125.00 Cross center of 10 ft. wash, course Southwesterly.
- 1500.00 To Cor. No. 2, identical with location monument, and Cor. 4 Florence lode of this survey, a 3½ft. ½in. pipe with a 2in. brass cap marked U.S. MINERAL SURVEY NO. 4047-E-2; F-4; set 24 ins. in ground and surrounded with a substantial mound of earth and rock. No suitable bearings available.
- Thence N. 65° 16' W.
- 300.00 To South End Center, a substantial mound of earth and rock identical with the location monument.
- 600.00 To Cor. No. 3 a 3½ft. ½in. pipe with a 2in. brass cap marked U.S. MINERAL SURVEY NO. 4047-E-3; set 20 ins. in ground and surrounded with a substantial mound of earth and rock, identical with the location monument.
- No suitable bearings available.
- Thence N. 24° 34' E.
- 1060.62 Intersect the line common to Sections 3 and 34, T. 2 and 3 N. R. 3 E. at S. 89° 32' W. 916.40 ft. from the ¼ corner common to said sections.



Feet  
 1500.00 To Cor. No. 4 a 3½ft. ¼in. pipe with a 2in. brass cap marked U.S. MINERAL SURVEY NO. 4047-E-4; set 24 ins. in ground and surrounded with a substantial mound of earth and rock, identical with the location monument.  
 Cor. 2 Rice lode of this survey bears N. 24° 34' E. 20 ft. No other suitable bearings available.  
 Thence S. 65° 16' E.

300.00 To North End Center, a substantial mound of earth and rock, identical with the location monument.

425.00 Cross center of 10 ft. wash, course Southerly.

600.00 To Cor. No. 1 the place of beginning.

-----  
 Florence Lode  
 Beginning at Cor. No. 1, identical with location monument, Cor. 1 Edna and Cor. 1 Plutus No. 2 lodes both of this survey previously described.  
 The ¼ corner common to Sections 3 and 34, T. 2 and 3 N. R. 3 E. bears S. 53° 13' E. 235.65 ft.  
 Thence S. 65° 16' E.  
 Along line 1-4 Plutus No. 2 lode of this survey.

205.89 Intersect the East line of the SW¼ of Section 34, T. 3 N. R. 3 E. at N. 1° 48' W. 54.99 ft. from the South ¼ corner of said section.

224.00 Intersect the South End Center Plutus No. 2 lode of this survey.

247.00 Cross center of Shea Blvd. which bears N. and S.

300.00 To North End Center, a substantial mound of earth and rock, identical with the location monument.

524.00 Intersect Cor. 4 Plutus No. 2 lode identical with Cor. 1 Igo lode both of this survey.  
 Along line 1-4 Igo lode of this survey.

600.00 To Cor. No. 2, identical with the location monument and Cor. 1 Ethel lode of this survey, a 3½ft. ¼in. pipe with a 2in. brass cap marked U.S. MINERAL SURVEY NO. 4047-F-2; E-1; set 20 ins. in ground and surrounded with a substantial mound of earth and rock. No suitable bearings available,



Feet	
	Thence S. 24° 34' W.
	Along line 1-4 Ethel lode of this survey.
1500.00	To Cor. No. 3, identical with the location monument and Cor. 4 Ethel lode of this survey, a 3½ft. ½in. pipe with a 2in. brass cap marked U.S. MINERAL SURVEY NO. 4047-F-3;E-4; set 15ins. in ground and surrounded with a substantial mound of earth and rock. No suitable bearings available.
	Thence N. 65° 16' W.
300.00	To South End Center, a substantial mound of earth and rock, identical with the location monument.
345.00	Cross center of Shea Blvd. bearing NEly. and SWly.
465.00	Cross center of 10 ft. wash, course SWly.
600.00	To Cor. No. 4, identical with location monument and Cor. 2 Edna lode of this survey previously described.
	Thence N. 24° 34' E.
	Along line 2-1 Edna lode of this survey.
375.00	Cross center of 10 ft. wash, course SWly.
550.00	Cross center of 10 ft. wash, course SWly.
770.00	Cross center of 10 ft. wash, course SWly.
1020.00	Cross center of 10 ft. wash, course SWly.
1180.00	Cross center of 10 ft. wash, course Sly.
1342.58	Intersect the line common to Section 3 and 34, T. 2 and 3 N. R. 3 E. at S. 89° 32' W. 254.19 ft. from the ¼ corner common to said sections.
1500.00	To Cor. No. 1 the place of beginning.
	-----
	Ethel Lode
	Beginning at Cor. No. 1, identical with the location monument and Cor. 2 Florence lode of this survey, previously described, on line 1-4 Igo lode of this survey.
	The ¼ corner common to Sections 3 and 34, T. 2 and 3 N. R. 3 E. bears N. 72° 51' W. 372.82 ft.
	Thence S. 65° 16' E.
	Along line 1-4 Igo lode of this survey.
224.00	Intersect the South End Center Igo lode this survey.



Feet  
 300.00 To North End Center, a substantial mound of earth and rock, identical with the location monument.

524.00 Intersect Cor. 4 Igo lode of this survey.

600.00 To Cor. No. 2, a 3½ft. ¾in. pipe with a 2in. brass cap marked U.S. MINERAL SURVEY NO. 4047-E-2; set 16ins. in ground and surrounded with a substantial mound of earth and rock, identical with the location monument.  
 No suitable bearings available.

Thence S. 24° 34' W.

1500.00 To Cor. No. 3, a 3½ft. ¾in. pipe with a 2in brass cap marked U.S. MINERAL SURVEY NO. 4047-E-3; set 20ins. in ground and surrounded with a substantial mound of earth and rock. No suitable bearings available.

Thence N. 65° 16' W.

300.00 To South End Center, a substantial mound of earth and rock, identical with the location monument.

600.00 To Cor. No. 4, identical with the location monument and Cor. 3 Florence lode of this survey previously described.

Thence N. 24° 34' E.

Along line 3-2 Florence lode of this survey.

1500.00 To Cor. No. 1 the place of beginning.

-----  
 Igo Lode

Beginning at Cor. No. 1, identical with the location monument and Cor. 4 Plutus <sup>#</sup> 2 lode of this survey, on line 1-2 Florence lode of this survey. A 3½ft. ¾in. pipe with a 2in. brass cap marked U.S. MINERAL SURVEY NO. 4047-I-1; PNo. 2-4; set 20ins. in ground and surrounded with a substantial mound of earth and rock.

The ¼ corner common to Sections 3 and 34, T. 2 and 3 N. R. 3 E. bears N. 74° 47' W. 297.67 ft.

No other suitable bearings available.

Thence N. 24° 34' E.

Along line 4-3 Plutus <sup>#</sup> 2 lode of this survey.

1500.00 To Cor. No. 2, identical with location monument and Cor. 3 Plutus <sup>#</sup> ~~No.~~ 2 lode of this survey, a 3½ft. ¾in. pipe with a 2in. brass cap marked U.S. MINERAL SURVEY NO. 4047-I-2; PNo. 2-3;



-5-

Feet	set 20ins. in ground and surrounded with a substantial mound of earth and rock, on line 2-3 Plutus lode of this survey. No suitable bearings available. Thence S. 65° 16' E. Along Line 3-2 Plutus lode of this survey.
76.00	Intersect Cor.2 Plutus lode, identical with Cor.3 Ugo lode both of this survey. Along line 3-2 Ugo lode of this survey.
300.00	To North End Center, a substantial mound of earth and rock, identical with the location monument.
376.00	Intersect the South End Center Ugo lode of this survey.
600.00	To Cor. No. 3, a 3½ft. ½in. pipe with a 2in. brass cap marked U.S.MINERAL SURVEY NO.4047-I-3; set 18ins. in ground and surrounded with a substantial mound of earth and rock, identical with location monument. Cor.2 Ugo lode of this survey bears S.65°16'E. 76 ft. No other suitable bearings available. Thence S. 24° 34' W.
1500.00	To Cor. No. 4, a 3½ft. ½in. pipe with a 2in. brass cap marked U.S.MINERAL SURVEY NO.4047-I-4; set 18ins. in ground and surrounded with a substantial mound of earth and rock, identical with the location monument. On line 1-2 Ethel lode of this survey, whence Cor.2 bears S.65°16'E. 76 ft. No other suitable bearings available. Thence N. 65° 16'W. Along line 2-1 Ethel lode of this survey.
224.00	Intersect the North End Center Ethel lode of this survey.
300.00	To South End Center, a substantial mound of earth and rock, identical with the location monument.
524.00	Intersect Cor.1 Ethel lode identical with Cor.2 Florence lode both of this survey.
600.00	To Cor. No. 1 the place of beginning.

-----  
Plutus #. 2 Lode

Beginning at Cor. No. 1, identical with Cor.1 Edna lode, and Cor. 1 Florence lode both of this survey, previously described.



## Feet

The  $\frac{1}{4}$  corner common to Sections 3 and 34, T. 2 and 3 N.  
R. 3 E. bears S.53°13'E. 235.65 ft.

The location monument bears N.65°16'W. 76 ft.

No other bearings available.

Thence N. 24° 34' E.

20.00 Intersect Cor. 1 Rico lode of this survey.

Along line 1-4 Rico lode of this survey.

414.77 Intersect the East line of the SW $\frac{1}{4}$  of Section 34, T. 3 N.  
R. 3 E. at N.1°48'W. 518.59 ft. from the S $\frac{1}{4}$  corner of  
said section.

565.00 Cross center of Shea Blvd. bearing Nly. and Sly.

1500.00 To Cor. No. 2, identical with Cor.3 Plutus lode of this  
survey, a 3 $\frac{1}{2}$ ft.  $\frac{3}{4}$ in. pipe with a 2in. brass cap marked  
U.S.MINERAL SURVEY NO.40474PNO.2-2;P-3; set 18ins. in ground  
and surrounded with a substantial mound of earth and rock,  
whence the location monument bears N.65°16'W. 76 ft.

Cor.4 Rico lode of this survey bears N.24°34'E. 20 ft.

No other suitable bearings available.

Thence S. 65°16'E.

Along line 3-2 Plutus lode of this survey.

224.00 To North End Center, a substantial mound of earth and  
rock identical with the location monument.

300.00 Intersect the South End Center of Plutus lode of this sur.

524.00 To Cor. No. 3, identical with the location monument and  
Cor.2 Igo lode of this survey previously described.

Thence S. 24° 34' W.

Along line 2-1 Igo lode of this survey.

1500.00 To Cor. No. 4, identical with the location monument and  
Cor.1 Igo lode of this survey previously described.

Thence N. 65° 16'W.

Along line 2-1 Florence lode of this survey.

224.00 Intersect North End Center Florence lode this survey.

277.00 Cross center of Shea Blvd. bears Nly. and Sly.

300.00 To South End Center, a substantial mound of earth and  
rock, identical with the location monument.

318.11 Intersect the East line of the SW $\frac{1}{4}$  of Section 34, T. 3 N.



Feet	R. 3 E. at N.1°48'W. 54.99 ft. from the S $\frac{1}{4}$ corner of said section.
524.00	To Cor. No. 1 the place of beginning.
----- Rico Lode	
Beginning at Cor. No. 1, a 3 $\frac{1}{2}$ ft. $\frac{3}{4}$ in. pipe with a 2 in. brass cap marked U.S.MINERAL SURVEY NO.4047-R-1; set 20ins. in ground and surrounded with a substantial mound of earth and rock, identical with the location monument.	
Cor.1 Plutus #.2 lode, identical with Cor.1 Florence and Edna lodes of this survey bears S.24°34'W. 20 ft.	
The $\frac{1}{4}$ corner common to Section 3 and 34, T. 2 and 3 N. R. 3 E. bears S.48°33'30"E. 240.67 ft.	
No other suitable bearings available.	
Thence N. 65° 16' W.	
180.00	Cross center of 10 ft. wash, course Sly.
300.00	To South End Center, a substantial mound of earth and rock, identical with the location monument.
600.00	To Cor. No. 2, a 3 $\frac{1}{2}$ ft. $\frac{3}{4}$ in. pipe with a 2in. brass cap marked U.S.MINERAL SURVEY NO.4047-R-2; set 22ins. in ground and surrounded with a substantial mound of earth and rock, identical with the location monument. Cor.4 Edna lode of this survey bears S.24°34'W. 20 ft. No other suitable bearings available.
Thence N. 24° 34' E.	
1500.00	To Cor. No. 3, a 3 $\frac{1}{2}$ ft. $\frac{3}{4}$ in. pipe with a 2in. brass cap marked U.S.MINERAL SURVEY NO.4047-R-3; set 18ins. in ground and surrounded with a substantial mound of earth and rock, identical with the location monument. No suitable bearings available.
Thence S. 65° 16'E.	
51.37	Intersect the East line of the SW $\frac{1}{4}$ of Section 34, T. 3 N. R. 3 E. at N.1°48'W. 1753.94 ft. from the S $\frac{1}{4}$ corner of said section.
160.00	Cross center of Shea Blvd. bearing NEly. and Sly.
300.00	To North End Center, a substantial mound of earth and rock, identical with the location monument.



Feet	
325.00	Cross center of 10 ft. wash, course SWly.
600.00	To Cor. No. 4, a 3½ft. ½in. pipe with a 2in. brass cap marked U.S. MINERAL SURVEY NO. 4047-R-4; set 20ins. in ground and surrounded with a substantial mound of earth and rock, identical with the location monument. On line 3-4 Plutus lode of this survey, whence Cor. 3 bears S. 24° 34' W. 20 ft. No other suitable bearings available. Thence S. 24° 34' W. Along line 4-3 Plutus lode of this survey.
20.00	Intersect Cor. 3 Plutus lode identical with Cor. 2 Plutus #.2 lode both of this survey. Along line 2-1 Plutus #.2 lode of this survey.
955.00	Cross center of Shea Blvd, Bears Nly. and Sly.
1105.23	Intersect the East line of the SW¼ of Section 34, T. 3 N. R. 3 E. at N. 1° 48' W. 518.59 ft. from the S¼ corner of said section.
1500.00	To Cor. No. 1 the place of beginning.
	----- Plutus Lode
	Beginning at Cor. No. 1, a 3½ft. ½in. pipe with a 2in. brass cap marked U.S. MINERAL SURVEY NO. 4047-P-1; /set 18 <sup>U-4;</sup> ins. in ground and surrounded with a substantial mound of earth and rock, identical with location monument and Cor. 4 Ugo lode of this survey. The E¼ corner of Section 34, T. 3 N. R. 3 E. bears N. 88° 59' E. 1262.21 ft. No other suitable bearings available. Thence S. 24° 34' W. Along line 4-3 Ugo lode of this survey.
1500.00	To Cor. No. 2, a 3½ft. ½in. pipe with a 2in. brass cap marked U.S. MINERAL SURVEY NO. 4047-P-2; U-3; set 18ins. in ground and surrounded with a substantial mound of earth and rock, identical with location monument and Cor. 3 Ugo lode of this survey, on line 2-3 Igo lode of this survey. No suitable bearings available. Thence N. 65° 16' W. Along line 3-2 Igo lode of this survey.

see cor. to  
letter herewith



Feet	
76.00	Intersect Cor.2 Igo lode identical with Cor.3 Plutus #.2 lode both of this survey. Along line 3-2 Plutus #.2 lode of this survey.
300.00	To South End Center, a substantial mound of earth and rock identical with the location monument.
376.00	Intersect the North End Center of Plutus No.2 lode of this survey.
600.00	To Cor. No. 3, identical with the location monument and Cor.2 Plutus #.2 lode of this survey previously described. The $\frac{1}{4}$ corner common to Sections 3 and 34, T. 2 and 3 N. R. 3 E. bears S.16°07'W. 1566.80 ft. No other suitable bearings available. Thence N. 24° 34' E. Along line 1-4 Rico lode of this survey.
20.00	Intersect Cor.4 Rico lode of this survey.
410.00	Cross center of 10 ft. wash, course SWly.
580.00	Cross center of Shea Blvd. bears NEly. and SWly.
1500.00	To Cor. No. 4, a 3 $\frac{1}{2}$ ft. $\frac{3}{4}$ in. pipe with a 2in. brass cap marked U.S.MINERAL SURVEY NO.4047-P-4; set 20ins. in ground and surrounded with a substantial mound of earth and rock, identical with the location monument. No suitable bearings available. Thence S. 65° 16' E.
300.00	To North End Center, a substantial mound of earth and rock identical with the location monument.
382.00	Cross center of Shea Blvd. bears NEly. and SWly.
450.00	Cross center of 10 ft. wash, course SWly.
600.00	To Cor. No. 1 the place of beginning.

-----  
Ugo Lode

Beginning at Cor. No. 1, a 3 $\frac{1}{2}$ ft.  $\frac{3}{4}$ in. pipe with a 2in brass cap marked U.S.MINERAL SURVEY NO4047-U-1; set 18ins. in ground and surrounded with a substantial mound of earth and rock, identical with the location monument.

The E $\frac{1}{4}$  corner of Section 34, T. 3 N. R 3 E. bears N.69° 08'E. 767.38 ft. No other suitable bearings available.

Thence S. 24° 34' W.

*see correct  
the in letter  
herewith*



Feet  
1500.00 To Cor. No. 2, a 3 $\frac{1}{2}$ ft.  $\frac{3}{4}$ in. pipe with a 2in. brass cap marked U.S. MINERAL SURVEY NO. 4047-U-2; set 20ins. in ground and surrounded with a substantial mound of earth and rock, identical with the location monument.  
No suitable bearings available.

Thence N. 65° 16' W.

76.00 Intersect Cor. 3 Igo lode of this survey. Along line 3-2 Igo lode of this survey.  
300.00 To South End Center, a substantial mound of earth and rock, identical with location monument.  
376.00 Intersect the North End Center of Igo lode this survey.  
600.00 To Cor. No. 3, identical with the location monument and Cor. 2 Plutus lode of this survey previously described. The  $\frac{1}{4}$  corner common to Sections 3 and 34, T. 2 and 3 N. R. 3 E. bears S. 38° W. 1591.63 ft.

Thence N. 24° 34' E.

Along line 2-1 Plutus lode of this survey.

1500.00 To Cor. No. 4, identical with the location monument and Cor. 1 Plutus lode of this survey previously described.

Thence S. 65° 16' E.

300.00 To North End Center, a substantial mound of earth and rock, identical with the location monument.  
600.00 To Cor. No. 1 the place of beginning.

-----  
The Mean magnetic variation at all corners is 14° 45' E.  
-----

#### Lode Lines

As near as can be determined from the present developments the veins of the several locations embraced in this claim extend as follows from their discovery points:

Edna lode, N. 24° 34' E. 268 ft. and S. 24° 34' W. 1232 ft.  
Florence lode, N. 24° 34' E. 255 ft. and S. 24° 34' W. 1245 ft.  
Ethel lode, N. 24° 34' E. 135 ft. and S. 24° 34' W. 1365 ft.  
Igo lode, N. 24° 34' E. 30 ft. and S. 24° 34' W. 1470 ft.  
Plutus #2 lode, N. 24° 34' E. 30 ft. and S. 24° 34' W. 1470 ft.  
Rico lode, N. 24° 34' E. 60 ft. and S. 24° 34' W. 1440 ft.  
Plutus lode, S. 24° 34' W. 390 ft. and N. 24° 34' E. 1110 ft.



-11-

Ugo lode, S.24°34'W. 135 ft. and N.24°34'E. 1365 ft.

-----  
Area

Total area Edna lode, 20.661 Acres

Area in conflict with:

SW $\frac{1}{4}$  Sec.34, T. 3 N. R. 3 E.

Hd.023897 4.110

Total area Florence lode, 20.661

Area in conflict with:

SW $\frac{1}{4}$  Sec.34, T. 3 N. R. 3 E.

Hd.023897 0.532

Total area Ethel lode, 20.661

Total area Igo lode, 20.661

Total area Plutus #.2, lode, 18.044

Area in conflict with:

SW $\frac{1}{4}$  Sec.34, T. 3 N. R. 3 E.

Hd023897 0.980

Total area Rico lode, 20.661

Area in conflict with:

SW $\frac{1}{4}$  Sec.34, T. 3 N. R. 3 E.

Hd.023897 13.701

Total area Plutus lode, 20.661

Total area Ugo lode, 20.661

-----  
Location

This survey is located in the N $\frac{1}{2}$  of Section 3, T. 2 N.  
R. 3 E. and <sup>E $\frac{1}{2}$  & SW $\frac{1}{4}$</sup>  S $\frac{1}{4}$  of Section 34, T. 3 N. R. 3 E. Gila and  
Salt River Base and Meridian, Winifred Mining District,  
Maricopa County, Arizona.

-----  
Expenditure of Five Hundred Dollars

I certify that the value of the labor and improvements  
made upon or for the benefit of the locations embraced  
in said mining claim by the claimant or his grantors, is  
not less than Five Hundred Dollars, and that said improve-  
ments consist of:



## Edna Lode

No.1 Disc. shaft 4x6x8 ft. deep bears S.24°34'W. 268 ft. from the North End Center. Value \$ 100.00

No.2 shaft 4x6x8 ft. deep bears N.18°52'W. 460 ft. from the 874 ft. point on line 1-2, Value \$ 100.00

No.3 cut 3x3x12 ft. long, the SE. end of which bears N.3°50'W. 494 ft. from the 874 ft. point on line 1-2.

Value \$ 50.00

No.4 shaft 4x6x25 ft. deep bears N.5°06'E. 423 ft. from the 874 ft. point on line 1-2; Value \$ 312.50

No.5 cut 3x4x20 ft. long the SE. end of which bears N.8°15'E. 418 ft. from the 874 ft. point on line 1-2;

Value \$ 125.00

No.6 shaft 4x6x26.5 ft. deep bears S.37°30'W. 175 ft. from the 874 ft. point on line 1-2; Value \$ 331.25

An undivided 1/8th. interest in No.2 improvement Rico lode of this survey is accredited to this lode.

Value \$ 482.00

## Florence Lode

No.1 Disc. cut 5x6x6 ft. facing NWly. the mouth of which bears S.24°34'W. 255 ft. from the North End Center.

Value \$ 50.00

No.2 cut 5x10x6 ft. facing NWly. the mouth of which bears N.48°30'E. 642 ft. from the 626 ft. point on line 4-1;

Value \$ 75.00

No.3 cut 2x3x25 ft. long, the NW end of which bears N.29°35'E. 620 ft. from the 626 ft. point on line 4-1;

Value \$ 75.00

No.4 cut 4x8x6 ft. facing NWly. the mouth of which bears N.76°40'E. 703 ft. from the 626 ft. point on line 4-1;

Value \$ 50.00

No.5 cut 3.5x80x12 ft. long, the NWly end of which bears N.88°15'E. 602 ft. from the 626 ft. point on line 4-1;

Value \$ 750.00

As this improvement lies partly across line 2-3 identical with line 1-4 Ethel lode of this survey, an undivided 1/2



each interest is accredited to this lode and the Ethel lode of this survey. Value  $\frac{1}{2}$  \$ 375.00

An undivided 1/8th. interest in No.2 improvement Rico lode of this survey is accredited to this lode.

Value \$ 482.00

Ethel Lode

No.1 Disc. shaft 4x6x8 ft. deep bears S.24°34'W. 135 ft. from North End Center; Value \$ 100.00

No.2 shaft 4x6x8 ft. deep bears S.24°34'W. 625 ft. from North End Center; Value \$ 100.00

An undivided 1/2 interest in improvement No.5 Florence lode of this survey is accredited to this lode.

Value \$ 375.00

An undivided 1/8th. interest in improvement No.2 Rico lode of this survey is accredited to this lode.

Value \$ 482.00

Igo Lode

No.1 Disc. shaft 4x6x8 ft. deep bears S.24°34'W. 30 ft. from North End Center. Value \$ 100.00

No.2 shaft 4x6x6 ft. deep bears S.55°W. 52 ft. from North End Center. Value \$ 75.00

No.3 cut 2x2x12 ft. long, the NW. end of which bears S.55°W. 122 ft. from North End Center. Value \$ 25.00

No.4 shaft 4x6x12 ft. deep, bears S.24°34'W. 190 ft. from North End Center. Value \$ 150.00

No.5 cut 2x10x6 ft. facing SWly. the mouth of which bears N.55°37'E. 230 ft. from Cor.1; Value \$ 50.00

No.6 cut 2x6x4 ft. facing SWly. the mouth of which bears N.59°10'E. 250 ft. from Cor.1; Value \$ 25.00

No.7 cut 2x6x4 ft. facing SWly. the mouth of which bears N.64°15'E. 270 ft. from Cor.1; Value \$ 25.00

No.8 cut 2x4x30 ft. long the Wly. end of which bears N.64°15'E. 310 ft. from Cor.1; Value \$ 125.00

An undivided 1/2 interest in improvement No.4 Ugo lode of this survey is accredited to this lode. Value \$ 237.50

An undivided 1/8th. interest in improvement No.2 Rico lode this survey is accredited to this lode. Value \$ 482.00



## Plutus #. 2 Lode

No.1 Disc. shaft 4x6x42 ft. deep, with cross-cut to NW. 4x6x10 ft. long and drift to SW. 4x6x12 ft. long, bears S.24°34'W. 30 ft. from North End Center. Value \$ 855.00

No.2 shaft 4x6x20 ft. deep bears S.31°35'W. 200 ft. from North End Center. Value \$ 250.00

No.3 shaft 4x6x10 ft. deep bears N.70°W. 170 ft. from North End Center. Value \$ 125.00

An undivided 1/8th. interest in improvement No.2 Rico lode of this survey is accredited to this lode.

Value \$ 482.00

## Rico Lode

No.1 Disc. point an outcropping ledge in place, bears S.24°34'W. 60 ft. from the North End Center.

No.2 incline shaft 4x6x100 ft. deep, bears S.24°34'W. 11 ft. from the bottom of which a cross-cut runs SEly. 4x6x100 ft. long, and a drift runs SWly. 4x6x60 ft. long. Total Value \$3856.00

This improvement being a shaft inclining to the southeast about 70° and having a location which is logical and advantageous from a mining standpoint, is situated near the westerly edge of the claim in the north third of same.

The general slope of the ground surface of this claim is slightly downward toward the west and southwest, with no very abrupt changes of elevation on the claim, the surface would be generally classified as rolling,

The present bottom of this improvement is well below the ground surface of all parts of this claim and by extending the depth of the shaft and the lateral workings therefrom in the several directions necessary to reach the ore bodies lying under each lode of this claim, thereby tending to expedite the extraction of the ore from each lode.

Therefore this improvement can be said to redound to the benefit of each lode of this claim and <sup>each</sup> has an undivided equal participation in the total value of this improvement.

~~Total Value \$ 3856.00~~

An undivided 1/8th. interest in this improvement is therefore accredited to this lode. Value \$ 482.00



No.3 shaft 5x6x8 ft. deep bears N.75°30'W. 320 ft. from Cor.4; Value \$ 100.00

No.4 shaft 4x6x20 ft. deep bears S.24°34'W. 155 ft. from North End Center. Value \$ 250.00

No.5 shaft 5x6x8 ft. deep bears N.68°32'W. 205 ft. from Cor.4; Value \$ 100.00

No.6 shaft 4x6x10 ft. deep bears S.36°10'W. 90 ft. from Cor.4; Value \$ 125.00

Plutus Lode

No.1 Disc. cut 4x12x8 ft. facing SWly. the mouth of which bears N.24°34'E. 390 ft. from South End Center.

Value \$ 100.00

No.2 shaft 5x6x17 ft. deep bears N.51°25'E. 445 ft. from Cor.3; Value \$ 212.50

No.3 shaft 4x6x8 ft. deep bears S.38°10'W. 670 ft. from North End Center; Value \$ 100.00

No.4 shaft 4x6x8 ft. deep bears S.24°34'W. 35 ft. from North End Center; Value \$ 100.00

An undivided 1/8th. interest in improvement No.2 Rico lode of this survey is accredited to this lode.

Value \$ 482.00

Ugo Lode

No.1 Disc. cut 6x12x9 ft. facing SWly. the mouth of which bears N.24°34'E. 135 ft. from the South End Center.

Value \$ 100.00

No.2 shaft 5x8x10 ft. deep bears N.24°34'E. 255 ft. from the South End Center. Value \$ 200.00

No.3 cut 2x2x12 ft. long the SE. end of which bears N.50°15'W. 280 ft. from South End Center. Value \$ 25.00

No.4 shaft 4x6x20 ft. with drift 4x6x15 ft. running SWly. bears N.56°55'W. 100 ft. from South End Center.

Value \$ 475.00

As this improvement extends across line 2-3 identical with line 2-3 Igo lode of this survey, therefore each lode shares in an equal division of the total value of same.

An undivided 1/2 interest in this improvement is accredited to this lode. Value \$ 237.50



An undivided 1/8th. interest in improvement No. 2 Rico lode of this survey is accredited to this lode.

Value. \$ 482.00

-----  
Other Improvements

A frame house 12x36 ft. with lean-top additions, the NW. cor. of which bears S.27°25'W. 525 ft. from Cor. 3 Plutus No. 2 lode.

A cut 5x20x9 ft. facing NWly. bears S.86°13'E. 571 ft. from the 626 ft. point on line 4-1 Florence lode.

A cut 5x20x8 ft. facing NWly. bears S.67°20'E. 460 ft. from the 626 ft. point on line 4-1 Florence lode.

A cut 5x14x8 ft. facing NWly. bears S.43°04'E. 530 ft. from the 626 ft. point on line 4-1 Florence lode.

A cut 6x15x10 ft. facing NWly. bears S.8°30'E. 740 ft. from the 626 ft. point on line 4-1 Florence lode.

A cut 12x15x8 ft. facing SEly. bears N.28°47'W. 362 ft. from the 874 ft. point on line 1-2 Edna lode.

A cut 2x5x4 ft. facing SEly. bears N.28°47'W. 336 ft. from the 874 ft. point on line 1-2 Edna lode.

The NE. cor. of an old lime kiln bears S.59°13'W. 680 ft. from the 874 ft. point on line 1-2 Edna lode.

A cut 4x6x6 ft. facing SEly. bears N.36°45'W. 423 ft. from the 874 ft. point on line 1-2 Edna lode.

A cut 30x40x12 ft. facing SEly. the SE. corner of which bears S.66°55'W. 640 ft. from the 874 ft. point on line 1-2 Edna lode.

A cut 7x18x5 ft. facing SEly. bears S.56°45'W. 692 ft. from the 874 ft. point on line 1-2 Edna lode.

-----  
Adjoining Claims

This claim is bounded on the West by public domain, and patented Hd. 023897, and Mary Ann lode and Dolores lode, <sup>unsurveyed,</sup> both on the North by Dolores, Red Top and Afterthought lodes, <sup>unsurveyed,</sup> on the East and South by public domain.

-----



INSTRUMENT

This survey was made with a W. & L.E. Gurley light mountain transit.

The courses were deflected from a true meridian as determined by direct solar observations.

The distances were measured with a 660 ft. steel tape.

-----  
Report

The public land corner to which this survey is tied, the  $\frac{1}{4}$  corner common to Sections 3 and 34, T. 2 and 3 N. R. 3 E. is a stone properly set and marked.

I could not definitely identify the  $N\frac{1}{4}$  corner,  $E\frac{1}{4}$  corner, or SW. corner of Section 34, T. 3 N. R. 3 E. as the marked stone was not in evidence at any of the said points; however a mound of rock which had all of the indications of being a marker for a public land corner was in the position as indicated in each instance, and in all probability is the accepted corner for each point respectively, the same being used to tie this survey to as shown herein.

In each instance where a definite corner stone could not be found and identified I set in the mound of rock which was used, a schist rock approximately 4x8x24 inches.

*Henry Jones*  
U.S. Mineral Surveyor.



This survey was made with a ...

The corners were delineated ...

The distance was measured with a ...

NOTES

The ...

I could not determine ...

There was no evidence ...

Being a matter for a public land corner ...

as indicated in each instance, and in all probability ...


the corner for each point respectively, the same ...

being used to the same to be shown herein.

In each instance these ...

was found and identified ...

was used, a ...





Field Notes

of

The subdivision of the NW $\frac{1}{4}$  of  
Section 3, T. 2 N. R. 3 E.

in connection with

Sur. No. 4047

#####

In a retracement of the line common to the SW $\frac{1}{4}$  of Sec. 34, T. 3 N. R. 3 E. with the NW $\frac{1}{4}$  of Sec. 3, T. 2 N. R. 3 E. I find the course and length to be S.89°32'W. 2590.20 ft. the mid-point of this line becoming then the common cor. to Lots 3 and 4 of the said NW $\frac{1}{4}$  of Sec. 3, T. 2 N. R. 3 E. I find the course and length of the line common to the NW $\frac{1}{4}$  of Section 3, and the NE $\frac{1}{4}$  of Sec. 4, both of T. 2 N. R. 3 E. to be S.3°30'E. 2883.45 ft. the common corner point of Lots 4 and 5 of the said NW $\frac{1}{4}$  of Sec. 3, T. 2 N. R. 3 E. being fixed by the proportional method at N.3°30'W. 1427.90 ft. to the NW. corner of said Sec. 3, and S.3°30'E. 1455.55 ft. to the  $\frac{1}{4}$  corner common to said Sections 3 and 4, of T. 2 N. R. 3 E.

The center of Section 3, T. 2 N. R. 3 E. was determined by an intersection of the latitudinal mid-section line with the meridional mid-section line, the course and length of the line from the said section center to the W $\frac{1}{4}$  corner thereof is S.88°38'W. 2553.20 ft. and the mid-point of this line become's the common corner to Lots 5 and 6 of the NW $\frac{1}{4}$  of said Sec.3, T. 2 N. R. 3 E.

The course and length of the line from the section center to the N $\frac{1}{4}$  corner thereof is N.2°47'30"W. 2841.80 ft. and the common corner point of Lots 2, 3, 6 and 7 being fixed by the proportional method at S.2°47'30"E. 1435.42 ft. to said section center, and N.2°47'30"W. 1406.38 ft. to said N $\frac{1}{4}$  corner. The interior corner common to Lots 3, 4, 5, and 6 of the NW $\frac{1}{4}$  of said Sec. 3, I then fixed by intersection of the lines drawn from the lot corner points established on the exterior boundaries of said NW $\frac{1}{4}$ , the



18-A

latitudinal line from the corner point common to said Lots 3, 4, 5 and 6, being in course and length, N.89°05'E. 1285.92 ft. and S.89°05'W. 1285.92 ft. and the meridional line from said common corner point being in course and length N.3°08'45"W. 1417.14 ft. and S.3°08'45"E. 1445.58 ft.

-----  
 Edna lode, Sur. No. 4047 in conflict with Lot 4, (Hd.048-478) 0.369 Acres. ~~Thence~~ N. 65° 16' W.

Along line 2-3 Edna lode, Sur.No.4047,

469.98 Intersect the line common to Lot 3 and 4, of the NW $\frac{1}{4}$  of Section 3, T. 2 N. R. 3 E. at N.3°08'45"W. 399.67 ft. from the SW. and SE. corners respectively of said Lots.

600.00 To Cor. No. 3 previously described.

Thence N. 24° 34' E.

Along line 3-4 Edna lode, Sur. No. 4047,

247.16 Intersect the line common to Lot 3 and 4, of the NW $\frac{1}{4}$  of Section 3, T. 2 N. R. 3 E. at N.3°08'45"W. 679.28 ft. from the SW. and SE. corners respectively of said Lots.

-----  
 Florence lode, Sur. No.4047 in conflict with Lot6,(Hd.030-524) 0.120 acres. ~~Thence~~ S. 24° 34' W.

Along line 2-3 Florence lode, Sur. No. 4047, identical with line 4-1 Ethel lode of the same survey.

1429.33 Intersect the line common to Lot 3 and 6, of the NW $\frac{1}{4}$  of Section 3, T. 2 N. R. 3 E. at S.89°05'W. 306.52 ft. from the SE. and NE. corners respectively of said Lots.

1500.00 To Cor. No.3 previously described.

Thence N. 65° 16' W.

Along line 3-4 Florence lode, Sur. No. 4047,

147.38 Intersect the line common to Lot 3 and 6, of the NW $\frac{1}{4}$  of Section 3, T. 2 N. R. 3 E. at S.89°05'W. 469.78 ft. from the SE. and NE. corners respectively of said Lots.

-----  
 Ethel lode, Sur. No. 4047 in conflict with Lot 6 (Hd.030-524) 1.116 acres.

~~Thence~~ N. 65° 16' W.

Along line 3-4 Ethel lode, Sur. No. 4047,

217.92 Intersect the line common to Lot 7 and 6, of the NW $\frac{1}{4}$  of



Section 3, T. 2 N. R. 3 E. at S.2°47'30"E. 229.31 ft. from the NW. and NE. corners respectively of said Lots.

600.00 To Cor. No. 4 previously described, being identical with Cor. 3 Florence lode of the same survey.

Thence N. 24° 34' E.

Along line 4-1 Ethel lode, identical with line 3-2 Florence lode both of Sur. No. 4047,

70.67 Intersect the line common to Lot 3 and 6, of the NW $\frac{1}{4}$  of Section 3, T. 2 N. R. 3 E. at S.89°05'W. 306.52 ft. from the SE. and NE. corners respectively of said Lots.

~~XXXXXXXXXXXXXXXX~~

Areas in conflict with patented

ground	Acres
Edna lode in conflict with Lot 4,	0.369
Florence lode in conflict with Lot 6,	0.120
Ethel lode in conflict with Lot 6,	1.116

Report

The public land corners used in connection with this survey were in all instances the original corners, with the exception of the NW. corner of Section 3, which has been replaced with an iron pipe surrounded with a substantial mound of stone, and is being used for private surveys and subdivisions in all of the sections adjacent thereto.

This survey was executed in the interests of private parties, at which time the areas of conflict with Sur. No. 4047 were determined, and were unknown at the time of my making the official survey.

*Harry Jones*  
-----  
U. S. Mineral Surveyor.

# FINAL OATHS FOR SURVEYS.

## LIST OF NAMES.

A list of the names of the individuals employed by Harry E. Jones,

United States Mineral Surveyor, to assist in running, measuring, and marking the lines, corners, and boundaries described in the foregoing field notes of the survey of the mining claim of \_\_\_\_\_

Henry T. Bailey,

known as the Edna, Ethel, Florence, Igo, Plutus, Plutus #2, Rico, and Ugo Lodes.  
and showing the respective capacities in which they acted.

Ben Mollette, \_\_\_\_\_, Chainman.

Wm. Greer, \_\_\_\_\_, Chainman.

\_\_\_\_\_, Axman.

\_\_\_\_\_, Flagman.

## FINAL OATHS OF ASSISTANTS.

We, Ben Mollette,

and Wm. Greer, \_\_\_\_\_, do solemnly swear that we assisted \_\_\_\_\_

Harry E. Jones, \_\_\_\_\_, United States Mineral Surveyor, in marking the corners and surveying the boundaries of the mining claim of \_\_\_\_\_

Henry T. Bailey,

known as the Edna, Ethel, Florence, Igo, Plutus, Plutus #2, Rico and Ugo Lodes.

represented in the foregoing field notes as having been surveyed by said mineral surveyor and under his direction; and that said survey has been in all respects, to the best of our knowledge and belief, faithfully

and correctly executed, and the corner and boundary monuments established according to law and the instruc-

tions furnished by the ~~United States Surveyor-General~~ OFFICE CADASTRAL ENGINEER

Ben Mollette \_\_\_\_\_, Chainman.

William W. Greer \_\_\_\_\_, Chainman.

\_\_\_\_\_, Axman.

\_\_\_\_\_, Flagman.

Subscribed and sworn to by the above-named persons before me this 27th.

day of July, 19 27.

Ralph A. Phillip  
\_\_\_\_\_  
Notary Public.



## FINAL OATH OF U. S. MINERAL SURVEYOR.

21

23

I, Harry E. Jones, U. S. Mineral Surveyor,  
do solemnly swear that, in pursuance of instructions received from the Office Cadastral Engineer,  
at Phoenix, Arizona, dated June 28th. 1927,  
I have, in strict conformity to the laws of the United States, the official regulations and instruc-  
tions thereunder, and the instructions of said Office Cadastral Engineer, faithfully and correctly  
executed the survey of the Mining Claim of \_\_\_\_\_  
Henry F. Bailey, known as the  
Edna, Ethel, Florence, Igo, Flutus, Flutus #2, Rico, and Ugo, lodes  
situate in Winifred Mining District,  
Maricopa County, Arizona, in Section  
3 and 34, Township No. 2&3 N., Range No. 3 East, G&SRB&M.  
and designated as Survey No. 4047, as represented  
in the foregoing field notes, which accurately show the boundaries of said mining claim as distinctly  
marked by monuments on the ground, and described in the attached copy of the location certifi-  
cate, which was received by me from the Office Cadastral Engineer with said instructions, and  
that all corners of said survey have been established and perpetuated in strict accordance with  
the law, official regulations and instructions thereunder; and I do further solemnly swear that the  
foregoing are the true and original field notes of said survey and my report therein, and that the  
labor expended and improvements made upon said mining claim by claimant or his  
grantors are as therein fully stated, and that the character, extent, location, and itemized value  
thereof are specified therein with particularity and full detail, and that no portion of said labor  
or improvements so credited to this claim has been included in the estimate of expenditures upon  
any other claim.

*Harry E. Jones*  
U. S. Mineral Surveyor.

Subscribed and sworn to by the said Harry E. Jones,  
U. S. Mineral Surveyor, before me a notary public in and for the  
County of Maricopa State of Arizona this 27th.  
day of July, 1927.

*Ralph A. Phillips*  
Notary Public.

GOVERNMENT PRINTING OFFICE

My Commission expires June 23rd. 1931.

U. S. SURVEYOR-GENERAL'S FINAL CERTIFICATE ON FIELD NOTES.

Department of the Interior,

PUBLIC SURVEY OFFICE  
OFFICE OF U. S. SURVEYOR-GENERAL,

Phoenix, Arizona.

September 28, 19 27.

I, U. S. Surveyor-General for OFFICE CADASTRAL ENGINEER, at Phoenix, Arizona,

do hereby certify that the foregoing transcript of the Field Notes, return and approval of the survey of the mining claim of

Henry T. Bailey

known as the EDNA, ETHEL, FLORENCE, IGO, PLUTUS, PLUTUS #2, RICO, and UGO lodes

situate in Winifred

Mining District, Maricopa County, Arizona

in Sections 3 and 34, Township No. 283 N., Range No. 3 East, and

designated as Survey No. 4047, has been correctly copied from the originals on file in

this office; that said Field Notes furnish such an accurate description of said mining claim as will, if incorporated into a patent, serve fully to identify the premises, and that such reference is made therein to natural objects or permanent monuments as will perpetuate and fix the locus thereof.

And I further certify that five hundred dollars' worth of labor has been expended or improved or for each of  
ments made upon said mining claims by claimant or his grantors, and that said improvements consist of 22 shafts, 15 cuts, 3 drifts and 2 crosscuts, total value \$9767.25

and that no portion of said labor or improvements has been included in the estimate of expenditures upon any other claim.

I further certify that the plat thereof, filed in the U. S. Land Office at Phoenix, Arizona is correct and in conformity with the foregoing Field Notes.

John D. Adams

United States Surveyor-General for OFFICE CADASTRAL ENGINEER



~~SURVEYOR GENERAL'S~~ CERTIFICATE OF APPROVAL OF FIELD NOTES  
AND SURVEY OF MINING CLAIM

DEPARTMENT OF THE INTERIOR  
OFFICE OF U. S. SURVEYOR GENERAL  
PUBLIC SURVEY OFFICE

Phoenix, Arizona

September 28, 1927.

I, U. S. Surveyor General for OFFICE CADASTRAL ENGINEER, at Phoenix, Arizona,

do hereby certify that the foregoing and hereto attached Field Notes and Return of the Survey of the  
Mining Claim of

Henry T. Bailey

known as the

EDNA, ETHEL, FLORENCE, IGO, PLUTUS, PLUTUS #2, RICO, and UGO lodes

situate in Winifred mining district,

Maricopa County, Arizona

in Sections 3 and 34, Township No. 2 and 3 N., Range No. 3 East

designated as Survey No. 4047

executed by Harry E. Jones, U. S. Mineral

Surveyor, June 30 - July 14, 1927, under my instructions dated


June 28, 1927, have been critically examined and the necessary

corrections and explanations made, and the said Field Notes and Return, and the survey they describe,

are hereby approved. The certified copy of the location certificate filed by the applicant for survey is

on file in this office and a true copy of said certified copy of said location certificate is included and

made a part of the transcript of the field notes.



U. S. Surveyor General for OFFICE CADASTRAL ENGINEER

Copy.

40

orig. filed

42

Phoenix, Arizona,  
July 30, 1929.

District Cadastral Engineer,  
Public Survey Office,  
Federal Bldg.,  
Phoenix, Arizona.

Sir;

Recently in the field execution of Mineral Survey No. 4111, I had occasion to check the tie given to the  $\frac{1}{4}$  corner common to Sections 34 and 35, T. 3 N., R. 3 E. in Mineral Survey No. 4047, and find that the position of said  $\frac{1}{4}$  corner as reported by me to have been in error and the ties from Corners 1, of the Ugo and Plutus lodes are as given in error and are herewith correctly given;

Cor. 1 Ugo lode, the  $\frac{1}{4}$  corner common to Sections 34 and 35, T. 3 N. R. 3 E. bears N. 57° 47' E. 490.66 ft.

Cor. 1. Plutus lode, the  $\frac{1}{4}$  corner common to Sections 34 and 35, T. 3 N., R. 3 E., bears N. 89° 22' 15" E. 960.14 ft.

At the time of making Sur. No. 4047, I made diligent search for said  $\frac{1}{4}$  corner and failed to find same due to the fact that the original GLO corner had no monument alongside, it having been built and fallen down as it falls on the very steep side of a small canyon and would not have been very long until the actual corner would have been lost also, I reset this stone deeper into the ground and fixed a monument alongside same.

Respectfully yours,

Harry E. Jones

U. S. Mineral Surveyor.