

MINERAL SURVEY No. 4073

ARIZONA

Land District.

FIELD NOTES

OF THE SURVEY OF THE MINING CLAIM OF

Thomas J. Laird

KNOWN AS THE

BETH lode

Hessayampa

Mining District,

Yavapai

County,

Arizona.

Section 26, Township 13 N., Range 2 W.

Surveyed under instructions dated August 16, 1928, 19

by J. WILLIAM WAARA

U. S. Mineral Surveyor.

Claim located Oct. 1, 1915

Survey commenced Sept. 9, 1928

Survey completed Sept. 10, 1928

Address of claimant Groom Creek, Arizona.

DATES OF AMENDED LOCATIONS.

--

Total area corrected 3d sec.

MINERAL SURVEY NO. 4073

BETH Lode.

Beginning at Cor. No.1, identical with Cor. No. 4 Arizona Lode Sur. No. 1846, and situated on line 5-6 Illinois lode Sur.No. 671, S.6°-50'E. 127.9 ft from Cor. No.6, a shist stone 8x8x10 inches exposed with a substantial mound of stone alongside; chiseled B 1 4073, A 4 1846 with cross on top for exact corner point, whence,

The Cor to sections 25-26-35-36 T.13 N.R.2 W of the Gila and Salt River Base and Meridian brs. S. 23°-35'E. 1021.7 ft.

No other bearings available.

Thence N. 63°-40'W.

1292.3 TO COR.NO.2, identical with Cor. No. 2 Oakdale lode sur.No. and Cor. No.7 Oakdale lode Sur.No.672 1571, situated on line 4-5 Oriole lode Sur.No.3736, N.32°-03'-30"W. 20.5 feet from Cor. No.5, a granite stone 8x8x10 inches exposed with a substantial mound of stone alongside; chiseled B 2 4073, O 2 1571, with a cross on top for exact corner point,whence,

Cor.No.3 Arizona lode Sur. No. 1846 brs. N.48°-26'W. 129.0 ft.

Thence N.57°-59'E.

35.7 Intersect line 3-4 Arizona lode Sur.No.1846 N.62°-18'W. 1273.9 ft, from Cor. No. 4.

299.8 NORTHWEST CENTER END, a mound of stone.

465.0 Cross road brs north to south.

601.3 TO COR.NO.3 , identical with Cor.No.3 Oakdale lode Sur.No. Cor.No.5 Oakdale lode Sur. No. 672, 1571, /Cor.No.6 Rose lode Sur.No.3332, a granite stone 10x12x12 inches exposed with a substantial mound of stone alongside; chiseled B 3 4073, O 3 1571, R 6 3332 with a cross on top for exact corner point,whence,

An oak tree ~~yellow pine~~ 12 inches in diameter and scribed BxT R 6 3332 brs. S.42°-45'W. 23.6 ft.

Thence S.57°-39'E.

582.6 TO COR.NO.4 identical with Cor. No: 7 Rose lode Sur.No. 3332, a granite boulder 12x12x12 inches exposed with a substantial mound of stone alongside; chiseled B 4 4073,

R 7 3332 with cross on top for exact corner point, whence
A western yellow pine tree 10 inches in diameter
and scribed BxT R 7 3332 brs. N.64°-50'E. 17.4 ft.

Thence N.71°-05'-30"E.

39.6 TO COR.NO.5 identical with Cor. No.1 Rose lode Sur.No.
3332 situated on line 5-6 Chicago lode Sur. No. 669 N.12°-
30'W. 477.5 ft from Cor. No.6, a granite stone 10x14x12
inches exposed with a substantial mound of stone along-
side; chiseled B 5 4073, R 1 3332 with cross on top
for exact corner point,whence,

A western yellow pine tree 6 inches in diameter
and scribed BxT R 1 3332 brs. N.23°-52'E. 2.8 ft.

Thence S.40°-40'E.

490.0 Cross creek, flows northerly.

531.7 Intersect line 1-6 Chicago lode Sur.No. 669, identical
with line 1-6 Illinois lode Sur. No. 671 N.75°-30'E.
251.1 ft. from Cor.Nos.6 respectively.

572.4 TO COR. NO. 6 identical with South Center end, a granite
stone 6x10x24 inches long set twelve inches in the ground
with a substantial mound of stone alongside; chiseled
B 6 4073 with cross on top for exact corner point. whence
The most easterly corner of the location being a
post in mound of stone brs, N.61°E. 302.0 ft.
Thence S.57°-59'W.

20.0 Cross road brs. northwest to southeast.

50.0 Cross creek, flows northerly.

299.8 TO THE PLACE OF BEGINNING. All corners are identical with
their respective locations except where otherwise mentioned.
Variation at all corners 15°-15'E.

LODE LINE

As near as can be determined from the present
developments, the vein on this lode extends as follows
from the discovery;

N.63°-40'W. 907.3 ft and S.63°-40'E. 385.0 ft.

AREAS

BETH Lode

Total area - - - - - acres
12.532

	acres	acres
Area in conflict with		
Arizona lode Sur. No. 1846	0.451	
Chicago Lode Sur.No. 669	1.375	
Illinois lode Sur. No. 671	0.504	

LOCATION

This survey is located in Sec. 26 T.13 N.R.2 W. of the Gila and Salt River Base and Meridian, within the Prescott National Forest, Hassayampa Mining District, Yavapai County State of Arizona.

EXPENDITURE OF FIVE HUNDRED DOLLARS

I hereby certify that the value of the labor and improvements made upon or for the benefit of this location by the claimant or his grantors is not less than five hundred dollars, and that said improvements consist of;

No.1 discovery cut and tunnel, the mouth of tunnel brs. N.63°-40'W. 385.0 ft from Southeast Center end, cut 4x20x12 foot face, tunnel 4x6x50 ft long both bear southwest.

Value	cut	\$100.00
	tunnel	500.00

No.2 a shaft the center of which brs. S.6°-35'E .210 ft. from Cor. No.4, 4x6x10 ft deep.

Value	\$100.00
-------	----------

No.3 a shaft, the center of which brs. S.89°W. 455 ft. from Cor. No.4. 4x6x10 ft deep caved.

Value	\$80.00
-------	---------

No.4 a shaft, the center of which brs. N.88°-10'W. 435 ft from Cor. No.4, 4x6x10 ft deep caved,

Value	\$80.00
-------	---------

No.5 a cut and tunnel, the mouth of cut ~~xx~~ brs. S.2°E. 300 ft. from Cor. No.3, cut 4x25x10 foot face caved, tunnel 4x6x10 completely caved, brs. southeasterly.

Value	cut	\$150.00
	tunnel	\$ 50.00

OTHER IMPROVEMENTS

A house 12x21^{ft}, the northwest corner of which brs. N.73°-45'E. 112 ft. from the northwest center end.

ADJOINING CLAIMS

This lode is bounded on the north by the Rose lode Sur.No.3332 Alvina Clyburn, claimant; on the northeast by the Chicago lode Sur.No. 669; on the southeast by the Illinois lode Sur.No.671; on the southwest by the Arizona lode Sur. No. 1846; and on the northwest by the Sur.No. 672 and Oakdale lode/Sur. No. 1571, all owned by the Chicago Gold Mining Company, claimant.

INSTRUMENT

This survey was made with a Lietz Light Mountain transit No.9503. The courses were deflected from the true meridian as determined by direct solar observations. The distances were measured with a 500 foot steel tape.

REPORT

The southeast corner of Sec.26 T.13 N.R.2 W is an oak tree as described in the field notes of said survey.

Survey No. 669

The corners adjoining this survey are stones properly set and chiseled with the number of the corner and survey. I do not agree with the course and distance of line 5-6 of this survey, nor with its course and distance as reported in Sur.No. 3332
Survey No. 671

The corners adjoining this survey are stones properly set and chiseled with the number of the corner and survey.

Survey No. 672

The corners adjoining this survey are stones properly set and chiseled with the number of the corner and survey. I do not agree with the course and distance of line 5-7 of this survey.

Survey No.1571

The corners adjoining this survey are stones properly set and chiseled with the number of the corner and survey. I do not agree with the course and distance of line 2-3 of this survey.

Survey No. 1846

The corners adjoining this survey are stones properly set and chiseled with the number of the corner and survey, except Cor. No. 3 which was missing but the locus of which I was able to determine from the bearing tree as reported in the return of said survey. I do not agree with the distance of line 3-4 of this survey.

Survey No. 3332

The corners adjoining this survey are stones properly set and chiseled with the number of the corner and survey. I do not agree with; the course and distance of cor. No. 1 of this survey to Cor. No. 6 Chicago lode Sur. No. 669; the course and distance of line 5-6 Chicago lode Sur. No. 669 as reported in this survey. I do not check with the tie of this survey.

Survey No. 3736

The corners adjoining this survey are stones properly set and chiseled with the number of the corner and survey.

The discrepancies found existing between the claim as marked by the location monuments and as described in the location notices are due to errors in the location notices.

The discrepancies between the lines of this survey and prior approved surveys are due to errors in the latter.

William W. W. W.
U. S. Mineral Surveyor

FINAL OATHS FOR SURVEYS.

LIST OF NAMES.

A list of the names of the individuals employed by J. William Weara
 United States Mineral Surveyor, to assist in running, measuring, and marking the lines, corners, and
 boundaries described in the foregoing field notes of the survey of the mining claim of _____
 _____ Thomas J. Laird _____
 known as the BETH (lode) _____
 and showing the respective capacities in which they acted.

_____ Temp Gamel _____, *Chainman.*
 _____, *Chainman.*
 _____, *Arman.*
 _____, *Flagman.*

FINAL OATHS OF ASSISTANTS.

We, Temp Gamel _____
 and _____, do solemnly swear that we assisted J. William
Weara _____, United States Mineral Surveyor, in marking the corners and surveying
 the boundaries of the mining claim of Thomas J. Laird _____

 known as the Beth(lode) _____
 represented in the foregoing field notes as having been surveyed by said mineral surveyor and under his
 direction; and that said survey has been in all respects, to the best of our knowledge and belief, faithfully
 and correctly executed, and the corner and boundary monuments established according to law and the instruc-
 tions furnished by the Office Cadastral Engineer, at Phoenix Arizona. _____

Temp Gamel _____, *Chainman.*
 _____, *Chainman.*
 _____, *Arman.*
 _____, *Flagman.*

Subscribed and sworn to by the above-named persons before me this 12th _____
 day of Sept. _____, 19 28

E. F. Horne

 Notary Public

My commission expires Apr 26, 1931
GOVERNMENT PRINTING OFFICE

FINAL OATH OF U. S. MINERAL SURVEYOR

I, J. William Waara, U. S. Mineral Surveyor, do solemnly swear that, in pursuance of instructions received from the Office Cadastral Engineer, at Phoenix Arizona, dated August 16, 1928, I have, in strict conformity to the laws of the United States, the official regulations and instructions thereunder, and the instructions of said Office Cadastral Engineer, faithfully and correctly executed the survey of the Mining Claim of Thomas J. Laird, known as the BETH (lode), situate in Hassayampa Mining District, Yavapai County, Arizona, in Section 26, Township No. 13 N., Range No. 2 W. and designated as Survey No. 4073, as represented in the foregoing field notes, which accurately show the boundaries of said mining claim as distinctly marked by monuments on the ground, and described in the attached copy of the location certificate, which was received by me from the Office Cadastral Engineer with said instructions, and that all corners of said survey have been established and perpetuated in strict accordance with the law, official regulations and instructions thereunder; and I do further solemnly swear that the foregoing are the true and original field notes of said survey and my report therein, and that the labor expended and improvements made upon said mining claim by claimant or his grantors are as therein fully stated, and that the character, extent, location, and itemized value thereof are specified therein with particularity and full detail, and that no portion of said labor or improvements so credited to this claim has been included in the estimate of expenditures upon any other claim.

J. William Waara
U. S. Mineral Surveyor.

Subscribed and sworn to by the said J. William Waara

U. S. Mineral Surveyor, before me a Notary Public

this 12th day of Sept., 1928

E. J. F. Horne
Notary Public

My commission expires. Apr 26th 1931

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

DEFINING IRREGULAR BOUNDARIES OF

LOT 36, SEC. 26, T. 13 N., R. 2 W.,

GILA & SALT RIVER MERIDIAN, ARIZONA

ORIGINALLY SURVEYED AS THE BETH LODGE,

MINERAL SURVEY NO. 4073, BY J. WILLIAM WAARA,

MINERAL SURVEYOR, SEPTEMBER 9 to 10, 1928,

UNDER ORDER FOR SURVEY DATED AUGUST 16, 1928

SURVEY APPROVED OCTOBER 27, 1928 AND

CANCELED JULY 22, 1968 BY THE

STATE DIRECTOR, ARIZONA

Of the _____ Meridian,

In the State of _____

EXECUTED BY

Under special instructions dated _____, 19____, which provided for the surveys
included under Group Number _____, approved _____,
and assignment instructions dated _____, 19____.

Survey commenced _____, 19____

Survey completed _____, 19____

MINERAL SURVEY NO. 4073

BETH Lode.

Beginning at Cor. No.1, identical with Cor. No. 4 Arizona Lode Sur. No. 1846, and situated on line 5-6 Illinois lode Sur.No. 671, S.6°-50'E. 127.9 ft from Cor. No.6, a shist stone 8x8x10 inches exposed with a substantial mound of stone alongside; chiseled B 1 4073, A 4 1846 with cross on top for exact corner point, whence,

The Cor to sections 25-26-35-36 T.13 N.R.2 W of the Gila and Salt River Base and Meridian brs. S. 23°-35'E. 1021.7 ft.

No other bearings available.

Thence N. 63°-40'W.

1292.3 TO COR.NO.2, identical with Cor. No. 2 Oakdale lode sur.No. and Cor. No.7 Oakdale lode Sur.No.672 1571, situated on line 4-5 Oriole lode Sur.No.3736, N.32°-03'-30"W. 20.5 feet from Cor. No.5, a granite stone 8x8x10 inches exposed with a substantial mound of stone alongside; chiseled B 2 4073, O 2 1571, with a cross on top for exact corner point,whence,

Cor.No.3 Arizona lode Sur. No. 1846 brs. N.48°-26'W. 129.0 ft.

Thence N.57°-59'E.

35.7 Intersect line 3-4 Arizona lode Sur.No.1846 N.62°-18'W. 1273.9 ft, from Cor. No. 4.

299.8 NORTHWEST CENTER END, a mound of stone.

465.0 Cross road brs north to south.

601.3 TO COR.NO.3 , identical with Cor.No.3 Oakdale lode Sur.No. Cor.No.5 Oakdale lode Sur. No. 672, 1571, /Cor.No.6 Rose lode Sur.No.3332, a granite stone 10x12x12 inches exposed with a substantial mound of stone alongside; chiseled B 3 4073, O 3 1571, R 6 3332 with a cross on top for exact corner point,whence,

An oak tree ~~marked~~ 12 inches in diameter and scribed BxT R 6 3332 brs. S.42°-45'W. 23.6 ft.

Thence S.57°-39'E.

582.6 TO COR.NO.4 identical with Cor. No. 7 Rose lode Sur.No. 3332, a granite boulder 12x12x12 inches exposed with a substantial mound of stone alongside; chiseled B 4 4073,

R 7 3332 with cross on top for exact corner point, whence

A western yellow pine tree 10 inches in diameter and scribed BxT R 7 3332 brs. N.64°-50'E. 17.4 ft.

Thence N.71°-05'-30"E.

39.6 TO COR.NO.5 identical with Cor. No.1 Rose lode Sur.No. 3332 situated on line 5-6 Chicago lode Sur. No. 669 N.12°-30'W. 477.5 ft from Cor. No.6, a granite stone 10x14x12 inches exposed with a substantial mound of stone alongside; chiseled B 5 4073, R 1 3332 with cross on top for exact corner point,whence,

A western yellow pine tree 6 inches in diameter and scribed BxT R 1 3332 brs. N.23°-52'E. 2.8 ft.

Thence S.40°-40'E.

490.0 Cross creek, flows northerly.

531.7 Intersect line 1-6 Chicago lode Sur.No. 669, identical with line 1-6 Illinois lode Sur. No. 671 N.75°-30'E. 251.1 ft. from Cor.Nos.6 respectively.

572.4 TO COR. NO. 6 identical with South Center end, a granite stone 6x10x24 inches long set twelve inches in the ground with a substantial mound of stone alongside; chiseled B 5 4073 with cross on top for exact corner point. whence The most easterly corner of the location being a post in mound of stone brs, N.61°E. 302.0 ft. Thence S.57°-59'W.


20.0 Cross road brs. northwest to southeast.

50.0 Cross creek, flows northerly.

299.8 TO THE PLACE OF BEGINNING. All corners are identical with their respective locations except where otherwise mentioned. Variation at all corners 15°-15'E.

I HEREBY CERTIFY that the above field notes, required to completely identify and describe the irregular boundaries of lot 36, Section 26, Township 13 North, Range 2 West, Gila and Salt River Meridian, Arizona, are a true and literal copy of the field notes of the ground survey of the BETH lode, Mineral Survey No. 4073, abstracted from the original record which is on file in the Land Office at Phoenix, Arizona, as of this date.

Date JUL 2 1968



State Director

OFFICE CADASTRAL ENGINEER'S FINAL CERTIFICATE ON FIELD NOTES

Department of the Interior

PUBLIC SURVEY OFFICE

Phoenix, Arizona,

October 27, 19 28

I, Office Cadastral Engineer at Phoenix, Arizona,

do hereby certify that the foregoing transcript of the Field Notes, return and approval of the survey of the mining claim of

Thomas J. Laird

known as the BETH lode

situate in Hassayampa

Mining District Yavapai County Arizona

in Section 26, Township No. 13 N., Range No. 2 W., and

designated as Survey No. 4073, has been correctly copied from the originals on file in

this office; that said Field Notes furnish such an accurate description of said mining claim as will, if incorporated into a patent, serve fully to identify the premises, and that such reference is made therein to natural objects or permanent monuments as will perpetuate and fix the locus thereof.

I further certify that Five Hundred Dollars worth of labor has been expended or improvements made upon, or for the benefit of, each location embraced in said mining claim by claimant

or his grantors,

and that said improvements consist of

2 cut and tunnels and 3 shafts, total value \$1060.

and that no portion of said labor or improvements has been included in the estimate of expenditures upon any other claim.

I further certify that the plat thereof, filed in the U. S. Land Office at Phoenix, Arizona is correct and in conformity with the foregoing Field Notes.

John D. Adams Office Cadastral Engineer.

CERTIFICATE OF APPROVAL OF FIELD NOTES AND SURVEY OF
MINING CLAIM

DEPARTMENT OF THE INTERIOR
PUBLIC SURVEY OFFICE

At Phoenix, Arizona,

..... October 27, 192 8

I, Office Cadastral Engineer at Phoenix, Arizona,

do hereby certify that the foregoing and hereto attached Field Notes and Return of the Survey of the
Mining Claim of

Thomas J. Laird

....., known as the

BETH lode

situate in Hassayampa mining district,

Yavapai County, Arizona,

in Section 26, Township No. 13 N., Range No. 2 W.

....., designated as Survey No. 4073

executed by J. William Waara, U. S. Mineral

Surveyor, September 9 - 10, 1928, under my instructions dated


August 16, 1928, have been critically examined and the necessary

corrections and explanations made, and the said Field Notes and Return, and the Survey they describe,

are hereby approved. The certified copy of the location certificate filed by the applicant for survey is

on file in this office and a true copy of said certified copy of said location certificate is included and

made a part of the transcript of the field notes.


Office Cadastral Engineer.



RECEIVED
BUREAU OF
LAND MANAGEMENT
DEPARTMENT OF THE INTERIOR

1
IN REPLY REFER TO:
9183.3 E

BUREAU OF LAND MANAGEMENT

1968 JUL 26 AM 8 56 3 State Office
3022 Federal Building
Phoenix, Arizona 85025

LAND OFFICE
PHOENIX, ARIZONA

July 22, 1968

Memorandum

To : Land Office Manager, Arizona
From : State Director, Arizona
Subject: Mineral Survey No. 4073

This memorandum cancels the survey of the Beth lode claim of Mineral Survey No. 4073. A notation should be made on the plat of M. S. 4073 that the survey of the Beth lode claim has been canceled by memorandum dated July 22, 1968. The plat and field notes should remain in the files. The attached field notes should be made a part of the original notes.

By Relinquishment of Mining Claim form dated April 19, 1968, Noah and Velma I. Berry relinquished to the United States all right, title and interest in and to the Beth lode claim.

Attachment

cc: Director
(w/copy of Field Notes)