

8-6-30
10-18-30
10-27-30

1

4-687

MINERAL SURVEY No. 4107

ARIZONA Land District.

FIELD NOTES

OF THE SURVEY OF THE MINING CLAIM OF

SHELDON MINING COMPANY

KNOWN AS THE

MARY MAY, M & S, M & S NO.1, COPPER LODE, COPPER LODE NO. 1, COPPER LODE NO.2, COPPER LODE NO.3, and COPPER LODE NO.4 lodes

WALKER Mining District,

Yavapai County, Arizona.

Section 19, 20 & 30, Township 12 1/2 N., Range 1. W. unsurveyed

Surveyed under instructions dated June 11 & July 10, 1929

by J. WILLIAM WAARA U. S. Mineral Surveyor.

Claim located See location notices, 19
Survey commenced July 3, 1929
Survey completed May 19, 1930
Address of claimant O'SULLIVAN & MORGAN Attys.
Prescott Arizona.

DATES OF AMENDED LOCATIONS.

Feet

MINERAL SURVEY NO. 4107

Mary May lode.

Beginning at Cor. No.1, a granite stone 8x10x26 inches long set twelve inches in the ground with a substantial mound of stone alongside; chiseled M M 1 4107 with cross on top for exact corner point, whence,

The S.E. Cor Sec. 32 T.13 N.R.1 W of the Gila and Salt River Base and Meridian brs. N.60°-06'-15"E. 5909.2 feet.

A granite boulder 3x2x2 feet exposed and chiseled BxR M M 1 4107 brs. N.24°-14'W. 25.1 feet.

Cor. No.3 Champion lode Sur. No. 1354 brs. S.52°-05'W. 1047.8 feet.

Thence S.42°-18'W.

1039.9 Intersect line 2-3 Champion Lode Sur.No.1354, identical with line 1-4 Short Cut lode Sur. No. 1355, S.45°-20'E. 178.2 feet from Cor. No.3 Champion lode and 12.2 feet from Cor. No.4 Short Cut lode.

1190.4 Intersect line 2-3 Short Cut lode Sur.No.1355, identical with line 1-4 Shelton lode Sur. No. 1355, S.45°-30'E.

1491.6 34.0 feet from Cor.Nos. 3 and 4 respectively. Cor.No.3 said Short Cut lode brs. S.50°35'W.151.3 ft.from Cor.No.4 thereof. TO COR. NO.2, identical with Cor. No.1 Copper lode of this

survey, a granite boulder 3x2x3 feet exposed with a substantial mound of stone alongside; chiseled M M 2, C L 1, 4107 with cross on northwest face for exact corner point, whence,

Cor.No.4 Shelton lode Sur. No.1355 brs. N.35°-53'E. 304.4 feet.

Thence N.53°-00'W.

90.5 Intersect line 3-4 Shelton lode Sur. No. 1355, S.52°-32'W. 315.9 feet from Cor. No.4.

104.4 SOUTHWEST CENTER END, a mound of stone.

234.4 Northeast center end Copper Lode, this survey.

404.4 TO COR. NO.3 identical with Cor. No.6 Copper Lode, Cor.

Feet

1 Copper Lode No.1 and Cor. No.2 M & S lode all of this survey, a granite stone 12x12x26 inches long set twelve inches in the ground with a substantial mound of stone alongside; chiseled M M 3, C L 6, C L 1 1, M S 2 4107 with cross on top for exact corner point, whence,

A granite reef 4x4x2 feet exposed and chiseled BxR M M 3 4107 hrs. N.87°-04'W. 23.5 feet.

Thence N.45°-04'E.

1331.9 Intersect the southwesterly end line of the Mascot lode unsurveyed, S.85°-40'E. 20.0 feet from the Southwest center end monument of said lode.

1500.0 TO COR. NO.4 identical with Cor. No.1 M & S lode of this survey, a granite stone 8x10x24 inches long set twelve inches in the ground with a substantial mound of stone alongside; chiseled M M 4, M S 1 4107 with cross on top for exact corner point, whence,

~~The most westerly corner of the Mascot lode Unsurveyed, hrs. N.83°-33'W. 247.1 feet, whence the Southwest Center end of said lode hrs. S.36°-20'E. 180.0 ft.~~

Thence S.53°-00'E.

236.0 Intersect the southwesterly end line of the Mascot lode unsurveyed, S.85°-40'E. 328.4 feet from the southwesterly end center of said lode ~~(and 308.4 feet from its intersection with line 3-4 of this lode.)~~

247.5 Intersect line 3-4 Champion lode Sur. No.1354, N.47°-33'E. 1029.1 feet from Cor. No.3.

300.0 NORTHEAST CENTER END, a mound of stone.

331.7 TO THE PLACE OF BEGINNING. All corners are identical with their respective locations. Variation at all corners 14°-30'E.

M & S lode.

Beginning at Cor. No.1 identical with Cor. No.4 Mary May lode of this survey, previously described, whence,

The S.E. Cor. Sec. 32 T.13 N.R.1 W. hrs. N.62°-59'50"E 6047.6 feet.

Feet

The most westerly corner of the Mascot lode, unsurveyed, brs. N. 83° 33' W. 247.1 feet, whence the Southwest Center end of said lode brs. S. 36° 20' E. 180 ft. Thence S. 45°-04' W.

168.1 Intersect the southwesterly end line of the Mascot lode unsurveyed, S. 85°-40' E. 20.0 feet from the southwest center end monument of said lode.

1500.0 TO COR. NO. 2 identical with Cor. No. 3 Mary May lode, Cor. No. 6 Copper Lode and Cor. No. 1 Copper Lode No. 1, previously described.

Thence N. 53°-00' W.

190.7 Northeast center end Copper Lode No. 1, of this survey.

302.0 SOUTHWEST CENTER END, a mound of stone.

490.7 Cor. No. 4 Copper Lode No. 1 identical with Cor. No. 1 Copper Lode No. 4 of this survey.

530.5 Northeast center end, Copper Lode No. 4 of this survey.

600.6 TO COR. NO. 3 identical with Cor. No. 2 M & S No. 1 lode of this survey, a granite stone 6x14x24 inches long set twelve inches in the ground with a substantial mound of stone alongside; chiseled M S 3, M S 1 2 4107 with cross on top for exact corner point.

No bearings available.

Thence N. 44°-55' E.

1397.3 TO COR. NO. 4 identical with Cor. No. 1 M & S No. 1 lode of this survey, a granite stone 6x8x24 inches long set twelve inches in the ground with a substantial mound of stone alongside; chiseled M S 4, M S 1 1 4107 with cross on top for exact corner point, whence,

A granite rock in place 4x6x4 feet exposed and chiseled Bx R M S 1 1 4107 brs. S. 1°-18' W. 52.0 ft.

Thence N. 47°-30' E.

56.3 Intersect the southwesterly end line of Clear Title lode unsurveyed, N. 41°-35' W. 403.7 ft. from the most southerly corner.

102.7 TO COR. NO. 5, a granite stone 6x8x24 inches long set twelve inches in the ground with a substantial mound of stone alongside; chiseled M S 5 4107 with cross on top for exact corner point, whence,

A diorite reef 4x2x2 feet exposed and chiseled Bx R M S 5 4107 brs. S. 22°-37' E. 20.2 feet.

The most southerly corner of the Clear Title lode

Feet	unsurveyed, brs. S.35°-02'E. 407.1 feet. The location monument being a substantial mound of stone brs. N.53°-00'W. 5.0 ft. Thence S.53°-00'E.
298.1	^A NORTHEAST CENTER END, a mound of stone.
343.2	Intersect the southeasterly side line of the Clear Title lode identical with northwesterly side line of the Mascot lode both unsurveyed, N.17°-40'E. 133.1 feet from the most southerly corner of the Clear Title lode identical with the most westerly corner of the Mascot lode.
600.1	TO THE PLACE OF BEGINNING. All corners are identical with their respective locations, except where otherwise mentioned. Variation at all corners 14°-30'E.
	<u>M & S No.1 lode.</u> Beginning at Cor. No.1 identical with Cor. No.4 M & S lode of this survey previously described, whence The S.E.Cor. Sec. 32 T.13 N.R.1 W brs. N.67°-33'-45"E. 6430.0 feet. Thence S.44°-55'W.
1397.3	TO COR. NO.2 identical with Cor.No.3 M & S lode of this survey previously described and situated on line 1-4 Copper Lode No.4 of this survey. Thence N.53°-00'W.
29.9	Cor.No.4 Copper Lode No.4 identical with Cor. No.1 Copper Lode No.2,, of this survey.
300.0	SOUTHWEST CENTER END, a mound of stone.
329.9	Northeast Center end, Copper Lode No.2.
598.3	TO COR. NO. 3 situated on line 1-4 Copper Lode No.2, a granite stone 8x8x26 inches long set twelve inches in the ground with a substantial mound of stone alongside; chiseled M'S 1 3 4107 with cross on top for exact corner point. No bearings available. Thence N.52°-02'E.
1432.9	TO COR.NO.4, a granite rock in place 2x3x2 feet exposed with a substantial mound of stone alongside; chiseled M S 1-4 4107 with cross on top for exact corner point. No bearings available. Thence S.53°-00'E.
119.3	NORTHEAST CENTER END, a mound of stone.

Feet

419.3 TO THE PLACE OF BEGINNING. All corners are identical with their respective locations. Variation at all corners 14°-30'E.

COPPER LODE

Beginning at Cor. No.1 identical with Cor. No.2 Mary May lode of this survey, previously described, whence,

The S.E.Cor. Sec. 32 T.13 N.R.1 W brs. N. 56°-32'-40" E. 7344.1 feet.

Thence S.57°-56'W.

926.7 TO COR. NO. 2 identical with Cor.No.3 Shelton lode and Cor.No.4 American Flag lode both Sur.No. 1355, a granite stone 6x14x12 inches exposed with a substantial mound of stone alongside; chiseled A F 4 1355, S 3 1355, C L 2 4107 with cross on top for exact corner point.

No bearings available.

Thence S.22°-57'W.

327.86 Intersect line 4-1 Independence No.2 lode S ur. No. 4126,

333.9 TO COR. NO.3, situated on line 1-2 and 4-3 Independence No. 2 and Independence lodes, Sur. No. 4126, S.44°-46'W. 5.6 feet from Cor. Nos. 1 and 4 respectively, and ~~being~~ identical with Cor. No.3 American Flag lode

Sur. No. 1355, a granite stone 6x12x14 inches exposed with a substantial mound of stone alongside; chiseled A F 3 1355, C L 3 4107 with cross on top for exact corner point.

No bearings available.

Thence S.35°-55'W.

290.3 TO COR.NO.4, a granite stone 8x8x24 inches long set twelve inches in the ground with a substantial mound of stone alongside; chiseled C L 4 4107 with cross on top for exact corner point.

No bearings available.

Thence N. 53°-00'W.

45.1 Intersect line 3-4 Independence lode Identical with line 1-2 Independence No.2 lode both Sur. No. 4126, S.44°-46'w.

Feet

~~298.5 feet from Cor.Nos.4 and 1 respectively, (and ^{292.9} ~~287.5~~ from Cor. No.3 American Flag lode Sur. No.1355, situated on said line.~~

233.9 SOUTHWEST CENTER END, a mound of stone.

403.9 TO COR.NO.5 identical with Cor. No.2 Copper Lode No.1 of this survey, a granite stone 8x8x26 inches long set twelve inches in the ground with a substantial mound of stone alongside; chiseled C L 5, C L 1 2 4107 with cross on top for exact corner point,whence,

Cor.No.1 Independence No.2 lode Sur.No.4126 brs. S.89°-32'E. 496.8 feet.

Thence N.46°-22'E.

348.1 Intersect line 4-1 Independence No.2 lode Sur. No. 4126, S.45°-04'E. 254.2 feet from Cor. No.4.

1499.8 TO COR. NO.6 identical with Cor. No.1 Copper Lode No.1, Cor. No. 2 M & S lode and Cor. No.3 Mary May lode all of this survey, previously described.

Thence S.53°-00'E.

170.0 NORTHEAST CENTER END, a mound of stone.

300.0 Southwest center end Mary May lode of this survey.

313.9 Intersect line 3-4 Shelton Lode Sur.No. 1355, N.52°-32'E. 898.4 feet from Cor. No.3.

404.4 TO THE PLACE OF BEGINNING. All corners are identical with their respective locations except corners No. 2 and 3. these being within the location. Variation at all corners 14°-30'E.

COPPER LODE NO.1.

Beginning at Cor. No.1 identical with Cor. No. 2 M & S lode, Cor. No. 3 Mary May lode and Cor. No. 6 Copper Lode, all of this survey and previously described, whence,

The S.E.Cor. Sec. 32 T.13 N.R.1 W. brs. N.59°-27'-45"E. 7490.4 feet.

Thence S.46°-22'W.

1151.7 Intersect line 4-1 Independence No.2 lode Sur. No. 4126, S.45°-04'E. 254.2 feet from Cor. No.4

Feet	
1499.8	TO COR. NO.2 identical with Cor.No.5 Copper Lode of this survey, previously described. Thence N.53°-00'W.
190.7	SOUTHWEST CENTER END, a mound of stone.
210.2	Cor.No.1 Copper Lode No.3 of this survey.
235.6	Intersect line 3-4 Independence No.2 lode Sur.No.4126, S.43°-06'W. 380.8 feet from Cor, No.4.
490.0	TO COR. NO. 3 situated on line 1-4 Copper Lode No.3 of this survey, and identical with Cor. No. 2 Copper Lode No. 4 of this survey, a porphyry stone 8x14x26 inches long set twelve inches in the ground with a substantial mound of stone alongside; chiseled CL 1 3, C L 4 2 4107 with cross on top for exact corner point. No bearings available. Thence N.46°-21'E.
1499.8	TO COR. NO.4 situated on line 2-3 M & S lode of this survey, and identical with Cor. No.1 Copper Lode No.4 of this survey, a granite rock in place 2x1x1 foot exposed with a substantial mound of stone alongside; chiseled C L 1-4 C L 4-1,4107 with cross on top for exact corner point. No bearings available. Thence S.53°-00'E.
188.7	Southwest Center end, M & S lode of this survey.
300.0	NORTHEAST CENTER END, a mound of stone.
490.7	TO THE PLACE OF BEGINNING. All corners are identical with their respective locations. Variation at all corners 14°-30'E.
	<u>COPPER LODE NO.4</u>
	Beginning at Cor. No.1 situated on line 2-3 M & S lode of this survey, and identical with Cor. No. 4 Copper Lode No.1 of this survey, previously described, whence, The S.E.Cor. Sec. 32 T.13 N,R.1 W. brs. N. 62°-50'-30"E. 7689.9 feet. Thence S.46°-21'W.

Feet
 1499.8 TO COR. NO.2 situated on line 4-1 Copper Lode No.3, and identical with Cor. No. 3 Copper Lode No.1 of this survey previously described.
 No bearings available.
 Thence N.53°-00'W.
 .40.4 SOUTHWEST CENTER END, identical with Northeast center end Copper Lode No.3 of this survey, a mound of stone.
 140.4 TO COR. NO. 3 situated on line 4-1 Copper Lode No. 3 of this survey and identical with Cor. No. 2 Copper Lode No.2, a granite stone 6x8x24 inches long set twelve inches in the ground with a substantial mound of stone alongside; chiseled C L 4 3, C L 2 2 4107 with cross on top for exact corner point.
 No bearings available.
 Thence N.46°-22'E.
 1499.8 TO COR.NO.4, situated on line 3-2 M & S No.1 lode of this survey and identical with Cor. No. 1 Copper Lode No.2, a granite stone 8x8x26 inches long set twelve inches in the ground with a substantial mound of stone alongside; chiseled C L 4 4, C L 2 1 4107 with cross on top for exact corner point.
 No bearings available.
 Thence S.53°-00'E.
 29.9 Cor.No.2 M & S No.1 lode identical with Cor. No.3 M & S lode, both of this survey.
 1100.0 NORTHEAST CENTER END, a mound of stone.
 -139.8 TO THE PLACE OF BEGINNING. All corners are identical with their respective locations. Variation at all corners 14°-30'E.

COPPER LODE NO.2

Beginning at Cor. No.1 situated on line 2-3 3 M & S No.1 lode of this survey, and identical with Cor. No.4 Copper Lode No.4 of this survey, previously described, whence,

The S.E.Cor. Sec. 32 T.13 N.R.1 W. brs. N.63°-46'-

Feet

30"E. 7751.7 feet.

Thence S.46°-22'W.

1499.8 TO COR. NO. 2 situated on line 4-1 Copper Lode No.3, and identical with Cor. No. 3 Copper Lode No.4 of this survey, previously described.

Thence N.53°-00'W.

220.2 Cor. No. 4 Copper Lode No.3 of this survey.

300.0 SOUTHWEST CENTER END, a mound of stone.

597.8 TO COR. NO.3, a granite stone 6x8x24 inches long set twelve inches in the ground, with a substantial mound of stone alongside; chiseled C L 2 3 4107 with cross on top for exact corner point.

No bearings available.

Thence N.46°-21'E.

1499.8 TO COR. NO.4, a granite stone 8x12x24 inches long set twelve inches in the ground with a substantial mound of stone alongside; chiseled C L 2 4 4107 with cross on top for exact corner point.

No bearings available.

Thence S.53°-00'E.

29.4 Cor. No.3 M & S No.1 lode of this survey.

297.8 NORTHEAST CENTER END, a mound of stone.

327.7 Southwest center end M & S No.1 lode of this survey.

597.8 TO THE PLACE OF BEGINNING. All corners are identical with their respective locations. Variation at all corners 14°-30'E.

COPPER LODGE NO.3

Beginning at Cor. No.1 situated on line 2-3 Copper Lode No.1 of this survey, a granite stone 4x8x26 inches long set twelve inches in the ground with a substantial mound of stone alongside; chiseled C L 3 1 4107 with cross on top for exact corner point, whence,

The S.E.Cor. Sec. 32 T.13 N.R.1 W. brs. N.58°-32'-20"E. 9031.35 feet.

A granite reef 3x2x2feet exposed and chiseled BxR C L 3 1 4107 brs. S.69°-32'W. 10.2 ft.

Feet	
	Cor.No.4 Independence No.2 lode Sur. No.4126 brs. N.39°-17'E. 378.9 feet.
	Thence S.35°-26'W.
760.0	Cross gulch, flows southeasterly.
852.9	TO COR. NO.2 identical with SOUTHWEST CENTER END, a granite stone 6x8x24 inches long set twelve inches in the ground with a substantial mound of stone alongside; chiseled CL3 2 4107 with cross on top for exact corner point, whence,
	The most southerly location monument of this lode brs. S.53°-00'E. 315 feet.
	Thence N.53°-00'W.
139.4	TO COR. NO.3, a granite stone 8x10x26 inches long set twelve inches in the ground with a substantial mound of stone alongside; chiseled C L 3 3 4107 with cross on top for exact corner point, whence,
	A granite rock in place 2x2x1 foot exposed and chiseled Bx R C L 3 3 4107 brs. S.42°-14'E. 39.0 ft.
	Thence N.4°-58'E.
15.3	Intersect line 3-4 Independence No.2 lode Sur.No.4126, S.43°-06'W. 1225.2 feet from Cor. No.4.
33.3	Intersect the southeasterly side line of the Brunswick lode unsurveyed, S.25°-35'W. 65.3 feet from the side monument of said claim, whence the most easterly corner
	of said claim brs. N.17°-10'E. 682.4 feet.
334.0	Cross gulch, flows southeasterly.
811.4	Intersect the northeasterly end line of the Brunswick lode unsurveyed, N.68°-20'W. 174.6 feet from the most easterly corner of said claim..
1005.6	TO COR. NO.4 situated on line 2-3 Copper Lode No.2 of this survey, a granite stone 6x12x24 inches long set twelve inches in the ground with a substantial mound of stone alongside; chiseled C L 3 4 4107 with cross on top for exact corner point, whence,
	The most easterly corner of the Brunswick lode unsurveyed, brs. S.29°-25'E. 296.1 feet.
	Thence S.53°-00'E.
220.2	Cor.No.2 Copper Lode No.2 identical with Cor. No.3 Copper

Feet
 Lode No. 4 of this survey.
 320.2 NORTHEAST CENTER END, a mound of stone.
 360.6 Cor. No. 2 Copper Lode No. 4 identical with Cor. No. 3 Copper Lode No. 1 of this survey.
 615.0 Intersect line 3-4 Independence No. 2 lode Sur. No. 4126, S. 43°-06'W. 380.8 feet from Cor. No. 4.
 640.4 TO THE PLACE OF BEGINNING. All corners are identical with their respective locations except where otherwise mentioned. Variation at all corners 14°-30'E.

LODE LINES

As near as can be determined from the present developments, the veins on the respective lodes extend as follows from their discoveries;

Mary May Lode

N. 45°-04'E. 1365.0 ft. and S. 45°-04'W. 135.0 ft.

M & S lode

N. 45°-04'E. 1160.0 ft and S. 45°-04'W. 340.0 ft.

M & S No. 1 Lode

N. 44°-55'E. 1107.3 ft and S. 44°-55'W. 290.0 ft.

COPPER LODE

N. 46°-22'E. 220.0 ft. and S. 46°-22'W. 1279.8 ft.

COPPER LODE No. 1

N. 46°-22'E. 530.0 ft. and S. 46°-22'W. 969.8 ft.

COPPER LODE No. 4

N. 46°-22'E. 1469.8 ft and S. 46°-22'W. 30.0 ft.

COPPER LODE NO. 2

N. 46°-22'E. 335.0 ft and S. 46°-22'W. 1164.8 ft.

COPPER LODE No. 3

N. 15°-03'E. 100.0 ft. and S. 15°-03'W. 819.0 ft.

AREAS

MARY MAY LODE

Total area - - - - -	acres	acres
		12.549
Area in conflict with		
3 Shelton lode Sur. No. 1355 - - -	0.434	
3 Champion lode Sur. No. 1354 - - -	3.103	
3 Short Cut lode Sur. No. 1355 - - -	0.080	
3 Mascot lode, Unsurveyed - - -	0.451	

M & S Lode

	acres	acres
6 Total area - - - - -		20.542
Area in conflict with		
9 Mascot lode unsurveyed	0.774	
9 Clear Title lode unsurveyed	0.710	

M & S No.1 lode

6 Total area - - - - -		16.165
Area in conflict with		

COPPER LODE

4 Total area - - - - -		10.785
Area in conflict with		
8 Shelton lode Sur. No. 1355	0.899	
7 Independence lode Sur.No.4126	0.150	
2 Independence No.2 lode Sur.No.4126	2.599	

COPPER LODE NO.1

4 Total area - - - - -		16.658
Area in conflict with		
2 Independence No.2 lode Sur.4126	2.039	

COPPER LODE NO.4

5 Total area - - - - -		4.760
------------------------	--	-------

COPPER LODE NO.2

5 Total area - - - - -		20.309
------------------------	--	--------

COPPER LODE NO.3

Total area - - - - -		7.543
Area in conflict with		
1 Independence No.2 lode Sur.No.4126	1.616	
1 Brunswick lode, unsurveyed	1.530	

LOCATION

This survey is located in Sections 19-20- & -30 T.12½ N.R.1 W unsurveyed, of the Gila and Salt River Base and Meridian within the Prescott National Forest, Walker Mining District, Yavapai County, State of Arizona.

EXPENDITURE OF FIVE HUNDRED DOLLARS

I hereby certify that the value of the labor and improvements made upon or for the benefit of the several locations embraced in this survey by the claimant or his grantors is not less than five hundred dollars for each claim and that said improvements consist of;

MARY MAY lode

No.1 discovery shaft, the center of which bears N.45°-04'E. 135 feet from the Southwest center end, 4x6x8

feet deep.

Value \$80.00

To be accredited to this lode is an equal undivided 1/34th interest in Improvement No. 1 Champion lode Sur. No. 1354.

Value \$2140.00

M & S lode

No.1 discovery shaft, the center of which brs. N.45°-04'E. 340.0 ft from the Southwest center end. 4x6x8 ft deep.

Value \$80.00

To be accredited to this lode is an equal undivided 1/34th interest in Improvement No.1 Champion lode Sur.No. 1354.

Value \$2140.00

M & S No.1 lode

No.1 discovery shaft, the center of which brs. N.44°-55'E. 290 feet from the Southwest center end, 4x6x8 feet deep.

Value \$80.00

No.2 a shaft, the center of which brs. N.53°-30'E. 290 feet. from the southwest center end, 4x6x12 ft. deep.

Value \$120.00

To be accredited to this lode is an equal undivided 1/34th interest in Improvement No.1 Champion lode Sur. No. 1354.

Value \$2140.00

COPPER LODGE

No.1 discovery cut, the mouth of which brs. S.46°-22'W. 220 feet from the northeast center end, 4x15x10 foot face, brs. southwest.

Value \$100.00

To be accredited to this lode is an equal undivided 1/34th interest in Improvement No. 1 Champion lode Sur. No. 1354.

Value \$2140.00

COPPER LODGE NO.1

No.1 discovery cut, the mouth of which brs. S. 46°-22'W. 530 feet from the Northeast Center end, 4x15x10 foot face, brs. southwest.

Value \$100.00

To be accredited to this lode is an equal undivided 1/34th interest in Improvement No. 1 Champion lode

Sur. No. 1354.

Value \$2140.00

COPPER LODE No. 4

No. 1 discovery cut, the face of which hrs. N. 46°-22'E. 30.0 ft from southwest center end, 4x25x10 foot face hrs. north.- Value \$150.00

To be accredited to this lode is an equal undivided 1/34th interest in Improvement No. 1 Champion lode

Sur. No. 1354.

Value \$2140.00

COPPER LODE No. 2

No. 1 discovery cut, the mouth of which hrs. S. 46°-22'W. 335 feet from the northeast center end, 4x20x10 foot face. hrs. southwest. Value \$150.00

To be accredited to this lode is an equal undivided 1/34th interest in Improvement No. 1 Champion lode

Sur. No. 1354

Value \$2140.00

COPPER LODE NO. 3

No. 1 discovery cut, the face of which hrs. S. 15° 03'W. 100 feet from the northeast center end, 4x12x10 foot face hrs. east, Value \$100.00

To be accredited to this lode is an equal undivided 1/34th interest in Improvement No. 1 Champion lode

Sur. No. 1354.

Value \$2140.00

COMMON IMPROVEMENT

Improvement No. 1 Champion lode Sur. No. 1354, designated as such for brevity in reporting; the center of which hrs. N. 37°-08'W. 369.8 ft. from Cor. No. 1 Ellinor lode Sur. No. 3998, as reported in the Common Improvement report of said survey, is the main shaft of the Sheldon Mining Company, claimants of this survey. The shaft is situated centrally in a group of 34 patented and unpatented claims owned by the company. The shaft was 850 feet deep 1½ compartments and has been enlarged to 2½ compartments and sunk to a depth of 1250 feet. This shaft is so situated that drifts and cross-cuts run from its lower levels will develop all of the claims embraced in this survey as well

as the patented claims upon which it is situated, and other claims the surveys of which are to be reported. I consider the shaft a common improvement and of such a nature as to redound to the benefit of all of the following lode claims;

American Flag, Shelton and Short Cut lodes all Sur.No.1355, Champion, Link and Fortune lodes Sur.No.1354, Eureka lode Sur.No. 1173, Capital lode Sur. No. 1359, First North Extension Capitol lode Sur.No. 3287, Mid-Night Snap lode sur.No. 3655, White House lode Sur. No.2360 Ninety Seven lode Sur. No. 1631, New State, Luther Junior, Eagle, Monroe, The Penn, New Strike, Ellinor, Florence, Willetts, Lovekin, and Dyson lodes Sur. No. 3998, M & S, M & S No.1, Mary May Copper lode Copper Lode No.1, Copper Lode No.2 Copper Lode No.3 Copper Lode No.4, all Sur.No.4107, Grasshopper lode Sur.No. 4105 and Hoover and Ninety Eight lodes Sur.No. 4106, all contiguous claims owned by the claimant of this survey.

The old shaft was enlarged from a 4x9 size to 4x13 feet, total depth of enlarged shaft 850 feet.

Total depth of new shaft 400 feet, size 4x13 ft.

Value, enlarged \$42,500.00

new 30,260.0

To be accredited to each lode of this survey is an equal undivided 1/34th interest in the above mentioned improvement. Value \$2140.00

ADJOINING CLAIMS.

This survey is bounded on the southwest by the Independence, Independence No.2 lodes Sur.No.4126 owned by the Arizona Victory Copper Mines Corporation, and Brunswick lode unsurveyed, owned by Alex Ratcliff; and U.S.Land; on the northwest by U.S.Land, and the Red Dike lode unsurveyed, Frank Ritzel claimant; on the Northeast by U.S.Land, and Clear Title and Mascot lodes unsurveyed, owned by Laura A.Hicks, Sam Dreyer and the Sheldon Mining

Company; on the southeast by the Champion lode Sur.No. 1354, Shelton, Short Cut and American Flag lodes Sur.No. 1355 all owned by the Sheldon Mining Company, and the Independence lode Sur.No.4126 owned by the Arizona Victory Copper Mines Corporation.

INSTRUMENT

This survey was made with a Lietz Light Mountain transit No. 9503, The courses were deflected from the true meridian as determined by direct solar observations. The distances were measured with a 500 foot steel tape.

REPORT

The southeast corner of Sec. 32 T.13 N.R.1 W. is a stone set and chiseled as described in the field notes of said survey. This is the nearest corner of the Public Survey that can be found and identified, diligent search having been made for corners which come within the prescribed limits of this survey.

Sur.No.1354

The corners adjoining this survey are stones properly set and chiseled with the number of the corner and survey. I do not agree with the course and distance of lines 2-3 and 3-4 .

Sur. No. 1355

The corners adjoining this survey are stones properly set and chiseled with the number of the corner and survey. I do not agree with the course and distance of lines 1-4, Short cut lode, 3-4 Shelton lode, & 3-4 American Flag lode.

Sur.No.4126

The corners adjoining this survey are stones properly set and chiseled with the number of the corner and survey.

Unsurveyed lodes

The corners of these lodes are stone monuments of substantially built and proper size.

The discrepancies found existing between the claims as marked by the location monuments and as described in the location notices are due to errors in the location notices.

The discrepancies between the lines of this survey and prior approved surveys are due to errors in the latter.

William Coasa
- U.S. Mineral Surveyor -

FINAL OATHS FOR SURVEYS.

LIST OF NAMES.

A list of the names of the individuals employed by J. WILLIAM WAARA

United States Mineral Surveyor, to assist in running, measuring, and marking the lines, corners, and boundaries described in the foregoing field notes of the survey of the mining claim of SHELDON MINING COMPANY

known as the MARY MAY, M & S, M & S NO.1, COPPER LODE, COPPER LODE NO.1, COPPER LODE NO.2, COPPER LODE NO.3, COPPER LODE NO.4, lodes and showing the respective capacities in which they acted.

Temp Gamel, Chainman.
_____, Chainman.
_____, Axman.
_____, Flagman.

FINAL OATHS OF ASSISTANTS.

~~we~~ I, Temp Gamel

and _____, do solemnly swear that ~~we~~ ^I assisted J. William Waara, United States Mineral Surveyor, in marking the corners and surveying the boundaries of the mining claim of Sheldon Mining Company

known as the MARY MAY, M & S, M & S NO.1, COPPER LODE, COPPER LODE NO.1, COPPER LODE NO.2, COPPER LODE NO.3, COPPER LODE NO.4 lodes represented in the foregoing field notes as having been surveyed by said mineral surveyor and under his direction; and that said survey has been in all respects, to the best of our knowledge and belief, faithfully and correctly executed, and the corner and boundary monuments established according to law and the instructions furnished by the Office Cadastral Engineer, at Phoenix Arizona.

Temp Gamel, Chainman.
_____, Chainman.
_____, Axman.
_____, Flagman.

Subscribed and sworn to by the above-named persons before me this 23

day of July, 19 30
J. C. Bauer.

Notary Public

My commission expires 1/10/33.

FINAL OATH OF U. S. MINERAL SURVEYOR

J. William Waara

I,, U. S. Mineral Surveyor,

do solemnly swear that, in pursuance of instructions received from the Office Cadastral Engineer, at Phoenix Arizona, dated June 11, 1929 & July 10, 1929,

I have, in strict conformity to the laws of the United States, the official regulations and instructions thereunder, and the instructions of said Office Cadastral

Engineer, faithfully and correctly executed the survey of the Mining Claim of

Sheldon Mining Company

known as the MARY MAY, M & S, M & S No.1, COPPER LODE, COPPER LODE NO.1, COPPER LODE NO.2, COPPER LODE NO.3 AND COPPER LODE NO.4 lodes,

situate in Walker Mining District,

Yavapai

County, Arizona.

in Section

19, 20 & 30, Township No. 12 1/2 N., Range No. 1 W. unsur.

and designated as Survey No. 4107, as represented

in the foregoing field notes, which accurately show the boundaries of said mining claim as distinctly marked by monuments on the ground, and described in the attached copy

of the location certificate, which was received by me from the Office Cadastral Engineer with said instructions, and that all corners of said survey have been established

and perpetuated in strict accordance with the law, official regulations and instructions thereunder; and I do further solemnly swear that the foregoing are the true and

original field notes of said survey and my report therein, and that the labor expended and improvements made upon said mining claim by claimant or its

grantors are as therein fully stated, and that the character, extent, location, and itemized value thereof are specified therein with particularity and full detail, and

that no portion of said labor or improvements so credited to this claim has been included in the estimate of expenditures upon any other claim.

J. William Waara
U. S. Mineral Surveyor.

Subscribed and sworn to by the said J. William Waara

U. S. Mineral Surveyor, before me a NOTARY PUBLIC

this 17th

day of July 1930, 1930

J. Bauer
Notary Public

My commission expires 1/10/33.

OFFICE CADASTRAL ENGINEER'S FINAL CERTIFICATE ON FIELD NOTES

Department of the Interior

PUBLIC SURVEY OFFICE

Phoenix, Arizona,

December 6, 1930

I, Office Cadastral Engineer, at Phoenix, Arizona,

do hereby certify that the foregoing transcript of the Field Notes, return and approval of the survey of the mining claim of

Sheldon Mining Company

known as the MARY MAY, M & S, M & S No.1, COPPER LODE, COPPER LODE NO.1, COPPER LODE NO.2, COPPER LODE NO.3, and COPPER LODE NO.4 lodes

situate in Walker

Mining District Yavapai County Arizona

in Sections 19, 20, 30 Township No. 12 1/2 N., Range No. 1 W., Unsur., and

designated as Survey No. 4107, has been correctly copied from the originals on file in

this office; that said Field Notes furnish such an accurate description of said mining claim as will, if incorporated into a patent, serve fully to identify the premises, and that such reference is made therein to natural objects or permanent monuments as will perpetuate and fix the locus thereof.

I further certify that Five Hundred Dollars worth of labor has been expended or improvements made upon, or for the benefit of, each location embraced in said mining claim by claimant or its grantors,

and that said improvements consist of 4 shafts and 5 cuts, value \$960,

and eight 1-34th interests, value \$2140 each, in the

value of improvement No. 1, Champion lode, Sur. No.

1354, total, \$18,080.

and that no portion of said labor or improvements has been included in the estimate of expenditures upon any other claim.

I further certify that the plat thereof, filed in the U. S. Land Office at Phoenix, Arizona, is correct and in conformity with the foregoing Field Notes.

John D. Adams

Office Cadastral Engineer.

CERTIFICATE OF APPROVAL OF FIELD NOTES AND SURVEY OF
MINING CLAIM

DEPARTMENT OF THE INTERIOR
PUBLIC SURVEY OFFICE

At Phoenix, Arizona,

December 6, 1930

I, Office Cadastral Engineer at Phoenix, Arizona,

do hereby certify that the foregoing and hereto attached Field Notes and Return of the Survey of the
Mining Claim of _____

Sheldon Mining Company

_____, known as the
MARY MAY, M & S, M & S No.1, COPPER LODE, COPPER LODE NO. 1,
COPPER LODE NO.2, COPPER LODE NO.3, and COPPER LODE NO. 4 lodes

situate in Walker mining district,

Yavapai County, Arizona

in Section s 19, 20 & 30, Township No. 12 $\frac{1}{2}$ N., Range No. 1 W., Unsur.

_____, designated as Survey No. 4107

executed by J. William Waara, U. S. Mineral

Surveyor, July 3, 1929 - May 19,, 19 30 under my instructions dated

June 11 and July 10, 19 29, have been critically examined and the necessary

corrections and explanations made, and the said Field Notes and Return, and the Survey they describe,

are hereby approved. The certified copy of the location certificate filed by the applicant for survey is

on file in this office and a true copy of said certified copy of said location certificate is included and

made a part of the transcript of the field notes.


Office Cadastral Engineer.