

4-688

MINERAL SURVEY No. 4135

ARIZONA Land District

FIELD NOTES

OF THE SURVEY OF THE MINING CLAIM OF

TOM REED GOLD MINES COMPANY

KNOWN AS THE

DOVER No. 1, DOVER No. 2 and DOVER No. 3 / 10/23

SAN FRANCISCO Mining District,

Mohave County, Arizona

Section 24, Township 19 North, Range 20 West

Surveyed under instructions dated July 2, 1930

By L. H. Foster
U. S. Mineral Surveyor.

Claim located See location notices, 19

Survey commenced July 10, 1930

Survey completed July 20, 1930

Address of claimant's Atty. Louis L. Wallace, Atty for Claimant
Box 246, Kingman, Arizona

DATES OF AMENDED LOCATIONS

see back

1-081

MINERAL SURVEY NO. 2152

Land District

Claim	Located	Amended
Dower No. 1	February 19, 1927	June 18, 1930
Dower No. 2	February 10, 1927	June 18, 1930
Dower No. 3	February 19, 1927	June 18, 1930

SHOW AS THE

Mining District

County

Section

Surveyed under patent law dated July 10, 1900

BY J. J. Young

U.S. Mineral Surveyor

This location was located on

Survey commenced July 10, 1900

Survey completed July 20, 1900

Address of Mineral Surveyor, Jackson, Wyo. for District

Box 211, Jackson, Wyo.

Office of Amended Location

see back

Mineral Survey No. 4135

feet

Dower No. 1 lode

Beginning at Cor. No. 1, identical with Cor. No. 3, Blue Bird lode, Sur. No. 3342.

A redwood post, 4 ins. square, 4 ft. long, with a nail at the exact corner, set 18 ins. in the ground, in a mound of earth and stone, scribed D-1-1-4135-BB-3-3342.

The 1/4 corner between sections 23 and 24, T. 19 N. R. 20 W. G. & S. R. B. & M. bears N. 7° 18' W. 493.76 ft.

Thence N. 58° 44' E.

9.79

To Cor. No. 3, Aztec lode, Sur. No. 3845 and intersect line 1-4, Little Alice lode, Sur. No. 3231, at N. 45° 42' W. 204.60 ft. from Cor. No. 1.

255.81

To the north west end center post of the location.

551.81

To Cor. No. 2, identical with Cor. No. 4, Blue Bird lode, Sur. No. 3342.

A redwood post, 4 ins. square, 4 ft. long, with a nail at the exact corner, set 18 ins. in the ground, in a mound of earth and stone, scribed D-1-2-4135-BB-4-3342.

On line I-4, Dower No. 2 lode, this survey and line 2-3, Templar lode, Sur. No. 3342, at S. 46° 36' E. 218.32 ft. from Cors. No. 1 and 3, respectively.

Cor. No. 2, Aztec lode, Sur. No. 3845, bears N. 46° 36' W. 0.48 ft.

Thence S. 46° 36' E.

1063.48

To Cor. No. 3, identical with Cor. No. 1, Blue Bird lode, Sur. No. 3342.

A redwood post, 4 ins. square, 4 ft. long, with a nail at the exact corner, set 18 ins. in the ground, in a mound of earth and stone, scribed D-1-3-4135-BB-1-3342.

Thence S. 58° 44' W.

253.30

To Cor. No. 1, Aztec Center South East lode, Sur. No. 3199, ^{whence} Cor. No. 5, said Aztec Center South East lode, bears N. 64° 05' W. 766.72 ft.

Mineral Survey No. 4135, cont.,

feet

Dower No. 1 lode, cont.,

296.00

To the south east end center post of the location.

551.81

To Cor. No. 4, identical with Cor. No. 2, Blue Bird lode, Sur. No. 3342.

An iron pipe, 4 ft. long, 2 in. dia, with an iron cap punch marked for the exact corner, set 24 ins. in the ground, in a mound of earth and stone. Cap stamped D-1-4-4135-BB-2-3342.

Thence N. 46° 36' W.

646.93

Intersect line 4-5 and 2-I, Aztec Center Southeast and Aztec Center lodes, Sur. No. 3199, at S. 38° W. 57.81 ft. from Cors. No. 5 and I, respectively.

856.43

Intersect line I-2, Little Alice lode, Sur. No. 3231 at S. 44° 18' W. 6.23 ft. from Cor. No. I, and line 7-I, Aztec Center lode, Sur. No. 3199, at N. 62° 21' W. 212.02 ft. from Cor. No. I.

1063.48

To Cor. No. I, the place of beginning.

All corners are identical with the location.

No bearing objects available.

Variation, all corners, 15° 30' East.

* * * * *

Dower No. 2 lode

Beginning ^{at} Cor. No. I, identical with Cor. No. 3, Templar lode, Sur. No. 3342.

A redwood post, 4 ins. square, 4 ft. long, with a nail at the exact corner, set 18 ins. in the ground, in a mound of earth and stone, scribed D-2-I-4135-T-3-3342.

Identical also, with Cor. No. I, Aztec lode, Sur. No. 3845 and Cor. No. 4, Tape lode, Sur. No. 4130.

The 1/4 corner between sections 23 and 24, T. 19 N. R 20 W. G. & S, R. B. & M. bears N. 81° 55' W. 379.50 ft.

Thence N. 54° 31' 30" E.

255.00

To the north west end center post of the location.

Identical with the south east end center, Tape lode, Sur. No. 4130.

Mineral Survey No. 4135, cont.,

feet	Dower No. 2 lode, cont.,
525.70	To Cor. No. 3, Tape lode, Sur. No. 4130.
543.20	To Cor. No. 2, identical with Cor. No. 4, Templar lode, Sur. No. 3342.
	A redwood post, 4 ins. square, 4 ft. long, with a nail at the exact corner, set 18 ins. in the ground, in a mound of earth and stone, scribed D-2-2-4135-T-4-3342.
	On line I-4, Dower No. 3 lode, this survey, at N. 36° 27' W. 1025.00 ft. from Cor. No. 4. and on line I-2 THREE Square lode, Sur. No. 3845 at N 68° 45' E 175 ft. from Cor. No. 1.
	Thence S. 46° 36' E.
578.21	Intersect line I-2 and 4-3, Hawkeye and Pelican lodes, Sur. No. 3342 at N. 59° 48' E. 102.50 ft. and 79.25 ft., from Cors. No. 2 and 3, respectively.
1041.28	Intersect line 3-4, Dower No. 3 lode, this survey, at N. 53° 33' E. 183.49 ^{ft} from Cor. No. 4.
1281.80	To Cor. No. 3, identical with Cor. No. 1, Templar lode, Sur. No. 3342.
	A redwood post, 4 ins. square, 4 ft. long, with a nail at the exact corner, set 18 ins. in the ground, in a mound of earth and stone, scribed D-2-3-4135-T-1-3342.
	Thence S. 54° 31' 30" W.
266.57	Intersect line 2-3, Pelican lode, Sur. No. 3342, at S. 31° 13' 30" E. 699.59 ft. from Cor. No. 3.
288.20	To the south east end center post of the location.
543.20	To Cor. No. 4, identical with Cor. No. 2, Templar lode, Sur. No. 3342, and with Cor. No. 3, Dower No. 1 lode, this survey.
	A redwood post, previously described, scribed D-2-4-4135-T-2-3342.
	Thence N. 46° 36' W.
1063.48	To Cor. No. 2, Dower No. 1 lode, This survey.
1063.96	To Cor. No. 2, Aztec lode, Sur. No. 3845.
1281.80	To Cor. No. 1, the place of beginning.
	All corners are identical with the location.
	No bearing objects available.
	Variation, all corners, 15° 30' East.

Mineral Survey No. 4135, cont.,

feet	Dower No. 3 lode, cont.,
	Beginning at Cor. No. 1.
	An iron pipe, 4 ft. long, 2 in. dia, with an iron cap punchmarked for the exact corner, set 24 ins. in the ground, in a mound of earth and stone. Cap stamped D-3-I-4135.
	On line 2-3, Hawkeye lode, Sur. No. 3342, at S. $36^{\circ} 27' E.$ 467 ft. and N. $36^{\circ} 27' W.$ 1033.00 ft. from Cors. No. 3 and 2, respectively.
	The $1/4$ corner between sections 23 and 24, T. 19 N. R. 20 W. G. & S. R. B. & M. bears S. $39^{\circ} 46' W.$ 837.78 ft.
	Thence N. $53^{\circ} 33' E.$
299.46	To the north west end center monument of the location.
357.10	Intersect line 2-3, Three Square lode, Sur. No. 3845, at N. $39^{\circ} 23' W.$ 490.38 ft. from Cor. No. 2.
507.85	Intersect line 3-4, Rancee lode, Sur. 4118 at N. $67^{\circ} 40' W.$ 390.27 ft. from Cor. No. 3.
598.92	To Cor. No. 2.
	An iron pipe, 4 ft. long, 2 in. dia, with an iron cap punch marked for the exact corner, set 24 ins. in the ground, in a mound of earth and stone. Cap stamped D-3-2-4135.
	On line 4-1, Hawkeye lode, Sur. No. 3342, at S. $36^{\circ} 27' E.$ 401.42 ft. and N. $36^{\circ} 27' W.$ 1098.58 ft. from Cors. No. 4 and 1, respectively.
	Thence S. $36^{\circ} 27' E.$
150.28	To Cor. No. 1, Relief lode, Sur. No. 4118 and intersect line 3-4 Rancee lode, Sur. No. 4118 at N. $67^{\circ} 40' W.$ 214.50 ft. from Cor. No. 3.
1098.58	To Cors. No. 1 and 4, Hawkeye and Pelican lodes, respectively, Sur. No. 3342 and Cor. No. 5, Relief lode, Sur. No. 4118, Cors. No. 2 & 3, said Hawkeye and Pelican lodes, bears S. $59^{\circ} 48' W.$ 602.50 & 579.25 ft. respectively.
1500.00	To Cor. No. 3.
	An iron pipe, 4 ft. long, 2 in. dia, with an iron

Mineral Survey No. 4135, cont.,

feet	Dower No. 3 lode, cont.,
	cap punch marked for the exact corner, set 24 ins. in the ground, in a mound of earth and stone. Cap stamped D-3-3-4135.
	Thence S. 53° 33' W.
69.58	Intersect line 4-1 and 4-5, Pelican and Relief lodes, Sur. No. 3342 and 4118, respectively, at S. 26° 37' E. 407.40 ft. from Cors. No. 4-5.
299.46	To the south east end center post of the location.
415.43	Intersect line 2-3, Dower No. 2 lode, this survey, and line 4-1, Templar lode, Sur. No. 3342, at S. 46° 36' E. 1041.28 ft. from Cors. 2 and 4, respectively.
598.92	To Cor. No. 4.
	An iron pipe, 4 ft. long, 2 in. dia, with an iron cap punch marked for the exact corner, set 24 ins. in the ground, in a mound of earth and stone. Cap stamped D-3-4-4135.
	Thence N. 36° 27' W.
211.74	Intersect line 2-3, Pelican lode, Sur. No. 3342, at S. 31° 13' 30" E. 253.78 ft. from Cor. No. 3.
467.00	To Cor. No. 2, Hawkeye lode, Sur. No. 3342.
1025.00	To Cor. No. 2, Dower No. 2 lode, this survey, and intersect line I-2, Three Square lode, Sur. No. 3845, at S.
1500.00	To Cor. No. 1, the place of beginning. <i>55° 45' W. 3825 ft. from Cor. No. 2.</i>
	All corners are identical with the location.
	No bearing objects available.
	Variation, all corners, 15° 30' East.
	* * * * *

LOCATION.

This survey is located in the west half of section 24, T. 19 N. R. 20 W. G. & S. R. B. & M. in the San Francisco Mining District, Mohave County, Arizona, about one mile southeast of the Town of Oatman.

LODE Lines

As near as can be determined from present developments, the veins in the several claims of this survey extend from their respective discovery points, as follows:

Mineral Survey No. 4135, cont.,

Lode Lines, cont.,

Dower No. 1 lode. N. 46° 36' W. 434 ft. and S. 46° 36' E. 629.48 ft. from the discovery cut.

Dower No. 2 lode. N. 46° 36' W. 210 ft. and S. 46° 36' E. 1071.80 ft. from the discovery cut.

Dower No. 3 lode. N. 36° 27' W. 750 ft. and S. 36° 27' E. 750 ft. from the discovery cut.

* * * * *

AREAS

	Acres	Acres
Dower No. 1 lode -----	12.992	
Area in		
^ Conflict with ^P the Blue Bird lode, Sur. No. 3342 -----		12.992
Conflict with Little Alice lode, Sur. No. 3231 -----		0.037
Conflict with Aztec Center lode, Sur. No. 3199 -----		0.138
Conflict with Aztec Center South East lode, Sur. No. 3199 -----		2.635
Area in		
^ Dower No. 2 lode -----	15.684	
^ Conflict with ^P Templar lode, Sur. No. 3342 -----		15.684
Conflict with Pelican lode, Sur. No. 3342 -----		2.748
Conflict with Hawkeye lode, Sur. No. 3342 -----		0.653
Dower No. 3 lode -----	20.624	
Area in		
^ Conflict with ^P Hawkeye lode, Sur. No. 3342 -----		14.654
Conflict with Three Square lode, Sur. No. 3845 -----		4.091
Conflict with Dower No. 2 lode, this survey -----		2.159
Conflict with Pelican lode, Sur. No. 3342 -----		5.582
Conflict with Relief lode, Sur. No. 4118 -----		0.321
Conflict with Rancee lode, Sur. No. 4118 -----		0.157
Conflict with Dower No. 2 lode, this survey, exclusive of its conflict with Pelican lode, Sur. No. 3342 -----		0.720

* * * * *

Expenditure of Five Hundred Dollars

I certify that the value of labor and improvements made upon or for the benefit of this group of lode claims,

Mineral Survey No. 4135, cont.,

Improvements, cont.,

by the Claimant or its Grantors, is not less than Five Hundred Dollars and that said improvements consist of the following:

Dower No. 1 lode.

No. 1:- The discovery cut, 5 ft. wide, 10 ft. face, extends West 16 ft. to the mouth. Center of face is on the lode line, at 434 ft. from the north west end center. Value ----- \$50.00

No. 2:- An open cut, 12 ft. face, 5 ft. wide, extends N. 47° W. 22 ft. to mouth. From the face, a 4 by 7 ft. tunnel runs S. 47° E. 20 ft. Center of face is on the lode line at 385 ft. from the north west end center. Value ----- \$250.00

No. 3:- Face of a crosscut from the 950 foot level of the Black Eagle Working, Tom Reed Gold Mines, Claimant, is on the lode line at 520 ft. from the north west end center, and extends S. 13° 30' E. 105 ft. to Sta. 907 of the 950 ft. drift. Value \$2625,00

I/3 value to this claim --- \$875.00

No. 4:- An open cut, 5 ft. wide, 12 ft. face, extends N. 20° W. 21 ft. to mouth. From face, a 5 by 7 ft. tunnel runs S. 20° E. 5 ft. Center of face of cut bears S. 22° E. 285 ft. from the north west end center. Value ----- \$125.00

Dower No. 2 lode.

No. 1:- The discovery cut, the center of face 4 ft. wide, 10 ft. high is on the lode line at 210 ft. from the north west end center and extends North 17 ft. to its mouth. Value ----- \$50.00

No. 2:- An open cut, 5 ft. wide, 10 ft. face, extends N. 80° W. 27 ft. to mouth. Center of face bears S. 75° E. 225 ft. from Cor. No. 1. Value ----- \$75.00

1/3 interest in Improvement No. 3, Dower No. 1 lode, this survey----- \$875.00

Mineral Survey No. 4135, cont.,

Improvements, cont.,

Dower No. 3 lode.

No. 1:- The discovery cut, 5 ft. wide, 10 ft. face, extends West 18 ft. to its mouth. Center of face is on the lode line at 750 ft. from the north west end center.

Value -----\$50.00

1/3 interest in Improvement No. 3,
Dower No. 1 lode, this survey ----- \$875.00

OTHER IMPROVEMENTS

Dower No. 1 lode.

An open cut, 4 ft. wide, 8 ft. face, extends N. 46° W. 12 ft. to mouth. Center of face is on the lode line at 238 ft. from the north west end center.

A deep shaft, caved, the center of which bears S. 62° E. 300 ft. from the north west end center.

Dower No. 2 lode.

An open cut, 4 ft. wide, 7 ft. face, extends North 13 ft. to mouth. Center of face is on the lode line at 228 ft. from the north west end center.

Dower No. 3 lode.

An open cut, 4 ft. wide, 8 ft. face, extends South 14 ft. to mouth. Center of face bears N. 50° W. 160 ft. from the south east end center.

* * * * *

REPORT

The side and end lines and all other lines were measured directly on the ground.

The 1/4 corner between sections 23 and 24, T. 19 N. R. 20 W. G. & S. R. B. & M. is a one inch iron pipe with a brass cap, properly set and marked.

Corners of Surs. No. 3199, 3231 and 3845, tied to in this survey, are all redwood posts, 4 ins. square, properly set and marked. Also Surs. No. 4130 and 3342.

Corners of Sur. No. 4118 are iron pipe with iron caps.

Improvement No. 3, Dower No. 1 lode, is a cross cut from the 950 ft. level of the Black Eagle workings

Mineral Survey No. 4135, cont.,

Report, cont.,

by the Tom Reed Gold Mines Co., and was started for the express purpose of exploring and developing the claims of this survey. The value of \$2625.00 is divided equally between the three of this survey, \$875 being credited to each.

Instrument and Meridian

This survey was made with a C. L. Berger & Sons Transit and with a 100 and 500 ft. steel tape. Meridian was determined by direct observation on the Sun.

Adjoining and Conflicting Claims


This survey conflicts with the Aztec Center Southeast and Aztec Center lodes, Sur. No. 3199 and the Little Alice lode. Sur. No. 3231 on the south west side.

Joins the Aztec and Tape lodes, Surs. No. 3845 and 4130, respectively, and conflicts with the Three Square and Rancee lodes, Surs. No. 3845 and 4118, respectively, on the north west and north.

Joins the Relief lode, Sur. No. 4118 on the north east and conflicts with the Pelican lode, Sur. No. 3342 on the south east.

The Dower No. 1 lode conflicts with the Blue Bird lode, Sur. No. 3342 in its entirety, the Dower No. 2 lode conflicts with the Templar lode, Sur. No. 3342 in its entirety and the Dower No. 3 lode conflicts with the Hawkeye lode, Sur. No. 3342.

Joins Public Domain on the south.



L.H. Foster,
U.S. Mineral Surveyor,
~~P. O. Box 622~~
~~Kingman, Arizona~~

~~Atty. for Claimant-~~

~~Louis L. Wallace,~~
~~Kingman, Arizona.~~

FINAL OATHS FOR SURVEYS

LIST OF NAMES

A list of the names of the individuals employed by L. H. Foster

United States Mineral Surveyor, to assist in running, measuring, and marking the lines, corners, and boundaries described in the foregoing field notes of the survey of the mining claim of _____

Tom Reed Gold Mines Company

known as the Dower No. 1, Dower No. 2 and Dower No. 3 Lodes

and showing the respective capacities in which they acted.

N. J. Webb, Chainman.

XXXXXXXXXXXXXXXXXXXX, Chainman.

XXXXXXXXXXXXXXXXXXXX, Axman.

XXXXXXXXXXXXXXXXXXXX, Flagman.

FINAL OATHS OF ASSISTANTS

~~WEX~~ I, N. J. Webb

and XXXXXXXXXXXXXXXXXXXX, do solemnly swear that ~~we~~^I assisted _____

L. H. Foster, United States Mineral Surveyor, in marking the corners and surveying the boundaries of the mining claim of Tom Reed Gold Mines Company

known as the Dower No. 1, Dower No. 2 and Dower No. 3 Lodes

represented in the foregoing field notes as having been surveyed by said mineral surveyor and under his direction; and that said survey has been in all respects, to the best of our knowledge and belief, faithfully and correctly executed, and the corner and boundary monuments established according to law and the instructions furnished by the Office Cadastral Engineer, at Phoenix, Arizona

N. J. Webb, Chainman.

_____, Chainman.

_____, Axman.

_____, Flagman

Subscribed and sworn to by the above-named persons before me this 22

day of August, 1930

Charles P. Blum
Notary Public

FINAL OATH OF U. S. MINERAL SURVEYOR

I, L. H. Foster, U. S. Mineral Surveyor, do solemnly swear that, in pursuance of instructions received from the Office Cadastral Engineer, at Phoenix, Arizona, dated July 2, 1930, I have, in strict conformity to the laws of the United States, the official regulations and instructions thereunder, and the instructions of said Office Cadastral Engineer, faithfully and correctly executed the survey of the Mining Claim of Tom Reed Gold Mines Company, known as the Dower No. 1, Dower No. 2 and Dower No. 3 lodes, situate in San Francisco Mining District, Mohave County, Arizona, in Section 24, Township No. 19 North, Range No. 20 West and designated as Survey No. 4135, as represented in the foregoing field notes, which accurately show the boundaries of said mining claim as distinctly marked by monuments on the ground, and described in the attached copy of the location certificate, which was received by me from the Office Cadastral Engineer with said instructions, and that all corners of said survey have been established and perpetuated in strict accordance with the law, official regulations and instructions thereunder; and I do further solemnly swear that the foregoing are the true and original field notes of said survey and my report therein, and that the labor expended and improvements made upon said mining claim by claimant or its grantors are as therein fully stated, and that the character, extent, location, and itemized value thereof are specified therein with particularity and full detail, and that no portion of said labor or improvements so credited to this claim has been included in the estimate of expenditures upon any other claim.

L. H. Foster
U. S. Mineral Surveyor.

Subscribed and sworn to by the said L. H. Foster
U. S. Mineral Surveyor, before me Charles P. Elmer
a Notary Public this 22

day of August, 1930

Charles P. Elmer
Notary Public

My Commission Expires
Dec. 29, 1930

OFFICE CADASTRAL ENGINEER'S FINAL CERTIFICATE ON FIELD NOTES

Department of the Interior

PUBLIC SURVEY OFFICE

Phoenix, Arizona,

March 20, 1931.

I, Office Cadastral Engineer, at Phoenix, Arizona,

do hereby certify that the foregoing transcript of the Field Notes, return and approval of the survey of the mining claim of

Tom Reed Gold Mines Company

known as the DOWER NO. 1, DOWER NO. 2, and DOWER NO. 3 lodes

situate in San Francisco

Mining District Mohave County Arizona

in Section 24, Township No. 19 North Range No. 20 West, and

designated as Survey No. 4135, has been correctly copied from the originals on file in

this office; that said Field Notes furnish such an accurate description of said mining claim as will, if incorporated into a patent, serve fully to identify the premises, and that such reference is made therein to natural objects or permanent monuments as will perpetuate and fix the locus thereof.

I further certify that Five Hundred Dollars worth of labor has been expended or improvements made upon, or for the benefit of, each location embraced in said mining claim by claimant

or its grantors,

and that said improvements consist of 6 cuts, 2 tunnels and 1 crosscut,

total value \$3225.

and that no portion of said labor or improvements has been included in the estimate of expenditures upon any other claim.

I further certify that the plat thereof, filed in the U. S. Land Office at Phoenix, Arizona, is correct and in conformity with the foregoing Field Notes.

John D. Adams

Office Cadastral Engineer.

CERTIFICATE OF APPROVAL OF FIELD NOTES AND SURVEY OF
MINING CLAIM

DEPARTMENT OF THE INTERIOR
PUBLIC SURVEY OFFICE

At Phoenix, Arizona,

March 20, 1931, 19

I, Office Cadastral Engineer at Phoenix, Arizona,

do hereby certify that the foregoing and hereto attached Field Notes and Return of the Survey of the
Mining Claim of _____

Tom Reed Gold Mines Company

_____, known as the

DOWER NO. 1, DOWER NO. 2, and DOWER NO. 3 lodes

situate in San Francisco mining district,

Mohave County, Arizona

in Section 24, Township No. 19 North, Range No. 20 West

_____, designated as Survey No. 4135

executed by L. H. Foster, U. S. Mineral

Surveyor, July 10 - 20, 1930, under my instructions dated

July 2, 1930, have been critically examined and the necessary

corrections and explanations made, and the said Field Notes and Return, and the Survey they describe,

are hereby approved. The certified copy of the location certificate filed by the applicant for survey is

on file in this office and a true copy of said certified copy of said location certificate is included and

made a part of the transcript of the field notes.


Office Cadastral Engineer.