

MINERAL SURVEY No. 4220 A & B.

Arizona

Land District

FIELD NOTES

OF THE SURVEY OF THE MINING CLAIM OF

W. A. Paris

KNOWN AS THE

Kaaba, Kaaba Ext. Wonder, Castle, Castle Ext. Cedar, Diamond, Uranite, Gold Cross, Gem, Producer, Sakala No. 2, Sakala lodes, and Kaaba Millsite

Maynard

Mining District,

Mohave

County,

Arizona

Section 23-24-25-26

, Township 20 N.

, Range 14 W.

Surveyed under instructions dated November 15 , 1938

By L. H. Foster

U. S. Mineral Surveyor.

Claim located see back of this sheet , 19

Survey commenced January 26 , 1939

Survey completed September 30 , 1940

Address of claimant's Atty., Louis L. Wallace, Box 845 Kingman, Arizona

DATES OF AMENDED LOCATIONS

October 31, 1938 All lodes.

MINERAL SURVEY NO. 1234

Claim	Located
Kaaba -----	January 11, 1907 ✓
Kaaba Ext, -----	May 1, 1920 ✓
Wonder -----	October 14, 1920 ✓
Castle -----	February 25, 1916 ✓
Castle Ext. -----	February 25, 1916 ✓
Cedar -----	September 24, 1920 ✓
Diamond -----	February 26, 1916 ✓
Uranite -----	September 24, 1920 ✓
Gold & Cross -----	February 26, 1916 ✓
Gem -----	July 20, 1920 ✓
Producer -----	February 26, 1916 ✓
Sakala No. 2 -----	May 17, 1921 ✓
Sakala -----	October 1, 1908 ✓
Kaaba Mill site -----	January 11, 1907 ✓

KNOWN AS THE

... ..

... ..

... ..

(Name)

... ..

... ..

By

... ..

... ..

... ..

... ..

... ..

... ..

... ..

Mineral Survey No. 4220 A. & B.

Feet

Mineral Survey No. 4220 A. & B. was made with a Berger & Sons mining transit No. 17069 with 5 in. plates having opposite verniers, a $4\frac{1}{2}$ in. full vertical circle with one vernier, all reading to 1 minute of arc. The eye piece is equipped with a colored glass shade fastened to dust shutter, for making direct observations upon the sun. The instrument was in good condition at the time of the survey and all adjustments were in good order.

An A. M. observation of the sun for azimuth and an observation at noon for latitude was taken at the point of beginning. Time used was Pacific Standard, checked by Western Union. Details of the observation are shown on the accompanying calculation sheets. All Azimuth in this record are referred to the true meridian thus established by the method of deflection ^{angles} and calculated courses.

All lines were measured direct with a 100 and 300 ft. steel tape, graduated for each foot, with the first and last foot marked in tenths and hundredths; both tapes were in good condition and correct at time of survey.

The magnetic variation observed at each corner of the survey gave a uniform value of $15^{\circ} 30' E.$

Kaaba lode

at
Beginning Cor. No. 1.

A 2 in. iron pipe, 4 ft. long, set 2 ft. in the ground, in a mound of earth and stone, ^{with} An iron cap stamped with a center point for the exact corner and marked K-1-4220-A.

Identical with Cor. No. 1, Castle lode, this survey.

The corner of sections 23-24-25-26, T. 20 N. R. 14 W. bears N. $73^{\circ} 00' W.$ 65.00 feet.

Thence S. $9^{\circ} 12' W.$

1500.00

To Cor. No. 2.

A 2 in. iron pipe, 4 ft. long, set 2 ft. in the ground, in a mound of earth and stone, ^{with} An iron cap stamped with a center point for the exact corner and marked K-2-4220A.

Identical with Cors. No. 4, Castle and Kaaba Ext. lodes, this survey

Survey No. 4220 A. & B. , cont.,

feet

Kaaba lode, cont.,

Thence N. 73° 00' W.

302.73 Intersect the lode line at the south end center monument of the location.

Identical with the north end center, Kaaba Ext. lode, this survey.

605.46 To Cor. No. 3.

A 2 in. iron pipe, 4 ft. long, set 2 ft. in the ground, in a mound of earth and stone, with An iron cap stamped with a center point for the exact corner and marked K-3-4220A.

Identical with Cors. No. 3-2-2, Kaaba Ext., Uranite, and Producer lodes, this survey, respectively.

Thence N. 9° 12' E.

1500.00 To Cor. No. 4.

A 2 in. iron pipe, 4 ft. long, set 2 ft. in the ground in a mound of earth and stone, with An iron cap stamped with with a center point for the exact corner and marked K-4-4220A.

Identical with Cor. No. 1, Producer lode, this survey.

Thence S. 73° 00' E.

183.04 To Cors. No. 1 and 2, Sakala No. 2 and Sakala lodes, this survey, respectively.

302.73 Intersect the lode line at the north end center monument of the location.

496.75 To South end center, Sakala lode, this survey.

605.46 To Cor. No. 1, the place of beginning.

All corners are identical with the location.

No bearing objects available.

Castle lode

Beginning at Cor. No. 1.

A 2 in pipe, previously described, marked C-1-4220A.

Identical with Cor. No. 1, Kaaba lode, this survey.

The corner of sections 23-24-25-26, T. 20 N. R. 14 W. bears N. 73° 00' W. 65.00 feet.

Survey No. 4220 A. & B, cont.,

feet

Castle lode, cont.,

Thence S. 73° 00' E.

205.00 To Cor. No. 1, Sakala and Castle Ext. lodes, this survey.

302.73 Intersect the lode line at the north end center monument of the location.

518.71 To the south end center, Castle Ext. lode, this survey.

605.46 To Cor. No. 2.

A 2 in. iron pipe, 4 ft. long, set 2 ft. in the ground, in a mound of earth and stone, with an iron cap, stamped with a center point for the exact corner and marked C-2-4220A.

Identical with Cor. No. 1, Wonder lode, this survey.

Thence S. 9° 12' W.

1500.00 To Cor. No. 3.

A 2 in. iron pipe, 4 ft. long, set 2 ft. in the ground, in a mound of earth and stone, with an iron cap, stamped with a center point for the exact corner and marked C-3-4220A.

Identical with Cor. No. 4, Wonder lode, this survey.

Thence N. 73° 00' W.

302.73 Intersect the lode line at the south end center monument of the location.

605.46 To Cor. No. 4.

A 2 in. iron pipe, previously described, marked C-4-4220A.

Identical with Cors. No. 2 and 4, Kaaba and Kaaba Ext. lodes, this survey, respectively.

Thence N. 9° 12' E.

1500.00 To Cor. No. 1, the place of beginning

All corners are identical with the location.

No. bearing objects available.

Wonder lode at Beginning, Cor. No. 1.

A 2 in. iron pipe, previously described, marked W.-1

Survey No. 4220, A. & B. cont.,

feet	
	Wonder lode, cont.,
	4220A.
	Identical with Cor. No. 2, Castle lode, this survey.
	The corner of sections 23-24-25-26, T- 20N. R. 14 W.
	bears N. 73° 00' W. 670.46 ft.
	Thence S. 73° 00' E.,
226.96	To Cor. No. 4, Castle Ext. lode, this survey.
302.73	Intersect the lode line at the north end center monument of the location.
605.46	To Cor. No. 2.
	A 2 in. iron pipe, 4 ft. long, set 2 ft. in the ground, with in a mound of earth and stone, An iron cap, with a center point for the exact corner and marked W-2-4220A.
	Thence S. 9° 12' W.
1500.00	To Cor. No. 3.
	A 2 in. iron pipe, 4 ft. long, set 2 ft. in the ground, with in a mound of earth and stone, An iron cap, with a center point for the exact corner and marked W-3-4220A.
	Thence N. 73° 00' W.
302.73	Intersect the lode line at the south end center monument of the location.
605.46	To Cor. No. 4.
	A 2 in. iron pipe, previously described, marked W-4 4220A.
	Identical with Cor. No. 3, Castle lode, this survey.
	Thence N. 9° 12' E.
1500.00	To Cor. No. 1, the place of beginning.
	All corners are identical with the location.
	No bearing objects available.
	* * * * *
	Kaaba Ext. lode.
	at Beginning Cor. No. 1.
	An 1/2 in. iron pipe, 4 ft. long, set 2 ft. in the with ground, in a mound of earth and stone, An iron cap with a center point for the exact corner marked KE-1-4220A.
	Sec. The 1/4 corner between sections 25 and 26, T. 20 N. R. 14 W. bears N. 26° 10' E. 402.97 feet.

Survey No. 4220 A. & B. cont.,

feet	
	Kaaba Ext. lode, cont.,
	Thence N. 73° 00' W.
302.73	Intersect the lode line at the south end center monument of the location.
605.46	To Cor. No. 2.
	A 1 1/2 in. iron pipe, 4 ft. long, set 2 ft. in the ground, in a mound of earth and stone, ^{with} An iron cap with a center point for the exact corner, and marked KE-2-4220A.
	Thence North
1136.29	To Cor. No. 3, Uranite lode, this survey.
1450.00	To the easterly end center, Uranite lode, this survey.
1500.00	To Cor. No. 3.
	A 2 in. iron pipe, previously described, marked KE-3-4220A.
	Identical with Cors. No. 3-2-2, Kaaba, Producer, and Uranite lodes, this survey, respectively.
	Thence S. 73° 00' E.
302.73	Intersect the lode line at the north end center monument of the location.
	Identical with the south end center, Kaaba lode, this survey.
605.46	To Cor. No. 4.
	A 2 in. iron pipe, previously described, marked KE-4-4220A.
	Identical with Cors. No. 2 and 4, Kaaba and Castle lodes, this survey.
	Thence South
1500.00	To Cor. No. 1, the place of beginning.
	All corners are identical with the location.
	No bearing objects available.
	* * * * *
	Uranite lode
	at
	Beginning Cor. No. 1.
	A 2 in iron pipe, 4 ft. long, set 2 ft. in the ground, in a mound of earth and stone, ^{with} An iron cap with a center point for the exact corner and stamped U-1-4220A.

780

Survey No. 4220 A. & B. cont.,

feet		
	Uranite lode, cont.,	
	Sec.	
	The I/4 corner between sections 23 and 26, T. 20 N.	
	R. 14 W. bears N. 26° 29' W. 988.47 feet.	
	Thence S. 73° 00' E.	
44.08	Intersect the lode line	
	at the south end center Diamond lode, this survey.	
346.81	To Cors No. 4 and 3, Diamond and Gold Cross lodes,	
	this survey, respectively.	
649.54	To the south end center, Gold Cross lode, this survey.	
952.27	To Cors. No. 2 and 3, Gold Cross and Producer lodes,	
	this survey, respectively.	
1255.00	To the south end center, Producer lode, this survey.	
1500.00	To Cor. No. 2.	
	A 2 in iron pipe, previously described, marked U-2-	
	4220A.	
	Identical with Cors. No. 3, Kaaba and Kaaba Ext. lodes	
	this survey, and with Cor. No. 2, Producer lode, this survey.	
	Thence South	
50.00	Intersect the lode line	
	at the easterly end center monument of the location.	
363.71	To Cor. No. 3.	
	A 1 1/2 in. iron pipe, 4 ft. long, set 2 ft. in the	
	ground, in a mound of earth and stone, with	
	An iron cap with a	
	center point for the exact corner and stamped U-3-4220A.	
	On line 2-3, Kaaba Ext. lode, this survey, at 1136.29	
	ft. North of Cor. No. 2.	
	Thence N. 73° 00' W.	
1500.00	To Cor. No. 4.	
	A 1 1/2 in. iron pipe, 4 ft. long, set 2 ft. in the	
	ground, in a mound of earth and stone, with	
	An iron cap with a	
	center point for the exact corner, stamped U-4-4220A.	
	Thence North	
313.71	Intersect the lode line	
	at the westerly end center monument of the location.	
363.71	To Cor. No. 1, the place of beginning.	
	All corners are identical with the location.	
	No Bearing objects available.	
	* * * * *	

910

Survey No. 4220 A. & B. cont.,

feet	feet
	<p>Producer lode</p> <p>Beginning ^{at} Cor. No. 1.</p> <p>A 2 in. iron pipe, previously described, in the ground, in a mound of earth and stone. An iron cap with a center point for the exact corner, stamped P-1-4220A.</p> <p>Identical with Cor. No. 4, Kaaba lode, this survey.</p> <p>The corner of sections 23-24-25-26, T. 20 N. R. 14 W. bears S. 73° 00' E. 540.46 feet.</p> <p>Thence S. 9° 12' W.</p>
1500.00	<p>To Cor. No. 2.</p> <p>A 2 in. pipe, previously described, marked P-2-4220A.</p> <p>Identical with Cors. No. 3-3-2, Kaaba, Kaaba Ext. and Uranite lodes, this survey, respectively.</p> <p>Thence N. 73° 00' W.</p>
245.00	<p>Intersect the lode line at the south end center monument of the location.</p>
547.73	<p>To Cor. No. 3.</p> <p>A 1 1/2 in. iron pipe, 4 ft. long, set 2 ft. in the ground, in a mound of earth and stone, with an iron cap with a center point for the exact corner, stamped P-3-4220A.</p> <p>Identical with Cor. No. 2, Gold Cross lode, this survey.</p> <p>Thence N. 9° 12' E.</p>
1500.00	<p>To Cor. No. 4.</p> <p>A 2 in. iron pipe, 4 ft. long, set 2 ft. in the ground, in a mound of earth and stone, with an iron cap with a center point for the exact corner, stamped P-4-4220A.</p> <p>Identical with Cor. No. 1, Gold Cross lode, this survey.</p> <p>Thence S. 73° 00' E.</p>
103.35	<p>Cor. Nos.</p> <p>To 1 and 2, Gem and Sakala No. 2 lodes, this survey, respectively.</p>
302.73	<p>Intersect the lode line at the north end center monument of the location.</p>
417.06	<p>To the south end center, Sakala No. 2 lode, this survey.</p>
547.73	<p>To Cor. No. 1, the place of Beginning.</p> <p>All corners are identical with the location. No bearing objects available.</p>

10

Survey No. 4220, A & B. cont.,

feet

Gold Cross lode

at
Beginning Cor. No. 1.

A 2 in. pipe, previously described, marked GC-1-4220A.

Identical with Cor. No. 4, Producer lode, this survey.

The corner of sections 23-24-25-26, T. 20N. R. 14 W. bears S. 73° 00' E. 1088.19 feet.

Thence S. 9° 12' W.

1500.00

To Cor. No. 2.

A 1 1/2 in. pipe, previously described, marked GC-2-4220A.

Identical with Cor. No. 3, Producer lode, this survey.

Thence N. 73° 00' W.

302.73

Intersect the lode line at the south end center monument of the location.

605.46

To Cor. No. 3.

A 1 1/2 in. iron pipe, 4 ft. long, set 2 ft. in the ground, in a mound of earth and stone, with An iron cap with a center point for the exact corner, stamped GC-3-4220A.

Identical with Cor. No. 4, Diamond lode, this survey.

Thence N. 9° 12' E.

1500.00

To Cor. No. 4.

A 2 in. iron pipe, 4 ft. long, set 2 ft. in the ground, in a mound of earth and stone, with An iron cap with a center point for the exact corner, stamped GC-4-4220A.

Identical with Cor. No. 3, Diamond lode, this survey.

Thence S. 73° 00' E.

81.39

To Cor. No. 2, Gem lode, this survey.

302.73

Intersect the lode line at the north end center monument of the location.

395.10

To the south end center, Gem lode, this survey.

605.46

To Cor. No. 1, the place of beginning.

All corners are identical with the location.

No bearing objects available.

* * * * *

Diamond lode

at
Beginning Cor. No. 1.

Survey No. 4220 A. & B. cont.,

feet

Diamond lode, cont.

A 1 1/2 inch iron pipe, 4 ft. long, set 2 ft. in the ground, in a mound of earth and stone, with An iron cap with a center point for the exact corner, stamped D-1-4220A.

Identical with Cor. No. 4, Cedar lode, this survey.

The 1/4 corner between section 23 and 26 T. 20 N. R. 14 W. bears N. 13° 27' W. 831.94 feet.

Thence N. 9° 12' E.

1500.00

To Cor. No. 2.

A 2 in. iron pipe, 4 ft. long, set 2 ft. in the ground in a mound of earth and stone, with An iron cap with a center point for the exact corner, stamped D-2-4220A.

Identical with Cor. No.3, Cedar lode, this survey.

Thence S. 73° 00' E.

302.73

Intersect the lode line at the north end center monument of the location.

605.46

To Cor. No. 3.

A 2 in. pipe, previously described, marked D-3-4220A.

Identical with Cor. No. 4 Gold Cross lode, this survey.

Thence S. 9° 12' W.

1500.00

To Cor. No. 4.

A 1 1/2 in. pipe, previously described, marked D-4-4220A.

Identical with Cor. No. 3. Gold Cross lode, this survey.

Thence N. 73° 00' W.

302.73

Intersect the lode line at the south end center monument of the location.

346.81

To Cor. No. 1, Uranite lode, this survey.

605.46

To Cor. No. 1, the place of beginning.

All corners are identical with the location.

No bearing objects available.

* * * * *

Cedar lode

Beginning at Cor. No. 1.

A 1 1/2 in. iron pipe, 4 ft. long, set 2 ft. in the ground, in a mound of earth and stone, with cap An iron/with a center point for the exact corner, stamped C-1-4220A.

12

Survey No. 4220 A. & B. cont.,

feet	
	Cedar lode, cont.,
	The ^{Sec.} 1/4 corner between sections 23 and 26, T. 20 N. R. 14 W. bears N. 30° 39' E. 738.01 feet.
	Thence N. 9° 12' E.
1500.00	To Cor. No. 2.
	A 1 1/2 in. iron pipe, 4 ft. long, set 2 ft. in the ground, in a mound of earth and stone, ^{with} An iron cap with a center point for the exact corner, stamped C-2-4220A.
	Thence S. 73° 00' E.
302.73	Intersect the lode line at the north end center monument of the location.
595.73	To Cor. No. 3.
	A 2 in. iron pipe, previously described, marked C-3-4220A.
	Identical with Cor. No. 2, Diamond lode, this survey.
	Thence S. 9° 12' W.
1500.00	To Cor. No. 4.
	A 1 1/2 in. iron pipe, previously described, marked C-4-4220A.
	Identical with Cor. No. 1, Diamond lode, this survey.
	Thence N. 73° 00' W.
293.00	Intersect the lode line at the south end center monument of the location.
595.73	To Cor. No. 1, the place of beginning.
	All corners are identical with the location.
	No bearing objects available.
	* * * * *
	Gem lode.
	at Beginning Cor. No. 1.
	A 2 in. iron pipe, 4 ft. long, set 2 ft. in the ground, in a mound of earth and stone, ^{with} An iron cap with a center point for the exact corner, stamped G-1-4220A.
	Identical with Cor. No. 2, Sakala No. 2 lode, this survey.
	The corner of sections 23-24-25-26, T. 20N. R. 14 W. bears S. 73° 00' E. 984.84 ft.
	Thence N. 73° 00' W.

Survey No. 4220 A. & B. cont.,

feet

Gem lode cont.,

103.35

To Cors. No. 1 and 4, Gold Cross and Producer lodes, this survey, respectively.

313.71

Intersect the lode line at the south end center monument of the location.

406.08

To the north end center, Gold Cross lode, this survey.

627.42

To Cor. No. 2.

A 2 in. iron pipe, 4 ft. long, set 2 ft. in the ground in a mound of earth and stone, with An iron cap with a center point for the exact corner, stamped G-2-4220A.

Thence North.

1500.00

To Cor. No. 3.

A 1 1/2 in. iron pipe, 4 ft. long, set 2 ft. in the ground, in a mound of earth and stone, with An iron cap with a center point for the exact corner, stamped G-3-4220A.

Thence S. 73° 00' E.

313.71

Intersect the lode line at the north end center monument of the location.

627.42

To Cor. No. 4.

A 1 1/2 in. iron pipe, 4 ft. long, set 2 ft. in the ground, in a mound of earth and stone, with An iron cap with a center point for the exact corner, stamped G-4-4220A.

Identical with Cor. No. 3, Sakala No. 2 lode.

Thence South

1500.00

To Cor. No. 1, the place of Beginning.

All corners are identical with the location.

No bearing objects available.

* * * * *

Sakala No. 2 lode.

Beginning Cor. No. 1.

A 2 in. iron pipe, 4 ft. long, set 2 ft. in the ground, in a mound of earth and stone, with An iron cap with a center point for the exact corner, stamped S2-1-4220A.

Identical with Cor. No. 2, Sakala lode, this survey.

The corner of sections 23-24-25-26, T. 20 N. R. 14 W. bears S. 73° 00' E. 357.42 ft.

Thence N. 73° 00' W.

314

Survey No. 4220 A. & B. cont.,

feet	Sakala Node 2 lode, cont.
183.04	To Cors. No. 1 and 4, Producer and Kaaba lodes, this survey, respectively.
313.71	Intersect the lode line at the south end center monument of the location.
428.04	To north end center, Producer lode, this survey.
627.42	To Cor. No. 2.
	A 2 in. pipe, previously described, marked S2-4220A. Identical with Cor. No. 1, Gem lode, this survey. Thence North
1500.00	To Cor. No. 3.
	A 1 1/2 in. iron pipe, previously described, marked S2-4220A.
	Identical with Cor. No. 4, Gem lode, this survey.
	Thence S. 73° 00' E.
313.71	Intersect the lode line at the north end center monument of the location.
627.42	To Cor. No. 4.
	A 1 1/2 in. iron pipe, 4 ft. long, set 2 ft. in the ground, in a mound of earth and stone, with An iron cap with a center point for the exact corner, stamped S2-4220A. Identical with Cor. No. 3, Sakala lode, this survey. Thence South
1500.00	To Cor. No. 1, the place of beginning.
	All corners are identical with the location.
	No bearing objects available.
	* * * * *
	Sakala lode
	Beginning at Cor. No. 1.
	A 2 in. iron pipe, 4 ft. long, set 2 ft. in the ground, in a mound of earth and stone, with An iron cap with a center point for the exact corner, stamped S-1-4220A.
	Identical with Cor. No. 1, Castle Ext. lode, this survey.
	The corner of sections 23-24-25-26, T. 20 N. R. 14 W. bears N. 73° 00' W. 270.00 feet.

Survey No. 4220 A. & B. cont.,

feet

Sakala lode, cont.,

Thence N. 73° 00' W.

205.00 To Cor. No. 1, Kaaba lode, this survey.

313.71 Intersect the lode line at the south end center monument of the location.

507.73 To north end center, Kaaba lode, this survey.

627.42 To Cor. No. 2.

A 2 in. pipe, previously described, marked S-2-4220A.

Identical with Cor. No. 1, Sakala No. 2 lode, this survey.

Thence North

1500.00 To Cor. No. 3.

A 1 1/2 in. pipe, previously described, marked S-3-

4220A.

Identical with Cor. No. 4, Sakala No. 2 lode.

Thence S. 73° 00' E.

313.71 Intersect the lode line at the north end center monument of the location.

627.42 To Cor. No. 4

A 1 1/2 in. iron pipe, 4 ft. long, set 2 ft. in the ground, in a mound of earth and stone, with an iron cap with a center point for the exact corner, stamped S-4-4220A.

Identical with Cor. No. 2, Castle Ext. lode, this survey.

Thence South

1500.00 To Cor. No. 1, the place of beginning.

All corners are identical with the location.

No bearing objects available.

* * * * *

Castle Ext. lode.

Beginning at Cor. No. 1.

A 2 in. iron pipe, previously described, marked CE-1-4220A.

Identical with Cor. No. 1, Sakala lode, this survey.

The corner of sections 23-24-25-26, T. 20 N. R. 14 W. Bears N. 73° 00' W. 270.00 feet.

Thence North

1500.00 To Cor. No. 2.

Survey No. 4220A, & B. cont.,

feet

Castle Ext. lode, cont.,

A 1 1/2 inch pipe, previously described, marked CE-2-4220A.

Identical with Cor. No. 4, Sakala lode, this survey.

Thence S. 73° 00' E.

Intersect the lode line at the north end center monument of the location.

313.71

To Cor. No. 3.

627.42

A 1 1/2 in. iron pipe, 4 ft. long, set 2 ft. in the ground, in a mound of earth and stone, with An iron cap with a center point for the exact corner, stamped CE-3-4220A.

Thence South

1500.00 To Cor. No. 4.

A 2 in. iron pipe, 4 ft. long, set 2 ft. in the ground, in a mound of earth and stone, with An iron cap with a center point for the exact corner, stamped CE-4-4220A.

Thence N. 73° 00' W.

226.96 To Cor. No. 1 and 2, Wonder and Castle lodes, this survey, respectively.

313.71 Intersect the lode line at the south end center monument of the location.

529.69 To the north end center, Castle lode, this survey.

627.42 To Cor. No. 1, the place of beginning.

All corners are identical with the location.

No bearing objects available.

* * * * *

Lode lines

The presumed course of the vein of each of the several locations embraced in this survey, counted from the respective points of discovery, is as follows:

Kaaba lode, N. 9° 12' E. 800 ft. and S. 9° 12' W. 700 feet from the discovery cut.

Castle lode, N. 9° 12' E. 240 ft. and S. 9° 12' W. 1260 ft. from the discovery cut.

Wonder lode, N. 9° 12' E. 915 ft. and S. 9° 12' W. 585 ft. from the discovery cut.

Survey No. 4220 A. & B. cont.,

817

Lode lines, cont.,

~~omit~~
~~cut~~

Kaaba Ext. lode, North 50 ft. and South 1450 ft. from the discovery cut.

Uranite lode, N. 73° 00' W. 1180 ft. and S. 73° 00' E. 320 ft. from the discovery cut.

Producer lode, N. 9° 12' E. 1215 ft. and S. 9° 12' W. 285 ft. from the discovery cut.

Gold Cross^{lode}, N. 9° 12' E. 750 ft. and S. 9° 12' W. 750 ft. from the discovery cut.

Diamond lode, N. 9° 12' E. 850 ft. and S. 9° 12' W. 650 ft. from the discovery cut.

Cedar lode, N. 9° 12' E. 770 ft. and S. 9° 12' W. 730 ft. from the discovery cut.

Gem lode, North 655 ft. and South 845 ft. from the discovery cut.

Sakala No. 2 lode, North 1220 ft. and South 280 ft. from the discovery cut.

Sakala lode, North 1205 ft. and South 295 ft. from the discovery shaft.

Castle Ext. lode, North 1250 ft. and South 250 ft. from the discovery cut.

* * * * *

Kaaba Millsite

at Beginning Cor. No. 1, on the line between Secs. 23 and 26, T. 20 N., R. 14 W.

A 2 in. iron pipe, 4 ft. long, set 2 ft. in the ground, in a mound of earth and stone, with An iron cap with a center point for the exact corner, stamped KMS-1-4220B.

The 1/4^{Sec.} corner between sections 23 and 26, T. 20 N. R. 14 W. bears S. 89° 59' E. 630 feet.

Thence South

466.50

To Cor. No. 2.

A 2 in. iron pipe, 4 ft. long, set 2 ft. in the ground, in a mound of earth and stone, with An iron cap with a center point for the exact corner, stamped KMS-2-4220B.

Thence N. 89° 59' W.

Survey No. 4220 A. & B. cont.,

feet

Kaaba Millsite, cont.,

466.50

To Cor. No. 3

A 2 in iron pipe, 4 ft. long, set 2 ft. in the ground, in a mound of earth and stone, with An iron cap with a center point for the exact corner, stamped KMS-3-4220B.

Thence North

466.50

To Cor. No. 4

A 2 in. iron pipe, 4 ft. long, set 2 ft. in the ground, in a mound of earth and stone, with An iron cap with a center point for the exact corner, stamped KMS-4-4220B.

The Cor. of Secs. 22, 23, 26, & 27, T. 20 N., R. 14 W., bears N. 89° 59' Thence S. 89° 59' E. W. 1541.50 ft.

466.50

To Cor. No. 1, the place of beginning.

All corners are identical with the location.

No available bearing objects.

~~THE KAABA MILLSITE CONTAINS 5.000 ACRES~~

* * * * *

Areas

+ Kaaba lode	-----	20.656 acres.
+ Castle lode	-----	20.656
Wonder lode	-----	20.656
Kaaba Ext. lode	-----	19.938
Uranite	-----	11.977
Producer	-----	18.687
Gold Cross	-----	20.656
Diamond	-----	20.656
+ Cedar	-----	20.324
+ Gem	-----	20.661
Sakala No. 2	-----	20.661
Sakala	-----	20.661
Castle Ext.	-----	20.661
+ + Kaaba Millsite	-----	5.000

Location

This survey is located in sections 23-24-25-26 T. 20 N., R. 14 W. G. & S. R. XXXX M. in Mohave County, Arizona, in the Maynard Mining District.

Expenditure of \$500.00

I certify that the value of the labor and improvements made upon or for the benefit of each of the lode locations embraced in said group of mining claims by the Claimant or his Grantors is not less than \$500.00, and that said improvements consist of:

Survey No. 4220 A & B. cont.,

Improvements, cont.,

Kaaba lode:

No. 1, The center of the face of the discovery cut, 5 ft. wide, 12 ft. high and extending N. 80° W. 18 ft., on the lode line at 700 ft. from the south end center.

Value ----- \$50.00

No. 2, the center of the main workingshaft, 4 by 7 ft. bears N. 10° 15' W. 605 ft. from Cor. No. 2, dips 35° in a S. 86° E. direction, 1272 feet. (1042 ft. horizontal length and 930 ft. vertical depth), From the 120 ft. depth on the incline, a 4 by 7 ft. drift runs N. 20° W 150 ft. And S. 20° E: 335 ft. At 35 ft. on the south drift a cross cut runs S. 60° W. 160 ft. to cut a vein striking N. 55° W.

At 180 ft. in shaft, a drift runs N. 20° W. 150 ft. and S. 20° E. 240 ft. At 270 ft. a drift runs N. 20° W. 20 ft. and S. 20° E. 45 ft. At 550 ft. a drift runs N. 20° W. 100 ft. At 1200 ft. a raise 100 ft. high.

This development is the main working for the group of 13 claims and is valued at \$83,590.00 and 1/13 interest to each claim amounts to \$6430. The claims to the west are on higher ground; it is presumed that all veins have a similar dip and that it will be possible to crosscut each vein to the west.

No. 3, The center of a 4 by 6 ft. vertical shaft, 200 ft. deep, bears S. 29° W. 580 ft. from Cor. No. 1.

Value ----- \$5000.00

No. 4, the face of an open cut, 9 ft. high, 4 ft. wide, extending, S. 28° W. 12 ft. Center of face bears S. 28° W. 320 ft. from Cor. No. 1.

Value ----- \$35.00

No. 5, the face of an open cut, 9 ft. high, 4 ft. wide, extends North 10 ft. and bears S. 21° W. 320 ft. from Cor. No. 1.

Value ----- \$35.00

Castle lode:

No. 1, the center of face of discovery cut on lode line at 240 ft. from the north end center. 10 ft. high, 5 ft. wide, extends N. 45° E. 15 ft.

Value ----- \$45.00

1/13 interest in No. 2, Kaaba lode ----- \$6430.00

20

Survey No. 4220 A & B. cont.,

Improvements, cont.,

Wonder lode:

No. 1, center of face of discovery cut, on lode line at 585 ft. from the south end center, 10 ft. high, 5 ft. wide, extends S. 80° E. 15 ft. Value ----- \$45.00

1/13 interest in No. 2, Kaaba lode ----- \$6430.00

Kaaba Ext. lode:

No. 1, Center of face of the discovery cut on the lode line at 50 ft. from the north end center, 10 ft. high, 5 ft. wide, extends S. 73° E. 15 ft. Value ----- \$45.00

1/13 interest in No. 2, Kaaba lode ----- \$6430.00

Uranite lode:

No. 1, Center of face of discovery cut on lode line at 320 ft. from the east end center, 10 ft. high, 5 ft. wide, extends N. 50° E. 16 ft. Value ----- \$45.00

1/13 interest in No. 2, Kaaba lode ----- \$6430.00

Producer lode:

No. 1, Center of face of discovery cut on lode line at 285 ft. from the south end center, 10 ft. high, 4 ft. wide, extends N. 75° W. 15 ft. Value ----- \$45.00

No. 2, Center of face of an open cut bears S. 6° W. 720 ft. from Cor. No. 4, 4 ft. wide, 12 ft. high, extends N. 10° E. 10 ft. Value ----- \$40.00

Gold Cross lode,

No. 1, Center of face of discovery cut on the lode line at 750 ft. from the north end center, 4 ft. wide, 10 ft. high, extends N. 20° E. 10 ft. and a tunnel 4 by 6 ft. runs S. 20° W. 15 ft. Value ----- \$175.00

1/13 interest in No. 2, Kaaba lode ----- \$6430.00

Diamond lode:

No. 1, Center of face of discovery cut on lode line at 650 from the south end center, 4 ft. wide, 10 ft. high, extends S. 9° W. 10 ft. and a tunnel, 4 by 6 ft. runs N. 9° E. 10 ft. Value ----- \$125.00

No. 2, Center of a 4 by 6 shaft, 47 ft. deep, bears S. 2° W. 720 ft. from Cor. No. 2. value ----- \$600.00
1/13 interest in No. 2, Kaaba lode ----- \$6430.00

Survey No. 4220 A & B. cont.,

Improvements, cont.,

Cedar lode:

No. 1, center of face of the discovery cut, 5 ft. wide wide, 10 ft. high, extends South 16 ft. On lode line at 730 ft. from the south end center. Value -----\$50.00

1/13 interest in No. 2, Kaaba lode ----- \$6430.00

Gem lode:

No. 1, Center of face of discovery^{cut} on lode line at 655 ft. from the north end center, 5 ft. wide, 10 ft. high, extends S. 30° E. 15 ft. Value ----- \$45.00

No. 2, Center of 5 by 5 ft. shaft, 35 ft. deep, bears S. 16° 15' E. 770 ft. from Cor. No. 3.

Value ----- \$350.00

No. 3, Center of 4 by 4 ft. shaft, 8 ft. deep, bears S. 6° E. 700 ft. from Cor. No. 3. Value --- \$45.00

1/13 interest in No. 2, Kaaba lode -----\$6430.00

Sakala No. 2 lode:

No. 1, Center of face of discovery cut on lode line at 280 ft. from the south end center, 5 ft. wide, 10 ft. high, extends N. 75° E. 14 ft. Value ----- \$45.00

1/13 interest in No. 2, Kaaba lode -----\$6430.00

Sakala lode:

No. 1, Center of discovery shaft on lode line at 295 ft. from the south end center, 4 by 4 ft. by 8 ft. deep.

Value-----\$45.00

1/13 interest in No. 2 Kaaba lode -----\$6430.00

Castle Ext. lode.

No. 1, Center of face of discovery cut on lode line at 250 ft. from the south end center, 4 ft. wide, 10 ft. high, extends N. 20° E. 14 ft. Value -----\$45.00

1/13 interest in No. 2, Kaaba lode -----\$6430.00

Kaaba Millsite

~~Box 11~~ A well, 5 by 5 ft. by 90 ft. deep, bears S. 64° 30' W. 265 ft. from Cor. No. 1.

Value -----\$1250.00

22

Survey No. 4220 A & B. cont.,

Other Improvements

Kaaba lode,

No. 1, the southeast corner of Engine room and hoist house, bears N. 6° W. 570 ft. from Cor. No. 2, thence S. 80° W. 37 ft. thence N- 10° W. 20 ft. Thence N. 80° E. 18 ft. thence N. 10° W. 12 ft, thence N. 80° E. 19 ft. thence S. 10° E. 32 ft.

No. 2, the southeast corner of Mill and Warehouse, bears N. 5° E. 610 ft. from Cor. No. 2. Thence N. 5° W. 64 ft. thence S. 85° W. 14 ft. thence S. 5° E. 24 ft. thence S. 85° W. 46 ft. thence S. 5° E. 40 ft, thence N. 85° E. 60 ft.

No. 3, the southeast corner of Blacksmith and Machine shop, bears N. 4° 30' E. 720 ft. from Cor. No. 2. From the southeast corner/ N. 5° E. 60 ft. 20 ft. wide.

Castle lode:

No. 1, The south east corner of Assay office, 18 ft. wide, runs N. 80° W. 44 ft. Cor. No. 4, bears S. 15° 15' W. 670 ft.

No. 2, The southeast corner of a house, 16 ft. wide, runs N. 10° E. 30 ft. Cor. No. 4 bears S. 13° 15' W. 730 ft.

* * * * *

Other Corner descriptions

The corner of sections 23-24-25-26, and the corner of Secs. 22-23-26-27, West are 1/2 in. iron pipes, properly set and marked.

The 1/4 section corner between Secs. 23 and 26 and between Secs. 25 and 26 are 1 in. pipe, properly set and marked.

There are no conflicting claims or adjoining claims.

The end center monuments of location are all mounds of stone 3 ft. high. The differences between this survey and the location notices are due to errors in the latter.

Mineral Surveyor, G. L. O. Kingman, Arizona.

FINAL OATHS FOR SURVEYS

LIST OF NAMES

A list of the names of the individuals employed by L. H. Foster

United States Mineral Surveyor, to assist in running, measuring, and marking the lines, corners, and boundaries described in the foregoing field notes of the survey of the mining claim of _____

W. A. Faris

Kaaba, Kaaba Ext, Wonder, Castle, Castle Ext. Cedar, Diamond, known as the Uranite, Gold Cross, Gem, Producer, Sakala No. 2, Sakala lodes and Kaaba Mill site.

and showing the respective capacities in which they acted.

C. W. Burcham , *Chainman.*

XXXXXXXXXXXXXXXXXXXXXXX , *Chainman.*

XXXXXXXXXXXXXXXXXXXXXXX , *Asman.*

XXXXXXXXXXXXXXXXXXXXXXX , *Flagman.*

FINAL OATHS OF ASSISTANTS

XWA, I, C. W. Burcham

and XXXXXXXXXXXXXXXXXXXXXXX, do solemnly swear that ^I~~we~~ assisted _____

L. H. Foster, United States Mineral Surveyor, in marking the corners and surveying the boundaries of the mining claim of W. A. Faris

Kaaba, Kaaba Ext. Wonder, Castle, Castle Ext., Cedar, Diamond known as the Uranite, Gold Cross, Gem, Producer, Sakala No. 2, Sakala lodes and Kaaba Mill site.

represented in the foregoing field notes as having been surveyed by said mineral surveyor and under his direction; and that said survey has been in all respects, to the best of our knowledge and belief, faithfully and correctly executed, and the corner and boundary monuments established according to law and the instructions furnished by the Office Cadastral Engineer, at PHOENIX, Ariz.

CWBurcham , *Chainman.*

XXXXXXXXXXXXXXXXXXXXXXX , *Chainman.*

XXXXXXXXXXXXXXXXXXXXXXX , *Asman.*

XXXXXXXXXXXXXXXXXXXXXXX , *Flagman*

Subscribed and sworn to by the above-named persons before me this 28th

day of October, 19 40

George Farou
Notary Public

FINAL OATH OF ~~U.S.~~ MINERAL SURVEYOR

I, L. H. Foster, ~~U.S.~~ Mineral Surveyor,
do solemnly swear that, in pursuance of instructions received from the Office Cadastral
Engineer, at Phoenix, Arizona, dated November 15, 1938,

I have, in strict conformity to the laws of the United States, the official regulations
and instructions thereunder, and the instructions of said Office Cadastral Engineer,
faithfully and correctly executed the survey of the mining claim of

W. A. Faris, known as the
Kaaba, Kaaba Ext. Wonder, Castle, Castle Ext. Cedar, Diamond, Uranite
Gold Cross, Gem. Producer, Sakala No. 2, Sakala lodes and Kaaba Mill site.

situate in Maynard Mining District,

Mohave County, Arizona, in Sections

23, 24
26, 25, Township No. 20 North, Range No. 14 West

and designated as Survey No. 4220 A & B., as represented

in the foregoing field notes, which accurately show the boundaries of said mining claim
as distinctly marked by monuments on the ground, and described in the attached copy of
the location certificate, which was received by me from the Office Cadastral Engineer
with said instructions, and that all corners of said survey have been established and
perpetuated in strict accordance with the law, official regulations and instructions
thereunder; and I do further solemnly swear that the foregoing are the true and original
field notes of said survey and my report therein, and that the labor expended and im-
provements made upon said mining claim by claimant or his
grantors are as therein fully stated, and that the character, extent, location, and
itemized value thereof are specified therein with particularity and full detail, and
that no portion of said labor or improvements so credited to this claim has been in-
cluded in the estimate of expenditures upon any other claim.

L. H. Foster
(~~U.S.~~ Mineral Surveyor)

Subscribed and sworn to by the said L. H. Foster

~~U.S.~~ Mineral Surveyor, before me Mary E. Carson

Jotary Pabiz this 28th.

day of October, 19 40

Mary E. Carson
Jotary Pabiz

OFFICE CADASTRAL ENGINEER'S FINAL CERTIFICATE ON FIELD NOTES

United States
Department of the Interior
GENERAL LAND OFFICE
PUBLIC SURVEY OFFICE

Phoenix, Arizona

January 27, 19 41

I, Office Cadastral Engineer, at Phoenix, Arizona

do hereby certify that the foregoing transcript of the Field Notes, return and approval of the survey of the mining claim of W. A. Faris

known as the KAABA, KAABA EXT., WONDER, CASTLE, CASTLE EXT., CEDAR, DIAMOND, URANITE, GOLD CROSS, GEM, PRODUCER, SAKALA NO.2, SAKALA lodes, and KAABA Mill-Site situate in Maynard

Mining District Mohave County Arizona

in Section 23, 24, 25, 26, Township No. 20 N., Range No. 14 W., and

designated as Survey No. 4220 A&B, has been correctly copied from the originals on file in this office; that said Field Notes furnish such an accurate description of said mining claim as will, if incorporated into a patent, serve fully to identify the premises, and that such reference is made therein to natural objects or permanent monuments as will perpetuate and fix the locus thereof.

I further certify that Five Hundred Dollars worth of labor has been expended or improvements made upon, or for the benefit of, each location embraced in said mining claim by claimant or his grantors, and that said improvements consist of 15 outs, 6 shafts, 6 drifts, 1 crosscut, and 1 raise, total value \$90,500.

and that no portion of said labor or improvements has been included in the estimate of expenditures upon any other claim.

I further certify that the plat thereof, filed in the District Land Office at Phoenix, Arizona, is correct and in conformity with the foregoing Field Notes.

Sherman C. Fiske
Office Cadastral Engineer.

CERTIFICATE OF APPROVAL OF FIELD NOTES AND SURVEY OF
MINING CLAIM

UNITED STATES
DEPARTMENT OF THE INTERIOR
GENERAL LAND OFFICE
PUBLIC SURVEY OFFICE

At Phoenix, Arizona,

January 27, 1941

I, Office Cadastral Engineer at Phoenix, Arizona,

do hereby certify that the foregoing and hereto attached Field Notes and Return of the Survey of the
Mining Claim of _____

W. A. Faris

_____, known as the
KAABA, KAABA EXT., WONDER, CASTLE, CASTLE EXT., CEDAR, DIAMOND, URANITE,
GOLD CROSS, GEM, PRODUCER, SAKALA NO. 2, SAKALA lodes, and KAABA Mill-Site

situate in _____ Maynard _____ mining district,

Mohave County, Arizona

in Sections 23, 24, 25, 26, Township No. 20 North, Range No. 14 West

_____, designated as Survey No. 4220 A&B

executed by L. H. Foster, Mineral

Surveyor, January 26, 1939 - September 30, 1940, under my instructions dated


November 15, 1938, have been critically examined and the necessary

corrections and explanations made, and the said Field Notes and Return, and the Survey they describe,

are hereby approved. The certified copy of the location certificate filed by the applicant for survey is

on file in this office and a true copy of said certified copy of said location certificate is included and

made a part of the transcript of the field notes.


Office Cadastral Engineer.

Feet	
	<p>SUPPLEMENTAL FIELD NOTES</p> <p>MINERAL SURVEY NO. 4220A</p> <p>Beginning at the $\frac{1}{4}$ sec. cor. Secs. 23 and 26, T. 20 N., R. 14 W., the SE$\frac{1}{4}$ of the SW$\frac{1}{4}$ of said section 23,</p> <p style="text-align: center;">Thence N. 89° 59' W.</p> <p>along the S. bdy. of said SW$\frac{1}{4}$ section 23,</p>
273.39	<p>to an intersection with line 1-2 of the Cedar lode, Survey No. 4220A,</p> <p style="text-align: center;">Thence N. 9° 12' E.</p> <p>along line 1-2 said Cedar lode,</p>
856.74	<p>to Cor. No. 2 Cedar lode,</p> <p style="text-align: center;">Thence S. 73° E.</p> <p>along line 2-3 said Cedar lode,</p>
142.43	<p>to an intersection with the meridional $\frac{1}{4}$ sec. line of section 23,</p> <p style="text-align: center;">Thence S. 0° 01' E.</p> <p>along said meridional $\frac{1}{4}$ sec. line,</p>
804.13	<p>to the place of beginning.</p> <p style="text-align: center;">Containing 3.911 acres.</p>

Department of the Interior
 General Land Office
 Public Survey Office
 Phoenix, Arizona
 February 5, 1945

I certify that the foregoing supplemental field notes correctly describe the area of the Cedar lode, Sur. No. 4220A, in conflict with the SW $\frac{1}{4}$ of Section 23, T. 20 N., R. 14 W., G. & S.R.M., Arizona, as determined from the records of this office and that the plats of Mineral Survey 4220 A & B, on file in this office, the District Land Office, and the General Land Office, have been amended, in distinctive colored ink, to show such area.

E. A. Thompson
 Office Cadastral Engineer.