

Oct. 2, '44
Nov. 11, '44
1 3/5/45

4-683

UNITED STATES
DEPARTMENT OF THE INTERIOR
GENERAL LAND OFFICE

MINERAL SURVEY NO. 4283

Arizona Land District.

FIELD NOTES

Of The Survey Of The Mining Claim Of

DOVER COPPER MINING COMPANY

Known As The

Anita No.9, Anita No.8, Anita No.5 Anita No.4, Margot No.17, Margot No.15
Margot No.14, Anita No.3 Anita No.2 Anita No.1, Anita No.28, Anita No.29
Margot No.13 Margot No.12 and Margot No.16 lodes.
Copper Mountain Mining District,

Greenlee County, State of Arizona.
Section 7 and 18 Township 4 S. Range 29 E.
Section 12 and 13, Township 4 S., Range 28 E.

Surveyed under instructions dated March 10, 1944

by J.WILLIAM WAARA
Mineral Surveyor.

Margot No.12, Margot No.13, Margot No.14, Margot No.15,
Margot No.16, Margot No.17, April 17, 1925,
Anita No.1, Anita No.2, Anita No.3, Anita No.4, Anita No.
Claims located: Anita No.8, Anita No.9, Anita No.28, Anita No.29,
September 8, 1925

Survey commenced March 10, 1944

Survey completed May 30, 1944

Address of claimant Gibbs & Gibbs Attys for claimant
Phoenix Arizona.

DATES OF AMENDED LOCATIONS

Margot No. 12 Margot No. 13 Margot No. 14 Margot No. 15 Margot No. 16

MINERAL SURVEY NO. 4283

Mineral Survey No. 4283 was made with a Lietz Light Mountain transit No. 9503 Model No. 9 with a horizontal limb 5 inches in diameter having double opposite verniers and a full vertical circle 5 inches in diameter, having double opposite verniers; the horizontal verniers reading to thirty seconds of arc, and the vertical verniers reading to one minute of arc; the eye piece is fitted to receive a prismatic eye piece suitable for making direct observations upon the sun or polaris. The instrument was in good condition at the time of the survey and all adjustments were in good order. Observations upon Polaris were made for azimuth and latitude, the details of which observations are shown in the calculation sheets herewith submitted for examination. All azimuths in this record are referred to the true meridian thus determined, by the method of deflection angles and calculated courses.

The lines were measured with a 1/8 inch steel tape 500 feet in length, graduated every foot, which was compared with a steel standard tape at the time of beginning the survey and found correct.

All lines and connections of this survey were run by direct methods. The magnetic variation observed at each corner of the survey gave a uniform value of 13 -50'E.

Beginning at Cor. No.1 of the Anita No. 9 lode; Identical with Cor. No.1 Anita No.8-lode of this survey.

An iron pipe 30 inches long fitted with a brass cap 4x4x1 inch thick, driven 18 inches into the ground and surrounded by a substantial mound of stone; marked A 9-1, A 8-1-4283 with its center for exact corner point, whence, The south 1/4 sec. corner Sec.12 T. 4 S.R.28 E. Gila and Salt River Meridian brs. S.64 -37'W. 51.6 feet.

No other bearings available.

Thence N.9°-08'W.

300.9 / Intersect the lode line at the
WEST CENTER END, built a substantial mound of stone.

601.8 COR. NO.2.

An iron pipe 30 inches long fitted with a brass cap,
4x4x1 inch thick, driven 18 inches into the ground and
surrounded by a substantial mound of stone, marked A 9-2-
4283 with its center for exact corner point, whence,

No bearings available.

Thence N.78°-02 'E.

880.0 Cross gulch, flows southerly.

1247.0 Cross Dover mine road, brs. north to south.

1497.0 COR. NO.3.

Identical with Cor. No.3 Margot No. 17 lode of this survey

An iron pipe 30 inches long fitted with a brass cap
4x4x1 inch thick, driven 18 inches into the ground and
surrounded by a substantial mound of stone; marked A 9-3,
M 17-3-4283 with its center for exact corner point, whence
No bearings available.

Thence S.9°-08'E.

254.3 / Intersect the lode line at the
EAST CENTER END, built a substantial mound of stone.

555.2 COR. No.4.

Identical with Cor. No.2 Margot No. 17 lode, Cor. No. 3
Margot No.15 lode, Cor. No. 2 Anita No. 18 lode, all of this
survey.

An iron pipe 30 inches long fitted with a brass cap
4x4x1 inch thick, driven 18 inches into the ground and
surrounded by a substantial mound of stone, marked A 9-4,
M 17-2, M 15-3, A 8-2-4283 with its center for exact corner
point, whence,

No bearings available.

Thence S.76°-15'-30"W.

1100.0 Cross Dover Mine Road, brs. northwest to southeast.

1405.0 Cross gulch, flows southeasterly.

1500.0 TO COR. NO.1 and place of beginning.

ANITA NO. 8 LODGE

Beginning at Cor. No. 1 Anita No. 8 lode;

Identical with Cor. No. 1 Anita No. 9 lode of this survey, previously described.

Thence N.76°-15'-30"E.

1095.0 Cross gulch, flows southeasterly.

1400.0 Cross Dover Mine road, brs northwest to southeast.

1500.0 COR. NO. 2

Identical with Cor. No. 4 Anita No. 9 lode, Cor. No. 2 Margot No. 17 lode, Cor. No. 3 Margot No. 15 lode, all of this survey, previously described.

Thence S. 9°-08'E.

95.0 Cross Dover Mine Road, brs. northwest to southeast.

300.9/ Intersect the lode line at the EAST CENTER END, built a substantial mound of stone.

601.8 COR. NO.3.

Identical with Cor. No.2 Margot No. 15 lode, Cor. No. 4 Anita No. 3 lode, Cor. No.2 Anita No. 5 lode, all of this survey.

An iron pipe 30 inches long fitted with a brass cap 4x4x1 inch thick, driven 18 inches into the ground and surrounded by a substantial mound of stone, marked A 8-3, M 15-2, A 3-4, A 5-2-4283 with its center for exact corner point whence,

No bearings available.

Thence S.76°-15'-30"W.

200.0 Cross gulch, flows southerly.

1500.0 COR. NO.4.

Identical with Cor. No. 1 Anita No. 5 lode of this survey.

An iron pipe 30 inches long fitted with a brass cap 4x4x1 inch thick, driven 18 inches into the ground and surrounded by a substantial mound of stone, marked A 8-4, A 5-1-4283 with its center for exact corner point, whence

No bearings available.

Thence N.9°-08'W.

300.9/ Intersect the lode line at the WEST CENTER END, built a substantial mound of stone.

601.8 TO COR. NO. 1, and the place of beginning.

ANITA NO. 5 LODE

Beginning at Cor. No.1 Anita No.5 lode.;

Identical with Cor. No. 4 Anita No.8 lode of this survey,
previously described,whence,

T.4 S., R. 28 E., G.& SRM,
The South 1/4 sec. corner Sec. 12/brs. N.13°-57'-30"W.

589.3 feet.

Thence N. 76°-15'-30"E.

1300.0 Cross gulch, flows southerly.

1500.0 COR. NO.2

Identical with Cor. No. 3 Anita No.8 lode, Cor. No. 2

Margot No. 15 lode, Cor. No. 4 Anita No. 3 lode all of this
survey, previously described.

Thence S.9°-08'E.

Intersect the lode line at the

300.9 / EAST CENTER END, built a substantial mound of stone.

356.7 Intersect Cor. No. Anita No. 4 lode, identical with Cor. No.

4 Anita No. 2 lode, both of this survey. (described.)

594.7 Intersect Witness Corner to Cor.No.3 of this lode,hereafter/

601.8 COR. NO.3

Identical with Cor. No.3 Anita No. 3 lode, of this survey.

This corner fell at a point where it was impracticable to
set a pipe for corner due to roadway; from this corner I
established a witness corner N.9°-08'W. 7.1 feet.

An iron pipe 30 inches long fitted with a brass cap
4x4x1 inch thick, driven 18 inches into the ground and

surrounded by a substantial mound of stone, marked/A 5-3,

A 3-3-4283 with its center for exact corner point, whence,

No bearings available.

Thence S.76°-41'-30"W.(from true corner
point),

630.0 Cross gulch, flows southwesterly.

1447.0 Cross gulch, flows southerly.

1499.1 COR. NO. 4. S.80°45'W. 1494.3ft. from Cor. No.1 &

On line 4-1 Gold Belt No.4 lode Sur. No. 3535, N.80°-45'E.
6.4 feet from Cor. No. 4, also on line 4-1 Anita No.4 lode
of this survey.

An iron pipe 30 inches long fitted with a brass cap

4x4x1 inch thick driven 18 inches into the ground and

surrounded by a substantial mound of stone, marked A 5-4-4283

with its center for exact corner point, whence,

No bearings available.

Thence N.9°-08'W.

185.0 Cross gulch, flows southerly.

225.7 Intersect witness corner to Cor. No. 1 Anita No. 4 lode of

Handwritten notes: 225.7, 127, 3 5 2.7

of this survey.

235.0 Intersect Cor. No.1 Anita No. 4 lode of this survey.

255.0 Cross gulch, flows southwesterly.

289.5 / Intersect the lode line at the WEST CENTER END, built a substantial mound of stone.

590.4 TO COR. NO.1 and place of beginning.

ANITA NO.4 LODE.

Beginning at Cor. No. 1 of the Anita No. 4 lode;
 On line 4-1 Anita No. 5 lode of this survey.
 This corner fell at a point where it was impracticable to set a pipe for corner due to bed rock; from this corner I established a witness corner S.9°-08'E. 9.3 feet.
 An iron pipe 30 inches long fitted with a brass cap 4x4x1 inch thick driven 18 inches into the ground and surrounded by a substantial mound of stone, marked W C A 4-1-4283 with its center for exact corner point, whence, The South $\frac{1}{2}$ Sec. Cor. Sec. 12, $\frac{1}{4}$ brs. N. 12°-08'-30"W. 944.1 feet, from true corner point.
 Thence N.76°-18'-30"E. (from true corner point)

1070.0 Cross gulch, flows southwesterly.

1499.8 COR. NO. 2.
 On line 2-3 Anita No.5 lode and line 3-4 Anita No.3 lode, identical with Cor. No. 4 Anita No. 2 lode of this survey.
 An iron pipe 30 inches long fitted with a brass cap 4x4x1 inch thick, driven 18 inches into the ground and surrounded by a substantial mound of stone, marked A 4-2, A 2-4-4283 with its center for exact corner point, whence, No bearings available.
 Thence S.9°-08'E.

238.0 Intersect witness corner to Cor. No.3 Anita No.5 lode identical with/Cor. No. 3 Anita No.3 lode., both of this survey.

245.1 true pt. for Intersect/Cor. No. 3 Anita No. 5 lode, identical with Cor. No. 3 Anita No. 3 lode, both of this survey, on roadway.

300.0 / Intersect the lode line at the EAST CENTER END, built a substantial mound of stone.

351.1 Intersect Witness Corner to Cor. No. 4 Anita No. 1 lode of this survey and line 4-1 Anita No.1 lode, N.80°-34'-30"E.

1.5 feet from Cor. No. 4.

364.8 Cross gulch, flows westerly.

459.8 COR. NO. 3

Identical with Cor. No. 3 Anita No. 2 lode of this survey.

An iron pipe 30 inches long fitted with a brass cap 4x4x1 inch thick driven 18 inches into the ground and surrounded by a substantial mound of stone, marked A 4-3, A 2-3-4283 with its center for exact corner point, whence, Cor. No. 1 Gold Belt No. 4 lode Sur. No. 3535 brs.

N.9°-38'W. 108.7 feet.

Thence S. 80 -03'W.

1.1 Intersect line 1-2 Gold Belt No.4 lode Sur. No. 3535, S.9°-05'E. 108.7 feet from Cor. No.1

1.5 Intersect line 3-4 Anita No.1 lode of this survey, S.9°-08'E. 108.7 feet from Cor. No.4.

885.0 Cross gulch, flows southwesterly.

1425.0 Cross gulch, flows southerly.

1495.4 COR. NO. 4

An iron pipe 30 inches long fitted with a brass cap 4x4x1 inch thick driven 18 inches into the ground and surrounded by a substantial mound of stone, marked A 4-4-4283 with its center for exact corner point, whence, No bearings available.

Thence N. 9°-08'W.

Intersect the lode line at the WEST CENTER END, built a substantial mound of stone.

127.0 Intersect Cor. No. 4 Anita No.5 lode of this survey, on line 4-1 Gold Belt No. 4 lode Sur. No. 3535 N.80°-45'E.

6.40 feet from Cor. No.4, and S. 80°45'W. 1494.3 feet from

Cor. No.1.

312.0 Cross Gulch, flows southerly.

352.7 Intersect witness Corner to Cor. No.1, heretofore described.

~~this survey.~~

362.0 TO COR NO. 1, and the place of beginning.

MARGOT NO. 17 LODE

Beginning at Cor. No.1 of the Margot No. 17 lode;

Identical with Cor. No. 1 Margot No.16 lode, Cor. No.2

Margot No. 14 lode, Cor. No. 4 Margot No. 15 lode, all of this survey.

An iron pipe 30 inches long fitted with a brass cap 4x4x1 inch thick driven 18 inches into the ground and surrounded by a substantial mound of stone, marked M 17-1, M 16-1, M 14-2, M 15-4-4283 with its center for exact corner point, whence,

Ts. 4 S., Rs. 28 and 29 E.,

The ~~south~~ corner to Secs 7-12-13-14/brs. S. 24°-03'W.

815.6 feet.

No bearings available.

Thence S. 76°-15'-30"W.

1500.0 COR. NO. 2

Identical with Cor. No. 3 Margot No. 15 lode, Cor. No. 2 Anita No. 8 lode, Cor. No. 4 Anita No. 9 lode, all of this survey, previously described.

Thence N. 9°-08'W.

Intersect the lode line at the 300.9 / WEST CENTER END, built a substantial mound of stone.

555.2 COR. NO. 3

Identical with Cor. No. 3 Anita No. 9 lode of this survey, previously described.

Thence N. 76°-05'-30"E.

1500.6 COR. NO. 4

Identical with Cor. No. 2 Margot No. 16 lode of this survey.

An iron pipe 30 inches long fitted with a brass cap 4x4x1 inch thick driven 18 inches into the ground and surrounded by a substantial mound of stone, marked M 17-4, M 16-2-4283 with its center for exact corner point, whence,

A granite rock in place 8x15x4 feet exposed and chiseled BXR M 17-4-4283, brs. N. 18°-29'W. 18.7 feet.

Thence S. 9°-08'E.

Intersect the lode line at the 258.8 / EAST CENTER END, built a substantial mound of stone.

559.5 TO COR. NO. 1, and the place of beginning.

MARGOT NO. 15 LODE

Beginning at Cor. No. 1 of the Margot No. 15 lode;

Identical with Cor. No. 1 Margot No. 14 lode, Cor. No. 1 Margot No. 13 lode, Cor. No. 1 Anita No. 3 lode, all of this survey.

An iron pipe 30 inches long fitted with a brass cap 4x4x1 inch thick driven 18 inches into the ground and surrounded by a substantial mound of stone, marked M 15-1 M 14-1, M 13-1, A 3-1 4283 with its center for exact corner point, whence,

The Section corner to Secs. 7-12-13 & 18, brs. S. 70°-32'W. 453.8 feet.

Thence S. 76°-14'-30"W..

730.0 Cross Dover Mine Road, brs. northwest to southeast.

1500.0 COR. NO. 2

Identical with Cor. No. 4 Anita No. 3 lode, Cor. No. 2 Anita No. 5 lode, Cor. No. 3 Anita No. 8 lode, all of this survey, previously described.

Thence N. 9°-08'W.

Intersect the lode line at the 300.9 WEST CENTER END, built a substantial mound of stone.

506.8 Cross Dover Mine Road, brs. northwest to southeast.

601.8 COR. NO. 3

Identical with Cor. No. 2 Anita No. 8 lode, Cor. No. 4 Anita No. 9 lode, Cor. No. 2 Margot No. 17 lode, all of this survey, previously described.

Thence N. 76°-15'-30"E.

1500.0 COR. NO. 4

Identical with Cor. No. 1 Margot No. 17 lode, Cor. No. 1 Margot No. 16 lode, Cor. No. 2 Margot No. 14 lode, all of this survey, previously described.

Thence S. 9°-08'E.

Intersect the lode line at the 300.7 EAST CENTER END, built a substantial mound of stone.

601.4 TO COR. NO. 1 and the place of beginning.

ANITA NO. 3 LODE.

Beginning at Cor. No. 1 of the Anita No. 3 lode;

Identical with Cor. No. 1 Margot No. 15 lode, Cor. No. 1

Margot No. 14 lode, Cor. No. 1 Margot No. 13 lode, all of

this survey, previously described.

Thence S.9°-08'E.

Intersect the lode line at the
300.7/EAST CENTER END, built a substantial mound of stone.

357.1 Intersect Cor. No. 1 Anita No. 2 lode of this survey.

456.4 Cross gulch, flows westerly.

601.4 COR. NO. 2.
On line 1-2 Anita No. 2 lode of this survey.
Identical with Cor. No.4 Margot No. 13 lode of this survey.
and Cor. No. 1 Margot No. 11 lode Sur. No. 4282.
An iron pipe 30 inches long fitted with a brass cap
4x4x1 inch thick driven 18 inches into the ground and
surrounded by a substantial mound of stone, marked A 3-2,
M 11-1-4282
M 13-4-4283/with its center for exact corner point, whence,
No bearings available.

Thence S.76°-13'-30"W.

350.0 Cross Dover Mine road, brs northeast to southwest.

635.0 Cross gulch, flows southwesterly.

1500.0 COR. NO.3
On line 3-4 Anita No.2 lode, identical with line 2-3
Anita No. 4 lode, both of this survey, and identical with
Cor. No. 3 Anita No. 5 lode of this survey, previously
described.

Thence N.9°-08'W.

7.1 Intersect witness corner to Cor. No.3 of this lode, identical
with Wit. Corner to Cor.No.3 Anita No.5 lode, previously described.

245.1 Intersect Cor. No. 2 Anita No.4 lode identical with Cor.No.
4 Anita No. 2 lode, both of this survey.

Intersect the lode line at the
300.9/WEST CENTER END, built a substantial mound of stone.

601.8 COR. NO. 4.
Identical with Cor. No. 2 Anita No. 5 lode, Cor. No. 3
Anita No. 8 lode & Cor. No. 2 Margot No. 15 lode, all of this
survey, previously described.

Thence N.76°-14'-30"E.

770.0 Cross Dover Mine Road, brs. northwest to southeast.

1500.0 TO COR. NO.1 and the place of beginning.

ANITA NO. 2 LODE.
Beginning at Cor. No.1 of the Anita No. 2 lode;

On line 1-4 Margot No. 13 lode, and line 1-2 Anita No. 3 lode, both of this survey.

An iron pipe 30 inches long fitted with a brass cap 4x4x1 inch thick driven 18 inches into the ground and surrounded by a substantial mound of stone, marked A 2-1-4283 with its center for exact corner point, whence, Ts. 4 S., Rs. 28 and 29 E., The ~~section~~ corner to Sec. 7-12 13 & 18 / brs. N. 67°-26' W. 524.7 feet.

No other bearings available.

Thence S. 9°-08' E.

97.0 Cross gulch, flows westerly.

244.3 Intersect Cor. No. 2 Anita No. 3 lode, Cor. No. 4 Margot No. 13 lode both of this survey, identical with Cor. No. 1 Margot No. 11 lode Sur. No. 4282.

300.9 / EAST CENTER END, built a substantial mound of stone.

463.0 COR. NO. 2

On line 1-4 Margot No. 11 lode Sur. No. 4282, and identical with Cor. No. 1 Anita No. 1 lode of this survey.

An iron pipe 30 inches long fitted with a brass cap 4x4x1 inch thick driven 18 inches into the ground and surrounded by a substantial mound of stone, marked A 2-2, A 1-1-4283 with its center for exact corner point, whence, No bearings available.

Thence S. 76°-25' W.

600.0 Cross Dover Mine road, brs northeast to southwest.

1499.7 COR. NO. 3

~~On line 1-4 Margot No. 11 lode Sur. No. 4282, and identical with Cor. No. 3 Anita No. 4 lode of this survey, heretofore described.~~

~~An iron pipe 30 inches long fitted with a brass cap 4x4x1 inch thick, driven 18 inches into the ground and surrounded by a substantial mound of stone, marked A 2-3, A 4-3-4283 with its center for exact corner point, whence, No bearings available.~~

Thence N. 9°-08' W.

95.0 Cross gulch, flows westerly.

- 108.7 Intersect line 4-1 Anita No. 1 lode of this survey at Witness corner to Cor. No. 4 thereof which is N.80°-34'-30"E. 1.5 feet from said Cor. No.4.
- 159.8 / Intersect the lode line at the WEST CENTER END, a substantial mound of stone.
- 214.7 Intersect Cor. No. 3 Anita No. 3 lode identical with Cor. No. 3 Anita No.5 lode, both of this survey.
- 221.8 Intersect Witness corner to Cor.No.3 Anita No.3 lode, identical with Cor. No. 3 Anita No. 5 lode.
- 459.8 COR. NO.4
On line 3-4 Anita No. 3 lode, identical with line 2-3 Anita No. 5 lode, both of this survey, and identical with Cor. No. 2 Anita No. 4 lode of this survey, previously described.
Thence N.76°-17'-30"E.
- 1325.0 Cross Dover Mine Road, brs. northwest to southeast.
- 1500.0 TO COR. NO. 1 and the place of beginning.
ANITA NO. 1 LODGE.
Beginning at Cor. No.1 of the Anita No.1 lode.
On line 1-4 Margot No. 11 lode Sur. No. 4282, and identical with Cor. No. 2 Anita No. 2 lode of this survey, previously described, whence,
Ts. 4 S., Rs.28 and 29 E.,
The ~~section~~ corner to Secs 7-12-13&18/ brs. N. 40°-17'W.
863.0 feet.
Thence S.9°-08'E.
- 298.9 / Intersect the lode line at the EAST CENTER END, built a substantial mound of stone.
- 382.7 Intersect Cor. No. 4 Margot No.11 lode, identical with Cor. No.1 Margot No. 8 lode both Sur. No. 4282.
- 598.9 COR. NO. 2
On line 1-4 Margot No. 8 lode Sur. No. 4282, and on line 2-3 Gold Belt No.5 lode Sur. No. 3535, S.80°-57'W. 3.1 feet from Cor. No.1
An iron pipe 30 inches long fitted with a brass cap 4x4x1 inch thick driven 18 inches into the ground and surrounded by a substantial mound of stone, marked A 1-2-4283 with its center for exact corner point, whence,
No bearings available.

Thence S.80°-57'W.

- 1010.0 Cross Dover Mine Road brs. southeasterly and northwesterly.
 1495.2 Intersect witness corner to Cor. No. 3 of this lode.
 1496.7 COR. NO. 3.

Identical with Cor. No.2 Gold Belt No.4 lode, Cor. No.2 Gold Belt No.5 lode, and Cor. No.4 Gold Belt No.1 lode all Sur. No. 3535, a point occupied by a post corner set about six inches in the ground, on bed rock, and surrounded by a substantial mound of stone.

~~This corner fell at a point where it was impracticable to set a pipe for corner due to bed rock. From this corner~~

I established a witness corner N.80°-57'E. 1.5 feet;

An iron pipe 30 inches long fitted with a brass cap 4x4x1 inch thick driven 18 inches into the ground and surrounded by a substantial mound of stone, marked W C-A 1-3-4283 with its center for exact corner point. From true cor. pt. Cor. No.1 Gold Belt No.4 lode, brg. N.9°-05'W. 589.0 ft. Sur. No. 3535,
 No bearings available.
 other

Thence N.9°-08'W. (from true cor. pt.)

Intersect the lode line at the
 300.0 / WEST CENTER END, built a substantial mound of stone.

- 480.3 Intersect line 3-4 Anita No.4 lode of this survey, S.80°-03' W. 1.5 feet from Cor. No.3, and 0.4 feet from its intersection with line 1-2 Gold Belt No.4 lode Sur.No.3535.
 575.3 Cross gulch, flows westerly.
 589.0 COR. NO. 4.

On line 1-4 Gold Belt No. 4 lode Sur. No. 3535, S.80°-45'W. 0.5 feet from Cor. No.1.

This corner fell at a point where it was impracticable to set a pipe for corner, due to gravel embankment; from this corner I established a witness corner N.80°-34'-30"E. 1.5 feet, identical with

An iron pipe 30 inches long fitted with a brass cap 4x4x1 inch thick driven 18 inches into the ground and surrounded by a substantial mound of stone, marked W C A 1-4-4283 with its center for exact corner point, whence,

No bearings available.

Thence N.80°-34'-30"E. (from true cor.pt.)

- ~~5 Intersect Cor. No.1 Gold Belt No.4 lode Sur. No.3535, N.9°-05'W.589.0 feet from Cor. No.2 of said lode.~~

- 1.5 Intersect witness corner to Cor. No.4 of this lode, on line
2-3 Anita No. 4 lode identical with line 3-4 Anita No.2
lode, both of this survey.
- 251.8 Cross Gulch, flows westerly.
- 946.80 Cross Dover Mine Road, brs northeast to southwest.
- 1496.8 TO COR. NO.1 and the place of beginning.

MARGOT NO. 16 LODE.

Beginning at Cor. No.1 Margot No. 16 lode;
Identical with Cor. No.4 Margot No.15 lode, Cor. No. 1
Margot No.17 lode, Cor. No.2 Margot No.14 lode, all of this
survey, previously described, whence,
The ~~section~~ corner to sections 7-12-13¹⁸ and 29E.,
Ts.4 S.,Rs.28 and 29E.,
brs. S. 24 -03'W.
815.6 feet.

Thence N.9°-08'W.

- Intersect the lode line at the
300.7 / WEST CENTER END, built a substantial mound of stone.
- 559.5 COR. NO. 2

Identical with Cor. No. 4 Margot No.17 lode of this sur-
vey, previously described.

Thence N.76°-13'E.

- 1500.77 Intersect line 1-4 Anita No.26 lode Sur. No.4256A, N.37°-29'
W. 628.16 feet from Cor. No.4.

- 1500.9 COR. NO.3.

Identical with Cor.No.1Anita No.28 lode of this survey.
An iron pipe 30 inches long fitted with a brass cap
4x4x1 inch thick driven 18 inches into the ground and
surrounded by a substantial mound of stone, marked A 28-1,
M 16-3-4283, with its center for exact corner point, whence
No bearings available.

Thence S.9°-08'E.

- 0.26 Intersect line 1-4 Anita No.26 lode Sur. No. 4256A, N.37°-
29'W. 627.88 feet from Cor. No.4.
- Intersect the lode line at the
272.00 / EAST CENTER END, built a substantial mound of stone.

- 295.0 Cross gulch, flows southwesterly.

- 572.6 TO COR. NO.4 ~~and the place of beginning~~
Identical with Cor. No.4 Anita No.28 lode, Cor. No.3 Anita
No.29 lode, Cor. No.3 Margot No.14 lode, all of this survey.

An iron pipe 30 inches long, fitted with a brass cap 4x4x1 inch thick driven 18 inches into the ground and surrounded by a substantial mound of stone, marked A 28-4, A 29-3, M 14-3, M 16-4-4283 with its center for exact corner point, whence,

No bearings available.

Thence S.76°-42'W.

160.0 Cross gulch, flows southwesterly.

1500.0 TO COR. NO.1 and the place of beginning.

MARGOT NO. 14 LODE.

Beginning at Cor. No.1 Margot No.14 lode

Identical with Cor. No.1 Anita No.3 lode, Cor. No.1

Margot No.15 lode, Cor. No.1 Margot No.13 lode, all of this survey, previously described, whence,

Ts.4 S., Rs.28 and 29 E., The ~~western~~ corner to sections 7-12-13 & 18/ brs. S.70°-32'W.

453.8 feet.

Thence N.9°-08'W.

Intersect the lode line at the

300.7/ WEST CENTER END, built a substantial mound of stone.

601.4 COR. NO.2

Identical with Cor. No.4 Margot No.15 lode, Cor. No. 1

Margot No.17 lode, Cor. No.1 Margot No.16 lode, all of this survey, previously described.

Thence N.76°-42'E.

1340.0 Cross gulch, flows southwesterly.

1500.0 COR. NO.3

Identical with Cor. No.4 Margot No.16 lode, Cor. No.4

Anita No. 28 lode, Cor. No. 3 Anita No. 29 lode, all of this survey, previously described.

Thence S.9°-08'E.

Intersect the lode line at the

300.7/ EAST CENTER END, built a substantial mound of stone.

601.4 COR. NO.4

Identical with Cor. No.2 Anita No.29 lode, Cor. No. 3

Margot No.12 lode, Cor. No. 2 Margot No.13 lode, all of this survey.

An iron pipe 30 inches long fitted with a brass cap
 4x4x1 inch thick driven 18 inches into the ground and
 surrounded by a substantial mound of stone, marked A 29-2,
 M 12-3, M 13-2, M 14-4-4283 with its center for exact cor-
 ner point, whence,

No bearings available.

Thence S, 76°-42'W.

510.0 Cross gulch, flows southwesterly.
 1500.0 TO COR. NO.1 and the place of beginning.

MARGOT NO. 13 LODE.

Beginning at Cor. No.1 Margot No.13 lode;
 Identical with Cor. No.1 Anita No.3 lode, Cor. No.1 Margot
 No.15 lode, Cor. No.1 Margot No.14 lode, previously described
 whence,

Ts. 4 S., Rs.28 and 29 E.,
 The ~~section~~ corner to Secs 7-12-13&18/brs. S.70°-32'W.
 453.8 feet.

Thence N.76°-42'E.

990.0 Cross gulch, flows southwesterly.
 1500.0 COR. NO.2.

Identical with Cor. No. 4 Margot No.14 lode, Cor. No.2
 Anita No. 29 lode, Cor. No. 3 Margot No. 12 lode, all of
 this survey, previously described.

Thence S. 9°-08'E.

Intersect the lode line at the
 300.7 / EAST CENTER END, built a substantial mound of stone.

601.4 COR. NO. 3

Identical with Cor. No. 2 Margot No.12 lode of this
 survey, Cor. No.2 Margot No.11 lode, / Cor. No. 3 Margot No.9 lode,
 Sur. No. 4282.

An iron pipe 30 inches long fitted with a brass cap
 4x4x1 inch thick driven 18 inches into the ground and
 surrounded by a substantial mound of stone, marked M 12-2,
 M 13 -3- 4283; M 11-2, M 9-3-4282 with its center for exact
 Corner point, whence,

A quartzite boulder 4x4x1 foot exposed and chiseled BxR

M 11-2-4282 (no additionable markings possible)brs. S.43
-33'W. 12.1 feet.

Thence S.76°-42'W.

220.0 Cross gulch, flows westerly.

1500.0 COR. NO.4

On line 1-2 Anita No.2 lode of this survey and identical
with Cor. No.2 Anita No.3 lode of this survey, and Cor.1No.
1 Margot No.11 lode, Sur.No. 4282, previously described,whence,
No bearings available.

Thence N.9°-08'W.

144.6 Cross gulch, flows westerly.

244.3 Intersect Cor. No.1 Anita No.2 lode of this survey.

Intersect the lode line at the
300.7 / .WEST CENTER.END, built a substantial mound of stone.

601.4 TO COR. NO.1 and the place of beginning.

ANITA NO. 28 LODE

Beginning at Cor. No.1 Anita No.28 lode;

Identical with Cor. No. 3 Margot No.16 lode of this sur-
vey, previously described, whence,

T. 4 S., R. 29 E.,
The west 1/4 sec.COR.XXNER Section 7,/brs. N. 59°-49'-

00"W. 1963.9 feet.

Thence N.83°-31'E.

297.9 COR. NO.2.

An iron pipe 30 inches long fitted with a brass cap
4x4x1 inch thick driven 18 inches into the ground and
surrounded by a substantial mound of stone, marked A 28-2-

4283 with its center for exact corner point, whence,
Location monument bears N.75° E. 1220 feet.

No bearings available.

Thence S. 9°-08'E.

Intersect the lode line at the
238.5 / EAST CENTER END, built a substantial mound of stone.

536.1 Intersect line 3-4 Anita No. 29 lode of this survey, N.76°
-30'E. 299.0 feet from Cor. No.3.

539.1 COR. NO. 3,

Identical with Cor. No.4 Anita No.26 lode Sur. No. 4256A

An iron pipe 30 inches long fitted with a brass cap
4x4x1 inch thick 12 inches exposed and surrounded by a

substantial mound of stone, marked A 26-4-4256A, A 28-3-4283 with its center for exact corner point, whence, Location monument brs. N.77°-05'E. 1202 feet.
No bearings available.

Thence S.77°-04'-30"W.

298.8 COR. NO.4

Identical with Cor. No. 3 Anita No. 29 lode, Cor. No. 3 Margot No. 14 lode, Cor. No. 4 Margot No. 16 lode, all of this survey, previously described.

Thence N.9°-08'W.

277.6 Cross gulch, flows southwesterly.
Intersect the lode line at the

300.6 WEST CENTER END, built a substantial mound of stone.

572.34 Intersect line 4-1 Anita No. 26 lode Sur. No. 4256A, N.37°-29'W. 627.88 feet from Cor. No.4.

572.6 TO COR., NO. 1 and the place of beginning.

ANITA NO. 29 LODE.

Beginning at Cor. No.1 Anita No. 29 lode;

Identical with Cor. No.4 Margot No.12 lode of this survey,
An iron pipe 30 inches long driven 18 inches into the ground and surrounded by a substantial mound of stone, marked A 29-1, M 12-4-4283 with its center for exact corner point, whence,

The south 1/4 section corner Sec. $\frac{T. 4 S., R. 29 E.,}{7}$ brs. S.62 -29'E. 1782.5 feet.

Cor.No.1 Keystone lode, Sur.No. ³³⁴⁶ 2959, brs.N.77-59-30"W.329.75 feet.
No bearings available.

Thence S.76°-30'W.

242.91 Intersect line 4 Keystone lode Sur. No. 3346, S.34°-37'E. 152.32 feet from Cor. No. 1.

1500.0 COR. NO.2

Identical with Cor. No. 3 Margot No.12 lode, Cor. No.2 and Margot No.13 lode, Cor. No. 4 Margot No.14 lode, all of this survey, previously described.

Thence N.9°-08'W.

Intersect the lode line at the

300.7 WEST CENTER END, built a substantial mound of stone.

601.4 COR.. NO. 3

Identical with Cor. No. 3 Margot No.14 lode, Cor. No.4

- Margot No. 16 lode, & Cor. No. 4 Anita No. 28 lode, all of this survey, previously described.
Thence N. 76°-30'E.
- 297.44 Intersect line 1-4 Anita No. 26 lode Sur. No. 4256A, N. 37°-29'W. 3.27 feet from Cor. No. 4.
- 299.00 Intersect line 2-3 Anita No. 28 lode of this survey, N. 9°-08'W. 3.0 feet from Cor. No. 3.
- 787.40 Intersect line 1-2 Keystone No. 19 lode Sur. No. 3346, N. 3°-01'W, 331.0 feet from Cor. No. 1 and 15.40 feet from its intersection with line 3-4 Anita No. 26 lode Sur. No. 4256A.
- 954.04 Intersect line 2-3 Anita No. 26 lode Sur. No. 4256A N. 37°-29'W. 21.45 feet from Cor. No. 3. Cor. No. 4 said Anita No. 26 lode brs. S. 77°-56'W. 664.2 feet from Cor. No. 3 thereof, and the intersection of line 3-4 Anita No. 26 lode with line 1-2 Keystone No. 19 lode Sur. No. 3346 is 178.22 feet distant.
- 1500.0 COR. NO. 4. An iron pipe 30 inches long fitted with a brass cap 4x4x1 inch thick, driven 18 inches into the ground and surrounded by a substantial mound of stone, marked A 29-4-4283, with its center for exact corner point, whence,
Cor. No. 1 Keystone lode Sur. No. 3346 brs. S. 53°-40'W. 838.50 feet.
Thence S. 9°-08'E.
- 300.8 Intersect the lode line at the EAST CENTER END, -built a substantial mound of stone.
- 334.05 Intersect line 1-2 Keystone lode Sur. No. 3346, N. 55°-06'E. 341.73 feet from Cor. No. 1, and 243.12 feet from its intersection with line 1-4 Keystone No. 19 lode Sur. No. 3346.
- 463.20 Intersect line 1-4 Keystone No. 19 lode Sur. No. 3346, N. 86°-59'E. 750.08 feet from Cor. No. 1 and 220.20 feet from its intersection with line 1-2 Keystone lode Sur. No. 3346
- 601.6 TO COR. NO. 1 and the place of beginning.
MARGOT NO. 12 LODE.
Beginning at Cor. No. 1 Margot No. 12 lode.
Identical with Cor. No. 4 Margot No. 9 lode and Cor. No.

3 Margot No. 10 lode, both Sur. No. 4282.

An iron pipe 30 inches long fitted with a brass cap 4x4x1 inch thick, driven 18 inches into the ground and surrounded by a substantial mound of stone, marked M 12-1-4283, M 9-4, M 10-3-4282 with its center for exact corner point, whence,

T. 4 S., R. 29 E.,

The south 1/4 section corner Sec. 7/brs. S. 81 -13'E.

n 1503.0 feet.

Cor. No.1 Keystone No.1 lode Sur. No. 3346 brs. N.24^{-37'}W.

0"0", 185.7 feet.

Thence S.76°-30'-30"W.

1500.0 COR. NO. 2

Identical with Cor. No. 3 Margot No.13 lode of this survey, Cor. No. 3 Margot No.9 lode and Cor. No. 2 Margot No. 11 lode, both Sur. No. 4282, previously described.

Thence N.9°-08'W.

Intersect the lode line at the
300.7/ WEST CENTER END, built a substantial mound of stone.

601.4 COR. NO.3

Identical with Cor. No.2 Margot No.13 lode, Cor. No. 4 Margot No. 14 lode, Cor. No.2 Anita No. 29 lode all of this survey, previously described.

Thence N.76°-30'E.

1257.09 Intersect line 1-4 Keystone lode Sur. No.3346 N.34 -37'W.
447.68 feet from Cor. No.4.

1500.0 COR. NO.4

Identical with Cor. No. 1 Anita No. 29 lode of this survey previously described.

Thence S.9°-08'E.

300.80 Intersect the lode line at the East Center End, built a
398.62 substantial mound of stone.

Intersect line 1-2 Keystone No.1 lode identical with line
3-4 Keystone lode, both Sur. No.3346, N.55 -06'E. 55.07
feet from Cors No. 1 and 4 respectively.

525.87 Intersect line 4-1 Keystone No.1 lode Sur. No. 3346, S.34 -
46'-30"E. 114.6 feet, from Cor. No.1.

601.6 TO COR. NO.1 and the place of beginning.

LODE LINES

(19)

The presumed course of the vein of each of the several lode locations embraced in this survey, counted from the respective points of discovery, is as follows;

Anita No. 9 lode.

S. 76°-15'-30"W. 27.0 feet and N. 76°-15'-30"E. 1473.0 feet.

Anita No. 8 lode.

S. 76°-15'-30"W. 55.0 feet and N. 76°-15'-30"E. 1445.0 feet.

Anita No. 5 lode.

S. 76°-15'-30"W. 30.0 feet and N. 76°-15'-30"E. 1470.0 feet.

Anita No. 4 lode.

S. 76°-18'-30"W. 1489.8 feet and N. 76°-18'-30"E. 10.0 feet.

Margot No. 17 lode.

S. 76°-15'-30"W. 10.0 feet and N. 76°-15'-30"E. 1490.0 feet.

Margot No. 15 lode

S. 76°-15'W. 55.0 feet and N. 76° 15'E. 1445.0 feet.

Anita No. 3 lode.

S. 76°-14'W. 125.0 feet and N. 76°-14'E. 1375.0 feet.

Anita No. 2 lode.

S. 76°-17'-30"W. 20.0 feet and N. 76°-17'-30"E. 1480.0 feet

Anita No. 1 lode.

S. 80°-57'W. 1466.7 feet and N. 80°-57'E. 30.0 feet.

Margot No. 16 lode.

S. 76°-42'W. 25.0 feet and N. 76°-42'E. 1475.0 feet.

Margot No. 14 lode.

S. 76°-42'W. 15.0 feet and N. 76°-42'E. 1485.0 feet.

Margot No. 13 lode.

S. 76°-42'W. 20.0 feet and N. 76°-42'E. 1480.0 feet.

Anita No. 28 lode.

S. 77°-04'-30"W. 60.0 feet and N. 77°-04'-30"E. 238.8 feet.

Anita No. 29 lode

S. 76°-30'W. 15.0 feet and N. 76°-30'E. 1485.0 feet.

Margot No. 12 lode

S. 76°-30'W. 10.0 feet and N. 76°-30'E. 1490.0 feet.

Area Sheet No.

AREAS

Acres

| | | | |
|--------|--|--------|---|
| 5 | Anita No.1 lode, total area | 20.408 | + |
| 5 | Area in conflict with; Sur. No. 3535, Gold Belt No. 4 lode. | .003 | + |
| 4 | Anita No. 2 lode, total area. | 15.838 | + |
| 7/11 | Area in conflict with; Anita No.1 lode of this survey | 1.866 | + |
| 11 | Anita No.3 lode of this survey | 8.399 | + |
| 4 | Anita No.3 lode, total area | 20.648 | + |
| 2 | Anita No.4 lode, total area | 14.104 | + |
| 10 | Area in conflict with; Sur.No. 3535, Gold Belt No.4 lode. | 4.043 | + |
| 19/2 | Anita No.1 lode of this survey | 0.004 | + |
| 17/2 | Anita No.1 lode of this survey exclusive of its conflict with Gold Belt No.4 lode Sur. No. 3535 | 0.003 | + |
| 10 | Anita No. 5 lode of this survey | 8.239 | + |
| 2 | Anita No.5 lode, total area | 20.460 | + |
| 1 | Anita No.8 lode, total area | 20.656 | + |
| 1 | Anita No. 9 lode, total area | 19.856 | + |
| 8 | Anita No.28 lode. total area | 3.801 | + |
| 12 1/2 | Area in conflict with; Sur. No. 4256A, Anita No. 26 lode. | 1.841 | + |
| 9 | Anita No. 29 lode, total area | 20.653 | + |
| 14/2 | Area in conflict with Sur. No. 3346, Keystone No.19 lode | 6.627 | + |
| 20 | Sur.No.3346, Keystone lode | 1.341 | + |
| 18 | Sur. No. 3346, Keystone lode exclusive of its conflict with Keystone No.19 lode | 1.017 | + |
| 20 | Tract "A" | 0.143 | + |
| 13 | Sur.No.3346 Keystone No.19 lode, exclusive of its conflict with Tract "A" | 6.484 | + |
| 13 | Sur. No. 4256A. Anita No. 26 lode | .170 | + |
| 17 | Sur. No. 4256A Anita No. 26 lode, exclusive of its conflict with Keystone No. 19 lode. | .102 | + |
| 12 | Tract "B" | .031 | + |
| 12 | Sur. No. 4256A Anita No. 26 lode, exclusive of its conflict with Tract "B" | .139 | + |
| 12 | Anita No. 28 lode of this survey | .010 | + |
| 12 | Anita No. 28 lode of this survey, exclusive of its conflict with Sur. No. 4256A Anita No. 26 lode | .010 | + |
| 9 | Margot No. 12 lode. total area | 20.653 | + |
| 5 | Area in conflict with Sur. No. 3346 Keystone lode. | 1.391 | + |
| 16 | Sur. No. 3346 Keystone No.1 lode. | .072 | + |
| 7 1/2 | Margot No. 13 lode, total area | 20.654 | + |
| 7 1/2 | Margot No. 14 lode, total area | 20.654 | + |
| 3 1/2 | Margot No. 15 lode, total area | 20.649 | + |
| 7 1/2 | Margot No. 16 lode, total area | 19.438 | + |
| 12 | Area in conflict with Sur. No. 4256A, Anita No. 26 lode, (nominal), | .000 | + |
| 3 1/2 | Margot No.17 lode, total area | 19.132 | + |

TRACT "A"

That part of a certain area excluded from patent to the
Keystone No. 19 lode Sur. No. 3346 and not included in Sur.

(21)

4256A Anita No.26 lode, is described by metes and bounds as follows: Beginning at a point on line 1-2 Keystone No.19 lode Sur. No. 3346 N.3°-01'W. 258.07 feet from Cor. No.1, thence N.3°-01'W. 57.53 feet, thence N.77°-56'E. 89.02 feet, thence S.34°-57'E. 65.81 feet, thence S.79°-42'W. 123.72 feet to place of beginning, containing 0.143 acres.

TRACT "B"

That part of Tract "C" Sur. No. 4256A, Anita No. 26 lode (an area excluded from patent to Keystone No.19 lode Sur.No. 3346) in conflict with the Anita No. 29 lode of this survey, is described by metes and bounds as follows: Beginning at a point on line 3-4 Anita No. 26 lode Sur. No. 4256A. S.77°-56'W 89.2 feet from Cor. No.3. thence S.77°-56'W. 89.02 feet, thence N.3°-01'W. 15.40 feet; thence N.76°-30'E. 79.35 feet, thence S.34° 57'E. 18.67 feet to place of beginning, containing 0.031 acres.

LOCATION

This survey is located in lots 2,3,4 and 5 Sec. 18, lots 9,10,11,12,13 Sec. 7 T. 4 S.R.29 E. and S.E. 1/4 of S.W. 1/4, S.E. 1/4 of S.E. 1/4, S.W. 1/4 of S.E. 1/4 Sec. 12, and lots 1 and 2, Sec. 13 T.14 S.R. 28 E. of the Gila and Salt River Meridian, Greenlee County, State of Arizona.

The survey of the various lodes embraced in this survey is identical with the respective amended locations as marked on the ground, excepting Anita No. 29 lode which is within the location thereof.

EXPENDITURE OF FIVE HUNDRED DOLLARS

I hereby certify that the value of the labor and improvements made upon or for the benefit of each of the lode locations embraced in said mining claim by the claimant or its grantors is not less than five hundred dollars, and that said improvements consist of;

Anita No. 9 lode.

No.1 The discovery shaft of the Anita No.9 lode, the center of which is on the lode line and bears N.76°-15'-30"E. 27.0 feet from the West Center End, 4x6x8 feet deep.

| | | | |
|------|---|-------------------|--------------------|
| | | Value | \$80.00 |
| No.2 | A cut and tunnel, the mouth of cut brs. N.79 -39'E. 845 feet from Cor. No.2, cut 4x10x10 foot face, tunnel 4x6x20 long brs.westerly. | Value cut tun. | \$75.00 200.00 |
| | <u>Anita No. 8 lode.</u> | | |
| No.1 | The discovery shaft of the Anita No.8 lode, the center of which is on the lode line and bears N.76 -15'-30"E. 55.0 feet from the West Center End, 4x6x8 feet deep. | Value | \$80.00 |
| No.2 | A cut and tunnel, the mouth of cut brs. S. 76 W. 324.0 feet from Cor. No. 2, cut, 4x18x9 foot face, tunnel 4x6x21 feet long, brs. northeasterly. | Value cut Tun. | \$150.00 210.00 |
| No.3 | A cut and tunnel, the mouth of cut brs. S.44 W. 360 feet from Cor. No. 2, cut 4x20x8 foot face, tunnel 4x6x30 feet long brs. easterly. | Value cut Tun. | \$150.00 300.00 |
| No.4 | A cut and tunnel, the mouth of cut brs. N.30 -30'W. 272 feet from Cor. No.3, cut 4x18x8 foot face brs northeast, tunnel 4x6 ^{ft} runs northeasterly 17 feet, thence northerly 25 feet, also southerly 15 feet, total length of tunnel 57 ft. | Value cut tun. | \$150.00 570.00 |
| | <u>Anita No. 5 lode.</u> | | |
| No.1 | The discovery shaft of the Anita No. 5 lode, the center of which is on the lode line and bears N.76 -15'-30"E. 30 feet from the West Center End, 4x6x10 feet deep. | Value | \$100.00 |
| | <u>Anita No. 4 lode</u> | | |
| No.1 | The discovery shaft of the Anita No.4 lode, the center of which is on the lode line and bears S. 80 -45'W. 10.0 feet from the East Center End, 4x6x8 feet deep. | Value | \$80.00 |
| No.2 | A cut and tunnel, the mouth of cut brs. S.58 -45'W. 360 | | |

| | | | |
|---------------------------|--|----------------------|--------------------|
| | feet from Cor. No. 2, cut 4x22x10 foot face, caved, tunnel 4x6x10 feet, caved, brs. easterly. | Value cut tun. | \$200.00 100.00 |
| No. 3 | A shaft, the center of which brs. S.42°-30'W. 267 feet from Cor. No. 2, 5x6x60 feet deep. | Value | \$600.00 |
| <u>Margot No. 17 lode</u> | | | |
| No.1 | The discovery cut of the Margot No.17 lode, the center of the mouth of which is on the lode line and bears N.76°-15'-30"E. 10 feet from the West Center End, 4x11x10 foot face, brs. northeasterly. | Value | \$100.00 |
| No.2 | A cut, the mouth of which brs. N.46°E. 137 feet from Cor. No.2, 4x6x10 foot face, brs northerly. | Value | \$75.00 |
| <u>Margot No.15 lode</u> | | | |
| No.1 | The discovery shaft of the Margot No. 15 lode, the north side of which is on the lode line and bears N.76°-15'E. 55.0 feet from the West Center End, shaft 4x15x8 feet deep, tunnel 4x6x4 feet long, brs northerly from north side of shaft. | Value shaft. tun. | \$200.00 40.00 |
| No.2 | A cut and tunnel, the mouth of cut brs. N.81°W. 160 feet from Cor. No. 1, cut 4x30x12 foot face, tunnel 4x6x75 feet long, brs. northeast. | Value cut tun. | \$300.00 750.00 |
| No.3 | A cut and tunnel, the mouth of cut brs. N.51°E. 370 feet from Cor. No. 2, cut 4x30x12 foot face brs northeast, tunnel 4x6x24 feet long brs easterly. | Value cut tun. | \$300.00 240.00 |
| <u>Anita No. 3 lode.</u> | | | |
| No. 1 | The discovery cut and shaft of the Anita No.3 lode, the north side of face of cut is on the lode line, and bears N.76°-14'E. 125 feet from the West Center End, cut 4x12x6 foot face, shaft, just north of face of cut, 4x6x3 feet below | | |

floor of cut, cut bears northeast.

Value cut \$80.00
Shaft 30.00

Anita No. 2 lode.

No.1 The discovery shaft of the Anita No. 2 lode, the center of which is on the lode line, and bears N.76°-17'-30"E. 20 feet from the West Center End, 4x6x8 feet deep.

Value \$80.00

No.2 A shaft the center of which brs. N.62°-15'E. 325 feet from corner No. 3, 4x6x40 feet deep.

Value \$400.00

Anita No. 1 lode.

No.1 The discovery shaft of the Anita No. 1 lode, the center of which is on the lode line, and bears S.80°-57'W. 30 feet from the East Center End, 4x6x8 feet deep.

Value \$80.00

Margot No. 16 lode

No.1 The discovery cut of the Margot No. 16 lode, the center of the face of which is on the lode line, N. 76°-42'E. 25,0 feet from the West Center End, 4x19x10 foot face, brs north.

Value \$125.00

Margot No. 14 lode

No.1 The discovery cut of the Margot No. 14 lode, the center of the face of which is on the lode line, and bears N.76°-42'E. 15.0 feet from the West Center End, cut 4x19 x11 feet face, bears north.

Value \$125.00

No. 2 A cut, the mouth of which brs. N.74°-45'E. 697 feet from Cor. No. 1, cut 6x15x8 foot face, brs. north.

Value \$100.00

No.3 A shaft, the center of which brs. N.75°-30'E. 712 feet

from Cor. No. 1, 4x6x100 feet deep, (estimated)

Value \$1000.00

No. 4 A cut and tunnel, the mouth of cut brs. S.78°-30'W. 460 feet from Cor. No. 4, cut 4x18x14 foot face, tunnel 4x6x125 feet long brs. northeasterly.

Value cut \$200.00
tun. \$1250.00

No.5 A cut and tunnel, the mouth of cut brs. S.78°-00'W. 558 feet from Cor. No. 4, cut 8x15x8 foot face brs northwest to mouth of tunnel, thence tunnel 4x6 feet runs northwest 55 feet, thence westerly 95 feet (estimated)

Value cut \$250.00
tun. 1500.00

Margot No. 13 lode

No.1 The discovery shaft of the Margot No.13 lode, the center of which is on the lode line, N.76°-42'E. 20 feet from the West Center End, 4x6x8 feet deep.

Value \$80.00

No. 2 A cut, the mouth of which brs. N.78°W. 367 feet from Cor. No.3, 4x15x10 foot face, brs north.

Value \$125.00

No.3 A cut, the mouth of which brs. N.71°W. 257 feet from Cor. No. 3, 4x15x8 foot face, brs north.

Value \$100.00

No.4 A cut, the mouth of which brs. N.17°W 102 feet from Cor. No.3, cut 4x17x8 foot depth (at end line) brs. northeast. This improvement continues on the Margot No.12 lode and is further described as No.5 thereon.

Value \$125.00

No.5 A cut, the mouth of which brs. S.74°W 472 feet from Cor. No.2, 4x23x10 foot face, brs. easterly.

Value \$200.00

No.6 A cut and tunnel, the mouth of cut brs. S. 75°-45'W. 417 feet from Cor. No. 2, cut 4x15x10 foot face, tunnel 4x6x27 feet long bears easterly.

Value cut \$125.00
tun. 270.00

No.7 A cut and tunnel, the mouth of cut brs.N.80°-10'E. 727 feet from Cor. No. 1, cut 4x15x10 foot face, tunnel 4x6x7 feet long, bears northwest.

Value cut \$125.00
tun. 70.00

Anita No. 28 lode.

No.1 The discovery cut, of the Anita No. 28 lode, the center of the face of which is on the lode line, and bears N.77°-04'-30"E. 60 feet from West Center End, cut 4x18x12 feet face, bears northeasterly.

Value \$150.00

Anita No. 29 lode.

No.1 The discovery cut of the Anita No. 29 lode, the center of the mouth of which is on the lode line, and bears N.76°-30'E. 15.0 feet from the West Center End, cut 4x19x11 feet face brs. northeast.

Value \$150.00

No.2 A cut, the mouth of which brs. N.8°W. 293 feet from Cor. No. 2, cut 4x16x8 foot face, brs northeast.

Value \$100.00

Margot No. 12 lode

No.1 The discovery cut of the Margot No. 12 lode, the center of the face of which is on the lode line, and bears N.76°-30'E. 10 feet from the West Center End, 4x18x10 foot face, brs. northerly.

Value 125.00

No.2 A cut and tunnel, the mouth of cut brs. S.71°-30'E. 340 feet from Cor. No. 3, cut 4x36x14 feet face, tunnel 4x6x10 feet long, brs northwesterly.

Value cut \$300.00
tun. \$100.00

No.3 A cut, the mouth of which brs. S. 86°-30'E. 325 feet from Cor. No. 3, cut 4x20x10 feet face brs. north.

Value \$150.00

No.4 A shaft, the center of which brs. N.53°E. 212 feet from Cor. No. 2, 4x6x60 feet deep (estimated)

Value \$600.00

No. 5 A cut and tunnel, the center of cut brs. N.9°-08'W. 108 feet from Cor. No. 2, cut 4x10x12 feet face, tunnel 4x6x50 feet long brs. northeast. This is a continuation of improvement No.4 on the Margot No.13 lode.

Value cut \$250.00
tun. 500.00

An interest in a Common Improvement described as follows;

A privately constructed road, owned by the Dover Copper Mining Company, and constantly maintained and repaired by the company, claimant herein, traverses about 2600 feet across patented mining claims owned by other parties before reaching southerly boundary of the Anita No.1 lode of this survey, thence across this survey as shown in the survey plat, continuing across unsurveyed claims of the company, eventually reaching the operating mine of the company in Horseshoe Canyon, all as shown completely on the common improvement plat describing additional lode claims owned by the Dover Copper Mining Company, sharing in this common improvement.

Value of 9600 foot section of road, original construction costs, together with continuous repairs and yearly maintenance by the Dover Copper Mining Company.

\$17,600.00

Value of one thirty-second interest 550.00

This improvement was constructed for the development, and is also maintained for the development of all of the 15 lodes of this survey, and the Anita No. 6, Anita No.7, Anita No. 10, Anita No.11, Anita No. 12, Anita No. 14, Margot No. 20 Fraction, Anita No. 25 Fraction, Margot No. 18 Fraction, Margot No.19 Fraction, all unsurveyed, also Anita No. 13, Anita No. 15, Anita No. 16, Anita No. 17, Anita No. 18, Anita No,32 and Victory Fraction lodes Sur. No. 4284, which are all the

contiguous lode claims owned in common within the range of benefit and accessibility of said road.

The road traverses a rough mountain slope area, midway through this survey and other lode claims as platted, and with necessary laterals affords the only means of access to the lodes and the most practical and economical means of continuing the development of each of the stated lode claims.

Five hundred dollars or over has been expended in this improvement in such a manner as tends to the development of each lode of this survey and ^{of} 17 additional lodes, hereinbefore named, subsequent to its location and to the time since common ownership and contiguity have prevailed; therefore an undivided one thirty-second interest in its value and expenditure is hereby credited to each of said lodes of this survey, and a like interest apportioned to each of the other stated lodes.

OTHER IMPROVEMENTS

None.

OTHER CORNER DESCRIPTIONS

~~OFFICIAL SURVEYS~~

The West half of the line between Secs. 7 and 18 was found to be N. 89°-44'E. 4927.7 ft instead of East 4935.48 feet.

The corners of Sec: 7 and 18 T. 4 S.R.29 E and Secs. 12 and 13 T. 4 S.R.28E are pipe with cap properly set and marked as called for in the field notes of the official Survey thereof. SUR. NO. 3346.

Cor.No.4 Keystone No.1 lode, Cor. No. 1 Keystone No.1 lode identical with Cor. No. 4 Keystone lode, Cor. No. 1 Keystone lode, Cor. No. 1 and 2 Keystone No. 19 lode are all pine posts firmly set and properly marked.

Line 1-4 Keystone No.1 lode was found to be S.34°-46'-30"E. instead of S.34°-37'E. All other lines of this survey were found to be correct or approximately correct as approved.

SUR. NO. 3535

Cor. No.3 Gold Belt No. 5 lode, Cor. No. 2 Gold Belt No.5 lode identical with Cor. No. 4 Gold Belt No.1 lode, ~~Gold~~

~~Belt No. 1 lode~~ and Cor. No. 2 Gold Belt No. 4 lode, Cor. No. 1 Gold Belt No. 4 lode, Cor. No. 4 Gold Belt No. 4 lode identical with Cor. No. 3 Gold Belt No. 3 lode, are all pine posts, firmly set and properly marked. Line 2-3 Gold Belt No. 5 lode was found to be N.80°-57'E. 1499.8 feet instead of N.80°-50'E. 1500.0 feet. Line 1-2 Gold Belt No. 4 lode was found to be S.9°-05'E. 589.0 feet instead of S.9°-09'E. 589.0 feet. Line 4-1 Gold Belt No. 4 lode was found to be S.80°-45'W. 1500.7 feet instead of S.80°-50'W. 1500 feet.

SUR. NO. 4256A

Cors No. 3 and 4 Anita No. 26 lode are all pipe corners identical in construction with those of this survey and are firmly set and properly marked.

THIS SURVEY

The corners of this survey may be more particularly described as 3/4 inch black pipe 30 inches long fitted with a brass cap 4x4x1 inch thick, which cap was welded onto the upper end of the pipe. The top surface of the cap had the identification "U S MINERAL SURVEY" in raised letters cast in the moulding of the cap. The sides of the cap were smooth surfaces upon which were stamped the designation of the corner and survey.

REPORT.

Owing to the distance from the nearest Notary Public and the expense and delay which would be involved for my assistants to appear before one, I took the acknowledgment of my assistants in my capacity as a Mineral Surveyor.

The discrepancies found existing between the claims as marked by the location monuments and as described in the location notices are due to errors in the location notices.

William Waara
Mineral Surveyor G.L.O.

UNITED STATES
DEPARTMENT OF THE INTERIOR
GENERAL LAND OFFICE

FINAL OATHS FOR SURVEYS

LIST OF NAMES

A list of the names of the individuals employed by J. William Waara

Mineral Surveyor, to assist in running, measuring, and marking the lines, corners, and boundaries

described in the foregoing field notes of the survey of the mining claim of Dover Copper
Mining Company, known as the Anita No. 9, Anita No. 8, Anita No. 5, Anita No. 4
~~Anita No. 3 Anita No. 2 Anita No. 1 Anita No. 28, Anita No. 29, Margot No.~~
17, Margot No. 16, Margot No. 15, Margot No. 14, Margot No. 13 Margot No. 12
known as the lodes

and showing the respective capacities in which they acted.

- Ambrosia Romero, Chainman.
-, Chainman.
-, Axman.
-, Flagman.

FINAL OATHS OF ASSISTANTS

We, Ambrosio Romero

and, do solemnly swear that we assisted J. William Waara

....., United States Mineral Surveyor, in marking the corners and surveying
the boundaries of the mining claim of Dover Copper Mining Co. ^{company} known as the Anita No. 9,
Anita No. 8, Anita No. 5 Anita No. 4 Margot No. 17 Margot No. 15, Anita
~~No. 3 Anita No. 2 Anita No. 1, Margot No. 16 Margot No. 14 Margot No. 13,~~
Anita No. 28, Anita No. 29 and Margot No. 12 lodes.
~~known as the~~

represented in the foregoing field notes as having been surveyed by said mineral surveyor and under his
direction; and that said survey has been in all respects, to the best of our knowledge and belief, faithfully
and correctly executed, and the corner and boundary monuments established according to law and the
instructions furnished by the Office Cadastral Engineer, at Phoenix Arizona.

- Ambrosio Romero Chainman.
-, Chainman.
-, Axman.
-, Flagman.

Subscribed and sworn to by the above-named persons before me this 30

day of May, 19 44

J. William Waara
Mineral Surveyor G.L.O.

4283

UNITED STATES
DEPARTMENT OF THE INTERIOR
GENERAL LAND OFFICE

FINAL OATHS FOR SURVEYS

LIST OF NAMES

A list of the names of the individuals employed by J. William Waara

Mineral Surveyor, to assist in running, measuring, and marking the lines, corners, and boundaries described in the foregoing field notes of the survey of the mining claim of Dover Copper Mining Company, known as the Anita No.9, Anita No.8 Anita No.5 Anita No.4, Margot No.17, Margot No.15, Anita No.3 Anita No.2 Anita No.1 Margot No.16 Margot No. 14 Margot No. 13, Anita No.28, Anita No.29 and Margot No.12
~~known as the~~ Lodes.

and showing the respective capacities in which they acted.

- Federico M. Acuña....., *Chainman.*
- Joe M. Orozco....., *Chainman.*
- Eduardo W. Acuña....., *Axman.*
- Herlindo S. Romero....., *Flagman.*

FINAL OATHS OF ASSISTANTS

We, Federico M. Acuña, Joe M. Orozco, Eduardo W. Acuña and Herlindo S

~~and~~ Romero....., do solemnly swear that we assisted J. William Waara....., Mineral Surveyor, in marking the corners and surveying

the boundaries of the mining claim of Dover Copper Mining Company, known as the Anita No.9, Anita No.8, Anita No.5 Anita No.4, Margot No.17, Margot No.15, Anita No.3, Anita No.2 Anita No.1, Margot No.16, Margot No.14 Margot No.13, Anita No.28, Anita No.29, Margot No.12
~~known as the~~

represented in the foregoing field notes as having been surveyed by said mineral surveyor and under his direction; and that said survey has been in all respects, to the best of our knowledge and belief, faithfully and correctly executed, and the corner and boundary monuments established according to law and the instructions furnished by the Office Cadastral Engineer, at Phoenix Arizona.

- Federico M. Acuña....., *Chainman.*
- Joe M. Orozco....., *Chainman.*
- Eduardo W. Acuña....., *Axman.*
- Herlindo S. Romero....., *Flagman.*

Subscribed and sworn to by the above-named persons before me this 30th day of May, 19 44

J. William Waara
Mineral Surveyor G.L.O.

UNITED STATES
DEPARTMENT OF THE INTERIOR
GENERAL LAND OFFICE

FINAL OATH OF MINERAL SURVEYOR

I, J. William Waara, Mineral Surveyor,
do solemnly swear that, in pursuance of instructions received from the Office Cadastral
Engineer, at Phoenix Arizona, dated March 10. 1944,
I have, in strict conformity to the laws of the United States, the official regulations
and instructions thereunder, and the instructions of said Office Cadastral Engineer,
faithfully and correctly executed the survey of the mining claim of Dover Copper
Mining Company, known as the Anita No. 1, Anita No. 2, Anita, known as the
No. 2, Anita No. 3, Anita No. 4, Anita No. 5 Anita No. 8 Anita No. 9 Anita No. 28
Anita No. 29, Margot No. 12, Margot No. 13, Margot No. 14, Margot No. 15,
M. rgot No. 16, and Margot No. 17 lodes
situate in Copper Mountain Mining District,
Greenlee County, Arizona., in Section
7-18-12-13, Township No. 4 S., Range No. 29 and 28 E.
and designated as Survey No. 4283, as represented
in the foregoing field notes, which accurately show the boundaries of said mining claim
as distinctly marked by monuments on the ground, and described in the attached copy of
the location certificate, which was received by me from the Office Cadastral Engineer
with said instructions, and that all corners of said survey have been established and
perpetuated in strict accordance with the law, official regulations and instructions
thereunder; and I do further solemnly swear that the foregoing are the true and original
field notes of said survey and my report therein, and that the labor expended and im-
provements made upon said mining claim by claimant or its
grantors are as therein fully stated, and that the character, extent, location, and
itemized value thereof are specified therein with particularity and full detail, and
that no portion of said labor or improvements so credited to this claim has been included
in the estimate of expenditures upon any other claim.

J. William Waara
(Mineral Surveyor)

Subscribed and sworn to by the said J. William Waara
Mineral Surveyor, before me Frank E. McKindles, a Notary Public of
Houghton County, State of Michigan this Sixth
day of November, 1944.

Frank E. McKindles
Notary Public

My Commission Expires
June 18, 1947

OFFICE CADASTRAL ENGINEER'S FINAL CERTIFICATE ON FIELD NOTES

United States
Department of the Interior
GENERAL LAND OFFICE
PUBLIC SURVEY OFFICE

Phoenix, Arizona.

May 25, 1945

I, Office Cadastral Engineer at Phoenix, Arizona,

do hereby certify that the foregoing transcript of the Field Notes, return and approval of the survey

of the mining claim of Dover Copper Mining Company, known as the ANITA NO. 1, ANITA NO. 2, ANITA NO. 3, ANITA NO. 4, ANITA NO. 5, ANITA No. 8, ANITA NO. 9, ANITA NO. 28, ANITA NO. 29, MARGOT NO. 12, MARGOT NO. 13, MARGOT NO. 14, MARGOT NO. 15, MARGOT NO. 16, MARGOT NO. 17 lodes

situate in Copper Mountain

Mining District Greenlee County Arizona

in Section 7 and 18 Township No. 4 S., Range No. 28 E.

designated as Survey No. 4283, has been correctly copied from the originals on file in this office; that said Field Notes furnish such an accurate description of said mining claim as will, if incorporated into a patent, serve fully to identify the premises, and that such reference is made therein to natural objects or permanent monuments as will perpetuate and fix the locus thereof.

I further certify that Five Hundred Dollars worth of labor has been expended or improvements made upon, or for the benefit of, each location embraced in said mining claim by claimant or its grantors, and that said improvements consist of 27 cuts, 14 tunnels, 13 shafts, value \$13,915; a 1/32d interest, value \$550, in the value of a road is allotted to each of the 15 lodes of this survey.

and that no portion of said labor or improvements has been included in the estimate of expenditures upon any other claim.

I further certify that the plat thereof, filed in the District Land Office at Phoenix, Arizona is correct and in conformity with the foregoing Field Notes.

E. A. Thompson

Office Cadastral Engineer.

CERTIFICATE OF APPROVAL OF FIELD NOTES AND SURVEY OF
MINING CLAIM

UNITED STATES
DEPARTMENT OF THE INTERIOR
GENERAL LAND OFFICE
PUBLIC SURVEY OFFICE

At Phoenix, Arizona,

May 25, 1945

I, Office Cadastral Engineer at Phoenix, Arizona

do hereby certify that the foregoing and hereto attached Field Notes and Return of the Survey of the

Mining Claim of Dover Copper Mining Company, known as the

ANITA NO. 1, ANITA NO. 2, ANITA NO. 3, ANITA NO. 4, ANITA NO. 5,

ANITA NO. 8, ANITA NO. 9, ANITA NO. 28, ANITA NO. 29, MARGOT NO. 12,

MARGOT NO. 13, MARGOT NO. 14, MARGOT NO. 15, MARGOT NO. 16, MARGOT NO. 17 lodes

situate in Copper Mountain mining district,

Greenlee County, Arizona

in Section s 7 and 18, Township No. 4 S., Range No. 29 E.,
12 and 13, Township No. 4 S., Range No. 28 E.

, designated as Survey No. 4283

executed by J. William Waara, Mineral

Surveyor, March 10 - May 30, 1944, under my instructions dated

March 10, 1944, have been critically examined and the necessary

corrections and explanations made, and the said Field Notes and Return, and the Survey they describe,

are hereby approved. The certified copy of the location certificate filed by the applicant for survey is

on file in this office and a true copy of said certified copy of said location certificate is included and

made a part of the transcript of the field notes.

E. A. Thompson
Office Cadastral Engineer.

UNITED STATES DEPARTMENT OF THE INTERIOR 9605 (942)
BUREAU OF LAND MANAGEMENT M.S. 4283
ARIZONA STATE OFFICE

NOTICE OF CANCELLATION OF MINERAL SURVEY

The Anita No. 1, Anita No. 2, Anita No. 3, Anita No. 4, Anita No. 5 and Anita No. 8 lodes, Mineral Survey No. 4283, located in Townships 4 South, Ranges 28 and 29 East, Gila and Salt River Meridian, Arizona, are hereby canceled. As of this date, this notice of cancellation will become part of the field notes for Mineral Survey No. 4283, page 70.

These claims have not been filed with the Arizona State Office, Bureau of Land Management, in accordance with Section 314, 90 STAT. 2769, (43 U.S.C. 1744).

This cancellation was necessitated to clear the record.

The Mineral Survey Plat should be noted as follows:

"Anita No. 1, Anita No. 2, Anita No. 3, Anita No. 4, Anita No. 5 and Anita No. 8 lodes, M.S. 4283 were canceled February 15, 1996, by memo 9605 (942) M.S. 4283 which is now a part of the original field notes."

February 15, 1996
Date



Acting Chief Cadastral Surveyor of Arizona