

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

MINERAL SURVEY NO. 4484

Arizona Land District.

FIELD NOTES

Of The Survey Of The Mining Claim Of

Clara B. Dickie

Known As The

Omega, Divide, Key Nos. 1 and 2, Keystone Wedge and Moss Millsight lodes

San Francisco Mining District,

Mohave County, Arizona

Sections 19 and 30, Township 20 N., Range 20 W., G&SRM

Surveyed under order dated April 14, 1959

by Olaf Hondrum
Mineral Surveyor.

Claim located (See reverse), 19

Survey commenced April 15, 1959

Survey completed April 30, 1959

Address of claimant c/o James J. Dwight, Attorney at Law
7000 East Camelback
Scottsdale, Arizona

DATES OF AMENDED LOCATIONS

See reverse

<u>Amended</u> <u>Location Date</u>	<u>Location Date</u>	<u>Name of Claim</u>
5-21-58	1-1-15	Omega
5-21-58	11-16-15	Divide
5-21-58	7-1-28	Key No. 1
5-21-58	7-1-28	Key No. 2
5-21-58	1-1-15	Keystone Wedge
8-30-22 5-21-58	7-1-22	Moss Millisight

Survey No. 4484

1

Obstacles
Feet

This survey was made with a K & E transit, No. 129403, with horizontal limb 6.2 ins. diam., having two double opposite verniers, and full vertical circle 5 ins. diam., having one double vernier; the verniers read to one minute of arc; the eyepiece is equipped with a colored glass for making direct observations upon the sun. The instrument was in good condition at the time of the survey and all the adjustments were in good order.

All azimuths in this record were determined by the method of deflection angles referred to the meridian established by direct observation on the sun April 11, 1959, at Cor. No. 4 of the Keystone Wedge lode, latitude $35^{\circ} 06' N.$, longitude $114^{\circ} 26' 45'' W.$, turning from a reference point in a NW direction clockwise to the sun in the SE direction.

True bearing of the reference point: $N. 77^{\circ} 20' W.$

The lines were measured with a Lufkin steel tape 300 ft. in length, graduated every foot, with the first and last foot graduated to hundredths of a foot. The tape was compared with a standard of the Arizona Highway Department and found correct.

All lines and connections of this survey were run by direct methods where the lines are accessible; the inaccessible lines were run by traverse methods, as shown by the calculation sheets herewith submitted.

The magnetic declination observed at each corner of the survey gave a uniform value of $15^{\circ} 30' E.$

Survey No. 4484

OMEGA LODE

At Cor. No. 1 of the Omega lode, identical with Cor. No. 1 of the Divide lode of this survey.

Set an iron post, 42 ins. long, $1\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd. O-1-D-1-4484; from which

The $\frac{1}{4}$ Sec. cor. of Secs. 19 and 30, T. 20 N., R. 20 W., G&SRM, bears $S. 58^{\circ} 24' W.$, 187.1 ft. dist; an iron post, $1\frac{1}{2}$ ins. diam., 28 ins. above ground, marked and witnessed as described in the official record.

A rock ledge, 6 ft. above ground, bears $S. 89^{\circ} 32' W.$, 104.4 ft. dist., mkd. XBO-0-1-4484.

Thence $S. 8^{\circ} 15' E.$

230.0 Gully, 5 ft. wide, course SE.

300.0 Lode line; discovery pt. bears $S. 89^{\circ} 54' W.$, 240 ft. dist.

353.2 Cor. No. 1, Sur. No. 2213, Ruth lode, identical with Cor. No. 1, Keystone Wedge lode of this survey.

475.0 Ridge, bears NW and SE.

600.0 Cor. No. 2, on line 4-1, Sur. No. 2213, Ruth lode.

Set an iron post, 42 ins. long, $1\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd. O-2-4484; from which

Feet	Cor. No. 7, Sur. No. 857, Rattan lode, bears N. 89° 54' E., 378.2 ft. dist. A rock ledge, 1/4 ft. above ground, bears N. 22° 34' E., 35.8 ft. dist., mkd. X BO-0-2-4484. Thence S. 89° 54' W.
50.0	Gully, 5 ft. wide, course S.
268.0	Ridge, bears NW and SE.
782.0	Road, bears NW and SE.
1268.0	Gully, 8 ft. wide, course S.
1309.0	Road, bears N. and S.
1500.0	Cor. No. 3, Set an iron post, 1/2 ins. long, 1 1/2 ins. diam., 2 1/4 ins. in the ground, with aluminum cap mkd. O-3-4484; from which Cor. No. 2, Sur. No. 857, Rattan lode, bears S. 89° 19' E., 384.87 ft. dist. A rock ledge, 1/4 x 6 ft., 18 ins. above ground, bears S. 70° 40' W., 131.4 ft. dist., mkd. X BO-0-3-4484. Thumb of Mitten Mtn., a distant peak, bears S. 0° 42' E. Thence N. 8° 15' W.
300.0	Lode line; discovery point bears N. 89° 54' E., 1260 ft. dist.
600.0	Cor. No. 4, identical with Cor. No. 4 of the Moss Millsight lode of this survey. Set an iron post, 1/2 ins. long, 1 1/2 ins. diam., 2 1/4 ins. in the ground, with aluminum cap mkd. O-4-MM-4-4484; from which A boulder, 2 x 3 ft., 1-foot above ground, bears N. 15° 33' E., 27 ft. dist., mkd. X BO-0-4-4484. Thence N. 89° 54' E.
122.0	Road, bears NW and SE.
571.9	Cor. No. 2 of the Divide lode, identical with Cor. No. 5 of the Moss Millsight lode, both of this survey.
872.0	Ridge, bears NW and SE.
1472.0	Road, bears NW and SE.
1500.0	Cor. No. 1, and place of beginning.

DIVIDE LODE

Beginning at Cor. No. 1 of the Divide lode, identical with Cor. No. 1 of the Omega lode of this survey.

Chains Feet	
	Thence S. 89° 54' W.
28.0	Road, bears NW and SE.
628.0	Ridge, bears NW and SE.
928.1	Cor. No. 2, identical with Cor. No. 5 of the Moss Millsight lode of this survey, on line 4-1, Omega lode of this survey. Set an iron post, 42 ins. long, 1½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. D-2-MM-5-4484; from which A rock ledge, 8 ft. above ground, bears N. 31° E., 33 ft. dist., mkd. X BO-D-2-4484. Thence N. 8° 15' W.
100.0	Lode line; discovery point bears N. 89° 54' E., 528.1 ft. dist.
284.3	Cor. No. 3, identical with Cor. No. 4, Key No. 1 lode, Cor. No. 1, Key No. 2 lode, and Cor. No. 1, Moss Millsight lode, all of this survey. Set an iron post, 42 ins. long, 1½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. D-3-K1-4-K2-1-MM-1-4484; from which A rock ledge bears S. 82° 50' E., 2.5 ft. dist., mkd. X BO-D-3-4484. Thence S. 82° 50' E.
44.0	Ridge, bears NE and SW.
137.0	Ridge, bears NE and SW.
896.0	Road, bears NE and SW.
953.0	Cor. No. 4, on line 1-2, Keystone Wedge lode of this survey, and on line 4-1, Key No. 1 lode of this survey. Set an iron post, 42 ins. long, 1½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. D-4-4484; from which A rock ledge bears S. 87° 45' E., 67.4 ft. dist., mkd. X BO-D-4-4484. Thence S. 8° 15' E.
62.5	Lode line; discovery point bears S. 89° 54' W., 400 ft. dist.
112.5	Gully, 5 ft. wide, course SE.
162.5	Cor. No. 1, and place of beginning.

Key No. 1 lode

Beginning at Cor. No. 1, identical with Cor. No. 2, Sur. No. 182, California Moss lode. Corner missing; location determined from data on plat, Sur. No. 2213, Ruth lode.

Set an iron post, 42 ins. long, 1½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. CM-2-182-K1-1-4484; from which

The ¼ cor. of Secs. 19 and 30 bears S. 74° 19' W., 705.1 ft. dist., previously described.

Obvious	U.S.L.M.No.1 bears N. 87° 50' W., 132.0 ft. dist; a 3/4-in. steel rod, firmly set, 6 ins. above ground. A rock ledge, 6 ft. long, 3 ft. above ground, bears N. 35° 49' E., 149 ft. dist., mkd. X BO-K1-1-4484. Thence N. 12° 40' E.
35.0	Road, bears NW and SE.
245.92	Intersect line 2-3, Keystone Wedge lode of this survey.
272.0	Ridge, bears SE and NW.
300.0	Lode line; discovery point bears N. 82° 50' W., 570. ft. dist.
573.0	Road, bears NW and SE.
600.0	Cor. No. 2. Set an iron post, 42 ins. long, 1½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. K1-2-4484; from which Cor. No. 5, Sur. No. 182, California Moss lode, bears S. 22° 08' E., 15.55 ft. dist. A rock ledge, 4 ft. high, bears N. 42° 52' E., 113.6 ft. dist., mkd. X BO-K1-2-4484. Thence N. 82° 50' W.
353.0	Ridge, bears NE and SW.
776.0	Wash, 20 ft. wide, course SE.
1500.0	Cor. No. 3, identical with Cor. No. 4, Key No. 2 lode of this survey. Set an iron post, 42 ins. long, 1½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. K1-3-K2-4-4484; from which A boulder, 4 x 6 ft., 15 ft. high, bears S. 75° 50' E., 27.4 ft. dist., mkd. X BO-K1-3-4484. Thence S. 12° 40' W.
80.0	Base of cliff.
300.0	Lode line; discovery point bears S. 82° 50' E., 930 ft. dist.
600.0	Cor. No. 4, identical with Cor. No. 3, Divide, Cor. No. 1, Moss Mill-sight, and Cor. No. 1, Key No. 2 lodes, all of this survey. Thence S. 82° 50' E.
44.0	Ridge, bears NE and SW.
137.0	Ridge, bears NE and SW.
896.0	Road, bears NE and SW.
953.0	Cor. No. 4, Divide lode of this survey.
1160.0	W. edge of gulch, course SE.
1240.0	E. edge of gulch, course SE.

Station Feet	
1500.0	Cor. No. 1 and place of beginning.
	Key No. 2 lode
	Beginning at Cor. No. 1, identical with Cor. No. 4, Key No. 1 lode, Cor. No. 3, Divide lode, & Cor. No. 1, Moss Millsight lode, all of this survey; from which
	The $\frac{1}{4}$ cor. of Secs. 19 and 30 bears S. 65° 00' E., 893.3 ft. dist.
	Thence N. 67° 59' W.
62.0	Ridge, bears NE and SW.
1090.0	Ridge, bears NE and SW.
1416.9	Cor. No. 2, identical with Cor. No. 2 of the Moss Millsight lode of this survey.
	Set an iron post, 42 ins. long, 1 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd. K2-2-MM-2-4484; from which
	A boulder, 2 x 3 ft., 2 ft. high, bears N. 12° 40' W., 21.7 ft. dist., mkd. X BO-K2-4484.
	Thence N. 12° 40' E.
300.0	Lode line; discovery point bears S. 67° 59' E., 1076.9 ft. dist.
600.0	Cor. No. 3.
	Set an iron post, 42 ins. long, 1 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd. K2-3-4484; from which
	A rock ledge, 4 ft. above ground, bears S. 39° 32' E., 44.4 ft. dist., mkd. X BO-K2-3-4484.
	Thence S. 67° 59' E.
1005.0	Base of cliff, bears N. and S.
1416.9	Cor. No. 4, identical with Cor. No. 3, Key No. 1 lode of this survey.
	Thence S. 12° 40' W.
80.0	Base of cliff.
300.0	Lode line; discovery point bears N. 67° 59' W., 340 ft. dist.
600.0	Cor. No. 1, and place of beginning.
	MOSS MILLSIGHT LODE
	Beginning at Cor. No. 1 of the Moss Millsight lode, identical with Cor. No. 3, Divide lode, Cor. No. 4, Key No. 1 lode, and Cor. No. 1, Key No. 2 lode, all of this survey.

	Thence N. 67° 59' W.
62.0	Ridge, bears NE and SW.
1090.0	Ridge, bears NE and SW.
1416.9	Cor. No. 2, identical with Cor. No. 2, Key No. 2 lode of this survey.
	Thence S. 8° 15' E.
265.5	Lode line; discovery point bears S. 72° 10' E., 280 ft. dist.
565.5	Cor. No. 3.
	Set an iron post, 42 ins. long, 1½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. MM-3-4484; from which
	A rock ledge, 20 ft. wide, 15 ft. above ground, bears N. 51° 42' E., 20.6 ft. dist., mkd. X BO-MM3-4484.
	Thumb on Mitten Mtn., bears S. 4° 06' E.
	Thence S. 70° 06' E.
455.0	Road, bears E. and W.
745.8	Cor. No. 4, identical with Cor. No. 4 of the Omega Lode of this survey.
	Thence N. 89° 54' E.
122.0	Road, bears NW and SE.
571.9	Cor. No. 5, identical with Cor. No. 2 of the Divide lode of this survey, and on line 4-1, Omega lode of this survey.
	Thence N. 8° 15' W.
134.0	Lode line; discovery point bears N. 72° 10' W., 1082.4 ft. dist.
284.3	Cor. No. 1, and place of beginning.
KEYSTONE WEDGE LODGE	
Beginning at Cor. No. 1 Keystone Wedge lode, identical with Cor. No. 1, Sur. No. 2213, Ruth lode, a 4 x 4 in. wooden post, rotted at the ground, replaced with	
An iron post, 42 ins. long, 1½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. KW-1-4484-R-1-2213; from which	
The ¼ sec. cor. of Secs. 19 and 20 bears N. 39° 52' W., 327.67 ft. dist.	
A rock ledge, 2 ft. above ground, bears S. 86° 14' W., 87 ft. dist., mkd. X BO-KW-1-4484.	
	Thence N. 8° 15' W.
123.2	Gully, 5 ft. wide, course SE.
300.0	Lode line; discovery point bears N. 81° 45' E., 78 ft. dist.
353.2	Cor. No. 1, Omega lode, identical with Cor. No. 1, Divide lode of this survey.

Chains feet	
515.7	Cor. No. 4, Divide lode, on line 4-1, Key No. 1 lode, both of this survey.
600.0	Cor. No. 2. Set an iron post, 42 ins. long, $1\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd. KW-2-4484; from which Cor. No. 2, Sur. No. 182, California Moss lode, identical with Cor. No. 1 of the Key No. 1 lode of this survey bears S. 74° 43' E., 575.18 ft. dist. A rock ledge, 3 ft. above ground, bears S. 35° 54' E., 77 ft. dist., mkd. X BO-KW-2-4484. Thence N. 81° 45' E.
310.0	Road, bears NW and SE.
615.11	Intersect line 1-2 of the Key No. 1 lode of this survey.
619.12	Intersect line 2-5, Sur. No. 182, California Moss lode at a point from which Cor. No. 2 bears S. 13° 32' W., 247.38 ft. dist.
712.0	Road, bears NE and SW.
805.0	Ridge, bears S. 78° E., and N. 78° W.
1500.0	Cor. No. 3. Set an iron post, 42 ins. long, $1\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd. KW-3-4484; from which A boulder, 4 x 4 ft., 2 ft. above ground, bears S. 50° 51' W., 53.1 ft. dist., mkd. X BO-KW-3-4484. Thence S. 8° 15' E.
300.0	Lode line; discovery point bears S. 81° 45' W., 1422 ft. dist.
587.29	Intersect line 2-3, Sur. No. 182, California Moss lode, at a point from which Cor. No. 2 bears N. 78° 04' W., 1036.31 ft. dist.
600.0	Cor. No. 4, identical with Cor. No. 2, Sur. No. 2213, Ruth lode, a 4 x 4 in. wooden post, rotted at the ground, replaced with an iron post, 42 ins. long, $1\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd. KW-4-4484-R-2-2213; from which Cor. No. 3, Sur. No. 182, California Moss lode bears S. 79° 36' E., 446.07 ft. dist. A boulder, 2 ft. above ground, bears N. 52° 22' E., 138.5 ft. dist., mkd. X BO-KW-4-4484. Thence S. 81° 45' W.
125.0	Gully, 6 ft. wide, course S.
735.0	Road, bears NW and SE.
1062.0	E. bank gulch, 65 ft. wide, course SE.
1500.0	Cor. No. 1, and place of beginning.

Chains

AREAS

Acres

Total area, Omega lode	20.452
Total area, Divide lode	4.712
Total area, Key No. 1 lode	20.566
Total area, Key No. 2 lode	19.257
Total area, Moss Millsight lode	13.611
Total area, Keystone Wedge lode	20.661
Area in conflict with:	
Key No. 1 lode of this survey	2.132
Sur. No. 182, California Moss lode	8.879

LOCATION

This survey is located in the S $\frac{1}{2}$ of Sec. 19 and the N $\frac{1}{2}$ of Sec. 30, T. 20 N., R. 20 W., G&SRM.

The survey of all lodes is identical with the respective amended locations, as marked on the ground.

EXPENDITURES

The improvements and the value of the labor and improvements made upon or for the benefit of each of the lode locations embraced in said mining claim by the claimant or her grantors are as follows:

Omega Lode

- No. 1 The discovery point of the Omega lode is on the lode line, 240 ft. from the center of line 1-2.
- No. 2 A cut of the Omega lode bears N. 77° 45' W., 206 ft. dist. from the center of end line 1-2; 5 x 15-foot, 7-foot face, runs S. 20° W. Value, \$100.00
- No. 3 A cut bears N. 58° 40' W., 140 ft. dist. from Cor. No. 2, Omega lode; 4 x 6 ft., 6-foot face, with a tunnel at the end, 4 x 5 ft., 10 ft. long, runs N. 65° W. Value, \$125.00
- No. 4 A cut bears N. 71° 05' W., 220 ft. dist. from Cor. No. 2, Omega lode, 4 x 20 ft., 8 ft. face, with a tunnel at the end, 4 x 5 ft., 12 ft. long, runs N. 74° W. Value, \$200.00
- No. 5 A cut bears N. 75° 10' W., 270 ft. dist. from Cor. No. 2, Omega lode, 5 x 15 ft., 9 ft. face, with a shaft at the end, 5 x 5 ft., 5 ft. deep, runs N. 40° W. Value, \$150.00
- No. 6 A cut bears N. 75° W., 461 ft. dist. from Cor. No. 2, Omega lode, 6 x 15 ft., 9-foot face, runs N. 73° E. Value, \$75.00
- No. 7 A shaft, the center of which bears N. 76° 15' W., 400 ft. dist. from Cor. No. 2, Omega lode, 5 x 6 ft., 6 ft. deep. Value, \$100.00
- No. 8 A shaft, the center of which bears N. 76° 25' W., 425 ft. dist. from Cor. No. 2, Omega lode, 3 x 6 ft., 4 ft. deep. Value, \$60.00
- No. 9 A cut bears N. 83° 30' W., 340 ft. dist. from Cor. No. 2, 5 x 20 ft., 10-foot face, runs N. 32° E. Value, \$100.00

~~OTHERS~~

- No. 10 A shaft, the center of which bears N. $64^{\circ} 15'$ E., 391 ft. dist. from Cor. No. 3, Omega lode, 7 x 8 ft., 5 ft. deep.
Value, \$150.00
- No. 11 A cut bears N. 2° W., 320 ft. dist. from Cor. No. 3, Omega lode, 5 x 10 ft., 5-foot face, runs N. 55° E.
Value, \$60.00
- Divide lode
- No. 1 The discovery point of the Divide lode is on the lode line 400 ft. from a point on line 4-1, 100 ft. from Cor. No. 1.
- No. 2 A cut of the Divide lode bears S. $86^{\circ} 35'$ W., 402 ft. dist. from Cor. No. 1, 5 x 15 ft., 8-foot face, runs S. 75° W.
Value, \$150.00
- No. 3 A cut bears N. 83° W., 531 ft. dist. from Cor. No. 4, Divide lode, 4 x 18 ft., 10-foot face, runs south.
Value, \$150.00
- No. 4 A cut bears S. $67^{\circ} 50'$ W., 84 ft. dist. from Cor. No. 4, Divide lode, 4 x 18 ft., 6-foot face, runs S. 12° E.
Value, \$100.00
- No. 5 A cut bears N. 80° W., 105 ft. dist. from Cor. No. 1, Divide lode, 4 x 15 ft., 9-foot face, runs S. 15° W.
Value, \$150.00
- Key No. 1 lode
- No. 1 The discovery point of the Key No. 1 lode is on the lode line 570 ft. from the center of line 1-2.
- No. 2 A cut of the Key No. 1 lode bears N. 55° E., 20 ft. dist. from the discovery point, 8 x 60 ft., 8 ft. deep, runs N. 80° W.
Value, \$400.00
- No. 3 A cut bears S. $79^{\circ} 25'$ W., 547 ft. dist. from the discovery point, Key No. 1 lode, 5 x 10 ft., 5-foot face, runs N. 80° W.
Value, \$75.00
- No. 4 A shaft, the center of which bears S. 80° W., 765 ft. dist. from the discovery point, Key No. 1 lode, 4 x 6 ft., 10 ft. deep.
Value, \$150.00
- No. 5 A cut bears S. $80^{\circ} 30'$ W., 790 ft. from the discovery point, Key No. 1 lode, 4 x 18 ft., 8-foot face, runs N. 80° W.
Value, \$100.00
- No. 6 A tunnel, the portal of which bears N. $80^{\circ} 30'$ W., 615 ft. dist. from the discovery point, Key No. 1 lode, 4 x 8 ft., 20 ft. long, runs N. 12° E.
Value, \$200.00
- No. 7 A cut bears N. $79^{\circ} 30'$ W., 654 ft. dist. from the discovery point, Key No. 1 lode, 5 x 4 ft., 6-foot face, with a tunnel at the end, 4 x 5 ft., 6 ft. long, runs N. 10° E.
Value, \$100.00
- No. 8 A shaft bears N. 68° W., 172 ft. dist. from Cor. No. 1, Key No. 1 lode, 7 x 8 ft., 10 ft. deep.
Value, \$150.00

Chains

No. 9 A cut bears N. 16° 30' W., 320 ft. dist. from Cor. No. 1, Key No. 1 lode, 5 x 30 ft., 10-foot face, runs west.
Value, \$150.00

No. 10 A shaft, the center of which bears N. 6° 30' W., 323 ft. dist. from Cor. No. 1, Key No. 1 lode, 4 x 6 ft., 25 ft. deep.
Value, \$400.00

No. 11 A cut bears N. 2° 45' W., 320 ft. dist. from Cor. No. 1, Key No. 1 lode, 5 x 12 ft., 8-foot face, runs N. 10° E.
Value, \$100.00

No. 12 A cut bears N. 40° 30' E., 50 ft. dist. from Cor. No. 4, Key No. 1 lode, 5 x 14 ft., 8-foot face, runs N. 65° E.
Value, \$190.00

No. 13 A cut bears N. 40° E., 90 ft. dist. from Cor. No. 4, Key No. 1 lode, 4 x 10 ft., 6-foot face, runs S. 70° E.
Value, \$75.00

No. 14 A shaft, the center of which bears N. 53° E., 95 ft. dist. from Cor. No. 4, Key No. 1 lode, 4 x 6 ft., 5 ft. deep.
Value, \$75.00

Key No. 2 lode

No. 1 The discovery point of the Key No. 2 lode is on the lode line 340 ft. from the center of line 4-1.

No. 2 A cut of the Key No. 2 lode bears S. 89° 30' W., 379 ft. dist. from Cor. No. 4, 5 x 10 ft., 6-foot face, runs N. 5° E.
Value, \$150.00

No. 3 A cut bears N. 87° W., 502 ft. dist. from Cor. No. 4, Key No. 2 lode, 4 x 10 ft., 7-foot face, runs N. 65° W.
Value, \$50.00

No. 4 A cut bears S. 75° 30' W., 418 ft. dist. from Cor. No. 4, Key No. 2 lode, 5 x 8 ft., 5-foot face, runs N. 20° W.
Value, \$75.00

No. 5 A cut bears S. 80° 30' E., 595 ft. dist. from Cor. No. 2, Key No. 2 lode, 5 x 12 ft., 10-foot face, runs N. 71° E.
Value, \$250.00

Moss Millsight lode

No. 1 The discovery point of the Moss Millsight lode is on the lode line 280 ft. from a point on line 2-3, 265.5 ft. from Cor. No. 2.

No. 2 A cut of the Moss Millsight lode bears N. 35° 10' E., 360 ft. dist. from Cor. No. 3, 5 x 15 ft., 6-foot face, runs N. 60° E.
Value, \$75.00

No. 3 A cut bears N. 42° 30' E., 350 ft. dist. from Cor. No. 3, Moss Millsight lode, 5 x 15 ft., 5-foot face, runs N. 43° E.
Value, \$75.00

No. 4 A cut bears S. 34° E., 96 ft. dist. from Cor. No. 2, Moss Millsight lode, 10 x 10 ft., 6-foot face, runs east.
Value, \$100.00

No. 5 A cut bears N. 42° 55' W., 195 ft. dist. from Cor. No. 4, Moss Millsight lode, 5 x 12 ft., 7-foot face, runs N. 7° West.
Value, \$75.00

CLAIMS

- No. 6 A cut bears N. 44° 15' W., 215 ft. dist. from Cor. No. 4, Moss Millsight lode, 5 x 8 ft., 7-foot face, runs N. 5° W.
Value, \$75.00
- No. 7 A shaft, the center of which bears N. 51° 15' W., 240 ft. dist. from Cor. No. 4, Moss Millsight lode, 4 x 6 ft., 6-ft. deep.
Value, \$120.00
- No. 8 A cut bears N. 80° E., 40 ft. dist. from Cor. No. 4, Moss Millsight lode, 8 x 12 ft., 5-foot face, runs N. 80° E.
Value, \$75.00
- Keystone Wedge Lode
- No. 1 The discovery point of the Keystone Wedge lode is on the lode line, 78 ft. from the center of line 1-2.
- No. 2 A shaft of the Keystone Wedge lode, the center of which bears S. 86° E., 80 ft. dist. from the center of end line 1-2, 5 x 6 ft., 8-ft. deep.
Value, \$150.00
- No. 3 A cut bears S. 25° 20' E., 110 ft. dist. from the center of end line 1-2, Keystone Wedge lode, 5 x 20 ft., 7-foot face, runs S. 32° W.
Value, \$100.00
- No. 4 A cut bears N. 44° E., 170 ft. dist. from the center of end line 1-2, Keystone Wedge lode, 5 x 15 ft., 8-foot face, runs N. 5° E.
Value, \$75.00
- No. 5 A shaft, the center of which bears N. 59° E., 215 ft. dist. from the center of end line 1-2, Keystone Wedge lode, 5 x 5 ft., 6 ft. deep.
Value, \$100.00
- No. 6 A cut bears N. 84° E., 440 ft. dist. from the center of end line 1-2, Keystone Wedge lode, 5 x 35 ft., 8-foot face, with a shaft at the end, 6 x 6 ft., 10 ft. deep, runs N. 62° E.
Value, \$300.00
- No. 7 A cut bears N. 77° 30' E., 492 ft. dist. from the center of end line 1-2, Keystone Wedge lode, 12 x 10 ft., 5-foot face, runs N. 64° E.
Value, \$50.00
- No. 8 A shaft, the center of which bears N. 22° 55' E., 190 ft. dist. from Cor. No. 1, Keystone Wedge, 5 x 10 ft., 35 ft. deep.
Value, \$700.00

COMMON IMPROVEMENTS

A shaft, the center of which bears W. 15 ft. dist. from the discovery point of the Key No. 1 lode, 5 x 10 ft., 330 ft. deep.
Claimants share 100 ft.

Value, \$5000.00
Value of 1/3 interest, \$1,666.67

A drift, 5 x 6 ft. in size, runs in a southerly direction from the shaft 100 ft.; thence easterly a distance of 500 ft.

Value, \$6000.00
Value of 1/3 interest, \$2000.00

A diamond drill hole, 590 ft. deep, bears S. 72° W., 610 ft. dist. fr. the discovery point of the Key No. 1 lode.

Value, \$3800.00
Value of 1/3 interest, \$1266.67

Chains

The above described improvements are deemed common improvements to the Key No. 1, Key No. 2 and Divide lodes, being contiguous locations on the strike of the veins, with the surface rising rapidly to the west of the shaft.

Five hundred dollars or over has been expended in these improvements in such a manner as tends to the development of each of the above named lodes of this survey subsequent to its location and to the time since which common ownership and contiguity have prevailed; therefore, an undivided one-third of its value is hereby credited to each of said lodes. No portion or interest in these improvements has been credited heretofore as patent expenditure to any lode claim.

OTHER IMPROVEMENTS

A tunnel, 5 x 7 ft. in size, the portal of which bears N. 81° 30' W., 295 ft. dist. from Cor. No. 1, Key No. 1 lode; thence N. 6° 45' E., 270 ft.; thence N. 81° 30' W., 155 ft.; thence N. 65° W., 60 ft.; thence N. 70° W., 52 ft. to the shaft. Claimant unknown.

A tunnel, 5 x 6 ft. in size, the portal of which bears N. 65° E., 32 ft. dist. from the discovery point of Key No. 1 lode; thence S. 72° E., 42 ft. to face. Claimant unknown.

A tunnel, 4 x 6 ft. in size, the portal of which bears S. 50° E., 30 ft. dist. from the discovery point of Key No. 1 lode; thence S. 78° E., 75 ft. to face. Claimant unknown.

OTHER CORNER DESCRIPTIONS AND DATA

Sur. No. 2213, Ruth lode: Cors. Nos. 1 and 2, 4 x 4 in. wooden posts, rotted at the ground, were replaced with iron posts, 1 1/2 ins. diam. Line 1-2 was found to be N. 81° 45' E., instead of N. 81° 35' E., as approved. Line 4-1 was found to be N. 8° 15' W., instead of N. 8° 25' W., as approved. Cor. No. 4 is a 4 x 4 in. wooden post.

Sur. No. 182, California Moss lode: Cor. No. 2 was reset with an iron post 1 1/2 ins. diam., located from U.S.L.M. No. 1 and checked with ties given on plat of Sur. No. 2213, Ruth lode. Cor. No. 5 is a 2 x 4 in. wooden post set very loosely in a rock pile. Line 5-2 was found to be S. 13° 32' W., 587.3 ft. instead of S. 12° 30' W., 600 ft., as approved. Cor. No. 3 is a rock pile. Line 2-3 was found to be S. 78° 04' E., 1486.6 ft., instead of S. 77° 30' E., 1500 ft., as approved.

Sur. No. 857, Rattan lode: Cor. No. 2 is a 2 x 4 in. wooden post, loosely set in rock pile. Cor. No. 7 is missing; its location was determined from data on plat of Sur. No. 2213, Ruth lode. Line 7-2 was found to be S. 89° 42' W., 1493.4 ft. instead of S. 89° 45' W., 1500 ft., as approved.

FIELD ASSISTANTS

Name Capacity

Donald C. Hondrum Head Chairman
S. O. Hondrum Chairman

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

CERTIFICATE OF SURVEYOR

May 22, 1959

I, Olaf Hondrum

Mineral Surveyor, hereby certify upon honor that in pursuance of an order received from the _____

Office Cadastral Engineer _____, at Phoenix, Arizona

dated April 14, 1959, I have faithfully and correctly executed the survey of
the mining claim of Clara B. Dickie

known as the Omega, Divide, Key Nos. 1 and 2, Keystone Wedge and Moss Millsight lodes
(Lode, placer, or mill site)

situate in San Francisco Mining District, Mohave County, Sections 19 and 30,

T. 20 N., R. 20 W., Gila & Salt River Meridian, Arizona, and
(State)

designated as Survey No. 1484, which is represented in the foregoing field notes as having been
executed by me and under my direction, and that said survey has been made in strict conformity with said order,
the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner
described in the foregoing field notes, and I do further certify that the labor expended and improvements made

upon or for the benefit of the lode location(s) embraced in the said mining claim by
(Lode or placer)

claimant(s) or her grantors are fully stated in my report therein, and that the character,
extent, location, and itemized value thereof are specified therein with particularity and full detail, and that no
portion of, or interest in, said labor and improvements so credited to this claim has been included in the estimate
of expenditures upon any other claim.

Phoenix, Arizona
(Place)

Olaf Hondrum
(Mineral Surveyor)

CERTIFICATE OF APPROVAL

Cadastral Survey Office
Phoenix, Arizona

(Office)

Phoenix, Arizona November 6, 1959
(Place) (Date)

The foregoing field notes of mineral survey No. 1484, in Sections 19 and 30

T. 20 North, R. 20 West, Gila and Salt River Meridian,

Arizona, executed by Olaf Hondrum, Mineral Surveyor,
(State)

under order dated April 14, 1959, having been critically examined and the necessary
corrections made prior to their certification by the surveyor, the field notes and the survey therein described
are hereby approved.

Lester S. Mann
Lester S. Mann

Office Cadastral Engineer
(Title)

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of field notes of the above described mineral survey No. _____
is a true copy of the original field notes.

(Title)

