

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

MINERAL SURVEY NO. 4504

Arizona Land District.

FIELD NOTES

Of The Survey Of The Mining Claim Of

Jules L. Vermeersch, Jack Thomas and Beatrice W. Lewis

Known As The

Apociram, Opoeiram No. 3 and Ophir No. 3 lodes

Cave Creek Mining District,

Maricopa County, Arizona

Sections 8&9, Township 6N., Range 4E.

Surveyed under order dated September 2, 1959

by Harvey W. Smith  
Mineral Surveyor.

Claim located See Reverse Side, 19

Survey commenced September 3, 1959

Survey completed September 8, 1959

Address of claimant 4245 East Van Buren, Phoenix, Arizona

DATES OF AMENDED LOCATIONS

See Reverse Side

Name of Location	Located	DATE Recorded	Amended	Amended Recording
Apociram	12-29-30	1-3-31	8-24-59	8-27-59
Opoeiram No. 3	1-19-31	4-16-31	8-24-59	8-27-59
Ophir No. 3	5-28-37	6-16-37	8-24-59	8-27-59

Chains  
Feet

This survey was made with a C. L. Berger & Sons transit No. 15045, with horizontal limb 6-1/4 ins. diam., having two double opposite verniers, and full vertical circle 5 ins. diam., having one double vernier; the verniers read to one minute of arc. The instrument was in good condition at the time of the survey and all adjustments were in good order.

All azimuths in this record were determined by the method of horizontal-angles-right referred to the meridian established by the following direct observation on the sun: September 3, 1959 at Cor. No. 2 of the Apociram lode, latitude  $33^{\circ}52'47.3''N.$ , longitude  $111^{\circ}57'42.5''W.$ , turning from a reference point southeast clockwise to the sun in the west direction.

True bearing of the reference point  $S. 89^{\circ}29'30''E.$

The lines were measured with a Lufkin steel tape, 300 ft. in length graduated every foot for 299 ft. and the remaining foot graduated to tenths and hundredths. The tape was compared to a standard at the beginning of the survey and found to be correct.

All lines and connections of this survey were run by direct methods.

The magnetic declination observed at each corner of the survey gave a uniform value of  $14^{\circ}30'E.$

Chains Feet	APOCIRAM LODE
	<p>At Cor. No. 1 of the Apociram lode, identical with Cor. No. 1 of the Opoeiram No. 3 lode of this survey.</p> <p>Set a galvanized iron post, 18 ins. long, 3/4 in. diam. in a 15 pound concrete and rock base, 12 ins. in the ground, with a brass cap, 2 ins. diam., firmly fastened within the iron post, mkd., MS4504 A I O 3 1 X; from which</p> <p>The 1/4 Cor. common to Sec. s 8&amp;9, T. 6N., R. 4E., G. &amp; S. R. B. &amp; M., bears S. 61° 13' 30" W., 1,646.58 ft. dist.; a granite rock 3" x 6 ins., 8 ins. above ground, firmly set, marked and witnessed as described in the official record.</p> <p>A mound of stones constructed adjacent to the iron post</p> <p>Thence S. 31° 09' W.</p>
815.0	Right bank, Cave Creek, 20 ft. wide, course S. 80° W.
985.0	Unimproved road, bears west and S. 85° E.
1485.0	Unimproved road, bears west and East.
1496.34	<p>Cor. No. 2 identical with Cor. No. 4, Opoeiram No. 3 lode of this survey.</p> <p>Set a galvanized iron post, 18 ins. long, 3/4 in. diam. in a 15 pound concrete and rock base, 12 ins. in the ground, with a brass cap, 2 ins. diam., firmly fastened within the iron post., mkd., MS4504 A 2 O 3 4 X; from which</p>

## SURVEY 4504

Page 3.

Chains- Feet	
	<p>A mound of stones constructed adjacent to the iron post.</p> <p>Thence N. 89°29'30"W;</p>
7.49	Unimproved road, bears S. 20° W. and N. 20° E.
297.49	Cor. No. 4, Ophir No. 3 Lode of this survey.
347.00	Lode line; discovery pt. bears N. 31°09'E., 1196.34 ft. dist.
694.07	Cor. No. 3
	<p>Set a galvanized iron post, 18 ins. long, 3/4 in. diam. in a 15 pound concrete and rock base, 12 ins. in the ground, with a brass cap, 2 ins. diam., firmly fastened within the iron post., mkd., MS4504 A 3 X; from which</p> <p>A mound of stones constructed adjacent to the iron post.</p> <p>Thence N. 31°16'30"E.</p>
280.0	Left bank Cave Creek, 20 ft. wide, course S. 45°W.
1498.28	Cor. No. 4
	<p>Set a galvanized iron post 18 ins. long, 3/4 in. diam. in a 15 pound concrete and rock base, 12 ins. in the ground, with a brass cap, 2 ins. diam., firmly fastened within the iron post., mkd. MS4504 A 4 X;</p> <p>from which</p> <p>A mound of stones constructed adjacent to the iron post.</p> <p>Thence S. 89°29'30"E.</p>

Chains Feet	
343.35	Lode line; discovery pt. bears S. 31°09'W., 300.0 ft.
690.35	Cor. No. 1, and place of beginning.
	Opoeiram No. 3 Lode
	At Cor. No. 1, Opoeiram No. 3 lode identical with Cor. No. 1, Apociram lode, previously described.
	Thence S. 89°29'30"E.
347.50	Lode line; discovery pt. bears S. 31°09'W., 1486.34 ft. dist.
635.64	A witness pt. for Cor. No. 2, Opoeiram No. 3 lode. Set a galvanized iron post, 18 ins. long, 3/4 in. diam. in a 15 pound concrete and rock base, 12 ins. in the ground with a brass cap, 2 ins. diam. firmly fastened within the iron post, mkd. MS4504 O 3 2 W C X; from which A mound of stones constructed adjacent to the iron post.
695.00	Cor. No. 2 This cor. falls in a local drainage where a permanent corner would be demolished or covered over. Thence S. 31°07'30"W.
700.00	Right bank Cave Creek, 20 ft. wide, course S. 80°W.
1100.00	Unimproved road bears N. 60°W. and S. 60°E.
1455.0	Unimproved road bears East and West

-Chains - Feet	
1495.96	Cor. No. 3
	<p>Set a galvanized iron post, 18 ins. long, 3/4 in. diam. in a 15 pound concrete and rock base, with a brass cap, 2 ins. diam., firmly fastened within the iron post, mkd., MS4504 O 3 3 X; from which</p> <p>A mound of stones constructed adjacent to the iron post.</p>
	Thence N. 89°29'30"W.
65.0	Unimproved road bears N. 50°E. and S. 50°W.
270.0	Unimproved road bears S. 45°E. and N. 45°W.
348.20	Lode line; discovery pt. bears N. 31°09'E., 10.0 ft. dist.
397.36	Cor. No. 1, Ophir No. 3 lode of this survey.
695.70	<p>Cor. No. 4 identical with Cor. No. 2, Apociram lode, previously described.</p> <p>Thence N. 31°09'E.</p>
11.34	Unimproved road bears East and west
511.34	Unimproved road, bears west and S. 85°E.
661.34	Left bank Cave Creek, 20 ft. wide, course S. 80°W.
1496.34	Cor. No. 1 and place of beginning.
<p><b>OPHIR No. 3 LODE</b></p> <p>At Cor. No. 1 of the Ophir No. 3 lode, on line 3-4 of the Opoeiram No. 3 lode of this survey.</p>	

-Chains-  
Feet

Set a galvanized iron post, 18 ins. long, 3/4 in. diam. in a 15 pound concrete and rock base, 12 ins. in the ground with a brass cap, 2 ins. diam. firmly fastened within the iron post, mkd. MS4504 O 3 I X; from which

The 1/4 cor. common to Secs. 8 & 9 T. 6 N. R. 4 E., bears S. 40° 02' 30" E., 461.90 ft. dist., previously described.

1495.06

Cor. No. 2

Set a galvanized iron post, 18 ins. long, 3/4 in. diam., in a 15 pound concrete and rock base, 12 ins. in the ground, with a brass cap, 2 ins. diam. firmly fastened within the iron post, mkd. MS4504 O 3 2 X; from which

A mound of stone constructed adjacent to the iron post.

Thence N. 89° 29' 30" W.

297.46

Lode line; discovery pt. bears N. 0° 30' 30" E., 1245.06 ft. dist.

592.59

Cor. No. 3

Set a galvanized iron post, 18 ins. long, 3/4 in. diam., in a 15 pound concrete and rock base, 12 ins. in the ground, with a brass cap, 2 ins. diam. firmly fastened within the iron post, mkd. MS4504 O 3 3 X; from which



SURVEY 4504

Chains Feet	
	A mound of stones constructed adjacent to the iron post.  Thence N. 0°25'E.
1155.0	Unimproved road bears S. 70°W. and N. 70°E.
1495.06	Cor. No. 4, on line 2-3 of the Apociram lode of this survey.  Set a galvanized iron post, 18 ins. long, 3/4 in. diam. in a 15 pound concrete and rock base, 12 ins. in the ground, with a brass cap, 2 ins. diam., firmly fastened within the iron post, mkd., MS4504 O 3 4 X; from which  A mound of stones constructed adjacent to the iron post.  Thence S. 89°29'30"E.
290.0	Unimproved road, bears N. 20°E. and S. 20°W.
297.49	Cor. No. 2, Apociram lode, Cor. No. 4, Opoeiram No. 3 lode of this survey.  Lode line; discovery pt. bears S. 0°30'30"W. 250.0 ft. dist.
595.83	Cor. No. 1 and place of beginning.

SURVEY 4504

AREAS

Acres

Total area Apociram lode	20.458
Total area Opoeiram No. 3 lode	20.551
Total area Ophir No. 3 lode	20.394

LOCATION

This survey is located in NE1/4 and, SE1/4 Sec. 8 and NW1/4 Sec. 9, T.6N., R.4E., G. & S.R.B.&M.

Chains  
Feet

The survey of the Apociram, Opoeiram No. 3 and Ophir No. 3 lodes is identical with the respective locations as marked on the ground.

SURVEY 4504

EXPENDITURES

The improvements and the value of the labor and improvements made upon or for the benefit of each of the lode locations embraced in said mining claims by the claimant or its grantors are as follows:

No. 1 The discovery point of the Apociram lode is on the lode line 300.0 ft. from a pt.<sup>1</sup> on line 4-1, 343.35 ft. from Cor. No. 4.  
Value, None

No. 2 An open pit, the N. E. Cor. of which bears S. 41° W., 425 ft. dist from Cor. No. 1, Apociram lode; 5 x 5 ft. in size, 4 ft. deep.  
Value, \$50.00

No. 3 An open pit, the N. E. cor. of which bears S. 32° W., 530 ft. dist. from Cor. No. 1, Apociram lode; 8 x 8 ft. in size, 4 ft. deep.  
Value, \$80.00

No. 4 An untimbered shaft, the N. E. cor. of which bears S. 33° W., 510 ft. dist. from Cor. No. 1, Apociram lode; 6 x 8 ft. in size, 15 ft. deep.  
Value, \$300.00

## SURVEY 4504

Page 9.

Chain- Feet	
No. 5	<p>An open cut, the S. W. end of which bears N. 29° E., 350 ft. dist. from Cor. No. 2, Apociram lode; 6 ft. wide, 3 ft. deep and running N. 30° E., 10 ft.</p> <p>Value, \$50.00</p>
No. 6	<p>An underground stope broken through to the surface, the S. E. end of which bears N. 14° E., 280 ft. dist. from Cor. No. 2, Apociram lode; 4 ft. wide and running N. 78° W., 25 ft.</p> <p>Value, \$1,000.00</p>
No. 7	<p>An underground stope broken through to the surface, the S. W. cor. of which bears N. 16° E., 300 ft. dist., from Cor. No. 2., Apociram lode; 10 x 12 ft. in size</p> <p>Value, \$1000.00</p>
No. 8	<p>An open pit, the S. E. cor. of which bears N. 6° E., 50 ft. from Cor. No. 2, Apociram lode; 7 x 7 ft. in size, 6 ft. deep.</p> <p>Value, \$100.00</p>
No. 9	<p>An open cut, the north end of which bears N. 40° W., 260 ft. dist. from Cor. No. 2, Apociram lode; 6 ft. wide, 5 ft. deep and running S. 5° E., 12 ft.</p> <p>Value, \$150.00</p>
No. 10	<p>An untimbered shaft, the S. E. cor. of which bears N. 54° W., 240 ft. dist from Cor. No. 2, Apociram lode; 5 x 6 ft. in size, 20 ft. deep.</p> <p>Value, \$300.00</p>

Chains-  
Feet  
No. 11

An open cut, the south end of which bears N. 60°W. 245 ft. from Cor. No. 2, Apociram lode; 3 ft. wide, 4 ft. deep and running N. 55°W., 15 ft.  
Value, \$75.00

No. 12

An open cut, the north end of which bears N. 53°30'W., 305 ft. dist. from Cor. No. 2, Apociram lode; 4 ft. wide, 3 ft. deep and running S. 35°E., 12 ft.  
Value, \$60.00

No. 13

An underground stope broken through to the surface, the S. E. cor. of which bears N. 47°W., 305 ft. dist. from Cor. No. 2, Apociram lode; 4 x 5 ft. in size surface opening.  
Value, \$1000.00

No. 14

An open cut and adit, the north end of which bears N. 45°W., 350 ft. from Cor. No. 2, Apociram lode; 4 ft. wide, 5 ft. deep and running S. 40°E., 20 ft., thence an adit 4 x 5 ft. in size running S. 40°E., 15 ft.  
Value, \$400.00

An interest in a common improvement described as follows:

An adit, the portal of which bears N. 18°W., 350 ft. from Cor. No. 2 Apociram lode; 4 x 6 ft. in size and running S. 28°E. 380 ft. At 360 ft. a drift bears south running 30 ft.

Minimum value of all workings, \$9,000.00

Value of one-third interest, \$3000.00

## SURVEY 4504

Page 11.

-Chains  
Feet

The surface rises rapidly to the south from the portal of the adit and its extension along its present course, with necessary laterals, crosscuts, raises, drifts, and shafts, affords the most practical and economical means of developing each of the stated lodes at depth.

Five hundred dollars or over has been expended in this improvement in such a manner as tends to the development of each lode of this survey subsequent to its location and to the time since which common ownership and contiguity have prevailed, therefore an undivided one-third interest in its value is hereby credited to each of said lodes., Apociram, Opoeiram No. 3 and Ophir No. 3.

No portion of or interest in this improvement has been credited heretofore as patent expenditure to any lode claim.

No. 1 The discovery pt. of the Opoeiram No. 3 lode is on the lode 10 ft. from a point on line 3-4, 348.20 ft. from Cor. No. 3.

Value, None

No. 2 An open pit, the S.W. cor. of which bears N. 57° E., 260 ft. from Cor. No. 4, Opoeiram No. 3 lode; 3 x 6 ft. in size, 3 ft. deep

Value, \$35.00

No. 3 An open pit, the S.W. cor. of which bears N. 52° E., 250 ft. from Cor. No. 4, Opoeiram No. 3 lode; 3 x 5 ft. in size, 5 ft. deep

Value, \$50.00

Chains- Feet	No.	Description	Value
No. 4	4	An open pit the S. W. cor. of which bears N. 45° E., 240 ft. from Cor. No. 4 Opoeiram No. 3 lode; 6 x 6 ft. in size, 3 ft. deep.	\$40.00
No. 5	5	An open pit, the S. W. cor. of which bears N. 75° E., 29 ft. from Cor. No. 4, Opoeiram No. 3 lode; 8 x 12 ft. in size, 8 ft. deep.	\$150.00
No. 6	6	An open pit, the S. E. cor. of which bears N. 42° W., 90 ft. from Cor. No. 3, Opoeiram No. 3 lode; 8 x 5 ft. in size, 2 ft. deep.	\$25.00
No. 7	7	An adit, the portal of which bears S. 25° W., 570 ft. from Cor. No. 1, Opoeiram No. 3 lode, 3 x 6 ft. in size and running N. 42° W., 45 ft.	\$700.00
No. 8	8	An open pit, the N. W. cor. of which bears S. 26° 30' W. 560 ft. from Cor. No. 1, Opoeiram No. 3 lode; 4 x 5 ft. in size 8 ft. deep.	\$80.00
No. 9	9	An open pit, the N. W. cor. of which bears S. 27° 30' W., 510 ft. from Cor. No. 1, Opoeiram No. 3 lode; 4 x 6 ft. in size, 2 ft. deep.	\$25.00

## SURVEY 4504

Page 13.

Chains Feet No. 1	The discovery pt. of the Ophir No. 3 lode is on the lode line 250 ft. from a pt. on line 4-1, 297.49 ft. from Cor. No. 4.
	Value, None
No. 2	An open cut, the south end of which bears S. 31°W., 590 ft. from Cor. No. 1, Ophir No. 3 lode; 3 ft. wide, 6 ft. deep and running N. 65°W., 25 ft. Portal of adit caved at this point.
	Value, \$150.00
No. 3	An underground stope broken through to the surface, the north end of which bears S. 75°W., 270.0 ft. from Cor. No. 1, Ophir No. 3 lode; 8 x 10 ft. surface opening.
	Value, \$500.00
No. 4	An underground stope broken through to the surface, the north end of which bears S. 79°30'W., 260 ft. from Cor. No. 1, Ophir No. 3 lode; 8 x 10 ft. surface opening.
	Value, \$500.00
No. 5	An underground stope broken through to the surface, the north end of which bears S. 84°30'W. 265 ft. from Cor. No. 1, Ophir No. 3 lode; 4 x 6 ft. surface opening.
	Value, \$300.00
No. 6	An open cut, the north end of which bears S. 84°30'W., 280 ft. from Cor. No. 1, Ophir No. 3 lode; 8 ft. wide, 12 ft. deep and running south 60 ft.
	Value, \$500.00

Chains- Feet	SURVEY 4504	Value		
	<b>OTHER CORNER DESCRIPTIONS AND SUPPLEMENTAL DATA</b>			
	None			
	<b>FIELD ASSISTANTS</b>			
	<table border="0" style="width: 100%;"> <tr> <td style="width: 50%;"><b>Name</b></td> <td style="width: 50%;"><b>Capacity</b></td> </tr> </table>	<b>Name</b>	<b>Capacity</b>	
<b>Name</b>	<b>Capacity</b>			
	<table border="0" style="width: 100%;"> <tr> <td style="width: 50%;">Russell Hart</td> <td style="width: 50%;">Transitman</td> </tr> </table>	Russell Hart	Transitman	
Russell Hart	Transitman			
	<table border="0" style="width: 100%;"> <tr> <td style="width: 50%;">Hugh Stewart</td> <td style="width: 50%;">Chainman</td> </tr> </table>	Hugh Stewart	Chainman	
Hugh Stewart	Chainman			
	Value, \$500.00			
	Value, \$500.00			
	Value, \$500.00			
	Value, \$500.00			
	Value, \$500.00			
	Value, \$500.00			
	Value, \$500.00			
	Value, \$500.00			
	Value, \$500.00			
	Value, \$500.00			
	Value, \$500.00			
	Value, \$500.00			
	Value, \$500.00			
	Value, \$500.00			
	Value, \$500.00			
	Value, \$500.00			
	Value, \$500.00			
	Value, \$500.00			
	Value, \$500.00			
	Value, \$500.00			
	Value, \$500.00			
	Value, \$500.00			
	Value, \$500.00			
	Value, \$500.00			
	Value, \$500.00			
	Value, \$500.00			
	Value, \$500.00			
	Value, \$500.00			
	Value, \$500.00			
	Value, \$500.00			
	Value, \$500.00			
	Value, \$500.00			
	Value, \$500.00			



UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

CERTIFICATE OF SURVEYOR

September 9, 19 59

I, Harvey W. Smith,  
 Mineral Surveyor, hereby certify upon honor that in pursuance of an <sup>amended</sup> order received from the  
Cadastral Engineer, at Phoenix  
 dated September 2, 1959, I have faithfully and correctly executed the survey of  
 the mining claim of J. Vermeersch, J. Thomas and B. W. Lewis,  
 known as the Apociram, Opoeiram No. 3 and Ophir No. 3  
(Lode, placer, or mill site)  
 situate in Sec. 8&9, Maricopa County,  
 T. 6 N., R. 4 E., G & S R B and Meridian, Arizona, and  
(State)  
 designated as Survey No. 4504, which is represented in the foregoing field notes as having been  
 executed by me and under my direction, and that said survey has been made in strict conformity with said order,  
 the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner  
 described in the foregoing field notes, and I do further certify that the labor expended and improvements made  
 upon or for the benefit of the lode location(s) embraced in the said mining claim by  
(Lode or placer)  
 claimant(s) or their grantors are fully stated in my report therein, and that the character,  
 extent, location, and itemized value thereof are specified therein with particularity and full detail, and that no  
 portion of, or interest in, said labor and improvements so credited to this claim has been included in the estimate  
 of expenditures upon any other claim.

Scottsdale, Arizona  
(Place)

Harvey W. Smith  
(Mineral Surveyor)

CERTIFICATE OF APPROVAL

Bureau of Land Management--Survey Office  
(Office)  
Phoenix, Arizona December 2, 1959  
(Place) (Date)

The foregoing field notes of mineral survey No. 4504, in  
Sections 8 and 9, T. 6 North, R. 4 East, Gila & Salt River Meridian,  
Arizona, executed by Harvey W. Smith, Mineral Surveyor,  
amended  
 under/order dated September 2, 1959, having been critically examined and the necessary  
 corrections made prior to their certification by the surveyor, the field notes and the survey therein described  
 are hereby approved.

Lester S. Mann  
 Lester S. Mann  
 Office Cadastral Engineer  
(Title)

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of field notes of the above described mineral survey No. \_\_\_\_\_  
 is a true copy of the original field notes.

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

CERTIFICATE OF SURVEYOR

Arizona 1938

Harvey W. Smith

Mineral Surveyor hereby certifies upon honor that in pursuance of an order received from the

Department of the Interior at Phoenix

dated September 15, 1938 I have faithfully and correctly executed the survey of

the mining claim of J. Vermeersch, J. Thomas and E. W. Lewis

known as the Agostino, Quebrada No. 3 and Quita No. 3

situate in Section 34, T. 12 N., R. 10 E., Merino County,

Arizona and Merino

designated as Survey No. 3301 which is represented in the foregoing field notes as having been executed by me and under my direction and that said survey has been made in strict conformity with said order, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes, and I do further certify that the labor expended and improvements made

upon or for the benefit of the Agostino Quebrada No. 3 Quita No. 3 location(s) embraced in the said mining claim by

claimant(s) or them are fully stated in my report therein and that the character, extent, location, and estimated value thereof are specified therein with particularity and full detail, and that no portion of or interest in said labor and improvements so credited to this claim has been included in the estimate of expenditures upon any other claim.

*Harvey W. Smith*  
Harvey W. Smith  
Mineral Surveyor

Secretary, Arizona

CERTIFICATE OF APPROVAL

Bureau of Land Management - Survey Office

December 2, 1938

The foregoing field notes of mineral survey No. 3301 in

Section 34, T. 12 N., R. 10 E., Merino County, Arizona

executed by Harvey W. Smith, Mineral Surveyor,

under order dated September 15, 1938, having been critically examined and the necessary corrections made prior to their publication by the surveyor, the field notes and the survey therein described are hereby approved.

*Harvey W. Smith*  
Harvey W. Smith  
Mineral Surveyor

CERTIFICATE OF TRANSCRIPT

I certify that the foregoing transcript of field notes of the above described mineral survey No. 3301 is a true copy of the original field notes.



# United States Department of the Interior

IN REPLY REFER TO

9632 (942)

## BUREAU OF LAND MANAGEMENT

ARIZONA STATE OFFICE  
2400 VALLEY BANK CENTER  
PHOENIX, ARIZONA 85073

November 18, 1981

### Memorandum

To: Chief, Branch of Records and Data Management (952)  
From: Chief, Branch of Cadastral Survey  
Subject: Cancellation of Mineral Survey No. 4504

The signing of this memorandum hereby cancels the survey of unpatented Apociram, Operiram No. 3, and Ophir No. 3 lode claims of Mineral Survey No. 4504.

The following notation should be made on the plat of Mineral Survey No. 4504:

"Survey of Apociram, Operiram No. 3, and Ophir No. 3 lode claims cancelled by Chief, Branch of Cadastral Survey, memorandum dated November 18, 1981, File 9632 (942)."

A notation of this cancellation should also be made on the Mineral Mining District Sheets. This memorandum should be made a part of the original field notes. The plat and field notes should remain in the files.

This claim has not been recorded with the BLM in accordance with Section 314 of FLPMA of 1976, and is considered to be invalid as noted in a memorandum from the Chief, Division of Technical Services; reference A-15983 State Selection (943)(MH).

This cancellation clears the records and facilitates future land transactions.

*James F. Kelley*

*12-15-81  
Hed*

