

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

MINERAL SURVEY NO. 4580 A and B

Arizona Land District.

FIELD NOTES

Of The Survey Of The Mining Claim Of

R. L. Oliver

Known As The

G.O.P. No. 1, G.O.P. Number 2, G.O.P. Number 3, G.O.P. Number 4, G.O.P. Mill Site
Old Hat Mining District,

Pinal County, Arizona

Section 21, Township 10 S., Range 16 E.

Surveyed under order dated September 27th, 1961

by Robert Lenon
Mineral Surveyor.

Claim located Feb. 8, Sept. 3, Sept. 3, Sept. 3, 1947 July 20, 1959

Survey commenced Nov. 21, 1961

Survey completed Jan. 27, 1962

Address of claimant Box 111, Oracle, Arizona

DATES OF AMENDED LOCATIONS

Survey No. 4580 A and B

Feet
Chain

This survey was made with a Bausch & Lomb Precise Transit No. 9259, with horizontal limb 5-1/2 ins. diam., having two single opposite verniers, and full vertical circle 4-1/2 ins. diam., having two double opposite verniers, all verniers reading to one minute of arc. The eyepiece is equipped with a colored glass set in the dust shutter, for making direct observations on the sun. The instrument was in good condition at the time of the survey, and all adjustments were in good order.

All azimuths in this record were determined by the method of double horizontal angles referred to the meridian determined by the following observations:

November 25, 1961, at cor. No. 3 of the G.O.P. Number 2 lode, in latitude 32°30'30" N., and longitude 110°43' W., I make a series of four altitude observations (in two sets of two each) upon the sun for azimuth, at approximately equal time-intervals, two each with the telescope in direct and reversed positions, observing opposite limbs of the sun, and reading the horizontal angles clockwise, from cor. No. 4 of the G.O.P. Number 2, 600 feet NE'ly, SE. to the sun.

	(1st set)	(2nd set)
Mean time of observation,		
105th meridian standard time:	10 ^h 13 ^m A.M.	10 ^h 17 ^m A.M.
Declination of sun at mean time of observation:		20°48' S.
Mean observed vertical angles to sun's center:	30°29'	30°42'
Mean horizontal angles from reference point to sun's center:	124°09'30"	124°39'
True bearing to reference point:		N. 25°32' E.

The lines were measured with a Lufkin steel tape, 500 feet in length, graduated every foot, with the end feet graduated to tenths and hundredths; and a Chicago steel tape, 300 feet in length, graduated every foot, with the end feet graduated to tenths; both tapes were compared with a Lufkin standard steel tape at the time of beginning the survey, and found correct.

All lines and connections were run by direct methods.

The magnetic declination observed at each corner of the survey gave a uniform value of 12°30' E.

Survey No. 4580 A

G.O.P. NO. 1 LODE

Beginning at cor. No. 1 of the G.O.P. No. 1 lode.

Set a galvanized iron pipe, 1-1/2 ins. diam., 24 ins. long, 18 ins. in the ground, with a stone mound alongside, with brass cap mkd. GOP 1-1-4580A; from which

The 1/4 sec. cor. common to secs. 21 and 22, T. 10 S., R. 16 E., G. & S. R. B. & M., Arizona, bears N. 80°39'30" E., 1379.60 ft. dist.; an iron post, 1 in. diam., 12 ins. above ground, firmly set, and properly marked.

The CE 1/16 sec. cor. of sec. 21, bears N. 10°49' E., 221.00 ft. dist.; an iron pipe with brass cap, firmly set and properly marked.

A location monument bears N. 25°32' E., 32 ft. dist.

Thence S. 25°32' W.

19

Fence, bears S. 79° E. and N. 79° W.

Feet Chains	
38	Gulch, 3 ft. wide, course S. 50° E.
212	Gulch, 8 ft. wide, course N. 80° E.
300.0	Lode line, discovery point bears N. 71°25' W., 660 ft. dist.
320	Gulch, 6 ft. wide, course N. 70° E.
447	Fence, bears S. 80° W. and N. 80° E.
534	Enter gulch, 3 ft. wide, course N. 5° W. below this point and N. 25° E. above this point.
600.0	Cor. No. 2, identical with cor. No. 1, G.O.P. Number 4 lode of this survey. Set a galvanized iron pipe, 1-1/2 ins. diam., 24 ins. long, 18 ins. in the ground, with stone mound alongside, with brass cap mkd. GOP 1-2-GOP 4-1-4580A; from which A location monument bears S. 84°30' E., 137 ft. dist. Thence N. 71°25' W.
290	Fence, bears S. 80° W. and N. 80° E.
310	Gulch, 5 ft. wide, course N. 70° E.
1100	Gulch, 5 ft. wide, course N. 35° E.
1360.0	Cor. No. 3, identical with cor. No. 4, G.O.P. Number 4 lode, identical with cor. No. 1, G.O.P. Number 3 lode, identical with cor. No. 2, G.O.P. Number 2 lode, all of this survey. Set a galvanized iron pipe, 1-1/2 ins. diam., 24 ins. long, 18 ins. in the ground, with a stone mound alongside, with brass cap mkd. GOP 2-2- GOP 1-3-GOP 4-4-GOP 3-1-4580A. Thence N. 25°32' E.
60	Road, 8 ft. wide, bears S. 70° E. and N. 70° W.
120	Gulch, 5 ft. wide, course S. 77° E.
300.0	Lode line, discovery point bears S. 71°25' E., 700 ft. dist.
600.0	Cor. No. 4, identical with cor. No. 1, G.O.P. Number 2 lode, of this survey. Set a galvanized iron pipe, 1-1/2 ins. diam., 24 ins. long, 18 ins. in the ground, with stone mound alongside, with brass cap mkd. GOP 2-1-GOP 1-4-4580A. Thence S. 71°25' E.
342	Gulch, 3 ft. wide, course S. 45° W.
455	Gulch, 1 ft. wide, course S. 45° W.
875	Gulch, 6 ft. wide, course S. 30° E. above this point and S. 71° E. below this point.
1007	Gulch, 4 ft. wide, bears N. 75° E.

Survey No. 4580 A

1065	Fence, bears S. 4° E. and N. 4° W.
1109	Road, bears N. 5° W. and S. 5° E.
1142	Road, bears N. 82° E. and S. 82° W.
1360.0	Cor. No. 1, and place of beginning.

G.O.P. NUMBER 2 LODE

At cor. No. 1 of the G.O.P. Number 2 lode, identical with cor. No. 4 of the G.O.P. No. 1 lode of this survey, previously described; from which

The 1/4 sec. cor. of secs. 21 and 22, T. 10 S., R. 16 E., G. & S. R. B. & M., bears S. 85°28'52" E., 2658.65 ft. dist.; previously described.

Thence S. 25°32' W.

300.0 Lode line, discovery point bears N. 71°25' W., 830 ft. dist.

480 Gulch, 5 ft. wide, course S. 77° E.

540 Road, 8 ft. wide, bears S. 70° E. and N. 70° W.

600.0 Cor. No. 2, identical with cor. No. 3 of the G.O.P. No. 1 lode, identical with cor. No. 4, G.O.P. Number 4 lode, and identical with cor. No. 1 of the G.O.P. Number 3 lode, all of this survey, previously described.

Thence N. 71°25' W.

685 Gulch, 4 ft. wide, course N. 45° E.

1230.0 Cor. No. 3, identical with cor. No. 4 of the G.O.P. Number 3 lode of this survey, on line 3-4 Sur. No. 4250 Gold Mill Lode.

Set a copper-coated steel rod, 5/8 ins. diam., 24 ins. long, 18 ins. in the ground, with a stone mound alongside, with brass cap mkd. GOP 2-3-GOP 3-4-4580A; from which

The CW 1/16 cor. of sec. 21, T. 10 S., R. 16 E., G. & S. R. B. & M., Arizona, bears S. 55°40' E., 139.97 ft. dist.

Thence N. 25°32' E.

300.0 Lode line, discovery point bears S. 71°25' E., 400 ft. dist.

450 Road, 10 ft. wide, bears N. 50° W. and S. 50° E.

522.70 Cor. No. 3, Sur. No. 4250 Gold Mill Lode, identical with cor. No. 3 Sur. No. 4250 Don Pedro Lode.

Found iron pipe, 2 ins. diam., firmly set and properly marked.

600.0 Cor. No. 4, identical with cor. No. 2 Sur. No. 4580 B G.O.P. Mill Site, of this survey and on line 3-4 Sur. No. 4250 Don Pedro Lode.

Set a galvanized iron pipe, 1-1/2 ins. diam., 24 ins. long, 18 ins. in the ground, with a stone mound alongside, with brass cap mkd. GOP 2-4-GOP MS-2-4580A-4580B.

Feet Chain	
	Thence S. 71°25' E.
180	Gulch, 4 ft. wide, course S. 80° E. above this point and North below this point.
265	Gulch, 3 ft. wide, course N. 10° E.
330.0	Cor. No. 1 Sur. No. 4580 B G.O.P. Mill Site.
455	Gulch, 2 ft. wide, course N. 10° W.
1230.0	Cor. No. 1 and place of beginning.
	G.O.P NUMBER 3 LODE
	Beginning at cor. No. 1 of the G.O.P. Number 3 lode, identical with cor. No. 2 of the G.O.P. Number 2, identical with cor. No. 3 of the G.O.P. No. 1, identical with cor. No. 4 of the G.O.P. Number 4, all of this survey, previously described; from which
	The 1/4 sec. cor. common to secs. 21 and 22, T. 10 S., R. 16 E., G. & S. R. B. & M., Arizona, bears N. 83°29'26" E., 2927.89 ft. dist.
	Thence S. 25°32' W.
170	Gulch, 5 ft. wide, course S. 85° E.
300	Lode line, discovery point bears N. 71°25' W., 1130 ft. dist.
600.0	Cor. No. 2, identical with cor. No. 3, G.O.P. Number 4 lode, of this survey.
	Set a galvanized iron pipe, 1-1/2 ins. diam., 24 ins. long, 18 ins. in the ground, with stone mound alongside, with brass cap mkd. GOP 4-3-GOP 3-2-4580A.
	Thence N. 71°25' W.
342	Gulch junction, 8 ft. wide, course N. 48° E., also 3 ft. wide, course S. 71° E. above this point.
525	Gulch, 3 ft. wide, course N. 69° E.
719	Gulch, 5 ft. wide, course N. 53° E. below this point and S. 71° E. above this point.
821	Gulch, 5 ft. wide, course S. 65° E.
882.51	Intersect line 3-4 Sur. No. 4250 Leyner lode at a point from which cor. No. 4 bears S. 10°08' E., 146.10 ft. dist.
1230.0	Cor. No. 3.
	Set a copper-coated steel rod, 5/8 ins. diam., 24 ins. long, 18 ins. in the ground, with stone mound alongside, with brass cap mkd. GOP 3-3-4580A, from which
	Cor. No. 4 Sur. No. 4250 Leyner lode bears S. 54°21'50" E., 436.92 ft. dist.
	Thence N. 25°32' E.
300	Lode line, discovery point bears S. 71°25' E., 100 ft. dist.
522.70	Cor. No. 3 Sur. No. 4250 Leyner lode, identical with cor. No. 4 Sur. No. 4250 Gold Mill lode.

Survey No. 4580 A

5

Feet Chains	
	Found a lead capped pipe, 2 ins. diam., 12 ins. above the ground, firmly set and properly marked.
600.0	Cor. No. 4, identical with cor. No. 3 of the G.O.P. Number 2 lode, of this survey, previously described.
	Thence S. 71°25' E.
545	Gulch, 4 ft. wide, course N. 45° E.
1230.0	Cor. No. 1 and place of beginning.
G.O.P. NUMBER 4 LODE	
	Beginning at cor. No. 1, G.O.P. Number 4 lode, previously described; from which
	The 1/4 sec. cor. common to secs. 21 and 22, T. 10 S., R. 16 E., G. & S. R. B. & M., Arizona, bears N. 64°42'40" E., 1791.62 ft. dist.
	Thence S. 25°32' W.
138	Gulch, 3 ft. wide, course N. 25° E. below this point and N. 70° E. above this point.
300.0	Lode line, discovery point bears N. 71°25' W., 1260 ft. dist.
318	Gulch, 2 ft. wide, course N. 30° W.
600.0	Cor. No. 2.
	Set a galvanized iron pipe, 1-1/2-ins. diam., 24 ins. long, 18 ins. in the ground, with stone mound alongside, with brass cap mkd. GOP 4-2-4580A; from which
	An X chisled 2 ft. up on a rhyolite outcrop 4 ft. x 8 ft. in size, with B Q chisled on the west edge of outcrop.
	Thence N. 71°25' W.
55	Gulch, 4 ft. wide, course N. 40° E.
307	Gulch, 3 ft. wide, course N. 43° W.
357	Gulch, 3 ft. wide, course N. 15° E.
507	Gulch, 3 ft. wide, course N. 45° E.
622	Gulch, 3 ft. wide, course N. 05° E.
787	Gulch, 4 ft. wide, course N. 75° E.
951	Gulch, 4 ft. wide, course S. 80° E.
1150	Gulch, 5 ft. wide, course S. 85° E.
1310	Fence, bears S. 80° W. and N. 80° E.

7

Survey No. 4580 A

6

Feet Chains	
1360.0	Cor. No. 3, identical with cor. No. 2 of the G.O.P. Number 3 lode of this survey, previously described. Thence N. 25°32' E.
300.0	Lode line, discovery point bears S. 71°25' E., 100 ft. dist.
430	Gulch, 5 ft. wide, course S. 85° E.
600.0	Cor. No. 4, identical with cor. No. 1 G.O.P. Number 3 lode, identical with cor. No. 2 G.O.P. Number 2 lode, identical with cor. No. 3 G.O.P. No. 1 lode, all of this survey, previously described. Thence S. 71°25' E.
260	Gulch, 5 ft. wide, course N. 35° E.
1050	Gulch, 5 ft. wide, course N. 70° E.
1070	Fence, bears S. 80° W. and N. 80° E.
1360.0	Cor. No. 1 and place of beginning.

Survey No. 4580 B

G.O.P. MILL SITE

At Cor. No. 1 of the G.O.P. Mill Site, falling on line 4-1 of the G.O.P. Number 2 lode of this survey.

Set an iron pipe, 1-1/2 ins. diam., 24 ins. long, 18 ins. in the ground, with a mound of stone alongside, with brass cap mkd. GOP MS-1-GOP 2-1-4-4580A-4580B; from which

The 1/4 sec. cor. common to secs. 21 and 22, T. 10 S., R. 16 E., G. & S. R. B. & M., Arizona, bears S. 81°56'14" E., 3538.44 ft.

dist. Thence N. 71°25' W.

Thence N. 71°25' W.

65	Gulch, 3 ft. wide, course N. 10° E.
150	Gulch, 4 ft. wide, course S. 80° E. above this point and North below this point.
330.00	Cor. No. 2, identical with cor. No. 4 of the G.O.P. Number 2 lode of this survey and falling on line 3-4 of the Don Pedro lode of Sur. No. 4250, previously described. Thence N. 25°32' E.
155	Gulch, 3 ft. wide, course S. 53° E.
478	Gulch, 1 ft. wide, course N. 35° W.
522.70	Cor. No. 4 of the Don Pedro lode, identical with cor. No. 3 of the Fresno lode, both of Sur. No. 4250. Found a lead capped pipe, 2 ins. diam., 12 ins. above the ground, firmly set and properly marked.

Survey No. 4580 B

Feet Chain	
568	Gulch, 1 ft. wide, course S. 43° W.
639	Road, 12 ft. wide, bears N. 82° E. and S. 82° W.
660.00	Cor. No. 3, falling on line 3-4 of the Fresnal lode of Sur. No. 4250. Set an iron pipe, 1-1/2 ins. diam., 24 ins. long, 18 ins. in the ground, with a mound of stone alongside, with brass cap mkd. GOP Mill Site-3-4580-Fresnal. Thence S. 71°25' E.
70	Road, 12 ft. wide, bears S. 80° E. and N. 80° W.
330.00	Cor. No. 4. Set an iron pipe, 1-1/2 ins. diam., 24 ins. long, 18 ins. in the ground, with a mound of stone alongside, with brass cap mkd. GOP Mill Site-4-4580. Thence S. 25°32' W.
71	Gulch, 4 ft. wide, course N. 70° E.
112	Gulch, 3 ft. wide, course Due East.
237	Gulch, 2 ft. wide, course N. 60° E.
470	Gulch, 4 ft. wide, course N. 55° E.
564	Gulch, 3 ft. wide, course N. 70° W.
660.00	Cor. No. 1 and place of beginning.

Survey No. 4580 A and B

AREAS

	Acres
Total area, G.O.P. No. 1 lode	18.595
Total area, G.O.P. Number 2 lode	16.818
Total area, G.O.P. Number 3 lode	16.818
Area in conflict with-	
Sur. No. 4250 Leyner lode	2.070
Total area, G.O.P. Number 4 lode	18.595
Total area, G.O.P. Mill Site	4.963

LOCATION

This survey is located in the NW 1/4, NE 1/4, SE 1/4, and SW 1/4 sec. 21, of T. 10 S., R. 16 E., G. & S. R. B. & M., Pinal County, Arizona.

The survey of the G.O.P. Number 2 and G.O.P. Number 3 lodes and the G.O.P. Mill Site is identical with the respective location as marked on the ground. The survey of the G.O.P. No. 1 and the G.O.P. Number 4 lodes is wholly within the location as marked on the ground. Cors. Nos. 1 and 2 of the G.O.P. No. 1 lode differ to the extent previously shown.

Claims

EXPENDITURES

The improvements and the value of the labor and improvements made upon or for the benefit of each of the lode locations embraced in said mining claim by the claimant are as follows:

- | | |
|-------|--|
| No. 1 | The discovery point of the G.O.P. No. 1 lode, being on the lode line 700 ft. from the center of line 3-4.
No value. |
| No. 2 | A shaft, 6 x 9 ft., 30 ft. deep, the center of which bears S. 84° W., 345 ft. from Cor. No. 1, G.O.P. No. 1 lode.
Value, \$600. |
| No. 3 | A cut, 5 ft. wide, the face of which bears S. 50° E., 650 ft. from Cor. No. 4, G.O.P. No. 1 lode; runs N. 70° E., 8 ft. to 7 ft. face.
Value, \$70. |
| No. 4 | A shaft, 8 x 7 ft., 4 ft. deep, the center of which bears N. 55° E., 80 ft. from Cor. No. 3, G.O.P. No. 1 lode.
Value, \$100. |
| No. 1 | The discovery point of the G.O.P. Number 2 lode, being on the lode line 400 ft. from the center of line 3-4.
No value. |
| No. 2 | A cut, 5 ft. wide, the face of which bears N. 40° E., 240 ft. from Cor. No. 3, G.O.P. Number 2 lode; runs S. 66° W., 20 ft. to 5 ft. face.
Value, \$125. |
| No. 3 | A cut, 9 ft. wide, the face of which bears N. 30° E., 270 ft. from Cor. No. 3, G.O.P. Number 2 lode; runs N. 70° W., 15 ft. to 6 ft. face.
Value, \$200. |
| No. 4 | A cut, 7 ft. wide, the face of which bears S. 87° E., 300 ft. from Cor. No. 3, G.O.P. Number 2 lode; runs N. 86° E., 12 ft. to 7 ft. face.
Value, \$150. |
| No. 5 | A shaft, 7 x 10 ft., 2 ft. deep, the center of which bears N. 71° E., 430 ft. from Cor. No. 3, G.O.P. Number 2 lode.
Value, \$70. |
| No. 6 | An adit, 5 x 5 ft. in size, the portal of which bears S. 74° E., 620 ft. from Cor. No. 3, G.O.P. Number 2 lode; runs S. 25° E., 15 ft. to breast.
Value, \$180. |
| No. 7 | A shaft, 6 x 6 ft., 20 ft. deep, the center of which bears S. 87° E., 650 ft. from Cor. No. 3, G.O.P. Number 2 lode.
Value, \$400. |
| No. 8 | A shaft, 7 x 8 ft., 45 ft. deep, the center of which bears N. 39° W., 380 ft. from Cor. No. 2, G.O.P. Number 2 lode.
Value, \$900. |
| No. 1 | The discovery point of the G.O.P. Number 3 lode, being on the lode line 100 ft. from the center of line 3-4.
No value. |

~~CORNER~~

- No. 2 A shaft, 8 x 7 ft., 8 ft. deep, the center of which bears S. 51° E., 605 ft. from Cor. No. 4, G.O.P. Number 3 lode.
Value, \$100.
- No. 1 The discovery point of the G.O.P. Number 4 lode, being on the lode line 100 ft. from the center of line 3-4.
No value.
- No. 2 An adit, 6 x 4 ft. in size, the portal of which bears S. 16° W., 150 ft. from Cor. No. 4, G.O.P. Number 4 lode; runs Due North, 5 ft. to breast.
Value, \$60.
- No. 3 A cut, 5 ft. wide, the face of which bears S. 7° E., 130 ft. from Cor. No. 4, G.O.P. Number 4 lode; runs S. 38° E., 5 ft. to 4 ft. face.
Value, \$25.
- No. 4 A cut, 5 ft. wide, the face of which bears S. 67° E., 210 ft. from Cor. No. 4, G.O.P. Number 4 lode; runs N. 5° E., 10 ft. to 5 ft. face.
Value, \$60.
- No. 5 A shaft, 7 x 7 ft., 5 ft. deep, the center of which bears N. 25° W., 405 ft. from Cor. No. 2, G.O.P. Number 4 lode.
Value, \$120.
- No. 6 A shaft, 5 x 5 ft., 8 ft. deep, the center of which bears N. 16° W., 355 ft. from Cor. No. 2, G.O.P. Number 4 lode.
Value, \$100.
- No. 7 A trench, 14 ft. wide, 4 ft. deep, the West end of which bears N. 16° W., 355 ft. from Cor. No. 2, G.O.P. Number 4 lode; runs S. 32° E., 30 ft.
Value, \$200.

An interest in a common improvement described as follows:

A shaft 7 x 8 ft. in size, 135 ft. deep, with 40 ft. of drift, the portal of which bears N. 39° W., 445 ft. from Cor. No. 2, G.O.P. Number 2 lode.
Value of shaft, \$3600.
Value of 1/4 interest, \$900.

This improvement is for the development of the four lodes of this survey, which are all contiguous lode claims owned in common within the range of benefit of said shaft.

No portion of or interest in this improvement has been credited heretofore as patent expenditure to any lode claim.

OTHER CORNER DESCRIPTIONS AND SUPPLEMENTAL DATA

The CW 1/16 cor. of Sec. 21 is an iron pipe, 1-1/2 ins. diam., 24 ins. above the ground, with brass cap mkd. CW 1/16.

FIELD ASSISTANTS

- James Yanez-----Instrumentman
- Frank Vasquez-----Chainman
- Joe Alvarez-----Chainman
- Albert Maldonado-----Rodman
- Jack Schmeiser-----Rodman

10

Chains

NUMBER

No. 2	A chain 8 ft. long, the center of which bears N. 15° E. 100 ft. from the center of the lot; value, \$100.
No. 1	The discovery point of the G.O.P. Number 1 lot, being on the line 100 ft. from the center of line 3-4.
No. 3	A chain 8 ft. long, the face of which bears S. 70° W. 100 ft. from the center of the lot; value, \$100.
No. 4	A chain 8 ft. long, the face of which bears S. 70° W. 100 ft. from the center of the lot; value, \$100.
No. 5	A chain 8 ft. long, the center of which bears N. 25° W. 100 ft. from the center of the lot; value, \$100.
No. 6	A chain 8 ft. long, the center of which bears N. 15° W. 100 ft. from the center of the lot; value, \$100.
No. 7	A chain 8 ft. long, the west end of which bears N. 15° W. 100 ft. from the center of the lot; value, \$100.

An interest in a common improvement assumed as follows:

A chain 8 ft. long, the face of which bears N. 25° W. 100 ft. from the center of the lot; value, \$100.

Value of chain, \$100.

Value of lot interest, \$200.

This improvement is for the development of the four lots of this survey, which are all contiguous lots lying along the common right-of-way of a public street.

No portion of an interest in this improvement has been granted heretofore or is about to be granted to any party.

DATE OF THE IMPROVEMENT AND THE INTEREST THEREIN

The 1/16 cor. of sec. 31 is an iron pipe, 1-1/2 in. diam., 3 in. above the ground, with brass cap and 1/2 in. dia.

FIELD ASSISTANTS

James A. ...
 William A. ...
 Joe A. ...
 Albert A. ...
 John A. ...


UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

CERTIFICATE OF SURVEYOR

February 22, 1962

I, Robert Lenon,
 Mineral Surveyor, hereby certify upon honor that in pursuance of an order received from the _____
 Office Cadastral Engineer _____, at Phoenix, Arizona
 dated September 27, 1961, I have faithfully and correctly executed the survey of
 the mining claim of R. L. Oliver, Box 111, Oracle, Arizona,
 known as the G.O.P. No. 1, G.O.P. Number 2, G.O.P. Number 3, G.O.P. Number 4, G.O.P. Mill Site
(Lode, placer, or mill site)
 situate in Sec. 21,
 T. 10 S., R. 16 E., G. & S. R. Meridian, Arizona, and
(State)
 designated as Survey No. 4580 A & B, which is represented in the foregoing field notes as having been
 executed by me and under my direction, and that said survey has been made in strict conformity with said order,
 the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner
 described in the foregoing field notes, and I do further certify that the labor expended and improvements made
 upon or for the benefit of the lode & millsite location(s) embraced in the said mining claim by
(Lode or placer)
 claimant(s) or his grantors are fully stated in my report therein, and that the character,
 extent, location, and itemized value thereof are specified therein with particularity and full detail, and that no
 portion of, or interest in, said labor and improvements so credited to this claim has been included in the estimate
 of expenditures upon any other claim.


Patagonia, Arizona
(Place)


(Mineral Surveyor)

CERTIFICATE OF APPROVAL

Bureau of Land Management, Survey Office
(Office)
Phoenix, Arizona April 5, 1962
(Place) (Date)

The foregoing field notes of mineral survey No. 4580-A&B, in Old Hat Mining District
Sec. 21, T. 10 S., R. 16 E., G. & S. R. Meridian,
Arizona, executed by Robert Lenon, Mineral Surveyor,
(State)
 under order dated September 27, 1961, having been critically examined and the necessary
 corrections made prior to their certification by the surveyor, the field notes and the survey therein described
 are hereby approved.


Fred J. Weiler
State Director
(Title)

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of field notes of the above described mineral survey No. _____
is a true copy of the original field notes.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

CERTIFICATE OF SURVEYOR

Robert L. ...

Mineral Survey No. ...

Section 21

Surveyed and returned to the office of

the Surveyor of the

County of ... State of ...

Section 21

and

When it was found that the survey was correct and that the boundaries were as shown on the plat, the same was approved and the plat was returned to the Surveyor of the County of ... State of ...

upon the plat of the

and that the same is correct and true to the original survey and that the boundaries are as shown on the plat, the same was approved and the plat was returned to the Surveyor of the County of ... State of ...

CERTIFICATE OF APPROVAL

Surveyed and returned to the office of

Section 21

The foregoing field notes of mineral survey No. ... in ... District

Meridian

Mineral Survey No. ...

under order of the Surveyor of the County of ... State of ... and the survey therein described is a true copy of the original field notes.

CERTIFICATE OF TRANSCRIPT

I certify that the foregoing transcript of field notes of the above described mineral survey No. ... is a true copy of the original field notes.