

Form 4-683  
(January 1963)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

Mineral Survey number	4648
State	Arizona
Land District	Arizona

FIELD NOTES

Of the Survey of the Mining Claim of (name and address of Claimant) C. Darrel Wilson, Alice Ann Kilroy, Steven C. Chilson, Daniel G. Chilson, Jr., Russell A. & Ella C. Todd, Richard E. Chilson, Marian C. Chilson, Donna Gail Chilson, and Laurita Yarter, c/o Evans, Kitchel & Jenckes, Attorneys at Law, 363 North 1st Avenue, Phoenix, Arizona 85003

Known as the (name of group, if any)

CONSISTING OF LOCATIONS NAMED AND LOCATED AS FOLLOWS

NAME OF LOCATION	DATE	
	LOCATED	AMENDED
NEVADA NO. 1	11/10/55	11/10/55 10/28/64 3/4/66
NEVADA NO. 2	11/10/55	3/4/66
NEVADA NO. 3	11/10/55	11/10/55 3/4/66
NEVADA NO. 4	11/10/55	11/10/55 10/28/64 3/4/66
NEVADA NO. 5	11/10/55	11/10/55 10/30/64 3/4/66
NEVADA NO. 6	11/10/55	11/10/55 10/30/64 3/4/66
NEVADA NO. 7	11/10/55	11/10/55 10/30/64 3/4/66
NEVADA NO. 8	11/10/55	11/10/55 10/30/64 11/20/64 3/4/66
UTAH NO. 42	11/9/55	10/30/64 3/4/66
UTAH NO. 43	11/9/55	3/4/66
UTAH NO. 44	11/9/55	3/4/66
UTAH NO. 49	1/2/56	3/4/66
COLORADO NO. 13	11/4/55	3/4/66 9/30/66
COLORADO NO. 14	11/4/55	11/4/55 3/4/66 9/30/66
CWT NO. 2	3/11/65	3/4/66

Mining district			County	
PIMA			PIMA	
Section	Township	Range	Meridian	Survey under order dated
22, 23	17 South	12 East	Gila & Salt River	Jan 24, 1967
Survey commenced		Survey completed		Name of Mineral Surveyor
Feb. 20, 1967		Feb. 28, 1967		Robert L. Frazer

11  
No. 100  
Date: 10/10/1907

STATE OF TEXAS  
COUNTY OF TARRANT  
CITY OF FORT WORTH

Know all men by these presents that the undersigned, the Board of Directors of the Fort Worth Traction Company, do hereby certify that the following is a true and correct copy of the articles of incorporation of said company as filed in the office of the Secretary of State of the State of Texas on the 10th day of October, 1907.

ARTICLES OF INCORPORATION OF THE FORT WORTH TRACTION COMPANY

Section	Text
1	That the name of the corporation shall be the Fort Worth Traction Company.
2	That the purpose for which the corporation is organized shall be to acquire, own, operate, maintain and repair electric trolley lines and other means of public utility in the city of Fort Worth, Texas.
3	That the capital stock of the corporation shall be divided into shares of the par value of five dollars each.
4	That the total amount of the capital stock of the corporation shall be \$1,000,000.
5	That the number of shares of capital stock which the corporation has authority to issue shall be 200,000 shares.
6	That the corporation shall have the power to acquire, own, operate, maintain and repair electric trolley lines and other means of public utility in the city of Fort Worth, Texas, and to do all things necessary or proper to carry out the purposes of the corporation.
7	That the corporation shall have the power to borrow money and to issue bonds, notes, debentures or other securities in accordance with the provisions of these articles.
8	That the corporation shall have the power to lease, purchase, sell, convey, mortgage and otherwise dispose of all or any part of its property.
9	That the corporation shall have the power to make and alter its bylaws.
10	That the corporation shall have the power to do all things which natural persons are capable of doing.
11	That the corporation shall have perpetual existence.
12	That the officers of the corporation shall be the president, vice president, secretary and treasurer, who shall hold office until their successors are chosen.
13	That the corporation shall have the power to sue and be sued, to contract and to be bound by contracts.
14	That the corporation shall have the power to acquire, own, operate, maintain and repair electric trolley lines and other means of public utility in the city of Fort Worth, Texas, and to do all things necessary or proper to carry out the purposes of the corporation.
15	That the corporation shall have the power to borrow money and to issue bonds, notes, debentures or other securities in accordance with the provisions of these articles.
16	That the corporation shall have the power to lease, purchase, sell, convey, mortgage and otherwise dispose of all or any part of its property.
17	That the corporation shall have the power to make and alter its bylaws.
18	That the corporation shall have the power to do all things which natural persons are capable of doing.
19	That the corporation shall have perpetual existence.
20	That the officers of the corporation shall be the president, vice president, secretary and treasurer, who shall hold office until their successors are chosen.
21	That the corporation shall have the power to sue and be sued, to contract and to be bound by contracts.
22	That the corporation shall have the power to acquire, own, operate, maintain and repair electric trolley lines and other means of public utility in the city of Fort Worth, Texas, and to do all things necessary or proper to carry out the purposes of the corporation.
23	That the corporation shall have the power to borrow money and to issue bonds, notes, debentures or other securities in accordance with the provisions of these articles.
24	That the corporation shall have the power to lease, purchase, sell, convey, mortgage and otherwise dispose of all or any part of its property.
25	That the corporation shall have the power to make and alter its bylaws.
26	That the corporation shall have the power to do all things which natural persons are capable of doing.
27	That the corporation shall have perpetual existence.
28	That the officers of the corporation shall be the president, vice president, secretary and treasurer, who shall hold office until their successors are chosen.
29	That the corporation shall have the power to sue and be sued, to contract and to be bound by contracts.
30	That the corporation shall have the power to acquire, own, operate, maintain and repair electric trolley lines and other means of public utility in the city of Fort Worth, Texas, and to do all things necessary or proper to carry out the purposes of the corporation.

WITNESSED my hand and the seal of the Secretary of State of the State of Texas, this 10th day of October, 1907.

Secretary of State

11

FEET

This survey was made concurrently with Surveys Nos. 4656, 4657, and 4658.

A control traverse, including all four corners of Section 23, T. 17 S., R. 12 E., G&SR.B&M, was made by use of Electronic Distance-measuring Equipment. Angular error was  $0^{\circ} 00' 01''$ ; latitude error  $-0.230'$ . Departure  $-0.007'$ ; Ratio of closure  $1':107,152'$ .

The attached sketch shows the entire traverse in its relationship to Section 23, and to surveys 4648, 4656, 4657, and 4658. Traverse points controlling survey No. 4648 are shown on the survey map.

This survey was made with the following equipment:

Wilde T-2 Theodolites, Nos. 55949 and 92997.

Cubic Electrotape Units 205 and 206.

Lufkin 200 Ft. Steel Tape.

All equipment was in good condition and adjustment.

Angular values are the mean of angles in direct and inverse attitude from distant foresight.

Electrotape measurements are reciprocal, and values are the mean of measurement by both units. Taped traverses were checked at the ends by measured angle to a visible control point.

Position of final corners of this survey was checked in field by comparison of a field angle turned at the corner between two control points, with the difference in calculated bearing from these control points to the corner.

Due to the concurrency and contiguity of the above-noted surveys, and precision of the control traverse, determination of meridian was made only at the corner common to Sections 23, 24, 25, 26, T. 17 S., R. 12 E., G&SR.B&M., as follows:

On February 17, 1967, and February 20, 1967, at Lat.  $31^{\circ} - 55.5' N.$ , Long.  $111^{\circ} - 04.8' W.$ , (from U.S.G.S. Quadrangle Map "Twin Buttes"), at the corner common to Sections 23, 24, 25, 26, T. 17 S., R. 12 E., G&SR.B&M., I observed Polaris at the hours noted below. Angles were turned clock-wise from traverse pt. No. 4, a  $5/8$  in. reinforcing rod which bears North-westerly a distance of 1068.64 ft. from the above-recited section corner. Computation of local hour angle and bearing of Polaris by "Procedure B" in Keuffel & Esser Ephemeris for 1967.



FEET

DATE:

Feb. 17, 1967

TIME: (AVE)

8<sup>h</sup>: 41<sup>m</sup>: 48<sup>s</sup> P.M., MST

Horiz. Angle (Ave)-Pt. No. 4 to Star

33°-23'-37"

Calc. Bearing of

Polaris + 0°-54'-46"

BEARING - Sec. Cor.

to Pt. No. 4

N34°-18'-23"W.

DATE:

Feb. 20, 1967

TIME: (AVE)

8<sup>h</sup>: 58<sup>m</sup>: 51<sup>s</sup> P.M., MST.

Horiz. Angle (Ave)-Pt. No. 4 to Star

33°-20'-26"

Calc. Bearing of

Polaris + 0°-58'-06"

BEARING - Sec. Cor. to Pt. No. 4 N34°-18'-32"W.

AVERAGE BEARING, SEC. COR. TO TRAV. PT. NO. 4

N34°-18'-28"W.

The above average bearing was used as basis of bearing for this survey, as well as Surveys Nos. 4656, 4657, 4658.

An aerial photograph, with control points paneled in field to show thereon, was enlarged to scale of 1" = 200'. Road and drainage intersections were scaled from photograph. Approximate bearings protracted.

MEAN MAGNETIC DECLINATION IS 14° 30' E.

FEET	NEVADA NO. 1 LODE
	At Cor. No. 1 of the Nevada NO. 1 lode, identical with Cor. No. 2 NEVADA NO. 2 lode, Cor. No. 4 UTAH NO. 49 lode, Cor. No. 1 UTAH NO. 44 lode of this survey.
	Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 ins. in the ground, mkd. NV 1-1- NV 2-2- UT 49-4- UT 44-1-4658, from which
	The 1/4 sec. cor. of secs. 22 and 23, T.17 S., R.12 E., G&SR.B&M., bears S. 79° 01' 47" W., 776.39 ft. dist., a 2 in. diam. iron post projecting 10 in. above the ground, firmly set, with lead cap properly marked. Accepted as best evidence of wood post set in 1872 by T.F.White. Surveyor unknown. Thence N. 46° 26' 29" E.
299.94	Lode line, discovery point bears S. 45° 33' 31" E., 1400 ft. dist.
480	Road bears S. 35° E., N. 35° W.
599.88	Cor. No. 2, identical with Cor. No. 4 UTAH NO. 44 lode, Cor. No. 3 UTAH NO. 43 lode, Cor. No. 1 NEVADA NO. 4 lode of this survey.
	Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 ins. in the ground, mkd. NV 1-2- NV 4-1- UT 43-3- UT 44-4-4648.
	Thence S 45° 33' 31" E.
545	Fence bears N. 85° E., S. 85° W.
1130	Wash, 50 ft. wide drains N. 45° E.
1340	Road bears N. 30° E., S. 30° W.
1500.00	Cor. No. 3, identical with Cor. No. 4 of the NEVADA NO. 4 lode of this survey.
	Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 ins. in the ground, mkd. NV 1-3- NV 4-4-4648.
	Thence S. 44° 26' 29" W.
299.94	Lode line, discovery point bears N. 45° 33' 31" W., 100 ft. dist.
340	Road bears N. 45° W., S. 45° E.
599.88	Cor. No. 4, identical with Cor. No. 3 of the NEVADA NO. 2 lode of this survey.
	Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 ins. in the ground, mkd. NV 1-4- NV 2-3-4648.
	Thence N. 45° 33' 31" W.
410	Wash, 50 ft. wide drains N. 50° E.
445	Fence bears N. 14° 15' W., S. 14° 15' E.

FEET	
920	Road bears N. 85° E., S. 85° W.
1500.00	Cor. No. 1., and place of beginning.
<p style="text-align: center;">NEVADA NO. 2 LODE of the NEVADA NO. 2 lode At Cor. No. 1, identical with Cors. No. 1 of the UTAH NO. 49, and the NEVADA NO. 3 lodes of this survey</p> <p>Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 ins. in the ground, mkd. NV 2-1- NV 3-1- UT 49-1-4648; from which</p> <p>The 1/4 sec. cor. of secs. 22 and 23 bears N. 50° 40' 41" W., 442.51 ft. dist., previously described.</p> <p style="text-align: center;">Thence N. 44° 26' 29" E.</p>	
159.91	Intersect line 2-3 of the COLORADO NO. 13 lode, of this survey.
299.84	Lode line, discovery point bears S. 45° 33' 31" E., 30 ft. dist.
599.68	Cor. No. 2, identical with Cor. No. 1 of the NEVADA NO. 1 lode of this survey.
<p style="text-align: center;">Thence S. 45° 33' 31" E.</p>	
580	Road bears N. 85° E., S. 85° W.
1055	Fence bears N. 14° 15' W., S. 14° 15' E.
1090	Wash 50 ft. wide drains N. 50° E.
1500.00	Cor. No. 3, identical with Cor. No. 4 of the NEVADA NO. 1 lode of this survey.
<p style="text-align: center;">Thence S. 44° 26' 29" W.</p>	
270	Fence bears N. 14° 15' W., S. 14° 15' E.
299.84	Lode line, discovery point bears N. 45° 33' 31" W., 1470 ft. dist.
316.57	Intersect line 3-4 Sur. 4656 ELLA #3 lode, at a point from which Cor. 3 bears S. 89° 47' 36" W., 487.55 ft. dist.
599.68	Cor. No. 4, identical with Cor. No. 2 of the NEVADA NO. 3 and Cor. No. 2 of the NEVADA NO. 8 lodes of this survey.



FEET	
	Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 ins. in the ground, mkd. NV 2-4- NV 3-2- NV 8-2-4648; from which
	Cor. No. 3, Sur. 4656, ELLA #3 lode bears N, 55° 17' 44" W., 351.93 ft. dist.
	Thence N. 45° 33' 31" W.
286.61	Intersect line 3-4 Sur. 4656 ELLA #3 lode, at a point from which Cor. No. 3 bears S. 89° 47' 36" W., 84.70 ft. dist.
798.69	Intersect line 3-4 COLORADO NO. 13 lode of this survey.
800	Wash 50 ft. wide drains N. 65° E.
1390	Road bears N. 70° E., S. 70° W.
1500.00	Cor. No. 1, and place of beginning.
<hr/>	
	NEVADA NO. 3 LODE
	Beginning at cor. No. 1 of the NEVADA NO. 3 lode, identical with cor. No. 1 of the NEVADA NO. 2 lode of this survey.
	Thence S. 45° 33' 31" E.
110	Road bears N. 70° E., S. 70° W.
700	Wash 50 ft. wide drains N. 65° E.
701.31	Intersect line 3-4 COLORADO NO. 13 lode of this survey.
1213.39	Intersect line 3-4 Sur. 4656 ELLA #3 lode at a point from which Cor. No. 3 bears S. 89° 47' 36" W., 84.70 ft. dist.
1500.00	Cor. No. 2, identical with cor. No. 4, NEVADA NO. 2 lode of this survey, from which;
	Cor. 3 Sur. 4656 ELLA #3 lode, identical with Cor. 4 Sur. 4657 ELLA #5 lode bears N. 55° 17' 44" W., 351.93 ft. dist.
	Thence S. 44° 26' 29" W.
300.00	Lode Line, discovery point bears N. 45° 33' 31" W., 750 ft. dist.
462.54	Intersect common line 2-3 Sur. 4656 ELLA #3 lode, and 4-1 Sur. 4657 ELLA #5 lode, at a point from which Cor. No. 3 ELLA #3 lode, identical with Cor. No. 4 ELLA #5 lode bears N. 3° 43' 28" E., 531.73 ft. dist.
515	Power line bears N. 82° E., S. 82° W.
600.00	Cor. No. 3.

FEET	
	Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 ins. in the ground, mkd. NV 3-3-4648; from which
	Cor. No. 3 Sur. 4657 ELLA #5 lode bears N. 36° 49' 38" W., 782.80 ft. dist.
	Thence N. 45° 33' 31" W.
65	Power line bears N. 82° E., S. 82° W.
671.45	Intersect line 2-3 Sur. 4657, ELLA #5 lode at a point from which Cor. No. 3 bears N. 3° 43' 28" E., 156.78 ft. dist.
891.36	Intersect line 2-3 COLORADO NO. 14 lode of this survey.
894.02	Intersect Sur. 4657 line 3-4 ELLA #7 lode at a point from which Cor. No. 4 bears N. 89° 47' 36" E., 169.09 ft. dist.
1190	Wash 50 ft. wide bears East.
1310	Power line bears N. 2° 53' W., S. 2° 53' E.
1373.01	Intersect line between secs. 22 and 23 at a point from which the 1/4 cor. of secs. 22 and 23 bears N. 0° 55' 31" W., 797.81 ft. dist.
1410	Power line bears N. 1° W., S. 1° E.
1470	Underground telephone cable bears N. 1° W., S. 1° E.
1500	Cor. No. 4 Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 ins. in the ground, mkd. NV 3-4-4648. Thence N. 44° 26' 29" E.
35	Underground telephone cable bears N. 1° W., S. 1° E.
90	Power line bears N. 1° W., S. 1° E.
125.37	Intersect line between secs. 22 and 23 at a point from which the 1/4 cor. of secs. 22 and 23 bears N. 0° 55' 31" W., 619.32 ft. dist.
152.80	Intersect common line 1-2 COLORADO NO. 14 lode and 4-1 COLORADO NO. 13 lode of this survey.
185	Power line bears N. 2° 53' W., S. 2° 53' E.



FEET	
300.00	Lode line, discovery point bears S. 45° 33' 31" E., 750 ft. dist.
460.0	Road bears N. 80° E., S. 80° W.
600.00	Cor. No. 1, and place of beginning
<p style="text-align: center;">NEVADA NO. 4 LODE                      of the NEVADA NO. 4 lode                      Beginning at cor. No. 1, identical with                      cor. No. 2 of the NEVADA NO. 1 lode of                      this survey; from which</p> <p style="text-align: center;">The 1/4 sec. cor. of secs. 22 and 23                      bears S. 64° 01' 21" W., 1315.10 ft.                      dist., previously described.</p> <p style="text-align: center;">Thence N. 44° 26' 29" E.</p>	
259.00	Cor. No. 3 of the CWT NO. 2 lode of this survey, hereinafter described.
299.75	Lode line, discovery point bears S. 45° 33' 31" E., 1400 ft. dist.
499.35	Cor. No. 2 of the UTAH NO. 43 lode of this survey, hereinafter described.
500	Wash 50 ft. wide drains N. 70° E.
599.50	Cor. No. 2, identical with Cor. No. 1 of the NEVADA NO. 5 lode and Cor. No. 4 of the UTAH NO. 42 lode of this survey.
	Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 ins. in the ground, mkd. NV 4-2- NV 5-1- UT 42-4-4648
	Thence S. 45° 33' 31" E.
50	Wash 50 ft. wide drains N. 70° E.
1040	Wash 50 ft. wide drains N. 20° E.
1061.55	Intersect line 2-3 Sur. 4658 ARIZONA NO. 43 lode at a point from which Cor. No. 3 bears N. 5° 57' 14" W., 249.29 ft. dist.
1065	Fence bears N. 85° E., S. 85° W.
1410	Road bears N. 65° E., S. 65° W.
1500.00	Cor. No. 3 identical with Cor. No. 4 of the NEVADA NO. 5 lode of this survey.
	Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 ins. in the ground, mkd. NV 4-3- NV 5-4-4648.
	Thence S. 44° 26' 29" W.
299.75	Lode line, discovery point bears N. 45° 33' 31" W., 100 ft. dist.

FEET	
301.14	Cor. No. 3 of the NEVADA NO. 8 lode of this survey, hereinafter described.
362.78	Intersect. line 2-3 Sur. 4658 ARIZONA NO. 43 lode at a point from which Cor. No. 3 bears N. 5° 57' 14" W., 818.36 ft. dist.
599.50	Cor. No. 4, identical with Cor. No. 3 of the NEVADA NO. 1 lode, and on line 2-3 of the NEVADA NO. 8 lode of this survey.
	Thence N. 45° 33' 31" W.
160	Road bears N. 30° E., S. 30° W.
380	Wash. 50 ft. wide drains N. 45° E.
955	Fence bears N. 85° E., S. 85° W.
1500.00	Cor. No. 1, and place of beginning.
NEVADA NO. 5 LODE	
	Beginning at Cor. No. 1, identical with Cor. No. 2 of the NEVADA NO. 4 lode of this survey; from which
	The 1/4 sec. cor. of secs. 22 and 23 bears S. 57° 55' 20" W., 1890.63 ft. dist., previously described.
	Thence N. 44° 26' 29" E.
259.50	Cor. No. 2 of the CWT NO. 2 lode of this survey, hereinafter described.
300.00	Lode line, discovery point bears S. 45° 33' 31" E., 100 ft. dist.
600.00	Cor. No. 2, identical with Cor. No. 1 of the NEVADA NO. 6 lode, and Cor. No. 3 of the UTAH NO. 42 lode, both of this survey.
	Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 ins. in the ground, mkd. NV 5-2- NV 6-1- UT 42-3-4648.
	Thence S. 45° 33' 31" E.
570	Wash, 50 ft. wide drains East.
970	Wash, 50 ft. wide drains North.
1272.17	Intersect line 4-5 Sur. 4658 ARIZONA NO. 42 lode at a point from which Cor. No. 4 bears S. 5° 58' 37" E., 35.10 ft. dist.

FEET	
1322.16	Intersect line 3-4 Sur. 4658 ARIZONA NO. 41 lode at a point from which Cor. No. 3 bears N. 89° 48' 50" W., 32.04 ft. dist.
1500.00	Cor. No. 3, identical with Cor. No. 4 of the NEVADA NO. 6 lode of this survey. Set a 5/8 in. diam. steel bar, 24 in. long, with alumium cap affixed thereon, 16 ins. in the ground, mkd. NV 5-3- NV 6-4-4648; from which Cor. No. 3 Sur. 4658 ARIZONA NO. 41 lode bears N. 51° 54' 55" W., 202.01 ft. dist. Thence S. 44° 26' 29" W.
80	Fence bears N. 85° E., S. 85° W.
188.49	Intersect line 2-3 Sur. 4658 ARIZONA NO. 41 lode at a point from which Cor. No. 3 bears N. 5° 57' 14" W., 260.58 ft. dist.
300.00	Lode line, discovery point bears N. 45° 33' 31" W., 1400 ft. dist.
370	Road bears N. 70° E., S. 70° W.
600	Cor. No. 4, identical with Cor. No. 3 of the NEVADA NO. 4 lode of this survey; from which Cor. No. 3 Sur. 4658 ARIZONA NO. 43 lode bears N. 31° 24' 43" W., 650.23 ft. dist. Thence N. 45° 33' 31" W.
90.00	Road bears N. 65° E., S. 65° W.
435	Fence bears N. 85° E., S. 85° W.
438.45	Intersect line 2-3 Sur. 4658 ARIZONA NO. 43 lode at a point from which Cor. No. 3 bears N. 5° 57' 14" W., 249.29 ft. dist.
460	Wash 50 ft. wide drains N. 20° E.
1450	Wash 50 ft. wide drains N. 70° E.
1500.00	Cor. No. 1, and place of beginning.
<hr/> NEVADA NO. 6 LODE of the NEVADA NO. 6 lode, Beginning at Cor. No. 1/identical with Cor. No. 2 of the NEVADA NO. 5 lode of this survey; from which.	
The cor. of secs. 14, 15, 22, 23, T.17S., R.12E., bears N. 59° 53' 47" W., 2386.66 ft. dist. A 2 in. diam. iron post projecting 10 in. above ground, firmly set with lead cap with proper secs., Twp., and R. A recognized and accepted reconstruction of the monument set in 1872 by T.F. White, set by a surveyor whose name is not known.	



FEET	
	Thence N. $44^{\circ} 26' 29''$ E.
299.89	Lode line, discovery point bears S. $45^{\circ} 33' 31''$ E., 100 ft. dist.
599.77	Cor. No. 2, identical with Cor. No. 3 of the NEVADA NO. 7 lode of this survey. Set a $5/8$ in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 ins. in the ground, mkd. NV 6-2- NV 7-3-4648
	Thence S. $45^{\circ} 33' 31''$ E.
546.71	Intersect line 4-5 Sur. 4658 ARIZONA NO. 42 lode at a point from which Cor. No. 4 bears S. $5^{\circ} 58' 37''$ E., 976.39 ft. dist.
1090	Wash 50 ft. wide drains N. $60^{\circ}$ E.
1482.99	Intersect line 1-2 Sur. 4658 ARIZONA NO. 42 lode at a point from which Cor. No. 2 bears S. $5^{\circ} 58' 37''$ E., 269.10 ft. dist.
1500.00	Cor. No. 3, identical with Cor. No. 2 of the NEVADA NO. 7 lode of this survey. Set a $5/8$ in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 ins. in the ground, mkd. NV 6-3- NV 7-2-4648.
	Thence S. $44^{\circ} 26' 29''$ W.
14.06	Intersect line 1-2 Sur. 4658 ARIZONA NO. 42 lode at a point from which Cor. No. 2 bears S. $5^{\circ} 58' 40''$ E., 247.03 ft. dist.
299.88	Lode line, discovery point bears N. $45^{\circ} 33' 31''$ W., 1400 ft. dist.
426.34	Intersect line 3-4 Sur. 4658 ARIZONA NO. 42 lode at a point from which Cor. No. 3 bears S. $89^{\circ} 50' 23''$ E., 319.57 ft. dist.
599.77	Cor. No. 4, identical with Cor. No. 3 of the NEVADA NO. 5 lode of this survey.
	Thence N. $45^{\circ} 33' 31''$ W.
177.84	Intersect line 3-4 Sur. 4658 ARIZONA NO. 41 lode at a point from which Cor. No. 3 bears N. $89^{\circ} 50' 23''$ W., 32.04 ft. dist.
227.83	Intersect line 4-5 Sur. 4658 ARIZONA NO. 42 lode at a point from which Cor. No. 4 bears S. $5^{\circ} 58' 37''$ E., 35.10 ft. dist.
530	Wash 50 ft. wide drains North
930	Wash 50 ft. wide drains East
1500.00	Cor. No. 1, and place of beginning.

FEET	
	NEVADA NO. 7 LODE
	At Cor. No. 1 of the Nevada NO. 7 lode.
	Set a 5/8 in. diam. steel bar, 24 in long, with aluminum cap affixed thereon, 16 ins. in the ground, mkd. NV 7-1-4648; from which
	The cor. of secs. 13, 14, 23, 24, T.17 S., R.12 E., bears N. 43° 09' 42" E., 1957.59 ft. dist. A 5/8 in. diam. steel bar projecting 4 in. above ground, firmly set, with aluminum cap marked with proper secs., Twp., and R. A reconstruction, by double proportional measurement of the monument set in 1872 by T. F. White. Set by R.L. Frazer, Registration No. 1144, in 1964.
	Thence S. 44° 26' 29" W.
100	Wash 50 ft. wide drains from N. 60° W., to S. 50° E.
300.00	Lode line, discovery point bears N. 45° 33' 31" W., 1400 ft. dist.
600.00	Cor. No. 2, identical with Cor. No. 3 of the NEVADA NO. 6 lode of this survey
	Thence N. 45° 33' 31" W.
17.01	Intersect line 1-2 Sur. 4658 ARIZONA NO. 42 lode at a point from which Cor. No. 2 bears S. 5° 58' 40" E., 269.10 ft. dist.
410	Wash 50 ft. wide drains N. 60° E.
953.29	Intersect line 4-5 Sur. 4658 ARIZONA NO. 42 lode at a point from which Cor. No. 5 bears N. 5° 58' 37" W., 523.40 ft. dist.
1500.00	Cor. No. 3, identical with Cor. No. 2 of the NEVADA NO. 6 lode of this survey.
	Thence N. 44° 26' 29" E.
300.00	Lode line, discovery point bears S. 45° 33' 31" E., 100 ft. dist.
600.00	Cor. No. 4.
	Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 ins. in the ground, mkd. NV 7-4-4648; from which
	Cor. No. 5 Sur. 4658 Arizona NO. 42 lode bears S. 16° 16' 51" W., 302.76 ft. dist.
	Thence S. 45° 33' 31" E.
416.57	Intersect line 5-1 Sur. 4658 ARIZONA NO. 42 lode at a point from which Cor. No. 5 bears N. 89° 50' 23" W., 381.70 ft. dist.

FEET	
757.22	Intersect line 1-2 Sur. 4658 ARIZONA NO. 42 lode at a point from which Cor. No. 2 bears S. 5° 58' 40" E., 1210.77 ft. dist.
1500.00	Cor. No. 1, and place of beginning.
NEVADA NO. 8 LODE	
	At Cor. No. 1 of the NEVADA NO. 8 lode identical with Cor. No. 1 Sur. 4658 CWT NO. 1 lode .
	Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 ins. in the ground, mkd. NV 8-1-4648 - CWT 1-1-4658; from which
	<p style="text-align: right;">T. 17 S., R. 12 E.</p> <p>The cor. of secs. 22, 23, 26, 27/bears S. 63° 55' 20" W., 2003.37 ft. dist., monumented by an iron post, 2 in. diam., firmly set in an East-West fence, projects 10 in. above ground, with a lead cap marked with proper secs., Twp., and R. The original survey in 1872 called for a wooden post. This point has been reconstructed prior to 1941 by a surveyor whose name is not known.</p>
	Cor. No. 4 Sur. 4656 ELLA #1 lode bears N. 37° 41' 03" E., 788.54 ft. dist. Identical with Cor. No. 3 Sur. 4658 MIDLAND NO. 23 lode. Thence N. 45° 37' 39" W.
. 55	Fence bears N. 14° 15' W., S. 14° 15' E.
195	Power line bears N. 82° E., S. 82° W.
208.38	Intersect line 2-3 Sur. 4656 ELLA #1 lode at a point from which Cor. No. 3 bears N. 3° 43' 28" E., 477.16 ft. dist.
299.83	Lode line, discovery point bears N. 44° 24' 42" E., 900 ft. dist.
599.65	Cor. No. 2, identical with Cor. No. 4 NEVADA NO. 2 lode, and Cor. No. 2 NEVADA NO. 3 lode of this survey.
	Thence N. 44° 26' 29" E.
283.11	Intersect line 3-4 Sur. 4656 ELLA #3, at a point from which Cor. No. 4 bears N. 89° 47' 36" E., 112.45 ft. dist.
329.68	Fence bears N. 14° 15' W., S. 14° 15' E.
599.68	Cor. No. 3 NEVADA NO. 2 lode, identical with Cor. No. 4 NEVADA NO. 1 lode of this survey; from which
	The SW. corner of a 30 ft. x 100 ft. open shed bears S. 59° 05' E., 453 ft. dist.



FEET

	<p>The NW. corner of the same shed bears S. 70° 10' E., 396 ft. dist.</p> <p>The SW. corner of a 30 ft. x 52 ft. sheet steel hoist house bears S. 74° 46' E., 531 ft. dist. The NW. corner bears S. 80° 02' E., 512 ft. dist.</p> <p>The SW. corner of a 28 ft. x 50 ft. sheet steel building bears S. 76° 03' E., 379 ft. dist. The NW. corner bears S. 83° 20' E., 362 ft. dist.</p>
860	Road bears N. 45° W., S. 45° E.
1199.56	Cor. No. 3 NEVADA NO. 1 lode, identical with Cor. No. 4 NEVADA NO. 4 lode of this survey.
1436.28	Intersect line 2-3 Sur. 4658 ARIZONA NO. 43 lode, at a point from which Cor. No. 2 bears S. 5° 57' 14" E., 681.64 ft. dist.
1497.92	Cor. No. 3, on line 3-4 NEVADA NO. 4 lode of this survey.
	<p>Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 ins. in the ground, mkd. NV 8-3-4648.</p> <p>Thence S. 45° 37' 39" E.</p>
299.04	Lode line, discovery point bears S. 44° 24' 42" W., 597.92 ft. dist.
390	Road bears N. 40° E.; S. 40° W.
520	Road, 20 ft. wide bears N. 85° E., S. 85° W.
598.09	Cor. No. 4, identical with Cor. No. 2 Sur. 4658 CWT NO. 1 lode
	<p>A 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 ins. in the ground, mkd. NV 8-4-4648 - CWT 1-2-4658; from which</p> <p>The NE. corner of an 18 ft. x 120 ft. sheet steel building bears S. 75° 47' W., 560 ft. dist. The SE. corner bears S. 63° 56' W., 582 ft. dist.</p> <p>Cor. No. 2 Sur. 4658 ARIZONA NO. 43 lode bears S. 52° 47' 18" W., 502.22 ft. dist.</p> <p>Thence S. 44° 22' 55" W.</p>
425.44	Intersect line 1-2 Sur. 4658 ARIZONA NO. 43 lode at a point from which Cor. No. 2 bears N. 89° 48' 50" W., 102.42 ft. dist.
620	The SE. corner of a 96 ft. x 28 ft. sheet steel office building bears N. 45° 37' W., 18 ft. dist.
624.12	Intersect line 3-4 Sur. 4658 MIDLAND NO. 23 lode at a point from which Cor. No. 3 bears S. 89° 47' 36" W., 129.14 ft. dist.

FEET	
700	The SW. corner of the aforementioned office building bears N. $45^{\circ} 37'$ W., 78 ft. dist.
821.86	Intersect common line 2-3 Sur. 4658 MIDLAND NO. 23 lode, and 4-1 Sur. 4656 ELLA #1 lode at a point from which the common Cor. No. 3 MIDLAND NO. 23 lode and Cor. No. 4 ELLA #1 lode bears N. $3^{\circ} 43' 28''$ E., 141.16 ft. dist.
970	Road bears N. $20^{\circ}$ W., S. $20^{\circ}$ E.
1255	Power line bears S. $82^{\circ}$ W., N. $82^{\circ}$ E.
1497.93	Cor. No. 1, and place of beginning.
<hr/> COLORADO NO. 13 LODE	
At Cor. No. 1 of the COLORADO NO. 13 lode, identical with Cor. No. 1 of the COLORADO NO. 14 lode of this survey.	
Set a $5/8$ in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 ins. in the ground, mkd. COL 13-1 - COL 14-1-4648; from which	
The $1/4$ sec. cor. of secs. 22, 23 bears S. $78^{\circ} 25' 56''$ E., 505.05 ft. dist., previously described.	
Thence N. $53^{\circ} 13' 17''$ E.	
250	Wash 30 ft. wide drains N. $35^{\circ}$ E.
300.00	Lode ling, discovery point bears S. $36^{\circ} 46' 43''$ E., 100 ft. dist.
317.08	Intersect line 1-2 UTAH NO. 49 lode of this survey.
460	Road bears North and South
530	Underground telephone cable bears N. $1^{\circ}$ W., S. $1^{\circ}$ E.
580	Power line bears N. $1^{\circ}$ W., S. $1^{\circ}$ E.
600	Cor. No. 2
Set a $5/8$ in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 ins. in the ground, mkd. COL 13-2-4648	
Thence S. $36^{\circ} 46' 43''$ E.	
11.52	Intersect the line between secs. 22 and 23 at a point from which the $1/4$ cor. of secs. 22 and 23 bears S. $0^{\circ} 55' 46''$ E., 451.35 ft. dist., previously described.

FEET	
90	Power line bears N. 0° 55' W., S. 0° 55' E.
782.50	Intersect the common line 4-1 UTAH NO. 49 and and 1-2 NEVADA NO. 2 lodes of this survey.
950	Road bears S. 65° W.; East
1500.00	Cor. No. 3
	Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 ins. in the ground, mkd. COL 13-3-4648.
	Thence S 53° 13' 17" W.
30	Wash 20 ft. wide drains S. 65° E.
50.99	Intersect the common line 4-1 NEVADA NO. 2 and 1-2 NEVADA NO. 3 lodes of this survey.
300.00	Lode line, discovery point bears N. 36° 46' 43" W., 1400 ft. dist.
600.00	Cor. No. 4, identical with Cor. No. 2 of the COLORADO NO. 14 lode of this survey.
	Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 ins. in the ground, mkd. COL 13-4- COL 14-2-4648
	Thence N. 36° 46' 43" W.
180	Wash 20 ft. wide drains S. 80° E.
595	Power line bears W. 2° 53' W., S. 2° 53' E.
624.83	Intersect line 4-1 NEVADA NO. 3 lode of this survey.
658.14	Intersect the line between secs. 22 and 23 at a point from which the 1/4 cor. of secs. 22 and 23 bears N. 0° 55' 31" W., 573.09 ft. dist., previously described
700	Power line bears N. 1° W., S. 1° E.
765	Underground telephone cable bears N. 1° W., S. 1° E.
1415	Wash 30 ft. wide drains S. 80° E.
1500.00	Cor. No. 1, and place of beginning.
	<p style="text-align: center;">COLORADO NO. 14 LODE</p>
	Beginning at Cor. No. 1 of the COLORADO NO. 14 lode, identical with Cor. No. 1 of the COLORADO NO. 13 lode of this survey.
	Thence S. 36° 46' 43" E.
85	Wash 30 ft. wide drains S. 80° E.
735	Underground telephone cable bears N. 1° W., S. 1° E.



FEET	
800	Power line bears N. 1° W., S. 1° E.
841.86	Intersect the line between secs. 22 and 23 at a point from which the 1/4 cor. of secs. 22 and 23 bears N. 0° 55' 31" W., 573.09 ft. dist., previously described.
875.17	Intersect line 4-1 NEVADA NO. 3 lode of this survey
905	Power line bears N. 2° 53' W., S. 2° 53' E.
1320	Wash 20 ft. wide drains S. 80° E.
1500.00	Cor. No. 2, identical with Cor. No. 4 of the COLORADO NO. 13 lode of this survey.  Thence S. 53° 13' 17" W.
54.96	Intersect line 3-4 Sur. 4657 ELLA #7 lode at a point from which Cor. No. 3 bears S. 89° 47' 36" W., 435.32 ft. dist.
58.10	Intersect line 3-4 NEVADA NO. 3 lode of this survey.
300.00	Lode line, discovery point bears N. 36° 46' 43" W., 1400 ft. dist.
405	Power line bears N. 2° 53' W., S. 2° 53' E.
475.60	Intersect the line between secs. 22 and 23 at a point from which the 1/4 cor. of secs. 22 and 23 bears N. 0° 55' 31" W., 1385.09 ft. dist., previously described.
480	Road bears North & South
515	Power line bears N. 1° W., S. 1° E.
570	Underground telephone cable bears N. 1° W., S. 1° E.
600.00	Cor. No. 3.  Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 ins. in the ground, mkd. COL 14-3-4648; from which  Cor. No. 3 Sur. 4657 ELLA #7 lode bears N. 0° 13' 04" E., 324.76 ft. dist.  Thence N. 36° 46' 43" W.
30.58	Intersect line 2-3 Sur. 4657 ELLA #7 lode at a point from which Cor. No. 3 bears N. 3° 43' 28" E., 300.90 ft. dist.
670	Wash 10 ft. wide drains N. 20° E.
750	Wash 15 ft. wide drains from S. 50° W., to East.

FEET	
1500.00	<p>Cor. No. 4.</p> <p>Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 ins. in the ground, mkd. COL 14-4-4648</p> <p>Thence N. 53° 13' 17" E.</p>
300.00	<p>Lode line, discovery point bears S. 36° 46' 43" E., 100 ft. dist.</p>
535	<p>Wash 30 ft. wide drains S. 70° E.</p>
600.00	<p>Cor. No. 1, and place of beginning.</p>
<p>UTAH NO. 49 LODE</p>	
<p>Beginning at Cor. No. 1 of the UTAH NO. 49 lode, identical with Cor. No. 1 of the NEVADA NO. 2 lode of this survey.</p>	
<p>Thence N. 45° 34' 36" W.</p>	
420	<p>Power line bears N. 1° W., S. 1° E.</p>
480.59	<p>Intersect the line between secs. 22 and 23 at a point from which the 1/4 cor. of secs. 22 and 23 bears S. 0° 55' 46" E., 55.99 ft. dist., previously described</p>
520	<p>Power line bears N. 1° W., S. 1° E.</p>
580	<p>Underground telephone cable bears N. 1° W., S. 1° E.</p>
660	<p>Road bears North, S. 10° E.</p>
816.52	<p>Intersect line 1-2 COLORADO NO. 13 lode of this survey.</p>
880	<p>Wash 30 ft. wide drains North</p>
1498.93	<p>Cor. No. 2</p> <p>Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 ins. in the ground, mkd. UT 49-2-4648.</p> <p>Thence N. 44° 26' 29" E.</p>
80	<p>Wash 20 ft. wide drains S. 85° E.</p>
300.00	<p>Lode line, discovery point bears S. 45° 34' 14" E., 1398.93 ft. dist.</p>
600.00	<p>Cor. No. 3, identical with Cor. No. 2 of the UTAH NO. 44 lode of this survey.</p> <p>Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 ins. in the ground, mkd. UT 49-3 - UT 44-2-4648</p>

FEET	
	Thence S. 45° 33' 52" E.
315	Underground telephone cable bears N. 1° W., S. 1° E.
370	Power line bears N. 1° W., S. 1° E.
380	Road bears N. 1° W., S. 1° E.
410.81	Intersect the line between secs. 22 and 23 at a point from which the 1/4 cor. of secs. 22 and 23 bears S. 0° 55' 46" E., 862.16 ft. dist., previously described.
470	Power line bears N. 1° W., S. 1° E.
540	Wash 30 ft. wide drains from West to N: 45° E.
1498.93	Cor. No. 4, identical with Cor. No. 1 of the NEVADA NO. 1 lode of this survey.
	Thence S. 44° 26' 29" W.
299.84	Lode line, discovery point bears N. 45° 34' 14" W., 100 ft. dist.
439.77	Intersect line 2-3 COLORADO NO. 13 lode of this survey.
599.68	Cor. No. 1, and place of beginning.
UTAH NO. 44 LODGE	
	Beginning at Cor. No. 1 of the UTAH NO. 44 lode, identical with Cor. No. 1 of the NEVADA NO. 1 lode of this survey.
	Thence N. 45° 33' 52" W.
960	Wash 30 ft. wide drains from West to N. 45° E.
1028.93	Power line bears N: 1° W., S. 1° E.
1088.12	Intersect the line between secs. 22 and 23 at a point from which the 1/4 cor. of secs. 22 and 23 bears S. 0° 55' 46" E., 862.16 ft. dist., previously described
1120	Road bears S. 1° W., S. 1° E.
1128.93	Power line bears N. 1° W., S. 1° E.
1185	Underground telephone cable bears N. 1° W., S. 1° E.
1498.93	Cor. No. 2, identical with Cor. No. 3 UTAH NO. 49 lode of this survey.
	Thence N. 44° 26' 29" E.
299.44	Lode line, discovery point bears S. 45° 35' 02" E.; 1398.93 ft. dist.



FEET	
310	Underground telephone cable bears N. 1° W., S. 1° E.
360	Power line bears N. 1° W., S. 1° E.
370	Road bears N. 1° W., S. 1° E.
405.57	Intersect the line between secs. 22 and 23 at a point from which the 1/4 cor. of secs. 22 and 23 bears S. 0° 55' 46" E., 1486.91 ft. dist., previously described.
465	Power line bears N. 1° W., S. 1° E.
598.87	Cor. No. 3, identical with Cor. No. 4 . UTAH NO. 43 lode of this survey.
	Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 ins. in the ground, mkd. UT 44-3- UT 43-4-4648
	Thence S. 45° 36' 11" E.
200	Wash 20 ft. wide drains North
900	Wash 30 ft. wide drains East
1250	Road bears S. 10° W., N. 40° E.
1498.93	Cor. No. 4, identical with Cor. No. 2 of the NEVADA NO. 1 lode of this survey.
	Thence S. 44° 26' 29" W.
120	Road bears N. 35° W., S. 35° E.
299.94	Lode line, discovery point bears N. 45° 35' 02" W., 100 ft. dist.
599.88	Cor. No. 1, and place of beginning.
UTAH NO. 43 LODE	
	At Cor. No. 1 of the UTAH NO. 43 lode, on line 4-1 of the CWT NO. 2 lode of this survey.
	Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 ins. in the ground, mkd. UT 43-1-4648; from which
	The cor. of secs. 14, 15, 22, 23 bears N. 37° 52' 18" W., 820.76 ft. dist., previously described.
	Thence S. 45° 35' 04" E.
120	Wash 20 ft. wide drains N. 75° E.
1310	Road bears N. 75° E., S. 75° W.
1498.93	Cor. No. 2, on line 2-3 of the CWT NO. 2 lode and on line 1-2 of the NEVADA NO. 4 lode of this survey.

FEET	
	Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 ins. in the ground, mkd. UT 43-2-4648 Thence S. 44° 26' 29" W.
50	Wash 50 ft. wide drains N. 70° E.
240.35	Cor. No. 3 of the CWT NO. 2 lode of this survey, hereinafter described.
249.67	Lode line, discovery point bears N. 45° 35' 37" W., 100 ft. dist.
499.35	Cor. No. 3, identical with Cor. No. 1, NEVADA NO. 4 lode of this survey. Thence N. 45° 36' 11" W.
250	Road bears N. 40° E., S. 10° W.
600	Wash 30 ft. wide drains East
1300	Wash 20 ft. wide drains North
1498.93	Cor. No. 4, identical with Cor. No. 3 UTAH NO. 44 lode of this survey, Thence N. 44° 26' 29" E.
249.92	Lode line, discovery point bears S. 45° 35' 37" E., 1398.93 ft. dist.
261.00	Cor. No. 4 CWT NO. 2 lode of this survey, hereinafter described.
499.84	Cor. No. 1 and place of beginning.
UTAH NO. 42 LOPE	
	At Cor. No. 1 of the UTAH NO. 42 lode, on line 4-1 of the CWT NO. 2 lode of this survey.
	Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 ins. in the ground, mkd. UT 42-1-4648; from which Cor. No. 1 of the UTAH NO. 43 lode bears S. 44° 26' 29" W., 101.56 ft. dist. The cor. of secs. 14, 15, 22, 23 bears N. 44° 58' 44" W., 813.43 ft. dist., Previously described. Thence N. 44° 26' 29" E.
259.60	Cor. No. 1 of the CWT NO. 2 lode of this survey, hereinafter described.

FEET	
300.00	Lode line, discovery point bears S. 45° 31' 48" E., 1398.93 ft. dist.
410	Wash 50 ft. wide drains East.
600.00	Cor. No. 2. Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 ins. in the ground, mkd. UT 42-2-4648 Thence S. 45° 31' 48" E.
130	Wash 50 ft. wide drains from N. 50° W., to East.
630	Wash 60 ft. wide drains from N. 45° W., to East.
1260	Road bears North, South.
1498.93	Cor. No. 3, identical with Cor. No. 2 NEVADA NO. 5 lode of this survey. Thence S. 44° 26' 29" W.
300.00	Lode line, discovery point bears N. 45° 31' 48" W., 100 ft. dist.
340.50	Cor. No. 2 of the CWT NO. 2 lode of this survey, hereinafter described.
600.00	Cor. No. 4, identical with Cor. No. 2 NEVADA NO. 4 lode of this survey; from which Cor. No. 2 of the UTAH NO. 43 lode of this survey bears S. 44° 26' 29" W., 100.15 ft. dist. Thence N. 45° 31' 48" W.
130	Road bears East.
1330	Wash 30 ft. wide drains N. 60° E.
1498.93	Cor. No. 1, and place of beginning.
CWT NO. 2 LODE	
At Cor. No. 1, of the CWT NO. 2 lode, on line 1-2 of the UTAH NO. 42 lode of this survey:	
Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 ins. in the ground, mkd. CWT 2-1-4648; from which Cor. No. 1 of the UTAH NO. 42 lode bears S. 44° 26' 29" W., 259.60 ft. dist.	
The cor. of secs. 14, 15, 22, 23 bears N. 62° 43' 55" W., 851.34 ft. dist., previously described.	



FEET	
	Thence S. 45° 31' 36" E.
230	Wash 20 ft. wide drains N. 60° E.
1480	Road bears S. 45° E., N. 45° W.
1498.93	Cor. No. 2, on line 3-4 UTAH NO. 42 lode and on line 1-2 of the NEVADA NO. 5 lode of this survey. Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 ins. in the ground, mkd. CWT 2-2-4648
	Thence S. 44° 26' 29" W.
259.50	Cor. No. 4 UTAH NO. 42 lode of this survey.
300.00	Lode line, discovery point bears N. 45° 31' 36" W., 50 ft. dist.
359.65	Cor. No. 2 UTAH NO. 43 lode of this survey.
410.00	Wash 50 ft. wide drains N. 70° E.
600.00	Cor. No. 3, on line 2-3 UTAH NO. 43 lode of this survey. Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 ins. in the ground, mkd. CWT 2-3-4648.
	Thence N. 45° 31' 36" W.
250	Road bears N. 40° E., S. 40° W.
380	Wash 30 ft. wide drains from N. 70° W., to S. 65° E.
1420	Wash 20 ft. wide drains N. 40° E.
1498.93	Cor. No. 4, on line 4-1 UTAH NO. 43 lode of this survey. Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 ins. in the ground, mkd. CWT 2-4-4648
	Thence N. 44° 26' 29" E.
238.84	Cor. No. 1 UTAH NO. 43 lode of this survey.
300.00	Lode line, discovery point bears S. 45° 31' 36" E., 1448.93 ft. dist.
340.40	Cor. No. 1 UTAH NO. 42 lode of this survey.
600.00	Cor. No. 1, and place of beginning.

FEET	Areas	Acres
	Total area NEVADA NO. 8 lode	20.594
	Area in conflict with -	
130.00	Sur. 4658 ARIZONA NO. 43 lode	4.141
040.00	Sur. 4658 MIDLAND NO. 23 lode	0.209
720.00	Sur. 4656 ELLA #1 lode	5.865
100.00	Sur. 4656 ELLA #3 lode	1.886
	Total area NEVADA NO. 1 lode	20.657
	Total area NEVADA NO. 2 lode	20.650
	Area in conflict with -	
253.00	COLORADO NO. 13 lode of this survey	1.707
	Sur. 4656 ELLA #3 lode	0.931
	Total area NEVADA NO. 3 lode	20.661
	Area in conflict with -	
248.00	COLORADO NO. 13 lode of this survey	7.537
340.00	Sur. 4657 ELLA #5 lode	5.790
	Sur. 4656 ELLA #3 lode	2.037
180.00	COLORADO NO. 14 lode of this survey	1.484
	Sur. 4657 ELLA #7 lode	0.304
	Area of conflict COLORADO NO. 14 lode with ELLA #7 lode within NEVADA NO. 3 lode (4.5 sq.ft.)	0.000
	COLORADO NO. 14 lode exclusive of its conflict with Sur. 4657 ELLA #7 lode	1.484
	Total area NEVADA NO. 4 lode	20.644
	Area in conflict with -	
	Sur. 4658 ARIZONA NO. 43 lode	1.826
	Total area NEVADA NO. 5 lode	20.661
	Area in conflict with -	
	Sur. 4658 ARIZONA NO. 41 lode	0.480
	Sur. 4658 ARIZONA NO. 42 lode	0.013
	Sur. 4658 ARIZONA NO. 43 lode	9.562
	Total area NEVADA NO. 6 lode	20.653
	Area in conflict with -	
	Sur. 4658 ARIZONA NO. 42 lode	7.775
	Sur. 4658 ARIZONA NO. 40 lode	0.003
	Sur. 4658 ARIZONA NO. 41 lode	0.354
	Total area NEVADA NO. 7 lode	20.661
	Area in conflict with -	
	Sur. 4658 ARIZONA NO. 42 lode	11.074
	Sur. 4658 ARIZONA NO. 40 lode	5.233
	Total area COLORADO NO. 14 lode	20.661
	Area in conflict with -	
	Sur. 4657 ELLA #7 lode	1.691
	NEVADA NO. 3 lode of this survey	1.484
Sur. No. 4657	ELLA #7 lode exclusive of its conflict with NEVADA NO. 3 lode	1.691

FEET	<u>Areas</u>	<u>Acres</u>
	Total area COLORADO NO. 13 lode	20.661
	Area in conflict with -	
	UTAH NO. 49 lode of this survey	4.040
	NEVADA NO. 3 lode of this survey	7.537
	NEVADA NO. 2 lode of this survey	1.707
	Total area UTAH NO. 49 lode	20.641
	Area in conflict with	
	COLORADO NO. 13 lode of this survey	4.040
	Total area UTAH NO. 44 lode	20.625
	Total area UTAH NO. 43 lode	17.191
	Area in conflict with -	
	CWT NO. 2 lode of this survey	8.245
	Total area UTAH NO. 42 lode	20.646
	Area in conflict with	
	CWT NO. 2 lode of this survey	8.931
	Total area CWT NO. 2 lode	20.646
	Area in conflict with -	
	UTAH NO. 43 lode of this survey	8.245
	UTAH NO. 42 lode of this survey	8.931



FEET

LOCATION

This survey is located in secs. 22 & 23,  
T.17S., R.12E., G.&SR.B&M.

The survey is identical with the respective  
locations or amended locations as marked on  
the ground with 4 x 4 posts.

EXPENDITURES

The improvements and the value of the labor  
and improvements made upon or for the benefit  
of each of the lode locations embraced in said  
mining claims by the claimants or its grantors  
is as follows:

No. 1 The discovery point of the NEVADA NO. 1 lode  
is on the lode line 1400 ft., S. 45° 33'  
31" E. from the center of line 1-2.  
Value, None

No. 2 A trench, the center of which bears S. 61° 56'  
W., 313 ft. from Cor. No. 3 NEVADA NO. 1  
lode; 6 x 8 ft. 8 ft. deep.  
Value, \$25.00

No. 1 The discovery point of the UTAH NO. 44 lode  
is on the lode line, 100 ft., N. 45° 35'  
02" W., from the center of line 4-1.  
Value, None

No. 2 A trench, the center of which bears N. 31° 46'  
E., 281 ft. from Cor. No. 1 UTAH NO. 44  
lode, 8 x 20 ft., 8' deep.  
Value, \$25.00

An interest in a common improvement described  
as follows:

A core drill hole designated in mine records  
as "T-43", the center of which bears  
S. 87° 42' 21" E., 397.05 ft. dist. from  
Cor. No. 1 NEVADA NO. 1 lode. 4-1/2 in.  
diam., 2 in. core, 1088 ft. deep.

Value of 1088 ft. at  
\$4.37 per ft., \$4,754.55.  
Value of 1/2 interest, \$2,377.25

This improvement is for the development of  
the NEVADA NO. 1 and UTAH NO. 44 lodes of  
this survey, which are contiguous lode  
claims owned in common within range of  
benefit of said improvement.

Five hundred dollars or more has been expended  
in this improvement in such a manner as  
tends to the development of the aforesaid  
two lodes of this survey, subsequent to  
their location and to the time since which  
common ownership and contiguity have pre-  
vailed, therefore an undivided one-half  
interest is hereby credited to each of  
said claims.

Except as above stated, no portion or interest  
in this improvement has been credited here-  
tofore as patent expenditures to any lode  
claim.

FEET	
No. 1	The discovery point of the NEVADA NO. 4 lode is on the lode line, 1400 ft., S. 45° 33' 31" E., from the center of line 1-2. Value, None.
No. 2	A trench, the center of which bears S. 62° 00' W., 311 ft. from Cor. No. 3 NEVADA NO. 4, 7 x 18 ft., 8 ft. deep. Value, \$25.00
No. 1	The discovery point of the NEVADA NO. 5 lode is on the lode line, 100 ft., S. 45° 33' 31" E., from the center of line 1-2. Value, None
No. 2	A trench, the center of which bears S. 24° 27' W., 314 ft. from Cor. No. 2, NEVADA NO. 5, 5 x 18 ft., 8 ft. deep. Value, \$25.00
No. 1	The discovery point of the NEVADA NO. 6 lode is on the lode line, 100 ft., S. 45° 33' 31" E. from the center of line 1-2. Value, None
No. 2	A trench, the center of which bears S. 25° 34' W., 315 ft. from Cor. No. 2 NEVADA NO. 6 lode, 6 x 20 ft., 8 ft. deep. Value \$25.00
No. 1	The discovery point of the NEVADA NO. 7 lode is on the lode line, 1400 ft., N. 45° 33' 31" W., from the center of line 1-2. Value, None
No. 2	A trench, the center of which bears S. 24° 54' W., 316 ft. from Cor. No. 4 NEVADA NO. 7 lode, 8 x 20 ft., 8 ft. deep. Value, \$25.00
No. 1	The discovery point of the UTAH NO. 42 lode is on the lode line 1398.93 ft., S. 45° 31' 48" E., from the center of line 1-2 Value, None
No. 2	A trench, the center of which bears S. 61° 37' W., 307 ft. from Cor. No. 3 of the UTAH NO. 42 lode, 10 x 18 ft., 8 ft. deep. Value, \$25.00
No. 1	The discovery point of the UTAH NO. 43 lode is on the lode line, 1398.93 ft., S. 45° 35' 37" E., from the center of line 4-1. Value, None
No. 2	A trench, the center of which bears S. 65° 28' W., 268 ft. from Cor. No. 2 of the UTAH NO. 43 lode. 8 x 20 ft., 8 ft. deep Value, \$25.00

FEET

An interest in a common improvement described as follows:

A core drill hole designated in mine records as "T-11", the center of which bears S. 26° 04' 34" E., 694.40 ft. dist. from Cor. No. 2 of the NEVADA NO. 4 lode..  
 4-1/2 in. diam., 2 in. core, 1295 ft. deep.  
 Value of 1295 ft.  
 at \$4.37 per ft. \$5,659.15  
 Value of 1/6 interest, \$ 943.19

This improvement is for the development of the NEVADA NO. 4 lode of this survey and for the NEVADA NO. 5, NEVADA NO. 6, NEVADA NO. 7, UTAH NO. 42, and UTAH NO. 43 lodes of this survey, which are contiguous lode claims owned in common within range of benefit of said improvement.

Five hundred dollars or more has been expended in this improvement in such a manner as tends to the development of the aforesaid six lodes of this survey subsequent to their location and to the time since which common ownership and contiguity have prevailed, therefore an undivided one-sixth interest is hereby credited to each of said claims.

Except as above stated, no portion or interest in this improvement has been credited heretofore as patent expenditures to any lode claim.

No. 1 The discovery point of the NEVADA NO. 8 lode is on the lode line 900 ft., N. 44° 24' 42" E., from the center of line 1-2.  
 Value, None

No. 2 A trench, the center of which bears S. 70° 56' W., 670 ft. from Cor. No. 4 of the NEVADA NO. 8 lode. 6 x 8 ft., 8 ft. deep.  
 Value, \$25.00

No. 3 A core drill hole designated in mine records as "C-20", the center of which bears S. 28° 37' 14" W., 366.36 ft. dist. from Cor. No. 3 of the NEVADA NO. 8 lode.  
 4-1/2 ins. diam., 2 in. core, 791 ft. deep.  
 Value of 791 ft.  
 at \$4.37 per ft., \$ 3,456.67

No. 1 The discovery point of the NEVADA NO. 2 lode is on the lode line 30 ft., S. 45° 33' 31" E., from the center of line 1-2.  
 Value, None

No. 2 A trench, the center of which bears S. 37° 56' W., 299 ft. from Cor. No. 2 of the NEVADA NO. 2 lode. 8 x 10 ft., 8 ft. deep.  
 Value, \$25.00

No. 1 The discovery point of the NEVADA NO. 3 lode is on the lode line 750 ft., S. 45° 33' 31" E., from the center of line 4-1.  
 Value, None



FEET	
No. 2	A trench, the center of which bears S. 22° 58' W., 779 ft. from Cor. No. 1 of the NEVADA NO. 3 lode 6 x 10 ft., 8 ft. deep. Value, \$25.00
No. 1	The discovery point of the COLORADO NO. 13 lode is on the lode line 100 ft., S. 36° 46' 43" E., from the center of line 1-2. Value, None
No. 2	A trench, the center of which bears N. 55° 52' E., 295 ft. from Cor. No. 1 of the COLORADO NO. 13 lode. 8 x 8 ft., 8 ft. deep. Value, \$25.00
No. 1	The discovery point of the COLORADO NO. 14 lode is on the lode line 100 ft., S. 36° 46' 43" E., from the center of line 4-1 Value, None
No. 2	A trench, the center of which bears S. 31° 09' W., 315 ft. from Cor. No. 1 of the COLORADO NO. 14 lode, 10 x 20 ft., 8 ft. deep. Value, \$25.00
No. 1	The discovery point of the UTAH NO. 49 lode is on the lode line, 100 ft. N. 45° 34' 14" W. from the center of line 4-1. Value, None
No. 2	A trench, the center of which bears N. 26° 00' E., 316 ft. from Cor. No. 1 of the UTAH NO. 49 lode. 6 x 15 ft., 8 ft. deep. Value, \$25.00
	An interest in a common improvement described as follows:
	A core drill hole designated in mine records as "T-59", the center of which bears N. 83° 27' 38" W., 165.85 ft. dist. from Cor. No. 3 of the NEVADA NO. 2 lode. 4-1/2 ins. diam., 2 in. core, 1091 ft. deep.
	Value of 1091 ft.
	at \$4.37 per ft., \$4,767.67
	Value of 1/5 interest, \$ 953.53
	This improvement is for the development of the NEVADA NO. 2, NEVADA NO. 3, COLORADO NO. 13, COLORADO NO. 14, and UTAH NO. 49 lodes of this survey, which are contiguous lode claims owned in common within range of benefit of said improvement.
	Five hundred dollars or more has been expended in this improvement in such a manner as tends to the development of the aforesaid five lodes of this survey subsequent to their location and to the time since which common ownership and contiguity have prevailed, therefore an undivided one-fifth interest is hereby credited to each of said claims.

FEET	
	<p>Except as above stated, no portion or interest in this improvement has been credited heretofore as patent expenditures to any lode claim.</p>
No. 1	<p>The discovery point of the CWT NO. 2 lode is on the lode line 50 ft., N. 45° 31' 36" W. from the center of line 2-3. Value, None.</p>
No. 2	<p>A trench, the center of which bears S. 55° 22' W., 302 ft. from Cor. No. 2 of the CWT NO. 2 lode. 10 x 15 ft., 8 ft. deep. Value, \$25.00.</p>
	<p>An interest in a common improvement described as follows:</p> <p>A vertical shaft, 8 x 17 ft. in size, 1,000 ft. deep, the center of which bears S. 31° 10' 41" E., 2079.67 ft. from Cor. No. 3 of the CWT NO. 2 lode. The shaft is located on the NEVADA NO. 8 lode, S. 53° 18' 30" W., 560.4 ft. from Cor. No. 4 of the NEVADA NO. 8 lode of this survey.</p>
	<p>Hoist equipment installed and operating. Steel head frame. Main tunnel heading at 800 ft. and 900 ft. below shaft collar, averaging 12 ft. wide and 8 ft. to 12 ft. high. Various drifts, raises and stopes. Value of shaft, tunnels, drifts, raises, stopes, hoist equipment and steel head-frame, \$376,908.00. Value of one-fifteenth interest, \$25,127.20.</p>
	<p>This improvement is for the development of the fifteen lodes of this survey which are all the contiguous lode claims owned in common within the range of benefit of said shaft.</p>
	<p>Five hundred dollars or over has been expended in this improvement in such a manner as tends to the development of each lode of this survey subsequent to its location and to the time since when common ownership and contiguity have prevailed: therefore an undivided one-fifteenth interest in its value is hereby credited to each of said lodes.</p>
	<p>Except as above stated, no portion of or interest in this improvement has been credited heretofore as patent expenditures to any lode claim.</p>
	<p style="text-align: center;">OTHER IMPROVEMENTS</p>
	<p>Core drill holes, 4-1/2 ins. diam., 2 in. core, of depths and mine record designation as follows:</p>

FEET	Designation	Lode Claim	Depth Ft.
	P-1	NEVADA NO. 8	1137
	C-10	NEVADA NO. 8	857
	C-11	NEVADA NO. 8	784
	C-14	NEVADA NO. 8	789
	C-15	NEVADA NO. 8	775
	C-19	NEVADA NO. 8	775
	C-21	NEVADA NO. 8	778
	C-22	NEVADA NO. 8	793
	C-23	NEVADA NO. 8	733
	C-7	NEVADA NO. 8	837
	T-3	NEVADA NO. 4	1078
	C-3	NEVADA NO. 4	880
	C-8	NEVADA NO. 4	838
	C-12	NEVADA NO. 4	795
	C-13	NEVADA NO. 4	828
	C-17	NEVADA NO. 4	750
	Claimants herein		
	T-12	NEVADA NO. 1	1148
	C-9	NEVADA NO. 1	883
	T-10	NEVADA NO. 1	1167
	T-41	NEVADA NO. 2	1069
	T-44	NEVADA NO. 3	451
	Claimants herein		
	Buildings, as described in field notes, as follows:		
	A sheet steel office building. Claimants herein.		
	An open shed with corrugated iron roof, 30 x 100 ft. Claimants herein.		
	A sheet steel storage building, 28 x 50 ft. Claimants herein.		
	A sheet steel hoist house, 30 x 52 ft., and hoisting equipment. Claimants herein.		
	A bladed mine access road, approximately 20 ft. wide, across the NEVADA NO. 8 lode, as described in field notes and shown on plat. Claimants herein.		



	FEET	
		<p>An electrical power line, as described in field notes and shown on plat. Claimants unknown.</p> <p>A four-wire, steel post fence, as described in field notes and shown on plat. Claimants herein.</p> <p style="text-align: center;">OTHER CORNER DESCRIPTIONS AND SUPPLEMENTAL DATA</p> <p>The cor. of secs. 22, 23, 26 and 27, the 1/4 cor. of secs. 22 and 23, and the cor. of secs. 14, 15, 22 and 23 are monumented with 2 in. diam., iron posts projecting 10 ins. above the ground, and topped with lead caps marked with proper corner markings. These corners are accepted as the best remaining evidence of the wooden posts set in the official survey by T. F. White in 1872.</p> <p>The bearing and distance of the S-1/2 mile between secs. 22 and 23 was found to be N. 0° 55' 31" W. for 2631.03 ft. instead of the 1872 record of North for 2640.00 ft. The N. 1/2 mi. between secs. 22 and 23 was found to be N. 0° 55' 46" W. for 2629.85 ft. instead of the 1872 record of North for 2640.00 ft.</p>

(This form bound on left side)



UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

CERTIFICATE OF SURVEYOR

Name of Mineral Surveyor Robert L. Frazer	Date July 28, 1967
--	-----------------------

I HEREBY CERTIFY That in pursuance of an order received from the Division of Engineering, Bureau of Land Management, at Phoenix, Arizona, dated January 24, 1967, I have carefully executed the survey of the claims of C. Darrel Wilson and others as listed on reverse side hereof, known as the (lode, placer, or mill site) 15 lode claims listed on reverse side hereof situated in secs. 22 & 23, Township 17S., Range 12E., Gila and Salt River Base and Meridian, in the State of Arizona

This survey, designated as number 4648, has been executed by me and under my direction and has been made in strict conformity with said order, the Manual of Instructions for the Survey of Public Lands of the United States, and in the specific manner described in the foregoing field notes.

I FURTHER CERTIFY That the labor expended and improvements made upon and for the benefit of the (lode or placer) lode location(s) embraced in the said mining claim by claimant(s) or their grantors are fully stated in my report. The character, extent, location, and itemized value are specified in full detail. No portion of, or interest in, said labor and improvements so credited to this claim has been included in the estimate of expenditures upon any other claim.

P.O. Box 1711, Tucson, Arizona  
(Location)

*Robert L. Frazer*  
(Signature of Mineral Surveyor)

CERTIFICATE OF APPROVAL

Bureau of Land Management Office Arizona State Office Location Phoenix, Arizona Date December 19, 1968
--

The foregoing field notes of mineral survey number 4648, in Sections 22 and 23 Township 17 S., Range 12 E., Gila and Salt River Meridian, in the State of Arizona, executed by Robert L. Frazer, Mineral Surveyor, under order dated January 24, 1967, having been critically examined and the necessary corrections made prior to their certification by the surveyor, the field notes and the survey therein described are hereby approved.

*Gregg Lewis*  
(Authorized Signature)

State Director  
(Title)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of field notes of the above described mineral survey number is a true copy of the original field notes.

(Authorized Signature)

(Title)

18, U. S. C. section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious, or fraudulent statements or representations as to any matter within jurisdiction.



33A

DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT  
WASHINGTON, D. C. 20240

CLAIMS OF: C. Darrel Wilson  
Alice Ann Kilroy  
Steven C. Chilson  
Daniel G. Chilson, Jr.  
Russell A. & Ella C. Todd;  
Richard E. Chilson  
Marian C. Chilson  
Donna Gail Chilson, and  
Laurita Yarter  
c/o Evans, Kitchel & Jenckes, Attorneys at Law  
363 North 1st Avenue, Phoenix, Arizona

LODE CLAIMS KNOWN AS:

- NEVADA NO. 1
- NEVADA NO. 2
- NEVADA NO. 3
- NEVADA NO. 4
- NEVADA NO. 5
- NEVADA NO. 6
- NEVADA NO. 7
- NEVADA NO. 8
- UTAH NO. 42
- UTAH NO. 43
- UTAH NO. 44
- UTAH NO. 49
- COLORADO NO. 13
- COLORADO NO. 14
- CWT NO. 2

*[Handwritten signature]*

