

Form 4-683  
(January 1963)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTES

Mineral Survey number  
4673

State  
Arizona

Land District  
Arizona

Of the Survey of the Mining Claim of *(name and address of Claimant)*

John C. Rhodes  
Freddy A. Rhodes  
Charles R. Rhodes  
P.O. Box 27  
Fort Thomas, Arizona 85536

Known as the *(name of group, if any)*

CONSISTING OF LOCATIONS NAMED AND LOCATED AS FOLLOWS

NAME OF LOCATION	DATE	
	LOCATED	AMENDED
MOUNT JACKSON #1	9/19/64	
MT. JACKSON #2	9/19/64	

Mining district Aravaipa			County Graham	
Section 6, 7, & 8	Township 6 South	Range 22 East	Meridian G. & S. R. B. & M.	Survey under order dated 9/24/68
Survey commenced 2/8/69		Survey completed 4/12/69	Name of Mineral Surveyor Robert N. Hermon	



FEET	<p>This survey was performed using an Ogawa Sieki transit, No. 375951, having a horizontal limb, 5.84 ins. in diam., with two double opposite verniers and having a full vertical circle, 3.35 ins. in diam., with one double vernier; the horizontal vernier can be read to 20 seconds of arc and the vertical vernier to one minute. The instrument was in good condition at the time of the survey and all adjustments in order.</p> <p>All azimuths in this record were determined from deflection angles referred to the meridian determined by the following observation:</p> <p>February 8, 1969 at the corner common to Sections 5, 6, 7 and 8, T. 6 S., R. 22 E., G.&amp;S.R.B.&amp;M. in Latitude 32°56' N. and Longitude 110°07'30" W., I make a series of six altitude observations upon the sun for azimuth at approximately equal time intervals, three each with the telescope in direct and reversed positions observing opposite limbs of the sun and reading the horizontal angle from a reference point about 370 feet Northwesterly; angles turned clockwise SE to the sun.</p> <p>Mean time of observation 105th meridian standard time = 9:59:23 a.m.  Declination of sun at mean time of observation = 14°53'16" S.  Mean observed vertical angle to suns center = 29°38'40"  Mean horizontal angle from reference point to suns center = 186°07'15"  True bearing to reference point = N. 49° 59'25" W.</p> <p>The lines were measured with a Dietzgen steel tape 101 feet in length graduated every foot for 100 feet and the remaining foot in tenths and hundredths. The tape was compared to a standard and found to be correct. All lines and connections of this survey were run by direct methods.</p> <p>The magnetic declination observed at each corner of the survey gave a uniform value of 14° East.</p>
	<p>MT. JACKSON #2 LODE</p> <p>At Cor. No. 1 of the MT. JACKSON #2 lode.</p> <p>Set a 3/4 in. Galv. pipe, 36 ins. long, concrete filled and flared at one end, 12 ins. in the ground to bedrock, with concrete around base of pipe, surrounded by a mound of stone to top, with 2 in. brass cap, mkd. M.J.2-1-4673; from which</p> <p>The cor. of secs. 5, 6, 7 and 8, T. 6</p>

(This form bound on left side)

FEET	
	<p>S., R. 22 E., G.&amp;S.R.B.&amp;M., bears N. 29°09' W. 66.42 ft. dist.; an iron post 2 ins. diam., 12 ins. above ground, mkd. and witnessed as described in the official record.</p> <p>Thence S. 51°43' W.</p>
41.06	Intersect line between sections 7 and 8 at a point from which the corner of sections 5, 6, 7 and 8 bears N. 0°05' W., 83.45 ft. distant previously described.
297	Center of small gulch, 2 ft. dry wash, course N. 15° E.
300.0	<p>Lode line; discovery point bears N. 41° 14' W., 1,388.33 ft. dist.</p> <p>Set a 3/4 in. Galv. pipe, 36 ins. long, 12 ins. in ground to bedrock, with concrete around base of pipe, surrounded by a mound of stone to top, with a 2 in. brass cap, mkd. M.J.2-S.E.E.C.M.-4673.</p>
383	Top of steep rock bedrock out crop, course N. 20° W.
591.91	<p>A point on granite bedrock out crop, even with general surface, bearing object for Cor. No. 3.</p> <p>Set a 1-1/2 in. lead cap on a 5/8 in. X 5 in. iron pin leaded 4 ins. into solid rock, mkd. B.O.-M.J.2-2-4673.</p>
600.0	<p>Cor. No. 2.</p> <p>This corner falls 3.5 ft. above general surface on the point of a bedrock out crop that slopes S. 45° from Vertical.</p> <p>Set a 3/4 in. Galv. pipe, 4 ins. long, over an 1/2 in. X 8 in. iron pin leaded 4 ins. into solid rock and 4 ins. inside of 3/4 in. Galv. pipe, with a 2 in. brass cap, mkd. M.J.2-2-4673.</p> <p>Thence N. 41°14' W.</p>
170	Begin decent of a long steep slope into a large gulch, bears North & South.
561	Toe of slope and Southeast upper bank of wash, course North.
624	Center of large wash & gulch, course North.
687	Point on Crest of low ridge between washes, course N. 15° E.
792	Center of large wash & gulch, course N. 40° E.

FEET	
897	Top of upper bank of large wash, course N. 45° E.
1,131	Crest of ridge between drainage areas, course N. 45° E.
1,500.0	Cor. No. 3, identical with Cor. No. 2 of the MOUNT JACKSON #1 lode of this survey.
	<p>Set a 3/4 in. Galv. pipe, 36 ins. long, 14 ins. in ground to bedrock, with concrete around base, surrounded by a mound of stone concreted in place to top, with 2 in. brass cap, mkd. M.J.1-2-M.J.2-3-4673; from which</p> <p>A 1-1/2 in. Lead Cap set on a 5/8 in. iron pin leaded flush into face of vertical bedrock out crop, 3.5 ft. above general surface, bears S. 31°43' W., 5.97 ft. dist., mkd. B.O.-M.J.1-2-M.J.2-3-4673.</p> <p style="text-align: center;">Thence N. 51°43' E.</p>
300.0	<p>Lode line; discovery point bears S. 41° 14' E., 111.67 ft. dist.</p> <p>Set a 3/4 in. Galv. pipe, 36 ins. long, 12 ins. in ground to bedrock, with concrete around base, surrounded by mound of stone to top, concreted in place, with a 2 in. brass cap, mkd. M.J.1-S.E.E.C.M.-M.J.2-N.W.E.C.M.-4673; from which</p> <p>A distant peak, known as Mt. Turnbull, bears N. 38°29' W.</p>
305	Southwest edge of a mine cut, bears N. 38°17' W., and S. 38°17' E.
325	Northeast edge of a mine cut, bears N. 38°17' W., and S. 38°17' E.
384	Center of mine road, bears N. 14° W. and S. 14° E.
550	Center of wash, 20 ft. wide and 5 ft. deep, course North.
600.0	Cor. No. 4, identical with Cor. No. 1 of the MOUNT JACKSON #1 lode of this survey.
	<p>Set a 3/4 in. Galv. pipe, 36 ins. long, 14 ins. in ground to bedrock, with concrete around base, surrounded by mound of stone, concreted in place to top, with 2 in. brass cap, mkd. M.J.1-1-M.J.2-4-4673.</p> <p style="text-align: center;">Thence S. 41°14' E.</p>
159	Center of wash, 25 ft. wide, course N.

(This form bound on left side)

FEET	
	10° W.
1,065	Crest of high ridge, course N. 20° E.
1,422.81	Intersect the line between secs. 6 and 7, at a point from which the corner of secs. 5, 6, 7 and 8, bears S. 89°52' E., 18.53 ft. dist., previously described.
1,450.97	Intersect the line between secs. 7 and 8, at a point from which the corner of secs. 5, 6, 7 and 8, bears N. 0°05' W., 21.14 ft. dist., previously described.
1,500.0	Cor. No. 1, and place of beginning.
MOUNT JACKSON #1 LODE	
	Beginning at Cor. No. 1 of the MOUNT JACKSON #1 lode, identical with Cor. No. 4 of the MT. JACKSON #2 lode of this survey; from which
	The cor. of secs. 5, 6, 7 and 8, T. 6 S., R. 22 E., G.&S.R.B.&M., bear S. 41°47'18" E., 1,435.12 ft. dist., previously described.
	Thence S. 51°43' W.
50	Center of dry wash, 20 ft. wide & 5 ft. deep, course North.
216	Center of mine road, bears N. 14° W. and S. 14° E.
275	Northeast edge of mine cut, bears N. 38° 17' W., and S. 38°17' E.
295	Southwest edge of mine cut, bears N. 38° 17' W. and S. 38°17' E.
300.0	Lode line and S.E.E.C. monument, previously described; discovery point bears N. 38°17' W., 672.54 ft. dist.
600.0	Cor. No. 2, identical with Cor. No. 3 of MT. JACKSON #2 lode of this survey, previously described.
	Thence N. 38°17' W.
328	Center of wash, course N. 35° E.
523	Crest of ridge, course N. 45° E.
949	Center of large gulch, dry wash, 30 ft. wide, course N. 65° E.
1,500.0	Cor. No. 3
	Set a 3/4 in. Galv. pipe, 36 ins. long, 14 ins. in ground to bedrock, with concrete around base, surrounded by a

FEET	<p>mound of stone to top, with a 2 in. brass cap, mkd. M.J.1-3-4673.</p> <p style="text-align: center;">Thence N. 51°43' E.</p> <p>300.0 Lode line; discovery point bears S. 38° 17' E., 827.46 ft. dist.</p> <p>Set a 3/4 in Galv. pipe, 36 ins. long, 16 ins. in ground to bedrock, with concrete around base, surrounded by a mound of stone to top, with a 2 in. brass cap, mkd. M.J.1-N.W.E.C.M.-4673.</p> <p>600.0 Cor. No. 4.</p> <p>Set a 3/4 in. Galv. pipe, 36 ins. long, 14 ins. in ground to bedrock, with concrete around base, surrounded by a mound of stone to top, with a 2 in. brass cap, mkd. M.J.1-4-4673; from which</p> <p style="text-align: center;">The 1/4 Section Corner, between Secs. 5 and 6, T. 6 S., R. 22 E., G.&amp;S.R.B. &amp;M., bears N. 78°04' E., 1,923.38 ft. dist.</p> <p style="text-align: center;">Thence S. 38°17' E.</p> <p>557 Center of large gulch, dry wash 14 ft. wide and 5 ft. deep, course N. 40° E.</p> <p>675 Center of mine road, course N. 45° E. and S. 45° W.</p> <p>1,075 Crest of ridge, course N. 35° E.</p> <p>1,244 Center of mine road, course N. 10° W. and N. 80° W.</p> <p>1,427 Center of dry wash, 20 ft. wide and 5 ft. deep, course North.</p> <p>1,500.0 Cor. No. 1, and place of beginning.</p>						
	Survey No. 4673						
	<p style="text-align: center;">AREAS</p> <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 80%;"></th> <th style="text-align: right;">Acres</th> </tr> </thead> <tbody> <tr> <td>Total area MOUNT JACKSON #1 lode</td> <td style="text-align: right;">20.661</td> </tr> <tr> <td>Total area MT. JACKSON #2 lode</td> <td style="text-align: right;">20.634</td> </tr> </tbody> </table> <p style="text-align: center;">LOCATION</p> <p>This survey is located in the Southeast Quarter of Section 6, Northeast Quarter of Section 7, and Northwest Quarter of Section 8, T. 6 S., R. 22 E., G. &amp; S.R.B. &amp;M.</p> <p>The survey of the MOUNT JACKSON #1 and MT. JACKSON #2 lodes is identical with the respective location as marked on the</p>		Acres	Total area MOUNT JACKSON #1 lode	20.661	Total area MT. JACKSON #2 lode	20.634
	Acres						
Total area MOUNT JACKSON #1 lode	20.661						
Total area MT. JACKSON #2 lode	20.634						

(This form bound on left side)

FEET	
	ground.
	EXPENDITURES
	The improvements and the value of the labor and improvements made upon or for the benefit of each of the lode locations embraced in said mining claim by the claimant or their grantors are as follows:
No. 1	The discovery point of the MOUNT JACKSON #1 lode is on the lode line 672.54 feet from a point on line 1-2, and 300 feet from Cor. No. 1.
	Value,       None
No. 2	The discovery cut of the MOUNT JACKSON #1 lode, the Northwest end of which is on the lode line, 705.5 ft. from a point on line 1-2, 300 ft. from Cor. No. 1, 6 ft. wide, runs S. 38°17' E. for 40 ft. to a 12 ft. face, thence rises and runs S. 38°17' E. 16 feet to a 5 ft. face.
	Value of cut & trench,       \$70.00
No. 3	A road, the centerline of which intersects line 4-1 675 feet from Cor. No. 4 of the MOUNT JACKSON #1 lode, runs S. 45° W. 300 feet to the cut described in No. 2 preceding.
	Value,       \$100.00
No. 1	The discovery point of the MT. JACKSON #2 lode is on the lode line 111.67 feet from a point on line 3-4, 300 ft. from Cor. No. 3.
	Value,       None
No. 2	The discovery cut, the face of which bears S. 28°05' W. 297.6 feet from Cor. No. 4 of the MT. JACKSON #2 lode, 5 ft. wide running East 25 feet to end. Face 7 ft. high.
	Value,       \$50.00
	An interest in a common improvement described as follows:
	A cut, the end of which lying in MT. JACKSON #2 lode bears S. 34°12' W. 298.9 ft. from Cor. No. 4, 20 feet wide runs N. 38°17' W. 170 feet to a 20 foot high by 15 foot wide portal in a 30 ft. face; thence N. 38°17' W. 15 feet to a 5' x 5' winze timbered with stope overhead. A road leads from the end of the cut Northwesterly across both claims and is the only means of vehicular access to the cut.



FEET													
	<p>Value of cut, winze and stope, and road, \$2,000.00 Value of one-half interest, \$1,000.00</p> <p>This improvement is in course of construction for the development of the two lodes of this survey, which are contiguous lode claims owned in common within range of said cut.</p> <p>Five hundred dollars or over has been expended in this improvement in such a manner as tends to the development of each lode of this survey subsequent to its location and to the time since which common ownership and contiguity have prevailed; therefore an undivided one-half interest in its value is hereby credited to each of said lodes.</p> <p>No portion of or interest in this improvement has been credited heretofore as patent expenditure to any lode claim.</p> <p style="text-align: center;">OTHER IMPROVEMENTS</p> <p>An unfinished building 8.4 by 9.6 one story, the center of which bears S. 38° 28' W. 343.7 feet from Cor. No. 4 of MT. JACKSON #2 lode. Wood construction floor framing, walls, and roof. No sheathing.</p> <p style="text-align: center;">Claimant herein</p>												
	FIELD ASSISTANTS												
	<table border="0" style="width: 100%;"> <thead> <tr> <th style="text-align: left;">Name</th> <th style="text-align: left;">Capacity</th> </tr> </thead> <tbody> <tr> <td>Dennis H. Brady</td> <td>Transitman</td> </tr> <tr> <td>J. W. Kent Rountree</td> <td>Transitman</td> </tr> <tr> <td>David B. Hall</td> <td>Chainman</td> </tr> <tr> <td>James L. Goode</td> <td>Chainman</td> </tr> <tr> <td>Lyman D. Hagan</td> <td>Chainman</td> </tr> </tbody> </table>	Name	Capacity	Dennis H. Brady	Transitman	J. W. Kent Rountree	Transitman	David B. Hall	Chainman	James L. Goode	Chainman	Lyman D. Hagan	Chainman
Name	Capacity												
Dennis H. Brady	Transitman												
J. W. Kent Rountree	Transitman												
David B. Hall	Chainman												
James L. Goode	Chainman												
Lyman D. Hagan	Chainman												

FEET

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT


CERTIFICATE OF SURVEYOR

Name of Mineral Surveyor	Date
Robert N. Hermon	4/12/69

I HEREBY CERTIFY That in pursuance of an order received from the Bureau of Land Management, at Phoenix, Arizona, dated September 24, 1968, I have carefully executed the survey of the claim of John C., Freddy A., & Charles R. Rhodes, known as the (lode, placer, or mill site) MOUNT JACKSON #1 and MT. JACKSON #2 lodes, situated in Sections 6, 7 and 8, Township 6 S., Range 22 E., Gila & Salt River Base and Meridian, in the State of Arizona.

This survey, designated as number 4673, has been executed by me and under my direction and has been made in strict conformity with said order, the Manual of Instructions for the Survey of Public Lands of the United States, and in the specific manner described in the foregoing field notes.

I FURTHER CERTIFY That the labor expended and improvements made upon and for the benefit of the (lode or placer) lode location(s) embraced in the said mining claim by claimant(s) or their grantors are fully stated in my report. The character, extent, location, and itemized value are specified in full detail. No portion of, or interest in, said labor and improvements so credited to this claim has been included in the estimate of expenditures upon any other claim.


3300 S. Mill Ave., Tempe, Ariz. (Location) 85281	 (Signature of Mineral Surveyor)
---	---

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT

Office
Arizona State Office
Location
Phoenix, Arizona
Date
July 30, 1969

The foregoing field notes of mineral survey number 4673, in Sections 6, 7 and 8, Township 6 S., Range 22 E., Gila and Salt River Meridian, in the State of Arizona, executed by Robert N. Hermon, Mineral Surveyor, under order dated September 24, 1968, having been critically examined and the necessary corrections made prior to their certification by the surveyor, the field notes and the survey therein described are hereby approved.

 Fred J. Weller (Authorized Signature)	State Director (Title)
---	---------------------------

CERTIFICATE OF TRANSCRIPT

~~I CERTIFY That the foregoing transcript of field notes of the above described mineral survey number is a true copy of the original field notes.~~

<del>(Authorized Signature)</del>	<del>(Title)</del>
-----------------------------------	--------------------

Title 18, U. S. C. section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious, or fraudulent statements or representations as to any matter within its jurisdiction.

STATE OF NEW YORK  
IN SENATE  
January 11, 1906

REPORT OF THE  
COMMISSIONERS OF THE LAND OFFICE  
IN RESPONSE TO A RESOLUTION PASSED BY THE SENATE  
ON JANUARY 11, 1906

ALBANY: JAMES BROWN PUBLISHER, 1906.

THE STATE OF NEW YORK  
OFFICE OF THE COMMISSIONERS OF THE LAND OFFICE  
ALBANY, N. Y.

*Handwritten signature*

ALBANY: JAMES BROWN PUBLISHER, 1906.