

Form 3400-11  
(September 1967)  
(formerly 4-683)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

Mineral Survey number	4692
State	Arizona
Land District	Arizona

FIELD NOTES

Of the Survey of the Mining Claim of *(name and address of Claimant)*

Inspiration Consolidated Copper Company  
c/o G. Henry Ladendorff, Attorney at Law  
Suite 716 Arizona Bank Building  
Phoenix, Arizona 85003

Known as the *(name of group, if any)*

CLAY GROUP

CONSISTING OF LOCATIONS NAMED AND LOCATED AS FOLLOWS

NAME OF LOCATION	DATE	
	LOCATED	AMENDED
CLAY No. 5	4/8/65	2/24/71
CLAY 16	1/26/67	2/24/71

Mining district			County	
Globe			Gila	
Sections	Township	Range	Meridian	Survey under order dated
2 and 3	1 South	14 East	Gila & Salt River	June 21, 1971
Survey commenced		Survey completed		Name of Mineral Surveyor
Dec. 21, 1971		Jan. 3, 1972		Travis L. Gant

May 1864  
May 1864

FEET

This survey was made with a W. & L. E. Gurley transit, No. 57289, equipped with horizontal limb  $6\frac{1}{2}$  ins. diam., having two double opposite verniers, and a full vertical circle 5 ins. diam., having one double vernier; the horizontal verniers read to 30 secs. of arc; the vertical vernier reads to one minute of arc. This instrument was used in all-purpose taping and alignment procedures where great distances were not involved. Distances greater than 500 feet were measured in many cases using electronic distance measuring equipment, i.e., the Hewlett-Packard Model 3800 Distance Meter, Ser. No. 0987 A 00472, having a range of 10,000 feet and an absolute accuracy of 0.01 feet plus the distance measured divided by 100,000 in the normal operating temperature range. In all instances wherein the distance meter was used, vertical angles were measured with a Kern theodolite, Model DKM2 AE, Ser. No. 145997, with microscopic angle-reading capabilities enabling the instrument-man to read angles, either horizontal or vertical, to 1 sec. of arc. All three of these instruments were in good condition at the time of the survey and all adjustments were in good order.

All azimuths in this record were determined by the method of deflection angles referred to the meridian determined by the following observation:

December 23, 1971, at Cor. No. 3 of the CLAY 16 lode, in latitude  $33^{\circ} 22' 13''$  N. and longitude  $110^{\circ} 54' 53''$  W., I make a series of six altitude observations upon the sun for azimuth at approximately equal time intervals, three each with the theodolite telescope in direct and reversed positions, observing opposite limbs of the sun, and reading the horizontal angles from a reference point approximately 1500 feet westerly clockwise to the sun.

Mean time of observation, 105th  
meridian, standard time = 10:27 a.m.

Declination of sun at mean  
time of observation =  $23^{\circ} 26' 19''$  S.

Mean observed vertical angle  
to sun's center, corrected for  
refraction and parallax =  $27^{\circ} 50' 32''$

Mean horizontal angle from  
reference point to sun's center,  
turned clockwise and to the  
right to sun's center =  $242^{\circ} 27' 25''$

True bearing to reference  
point = S.  $89^{\circ} 59' 00''$  W.

FEET

The lines were measured with either a Lufkin steel tape or with the aforementioned electronic distance meter. The tape was 500 feet in length, graduated every foot for 500 feet, with an added foot on the zero end graduated in tenths and hundredths; the tape was compared with a standard 100.00 foot tape at the time of the beginning of the survey and found to be correct. The distance meter was compared with a taped course, 1200 feet in length, measured as a base-line with a standard 100.00 tape, and found to be precise and accurate.

All lines and connections of this survey were run by direct methods.

The magnetic declination observed at each corner of the survey gave a uniform value of 13° 30' E.

Note concerning monumentation: With the exception of those corners which were not monumented for reasons given in each case, I have set iron posts at each corner of each lode claim comprising this survey. Each iron post consists of a 3/4-inch nominal inside diam. galvanized water pipe having a 1 ins. exterior diam.; each pipe has been placed in the ground in a foundation consisting of not less than 1/2 cu. ft. of high early strength portland cement concrete mixed at the site. Brass caps have been securely set into the tops of the iron posts and marked as described, using 1/8-in. steel dies for stamping. Alongside every corner monument I have erected a rock monument having a base two feet minimum diam., and a height of not less than two feet.

---

SURVEY NO. 4692

---

CLAY No. 5 Lode

At Cor. No. 1 of the CLAY No. 5 lode, established on line 2-3 Sur. No. 4706 INSPIRATION MILL SITE NO. IL 108, and identical with witness Cor. No. 2 Sur. No. 4706 INSPIRATION MILL SITE NO. IL 108.

To the surface of the existing 2 ins. diam brass cap witness corner monument described in the official record of Sur. No. 4706, I add the following: CLAY 5-1-4692; from which

The standard 1/4 sec. cor. of sec. 34, T. 1 N., R. 14 E., G. & S. R. M., bears N. 30° 43' 16" E., 777.43 ft. dist., an iron post, 2 ins. diam., surrounded by a mound of stone raised to base of brass cap, marked as described in the official record.

FEET	
	<p>Cor. No. 2 Sur. No. 4706 INSPIRATION MILL SITE NO. IL 108 bears EAST, 136.25 ft. dist.</p> <p>Cor. No. 4, Sur. No. 4698 CROW No. 1 lode, identical with Cor. No. 4 Sur. No. 4698 SCHULZA'S lode, bears S. 57° 55' 19" E., 594.21 ft. dist.</p> <p>Thence S. 58° 34' 36" E.</p>
52	Centerline of haul road, 30 ft. wide, curved northeasterly and southwesterly.
594.06	Intersect lines 4-1 Sur. No. 4698 CROW No. 1 and SCHULZA'S lodes at a point from which Cors. Nos. 4 bear S. 30° 29' 50" W., 6.79 ft. dist.
909	Center of local drainage, 10 ft. wide, course N. 75° E.
1,498.59	Cor. No. 2, on line 1-2 of the CLAY 16 lode of this survey.
	<p>Set an iron post, 2 ft. long, 1 ins. diam., 16 ins. in the ground, with brass cap mkd. CLAY 5-2-4692; from which</p> <p>Cor. No. 2 Sur. No. 4706 INSPIRATION MILL SITE NO. IL 200 bears N. 74° 39' 15" W., 503.80 ft. dist.</p> <p>Thence WEST</p>
10.87	Intersect line 3-4 Sur. No. 4698 SCHULZA'S lode at a point from which Cor. No. 4, identical with Cor. No. 4 Sur. No. 4698 CROW No. 1 lode, bears N. 58° 38' 56" W., 895.15 ft. dist.
485.84	Intersect line 2-3 Sur. No. 4706 INSPIRATION MILL SITE NO. IL 200 at a point from which Cor. No. 2 bears NORTH, 133.33 ft. dist.
574	Lode line; discovery point bears N. 58° 34' 36" W., 290 ft. dist.
996.44	Intersect Cor. No. 1 of the CLAY 16 lode of this survey.
1,143.88	Intersect lines 4-1 Sur. No. 4706 INSPIRATION MILL SITES NOS. IL 200 and IL 113 at a point from which Cors. Nos. 1, identical with Cor. No. 1 Sur. No. 4706 INSPIRATION MILL SITE NO. IL 111, bear N. 0° 05' 49" E., 128.94 ft. dist.

FEET	
1,148.00	<p>Cor. No. 3.</p> <p>Set an iron post, 2 ft. long 1 ins. diam., 17 ins. in the ground, with brass cap mkd. CLAY 5-3-4692; from which</p> <p>Cors. Nos. 1 Sur. No. 4706 INSPIRATION MILL SITES NOs IL 200, IL 113, and IL 111 bear N. 1° 55' 30" E., 129.01 ft. dist.</p> <p>Thence N. 58° 34' 36" W.</p>
249.33	<p>Intersect lines 1-2 Sur. No. 4706 INSPIRATION MILL SITES NOs. IL 113 and IL 111 at a point from which Cors. Nos. 1, identical with Cor. No. 1 Sur. No. 4706 INSPIRATION MILL SITE NO. IL 200, bear S. 89° 43' 22" E., 217.10 ft. dist.</p>
765.07	<p>Intersect lines 2-3 Sur. No. 4706 INSPIRATION MILL SITES NOs. IL 111 and IL 110 at a point from which Cors. Nos. 3, identical with Cor. No. 3 Sur. No. 4706 INSPIRATION MILL SITE NO. IL 109, bear N. 0° 00' 53" E., 62.35 ft. dist.</p>
884.11	<p>Intersect lines 3-4 Sur. No. 4706 INSPIRATION MILL SITES NOs. IL 110 and IL 109 at a point from which Cors. Nos. 3, identical with Cor. No. 3 Sur. No. 4706 INSPIRATION MILL SITE NO. IL 111, bear N. 89° 50' 02" E., 101.59 ft. dist.</p>
1,498.59	<p>Cor. No. 4.</p> <p>Set an iron post, 2 ft. long, 1 ins. diam., 18 ins. in the ground, with brass cap mkd. CLAY 5-4-4692; from which</p> <p>Cors. Nos. 1 Sur. No. 4706 INSPIRATION MILL SITES NOs. IL 98, IL 100, IL 107, and IL 109 bear N. 77° 57' 30" W., 33.65 ft. dist.</p> <p>Cors. Nos. 2 Sur. No. 4706 INSPIRATION MILL SITES NOs. IL 107 and IL 109, on line 3-4 Sur. No. 4706 INSPIRATION MILL SITE NO. IL 108, bear N. 89° 10' 42" E., 626.10 ft. dist.</p> <p>Cors. Nos. 3 Sur. No. 4706 INSPIRATION MILL SITES NOs. IL 109, IL 110, and IL 111 bear S. 62° 55' 05" E., 703.04 ft. dist.</p> <p>Thence EAST</p>
574	<p>Lode line; discovery point bears S. 58° 34' 36" E., 1208.59 ft. dist.</p>
626.04	<p>Intersect Cor. No. 3 Sur. No. 4706 INSPIRATION</p>

FEET	
	MILL SITE NO. IL 108 which had been established on line 2-3 Sur. No. 4706 INSPIRATION MILL SITE NO. IL 109 at a point from which Cor. No. 2, identical with Cor. No. 2 INSPIRATION MILL SITE NO. IL 107, bears N. 0° 00' 53" E., 8.98 ft. dist.
699	Center of local drainage, 10 ft. wide, course S. 15° E.
894	Centerline of haul road, 30 ft. wide, bears N. 35° W. and S. 35° E.
1,145.80	Intersect line 3-4 Sur. No. 4698 CROW No. 1 lode at a point from which Cor. No. 4, identical with Cor. No. 4 Sur. No. 4698 SCHULZA'S lode, bears S. 58° 02' 03" E., 596.08 ft. dist.
1,148.00	Cor. No. 1, and place of beginning.
CLAY 16 Lode	
At Cor. No. 1 of the CLAY 16 lode, on line 2-3 of the CLAY No. 5 lode of this survey.	
Set an iron post, 2 ft. long, 1 ins. diam., 17 ins. in the ground, with brass cap mkd. CLAY 16-1-4692; from which	
The standard $\frac{1}{4}$ sec. cor. of sec. 34, T. 1 N., R. 14 E., G. & S. R. M., bears N. 4° 31' 39" E., 1454.17 ft. dist., previously described.	
Cors. Nos. 3 Sur. No. 4706 INSPIRATION MILL SITES NOs. IL 200 and IL 118 bear S. 69° 01' 07" E., 546.86 ft. dist.	
Thence EAST	
510.60	Intersect line 2-3 Sur. No. 4706 INSPIRATION MILL SITE NO. IL 200 at a point from which Cor. No. 3, identical with Cor. No. 3 Sur. No. 4706, INSPIRATION MILL SITE NO. IL 118, bears SOUTH, 195.81 ft. dist.
985.57	Intersect line 3-4 Sur. No. 4698 SCHULZA'S lode at a point from which Cor. No. 3 bears S. 58° 38' 56" E., 600.71 ft. dist.
996.44	Intersect Cor. No. 2 of the CLAY No. 5 lode of this survey.
1,030	Center of Needle Creek, 20 ft. wide, course S. 55° E.
1,110	Centerline of entrance road to Ox-Hide Mine, 25 ft. wide, bears N. 30° W. and S. 50° E; another leg of entrance road bears South.

FEET	
1,498.58	<p>The true point for Cor. No. 2.</p> <p>This corner falls near the centerline of U. S. Highway 60 where a permanent monument cannot be established; centerline of highway bears N. 57° E. and S. 57° W.</p> <p style="text-align: center;">Thence SOUTH</p>
70	Road, bears N. 55° E. and S. 55° W.
115.27	<p>A point selected for witness Cor. No. 2.</p> <p>Set an iron post, 2 ft. long, 1 ins. diam., 16 ins. in the ground, with brass cap mkd. WC CLAY 16-2-4692.</p>
212	Center of Bloody Tanks Wash, 25 ft. wide, course N. 25° E.
300	Lode line; discovery point bears WEST, 898.58 ft. dist.
312.54	Intersect Cor. No. 3 Sur. No. 4698 SCHULZA'S lode.
590.06	<p>Intersect the south bdy. Lot 13 of Sec. 2, T. 1 S., R. 14 E., said bdy. being also a portion of the northerly bdy. of the Minnie Schulze Homestead, Pat No. 458733, at a point from which the S-S-N 1/256 sec. cor. of secs. 2 and 3, T. 1 S., R. 14 E., bears N. 89° 42' 23" W., 301.79 ft. dist.</p>
597.56	<p>Cor. No. 3.</p> <p>Set an iron post, 2 ft. long, 1 ins. diam., 17 ins. in the ground, with brass cap mkd. CLAY 16-3-4692; from which</p> <p style="padding-left: 40px;">The S-S-N 1/256 sec. cor. of secs. 2 and 3 bears N. 88° 16' 55" W., 301.93 ft. dist., an iron post, 2 ins. diam., with brass cap mkd. as described in the official record.</p> <p style="padding-left: 40px;">Cor. 3, Lot 11, sec. 2, bears N. 85° 46' E., 94.98 ft. dist., an iron post 2 ins. diam., with brass cap mkd. as described in the official record.</p> <p style="text-align: center;">Thence S. 89° 59' 00" W.</p>
288	Center of Bloody Tanks Wash, 25 ft. wide, course N. 15° E.
343	Road; bears N. 30° E. and S. 30° W.



FEET	
787	Centerline of U.S. Highway 60, width 40 ft., bears N. 57° E. and S. 57° W.
987.98	Intersect line 2-3 Sur. No. 4706 INSPIRATION MILL SITE NO. IL 119 at a point from which Cors. Nos. 2 Sur. No. 4706 INSPIRATION MILL SITES NOs. IL 119 and IL 118 bear NORTH, 72.67 ft. dist.
1,298.76	Intersect the westerly boundary of the Minnie Schulze Homestead, Pat. No. 458733, at a point from which the NW. cor. thereof bears N. 0° 08' 15" E., 17.31 ft. dist.
1,498.58	Cor. No. 4.  Set an iron post, 2 ft. long, 1 ins. diam., 17 ins. in the ground, with brass cap mkd. CLAY 16-4-4692; from which  The NW. cor. of the Minnie Schulze Homestead, Pat. No. 458733, bears N. 85° 02' E., 200.61 ft. dist.  Cors. Nos. 2 Sur. No. 4706 INSPIRATION MILL SITES. NOs. IL 119 and IL 118 bear N. 81° 53' E., 515.77 ft. dist.  Thence NORTH
69.89	Intersect lines 1-2 Sur. No. 4706 INSPIRATION MILL SITES NOs. IL 119 and IL 118 at a point from which Cors. Nos. 2 bears N. 89° 40' 17" E., 510.61 ft. dist.
298	Lode line; discovery point bears EAST, 600 ft. dist.
398.89	Intersect lines 3-4 Sur. No. 4706 INSPIRATION MILL SITES NOs. IL 118 and IL 200 at a point from which Cors. Nos. 3 bear N. 89° 37' 48" E., 510.61 ft. dist.
598.00	Cor. No. 1, and place of beginning.
	AREAS
	acres
	Total area, CLAY No. 5 lode 20.591
	Area in conflict with --
	Sur. No. 4698 CROW No. 1 lode 0.054
	Sur. No. 4698 SCHULZA'S lode 0.129
	Sur. No. 4706 INSPIRATION MILL SITE NO. IL 109 2.675
	Sur. No. 4706 INSPIRATION MILL SITE NO. IL 110 0.073
	Sur. No. 4706 INSPIRATION MILL SITE NO. IL 111 3.619
	Sur. No. 4706 INSPIRATION MILL SITE NO. IL 113 0.327
	Sur. No. 4706 INSPIRATION MILL SITE NO. IL 200 1.987
	Total area, CLAY 16 lode 20.565

(This form bound on left side)

FEET

acres

FEET	acres
Area in conflict with --	
Pat. No. 458733 Schulze Homestead	0.360
Sur. No. 4698 SCHULZA'S lode	1.840
Sur. No. 4706 INSPIRATION MILL SITE NO. IL 119	0.835
Sur. No. 4706 INSPIRATION MILL SITE NO. IL 119, exclusive of its conflict with:	
(1) Pat. No. 458733 Schulze Homestead	0.721
Sur. No. 4706 INSPIRATION MILL SITE NO. IL 118	3.859
Sur. No. 4706 INSPIRATION MILL SITE NO. IL 200	2.315

## LOCATION

This survey is located in the NW $\frac{1}{4}$  sec. 2 and in the NE $\frac{1}{4}$  sec. 3, T. 1 S., R. 14 E., of the Gila and Salt River Meridian, Gila County, Arizona.

The survey of the two (2) lode claims comprising this order for mineral survey and described herein is identical with the respective locations or amended locations as marked on the ground.

## EXPENDITURES

The improvements and the value of the labor and improvements made upon or for the benefit of each of the lode locations embraced in said mining claim by the claimant are as follows:

- |        |   |
|--------|---|
| No. 1. | The discovery point of the CLAY No. 5 lode is on the lode line 290 ft. from a point on line 2-3, 574 ft. from Cor. No. 2.<br>Value, none. |
| No. 2. | A diamond drill hole bears N. 70° 46' W., 452 ft. from Cor. No. 2; 3 $\frac{1}{2}$ ins. diam., 175 ft. depth.<br>Value, \$1,575.00.       |
| No. 1. | The discovery point of the CLAY 16 lode is on the lode line 600 ft. from a point on line 4-1, 298 ft. from Cor. No. 4.<br>Value, none.    |
| No. 2. | A churn drill hole bears S. 84° 01' E., 577 ft. from Cor. No. 1; 12 ins. diam., 175 ft. depth.<br>Value, \$1,225.00                       |

FEET

A graded and surfaced entrance "Y" has been constructed in the eastern end of the CLAY 16 lode, and a portion of a 30 foot wide haul road requiring extensive removal of rock for the establishment of a roadbed suitable for ore trucks has been constructed in the northerly portion of the CLAY No. 5 lode.

Value of constructed roads, \$4,200.00

Value of one-half interest, \$2,100.00

This improvement is for the development of the two lodes of this survey and was made subsequent to the location of each lode and to the time since which common ownership and contiguity have prevailed; therefore an undivided one-half interest in its value is hereby credited to each of said lodes of the common group.

OTHER CORNER DESCRIPTIONS AND SUPPLEMENTAL DATA

Sur. No. 4698 CROW No. 1 and SCHULZA'S lodes: All corners and witness corners were found firmly set and properly marked, having been set by this mineral surveyor in the year 1971 and in the early part of the year 1972. since no discrepancies are known to exist between Sur. No. 4698 and subject mineral survey, all lines are correct as approved.

Sur. No. 4706 INSPIRATION MILL SITES NOS. IL 107, IL 108, IL 109, IL 110, IL 111, IL 113, IL 118, IL 119, and IL 200: All corners and witness corners were found firmly set and properly marked, having been set by this mineral surveyor in the year 1971. Since no discrepancies are known to exist between Sur. No. 4706 and subject mineral survey, all lines are correct as approved.

The CLAY 16 lode of this survey conflicts in part with Pat. No. 458733, a homestead grant to Minnie Schulze under Act of Congress of May 20, 1862, (patent dated February 18, 1915), and currently owned, both surface and mineral rights, by private individuals. The portion of this homestead situate in sec. 2, T. 1 S., R. 14 E., G. & S. R. M., was the subject of a cadastral survey by the B.L.M. in the year 1967, at which time some of the corners of the homestead were re-monumented, but only those corners within the boundaries of said sec. 2, no recent B.L.M. work having been done in sec. 3. However, I am in possession of the records of a survey of the entire Schulze Homestead made by Oscar T. Smith, Ariz. Land Surveyor - Regis. No. 2648, and U.S. Mineral Surveyor. Mr. Smith made this survey in 1948 while an

FEET

employee of Kenneth W. Hammes, Ariz. Civil Engineer Regis. No. 1038, and also made the survey plat which is on file in the Gila County Courthouse as Official Map No. 96, Gila County Records. Iron drill-steel pins were set by Mr. Smith at several positions along the borders of the homestead; however, he did not set a monument at the SW. corner in sec. 3. The position of the true point for said SW. cor. was calculated from recorded survey data, using found drill-steel monuments as direct evidence for the establishment of bearings for the southerly and westerly boundaries of the homestead. The NW. corner is a drill steel projecting 1 ins. above ground with a mound of stones alongside. The direction for the bearing of the northerly boundary of that part of the homestead situate in sec. 3 was determined by connecting said NW. corner with the S-S-N 1/256 sec. cor. of secs. 2 and 3, mkd. by an iron post with brass cap marked as described in the official record of the 1967 cadastral survey by the B.L.M. The westerly boundary of the Schulze Homestead in sec. 3 was found to bear N. 0° 08' 15" E., 986.08 ft. dist., instead of N. 0° 09' 10" E., 985.30 ft. dist., as recorded in the aforementioned Hammes survey plat. The northerly boundary of the Schulze Homestead in sec. 3 was found to bear S. 89° 32' 50" E., 996.96 ft. dist., instead of S. 89° 35' 20" E., no distance given, as recorded in said survey plat.

The line between the S-S-N 1/256 sec. cor. of secs. 2 and 3, T. 1 S., R. 14 E., and the brass-capped iron post marking Cor. 3. Lot 11, sec. 2, was found to be S. 89° 42' 23" E., 396.52 ft. dist., instead of S. 89° 38' E., 396.99 ft. dist., as approved.

The line connecting the S-S-N 1/256 sec. cor. of secs. 2 and 3, T. 1 S., R. 14 E., with the brass-capped iron post marking the closing cor. of secs. 2 and 3, T. 1 S., R. 14 E., was found to bear N. 0° 37' 38" W., 2040.13 ft. dist., instead of N. 0° 42' W., 2040.72 ft. dist., as approved.

## FIELD ASSISTANTS

Name	Capacity
Loren E. Bunney	Instrumentman
Joseph E. Cummings	Chainman

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

CERTIFICATE OF SURVEYOR

Name of Mineral Surveyor Travis L. Gant	Date May 3, 1972
--	---------------------

I HEREBY CERTIFY That in pursuance of an order received from the Bureau of Land Management, at Phoenix, Arizona, dated June 21, 1971, I have carefully executed the survey of the claim of Inspiration Consolidated Copper Company, known as the (lode, placer, or mill site) CLAY No. 5 lode, and CLAY 16 lode, situated in Secs. 2 and 3, Township 1 South, Range 14 East, Gila & Salt River Meridian, in the State of Arizona.

This survey, designated as number 4692, has been executed by me and under my direction and has been made in strict conformity with said order, the Manual of Instructions for the Survey of Public Lands of the United States, and in specific manner described in the foregoing field notes.

I FURTHER CERTIFY That the labor expended and improvements made upon and for the benefit of the (lode or placer) location(s) embraced in the said mining claim by claimant(s) or its grantors are fully stated in my report. The character, extent, location, and itemized value are specified in full detail. No portion of, or interest in, said labor and improvements so credited to this claim has been included in the estimate of expenditures upon any other claim.

Globe, Arizona (Location)	<i>Travis L. Gant</i> (Signature of Mineral Surveyor)
------------------------------	--

CERTIFICATE OF APPROVAL

Office Arizona State Office
Location Phoenix, Arizona
Date March 5, 1973

The foregoing field notes of mineral survey number 4692, in Section 2 and 3, Range 14 E., Gila and Salt River Meridian, in the State of Arizona,  surveyed  unsurveyed Township 1 S., executed by Travis L. Gant, Mineral Surveyor, under order dated June 21, 1971, having been critically examined and the necessary corrections made prior to their certification by the surveyor, the field notes and the survey therein described are hereby approved.

<i>Edward J. Hoffman</i> (Authorized Signature)	Acting State Director (Title)
Edward J. Hoffman	

CERTIFICATE OF TRANSCRIPT

I HEREBY CERTIFY That the foregoing transcript of field notes of the above-described mineral survey number is a true copy of the original field notes.

(Authorized Signature)	(Title)
------------------------	---------

Title 18, U.S.C. section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious, or fraudulent statements or representations as to any matter within its jurisdiction.

