

Form 3400-11  
(September 1967)  
(formerly 4-683)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

RECEIVED  
B.L.M. LAND OFFICE  
MAR 28 1973  
10:00 A.M.  
PHOENIX, ARIZONA

Mineral Survey number	4721
State	Arizona
Land District	Arizona

FIELD NOTES

Of the Survey of the Mining Claim of *(name and address of Claimant)*  
 Harold F. & Tillie Lou Carpenter/ c/o G. Henry Ladendorff, Atty. at Law  
 William W. & Loraine R. Sorsen/ Suite 716, Arizona Bank Bldg.  
 Hearold & Charleen Elmer / Phoenix, Arizona 85003  
 Harold D. & Doris H. Maryott/

Known as the *(name of group, if any)*

Carpenter Group

CONSISTING OF LOCATIONS NAMED AND LOCATED AS FOLLOWS

NAME OF LOCATION	DATE	
	LOCATED	AMENDED
Blowout No. 1	2/25/56	
Blowout No. 2	2/25/56	
Blowout No. 3	2/25/56	
Blowout No. 4	2/25/56	
Blowout No. 5	2/25/56	
Blowout No. 6	2/25/56	
FOX No. 1	1/15/56	8/11/64
FOX No. 2	1/15/56	8/11/64
FOX No. 8	1/18/56	8/11/64
FOX No. 9	1/18/56	8/11/64
Pat # 4	4/20/56	
Pat # 5	4/20/56	
Shasta # I	4/20/56	
Shasta # 2	4/20/56	

Mining district			County	
Lone Star			Graham	
Section s	Township	Range	Meridian	Survey under order dated
25 & 26	6 South	27 East	Gila & Salt River	April 5, 1972
Survey commenced		Survey completed	Name of Mineral Surveyor	
July 12, 1972		July 16, 1972	Travis L. Gant	

...

...

FEET

This survey was made with a W. & L. E. Gurley transit, No. 57289, equipped with horizontal limb  $6\frac{1}{2}$  ins. diam., having two double opposite verniers, and a full vertical circle 5 ins. diam., having one double vernier; the horizontal verniers read to 30 secs. of arc; the vertical vernier reads to one minute of arc. This instrument was used in all-purpose taping and alignment procedures where great distances were not involved. Most distances greater than 500 feet were measured with electronic distance measuring equipment, i.e., the Hewlett-Packard Model 3800 Distance Meter, Ser. No. 0987 A 00472, having a range of 10,000 feet and an absolute accuracy of 0.01 feet plus the distance measured divided by 100,000 in the normal operating temperature range. In all instances wherein the distance meter was used, vertical angles were measured with a Kern theodolite, Model DKM 2 AE, Ser. No. 145997, with microscopic angle-reading capabilities enabling the instrument man to read angles, either horizontal or vertical, to 1 sec. of arc. All three of these instruments were in good condition at the time of the survey and all adjustments were in good order.

All azimuths in this record were determined by the method of deflection angles referred to the meridian determined by the following observation:

July 14, 1972, at Cor. No. 4 of the Blowout No. 5 lode, in latitude  $32^{\circ} 52' 45''$  N., and longitude  $109^{\circ} 32' 41''$  W., I make a series of six altitude observations upon the sun for azimuth at approximately equal time intervals, three each with the theodolite telescope in direct and reversed positions, observing opposite limbs of the sun, and reading the horizontal angles from a reference point approximately 1200 feet easterly clockwise to the sun.

Mean time of observation, 105th  
meridian, standard time = 4:16 p.m.

Declination of sun at mean  
time of observation =  $21^{\circ} 33' 15''$  N.

Mean observed vertical angle  
to sun's center, corrected for  
refraction and parallax =  $38^{\circ} 24' 07''$

Mean horizontal angle from  
reference point to sun's center,  
turned clockwise and to the  
right to sun's center =  $183^{\circ} 07' 36''$

True bearing to reference  
point = N.  $89^{\circ} 30' 00''$  E.

FEET

The lines were measured with either a Lufkin steel tape or with the aforementioned electronic distance meter. The tape was 500 feet in length, graduated every foot for 500 ft., with an added foot on the zero end graduated in tenths and hundredths; the tape was compared with a standard 100.00 foot tape at the time of the beginning of the survey and found to be correct. The distance meter was compared with a taped course, 1200 feet in length, measured as a base-line with a standard 100.00 ft. tape, and found to be precise and accurate.

All lines and connections of this survey were run by direct methods.

The magnetic declination observed at each corner of the survey gave a uniform value of 13° 45' E.

Note concerning monumentation: Iron posts have been set at each corner of each lode claim comprising this survey, with the exception of those corners which were not monumented for reasons given in each case. Each iron post consists of a 3/4-inch nominal inside diam. galvanized water pipe having a 1 ins. exterior diam.; each pipe has been placed in the ground in a foundation consisting of not less than 1/2 cu. ft. of high early strength portland cement concrete mixed at the site. Brass caps have been securely attached and marked as described, using 1/8-in. steel dies for stamping. Alongside every corner monument I have erected a rock monument having a base two feet minimum diam., and a height of not less than two feet.

## SURVEY NO. 4721

## Blowout No. 1 Lode

At Cor. No. 1 of the Blowout No. 1 lode, identical with Cors. Nos. 2 of the Blowout No. 2 and Blowout No. 5 lodes and Cor. No. 1 of the Blowout No. 4 lode of this survey.

Set an iron post, 2 ft. long, 1 ins. diam., 16 ins. in the ground, with brass cap mkd. BLO 1-1, BLO 2-2, BLO 5-2, and BLO 4-1-4721; from which

FEET	
	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 25 and 26, T. 6 S., R. 27 E., G. &amp; S. R. M., bears S. <math>47^{\circ} 26' 30''</math> E., 892.34 ft. dist., an iron post, 2 ins. diam., surrounded by a mound of stone raised to base of brass cap, mkd. as described in the official record.</p> <p style="text-align: center;">Thence S. <math>89^{\circ} 30'</math> W.</p>
300	Lode line; discovery point bears N. $0^{\circ} 24' 41''$ W., 100 ft. dist.
598.12	<p>Cor. No. 2, identical with Cor. No. 2 of the Blowout No. 4 lode, and Cors. Nos. 3 of the FOX No. 2 and FOX No. 1 lodes of this survey.</p> <p>Set an iron post, 2 ft. long, 1 ins. diam., 16 ins. in the ground, with brass cap mkd. BLO 1-2, BLO 4-2, FOX 2-3, and FOX 1-3-4721.</p> <p style="text-align: center;">Thence N. <math>0^{\circ} 24' 08''</math> W.</p>
43	Road; bears S. $55^{\circ}$ W. and N. $55^{\circ}$ E.
1,495.94	<p>Cor. No. 3, identical with Cor. No. 2 of the FOX No. 1 lode of this survey.</p> <p>Set an iron post, 2 ft. long, 1 ins. diam., 17 ins. in the ground, with brass cap mkd. BLO 1-3-4721 and FOX 1-2-4721.</p> <p style="text-align: center;">Thence N. <math>89^{\circ} 30''</math> E.</p>
297.89	Lode line; discovery point bears S. $0^{\circ} 24' 41''$ E., 1395.94 ft. dist.
597.89	<p>Cor. No. 4, identical with Cor. No. 3 of the Blowout No. 2 lode of this survey.</p> <p>Set an iron post, 2 ft. long, 1 ins. diam., 16 ins. in the ground, with brass cap mkd. BLO 1-4-4721 and BLO 2-3-4721.</p> <p style="text-align: center;">Thence S. <math>0^{\circ} 24' 41''</math> E.</p>
1,495.94	Cor. No. 1, and place of beginning.
<p>Blowout No. 2 Lode</p> <p>At Cor. No. 1 of the Blowout No. 2 lode, identical with Cors. Nos. 1 of the Blowout No. 3, Blowout No. 6, and Blowout No. 5 lodes of this survey.</p>	

FEET	
	<p>Set an iron post, 2 ft. long, 1 ins. diam., 17 ins. in the ground, with brass cap mkd. BLO 2-1, BLO 3-1, BLO 6-1, and BLO 5-1-4721; from which</p> <p>The <math>\frac{1}{4}</math> sec. cor. of secs. 25 and 26 bears S. <math>5^{\circ} 33' 21''</math> E., 611.62 ft. dist., previously described.</p> <p>Thence S. <math>89^{\circ} 30'</math> W.</p>
300	Lode line; discovery point bears N. $0^{\circ} 23' 16''$ W., 100 ft. dist.
598.10	<p>Cor. No. 2, identical with Cor. No. 2 of the Blowout No. 5 lode and Cors. Nos. 1 of the Blowout No. 4 and Blowout No. 1 lodes of this survey.</p> <p>Thence N. <math>0^{\circ} 24' 41''</math> W.</p>
1,495.94	<p>Cor. No. 3, identical with Cor. No. 4 of the Blowout No. 1 lode of this survey.</p> <p>Thence N. <math>89^{\circ} 30'</math> E.</p>
298.71	Lode line; discovery point bears S. $0^{\circ} 23' 16''$ E., 1395.94 ft. dist.
598.71	<p>Cor. No. 4, identical with Cor. No. 4 of the Blowout No. 3 lode of this survey.</p> <p>Set an iron post, 2 ft. long, 1 ins. diam., 17 ins. in the ground, with brass cap mkd. BLO 2-4-4721 and BLO 3-4-4721.</p> <p>Thence S. <math>0^{\circ} 23' 16''</math> E.</p>
1,495.94	Cor. No. 1, and place of beginning.
	<p style="text-align: center;">Blowout No. 3 Lode</p> <p>Beginning at Cor. No. 1 of the Blowout No. 3 lode, identical with Cors. Nos. 1 of the Blowout No. 6, Blowout No. 5, and Blowout No. 2 lodes of this survey.</p> <p>Thence N. <math>89^{\circ} 30'</math> E.</p>
300	Lode line; discovery point bears N. $0^{\circ} 23' 16''$ W., 100 ft. dist.
394	Center of dry wash, 10 ft. wide, course S. $50^{\circ}$ W.

FEET	
598.74	<p>Cor. No. 2, identical with Cors. Nos. 1 of the FOX No. 8 and FOX No. 9 lodes, and Cor. No. 2 of the Blowout No. 6 lode of this survey.</p> <p>Set an iron post, 2 ft. long, 1 ins. diam., 18 ins. in the ground, with brass cap mkd. BLO 3-2, FOX 8-1, FOX 9-1, and BLO 6-2-4721.</p> <p>Thence No. 0° 20' 41" W.</p>
1,495.94	<p>Cor. No. 3, identical with Cor. No. 2 of the FOX No. 8 lode of this survey.</p> <p>Set an iron post, 2 ft. long, 1 ins. diam., 18 ins. in the ground, with brass cap mkd. BLO 3-3-4721 and FOX 8-2-4721.</p> <p>Thence S. 89° 30' W.</p>
266	<p>Center of dry wash, 10 ft. wide, course South.</p>
299.86	<p>Lode line; discovery point bears S. 0° 23' 16" E., 1395.94 ft. dist.</p>
599.86	<p>Cor. No. 4, identical with Cor. No. 4 of the Blowout No. 2 lode of this survey.</p> <p>Thence S. 0° 23' 16" E.</p>
1,495.94	<p>Cor. No. 1, and place of beginning.</p>
<p>Blowout No. 4 Lode</p>	
<p>Beginning at Cor. No. 1 of the Blowout No. 4 lode, identical with Cor. No. 1 of the Blowout No. 1 lode and Cors. Nos. 2 of the Blowout No. 2 and Blowout No. 5 lodes of this survey.</p>	
<p>Thence S. 89° 30' W.</p>	
300	<p>Lode line; discovery point bears S. 0° 28' 24" W., 100 ft. dist.</p>
598.12	<p>Cor. No. 2, identical with Cors. Nos. 3 of the FOX No. 2 and FOX No. 1 lodes and Cor. No. 2 of the Blowout No. 1 lode of this survey.</p> <p>Thence S. 0° 28' 48" W.</p>
60	<p>Center of dry wash, 15 ft. wide, course S. 80° E.</p>
603.41	<p>Road; bears N. 30° E. and S. 30° W.</p>

FEET	
1,421.41	Road; bears N. 80° W. and S. 80° E.
1,499.41	<p>Cor. No. 3, identical with Cor. No. 3 of the Pat # 4 lode and Cor. No. 2 of the FOX No. 2 lode of this survey.</p> <p>Set an iron post, 2 ft. long, 1 ins. diam., 18 ins. in the ground, with brass cap mkd. BLO 4-3-4721, PAT 4-3-4721, and FOX 2-2-4721.</p> <p>Thence No. 89° 30" E.</p>
183	Center of dry wash, 15 ft. wide, course S. 50° E.
298.29	Lode line; discovery point bears N. 0° 28' 24" E., 1399.40 ft. dist.
598.29	<p>Cor. No. 4, identical with Cors. Nos. 3 of the Blowout No. 5 and Pat # 5 lodes, and Cor. No. 4 of the Pat # 4 lode of this survey.</p> <p>Set an iron post, 2 ft. long, 1 ins. diam., 18 ins. in the ground, with brass cap mkd. BLO 4-4, BLO 5-3, PAT 5-3, and PAT 4-4-4721.</p> <p>Thence N. 0° 28' 24" E.</p>
290	Road; bears S. 60° W. and N. 60° E.
1,086	Road; bears S. 70° E. and N. 70° W.
1,390	Road; bears S. 85° E. and N. 85° W.
1,499.40	Cor. No. 1, and place of beginning.
	<p>Blowout No. 5 Lode</p>
	<p>Beginning at Cor. No. 1 of the Blowout No. 5 lode, identical with Cors. Nos. 1 of the Blowout No. 2, Blowout No. 3, and Blowout No. 6 lodes of this survey.</p> <p>Thence S. 89° 30' W.</p>
300	Lode line; discovery point bears S. 0° 29' 02" W., 100 ft. dist.
598.10	<p>Cor. No. 2, identical with Cors. Nos. 1 of the Blowout No. 4 and Blowout No. 1 lodes, and Cor. No. 2 of the Blowout No. 2 lode of this survey.</p> <p>Thence S. 0° 28' 24" W.</p>



FEET	
109.40	Road; bears S. 85° E. and N. 85° W.
413.40	Road; bears S. 70° E. and N. 70° W.
1,209.40	Road; bears S. 60° W. and N. 60° E.
1,499.40	Cor. No. 3, identical with Cor. No. 3 of the Pat # 5 lode, and Cors. Nos. 4 of the Pat # 4 and Blowout No. 4 lodes of this survey.
	Thence N. 89° 30' E.
297.83	Lode line; discovery point bears N. 0° 29' 02" E., 1399.41 ft. dist.
441	Center of dry wash, 12 ft. wide, course South.
597.83	The true point for Cor. No. 4, identical with Cors. Nos. 4 of the Blowout No. 6 and Pat # 5 lodes of this survey, and Cor. No. 4 Sur. No. 4719 BASALT § 16 lode.
	This corner falls on the surface of a graded access road, bears N. & S., where a permanent monument cannot be maintained. Witnessed N. 89° 30' E., 82.84 ft. dist.
	Set a temporary spike at the true point for the purpose of measuring distances and angles.
	Thence N. 0° 29' 02" E.
1,097	Road; bears S. 85° W. and N. 85° E.
1,189	Center of dry wash, 10 ft. wide, course S. 55° W.
1,272	Road; bears southwesterly and northeasterly.
1,410	Road; bears northwesterly and southeasterly.
1,499.41	Cor. No. 1, and place of beginning.
	Blowout No. 6 Lode
	Beginning at Cor. No. 1 of the Blowout No. 6 lode, identical with Cors. Nos. 1 of the Blowout No. 5, Blowout No. 2, and Blowout No. 3 lodes of this survey.
	Thence N. 89° 30' E.
300	Lode line; discovery point bears S. 0° 29' 02" W., 100 ft. dist.
394	Center of dry wash, 10 ft. wide, course S. 50° W.

(This form bound on left side)

FEET	
598.74	Cor. No. 2, identical with Cor. No. 2 of the Blowout No. 3 lode, and Cors. Nos. 1 of the FOX No. 8 and FOX No. 9 lodes of this survey.
	Thence S. 0° 29' 32" W.
434	Road; bears S. 60° W. and N. 60° E.
1,200	Road; bears N. 20° W. and S. 20° E.
1,499.41	Cor. No. 3, identical with Cor. No. 2 of the FOX No. 9 lode of this survey and Cor. No. 3 Sur. No. 4719 BASALT # 16 lode.
	To the surface of the existing brass capped pipe monument marking said Cor. No. 3 Sur. No. 4719 BASALT # 16 lode, I add the following in the proper quadrants: BLO 6-3-4721 and FOX 9-2-4721.
	Thence S. 89° 30' W.
298.52	Lode line; discovery point bears N. 0° 29' 02" E., 1399.41 ft. dist.
515.68	Witness Cor. No. 4 Sur. No. 4719 BASALT # 16 lode. This monument selected for witness Cor. No. 4, identical with Cors. Nos. 4 of the Pat # 5 and Blowout No. 5 lodes of this survey.
	To the surface of the existing brass capped pipe monument marking this witness corner No. 4 Sur. No. 4719 BASALT # 16 lode, I add the following in the proper quadrants: W C-BLO 6-4-4721, PAT 5-4-4721, and BLO 5-4-4721.
598.52	The true point for Cor. No. 4, identical with Cors. Nos. 4 of the Pat # 5 and Blowout No. 5 lodes of this survey, and Cor. No. 4 Sur. No. 4719 BASALT # 16 lode, previously described.
	Thence N. 0° 29' 02" E.
1,097	Road; bears S. 85° W. and N. 85° E.
1,189	Center of dry wash, 10 ft. wide, course S. 55° W.
1,272	Road; bears southwesterly and northeasterly.
1,410	Road; bears northwesterly and southeasterly.
1,499.41	Cor. No. 1, and place of beginning.

FEET	
	FOX No. 1 Lode
	At Cor. No. 1 of the FOX No. 1 lode, identical with Cor. No. 4 of the Shasta # 2 lode of this survey.
	Set an iron post, 2 ft. long, 1 ins. diam., 17 ins. in the ground, with brass cap mkd. FOX 1-1-4721 and SHA 2-4-4721; from which
	The $\frac{1}{4}$ sec. cor. of secs. 23 and 26, T. 6 S., R. 27 E., G. & S. R. M., bears N. $56^{\circ} 27' 44''$ W., 925.02 ft. dist.; an iron post, 2 ins. diam., surrounded by a mound of stone raised to base of brass cap, mkd. as described in the official record.
	Thence N. $89^{\circ} 30'$ E.
235	Center of dry wash, 8 ft. wide, course S. $25^{\circ}$ E.
300	Lode line; discovery point bears S. $0^{\circ} 23' 22''$ E., 1395.94 ft. dist.
598.21	Cor. No. 2, identical with Cor. No. 3 of the Blowout No. 1 lode of this survey.
	Thence S. $0^{\circ} 24' 08''$ E.
1,452.94	Road; bears S. $55^{\circ}$ W. and N. $55^{\circ}$ E.
1,495.94	Cor. No. 3, identical with Cors. Nos. 2 of the Blowout No. 1 and Blowout No. 4 lodes, and Cor. No. 3 of the FOX No. 2 lode of this survey.
	Thence S. $89^{\circ} 30'$ W.
56	Road; bears N. $55^{\circ}$ E. and S. $55^{\circ}$ W.
104	Center of dry wash, 10 ft. wide, course S. $20^{\circ}$ E.
298.54	Lode line; discovery point bears N. $0^{\circ} 23' 22''$ W., 100 ft. dist.
316	Road; bears N. $50^{\circ}$ W. and S. $50^{\circ}$ E.
598.54	Cor. No. 4, identical with Cor. No. 4 of the FOX No. 2 lode and Cors. Nos. 3 of the Shasta # I and Shasta # 2 lodes of this survey.
	Set an iron post, 2 ft. long, 1 ins. diam., 17 ins. in the ground, with brass cap mkd. FOX 1-4, FOX 2-4, SHA 1-3, and SHA 2-3-4721.
	Thence N. $0^{\circ} 23' 22''$ W.
345	Road; bears N. $45^{\circ}$ W. and S. $40^{\circ}$ E.
1,495.94	Cor. No. 1, and place of beginning.

(This form bound on left side)

FEET

## FOX No. 2 Lode

At Cor. No. 1 of the FOX No. 2 lode, identical with Cor. No. 4 of the Shasta # I lode of this survey.

Set an iron post, 2 ft. long, 1 ins. diam., 17 ins. in the ground, with brass cap mkd. FOX 2-1-4721 and SHA 1-4-4721; from which

The  $\frac{1}{4}$  sec. cor. of secs. 26 and 35, T. 6 S., R. 27 E., G. & S. R. M., bears S.  $23^{\circ} 37' 12''$  W., 1913.06 ft. dist.; an iron post, 2 ins. diam., surrounded by a mound of stone raised to base of brass cap, mkd. as described in the official record.

Thence N.  $89^{\circ} 30'$  E.

300	Lode line; discovery point bears N. $0^{\circ} 30' 46''$ E., 1399.42 ft. dist.
378	Center of dry wash, 8 ft. wide, course SSE.
456	Road; bears S. $19^{\circ}$ W. and N. $19^{\circ}$ E.
599.40	Cor. No. 2, identical with Cors. Nos. 3 of the Blowout No. 4 and Pat # 4 lodes of this survey.
	Thence N. $0^{\circ} 28' 48''$ E.
78	Road; bears N. $80^{\circ}$ W. and S. $80^{\circ}$ E.
896	Road; bears N. $30^{\circ}$ E. and S. $30^{\circ}$ W.
1,439.41	Center of dry wash, 15 ft. wide, course S. $80^{\circ}$ E.
1,499.41	Cor. No. 3, identical with Cor. No. 3 of the FOX No. 1 lode and Cors. Nos. 2 of the Blowout No. 1 and Blowout No. 4 lodes of this survey.
	Thence S. $89^{\circ} 30'$ W.
56	Road; bears N. $55^{\circ}$ E. and S. $55^{\circ}$ W.
104	Center of dry wash, 10 ft. wide, course S. $20^{\circ}$ E.
298.54	Lode line; discovery point bears S. $0^{\circ} 30' 46''$ W., 100 ft. dist.
316	Road; bears N. $50^{\circ}$ W. and S. $50^{\circ}$ E.
598.54	Cor. No. 4, identical with Cors. Nos. 3 of the Shasta # I and Shasta # 2 lodes, and Cor. No. 4 of the FOX No. 1 lode of this survey.

FEET	
691 1,499.42	<p>Thence S. 0° 30' 46" W.</p> <p>Center of dry wash, 8 ft. wide, course S. 45° E.</p> <p>Cor. No. 1, and place of beginning.</p>
1,495.94  110 300 579.16  600.00  312 1,495.95	<p>FOX No. 8 Lode</p> <p>Beginning at Cor. No. 1 of the FOX No. 8 lode, identical with Cor. No. 1 of the FOX No. 9 lode, and Cors. Nos. 2 of the Blowout No. 6 and Blowout No. 3 lodes of this survey; from which</p> <p>The <math>\frac{1}{4}</math> sec. cor. of secs. 25 and 26 bears S. 41° 18' 22" W., 817.32 ft. dist., previously described.</p> <p>Thence N. 0° 20' 41" W.</p> <p>Cor. No. 2, identical with Cor. No. 3 of the Blowout No. 3 lode of this survey.</p> <p>Thence N. 89° 30' E.</p> <p>Road; bears S. 25° E. and N. 25° W.</p> <p>Lode line; discovery point bears S. 0° 16' 24" E., 1445.95 ft. dist.</p> <p>A point selected for witness Cor. No. 3.</p> <p>Set an iron post, 2 ft. long, 1 ins. diam., 18 ins. in the ground, with brass cap mkd. WC - FOX 8-3-4721.</p> <p>The true point for Cor. No. 3.</p> <p>This corner falls in the surface of an access road where a permanent monument cannot be maintained. Access Road bears northerly and southwesterly.</p> <p>Thence S. 0° 16' 24" E.</p> <p>Road; bears S. 35° E. and N. 30° W.</p> <p>Cor. No. 4, identical with Cor. No. 4 of the FOX No. 9 lode of this survey and Cor. No. 1 Sur. No. 4720 BASALT # 23 lode.</p> <p>To the surface of the existing brass capped pipe monument marking Cor. No. 1 Sur. No. 4720 BASALT # 23 lode, I add the following in the proper quadrants: FOX 8-4-4721 and FOX 9-4-4721.</p>

(This form bound on left side)

FEET	
	Thence S. 89° 30' W.
291	Road; bears N. 35° E. and S. 10° W.
300	Lode line; discovery point bears N. 0° 16' 24" W., 50 ft. dist.
598.13	Cor. No. 1, and place of beginning.
FOX No. 9 Lode	
Beginning at Cor. No. 1 of the FOX No. 9 lode, identical with Cors. Nos. 2 of the Blowout No. 6 and Blowout No. 3 lodes, and Cor. No. 1 of the FOX No. 8 lode of this survey.	
Thence S. 0° 29' 32" W.	
434	Road; bears N. 60° E. and S. 60° W.
1,200	Road; bears N. 20° W. and S. 20° E.
1,499.41	Cor. No. 2, identical with Cor. No. 3 of the Blowout No. 6 lode of this survey, and Cor. No. 3 Sur. No. 4719 BASALT # 16 lode.
Thence N. 89° 30' E.	
68	Road; bears N. 5° W. and S. 5° E.
298.44	Lode line; discovery point bears N. 0° 28' 49" E., 1399.40 ft. dist.
598.44	Cor. No. 3, identical with Cor. No. 4 Sur. No. 4720 BASALT # 23 lode.
To the surface of the existing brass capped pipe monument marking Cor. No. 4 Sur. No. 4720 BASALT # 23 lode, I add the following in the proper quadrant: FOX 9-3-4721.	
Thence N. 0° 28' 49" E.	
1,499.40	Cor. No. 4, identical with Cor. No. 4 of the FOX No. 8 lode of this survey and Cor. No. 1 Sur. No. 4720 BASALT # 23 lode.
Thence S. 89° 30' W.	
291	Road; bears N. 35° E. and S. 10° W.
300	Lode line; discovery point bears S. 0° 28' 49" W., 100 ft. dist.
598.13	Cor. No. 1, and place of beginning

FEET	
	Pat #4 Lode
	At Cor. No. 1 of the Pat #4 lode, identical with Cor. No. 2 of the Pat #5 lode of this survey.
	Set an iron post, 2 ft. long, 1 ins. diam., 17 ins. in the ground, with brass cap mkd. PAT 4-1-4721 and PAT 5-2-4721; from which
	The cor. of secs. 25, 26, 35 and 36, T. 6 S., R. 27 E., G. & S. R. M., bears S. 68° 05' 55" E., 686.27 ft. dist.; an iron post, 2 ins. diam., surrounded by a mound of stone raised to base of brass cap, mkd. as described in the official record.
	Thence S. 89° 30' W.
144	Center of dry wash, 20 ft. wide, course S. 5° W.
300	Lode line; discovery point bears N. 1° 22' 12" W., 1424.12 ft. dist.
382	Road; bears N. 20° E. and S. 30° W.
598.25	Cor. No. 2.
	Set an iron post, 2 ft. long, 1 ins. diam., 18 ins. in the ground, with brass cap mkd. PAT 4-2-4721.
	Thence N. 1° 22' 19" W.
760	Road; bears N. 5° W. and S. 5° E.
1,146	Center of dry wash, 10 ft. wide, course S. 70° E.
1,474.12	Cor. No. 3, identical with Cor. No. 2 of the FOX No. 2 lode and Cor. No. 3 of the Blowout No. 4 lode of this survey.
	Thence N. 89° 30' E.
183	Center of dry wash, 15 ft. wide, course S. 50° E.
298.29	Lode line; discovery point bears S. 1° 22' 12" E., 50 ft. dist.
598.29	Cor. No. 4, identical with Cor. No. 4 of the Blowout No. 4 lode, and Cors. Nos. 3 of the Blowout No. 5 lode and Pat #5 lode of this survey.
	Thence S. 1° 22' 12" E.

FEET	
400	Center of dry wash, 18 ft. wide, course S. 55° E.
740.12	Center of dry wash, 20 ft. wide, course S. 35° W.
1,474.12	Cor. No. 1, and place of beginning.
Pat #5 Lode	
At Cor. No. 1 of the Pat #5 lode, identical with Cor. No. 1 Sur. No. 4719 BASALT #16 lode.	
To the surface of the existing brass capped pipe monument marking Cor. No. 1 Sur. No. 4719 BASALT #16 lode, I add the following in the proper quadrant: PAT 5-1-4721; from which	
The cor. of secs. 25, 26, 35 and 36 bears S. 8° 37' 50" E., 254.09 ft. dist., previously described.	
Thence S. 89° 30' W.	
300	Lode line; discovery point bears N. 1° 24' 05" W., 50 ft. dist.
598.63	Cor. No. 2, identical with Cor. No. 1 of the Pat #4 lode of this survey.
Thence N. 1° 22' 12" W.	
734	Center of dry wash, 20 ft. wide, course S. 35° W.
1,074.12	Center of dry wash, 18 ft. wide, course S. 55° E.
1,474.12	Cor. No. 3, identical with Cors. Nos. 4 of the Pat #4 and Blowout No. 4 lodes, and Cor. No. 3 of the Blowout No. 5 lode of this survey.
Thence N. 89° 30' E.	
297.83	Lode line; discovery point bears S. 1° 24' 05" E., 1424.12 ft. dist.
441	Center of dry wash, 12 ft. wide, course South.
597.83	The true point for Cor. No. 4, identical with Cors. Nos. 4 of the Blowout No. 5 and Blowout No. 6 lodes of this survey, and Cor. No. 4 Sur. No. 4719 BASALT #16 lode, previously described; witnessed N. 89° 30' E., 82.84 ft. dist.
Thence S. 1° 24' 05" E.	



FEET	
42	Center of local drainage, 6 ft. wide, course West.
1,075	Crest of sharp ridge; crest bears N. 70° E. and S. 70° W.
1,474.12	Cor. No. 1, and place of beginning.
Shasta #I Lode	
At Cor. No. 1 of the Shasta #I lode.	
Set an iron post, 2 ft. long, 1 ins. diam., 18 ins. in the ground, with brass cap mkd. SHA 1-1-4721; from which	
The $\frac{1}{4}$ sec. cor. of secs. 26 and 35 bears S. 5° 27' 06" W., 1755.50 ft. dist., previously described.	
Thence N. 0° 31' 49" E.	
1,499.42	Cor. No. 2, identical with Cor. No. 2 of the Shasta #2 lode of this survey.
Set an iron post, 2 ft. long, 1 ins. diam., 18 ins. in the ground, with brass cap mkd. SHA 1-2-4721 and SHA 2-2-4721.	
Thence N. 89° 30' E.	
102	Center of dry wash, 6 ft. wide, course South.
300	Lode line; discovery point bears S. 0° 31' 49" W., 100 ft. dist.
599.29	Cor. No. 3, identical with Cor. No. 3 of the Shasta #2 lode and Cors. No. 4 of the FOX No. 1 and FOX No. 2 lodes of this survey.
Thence S. 0° 30' 46" W.	
691	Center of dry wash, 8 ft. wide, course S. 45° E.
1,499.42	Cor. No. 4, identical with Cor. No. 1 of the FOX No. 2 lode of this survey.
Thence S. 89° 30" W.	
299.74	Lode line; discovery point bears N. 0° 31' 49" E., 1399.42 ft. dist.
599.74	Cor. No. 1, and place of beginning.

(This form bound on left side)

FEET

## Shasta #2 Lode

At Cor. No. 1 of the Shasta #2 lode.

Set an iron post, 2 ft. long, 1 ins. diam.,  
18 ins. in the ground, with brass cap mkd.  
SHA 2-1-4721; from whichThe  $\frac{1}{4}$  sec. cor. of secs. 23 and 26  
bears N.  $18^{\circ} 27' 44''$  W., 544.30 ft.  
dist., previously described.Thence S.  $0^{\circ} 21' 58''$  E.

1,153	Center of local drainage, 5 ft. wide, course S. $40^{\circ}$ E.
1,495.94	Cor. No. 2, identical with Cor. No. 2 of the Shasta #I lode of this survey.  Thence N. $89^{\circ} 30'$ E.
102	Center of dry wash, 6 ft. wide, course South.
300	Lode line; discovery point bears N. $0^{\circ} 21' 58''$ W., 100 ft. dist.
599.29	Cor. No. 3, identical with Cors. Nos. 4 of the FOX No. 1 and FOX No. 2 lodes, and Cor. No. 3 of the Shasta #I lode of this survey.  Thence N. $0^{\circ} 23' 22''$ W.
345	Road; bears N. $45^{\circ}$ W. and S. $40^{\circ}$ E.
1,495.94	Cor. No. 4, identical with Cor. No. 1 of the FOX No. 1 lode of this survey.  Thence S. $89^{\circ} 30'$ W.
260	Road; bears N. $30^{\circ}$ W. and S. $15^{\circ}$ E.
298.67	Lode line; discovery point bears S $0^{\circ} 21' 58''$ E., 1395.94 ft. dist.
598.67	Cor. No. 1, and place of beginning.

## AREAS

Acres

Total area, Blowout No. 1 lode	20.537
Total area, Blowout No. 2 lode	20.550
Total area, Blowout No. 3 lode	20.581
Total area, Blowout No. 4 lode	20.588
Total area, Blowout No. 5 lode	20.580
Total area, Blowout No. 6 lode	20.603
Total area, FOX No. 1 lode	20.549
Total area, FOX No. 2 lode	20.615
Total area, FOX No. 8 lode	20.573
Total area, FOX No. 9 lode	20.591
Total area, Pat #4 lode	20.244
Total area, Pat #5 lode	20.242
Total area, Shasta #I lode	20.633
Total area, Shasta #2 lode	20.570

FEET	LOCATION
	<p>This survey is located in NW<math>\frac{1}{4}</math> and SW<math>\frac{1}{4}</math> sec. 25, and in NE<math>\frac{1}{4}</math> and SE<math>\frac{1}{4}</math> sec. 26, T. 6 S., R. 27 E. of the Gila and Salt River Meridian, Graham County, Arizona.</p> <p>The survey of the fourteen (14) lode claims embraced in this order for mineral survey and described herein is identical with the respective locations or amended locations as marked on the ground.</p>
	EXPENDITURES
	<p>The improvements and the value of the labor and improvements made upon or for the benefit of each of the lode locations embraced in said mining claim by the claimant are as follows:</p>
No. 1	<p>The discovery point of the Blowout No. 1 lode is on the lode line 100 ft. from a point on line 1-2, 300 ft. from Cor. No. 1. Value, none.</p>
No. 2	<p>A diamond drill hole bears S. 3° 10' W., 602 ft. from Cor. No. 4 Blowout No. 1 lode; 3<math>\frac{1}{2}</math> ins. diam., 301 ft. depth. Value, \$2,700.00</p>
No. 3	<p>A diamond drill hole bears N. 28° 21' W., 151 ft. from Cor. No. 1 Blowout No. 1 lode; 3<math>\frac{1}{2}</math> ins. diam., 1575 ft. depth. Value, \$14,175.00.</p>
No. 4	<p>A diamond drill hole bears N. 82° 40' E., 272 ft. from Cor. No. 2, Blowout No. 1 lode; 3<math>\frac{1}{2}</math> ins. diam., 1255 ft. depth. Value, \$11,295.00.</p>
No. 1	<p>The discovery point of the Blowout No. 2 lode is on the lode line 100 ft. from a point on line 1-2, 300 ft. from Cor. No. 1. Value, none.</p>
No. 2	<p>A diamond drill hole bears S. 35° 52' E., 476 ft. from Cor. No. 3, Blowout No. 2 lode; 3<math>\frac{1}{2}</math> ins. diam., 500 ft. depth. Value, \$4,500.00.</p>
No. 3	<p>A diamond drill hole bears N. 23° 22' E., 175 ft. from Cor. NO. 2, Blowout No. 2 lode; 3<math>\frac{1}{2}</math> ins. diam., 1517 ft. depth. Value, \$13,650.00.</p>
No. 4	<p>A diamond drill hole bears N. 59° 48' E., 303 ft. from Cor. NO. 2, Blowout No. 2 lode; 3<math>\frac{1}{2}</math> ins. diam., 1374 ft. depth. Value, \$12,365.00.</p>

FEET	
No. 5	A diamond drill hole bears N. 84° 34' E., 231 ft. from Cor. NO. 2, Blowout No. 2 lode; 3½ ins. diam., 2105 ft. depth. Value, \$18,945.00.
No. 1	The discovery point of the Blowout No. 3 lode is on the lode line 100 ft. from a point on line 1-2, 300 ft. from Cor. No. 1. Value, none.
No. 2	A diamond drill hole bears N. 12° 45' E., 659 ft. from Cor. No. 1 Blowout No. 3 lode; 3½ ins. diam., 350 ft. depth. Value, \$3,150.00.
No. 3	A diamond drill hole bears N. 31° 13' W., 470 ft. from Cor. No. 2 Blowout No. 3 lode; 3½ ins. diam., 651 ft. depth. Value, \$5,860.00.
No. 4	A diamond drill hole bears N. 36° 08' E., 270 ft. from Cor. No. 1 Blowout No. 3 lode; 3½ ins. diam., 1705 ft. depth. Value, \$15,345.00.
No. 1	The discovery point of the Blowout No. 4 lode is on the lode line 100 ft. from a point on line 1-2, 300 ft. from Cor. No. 1. Value, none.
No. 2	A diamond drill hole bears S. 50° 10' W., 55 ft. from Cor. No. 1 Blowout No. 4 lode; 3 ½ ins. diam., 1295 ft. depth. Value, \$11,655.00.
No. 3	A diamond drill hole bears S. 26° 33' W., 277 ft. from Cor. No. 1 Blowout No. 4 lode; 3½ ins. diam., 1396 ft. depth. Value, \$12,565.00.
No. 4	A diamond drill hole bears S. 38° 58' W., 377 ft. from Cor. No. 1 Blowout No. 4 lode; 3½ ins. diam., 1050 ft. depth. Value, \$9,450.00.
No. 5	A diamond drill hole bears S. 7° 37' W., 413 ft. from Cor. No. 1 Blowout No. 4 lode; 3½ ins. diam., 2482 ft. depth. Value, \$22,340.00.
No. 6	A diamond drill hole bears S. 14° 45' W., 539 ft. from Cor. No. 1 Blowout No. 4 lode; 3½ ins. diam., 1353 ft. depth. Value, \$12,175.00.

FEET		
No. 7	A diamond drill hole bears N. 17° 31' W., 748 ft. from Cor. No. 4 Blowout No. 4 lode; 3½ ins. diam., 1268 ft. depth. Value, \$11,410.00.	
No. 8	A diamond drill hole bears N. 2° 21' W., 720 ft. from Cor. No. 4 Blowout No. 4 lode; 3½ ins. diam., 1059 ft. depth. Value, \$9,530.00.	
No. 9	A diamond drill hole bears N. 24° 00' W., 568 ft. from Cor. No. 4 Blowout No. 4 lode; 3½ ins. diam., 1050 ft. depth. Value, \$9,450.00.	
No. 1	The discovery point of the Blowout No. 5 lode is on the lode line 100 ft. from a point on line 1-2, 300 ft. from Cor. No. 1. Value, none.	
No. 2	A diamond drill hole bears S. 30° 16' E., 98 ft. from Cor. No. 2 Blowout No. 5 lode; 3½ ins. diam., 985 ft. depth. Value, \$8,865.00.	
No. 3	A diamond drill hole bears S. 74° 15' W., 261 ft. from Cor. No. 1 Blowout No. 5 lode; 3½ ins. diam., 1105 ft. depth. Value, \$9,945.00.	
No. 4	A diamond drill hole bears S. 39° 47' E., 235 ft. from Cor. No. 2 Blowout No. 5 lode; 3½ ins. diam., 2566 ft. depth. Value, \$23,095.00.	
No. 5	A diamond drill hole bears S. 14° 55' W., 493 ft. from Cor. No. 1 Blowout No. 5 lode; 3½ ins. diam., 1438 ft. depth. Value, \$12,940.00.	
No. 6	A diamond drill hole bears S. 4° 56' W., 684 ft. from Cor. No. 1 Blowout No. 5 lode; 3½ ins. diam., 2755 ft. depth. Value, \$24,800.00.	
No. 7	A diamond drill hole bears N. 13° 46' E., 752 ft. from Cor. No. 3 Blowout No. 5 lode; 3½ ins. diam., 1122 ft. depth. Value, \$10,100.00	
No. 8	A diamond drill hole bears N. 23° 18' W., 571 ft. from Cor. No. 4, Blowout No. 5 lode; 3½ ins. diam., 2303 ft. depth. Value, \$20,725.00.	

FEET	
No. 1	The discovery point of the Blowout No. 6 lode is on the lode line 100 ft. from a point on line 1-2, 300 ft. from Cor. No. 1. Value, none.
No. 2	A diamond drill hole bears S. 58° 45' W., 296 ft. from Cor. No. 2 Blowout No. 6 lode; 3½ ins. diam., 1574 ft. depth. Value, \$14,165.00.
No. 3	A diamond drill hole bears S. 26° 47' E., 345 ft. from Cor. No. 1 Blowout No. 6 lode; 3½ ins. diam., 1235 ft. depth. Value, \$11,115.00.
No. 4	A diamond drill hole bears S. 19° 20' E., 508 ft. from Cor. No. 1 Blowout No. 6 lode; 3½ ins. diam., 1256 ft. depth. Value, \$11,300.00.
No. 5	A diamond drill hole bears S. 20° 25' E., 627 ft. from Cor. No. 1 Blowout No. 6 lode; 3½ ins. diam., 1104 ft. depth. Value, \$9,935.00.
No. 6	A diamond drill hole bears N. 18° 42' E., 553 ft. from Cor. No. 4 Blowout No. 6 lode; 3½ ins. diam., 1444 ft. depth. Value, \$13,000.00.
No. 7	A diamond drill hole bears N. 48° 37' E., 503 ft. from Cor. No. 4 Blowout No. 6 lode; 3½ ins. diam., 1844 ft. depth. Value, \$16,600.00.
No. 1	The discovery point of the FOX No. 1 lode is on the lode line 100 ft. from a point on line 3-4, 298.54 ft. from Cor. No. 3. Value, none.
No. 2	A diamond drill hole bears S. 9° 40' E., 738 ft. from Cor. No. 1 FOX No. 1 lode; 3½ ins. diam., 704 ft. depth. Value, \$6,336.00.
No. 1	The discovery point of the FOX No. 2 lode is on the lode line 100 ft. from a point on line 3-4, 298.54 ft. from Cor. No. 3. Value, none.
No. 2	A diamond drill hole bears N. 26° 32' E., 377 ft. from Cor. No. 1 FOX No. 2 lode; 3½ ins. diam., 823 ft. depth. Value, \$7,400.00.
No. 3	A diamond drill hole bears N. 0° 01' E., 329 ft. from Cor. No. 2 FOX No. 2 lode; 3½ ins. diam., 2000 ft. depth. Value, \$18,000.00.

FEET		
No. 1	The discovery point of the FOX No. 8 lode is on the lode line, 50 ft. from a point on line 4-1, 300 ft. from Cor. No. 4. Value, none.	
No. 2	A diamond drill hole bears N. 0° 48' E., 214 ft. from Cor. No. 1 FOX No. 8 lode; 3½ ins. diam., 400 ft. depth. Value, \$3,600.00.	
No. 1	The discovery point of the FOX No. 9 lode is on the lode line, 100 ft. from a point on line 4-1, 300 ft. from Cor. No. 4. Value, none.	
No. 2	A diamond drill hole bears S. 16° 22' E., 612 ft. from Cor. No. 1 FOX No. 9 lode; 3½ ins. diam., 1645 ft. depth. Value, \$14,800.00.	
No. 1	The discovery point of the Pat #4 lode is on the lode line, 50 ft. from a point on line 3-4, 298.29 ft. from Cor. No. 3. Value, none.	
No. 2	A diamond drill hole bears S. 72° 06' W., 228 ft. from Cor. No. 4 Pat #4 lode; 3½ ins. diam., 524 ft. depth. Value, \$4,716.00.	
No. 3	A rotary drill hole bears S. 1° 42' W., 634 ft. from Cor. No. 4 Pat #4 lode; 3½ ins. diam., 1,000 ft. depth. Value, \$7,000.00.	
No. 1	The discovery point of the Pat #5 lode is on the lode line, 50 ft. from a point on line 1-2, 300 ft. from Cor. No. 1. Value, none.	
No. 2	A diamond drill hole bears S. 76° 13' W., 250 ft. from Cor. No. 4 Pat #5 lode; 3½ ins. diam., 533 ft. depth. Value, \$4,800.00.	
No. 1	The discovery point of the Shasta #I lode is on the lode line, 100 ft. from a point on line 2-3, 300 ft. from Cor. No. 2. Value, none.	
No. 2	A diamond drill hole bears S. 14° 28' W., 157 ft. from Cor. No. 3 Shasta #I lode; 3½ ins. diam., 550 ft. depth. Value, \$4,950.00.	
No. 1	The discovery point of the Shasta #2 lode is on the lode line, 100 ft. from a point on line 2-3, 300 ft. from Cor. No. 2. Value, none.	
No. 2	A diamond drill hole bears N. 46° 13' W., 70 ft. from Cor. No. 3 Shasta #2 lode; 3½ ins. diam., 601 ft. depth. Value, \$5,410.00.	

(This form bound on left side)

FEET

An interest in a common improvement described as follows:

A network of access roads as shown on the mineral survey plat.

Value of access roads, \$16,000.00.

Value of one-fourteenth interest, \$1,000.00.

This improvement is for the development of the fourteen lodes of this survey and was made subsequent to the location of each lode and to the time since which common ownership and contiguity have prevailed; therefore an undivided one-fourteenth interest in its value is hereby credited to each of said lodes of the common group.

OTHER IMPROVEMENTS

none

OTHER CORNER DESCRIPTIONS AND SUPPLEMENTAL DATA

Sur. No. 4719 BASALT #16 lode: All corners are brass capped pipe monuments with concrete foundations, firmly set and properly marked. All lines shown as approved.

Sur. No. 4720 BASALT #23 lode: All corners are brass capped pipe monuments with concrete foundations, firmly set and properly marked. All lines shown as approved.

The line between the cor. of secs. 25, 26, 35, and 36, T. 6 S., R. 27 E., and the 1/4 sec. cor. of secs. 26 and 35 bears S. 89° 35' 47" W., 2636.42 ft. dist., instead of N. 89° 55' W., 2632.08 ft. dist., as approved.

The line between the cor. of secs. 25, 26, 35, and 36 and the 1/4 sec. cor. of secs. 25 and 26 bears N. 0° 03' 17" W., 2640.50 ft. dist., instead of NORTH, 2640.00 ft., as approved.

The line between the 1/4 sec. cor. of secs. 25 and 26 and the cor. of secs. 23, 24, 25, and 26 bears N. 0° 07' 20" W., 2599.82 ft. dist., instead of NORTH, 2597.10 ft. dist., as approved.

The line between the cor. of secs. 23, 24, 25, and 26 and the 1/4 sec. cor. of secs. 23 and 26 bears N. 89° 59' 41" W., 2629.56 ft. dist., instead of WEST, 2629.44 ft. dist., as approved.

FIELD ASSISTANTS

Name	Capacity
Loren E. Bunney	Instrumentman
Robert E. Hungerford	Chainman



UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

CERTIFICATE OF SURVEYOR

Name of Mineral Surveyor Travis L. Gant	Date August 21, 1972
--	-------------------------

I HEREBY CERTIFY That in pursuance of an order received from the Bureau of Land Management, at Phoenix, Arizona, dated April 5, 19 72, I have carefully executed the survey of the claim of Harold F. & Tillie Lou Carpenter, William & Loraine R. Sorsen, Hearold & Charleen known as the (lode, placer, or mill site) Elmer, and Harold D. & Doris Maryott (see below) situated in Secs. 25 and 26, Township 6 South, Range 27 East, Gila & Salt River Meridian, in the State of Arizona.

This survey, designated as number 4721, has been executed by me and under my direction and has been made in strict conformity with said order, the Manual of Instructions for the Survey of Public Lands of the United States, and in specific manner described in the foregoing field notes.

I FURTHER CERTIFY That the labor expended and improvements made upon and for the benefit of the (lode or placer) location(s) embraced in the said mining claim by claimant(s) or their grantors are fully stated in my report. The character, extent, location, and itemized value are specified in full detail. No portion of, or interest in, said labor and improvements so credited to this claim has been included in the estimate of expenditures upon any other claim.

- \* Blowout Nos. 1 thru 6                      Pat # 4
- FOX No. 1                                      Pat # 5
- FOX No. 2                                      Shast # I
- FOX No. 8                                      Shasta # 2
- FOX No. 9

Globe, Arizona (Location)	<i>Travis L. Gant</i> (Signature of Mineral Surveyor)
------------------------------	--

CERTIFICATE OF APPROVAL

Office Arizona State Office
Location Phoenix, Arizona
Date April 5, 1973

The foregoing field notes of mineral survey number 4721, in Sections 25 & 26, Range 27 E., Gila and Salt River Meridian, in the State of Arizona, executed by Travis L. Gant, Mineral Surveyor, under order dated April 5, 19 72, having been critically examined and the necessary corrections made prior to their certification by the surveyor, the field notes and the survey therein described are hereby approved.

<i>Joe T. Fullmer</i> Joe T. Fullmer (Authorized Signature)	State Director (Title)
--	---------------------------

CERTIFICATE OF TRANSCRIPT

I HEREBY CERTIFY That the foregoing transcript of field notes of the above-described mineral survey number is a true copy of the original field notes.

(Authorized Signature)	(Title)
------------------------	---------

Title 18, U.S.C. section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious, or fraudulent statements or representations as to any matter within its jurisdiction.

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911