

Form 3400-11  
(September 1967)  
(formerly 4-683)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

Mineral Survey number	4730
State	Arizona
Land District	Arizona

FIELD NOTES

Of the Survey of the Mining Claim of *(name and address of Claimant)*

Inspiration Consolidated Copper Company  
c/o G. Henry Ladendorff, Atty. at Law  
Suite 716, Arizona Bank Building  
Phoenix, Arizona 85003

Known as the *(name of group, if any)*

WEBSTER Group

CONSISTING OF LOCATIONS NAMED AND LOCATED AS FOLLOWS

NAME OF LOCATION	DATE	
	LOCATED	AMENDED
WEBSTER 1	5/9/72	
WEBSTER 2	5/9/72	
WEBSTER 3	5/9/72	
WEBSTER 4	5/9/72	
WEBSTER 5	5/9/72	
WEBSTER 6	5/9/72	
WEBSTER 7	5/9/72	
WEBSTER 8	5/9/72	
WEBSTER 9	5/9/72	
WEBSTER 10	5/9/72	
WEBSTER 11	5/9/72	
WEBSTER 12	5/9/72	
WEBSTER 13	5/2/72	
WEBSTER 14	5/11/72	
WEBSTER 15	5/2/72	
WEBSTER 16	5/11/72	
WEBSTER 17	5/2/72	
WEBSTER 18	5/11/72	
WEBSTER 19	5/2/72	
WEBSTER 20	5/11/72	
WEBSTER 21	4/25/72	
WEBSTER 22	5/11/72	

Mining district		County	
Globe		Gila	
Section 13 Uns. 18 Surv.	Township 1 N. 1 North	Range 14 East 15 East	Meridian Gila & Salt River
Survey commenced September 15, 1972		Survey completed December 21, 1972	Survey under order dated August 21, 1972
			Name of Mineral Surveyor Travis L. Gant

1000  
 900  
 800  
 700  
 600  
 500  
 400  
 300  
 200  
 100  
 0



1000  
 900  
 800  
 700  
 600  
 500  
 400  
 300  
 200  
 100  
 0

FIELD NOTES

CONSISTING OF LOCATIONS NAMED AND LOCATED AS FOLLOWS

NAME OF LOCATION	DATE	
	LOCATED	AMENDED
WEBSTER 23	4/25/72	
WEBSTER 24	5/11/72	
WEBSTER 25	4/25/72	
WEBSTER 26	5/11/72	
WEBSTER 27	4/25/72	
WEBSTER 28	5/11/72	
WEBSTER 29	4/24/72	
WEBSTER 30	5/11/72	
WEBSTER 31	4/24/72	
WEBSTER 32	5/10/72	
WEBSTER 33	4/24/72	
WEBSTER 34	5/10/72	
WEBSTER 35	4/24/72	
WEBSTER 36	5/10/72	
WEBSTER 37	5/9/72	
WEBSTER 38	5/10/72	
WEBSTER 39	5/9/72	
WEBSTER 40	5/10/72	
WEBSTER 41	5/10/72	
WEBSTER 42	5/9/72	
WEBSTER 43	5/9/72	
WEBSTER 44	5/10/72	
WEBSTER 45	5/10/72	
WEBSTER 46	5/10/72	
WEBSTER 47 mill site	7/7/72	
WEBSTER 48 mill site	7/7/72	

1911  
1912  
1913  
1914  
1915  
1916  
1917  
1918  
1919  
1920  
1921  
1922  
1923  
1924  
1925  
1926  
1927  
1928  
1929  
1930  
1931  
1932  
1933  
1934  
1935  
1936  
1937  
1938  
1939  
1940  
1941  
1942  
1943  
1944  
1945  
1946  
1947  
1948  
1949  
1950  
1951  
1952  
1953  
1954  
1955  
1956  
1957  
1958  
1959  
1960  
1961  
1962  
1963  
1964  
1965  
1966  
1967  
1968  
1969  
1970  
1971  
1972  
1973  
1974  
1975  
1976  
1977  
1978  
1979  
1980  
1981  
1982  
1983  
1984  
1985  
1986  
1987  
1988  
1989  
1990  
1991  
1992  
1993  
1994  
1995  
1996  
1997  
1998  
1999  
2000  
2001  
2002  
2003  
2004  
2005  
2006  
2007  
2008  
2009  
2010  
2011  
2012  
2013  
2014  
2015  
2016  
2017  
2018  
2019  
2020  
2021  
2022  
2023  
2024  
2025  
2026  
2027  
2028  
2029  
2030  
2031  
2032  
2033  
2034  
2035  
2036  
2037  
2038  
2039  
2040  
2041  
2042  
2043  
2044  
2045  
2046  
2047  
2048  
2049  
2050  
2051  
2052  
2053  
2054  
2055  
2056  
2057  
2058  
2059  
2060  
2061  
2062  
2063  
2064  
2065  
2066  
2067  
2068  
2069  
2070  
2071  
2072  
2073  
2074  
2075  
2076  
2077  
2078  
2079  
2080  
2081  
2082  
2083  
2084  
2085  
2086  
2087  
2088  
2089  
2090  
2091  
2092  
2093  
2094  
2095  
2096  
2097  
2098  
2099  
2100



FEET

The lines were measured with either a Lufkin steel tape or with the aforementioned electronic distance meter. The tape was 500 feet in length, graduated every foot for 500 feet, with an added foot on the zero end graduated in tenths and hundredths; the tape was compared with a standard 100.00 foot tape at the time of the beginning of the survey and found to be correct. The distance meter was compared with a taped course, 1200 feet in length, measured as a base-line with a standard 100.00 foot tape, and found to be precise and accurate.

All lines and connections of this survey were run by direct methods.

The magnetic declination observed at each corner of the survey gave a uniform value of 13° 30' E.

Note concerning monumentation: With the exception of those corners which were not monumented for reasons given in each case, or which were monumented as otherwise described herein, I set iron posts at each corner of each mill site claim comprising this survey. Each iron post consists of a 3/4-inch nominal inside diam. galvanized water pipe having a 1 ins. exterior diam.; each pipe was placed in the ground in a foundation consisting of not less than 1/2 cu. ft. of high early strength portland cement concrete, mixed at the site. Brass caps were securely attached and marked as described, using 1/8-in. steel dies for stamping. Alongside every corner monument I erected a rock monument having a base two feet minimum diam., and a height of not less than two feet.

SURVEY NO. 4730

WEBSTER 1 Mill Site

At Cor. No. 1 of the WEBSTER 1 mill site, identical with Cors. Nos. 1 of the WEBSTER 2, WEBSTER 4, and WEBSTER 3 mill sites of this survey.

Set an iron post, 2 ft. long, 1 ins. diam., 14 ins. in the ground, with brass cap mkd. WEB 1-1, WEB 2-1, WEB 4-1, and WEB 3-1-4730; from which

FEET		
	<p>The west <math>\frac{1}{4}</math> section corner of sec. 18, T. 1 N., R. 15 E., G. &amp; S. R. M., bears S. 81° 04' 04" E., 3509.51 ft. dist.; an iron post 1 ins. diam., 12 ins. above ground, firmly set, and surrounded by a mound of stone, with brass cap marked as described in the official record.</p> <p>Thence N. 50° 31' W.</p>	
122.37	<p>Intersect line 2-3 Sur. No. 3489 Oriole No. 1 lode at a point from which the true point for Cor. No. 2, identical with Cor. No. 3 Sur. No. 3489 Oriole lode, bears S. 40° 57' 35" W., 863.58 ft. dist.</p>	
174.37	<p>Cor. No. 2, identical with Cor. No. 2 of the WEBSTER 2 mill site of this survey.</p> <p>Set an iron post, 2 ft. long, 1 ins. diam., 16 ins. in the ground, with brass cap mkd. WEB 1-2-4730 and WEB 2-2-4730.</p> <p>Thence S. 40° 10' 31" W.</p>	
700	<p>Center of dry wash, 12 ft. wide, course N. 50° E.</p>	
862.52	<p>Intersect line 1-2 Sur. No. 3489 Oriole No. 1 lode and line 3-4 Sur. No. 3489 Oriole lode at a point from which the true point for Cors. Nos. 2 and 3, respectively, bear S. 49° 19' E., 40.17 ft. dist.</p>	
989.58	<p>Cor. No. 3.</p> <p>Set an iron post, 2 ft. long, 1 ins. diam., 12 ins. in the ground, with brass cap mkd. WEB 1-3-4730; from which</p> <p>The true point for Cor. No. 3 Sur. No. 3489 Oriole lode, identical with Cor. No. 2 Sur. No. 3489 Oriole No. 1 lode, bears N. 57° 46' E., 132.92 ft. dist.</p> <p>Thence S. 50° 31' E.</p>	
37.55	<p>Intersect line 2-3 Sur. No. 3489 Oriole lode at a point from which the true point for Cor. No. 3, identical with Cor. No. 2 Sur. No. 3489 Oriole No. 1 lode, bears N. 41° 22' E., 126.28 ft. dist.</p>	
186.58	<p>Cor. No. 4, identical with Cor. No. 4 of the WEBSTER 3 mill site of this survey.</p> <p>Set an iron post, 2 ft. long, 1 ins. diam., 17 ins. in the ground, with brass cap mkd. WEB 1-4-4730 and WEB 3-4-4730.</p>	

FEET	
	<p style="text-align: center;">Thence N. 39° 28' 05" E.</p>
443	Center of dry wash, 12 ft. wide, course East.
989.51	Cor. No. 1, and place of beginning.
	<p style="text-align: center;">WEBSTER 2 Mill Site</p>
	<p>Beginning at Cor. No. 1 of the WEBSTER 2 mill site, identical with Cors. Nos. 1 of the WEBSTER 4, WEBSTER 3, and WEBSTER 1 mill sites of this survey.</p>
	<p style="text-align: center;">Thence N. 50° 31' W.</p>
122.37	Intersect line 2-3 Sur. No. 3489 Oriole No. 1 lode at a point from which the true point for Cor. No. 3 bears N. 40° 57' 35" E., 563.60 ft. dist.
174.37	Cor. No. 2, identical with Cor. No. 2 of the WEBSTER 1 mill site of this survey; from which
	<p style="text-align: center;">The true point for Cor. No. 3 Sur. No. 3489 Oriole No. 1 lode bears N. 46° 13' E., 567.33 ft. dist.</p>
	<p style="text-align: center;">Thence N. 37° 21' 57" E.</p>
151	Center of Lost Gulch, 50 ft. wide, stream course S. 80° E.
335	Road, bears East and West.
565.63	Intersect line 3-4 Sur. No. 3489 Oriole No. 1 lode at a point from which the true point for Cor. No. 3 bears S. 49° 19' E., 87.44 ft. dist.
1,085.23	Cor. No. 3
	<p>An existing brass-topped iron post, 2 ins. diam., projecting 18 ins. above ground, set in a concrete foundation projecting 9 ins. above ground. I obliterate all markings found thereon and add the following, using steel dies: WEB 2-3-4730.</p>
	<p style="text-align: center;">Thence S. 50° 01' 05" E.</p>
199.94	Cor. No. 4, identical with Cor. No. 4 of the WEBSTER 4 mill site of this survey.
	<p>Set an iron post, 2 ft. long, 1 ins. diam., 15 ins. in the ground, with brass cap mkd. WEB 2-4-4730 and WEB 4-4-4730.</p>



FEET	
	Thence S. 38° 42' 51" W.
650	Road, bears East and West.
882	Center of Lost Gulch, 50 ft. wide, stream course S. 45° E.
900	Road, bears N. 10° W. and S. 10° E.
1,082.85	Cor. No. 1, and place of beginning.
	WEBSTER 3 Mill Site
	Beginning at Cor. No. 1 of the WEBSTER 3 mill site, identical with Cors. Nos. 1 of the WEBSTER 1, WEBSTER 2, and WEBSTER 4 mill sites of this survey.
	Thence S. 50° 31' E.
199.80	The true point for Cor. No. 2, identical with Cors. Nos. 2 of the WEBSTER 4, WEBSTER 6, and WEBSTER 5 mill sites of this survey.
	This corner falls in an access road where a permanent monument cannot be established, witnessed S. 50° 31' E., 7.52 ft. dist., hereinafter described; access road bears N. 40° E. and S. 35° W.
	Set a temporary point for Cor. No. 2.
	Thence S. 39° 26' 53" W.
446	Center of dry wash, 12 ft. wide, course East.
989.51	Cor. No. 3, identical with Cor. No. 3 of the WEBSTER 5 mill site of this survey.
	Set an iron post, 2 ft. long, 1 ins. diam., 11 ins. in the ground, with brass cap mkd. WEB 3-3-4730 and WEB 5-3-4730.
	Thence N. 50° 31' W.
200.16	Cor. No. 4, identical with Cor. No. 4 of the WEBSTER 1 mill site of this survey.
	Thence N. 39° 28' 05" E.
443	Center of dry wash, 12 ft. wide, course East.
989.51	Cor. No. 1, and place of beginning.
	WEBSTER 4 Mill Site
	Beginning at Cor. No. 1 of the WEBSTER 4 mill site, identical with Cors. Nos. 1 of the WEBSTER 3, WEBSTER 1, and WEBSTER 2 mill sites of this survey.

(This form bound on left side)

FEET	
	Thence S. 50° 31' E.
199.80	The true point for Cor. No. 2, identical with Cors. Nos. 2 of the WEBSTER 6, WEBSTER 5, and WEBSTER 3 mill sites of this survey, previously described.
	Thence N. 38° 43' 19" E.
40	Road, bears northerly and southwesterly.
184	Center of Lost Gulch, 60 ft. wide, stream course S. 50° E.
665	Road, bears S. 15° E. and N. 15° W.
902	Center of local drainage, 10 ft. wide, course South.
1,081.11	Cor. No. 3, identical with Cor. No. 3 of the WEBSTER 6 mill site of this survey.  Set an iron post, 2 ft. long, 1 ins. diam., 13 ins. in the ground, with brass cap mkd. WEB 4-3-4730 and WEB 6-3-4730.
	Thence N. 50° 01' 05" W.
50	Center of local drainage, 10 ft. wide, course S. 30° W.
199.98	Cor. No. 4 identical with Cor. No. 4 of the WEBSTER 2 mill site of this survey.
	Thence S. 38° 42' 51" W.
650	Road, bears East and West.
882	Center of Lost Gulch, 50 ft. wide, stream course S. 45° E.
900	Road, bears N. 10° W. and S. 10° E.
1,082.85	Cor. No. 1, and place of beginning.
	WEBSTER 5 Mill Site
	At Cor. No. 1 of the WEBSTER 5 mill site, identical with Cors. Nos. 1 of the WEBSTER 6, WEBSTER 8, and WEBSTER 7 mill sites of this survey.
	Set an iron post, 2 ft. long, 1 ins. diam., 16 ins. in the ground, with brass cap mkd. WEB 5-1, WEB 6-1, WEB 8-1, and WEB 7-1-4730; from which west The $\frac{1}{4}$ sec. cor. of sec. 18, T.1 N., R.15 E., bears S. 84° 44' 11" E., 3172.17 ft. dist., previously described.

FEET		
	Thence N. 50° 31' W.	
111	Center of dry wash, 12 ft. wide, course N. 80° E.	
191.95	A point selected for witness Cor. No. 2, identical with witness Cors. Nos. 2 of the WEBSTER 3, WEBSTER 4, and WEBSTER 6 mill sites of this survey.  Set an iron post, 2 ft. long, 1 ins. diam., 12 ins. in the ground, with brass cap mkd. WC - WEB 5-2, WEB 3-2, WEB 4-2, and WEB 6-2-4730.	
199.47	The true point for Cor. No. 2, identical with Cors. Nos. 2 of the WEBSTER 3, WEBSTER 4, and WEBSTER 6 mill sites of this survey, previously described.  Thence S. 39° 26' 53" W.	
446	Center of dry wash, 12 ft. wide, course East.	
989.51	Cor. No. 3, identical with Cor. No. 3 of the WEBSTER 3 mill site of this survey.  Thence S. 50° 31' E.	
198.70	Cor. No. 4, identical with Cor. No. 4 of the WEBSTER 7 mill site of this survey.  Set an iron post, 2 ft. long, 1 ins. diam., 17 ins. in the ground, with brass cap mkd. WEB 5-4-4730 and WEB 7-4-4730.  Thence N. 39° 29' 33" E.	
603	Road, bears N. 85° E. and S. 85° W.	
989.50	Cor. No. 1, and place of beginning.	
	WEBSTER 6 Mill Site	
	Beginning at Cor. No. 1 of the WEBSTER 6 mill site, identical with Cors. Nos. 1 of the WEBSTER 8, WEBSTER 7, and WEBSTER 5 mill sites of this survey.  Thence N. 50° 31' W.	
111	Center of dry wash, 12 ft. wide, course N. 80° E.	
191.95	Witness Cor. No. 2, previously described.	
199.47	The true point for Cor. No. 2, identical with Cors. Nos. 2 of the WEBSTER 5, WEBSTER 3, and WEBSTER 4 mill sites of this survey, previously described.	

(This form bound on left side)

FEET	
	Thence N. 38° 43' 19" E.
40	Road, bears northerly and southwesterly.
184	Center of Lost Gulch, 60 ft. wide, stream course S. 50° E.
665	Road, bears S. 15° E. and N. 15° W.
902	Center of local drainage, 10 ft. wide, course South.
1,081.11	Cor. No. 3, identical with Cor. No. 3 of the WEBSTER 4 mill site of this survey.
	Thence S. 50° 01' 05" E.
55	Center of local drainage, 10 ft. wide, course West.
200.00	Cor. No. 4.
	An existing brass-topped iron post, 2 ins. diam., projecting 18 ins. above ground, set in a concrete foundation projecting 10 ins. above ground. I obliterate all markings found thereon and add the following, using steel dies: WEB 6-4-4730.
	Thence S. 38° 44' 56" W.
89.19	Intersect the true point for Cor. No. 4 of the WEBSTER 8 mill site of this survey, which falls in an access road which bears N. 55° E. and S. 55° W.
229	Road, bears northeasterly and southeasterly.
606	Road, bears northerly and southerly.
722	North bank of water storage reservoir, hereinafter referred to as Webster Lake, bears N. 10° W. and S. 10° E.
989	South bank of Webster Lake, bears N. 70° W. and S. 70° E.
1,079.36	Cor. No. 1, and place of beginning.
	WEBSTER 7 Mill Site
	Beginning at Cor. No. 1 of the WEBSTER 7 mill site, identical with Cors. Nos. 1 of the WEBSTER 5, WEBSTER 6, and WEBSTER 8 mill sites of this survey.
	Thence S. 50° 31' E.

FEET		
218.27	<p>Cor. No. 2, identical with Cors. Nos. 2 of the WEBSTER 8, WEBSTER 10, and WEBSTER 9 mill sites of this survey.</p> <p>Set an iron post, 2 ft. long, 1 ins. diam., 11 ins. in the ground, with brass cap mkd. WEB 7-2, WEB 8-2, WEB 10-2, and WEB 9-2-4730.</p> <p>Thence S. 39° 28' 49" W.</p>	
179	<p>Road, bears westerly and southeasterly.</p>	
989.50	<p>Cor. No. 3, identical with Cor. No. 3 of the WEBSTER 9 mill site of this survey.</p> <p>Set an iron post, 2 ft. long, 1 ins. diam., 18 ins. in the ground, with brass cap mkd. WEB 7-3-4730 and WEB 9-3-4730.</p> <p>Thence N. 50° 31' W.</p>	
218.47	<p>Cor. No. 4, identical with Cor. No. 4 of the WEBSTER 5 mill site of this survey.</p> <p>Thence N. 39° 29' 33" E.</p>	
603	<p>Road, bears N. 85° E. and S. 85° W.</p>	
989.50	<p>Cor. No. 1, and place of beginning.</p>	
<p>WEBSTER 8 Mill Site</p>		
<p>Beginning at Cor. No. 1 of the WEBSTER 8 mill site, identical with Cors. Nos. 1 of the WEBSTER 7, WEBSTER 5, and WEBSTER 6 mill sites of this survey.</p>		
<p>Thence S. 50° 31' E.</p>		
218.27	<p>Cor. No. 2, identical with Cors. Nos. 2 of the WEBSTER 10, WEBSTER 9, and WEBSTER 7 mill sites of this survey.</p> <p>Thence N. 38° 40' 34" E.</p>	
60	<p>South bank of Webster Lake, bears N. 33° W. and S. 33° E.</p>	
240	<p>North bank of Webster Lake, bears N. 30° W. and S. 50° E.</p>	
395	<p>Road, bears N. 70° W. and S. 60° E.</p>	
472	<p>Road, bears N. 10° W. and S. 10° E.</p>	
990.19	<p>Cor. No. 3, identical with Cor. No. 3 of the WEBSTER 10 mill site of this survey.</p>	

FEET	
	<p>Set an iron post, 2 ft. long, 1 ins. diam., 12 ins. in the ground, with brass cap mkd. WEB 8-3-4730 and WEB 10-3-4730.</p> <p>Thence N. 50° 31' W.</p>
197.23	<p>A point selected for witness Cor. No. 4.</p> <p>Set an iron post, 2 ft. long, 1 ins. diam., 17 ins. in the ground, with brass cap mkd. WC - WEB 8-4-4730.</p>
217.01	<p>The true point for Cor. No. 4, on line 4-1 of the WEBSTER 6 mill site of this survey.</p> <p>This corner falls in an access road where a permanent monument cannot be maintained; access road bears N. 55° E. and S. 55° W.</p> <p>Thence S. 38° 44' 56" W.</p>
139.81	Road, bears northeasterly and southeasterly.
516.81	Road, bears northerly and southerly.
632.81	North bank of Webster Lake, bears N. 10° W. and S. 10° E.
899.81	South bank of Webster Lake, bears N. 70° W. and S. 70° E.
990.17	Cor. No. 1, and place of beginning.
	<p style="text-align: center;">WEBSTER 9 Mill Site</p> <p>At Cor. No. 1 of the WEBSTER 9 mill site, identical with Cors. Nos. 1 of the WEBSTER 10, WEBSTER 12, and WEBSTER 11 mill sites of this survey.</p> <p>Set an iron post, 2 ft. long, 1 ins. diam., 13 ins. in the ground, with brass cap mkd. WEB 9-1, WEB 10-1, WEB 12-1, and WEB 11-1-4730; from which</p> <p style="padding-left: 40px;">west</p> <p style="padding-left: 40px;">The <math>\frac{1}{4}</math> sec. cor. of sec. 18, T. 1 N., R. 15 E., bears S. 89° 44' 37" E., 2820.90 ft. dist., previously described.</p> <p>Thence N. 50° 31' W.</p>
219.56	Cor. No. 2, identical with Cors. Nos. 2 of the WEBSTER 7, WEBSTER 8, and WEBSTER 10 mill sites of this survey.

FEET	
	Thence S. 39° 28' 49" W.
179	Road, bears westerly and southeasterly.
989.50	Cor. No. 3, identical with Cor. No. 3 of the WEBSTER 7 mill site of this survey.
	Thence S. 50° 31' E.
219.50	Cor. No. 4, identical with Cor. No. 4 of the WEBSTER 11 mill site of this survey.
	Set an iron post, 2 ft. long, 1 ins. diam., 16 ins. in the ground, with brass cap mkd. WEB 9-4-4730 and WEB 11-4-4730.
	Thence N. 39° 29' 01" E.
756	Road, bears N. 15° E. and S. 15° W.
989.50	Cor. No. 1, and place of beginning.
	WEBSTER 10 Mill Site
	Beginning at Cor. No. 1 of the WEBSTER 10 mill site, identical with Cors. Nos. 1 of the WEBSTER 12, WEBSTER 11, and WEBSTER 9 mill sites of this survey.
	Thence N. 50° 31' W.
219.56	Cor. No. 2, identical with Cors. Nos. 2 of the WEBSTER 9, WEBSTER 7, and WEBSTER 8 mill sites of this survey.
	Thence N. 38° 40' 34" E.
60	South bank of Webster Lake, bears N. 33° W. and S. 33° E.
240	North bank of Webster Lake, bears N. 30° W. and S. 50° E.
395	Road, bears N. 70° W. and S. 60° E.
472	Road, bears N. 10° W. and S. 10° E.
990.19	Cor. No. 3, identical with Cor. No. 3 of the WEBSTER 8 mill site of this survey.
	Thence S. 50° 31' E.
220.34	Cor. No. 4, identical with Cor. No. 4 of the WEBSTER 12 mill site of this survey.



FEET	
	<p>Set an iron post, 2 ft. long, 1 ins. diam., 14 ins. in the ground, with brass cap mkd. WEB 10-4-4730 and WEB 12-4-4730.</p> <p>Thence S. 38° 43' 16" W.</p>
652	Road, bears northwesterly and southeasterly.
783	North bank of Webster Lake, bears N. 60° W. and S. 60° E.
980	South bank of Webster Lake, bears N. 55° W. and S. 55° E.
990.18	Cor. No. 1, and place of beginning.
	<p style="text-align: center;">WEBSTER 11 Mill Site</p> <p>Beginning at Cor. No. 1 of the WEBSTER 11 mill site, identical with Cors. Nos. 1 of the WEBSTER 9, WEBSTER 10, and WEBSTER 12 mill sites of this survey.</p> <p>Thence S. 50° 31' E.</p>
114	South bank of Webster Lake, bears N. 40° W. and S. 40° E.
219.00	<p>The true point for Cor. No. 2, identical with Cors. Nos. 2 of the WEBSTER 12, WEBSTER 14, and WEBSTER 13 mill sites of this survey.</p> <p>This corner falls in Webster Lake where a monument cannot be established.</p> <p>Thence S. 39° 30' 09" W.</p>
55	South bank of Webster Lake, bears N. 35° W. and S. 35° E.
475	Road, bears N. 10° W. and S. 10° E.
989.51	<p>Cor. No. 3, identical with Cor. No. 3 of the WEBSTER 13 mill site of this survey.</p> <p>Set an iron post, 2 ft. long, 1 ins. diam., 15 ins. in the ground, with brass cap mkd. WEB 11-3-4730 and WEB 13-3-4730.</p> <p>Thence N. 50° 31' W.</p>
218.68	Cor. No. 4, identical with Cor. No. 4 of the WEBSTER 9 mill site of this survey.



FEET	
	Thence N. 39° 29' 01" E.
756	Road, bears N. 15° E. and S. 15° W.
989.50	Cor. No. 1, and place of beginning.
	WEBSTER 12 Mill Site
	Beginning at Cor. No. 1 of the WEBSTER 12 mill site, identical with Cors. Nos. 1 of the WEBSTER 11, WEBSTER 9, and WEBSTER 10 mill sites of this survey.
	Thence S. 50° 31' E.
114	South bank of Webster Lake, bears N. 40° W. and S. 40° E.
219.00	The true point for Cor. No. 2, identical with Cors. Nos. 2 of the WEBSTER 14, WEBSTER 13, and WEBSTER 11 mill sites of this survey, previously described.
	Thence N. 38° 43' 53" E.
332	North bank of Webster Lake, bears West and S. 30° E.
498	Road, bears northwesterly and southeasterly.
990.11	Cor. No. 3, identical with Cor. No. 3 of the WEBSTER 14 mill site of this survey.
	Set an iron post, 2 ft. long, 1 ins. diam., 12 ins. in the ground, with brass cap mkd. WEB 12-3-4730 and WEB 14-3-4730.
	Thence N. 50° 29' 50" W.
219.18	Cor. No. 4, identical with Cor. No. 4 of the WEBSTER 10 mill site of this survey.
	Thence S. 38° 43' 16" W.
652	Road, bears northwesterly and southeasterly.
783	North bank of Webster Lake, bears N. 60° W. and S. 60° E.
980	South bank of Webster Lake, bears N. 55° W. and S. 55° E.
990.18	Cor. No. 1, and place of beginning

FEET	
	<p>WEBSTER 13 Mill Site</p> <p>At the true point for Cor. No. 1 of the WEBSTER 13 mill site, identical with Cors. Nos. 1 of the WEBSTER 14, WEBSTER 16, and WEBSTER 15 mill sites of this survey.</p> <p>This corner falls in Webster Lake where a monument cannot be established; from which</p> <p style="padding-left: 40px;">The west <math>\frac{1}{4}</math> sec. cor. of sec. 18, T.1 N., R.15 E., bears N. <math>83^{\circ} 53' 18''</math> E., 2497.04 ft. dist., previously described.</p> <p style="padding-left: 40px;">Thence N. <math>50^{\circ} 31'</math> W.</p>
218.95	<p>The true point for Cor. No. 2, identical with Cors. Nos. 2 of the WEBSTER 11, WEBSTER 12, and WEBSTER 14 mill sites of this survey, previously described.</p> <p style="padding-left: 40px;">Thence S. <math>39^{\circ} 30' 09''</math> W.</p>
55	<p>South bank of Webster Lake, bears N. <math>35^{\circ}</math> W. and S. <math>35^{\circ}</math> E.</p>
475	<p>Road, bears N. <math>10^{\circ}</math> W. and S. <math>10^{\circ}</math> E.</p>
989.51	<p>Cor. No. 3, identical with Cor. No. 3 of the WEBSTER 11 mill site of this survey.</p> <p style="padding-left: 40px;">Thence S. <math>50^{\circ} 31'</math> E.</p>
117	<p>Road, bears northeasterly and southwesterly.</p>
218.99	<p>Cor. No. 4, identical with Cor. No. 4 of the WEBSTER 15 mill site of this survey.</p> <p>Set an iron post, 2 ft. long, 1 ins. diam., 16 ins. in the ground, with brass cap mkd. WEB 13-4-4730 and WEB 15-4-4730.</p> <p style="padding-left: 40px;">Thence N. <math>39^{\circ} 29' 59''</math> E.</p>
770	<p>South bank of Webster Lake, bears North and S. <math>10^{\circ}</math> E.</p>
989.51	<p>Cor. No. 1, and place of beginning.</p>

FEET	
	WEBSTER 14 Mill Site
	Beginning at the true point for Cor. No. 1 of the WEBSTER 14 mill site, identical with Cors. Nos. 1 of the WEBSTER 16, WEBSTER 15, and WEBSTER 13 mill sites of this survey, previously described.
	Thence N. 50° 31' W.
218.95	The true point for Cor. No. 2, identical with Cors. Nos. 2 of the WEBSTER 13, WEBSTER 11, and WEBSTER 12 mill sites of this survey, previously described.
	Thence N. 38° 43' 53" E.
332	North bank of Webster Lake, bears West and S. 30° E.
498	Road, bears northwesterly and southeasterly.
990.11	Cor. No. 3, identical with Cor. No. 3 of the WEBSTER 12 mill site of this survey.
	Thence S. 50° 29' 50" E.
128	Center of local drainage, 5 ft. wide, course S. 45° W.
219.77	Cor. No. 4, identical with Cor. No. 4 of the WEBSTER 16 mill site of this survey.
	Set an iron post, 2 ft. long, 1 ins. diam., 15 ins. in the ground, with brass cap mkd. WEB 14-4-4730 and WEB 16-4-4730.
	Thence S. 38° 46' 43" W.
310	Road, bears northwesterly and southeasterly.
352	Center of local drainage, 6 ft. wide, course South.
735	North bank of Webster Lake, bears N. 30° W. and S. 30° E.
990.02	Cor. No. 1, and place of beginning.
	WEBSTER 15 Mill Site
	Beginning at the true point for Cor. No. 1 of the WEBSTER 15 mill site, identical with Cors. Nos. 1 of the WEBSTER 13, WEBSTER 14, and WEBSTER 16 mill sites of this survey, previously described.

FEET		
	Thence S. 50° 31' E.	
219.34	The true point for Cor. No. 2, identical with Cors. Nos. 2 of the WEBSTER 16, WEBSTER 18, and WEBSTER 17 mill sites of this survey.  This corner falls in Webster Lake where a monument cannot be established.	
	Thence S. 39° 31' 38" W.	
438	South bank of Webster Lake, bears N. 60° W. and S. 60° E.	
700	Center of dry wash, 14 ft. wide, course N. 65° E.	
989.50	Cor. No. 3, identical with Cor. No. 3 of the WEBSTER 17 mill site of this survey.  Set an iron post, 2 ft. long, 1 ins. diam., 11 ins. in the ground, with brass cap mkd. WEB 15-3-4730 and WEB 17-3-4730.	
	Thence N. 50° 31' W.	
140	Center of dry wash, 14 ft. wide, course N. 85° E.	
218.86	Cor. No. 4, identical with Cor. No. 4 of the WEBSTER 13 mill site of this survey.	
	Thence N. 39° 29' 59" E.	
770	South bank of Webster Lake, bears North and S. 10° E.	
989.51	Cor. No. 1, and place of beginning.	
	WEBSTER 16 Mill Site	
	Beginning at the true point for Cor. No. 1 of the WEBSTER 16 mill site, identical with Cors. Nos. 1 of the WEBSTER 15, WEBSTER 13, and WEBSTER 14 mill sites of this survey, previously described.	
	Thence S. 50° 31' E.	
219.34	The true point for Cor. No. 2, identical with Cors. Nos. 2 of the WEBSTER 18, WEBSTER 17, and WEBSTER 15 mill sites of this survey, previously described.	

FEET		
	Thence N. 38° 47' 12" E.	
181	North bank of Webster Lake, bears N. 5° W. and S. 15° E.	
413	Road, bears S. 10° W. and N. 10° E.	
989.91	Cor. No. 3, identical with Cor. No. 3 of the WEBSTER 18 mill site of this survey.  Set an iron post, 2 ft. long, 1 ins. diam., 16 ins. in the ground, with brass cap mkd. WEB 16-3-4730 and WEB 18-3-4730.	
	Thence N. 50° 29' 12" W.	
10	Center of local drainage, 6 ft. wide, course S. 75° W.	
219.47	Cor. No. 4, identical with Cor. No. 4 of the WEBSTER 14 mill site of this survey.	
	Thence S. 38° 46' 43" W.	
310	Road, bears northwesterly and southeasterly.	
352	Center of local drainage, 6 ft. wide, course South.	
735	North bank of Webster Lake, bears N. 30° W. and S. 30° E.	
990.02	Cor. No. 1, and place of beginning.	
	WEBSTER 17 Mill Site	
	At the true point for Cor. No. 1 of the WEBSTER 17 mill site, identical with Cors. Nos. 1 of the WEBSTER 18, WEBSTER 20, and WEBSTER 19 mill sites of this survey.	
	This corner falls in Webster Lake where a monument cannot be established; from which	
	The west $\frac{1}{4}$ sec. cor. of sec. 18, T. 1 N., R. 15 E., bears N. 75° 46' 07" E., 2212.60 ft. dist., previously described.	
	Thence N. 50° 31' W.	
219.00	The true point for Cor. No. 2, identical with Cors. Nos. 2 of the WEBSTER 15, WEBSTER 16, and WEBSTER 18 mill sites of this survey, previously described.	

FEET	
	Thence S. 39° 31' 38" W.
438	South bank of Webster Lake, bears N. 60° W. and S. 60° E.
700	Center of dry wash, 14 ft. wide, course N. 65° E.
989.50	Cor. No. 3, identical with Cor. No. 3 of the WEBSTER 15 mill site of this survey.
	Thence S. 50° 31' E.
219.19	Cor. No. 4, identical with Cor. No. 4 of the WEBSTER 19 mill site of this survey.
	Set an iron post, 2 ft. long, 1 ins. diam., 13 ins. in the ground, with brass cap mkd. WEB 17-4-4730 and WEB 19-4-4730.
	Thence N. 39° 31' 00" E.
361	South bank of Webster Lake, bears East and West.
989.50	Cor. No. 1, and place of beginning.
	WEBSTER 18 Mill Site
	Beginning at the true point for Cor. No. 1 of the WEBSTER 18 mill site, identical with Cors. Nos. 1 of the WEBSTER 20, WEBSTER 19, and WEBSTER 17 mill sites of this survey, previously described.
	Thence N. 50° 31' W.
219.00	The true point for Cor. No. 2, identical with Cors. Nos. 2 of the WEBSTER 17, WEBSTER 15, and WEBSTER 16 mill sites of this survey, previously described.
	Thence N. 38° 47' 12" E.
181	North bank of Webster Lake, bears N. 5° W. and S. 15° E.
413	Road, bears S. 10° W. and N. 10° E.
989.91	Cor. No. 3, identical with Cor. No. 3 of the WEBSTER 16 mill site of this survey.
	Thence S. 50° 29' 12" E.
218.56	Cor. No. 4, identical with Cor. No. 4 of the WEBSTER 20 mill site of this survey.

FEET	
	<p>Set an iron post, 2 ft. long, 1 ins. diam., 16 ins. in the ground, with brass cap mkd. WEB 18-4-4730 and WEB 20-4-4730.</p> <p style="text-align: center;">Thence S. 38° 45' 40" W.</p>
763	Road, bears N. 25° W. and S. 25° E.
888	North bank of Webster Lake, bears N. 35° W. and S. 35° E.
989.79	Cor. No. 1, and place of beginning.
	WEBSTER 19 Mill Site
	<p>Beginning at the true point for Cor. No. 1 of the WEBSTER 19 mill site, identical with Cors. Nos. 1 of the WEBSTER 17, WEBSTER 18, and WEBSTER 20 mill sites of this survey, previously described.</p> <p style="text-align: center;">Thence S. 50° 31' E.</p>
219.00	<p>The true point for Cor. No. 2, identical with Cors. Nos. 2 of the WEBSTER 20, WEBSTER 22, and WEBSTER 21 mill sites of this survey.</p> <p>This corner falls in Webster Lake where a monument cannot be established.</p> <p style="text-align: center;">Thence S. 39° 34' 08" W.</p>
403	South bank of Webster Lake, bears N. 40° W. and S. 40° E.
989.51	<p>Cor. No. 3, identical with Cor. No. 3 of the WEBSTER 21 mill site of this survey.</p> <p>Set an iron post, 2 ft. long, 1 ins. diam., 14 ins. in the ground, with brass cap mkd. WEB 19-3-4730 and WEB 21-3-4730.</p> <p style="text-align: center;">Thence N. 50° 31' W.</p>
218.09	<p>Cor. No. 4, identical with Cor. No. 4 of the WEBSTER 17 mill site of this survey.</p> <p style="text-align: center;">Thence N. 39° 31' 00" E.</p>
361	South bank of Webster Lake, bears East and West.
989.50	Cor. No. 1, and place of beginning.

FEET	
	WEBSTER 20 Mill Site
	Beginning at the true point for Cor. No. 1 of the WEBSTER 20 mill site, identical with Cors. Nos. 1 of the WEBSTER 19, WEBSTER 17, and WEBSTER 18 mill sites of this survey, previously described.
	Thence S. 50° 31' E.
219.00	The true point for Cor. No. 2, identical with Cors. Nos. 2 of the WEBSTER 22, WEBSTER 21, and WEBSTER 19 mill sites of this survey, previously described.
	Thence N. 38° 48' 46" E.
177	North bank of Webster Lake, bears N. 85 ° W. and S. 85° E.
289	Road, bears West and N. 80° E.
989.78	Cor. No. 3, identical with Cor. No. 3 of the WEBSTER 22 mill site of this survey.
	Set an iron post, 2 ft. long, 1 ins. diam., 12 ins. in the ground, with brass cap mkd. WEB 20-3-4730 and WEB 22-3-4730.
	Thence N. 50° 31' W.
219.90	Cor. No. 4, identical with Cor. No. 4 of the WEBSTER 18 mill site of this survey.
	Thence S. 38° 45' 40" W.
763	Road, bears N. 25° W. and S. 25° E.
888	North bank of Webster Lake, bears N. 35° W. and S. 35° E.
989.79	Cor. No. 1, and place of beginning.
	WEBSTER 21 Mill Site
	At the true point for Cor. No. 1 of the WEBSTER 21 mill site, identical with Cors. Nos. 1 of the WEBSTER 22, WEBSTER 24, and WEBSTER 23 mill sites of this survey.
	This corner falls in Webster Lake where a monument cannot be established; from which
	The west ¼ sec. cor. of secs. 18, T. 11 N., R. 15 E., bears N. 65° 30' E., 1985.07 ft. dist., previously described.



FEET		
	Thence N. 50° 31' W.	
219.20	The true point for Cor. No. 2, identical with Cors. Nos. 2 of the WEBSTER 19, WEBSTER 20, and WEBSTER 22 mill sites of this survey, previously described.	
	Thence S. 39° 34' 08" W.	
403	South bank of Webster Lake, bears N. 40° W. and S. 40° E.	
989.51	Cor. No. 3, identical with Cor. No. 3 of the WEBSTER 19 mill site of this survey.	
	Thence S. 50° 31' E.	
218.72	Cor. No. 4, identical with Cor. No. 4 of the WEBSTER 23 mill site of this survey.  Set an iron post, 2 ft. long, 1 ins. diam., 18 ins. in the ground, with brass cap mkd. WEB 21-4-4730 and WEB 23-4-4730.	
	Thence N. 39° 35' 48" E.	
540	South bank of Webster Lake, bears N. 35° W. and S. 25° E.	
989.50	Cor. No. 1, and place of beginning.	
	WEBSTER 22 Mill Site	
	Beginning at the true point for Cor. No. 1 of the WEBSTER 22 mill site, identical with Cors. Nos. 1 of the WEBSTER 24, WEBSTER 23, and WEBSTER 21 mill sites of this survey, previously described.	
	Thence N. 50° 31' W.	
219.20	The true point for Cor. No. 2, identical with Cors. Nos. 2 of the WEBSTER 21, WEBSTER 19, and WEBSTER 20 mill sites of this survey, previously described.	
	Thence N. 38° 48' 46" E.	
177	North bank of Webster Lake, bears N. 85° W. and S. 85° E.	
289	Road, bears West and N. 80° E.	
989.78	Cor. No. 3, identical with Cor. No. 3 of the WEBSTER 20 mill site of this survey.	
	Thence S. 50° 31' E.	
166	Center of local drainage, 6 ft. wide, course S. 45° W.	
219.69	Cor. No. 4, identical with Cor. No. 4 of the WEBSTER 24 mill site of this survey.	

(This form bound on left side)

FEET	
	<p>Set an iron post, 2 ft. long, 1 ins. diam., 15 ins. in the ground, with brass cap mkd. WEB 22-4-4730 and WEB 24-4-4730.</p> <p>Thence S. 38° 50' 28" W.</p>
281	Center of local drainage, 8 ft. wide, course N. 60° W.
376	Road, bears N. 50° E. and S. 50° W.
956	North bank of Webster Lake, bears N. 30° W. and S. 15° E.
989.77	Cor. No. 1, and place of beginning.
	<p style="text-align: center;">WEBSTER 23 Mill Site</p> <p>Beginning at the true point for Cor. No. 1 of the WEBSTER 23 mill site, identical with Cors. Nos. 1 of the WEBSTER 21, WEBSTER 22, and WEBSTER 24 mill sites of this survey, previously described</p> <p>Thence S. 50° 31' E.</p>
219.20	<p>The true point for Cor. No. 2, identical with Cors. Nos. 2 of the WEBSTER 24, WEBSTER 26, and WEBSTER 25 mill sites of this survey.</p> <p>This corner falls in Webster Lake where a monument cannot be established</p> <p>Thence S. 39° 38' 39" W.</p>
511	South bank of Webster Lake, bears N. 50° W. and S. 50° E.
989.50	<p>Cor. No. 3, identical with Cor. No. 3 of the WEBSTER 25 mill site of this survey</p> <p>Set an iron post, 2 ft. long, 1 ins. diam., 17 ins. in the ground, with brass cap mkd. WEB 23-3-4730 and WEB 25-3-4730</p> <p>Thence N. 50° 31' W.</p>
218.39	<p>Cor. No. 4, identical with Cor. No. 4 of the WEBSTER 21 mill site of this survey.</p> <p>Thence N. 39° 35' 48" E.</p>

FEET	
540	South bank of Webster Lake, bears N. 35° W. and S. 25° E.
989.50	Cor. No. 1, and place of beginning.
WEBSTER 24 Mill Site	
Beginning at the true point for Cor. No. 1 of the WEBSTER 24 mill site, identical with Cors. Nos. 1 of the WEBSTER 23, WEBSTER 21, and WEBSTER 22 mill sites of this survey, previously described.	
Thence S. 50° 31' E.	
219.20	The true point for Cor. No. 2, identical with Cors. Nos. 2 of the WEBSTER 26, WEBSTER 25, and WEBSTER 23 mill sites of this survey, previously described.
Thence N. 38° 52' 24" E.	
14	North bank of Webster Lake, bears N. 55° W. and S. 52° E.
322	Road, bears northwesterly and southeasterly.
989.77	Cor. No. 3, identical with Cor. No. 3 of the WEBSTER 26 mill site of this survey.
Set an iron post, 2 ft. long, 1 ins. diam., 11 ins. in the ground, with brass cap mkd. WEB 24-3-4730 and WEB 26-3-4730.	
Thence N. 50° 31' W.	
48	Center of local drainage, 6 ft. wide, course West.
219.76	Cor. No. 4, identical with Cor. No. 4 of the WEBSTER 22 mill site of this survey.
Thence S. 38° 50' 28" W.	
281	Center of local drainage, 8 ft. wide, course N. 60° W.
376	Road, bears N. 50° E. and S. 50° W.
956	North bank of Webster Lake, bears N. 30° W. and S. 15° E.
989.77	Cor. No. 1, and place of beginning.

FEET	
	<p>WEBSTER 25 Mill Site</p> <p>At the true point for Cor. No. 1 of the WEBSTER 25 mill site, identical with Cors. Nos. 1 of the WEBSTER 26, WEBSTER 28, and WEBSTER 27 mill sites of this survey.</p> <p>This corner falls in Webster Lake, where a monument cannot be established; from which</p> <p style="padding-left: 40px;">The west <math>\frac{1}{4}</math> sec. cor. of sec. 18, T. 11 N., R. 15 E., bears N. <math>53^{\circ} 06' 42''</math> E., 1835.59 ft. dist., previously described.</p> <p style="padding-left: 40px;">Thence N. <math>50^{\circ} 31'</math> W.</p>
219.00	<p>The true point for Cor. No. 2, identical with Cors. Nos. 2 of the WEBSTER 23, WEBSTER 24, and WEBSTER 26 mill sites of this survey, previously described.</p> <p style="padding-left: 40px;">Thence S. <math>39^{\circ} 38' 39''</math> W.</p>
511	<p>South bank of Webster Lake, bears N. <math>50^{\circ}</math> W. and S. <math>50^{\circ}</math> E.</p>
989.50	<p>Cor. No. 3, identical with Cor. No. 3 of the WEBSTER 23 mill site of this survey.</p> <p style="padding-left: 40px;">Thence S. <math>50^{\circ} 31'</math> E.</p>
88	<p>Center of local drainage, 8 ft. wide, course N. <math>50^{\circ}</math> E.</p>
219.72	<p>Cor. No. 4, identical with Cor. No. 4 of the WEBSTER 27 mill site of this survey.</p> <p>Set an iron post, 2 ft. long, 1 ins. diam., 18 ins. in the ground, with brass cap mkd. WEB 25-4-4730 and WEB 27-4-4730.</p> <p style="padding-left: 40px;">Thence N. <math>39^{\circ} 36' 09''</math> E.</p>
432	<p>South bank of Webster Lake, bears N. <math>45^{\circ}</math> W. and S. <math>45^{\circ}</math> E.</p>
989.51	<p>Cor. No. 1, and place of beginning.</p>
	<p>WEBSTER 26 Mill Site</p> <p>Beginning at the true point for Cor. No. 1 of the WEBSTER 26 mill site, identical with Cors. Nos. 1 of the WEBSTER 28, WEBSTER 27, and WEBSTER 25 mill sites of this survey, previously described.</p>

FEET	
	Thence N. 50° 31' W.
219.00	The true point for Cor. No. 2, identical with Cors. Nos. 2 of the WEBSTER 25, WEBSTER 23, and WEBSTER 24 mill sites of this survey, previously described
	Thence N. 38° 52' 24" E.
14	North bank of Webster Lake, bears N. 55° W. and S. 52° E.
322	Road, bears northwesterly and southeasterly.
989.77	Cor. No. 3, identical with Cor. No. 3 of the WEBSTER 24 mill site of this survey.
	Thence S. 50° 31' E.
219.74	Cor. No. 4, identical with Cor. No. 4 of the WEBSTER 28 mill site of this survey.
	Set an iron post, 2 ft. long, 1 ins. diam., 14 ins. in the ground, with brass cap mkd. WEB 26-4-4730 and WEB 28-4-4730.
	Thence S. 38° 54' 59" W.
127	Road junction, roads bear easterly, southeasterly, and southwesterly.
840	North bank of Webster Lake, bears N. 80° W. and S. 80° E.
989.75	Cor. No. 1, and place of beginning.
	WEBSTER 27 Mill Site
	Beginning at the true point for Cor. No. 1 of the WEBSTER 27 mill site, identical with Cors. Nos. 1 of the WEBSTER 25, WEBSTER 26, and WEBSTER 28 mill sites of this survey, previously described.
	Thence S. 50° 31' E.
219.00	The true point for Cor. No. 2, identical with Cors. Nos. 2 of the WEBSTER 28, WEBSTER 30, and WEBSTER 29 mill sites of this survey, previously described.
	This corner falls in Webster Lake, where a monument cannot be established.
	Thence S. 39° 35' 35" W.
490	South bank of Webster Lake, bears East and West.
989.50	Cor. No. 3, identical with Cor. No. 3 of the WEBSTER 29 mill site of this survey.

FEET	
	<p>Set an iron post, 2 ft. long, 1 ins. diam., 13 ins. in the ground, with brass cap mkd. WEB 27-3-4730 and WEB 29-3-4730.</p> <p>Thence N. 50° 31' W.</p>
219.15	<p>Cor. No. 4, identical with Cor. No. 4 of the WEBSTER 25 mill site of this survey.</p> <p>Thence N. 39° 36' 09" E.</p>
432	<p>South bank of Webster Lake, bears N. 45° W. and S. 45° E.</p>
989.51	<p>Cor. No. 1, and place of beginning.</p>
	<p>WEBSTER 28 Mill Site</p>
	<p>Beginning at the true point for Cor. No. 1 of the WEBSTER 28 mill site, identical with Cors. Nos. 1 of the WEBSTER 27, WEBSTER 25, and WEBSTER 26 mill sites of this survey, previously described.</p> <p>Thence S. 50° 31' E.</p>
219.00	<p>The true point for Cor. No. 2, identical with Cors. Nos. 2 of the WEBSTER 30, WEBSTER 29, and WEBSTER 27 mill sites of this survey, previously described.</p> <p>Thence N. 38° 57' 44" E.</p>
275	<p>North bank of Webster Lake, bears N. 85° W. and S. 85° E.</p>
860	<p>Road, bears N. 48° W. and S. 48° E.</p>
989.75	<p>Cor. No. 3, identical with Cor. No. 3 of the WEBSTER 30 mill site of this survey.</p>
	<p>Set an iron post, 2 ft. long, 1 ins. diam., 16 ins. in the ground, with brass cap mkd. WEB 28-3-4730 and WEB 30-3-4730.</p> <p>Thence N. 50° 31' W.</p>
41	<p>Road, bears northwesterly and northeasterly.</p>
219.78	<p>Cor. No. 4, identical with Cor. No. 4 of the WEBSTER 26 mill site of this survey.</p> <p>Thence S. 38° 54' 59" W.</p>

FEET	
127	Road junction, roads bear easterly, southeasterly, and southwesterly.
840	North bank of Webster Lake, bears N. 80° W. and S. 80° E.
989.75	Cor. No. 1, and place of beginning.
<p>WEBSTER 29 Mill Site</p> <p>At the true point for Cor. No. 1 of the WEBSTER 29 mill site, identical with Cors. Nos. 1 of the WEBSTER 30, WEBSTER 32, and WEBSTER 31 mill sites of this survey.</p> <p>This corner falls in Webster Lake, where a monument cannot be established; from which</p> <p style="padding-left: 40px;">The west <math>\frac{1}{4}</math> sec. cor. of sec. 18, T. 1 N., R. 15 E., bears N. 39° 18' 25" E., 1783.93 ft. dist., previously described.</p> <p style="padding-left: 40px;">Thence N. 50° 31' W.</p>	
219.00	The true point for Cor. No. 2, identical with Cors. Nos. 2 of the WEBSTER 27, WEBSTER 28, and WEBSTER 30 mill sites of this survey, previously described.
<p style="padding-left: 40px;">Thence S. 39° 35' 35" W.</p>	
490	South bank of Webster Lake, bears East and West.
989.50	Cor. No. 3, identical with Cor. No. 3 of the WEBSTER 27 mill site of this survey.
<p style="padding-left: 40px;">Thence S. 50° 31' E.</p>	
218.84	Cor. No. 4, identical with Cor. No. 4 of the WEBSTER 31 mill site of this survey.
<p style="padding-left: 40px;">Set an iron post, 2 ft. long, 1 ins. diam., 15 ins. in the ground, with brass cap mkd. WEB 29-4-4730 and WEB 31-4-4730</p> <p style="padding-left: 40px;">Thence N. 39° 36' 11" E.</p>	
689	South bank of Webster Lake, bears S. 85° W. and S. 88° E.
989.50	Cor. No. 1, and place of beginning.



FEET	
	<p>WEBSTER 30 Mill Site</p> <p>Beginning at the true point for Cor. No. 1 of the WEBSTER 30 mill site, identical with Cors. Nos. 1 of the WEBSTER 32, WEBSTER 31, and WEBSTER 29 mill sites of this survey, previously described.</p> <p style="text-align: center;">Thence N. 50° 31' W.</p>
219.00	<p>The true point for Cor. No. 2, identical with Cors. Nos. 2 of the WEBSTER 29, WEBSTER 27, and WEBSTER 28 mill sites of this survey, previously described.</p> <p style="text-align: center;">Thence N. 38° 57' 44" E.</p>
275	<p>North bank of Webster Lake, bears N. 85° W. and S. 85° E.</p>
860	<p>Road, bears N. 48° W. and S. 48° E.</p>
989.75	<p>Cor. No. 3, identical with Cor. No. 3 of the WEBSTER 28 mill site of this survey.</p> <p style="text-align: center;">Thence S. 50° 31' E.</p>
200	<p>Road, bears N. 35° E. and S. 40° W.</p>
218.98	<p>Cor. No. 4, identical with Cor. No. 4 of the WEBSTER 32 mill site of this survey.</p> <p>Set an iron post, 2 ft. long, 1 ins. diam., 11 ins. in the ground, with brass cap mkd. WEB 30-4-4730 and WEB 32-4-4730.</p> <p style="text-align: center;">Thence S. 38° 57' 38" W.</p>
729	<p>North bank of Webster Lake, bears N. 15° W. and S. 15° E.</p>
989.75	<p>Cor. No. 1, and place of beginning.</p>
	<p>WEBSTER 31 Mill Site</p> <p>Beginning at the true point for Cor. No. 1 of the WEBSTER 31 mill site, identical with Cors. Nos. 1 of the WEBSTER 29, WEBSTER 30, and WEBSTER 32 mill sites of this survey, previously described.</p> <p style="text-align: center;">Thence S. 50° 31' E.</p>
219.00	<p>The true point for Cor. No. 2, identical with Cors. Nos. 2 of the WEBSTER 32, WEBSTER 34, and WEBSTER 33 mill sites of this survey, previously described.</p>



FEET	
	<p>This corner falls in Webster Lake, where a monument cannot be established.</p> <p>Thence S. 39° 34' 33" W.</p>
249	<p>South bank of Webster Lake, bears S. 60° E. and N. 60° W.</p>
989.50	<p>Cor. No. 3, identical with Cor. No. 3 of the WEBSTER 33 mill site of this survey.</p> <p>Set an iron post, 2 ft. long, 1 ins. diam., 14 ins. in the ground, with brass cap mkd. WEB 31-3-4730 and WEB 33-3-4730.</p> <p>Thence N. 50° 31' W.</p>
219.46	<p>Cor. No. 4, identical with Cor. No. 4 of the WEBSTER 29 mill site of this survey.</p> <p>Thence N. 39° 36' 11" E.</p>
689	<p>South bank of Webster Lake, bears S. 85° W. and S. 88° E.</p>
989.50	<p>Cor. No. 1, and place of beginning.</p>
<p>WEBSTER 32 Mill Site</p>	
	<p>Beginning at the true point for Cor. No. 1 of the WEBSTER 32 mill site, identical with Cors. Nos. 1 of the WEBSTER 31, WEBSTER 29, and WEBSTER 30 mill sites of this survey, previously described.</p> <p>Thence S. 50° 31' E.</p>
219.00	<p>The true point for Cor. No. 2, identical with Cors. Nos. 2 of WEBSTER 34, WEBSTER 33, and WEBSTER 31 mill sites of this survey, previously described.</p> <p>Thence N. 39° 01' 08" E.</p>
256	<p>North bank of Webster Lake, bears N. 55° W. and S. 55° E.</p>
838	<p>Center of local drainage, 5 ft. wide, course SE.</p>
989.74	<p>Cor. No. 3, identical with Cor. No. 3 of the WEBSTER 34 mill site of this survey.</p> <p>Set an iron post, 2 ft. long, 1 ins. diam., 18 ins. in the ground, with brass cap mkd. WEB 32-3-4730 and WEB 34-3-4730.</p> <p>Thence N. 50° 31' W.</p>
139	<p>Center of local drainage 5 ft. wide, course South.</p>

FEET	
220.00	<p>Cor. No. 4, identical with Cor. No. 4 of the WEBSTER 30 mill site of this survey.</p> <p>Thence S. 38° 57' 38" W.</p>
729	<p>North bank of Webster Lake, bears N. 15° W. and S. 15° E.</p>
989.75	<p>Cor. No. 1, and place of beginning.</p>
	<p style="text-align: center;">WEBSTER 33 Mill Site</p> <p>At the true point for Cor. No. 1 of the WEBSTER 33 mill site, identical with Cors. Nos. 1 of the WEBSTER 34, WEBSTER 36, and WEBSTER 35 mill sites of this survey.</p> <p>This corner falls in Webster Lake where a monument cannot be established; from which</p> <p style="padding-left: 40px;">The west <math>\frac{1}{4}</math> sec. cor. of sec. 18, T. 1 N., R. 15 E., bears N. 25° 33' 10" E., 1837.98 ft. dist., previously described.</p> <p style="text-align: center;">Thence N. 50° 31' W.</p>
218.00	<p>The true point for Cor. No. 2, identical with Cors. Nos. 2 of the WEBSTER 31, WEBSTER 32, and WEBSTER 34 mill sites of this survey, previously described.</p> <p style="text-align: center;">Thence S. 39° 34' 33" W.</p>
249	<p>South bank of Webster Lake, bears S. 60° E. and N. 60° W.</p>
989.50	<p>Cor. No. 3, identical with Cor. No. 3 of the WEBSTER 31 mill site of this survey.</p> <p style="text-align: center;">Thence S. 50° 31' E.</p>
218.94	<p>Cor. No. 4, identical with Cor. No. 6 of the WEBSTER 35 mill site of this survey.</p> <p>Set an iron post, 2 ft. long, 1 ins. diam., 14 ins. in the ground, with brass cap mkd. WEB 33-4-4730 and WEB 35-6-4730.</p> <p style="text-align: center;">Thence N. 39° 31' 16" E.</p>
762	<p>South bank of Webster Lake, bears N. 50° W. and S. 45° E.</p>
989.50	<p>Cor. No. 1, and place of beginning.</p>

FEET	
	WEBSTER 34 Mill Site
	Beginning at the true point for Cor. No. 1 of the WEBSTER 34 mill site, identical with Cors. Nos. 1 of the WEBSTER 36, WEBSTER 35, and WEBSTER 33 mill sites of this survey, previously described.
	Thence N. 50° 31' W.
218.00	The true point for Cor. No. 2, identical with Cors. Nos. 2 of the WEBSTER 33, WEBSTER 31, and WEBSTER 32 mill sites of this survey, previously described.
	Thence N. 39° 01' 08" E.
256	North bank of Webster Lake, bears N. 55° W. and S. 55° E.
838	Center of local drainage, 5 ft. wide, course SE.
989.74	Cor. No. 3, identical with Cor. No. 3 of the WEBSTER 32 mill site of this survey.
	Thence S. 50° 31' E.
221.00	Cor. No. 4, identical with Cors. Nos. 4 of the WEBSTER 44 and WEBSTER 36 mill sites of this survey.
	Set an iron post, 2 ft. long, 1 ins. diam., 17 ins. in the ground, with brass cap mkd. WEB 34-4, WEB 44-4, and WEB 36-4-4730.
	Thence S. 39° 11' 34" W.
318	North bank of Webster Lake, bears N. 15° E. and South.
989.73	Cor. No. 1, and place of beginning.
	WEBSTER 35 Mill Site
	Beginning at the true point for Cor. No. 1 of the WEBSTER 35 mill site, identical with Cors. Nos. 1 of the WEBSTER 33, WEBSTER 34, and WEBSTER 36 mill sites of this survey, previously described.
	Thence S. 50° 31' E.
220.00	The true point for Cor. No. 2, identical with Cors. Nos. 2 of the WEBSTER 36, WEBSTER 38, and WEBSTER 37 mill sites of this survey.
	This corner falls in Webster Lake where a monument cannot be established.

FEET	
	Thence S. 39° 27' 06" W.
230	South bank of Webster Lake, bears N. 75° W. and S. 65° E.
652	Road, bears N. 55° W. and S. 50° E.
739.18	Cor. No. 3, identical with Cor. No. 3 of the WEBSTER 37 mill site of this survey, established on line 4-1 Sur. No. 3015 Old Ironsides lode at a point from which the true point for Cor. No. 1 bears S. 83° 35' 10" E., 1364.99 ft. dist.  Set an iron post, 2 ft. long, 1 ins. diam., 18 ins. in the ground, with brass cap mkd. WEB 35-3-4730 and WEB 37-3-4730.
	Thence N: 83° 35' 10" W.
26	Road, bears northwesterly and southwesterly.
134.93	Cor. No. 4, identical with Cor. No. 4 Sur. No. 3015 Old Ironsides lode.  To the top surface of the 4-ins. diam. steel-capped pipe marking Cor. No. 4 Sur. No. 3015 Old Ironsides lode, I add the following: WEB 35-4-4730.
	Thence S. 6° 32' 10" W.
132	Road, bears N. 60° E. and S. 60° W.
210.55	Cor. No. 5, established on line 3-4 Sur. No. 3015 Old Ironsides lode at a point from which Cor. No. 3 bears S. 6° 32' 10" W., 390.07 ft. dist.  Set an iron post, 2 ft. long, 1 ins. diam., 16 ins. in the ground, with brass cap mkd. WEB 35-5-4730.
	Thence N. 50° 31' W.
88	Road, bears N. 70° E. and West.
222.51	Cor. No. 6, identical with Cor. No. 4 of the WEBSTER 33 mill site of this survey.
	Thence N. 39° 31' 16" E.
762	South bank of Webster Lake, bears N. 50° W. and S. 45° E.
989.50	Cor. No. 1, and place of beginning.

FEET	
	<p>WEBSTER 36 Mill Site</p> <p>Beginning at the true point for Cor. No. 1 of the WEBSTER 36 mill site, identical with Cors. Nos. 1 of the WEBSTER 35, WEBSTER 33, and WEBSTER 34 mill sites of this survey, previously described.</p> <p style="text-align: center;">Thence S. 50° 31' E.</p>
220.00	<p>The true point for Cor. No. 2, identical with Cors. Nos. 2 of the WEBSTER 38, WEBSTER 37, and WEBSTER 35 mill sites of this survey, previously described.</p> <p style="text-align: center;">Thence N. 39° 11' 37" E.</p>
731	<p>North bank of Webster Lake, bears northwesterly and southeasterly.</p>
989.72	<p>Cor. No. 3, identical with Cor. No. 3 of the WEBSTER 38 mill site, on line 3-4 of the WEBSTER 44 mill site of this survey.</p> <p>Set an iron post, 2 ft. long, 1 ins. diam., 12 ins. in the ground, with brass cap mkd. WEB 36-3-4730 and WEB 38-3-4730.</p> <p style="text-align: center;">Thence N. 50° 31' W.</p>
220.00	<p>Cor. No. 4, identical with Cors. Nos. 4 of the WEBSTER 34 and WEBSTER 44 mill sites of this survey.</p> <p style="text-align: center;">Thence S. 39° 11' 34" W.</p>
318	<p>North bank of Webster Lake, bears N. 15° E. and South.</p>
989.73	<p>Cor. No. 1, and place of beginning.</p>
	<p>WEBSTER 37 Mill Site</p> <p>At the true point for Cor. No. 1 of the WEBSTER 37 mill site, identical with Cor. No. 1 of the WEBSTER 39 mill site, on line 1-2 of the WEBSTER 40 mill site of this survey.</p> <p>This corner falls in Webster Lake where a monument cannot be established; from which west</p> <p style="text-align: center;">The <math>\frac{1}{4}</math> sec. cor. of sec. 18, T.1 N., R.15 E., bears N. 10° 08' 58" E., 2046.30 ft. dist., previously described.</p>

FEET	
	Thence N. 50° 31' W.
120.00	Intersect the true point for Cors. Nos. 1 of the WEBSTER 38 and WEBSTER 40 mill sites of this survey, hereinafter described.
340.00	The true point for Cor. No. 2, identical with Cors. Nos. 2 of the WEBSTER 35, WEBSTER 36, and WEBSTER 38 mill sites of this survey, previously described.
	Thence S. 39° 27' 06" W.
230	South bank of Webster Lake, bears N. 75° W. and S. 65° E.
652	Road, bears N. 55° W. and S. 50° E.
739.18	Cor. No. 3, identical with Cor. No. 3 of the Webster 35 mill site of this survey, established on line 4-1 Sur. No. 3015 Old Ironsides lode at a point from which Cor. No. 4 bears N. 83° 35' 10" W., 134.93 ft. dist.
	Thence S. 83° 35' 10" E.
150	Road, bears N. 50° W. and S. 45° E.
194	Road, bears S. 60° W. and N. 50° E.
417.17	Cor. No. 4, identical with Cor. No. 4 of the WEBSTER 39 mill site of this survey, established on line 4-1 Sur. No. 3015 Old Ironsides lode.  Set an iron post, 2 ft. long, 1 ins. diam., 15 ins. in the ground, with brass cap mkd. WEB 37-4-4730 and WEB 39-4-4730.
	Thence N. 38° 21' 47" E.
58	Road, bears N. 75° W. and S. 75° E.
261	South bank of Webster Lake, bears N. 45° W. and S. 70° E.
511.64	Cor. No. 1, and place of beginning.
	WEBSTER 38 Mill Site
	At the true point for Cor. No. 1 of the WEBSTER 38 mill site, identical with Cor. No. 1 of the WEBSTER 40 mill site, on line 1-2 of the WEBSTER 37 mill site of this survey.

FEET		
	<p>This corner falls in Webster Lake where a monument cannot be established; from which west The <math>\frac{1}{4}</math> sec. cor. of sec. 18, T. 1 N., R. 15 E., bears N. <math>13^{\circ} 09' 44''</math> E., 1990.27 ft. dist., previously described.</p> <p>Thence N. <math>50^{\circ} 31'</math> W.</p>	
220.00	<p>The true point for Cor. No. 2, identical with Cors. Nos. 2 of the WEBSTER 37, WEBSTER 35, and WEBSTER 36 mill sites of this survey, previously described.</p> <p>Thence N. <math>39^{\circ} 11' 37''</math> E.</p>	
731	<p>North bank of Webster Lake, bears northwesterly and southeasterly.</p>	
989.72	<p>Cor. No. 3, identical with Cor. No. 3 of the WEBSTER 36 mill site, on line 3-4 of the WEBSTER 44 mill site of this survey.</p> <p>Thence S. <math>50^{\circ} 31'</math> E.</p>	
220.00	<p>Cor. No. 4, identical with Cors. Nos. 3 of the WEBSTER 44 and WEBSTER 45 mill sites, and Cor. No. 4 of the WEBSTER 40 mill site of this survey.</p> <p>Set an iron post, 2 ft. long, 1 ins. diam., 18 ins. in the ground, with brass cap mkd. WEB 38-4, WEB 44-3, WEB 45-3, and WEB 40-4-4730.</p> <p>Thence S. <math>39^{\circ} 11' 37''</math> W.</p>	
458	<p>North bank of Webster Lake, bears N. <math>80^{\circ}</math> E. and S. <math>80^{\circ}</math> W.</p>	
989.72	<p>Cor. No. 1, and place of beginning.</p>	
	<p style="text-align: center;">WEBSTER 39 Mill Site</p> <p>Beginning at the true point for Cor. No. 1 of the WEBSTER 39 mill site, identical with Cor. No. 1 of the WEBSTER 37 mill site, on line 1-2 of the WEBSTER 40 mill site of this survey, previously described.</p> <p>Thence S. <math>50^{\circ} 31'</math> E.</p>	
100.00	<p>Intersect the true point for Cors. Nos. 2 of the WEBSTER 40 and WEBSTER 41 mill sites of this survey, hereinafter described.</p>	



FEET	
315.00	Intersect the true point for Cors. Nos. 1 of the WEBSTER 41 and WEBSTER 42 mill sites of this survey, hereinafter described.
364	South bank of Webster Lake, bears N. 77° E. and S. 77° W.
435.00	Cor. No. 2, identical with Cor. No. 2 of the WEBSTER 42 mill site and Cor. No. 5 of the WEBSTER 43 mill site of this survey.
	Set an iron post, 2 ft. long, 1 ins. diam., 14 ins. in the ground, with brass cap mkd. WEB 39-2, WEB 42-2, and WEB 43-5-4730.
	Thence S. 51° 23' 30" E.
44.34	North bank of southwest arm of Webster Lake, bears N. 35° E. and S. 35° W.
369.34	The true point for Cor. No. 3, identical with Cor. No. 4 of the WEBSTER 43 mill site of this survey, and Cor. No. 1 Sur. No. 3015 Old Ironsides lode.
	This corner falls in Webster Lake where a monument cannot be established.
	Thence N. 83° 35' 10" W.
395	North bank of southwest arm of Webster Lake, bears N. 55° E. and S. 55° W.
947.83	Cor. No. 4, identical with Cor. No. 4 of the WEBSTER 37 mill site of this survey, established on line 4-1 Sur. No. 3015 Old Ironsides lode at a point from which Cor. No. 4 bears N. 83° 35' 10" W., 552.09 ft. dist.
	Thence N. 38° 21' 47" E.
261	South bank of Webster Lake, bears N. 45° W. and S. 70° E.
511.64	Cor. No. 1, and place of beginning.
	WEBSTER 40 Mill Site
	Beginning at the true point for Cor. No. 1 of the WEBSTER 40 mill site, identical with Cor. No. 1 of the WEBSTER 38 mill site, on line 1-2 of the WEBSTER 37 mill site of this survey, previously described.



FEET	
	Thence S. 50° 31' E.
120.00	Intersect the true point for Cors. Nos. 1 of the WEBSTER 39 and WEBSTER 37 mill sites of this survey, previously described.
220.00	The true point for Cor. No. 2, identical with Cor. No. 2 of the WEBSTER 41 mill site, on line 1-2 of the WEBSTER 39 mill site of this survey.
	This corner falls in Webster Lake where a monument cannot be established.
	Thence N. 39° 09' 46" E.
796	North bank of Webster Lake, bears N. 70° W. and S. 70° E.
989.73	Cor. No. 3, identical with Cor. No. 3 of the WEBSTER 41 mill site, on line 3-4 of the WEBSTER 45 mill site of this survey.
	Set an iron post, 2 ft. long, 1 ins. diam., 17 ins. in the ground, with brass cap mkd. WEB 40-3, and WEB 41-3-4730.
	Thence N. 50° 31' W.
219.47	Cor. No. 4, identical with Cor. No. 4 of the WEBSTER 38 mill site and Cors. Nos. 3 of the WEBSTER 44 and WEBSTER 45 mill sites of this survey.
	Thence S. 39° 11' 37" W.
458	North bank of Webster Lake, bears N. 80° E. and S. 80° W.
989.72	Cor. No. 1, and place of beginning.
	WEBSTER 41 Mill Site
	At the true point for Cor. No. 1 of the WEBSTER 41 mill site, identical with Cor. No. 1 of the WEBSTER 42 mill site, on line 1-2 of the WEBSTER 39 mill site of this survey.
	This corner falls in Webster Lake where a monument cannot be established; from which
	The west $\frac{1}{4}$ sec. cor. of sec. 18, T. 1 N., R. 15 E. bears N. 3° 02' 10" E., 2217.69 ft. dist., previously described.
	Thence N. 50° 31' W.

FEET	
215.00	<p>The true point for Cor. No. 2, identical with Cor. No. 2 of the WEBSTER 40 mill site, on line 1-2 of the WEBSTER 39 mill site of this survey, previously described.</p> <p>Thence N. 39° 09' 46" E.</p>
796	<p>North bank of Webster Lake, bears N. 70° W. and S. 70° E.</p>
989.73	<p>Cor. No. 3, identical with Cor. No. 3 of the WEBSTER 40 mill site, on line 3-4 of the WEBSTER 45 mill site of this survey.</p> <p>Thence S. 50° 31' E.</p>
84	<p>North bank of Webster Lake, bears S. 30° W. and N. 20° E.</p>
220.53	<p>The true point for Cor. No. 4, identical with Cor. No. 4 of the WEBSTER 45 mill site, Cor. No. 2 of the WEBSTER 46 mill site, and Cor. No. 4 of the WEBSTER 42 mill site of this survey.</p> <p>This corner falls in Webster Lake where a monument cannot be established.</p> <p>Thence S. 39° 28' 58" W.</p>
989.72	<p>Cor. No. 1, and place of beginning.</p>
	<p style="text-align: center;">WEBSTER 42 Mill Site</p> <p>Beginning at the true point for Cor. No. 1 of the WEBSTER 42 mill site, identical with Cor. No. 1 of the WEBSTER 41 mill site, on line 1-2 of the WEBSTER 39 mill site of this survey, previously described.</p> <p>Thence S. 50° 31' E.</p>
49	<p>South bank of Webster Lake, bears N. 77° E. and S. 77° W.</p>
120.00	<p>Cor. No. 2, identical with Cor. No. 5 of the WEBSTER 43 mill site and Cor. No. 2 of the WEBSTER 39 mill site of this survey.</p> <p>Thence N. 47° 49' 06" E.</p>
96	<p>South bank of Webster Lake, bank bears S. 80° W. and East.</p>

FEET		
1,000.28	<p>The true point for Cor. No. 3, identical with Cor. No. 3 of the WEBSTER 46 mill site and Cor. No. 1 of the WEBSTER 43 mill site, on line 1-2 of the WEBSTER 47 mill site of this survey, established on line 2-3 Sur. No. 3015 Santa Clara lode at a point from which Cor. No. 3 bears N. 24° 38' 52" E., 730.13 ft. dist.</p> <p>This corner falls in Webster Lake where a monument cannot be established.</p> <p style="text-align: center;">Thence N. 50° 31' W.</p>	
265.00	<p>The true point for Cor. No. 4, identical with Cors. Nos. 4 of the WEBSTER 41 and WEBSTER 45 mill sites and Cor. No. 2 of the WEBSTER 46 mill site of this survey, previously described.</p> <p style="text-align: center;">Thence S. 39° 28' 58" W.</p>	
989.72	<p>Cor. No. 1, and place of beginning.</p>	
<p>WEBSTER 43 Mill Site</p>		
<p>Beginning at the true point for Cor. No. 1 of the WEBSTER 43 mill site, identical with Cors. Nos. 3 of the WEBSTER 42 and WEBSTER 46 mill sites and on line 1-2 of the WEBSTER 47 mill site of this survey, established on line 2-3 Sur. No. 3015 Santa Clara lode, previously described.</p>		
<p>From the true point; west The <math>\frac{1}{4}</math> sec. cor. of sec. 18, T.1 N., R.15 E., bears N. 23° 51' 57" W., 1770.60 ft. dist., previously described.</p> <p style="text-align: center;">Thence S. 24° 38' 52" W.</p>		
415.69	<p>Intersect the true point for Cor. No. 2 of the WEBSTER 47 mill site of this survey, established on line 2-3 Sur. No. 3015 Santa Clara lode, hereinafter described.</p>	
627.41	<p>The true point for Cor. No. 2, identical with Cor. No. 2 Sur. No. 3015 Santa Clara lode and Cor. No. 4 Sur. No. 3015 Columbus lode.</p> <p>This corner falls in Webster Lake where a monument cannot be established.</p> <p style="text-align: center;">Thence S. 24° 03' 13" W.</p>	

FEET	
505.23	<p>The true point for Cor. No. 3, established at the intersection of line 3-4 Sur. No. 3015 Columbus lode with line 1-2 Sur. No. 3015 Old Ironsides lode.</p> <p>This corner falls in Webster Lake where a monument cannot be established.</p> <p style="text-align: center;">Thence N. 6° 35' 30" E.</p>
130.33	<p>The true point for Cor. No. 4, identical with Cor. No. 3 of the WEBSTER 39 mill site of this survey and Cor. No. 1 Sur. No. 3015 Old Ironsides lode, previously described.</p> <p style="text-align: center;">Thence N. 51° 23' 30" W.</p>
325	<p>North bank of southwest arm of Webster Lake, bears N. 35° E. and S. 35° W.</p>
369.34	<p>Cor. No. 5, identical with Cors. Nos. 2 of the WEBSTER 39 and WEBSTER 42 mill sites of this survey.</p> <p style="text-align: center;">Thence N. 47° 49' 06" E.</p>
96	<p>South bank of Webster Lake, bank bears S. 80° W. and East.</p>
1,000.28	<p>Cor. No. 1, and place of beginning.</p>
	<p style="text-align: center;">WEBSTER 44 Mill Site</p>
	<p>At Cor. No. 1 of the WEBSTER 44 Mill Site.</p>
	<p>Set an iron post, 2 ft. long, 1 ins. diam., 13 ins. in the ground, with brass cap mkd. WEB 44-1-4730; from which</p> <p style="text-align: center;">west</p> <p style="text-align: center;">The <math>\frac{1}{4}</math> sec. cor. of sec. 18, T. 14 N., R. 15 E., bears N. 20° 38' 20" W., 510.30 ft. dist., previously described.</p> <p style="text-align: center;">Thence S. 50° 30' 58" E.</p>
360.00	<p>Cor. No. 2, identical with Cor. No. 2 of the WEBSTER 45 mill site of this survey.</p> <p>Set an iron post, 2 ft. long, 1 ins. diam., 18 ins. in the ground, with brass cap mkd. WEB 44-2-4730 and WEB 45-2-4730.</p>

FEET	
	Thence S. 31° 34' 32" W.
131	Road, bears N. 50° W. and S. 60° E.
545.18	Cor. No. 3, identical with Cor. No. 3 of the WEBSTER 45 mill site and Cors. Nos. 4 of the WEBSTER 40 and WEBSTER 38 mill sites of this survey.
	Thence N. 50° 31' W.
220.00	Intersect Cors. Nos. 3 of the WEBSTER 38 and WEBSTER 36 mill sites of this survey.
440.00	Cor. No. 4, identical with Cors. Nos. 4 of the WEBSTER 36 and WEBSTER 34 mill sites of this survey.
	Thence N. 40° 00' 54" E.
122	Road, bears West and S. 70° E.
433	Road, bears North and South.
504	Road, bears N. 60° W. and S. 60° E.
540.02	Cor. No. 1, and place of beginning.
	<p style="text-align: center;">WEBSTER 45 Mill Site</p> <p>At Cor. No. 1 of the WEBSTER 45 mill site, identical with Cor. No. 1 of the WEBSTER 46 mill site of this survey.</p> <p>Set an iron post, 2 ft. long, 1 ins. diam., 15 ins. in the ground, with brass cap mkd. WEB 45-1-4730 and WEB 46-1-4730; from which west</p> <p style="padding-left: 40px;">The <math>\frac{1}{4}</math> sec. cor. of sec. 18, T.1 N., R.15 E., bears N. 38° 10' 53" W., 1189.95 ft. dist., previously described.</p> <p style="text-align: center;">Thence N. 50° 30' 58" W.</p>
360.00	Cor. No. 2, identical with Cor. No. 2 of the WEBSTER 44 mill site of this survey.
	Thence S. 31° 34' 32" W.
131	Road, bears N. 50° W. and S. 60° E.

(This form bound on left side)

FEET	
545.18	Cor. No. 3, identical with Cors. Nos. 4 of the WEBSTER 40 and WEBSTER 38 mill sites and Cor. No. 3 of the WEBSTER 44 mill site of this survey.  Thence S. 50° 31' E.
219.47	Intersect Cors. Nos. 3 of the WEBSTER 41 and WEBSTER 40 mill sites of this survey.
303.47	North bank of Webster Lake, bears S. 30° W. and N. 20° E.
440.00	The true point for Cor. No. 4, identical with Cor. No. 2 of the WEBSTER 46 mill site and Cors. Nos. 4 of the WEBSTER 42 and WEBSTER 41 mill sites of this survey, previously described.  Thence N. 23° 28' 02" E.
328	North bank of Webster Lake, bears northwesterly and southeasterly.
510	Road, bears N. 75° W. and S. 75° E.
561.80	Cor. No. 1, and place of beginning.
WEBSTER 46 Mill Site	
Beginning at Cor. No. 1 of the WEBSTER 46 mill site, identical with Cor. No. 1 of the WEBSTER 45 mill site of this survey.  Thence S. 23° 28' 02" W.	
51.80	Road, bears N. 75° W. and S. 75° E.
233.80	North bank of Webster Lake, bears northwesterly and southeasterly.
561.80	The true point for Cor. No. 2, identical with Cors. Nos. 4 of the WEBSTER 42, WEBSTER 41, and WEBSTER 45 mill sites of this survey, previously described.  Thence S. 50° 31' E.
265.00	The true point for Cor. No. 3, identical with Cor. No. 1 of the WEBSTER 43 mill site and Cor. No. 3 of the WEBSTER 42 mill site, on line 1-2 of the WEBSTER 47 mill site of this survey, established on line 2-3 Sur. No. 3015 Santa Clara lode, previously described.

FEET	
	Thence N. 24° 38' 52" E.
138.13	North bank of Webster Lake, bears N. 30° W. and S. 60° E.
428.13	Intersect Cor. No. 1 of the WEBSTER 47 mill site, identical with Cor. No. 4 of the WEBSTER 48 mill site of this survey, established on line 2-3 Sur. No. 3015 Santa Clara lode, hereinafter described.
496.13	Road, bears N. 41° W. and S. 45° E.
730.13	Cor. No. 4, identical with Cor. No. 1 of the WEBSTER 48 mill site of this survey and Cor. No. 3 Sur. No. 3015 Santa Clara lode, re-established from bearing rocks as hereinafter described.  Set an iron post, 2 ft. long, 1 ins. diam., 11 ins. in the ground, with brass cap mkd. WEB 46-4-4730, WEB 48-1-4730, and SC-3-3015.
	Thence N. 85° 56' 39" W.
286.02	Cor. No. 1, and place of beginning.
	WEBSTER 47 Mill Site
	At Cor. No. 1 of the WEBSTER 47 mill site, identical with Cor. No. 4 of the WEBSTER 48 mill site, on line 3-4 of the WEBSTER 46 mill site of this survey, established on line 2-3 Sur. No. 3015 Santa Clara lode at a point from which Cor. No. 3, identical with Cor. No. 4 of the WEBSTER 46 mill site and Cor. No. 1 of the WEBSTER 48 mill site of this survey, bears N. 24° 38' 52" E., 302.00 ft. dist.
	Set an iron post, 2 ft. dist., 1 ins. diam., 17 ins. in the ground, with brass cap mkd. WEB 47-1, and WEB 48-4-4730; from which
	The west ¼ sec. cor. of sec. 18, T. 1 N., R. 15 E., bears N. 36° 02' 13" W., 1521.18 ft. dist., previously described.
	Thence S. 24° 38' 52" W.
290	North bank of Webster Lake, bears N. 30° W. and S. 60° E.



FEET	
428.13	Intersect the true point for Cor. No. 1 of the WEBSTER 43 mill site and Cors. Nos. 3 of the WEBSTER 42 and WEBSTER 46 mill sites of this survey, on line 2-3 Sur. No. 3015 Santa Clara lode, previously described.
843.82	<p>The true point for Cor. No. 2, established on line 2-3 Sur. No. 3015 Santa Clara lode, and on line 1-2 of the WEBSTER 43 mill site of this survey.</p> <p>This corner falls in Webster Lake where a monument cannot be established; from which</p> <p>The true point for Cor. No. 2 Sur. No. 3015 Santa Clara lode, identical with Cor. No. 4 Sur. No. 3015 Columbus lode and Cor. No. 2 of the WEBSTER 43 mill site of this survey, bears S. 24° 38' 52" W., 211.72 ft. dist.</p> <p style="text-align: center;">Thence S. 65° 28' 20" E.</p>
50.70	<p>The true point for Cor. No. 3.</p> <p>This corner falls in Webster Lake where a monument cannot be established.</p> <p style="text-align: center;">Thence N. 55° 47' E.</p>
148.34	<p>The true point for Cor. No. 4.</p> <p>This corner falls in Webster Lake where a monument cannot be established.</p> <p style="text-align: center;">Thence N. 49° 31' 20" E.</p>
690	North bank of Webster Lake, bears southwesterly and southeasterly.
740.56	<p>Cor. No. 5, identical with Cor. No. 3 of the WEBSTER 48 mill site of this survey.</p> <p>Set an iron post, 2 ft. long, 1 ins. diam., 16 ins. in the ground, with brass cap mkd. WEB 47-5-4730 and WEB 48-3-4730.</p> <p style="text-align: center;">Thence N. 59° 30' 53" W.</p>
441.20	Cor. No. 1, and place of beginning.



FEET	
	<p>WEBSTER 48 Mill Site</p> <p>Beginning at Cor. No. 1 of the WEBSTER 48 mill site, identical with Cor. No. 4 of the WEBSTER 46 mill site of this survey and Cor. No. 3 Sur. No. 3015 Santa Clara lode; from which</p> <p style="padding-left: 40px;">The west <math>\frac{1}{4}</math> sec. cor. of sec. 18, T. 1 N., R. 15 E., bears N. <math>46^{\circ} 53' 29''</math> W., 1398.34 ft. dist., previously described.</p> <p style="padding-left: 40px;">Thence S. <math>65^{\circ} 29' 48''</math> E.</p>
600.44	<p>Cor. No. 2, identical with Cor. No. 4 Sur. No. 3015 Santa Clara lode.</p> <p>To the top surface of an iron capped post 3 ins. diam., projecting <math>1\frac{1}{2}</math> ft. above concrete foundation, I add the following: WEB 48-2-4720; from which</p> <p style="padding-left: 40px;">A schist stone 10 x 17 x 20 ins. above ground, chiseled "+" BR 3015 bears N. <math>33^{\circ} 53' E.</math>, 36.31 ft. dist.</p> <p style="padding-left: 40px;">Thence S. <math>49^{\circ} 31' 20''</math> W.</p>
151	Road, bears N. $80^{\circ}$ W. and East.
384.01	<p>Cor. No. 3, identical with Cor. No. 5 of the WEBSTER 47 mill site of this survey.</p> <p style="padding-left: 40px;">Thence N. <math>59^{\circ} 30' 53''</math> W.</p>
441.20	<p>Cor. No. 4, identical with Cor. No. 1 of the WEBSTER 47 mill site, on line 3-4 of the WEBSTER 46 mill site of this survey, established on line 2-3 Sur. No. 3015 Santa Clara lode.</p> <p style="padding-left: 40px;">Thence N. <math>24^{\circ} 38' 52''</math> E.</p>
68	Road, bears N. $41^{\circ}$ W. and S. $45^{\circ}$ E.
302.00	Cor. No. 1, and place of beginning.

FEET	AREAS	Acres
	Total area, WEBSTER 1 mill site	4.100
	Area in conflict with --	
	Sur. No. 3489 Oriole lode	0.113
	Sur. No. 3489 Oriole No. 1 lode	0.913
	Total area, WEBSTER 2 mill site	4.655
	Area in conflict with --	
	Sur. No. 3489 Oriole No. 1 lode	0.903
	Total area, WEBSTER 3 mill site	4.543
	Total area, WEBSTER 4 mill site	4.964
	Total area, WEBSTER 5 mill site	4.522
	Total area, WEBSTER 6 mill site	4.952
	Total area, WEBSTER 7 mill site	4.961
	Total area, WEBSTER 8 mill site	4.947
	Total area, WEBSTER 9 mill site	4.987
	Total area, WEBSTER 10 mill site	4.999
	Total area, WEBSTER 11 mill site	4.971
	Total area, WEBSTER 12 mill site	4.980
	Total area, WEBSTER 13 mill site	4.974
	Total area, WEBSTER 14 mill site	4.985
	Total area, WEBSTER 15 mill site	4.977
	Total area, WEBSTER 16 mill site	4.986
	Total area, WEBSTER 17 mill site	4.977
	Total area, WEBSTER 18 mill site	4.971
	Total area, WEBSTER 19 mill site	4.964
	Total area, WEBSTER 20 mill site	4.986
	Total area, WEBSTER 21 mill site	4.974
	Total area, WEBSTER 22 mill site	4.986
	Total area, WEBSTER 23 mill site	4.970
	Total area, WEBSTER 24 mill site	4.987
	Total area, WEBSTER 25 mill site	4.983
	Total area, WEBSTER 26 mill site	4.984
	Total area, WEBSTER 27 mill site	4.976
	Total area, WEBSTER 28 mill site	4.985
	Total area, WEBSTER 29 mill site	4.973
	Total area, WEBSTER 30 mill site	4.976
	Total area, WEBSTER 31 mill site	4.980
	Total area, WEBSTER 32 mill site	4.987
	Total area, WEBSTER 33 mill site	4.963
	Total area, WEBSTER 34 mill site	4.987
	Total area, WEBSTER 35 mill site	4.689
	Total area, WEBSTER 36 mill site	4.999
	Total area, WEBSTER 37 mill site	4.964
	Total area, WEBSTER 38 mill site	4.999
	Total area, WEBSTER 39 mill site	4.695
	Total area, WEBSTER 40 mill site	4.993
	Total area, WEBSTER 41 mill site	4.948
	Total area, WEBSTER 42 mill site	4.374
	Total area, WEBSTER 43 mill site	4.666
	Total area, WEBSTER 44 mill site	4.959
	Total area, WEBSTER 45 mill site	4.959
	Total area, WEBSTER 46 mill site	3.886
	Total area, WEBSTER 47 mill site	4.853
	Area in conflict with --	
	Sur. No. 3015 Santa Clara lode, unpatented portion.	4.853

FEET

Total area, WEBSTER 48 mill site	3.920
Area in conflict with --	
Sur. No. 3015 Santa Clara lode, unpatented portion	3.920

LOCATION

This survey is located in Uns. sec. 13, T. 1 N., R. 14 E. and in surveyed sec. 18, T. 1 N., R. 15 E., of the Gila and Salt River Meridian, Gila County, Arizona.

The survey of the forty-eight (48) mill site claims embraced in the order for mineral survey and described herein is identical with the respective locations as marked on the ground.

OTHER CORNER DESCRIPTIONS AND SUPPLEMENTAL DATA

Sur. No. 3015 Old Ironside lode: Cors. Nos. 3 and 4 are iron pipes, 3 ins. diam., firmly set in pyramidal concrete foundations, and projecting 18 ins. above ground, with iron caps properly marked; Cors. Nos. 1 and 2 have been covered by waters of Webster Lake. Line 3-4 was found to be N. 6° 32' 10" E., 600.62 ft. instead of N. 6° 35' E., 600 ft., as approved. Line 4-1 and the direction of Line 1-2 are shown as calculated, resorting to the use of the instructions given in Sec. 380 of the 1947 Edition of the Manual of Surveying Instructions for the restoration of angle points of nonriparian meander lines (see Boundary Restoration Traverse 'A'); consequently, line 4-1 was found to be S. 83° 35' 10" E., 1499.92 ft., instead of S. 83° 33' E., 1500 ft., as approved, and line 1-2 was found to bear S. 6° 35' 30" W., instead of S. 6° 35' W., as approved.

Sur. No. 3015 Columbus lode: Cors. Nos. 1 and 4 have been covered by waters of Webster Lake; Cor. No. 3 could not be found. The bearing of line 3-4 is shown as calculated in the aforementioned Exterior Boundary Restoration Traverse 'A' and was found to be N. 24° 03' 13" E. instead of N. 24° 04' E., as approved. The bearing of line 4-1 is shown as approved.

FEET

Sur. No. 3015 Santa Clara lode: Cors. Nos. 1 and 2 have been covered by waters of Webster Lake. Cor. No. 3 was restored from found bearing rocks. Cor. No. 4 is an iron pipe, 3 ins. diam., firmly set in pyramidal concrete foundation, and projecting 16 ins. above ground, with iron cap properly marked. Line 2-3 is shown as calculated in the aforementioned Traverse 'A' and was found to be N. 24° 38' 52" E., 1357.54 ft., instead of N. 24° 40' E., 1356.8 ft., as approved. Line 3-4 was found to be S. 65° 29' 48" E., 600.44 ft., instead of S. 65° 24' E., 600 ft., as approved. The bearings of lines 4-1 and 1-2 are shown as approved. Those portions of the Santa Clara lode which were not patented have been covered by the claimant into mill site claims WEBSTER 37 and WEBSTER 38, which explains why said mill site claims fall entirely within the boundaries of the Santa Clara lode. These exclusions are shown on the approved plat of Sur. No. 3015 as TRACT C and a conflict with Raven No. 4 lode, a location now abandoned. In order to properly derive the boundaries of the subject exclusions and to thus establish the southwesterly and southeasterly boundaries of the WEBSTER 37 mill site and the southeasterly boundary of the WEBSTER 38 mill site, it was necessary to resort to the use of the instructions given in the aforementioned Sec. 380 of the Manual of Surveying Instructions (see Boundary Restoration Traverse 'B'); it will be noted that the westernmost corner of TRACT C was approved at a distance of 211.60 ft. along line 2-3 Sur. No. 3015 Santa Clara lode; by single proportion, this distance becomes 211.72 ft. along said line 2-3 (and becomes the point of beginning of Traverse 'B'). Consequently, the southwesterly boundary of TRACT C of Sur. No. 3015 Santa Clara lode was found to be S. 65° 28' 20" E., 50.70 ft., instead of S. 65° 24' E., 50.7 ft., as approved, and the southeasterly boundary of said TRACT C was found to be N. 55° 47' E., 148.34 ft., instead of N. 55° 49' E., 148.18 ft., as approved. Also, the southeasterly boundary of that portion of said Santa Clara lode excluded from patent in favor of the Raven No. 4 lode, subsequently abandoned, was found to be N. 49° 31' 20" E., 1124.57 ft., instead of N. 49° 33' E., 1123.3 ft., as approved.

FEET

Sur. No. 3489 Oriole lode: No corners could be found. However, Cors. Nos. 2 and 3 Sur. No. 3489 Calendar lode were found, being 4 ins. x 4 ins. pine posts, firmly set, and properly marked, and from the measurement of the positions of these cor. monuments I was able to calculate the position of Cor. No. 1 as follows: Line 2-3 Sur. No. 3489 Calendar lode was found to be N. 40° 16' 40" E., 1448.90 ft., instead of N. 40° 21' E., 1451.8 ft., as approved. On the approved plat of Sur. No. 3489, the intersection of line 2-3 Sur. No. 3489 Calendar lode with line 3-4 Sur. No. 3489 Oriole lode is shown to be at 967.1 feet along said line 2-3; single proportional distance places this intersection at 965.17 feet. The position of Cor. No. 4 Sur. No. 3489 Oriole lode was then calculated to be N. 49° 19' W., 3.38 ft., from said intersection, as shown on approved plat. With the position of Cor. No. 4 thus fixed, line 3-4 is shown as approved and the bearing of line 2-3 is shown as approved.

Sur. No. 3489 Oriole No. 1 lode: No corners could be found. Cors. Nos. 1 and 2 are respectively identical with Cors. Nos. 4 and 3 Sur. No. 3489 Oriole lode, described above. Using a procedure similar to that described in the preceding paragraph, I was able to fix the position of Cor. No. 4 as follows: Line 2-3 Sur. No. 3489 Bohemian lode could be established, Cor. No. 2 being identical with Cor. No. 3 Sur. No. 3489 Calendar lode, described above, and Cor. No. 3 being tentatively identified by the rotted remnants of what appeared to be the base of a 4 ins. x 4 ins. wooden post found in a low mound of stone. My assumption that this evidence fixes the position of Cor. No. 3 is borne out by the fact that line 2-3 was found to be N. 40° 37' 08" E., 1483.82 ft., instead of N. 40° 45' E., 1483.9 ft., as approved. On the approved plat of Sur. No. 3489, Cor. No. 4 is shown to be on line 2-3 Sur. No. 3489 Bohemian lode at a distance of 943.50 ft.; single proportional distance places Cor. No. 4 on line 2-3 at a distance of 943.45 ft. With the position of Cor. No. 4 thus fixed, line 3-4 is shown as approved. As a result of the above corner restoration procedures, line 2-3 was found to be N. 40° 57' 35" E., 1427.18 ft., instead of N. 41° 04' E., 1428.2 ft., as approved.

FEET

Discussion of Boundary Restoration Traverses:  
The first traverse was required in order to determine the proper positions for the missing angle-points along the northerly and westerly boundaries of Sur. No. 3015 Old Ironsides, Columbus, and Santa Clara lodes; the second traverse was required in order to re-establish the positions for the missing angle-points of the excluded portions of Sur. No. 3015 Santa Clara lode, for reasons explained above. Reference is made to Sec. 380 of the 1947 Edition of the Manual of Surveying Instructions, entitled "Angle Points of Nonriparian Meander Lines"; all boundary restoration calculations were made in accordance with these instructions.

Traverse 'A' -- Beginning at the 4 ins. diam. iron post marking Cor. No. 4 Sur. No. 3015 Old Ironsides lode; thence S. 83° 35' 10" E., 1499.92 ft. to Cor. No. 1; thence S. 6° 35' 30" W. along line 1-2 a distance of 130.33 ft. to its intersection with line 3-4 Sur. No. 3015 Columbus lode; thence N. 24° 03' 13" E. along said line 3-4 a distance of 505.23 ft. to Cor. No. 4 Sur. No. 3015 Columbus lode, identical with Cor. No. 2 Sur. No. 3015 Santa Clara lode; thence N. 24° 38' 52" W., 1357.54 ft. to the 1 ins. diam. iron post with brass cap marking Cor. No. 3 Sur. No. 3015 Santa Clara lode as restored in this survey from bearing rocks scribed by the mineral surveyor who executed Sur. No. 3015.

Traverse 'B' -- Beginning at the calculated position of the westernmost corner of TRACT C of Sur. No. 3015 Santa Clara lode, the derivation of which is explained in the discussion of Sur. No. 3015 Santa Clara lode, appearing on Page 48 of these Notes; thence S. 65° 28' 20" E., 50.70 ft. to the most southerly corner of TRACT C of Sur. No. 3015 Santa Clara lode; thence N. 55° 47' E., 148.34 ft. to the most easterly corner of said TRACT C, identical with the most southerly corner of the Raven No. 4 lode location, now abandoned; thence N. 49° 31' 20" E. along the south-easterly side-line of said Raven No. 4 lode location a distance of 1124.57 ft. to the 4 ins. diam. iron post marking Cor. No. 4 Sur. No. 3015 Santa Clara lode.

## FIELD ASSISTANTS

Name	Capacity
Loren E. Bunney	Instrumentman
Edward E. Zaragoza	Assistant
Joseph C. Donegan	Assistant



UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

CERTIFICATE OF SURVEYOR

Name of Mineral Surveyor  Travis L. Gant	Date  April 9, 1973
--	---------------------------

I HEREBY CERTIFY That in pursuance of an order received from the Dept. of Interior Bureau of Land Management, at Phoenix, Arizona, dated August 21, 1972, I have carefully executed the survey of the claim of Inspiration Consolidated Copper Company, known as the (lode, placer, or mill site) WEBSTER Group \* (see below), situated in Sec. 13, Uns. and Sec. 18 Surv., Township 1 N.&1 N., Range 14 East, Gila & Salt River Meridian, in the State of Arizona.

15 East  
This survey, designated as number 4730, has been executed by me and under my direction and has been made in strict conformity with said order, the Manual of Instructions for the Survey of Public Lands of the United States, and in specific manner described in the foregoing field notes.

I FURTHER CERTIFY That the labor expended and improvements made upon and for the benefit of the (lode or placer) Mill Site location(s) embraced in the said mining claim by claimant(s) or its grantors are fully stated in my report. The character, extent, location, and itemized value are specified in full detail. No portion of, or interest in, said labor and improvements so credited to this claim has been included in the estimate of expenditures upon any other claim.

WEBSTER 1 through 46, WEBSTER 47 mill site and WEBSTER 48 mill site.

Globe, Arizona (Location)	<i>Travis L. Gant</i> (Signature of Mineral Surveyor)
------------------------------	--

CERTIFICATE OF APPROVAL

Office Arizona State Office
Location Phoenix, Arizona
Date February 8, 1974

The foregoing field notes of mineral survey number 4730, in Sec. 13, Uns. & Sec. 18 Surv. Range 14&15 E., Gila and Salt River Meridian, in the State of Arizona,  surveyed  unsurveyed Township 1 N., executed by Travis L. Gant, Mineral Surveyor, under order dated August 21, 1972, having been critically examined and the necessary corrections made prior to their certification by the surveyor, the field notes and the survey therein described are hereby approved.

<i>Joe T. Fellini</i> (Authorized Signature)	State Director (Title)
---	---------------------------

CERTIFICATE OF TRANSCRIPT

I HEREBY CERTIFY That the foregoing transcript of field notes of the above described mineral survey number is a true copy of the original field notes.

(Authorized Signature)	(Title)
------------------------	---------

Title 18, U.S.C. section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious, or fraudulent statements or representations as to any matter within its jurisdiction.

Handwritten mark or signature in the top right corner.

Vertical text or markings on the right edge of the page.

Vertical text or markings on the right edge of the page.