

Form 3400-11
(September 1967)
(formerly 4-683)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Mineral Survey number	4787
State	Arizona
Land District	Arizona

FIELD NOTES

Of the Survey of the Mining Claim of *(name and address of Claimant)*

Jaquays Mining Corporation
P. O. Box 328
Globe, Arizona 85501

Known as the *(name of group, if any)*

Oly Group

CONSISTING OF LOCATIONS NAMED AND LOCATED AS FOLLOWS

NAME OF LOCATION	DATE	
	LOCATED	AMENDED
Oly No. 1	2/21/75	
Oly No. 2	2/21/75	
Oly No. 3	2/21/75	
Oly No. 4	2/21/75	
Oly No. 5	2/21/75	

Mining district			County	
Globe			Gila	
Section	Township	Range	Meridian	Survey under order dated
Uns. 5	1 South	16 East, Uns.	Gila & Salt River	December 2, 1975
Survey commenced		Survey completed	Name of Mineral Surveyor	
Dec. 8, 1975		Dec. 10, 1975	Travis L. Gant	

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

1911

FEET	
	<p>This survey was made with a Kern theodolite, Model DKM 2 AE, Ser. No. 145997, equipped with automatic vertical indexing and a microscope for angle-reading purposes enabling the instrument operator to read angles, either horizontal or vertical, to 1 sec. of arc. The instrument was in good condition and all adjustments were in good order at the time of the survey.</p> <p>All azimuths in this record were determined by the method of deflection angles referred to the meridian determined by the following observation:</p> <p>December 8, 1975, at Cor. No. 1 of the Oly No. 1 millsite in latitude 33° 22' 18" N., and longitude 110° 44' 00" W. (as determined by scaling from U.S.G.S. quadrangle CUTTER, ARIZ., dated 1966), elevation 3565 ft. above mean sea level, and temperature 42° F., make a series of six altitude observations on the sun for azimuth at approximately equal time intervals, three each with the telescope in direct and reversed positions, observing opposite limbs of the sun, and reading the horizontal angle from a reference point about 990 feet southeasterly clockwise to the sun.</p> <p>Mean time of observation, 105th meridian, standard time 9:51 a.m.</p> <p>Declination of sun at mean time of observation 22° 42' 05.7"S.</p> <p>Mean observed vertical angle to sun's center, corrected for refraction and parallax 24° 10' 04"</p> <p>Mean horizontal angle, turned clockwise and to the right, from reference point to sun's center 32° 17' 21"</p> <p>True bearing to reference point S. 68° 57' 30" E.</p> <p>The lines were measured with a Lufkin steel tape 500 ft. in length, graduated at one-foot intervals for its entire 500 ft. length, with an added foot on the zero end graduated in tenths and hundredths; this tape was compared with a standard 100.00 foot tape at the time of the beginning of the survey and found to be correct.</p> <p>All lines and connections of this survey were run by direct methods.</p> <p>The magnetic declination observed at each corner of the survey gave a uniform value of 13° 30' E.</p>

(This form bound on left side)

FEET	
	<p>Note concerning monumentation: Except in the one instance hereinafter described, all corners and witness corners of this survey were monumented with iron posts, 2 ft. long, consisting of 3/4-inch nominal diam. galvanized water pipe having 1 ins. exterior diam., into the top of each of which was cemented a brass tablet, 2 ins. diam., with a stem 2½ ins. long. Epoxy materials were used for grouting the stems into the pipes. Each tablet was marked as described herein, using 1/8-inch steel dies for lettering and numbering. All such brass-capped posts were set in the ground in a foundation of at least ½ cu. ft. of portland cement concrete, mixed at the site. Alongside each corner monument has been erected a mound of rocks having a base not less than 2½ ft. diam. and a height not less than 2½ ft.</p>
	<p>Mineral Survey No. 4787</p>
	<p>Oly No. 1 Millsite</p>
	<p>At Cor. No. 1 of the Oly No. 1 millsite, identical with Cor. No. 1 of the Oly No. 2 millsite, established on the southwesterly right-of-way line of U.S. Highway 70.</p>
	<p>Set an iron post, 2 ft. long, 1 ins. diam., 16 ins. in the ground, with brass cap mkd. OLY 1-1-4787 and OLY 2-1-4787; from which</p>
	<p>The standard township corner of Township 1 North, Range 15½ East, and Township 1 North, Range 16 East, being the standard cor. of secs. 36 and 31 of these townships, respectively, bears N. 51° 47' 04" E., 4326.19 ft. dist.; a scribed stone, firmly set, projecting 5 ins. above ground, mkd. as described in the official record.</p>
	<p>The centerline of U.S. Highway 70 bears N. 21° 02' 30" E., 100.00 ft. dist.</p>
	<p>Thence N. 68° 57' 30" W.</p>
	<p>Along the southwesterly right-of-way line of U.S. Highway 70.</p>
328.50	<p>Cor. No. 2, established on the southwesterly right-of-way line of U.S. Highway 70.</p>
	<p>Set an iron post, 2 ft. long, 1 ins. diam., 15 ins. in the ground, with brass cap mkd. OLY 1-2-4787; from which</p>
	<p>Cor. No. 2, M.S. No. 4784 Pocket No. 3 Mill Site bears N. 47° 29' W., 0.36 ft. dist.</p>

FEET	
	<p>Cor. No. 1, M.S. No. 4784 Pocket No. 2 Millsite, being a 4 ins. steel angle iron right-of-way monument marking a point 100 ft. to the right of both U.S. Hwy. 70 and Ariz. State Rte. 77, bears N. 68° 57' 30" W., 1242.68 ft. dist.</p> <p style="text-align: center;">Thence S. 21° 02' 30" W.</p>
120.	Power line, bears N. 68° 57' W., and S. 68° 57' E.
238.	Center of Aliso Wash, 8 ft. wide, course N. 88° E.
329.	Underground high-pressure gas line, bears N. 71° W. and S. 71° E.
374.	Center of dry wash, 6 ft. wide, course S. 70° E.
660.00	<p>Cor. No. 3.</p> <p>Set an iron post, 2 ft. long, 1 ins. diam., 17 ins. in the ground, with brass cap mkd. OLY 1-3-4787; from which</p> <p style="text-align: center;">Cor. No. 3, M.S. No. 4784 Pocket No. 3 Mill Site bears N. 20° 45' 15" E., 160.65 ft. dist.</p> <p style="text-align: center;">Thence S. 68° 57' 30" E.</p>
328.50	<p>Cor. No. 4, identical with Cor. No. 4 of the Oly No. 2 millsite of this survey.</p> <p>Set an iron post, 2 ft. long, 1 ins. diam., 18 ins. in the ground, with brass cap mkd. OLY 1-4-4787 and OLY 2-4-4787.</p> <p style="text-align: center;">Thence N. 21° 02' 30" E.</p>
275.	Center of dry wash, 6 ft. wide, course S. 75° E.
342.	Underground high-pressure gas line, bears N. 71° W. and S. 71° E.
526.	Center of Aliso Wash, 8 ft. wide, course S. 60° E.
540.	Power line, bears N. 68° 57' W. and S. 68° 57' E.
660.00	Cor. No. 1, and place of beginning.

FEET		
	Oly No. 2 Millsite	
	Beginning at Cor. No. 1 of the Oly No. 2 millsite, identical with Cor. No. 1 of the Oly No. 1 millsite of this survey, on the southwesterly right-of-way line of U.S. Highway 70.	
	Thence S. 68° 57' 30" E.	
	Along the southwesterly right-of-way line of U.S. Highway 70.	
330.00	Cor. No. 2, identical with Cor. No. 2 of the Oly No. 3 millsite of this survey; also identical with the steel right-of-way marker marking a point 100.00 ft. to the right of centerline at Highway Engineers' Sta. 164 + 00.00, said steel marker defining the southwesterly right-of-way line of U.S. Highway 70.	
	To the shaft of the 3 ins. x 3 ins. x ½ ins. angle-iron post, projecting 24 ins. above ground, I firmly attach a copper plate, 2 ins. x 3 ins., mkd. OLY 2-2-4787 and OLY 3-2-4787; also witnessed S. 68° 57' 30" E., 50.00 ft. dist., hereinafter described. From Cor. No. 2	
	The steel right-of-way monument marking a point 100.00 ft. (nominally) to the left of centerline at Engineers' Sta. 164 + 00.00 bears N. 21° 03' 25" E., 199.86 ft. dist.	
	Thence S. 21° 02' 30" W.	
120.	Power line, bears N. 68° 57' W., and S. 68° 57' E.	
171.	Center of Aliso Wash, 8 ft. wide, course S. 60° E.	
306.	Underground high-pressure gas line, bears N. 71° W. and S. 71° E.	
360.	Center of dry wash, 6 ft. wide, course S. 65° E.	
660.00	Cor. No. 3, identical with Cor. No. 3 of the Oly No. 3 millsite of this survey.	
	Set an iron post, 2 ft. long, 1 ins. diam., 17 ins. in the ground, with brass cap mkd. OLY 2-3-4787 and OLY 3-3-4787.	
	Thence N. 68° 57' 30" W.	
330.00	Cor. No. 4, identical with Cor. No. 4 of the Oly No. 1 millsite of this survey.	
	Thence N. 21° 02' 30" E.	

FEET	
275.	Center of dry wash, 6 ft. wide, course S. 75° E.
342	Underground high-pressure gas line, bears N. 71° W. and S. 71° E.
526.	Center of Aliso Wash, 8 ft. wide, course S. 60° E.
540.	Power line, bears N. 68° 57' W. and S. 68° 57' E.
660.00	Cor. No. 1, and place of beginning.
<p>Oly No. 3 Millsite</p> <p>At Cor. No. 1 of the Oly No. 3 millsite, identical with Cor. No. 1 of the Oly No. 4 millsite, established on the southwesterly right-of-way line of U.S. Highway 70.</p> <p>Set an iron post, 2 ft. long, 1 ins. diam., 18 ins. in the ground, with brass cap mkd. OLY 3-1-4787 and OLY 4-1-4787; from which</p> <p style="padding-left: 40px;">The standard cor. of secs. 36 and 31, T. 1 N., Rs. 15½ and 16 E., bears N. 43° 41' 27" E., 4028.94 ft. dist., heretofore described.</p> <p style="padding-left: 40px;">Cor. No. 2, M.S. No. 4487 Huntz Millsite, identical with Cor. No. 3, M. S. No. 4487 Asbestos King Millsite, bears N. 5° 31' 37" W., 225.20 ft. dist.</p> <p style="padding-left: 40px;">The centerline of U.S. Highway 70 bears N. 21° 02' 30" E., 100.00 ft. dist.</p> <p style="padding-left: 80px;">Thence N. 68° 57' 30" W.</p> <p>Along the southwesterly right-of-way line of U.S. Highway 70.</p>	
280.00	<p>A point selected for witness Cor. No. 2, identical with witness Cor. No. 2 of the Oly No. 2 millsite of this survey, established on the southwesterly right-of-way line of U.S. Highway 70. The purpose of this W. C. is to provide a reference in the event the highway right-of-way monument marking Cors. Nos. 2 is disturbed.</p> <p>Set an iron post, 2 ft. long, 1 ins. diam., 18 ins. in the ground, with brass cap mkd. WC - OLY 2-2-4787 and OLY 3-2-4787.</p>

FEET	
330.00	<p>Cor. No. 2, identical with Cor. No. 2 of the Oly No. 2 millsite of this survey; also identical with the right-of-way marker previously described.</p> <p style="text-align: center;">Thence S. 21° 02' 30" W.</p>
120.	<p>Power line, bears N. 68° 57' W. and S. 68° 57' E.</p>
171.	<p>Center of Aliso Wash, 8 ft. wide, course S. 60° E.</p>
306.	<p>Underground high-pressure gas line, bears N. 71° W. and S. 71° E.</p>
360.	<p>Center of dry wash, 6 ft. wide, course S. 65° E.</p>
660.00	<p>Cor. No. 3, identical with Cor. No. 3 of the Oly No. 2 millsite of this survey.</p> <p style="text-align: center;">Thence S. 68° 57' 30" E.</p>
330.00	<p>Cor. No. 4, identical with Cor. No. 4 of the Oly No. 4 millsite of this survey.</p> <p>Set an iron post, 2 ft. long, 1 ins. diam., 17 ins. in the ground, with brass cap mkd. OLY 3-4-4787 and OLY 4-4-4787.</p> <p style="text-align: center;">Thence N. 21° 02' 30" E.</p>
216.	<p>Center of dry wash, 7 ft. wide, course S. 60° E.</p>
366.	<p>Underground high-pressure gas line, bears N. 71° W. and S. 71° E.</p>
444.	<p>Center of Aliso Wash, 8 ft. wide, course S. 52° E.</p>
540.	<p>Power line, bears N. 68° 57' W. and S. 68° 57' E.</p>
660.00	<p>Cor. No. 1, and place of beginning.</p>
<p>Oly No. 4 Millsite</p> <p>Beginning at Cor. No. 1 of the Oly No. 4 millsite, identical with Cor. No. 1 of the Oly No. 3 millsite of this survey, on the southwesterly right-of-way line of U.S. Highway 70.</p> <p style="text-align: center;">Thence S. 68° 57' 30" E.</p> <p>Along the southwesterly right-of-way line of U.S. Highway 70.</p>	

FEET	
330.00	<p>Cor. No. 2, identical with Cor. No. 2 of the Oly No. 5 millsite of this survey, established on the southwesterly right-of-way line of U.S. Highway 70.</p> <p>Set an iron post, 2 ft. long, 1 ins. diam., 16 ins. in the ground, with brass cap mkd. OLY 4-2-4787 and OLY 5-2-4787.</p> <p style="text-align: center;">Thence S. 21° 02' 30" W.</p>
120.	<p>Power line, bears N. 68° 57' W. and S. 68° 57' E.</p>
283.	<p>Underground high pressure gas line, bears N. 71° W. and S. 71° E.</p>
386.	<p>Center of Aliso Wash, 10 ft. wide, course S. 30° E.</p>
452.	<p>Center of dry wash, 8 ft. wide, course S. 52° E.</p>
660.00	<p>Cor. No. 3, identical with Cor. No. 3 of the Oly 5 millsite of this survey.</p> <p>Set an iron post, 2 ft. long, 1 ins. diam., 18 ins. in the ground, with brass cap mkd. OLY 4-3-4787 and OLY 5-3-4787.</p> <p style="text-align: center;">Thence N. 68° 57' 30" W.</p>
330.00	<p>Cor. No. 4, identical with Cor. No. 4 of the Oly No. 3 millsite of this survey.</p> <p style="text-align: center;">Thence N. 21° 02' 30" E.</p>
216.	<p>Center of dry wash, 7 ft. wide, course S. 60° E.</p>
366.	<p>Underground high pressure gas line, bears N. 71° W. and S. 71° E.</p>
444.	<p>Center of Aliso Wash, 8 ft. wide, course S. 52° E.</p>
540.	<p>Power line, bears N. 68° 57' W. and S. 68° 57' E.</p>
660.00	<p>Cor. No. 1, and place of beginning.</p>

FEET	
	<p>Oly No. 5 Millsite</p> <p>At Cor. No. 1 of the Oly No. 5 millsite, established on the southwesterly right-of-way line of U.S. Highway 70.</p> <p>Set an iron post, 2 ft. long, 1 ins. diam., 18 ins. in the ground, with brass cap mkd. OLY 5-1-4787; from which</p> <p style="padding-left: 40px;">The standard cor. of secs. 36 and 31, T. 1 N., Rs. 15½ and 16 E., bears N. 34° 31' 28" E., 3823.60 ft. dist., heretofore described.</p> <p style="padding-left: 40px;">Cor. No. 3, M.S. No. 4487 Huntz Millsite, bears N. 21° 03' 06" W., 272.68 ft. dist.</p> <p style="padding-left: 40px;">Cor. No. 8, M.S. No. 4741 Jaquays Millsite, bears N. 21° 24' 09" W., 270.84 ft. dist.</p> <p style="padding-left: 40px;">The centerline of U.S. Highway 70 bears N. 21° 02' 30" E., 100.00 ft. dist.</p> <p style="padding-left: 40px;">The steel right-of-way marker marking a point 100.00 ft. to the right of centerline at Engineers' Sta. 185 + 00.00 bears S. 68° 57' 30" E., 1109.90 ft. dist.</p> <p style="padding-left: 80px;">Thence N. 68° 57' 30" W.</p> <p>Along the southwesterly right-of-way line of U.S. Highway 70.</p>
330.00	<p>Cor. No. 2, identical with Cor. No. 2 of the Oly No. 4 millsite of this survey, on the southwesterly right-of-way line of U.S. Highway 70.</p> <p style="padding-left: 80px;">Thence S. 21° 02' 30" W.</p>
120.	<p>Power line, bears N. 68° 57' W. and S. 68° 57' E.</p>
283.	<p>Underground high-pressure gas line, bears N. 71° W. and S. 71° E.</p>
386.	<p>Center of Aliso Wash, 10 ft. wide, course S. 30° E.</p>
452.	<p>Center of dry wash, 8 ft. wide, course S. 52° E.</p>
660.00	<p>Cor. No. 3, identical with Cor. No. 3 of the Oly 4 millsite of this survey.</p> <p style="padding-left: 80px;">Thence S. 68° 57' 30" E.</p>

FEET													
330.00	<p>Cor. No. 4.</p> <p>Set an iron post, 2 ft. long, 1 ins. diam., 17 ins. in the ground, with brass cap mkd. OLY 5-4-4787.</p> <p style="text-align: center;">Thence N. 21° 02' 30" E.</p>												
47.	Center of Aliso Wash, 12 ft. wide, course S. 45° E.												
389.	Underground high-pressure gas line, bears N. 71° W. and S. 71° E.												
540.	Power line, bears N. 68° 57' W. and S. 68° 57' E.												
660.00	Cor. No. 1, and place of beginning.												
	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: center;">AREAS</th> <th style="text-align: center;">Acres</th> </tr> </thead> <tbody> <tr> <td>Total area, Oly No. 1 Millsite</td> <td style="text-align: center;">4.977</td> </tr> <tr> <td>Total area, Oly No. 2 Millsite</td> <td style="text-align: center;">5.000</td> </tr> <tr> <td>Total area, Oly No. 3 Millsite</td> <td style="text-align: center;">5.000</td> </tr> <tr> <td>Total area, Oly No. 4 Millsite</td> <td style="text-align: center;">5.000</td> </tr> <tr> <td>Total area, Oly No. 5 Millsite</td> <td style="text-align: center;">5.000</td> </tr> </tbody> </table>	AREAS	Acres	Total area, Oly No. 1 Millsite	4.977	Total area, Oly No. 2 Millsite	5.000	Total area, Oly No. 3 Millsite	5.000	Total area, Oly No. 4 Millsite	5.000	Total area, Oly No. 5 Millsite	5.000
AREAS	Acres												
Total area, Oly No. 1 Millsite	4.977												
Total area, Oly No. 2 Millsite	5.000												
Total area, Oly No. 3 Millsite	5.000												
Total area, Oly No. 4 Millsite	5.000												
Total area, Oly No. 5 Millsite	5.000												
	<p>This survey is located in Uns. Sec. 5, T. 1 S., R. 16 E., Gila and Salt River Meridian, Gila County, Arizona.</p> <p>The survey of the five millsite claims comprising the Oly Group is identical with the locations as marked on the ground.</p> <p>OTHER CORNER DESCRIPTIONS AND SUPPLEMENTAL DATA</p> <p>M.S. No. 4487 Huntz Millsite: Cors. Nos. 2 and 3 are iron posts, firmly set, fitted with brass caps mkd. as described in the official record of Sur. No. 4487. Line 2-3 is correct as approved; the bearings of lines 1-2 and 3-4 are shown as approved.</p> <p>M.S. No. 4487 Asbestos King Millsite: Cors. Nos. 2 and 3 are iron posts, firmly set, fitted with brass caps mkd. as described in the official record of Sur. No. 4487. Line 2-3 is correct as approved; the bearings of lines 1-2 and 3-4 are shown as approved.</p>												

FEET

M.S. No. 4487 Regal Millsite: Cor. No. 3 is identical with Cor. No. 2, M.S. No. 4487 Asbestos King Millsite, described above. The bearings of lines 2-3 and 3-4 are shown as approved.

M.S. No. 4741 Jaquays Millsite: Cors. Nos. 7 and 8 are 2 ins. diam. brass tablets grouted into the centers of 12 ins. x 12 ins. concrete monuments placed flush with the ground. Line 7-8 is correct as approved and was found to coincide with a portion of the northeasterly right-of-way line of U.S. Highway 70 as defined by the steel right-of-way markers found on the left side of the highway at Engineers Stas. 164 + 00.00 and 185 + 00.00.

M.S. No. 4784 Pocket No. 3 Mill Site: Cors. Nos. 2 and 3 are iron posts, firmly set, fitted with 3 ins. square steel plates mkd. as described in the official record of M.S. No. 4784. Line 2-3 was found to be S. 21° 05' 45" W., 499.48 ft. instead of S. 21° 07' W., 500.16 ft., as approved. The bearing of line 3-4 is shown as approved.

The line connecting Cor. No. 1, M.S. 4784 Pocket No. 2 Millsite with Cor. No. 2, M.S. 4784 Pocket No. 3 Mill Site, said line being supposedly coincident with the southwesterly right-of-way line of U.S. 70, was found to be S. 68° 57' 52" E., 1242.34 ft., instead of S. 68° 53' E., 1242.03 ft., as approved.

The U.S. Highway right-of-way lines, as defined by the steel markers depicted on the accompanying mineral survey plat, do not precisely produce parallel lines nor do they provide a full 200-foot right-of-way width for the highway. For purposes of determining the positions of the northeasterly end-lines of the Oly Group of millsites, the southwesterly right-of-way markers were accepted as controlling for alignment.

FIELD ASSISTANTS

Name	Capacity
Evart D. Bungler	Instrumentman
Edward E. Zaragoza	Chainman

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

CERTIFICATE OF SURVEYOR

Name of Mineral Surveyor Travis L. Gant	Date January 2, 1976
--	-------------------------

I HEREBY CERTIFY That in pursuance of an order received from the Dept. of Interior, Bureau of Land Management, at Phoenix, Arizona, dated December 2, 1975, I have carefully executed the survey of the claim of Jaquays Mining Corporation known as the (lode, placer, or mill site) Oly Nos. 1 thru 5 millsites situated in Uns. Sec. 5, Township 1 South, Range 16 East, Uns., Gila & Salt River Meridian, in the State of Arizona.

This survey, designated as number 4787, has been executed by me and under my direction and has been made in strict conformity with said order, the Manual of Instructions for the Survey of Public Lands of the United States, and in specific manner described in the foregoing field notes.

I FURTHER CERTIFY That the labor expended and improvements made upon and for the benefit of the (lode or placer) millsite location(s) embraced in the said mining claim by claimant(s) or its grantors are fully stated in my report. The character, extent, location, and itemized value are specified in full detail. No portion of, or interest in, said labor and improvements so credited to this claim has been included in the estimate of expenditures upon any other claim.

Globe, Arizona (Location)	<i>Travis L. Gant</i> (Signature of Mineral Surveyor)
------------------------------	--

CERTIFICATE OF APPROVAL

Office Arizona State Office
Location Phoenix, Arizona
Date August 28, 1978

The foregoing field notes of mineral survey number 4787, in Uns. Sec. 5, Range 16 E., surveyed unsurveyed Township 1 S., Meridian, in the State of Arizona, executed by Travis L. Gant, Mineral Surveyor, under order dated December 2, 1975, having been critically examined and the necessary corrections made prior to their certification by the surveyor, the field notes and the survey therein described are hereby approved.

<i>Boyd S. Owens</i> (Authorized Signature) Boyd S. Owens	Chief, Br. of Cadastral Survey (Title)
---	---

CERTIFICATE OF TRANSCRIPT

I HEREBY CERTIFY That the foregoing transcript of field notes of the above-described mineral survey number is a true copy of the original field notes.

(Authorized Signature)	(Title)
------------------------	---------

Title 18, U.S.C. section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious, or fraudulent statements or representations as to any matter within its jurisdiction.

THE UNIVERSITY OF CHICAGO

DEPARTMENT OF CHEMISTRY

January 10, 1910

Dear Sir:

I have the pleasure to acknowledge the receipt of your letter of the 7th inst. and in reply to inform you that the same has been forwarded to the proper authorities for their consideration.

I am, Sir, very respectfully,
Yours truly,
[Signature]

Enclosed for you are the original and a copy of the report of the committee on the subject of the proposed change in the curriculum of the Department of Chemistry.

I am, Sir, very respectfully,
Yours truly,
[Signature]

I am, Sir, very respectfully,
Yours truly,
[Signature]

I am, Sir, very respectfully,
Yours truly,
[Signature]

I am, Sir, very respectfully,
Yours truly,
[Signature]

I am, Sir, very respectfully,
Yours truly,
[Signature]

I am, Sir, very respectfully,
Yours truly,
[Signature]

I am, Sir, very respectfully,
Yours truly,
[Signature]

I am, Sir, very respectfully,
Yours truly,
[Signature]

I am, Sir, very respectfully,
Yours truly,
[Signature]

I am, Sir, very respectfully,
Yours truly,
[Signature]

I am, Sir, very respectfully,
Yours truly,
[Signature]

I am, Sir, very respectfully,
Yours truly,
[Signature]

I am, Sir, very respectfully,
Yours truly,
[Signature]

UNITED STATES DEPARTMENT OF THE INTERIOR 9605 (956)
BUREAU OF LAND MANAGEMENT M.S. 4787
ARIZONA STATE OFFICE

NOTICE OF CANCELLATION OF MINERAL SURVEY

The Oly No. 1, Oly No. 2, Oly No. 3, Oly No. 4 and Oly No. 5 mill sites, Mineral Survey No. 4787, located in section 5, Township 1 South, Range 16 East, Gila and Salt River Meridian, Arizona, are hereby canceled.


These claims have not been filed with the Arizona State Office, Bureau of Land Management, in accordance with Section 314, 90 STAT. 2769, (43 U.S.C. 1744).

This cancellation was necessitated to clear the record.

The Mineral Survey Plat should be noted as follows:

"Oly No. 1, Oly No. 2, Oly No. 3, Oly No. 4 and Oly No. 5 mill sites, M.S. 4787, were canceled March 18, 2002, by memo 9605 (956) M.S. 4787, which is now a part of the original field notes."

March 18, 2002
Date



Chief Cadastral Surveyor of Arizona

