

Form 3860-10
(February 1987)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Mineral Survey Number
4862

State
Arizona

Land District
Arizona

FIELD NOTES

Of the Survey of the Mining Claim of (name and address of claimant)

Eddie Basha
P. O. Box 488
Chandler, Arizona 85224

Known as the (name of group, if any)

NAME OF CLAIM(S)

NAME OF LOCATION	DATE			BLM MINING CLAIM SERIAL NUMBER
	LOCATED AND AMENDED	RECORDED WITH COUNTY	RECORDED WITH BLM	
E.B. #1 lode Amended	6-05-85	6-21-85	6-19-85	239482
E.B. #2 lode Amended	8-20-86	10-8-86	10-14-86	239483
E.B. #3 lode Amended	6-05-85	6-21-85	6-19-85	239484
E.B. #4 lode Amended	8-20-86	10-8-86	10-14-86	239485
E.B. #5 lode Amended	6-05-85	6-21-85	6-19-85	239486
E.B. #6 lode Amended	8-20-86	10-8-86	10-14-86	239487
E.B. #7 lode Amended	6-05-85	6-21-85	6-19-85	239488
E.B. #8 lode Amended	8-20-86	10-8-86	10-14-86	239489
E.B. #9 lode Amended	6-05-85	6-21-85	6-19-85	239490
E.B. #10 lode Amended	8-20-86	10-8-86	10-14-86	239491
E.B. #11 lode Amended	6-05-85	6-21-85	6-19-85	208759
E.B. #12 lode Amended	10-05-83	10-17-83	11-08-83	239492
	8-20-86	10-8-86	10-14-86	
	6-11-85	6-21-85	6-19-85	
	8-20-86	10-8-86	10-14-86	

LOCATION OF CLAIM(S)

Mining district Hassayampa			County Pinal		
Section 1 & 12	Township 12 North	Range 2 West	Meridian G. & S.R.M.	Survey under order dated 10-31-86	
Survey commenced 10-31-86		Survey completed 1-25-96	Name of Mineral Surveyor Harvey W. Smith		

Mineral Survey No. 4862

FEET	
	<p>This survey was made with a Swiss Kern theodolite, Model DKM 1, No. 77769, having horizontal and vertical circles, 50 mm. in diam. The circles are graduated in degrees and 20-minute increments. An optical micrometer, adjustable to the vertical and horizontal circles, permits the reading of angles direct to ten-second accuracy and estimating to one-second accuracy. The instrument was in good condition at the time of the survey and all adjustments were in good order.</p>
	<p>All azimuths in this record were determined by the method of horizontal-angles-right referred to the meridian determined by the following observation:</p>
	<p>November 12, 1986, at Cor. No. 1 of the E.B. #1 lode, identical with Cor. No. 1 of the E.B. #2 lode of this survey, in latitude $34^{\circ}24.73'N.$ and longitude $112^{\circ}25.2'W.$, elevation 7,490. ft. above sea level, and temperature $40^{\circ}F.$, make a series of six altitude observations on the sun for azimuth at approximately equal time intervals, three each with the telescope in direct and reversed positions, observing opposite limbs of the sun, and reading the horizontal angle from a reference point about 250 ft. southeasterly to the sun.</p>
	<p>Mean time of observation, 105th meridian standard time = $10^h24^m20^s$ a.m.</p>
	<p>Declination of sun at mean time of observation = $17^{\circ}45'09.7''S.$</p>
	<p>Mean observed vertical angle to sun's center = $31^{\circ}32'42''$</p>
	<p>Mean horizontal angle from reference point clockwise to sun's center = $34^{\circ}10'25''$</p>
	<p>True bearing to reference point = $S.65^{\circ}32'44''E.$</p>
	<p>The lines were measured with a Lufkin steel tape, 300 ft. in length, graduated every foot for 299 ft. and the remaining foot graduated to tenths and hundredths; the tape was compared to an Invar standard tape at the beginning of the survey and found to be correct. In addition to the steel tape, a K & E Autoranger infrared distance measuring unit was used to measure some of the lines. Its accuracy was checked against a line measured with the foregoing steel tape and found to be correct.</p>
	<p>All lines and connections of this survey were run by direct methods.</p>

Mineral Survey No. 4862

FEET	
	<p>The magnetic declination observed at each corner of the survey gave a uniform value of 13°30'E.</p> <hr/> <p>Mineral Survey No. 4862</p> <hr/> <p>E.B. #1 LODE</p> <p>At Cor. No. 1 of the E.B. #1 lode, identical with Cor. No. 1 of the E.B. #2 lode of this survey.</p> <p>Set an iron post, 30 ins. long, 3/4 in. diam., 12 ins. in the ground, in a concrete and rock base, with a brass cap firmly secured to the iron post, mkd. X E.B.1 1 E.B.2 1 U.S.M.S. 4862; from which</p> <p style="padding-left: 40px;">The 1/4 sec. cor. of Secs. 1 and 6, T.12 N., Rs.1 and 2 W., G.& S.R.M., bears S.83°57'59"E., 2,223.92 ft. dist., monumented with an iron post, 2 1/2 ins. diam., 12 ins. above ground, firmly set, with a brass cap properly mkd.</p> <p style="padding-left: 40px;">A wood post, 2 x 2 ins. in size, 4 ft. above ground, sets adjacent to the iron post.</p> <p>No local bearing objects or bearing trees available.</p> <p style="padding-left: 40px;">Thence S.46°13'50"E.</p>
6.00	Cor. No. 3 of the E.B. #7 lode of this survey.
34.	Center of unimproved dirt road, 12 ft. wide, bears N.85°E. and S.85°W.
299.75	Lode line; discovery point bears S.38°30'57"W, 1,474.90 ft. dist.
464.	Center of unimproved dirt road, 12 ft. wide, bears North and South.
525.22	Intersect line 3-4, E.B. #10 lode of this survey.
599.50	<p>Cor. No. 2, identical with Cor. No. 1, M.S. No. 1588 Evergreen lode, on line 2-3, E.B. #7 lode of this survey.</p> <p>Found a mkd. stone 3 x 17 ins. in size, 11 ins. above ground, firmly set, markings illegible and a bearing tree with markings partially legible. I remove the stone and at the cor. point</p> <p>Set an iron post, 30 ins. long, 3/4 in. diam., 12 ins. in the ground, in a concrete and rock base, with a brass cap firmly secured to the iron post, mkd. X E.B.1 2 U.S.M.S. 4862, E.1 U.S.M.S. 1588; from which</p>

Mineral Survey No. 4862

FEET	
	<p>A pine, 26 ins. diam., bears N.68°03'W., 2.2 ft. dist., mkd. B.T. EG 1588.</p> <p>A wood post, 2 x 2 ins. in size, 4 ft. above ground, sets adjacent to the iron post.</p> <p>The mkd. stone is buried alongside.</p> <p>No other local bearing objects or bearing trees available.</p> <p>Thence S.38°30'57"W.</p>
75.	Center of unimproved dirt road, 12 ft. wide, bears N.5°W. and South.
416.51	Intersect line 2-3, E.B. #10 lode of this survey.
1,440.	Center of unimproved dirt road, 12 ft. wide, bears N.60°E. and S.60°W.
1,499.90	<p>Cor. No. 3, identical with Cor. No. 4 of the E.B. #4 lode of this survey, on line 4-1, M.S. No. 1588 Everygreen lode.</p> <p>Set an iron post, 30 ins. long, 3/4 in. diam., 12 ins. in the ground, in a concrete and rock base, with a brass cap firmly secured to the iron post, mkd. X E.B.1 3 E.B.4 4 U.S.M.S. 4862; from which</p> <p>Cor. No. 4, M.S. No. 1588 Evergreen lode, identical with Cor. No. 1, M.S. No. 1588 Mexia lode, bears S.38°30'57"W., 3.86 ft. dist.</p> <p>A wood post, 2 x 2 ins. in size, 4 ft. above ground, sets adjacent to the iron post.</p> <p>No local bearing objects or bearing trees available.</p> <p>Thence N.46°13'50"W.</p>
25.	Center of unimproved dirt road, 12 ft. wide, bears N.40°E. and S.40°W.
299.75	Lode line; discovery point bears N.38°30'57"E., 25.00 ft. dist.
599.50	Cor. No. 4, identical with Cor. No. 3 of the E.B. #4 lode, Cor. No. 3 of the E.B. #5 lode and Cor. No. 2 of the E.B. #2 lode, all of this survey.

Mineral Survey No. 4862

FEET	
	<p>Set an iron post, 30 ins. long, 3/4 in. diam., 12 ins. in the ground, in a concrete and rock base, with a brass cap firmly secured to the iron post, mkd. X E.B.1 4 E.B.4 3 E.B.5 3 E.B.2 2 U.S.M.S. 4862; from which</p> <p style="padding-left: 40px;">A wood post, 2 x 2 ins. in size, 4 ft. above ground, sets adjacent to the iron post.</p> <p>No local bearing objects or bearing trees available.</p> <p style="padding-left: 40px;">Thence N.38°30'57"E.</p>
1,480.	Center of unimproved dirt road, 12 ft. wide, bears N.85°E. and S.85°W.
1,499.90	Cor. No. 1, and place of beginning.
	<hr/> <p style="text-align: center;">E.B. #2 LODE</p> <p>Beginning at Cor. No. 1 of the E.B. #2 lode, identical with Cor. No. 1 of the E.B. #1 lode of this survey.</p> <p style="padding-left: 40px;">Thence S.38°30'57"W.</p>
20.	Center of unimproved dirt road, 12 ft. wide, bears N.85°E. and S.85°W.
1,499.90	<p>Cor. No. 2, identical with Cor. No. 4 of the E.B. #1 lode, Cor. No. 3 of the E.B. #4 lode and Cor. No. 3 of the E.B. #5 lode, all of this survey.</p> <p style="padding-left: 40px;">Thence N.46°13'50"W.</p>
299.75	Lode line; discovery point bears N.38°30'57"E., 25.00 ft. dist.
599.50	<p>Cor. No. 3, identical with Cor. No. 2 of the E.B. #5 lode, Cor. No. 4 of the E.B. #6 lode and Cor. No. 2 of the E.B. #3 lode, all of this survey.</p> <p>Set an iron post, 30 ins. long, 3/4 in. diam., 12 ins. in the ground, in a concrete and rock base, with a brass cap firmly secured to the iron post, mkd. X E.B.2 3 E.B.5 2 E.B.6 4 E.B.3 2 U.S.M.S. 4862; from which</p> <p style="padding-left: 40px;">A wood post, 2 x 2 ins. in size, 4 ft. above ground, sets adjacent to the iron post.</p> <p>No local bearing objects or bearing trees available.</p> <p style="padding-left: 40px;">Thence N.38°30'57"E.</p>

Mineral Survey No. 4862

FEET	
1,330.	Center of unimproved dirt road, 12 ft. wide, bears N.10°W. and S.40°E.
1,499.90	<p>Cor. No. 4, identical with Cor. No. 1 of the E.B. #3 lode.</p> <p>Set an iron post, 30 ins. long, 3/4 in. diam., 12 ins. in the ground, in a concrete and rock base, with a brass cap firmly secured to the iron post, mkd. X E.B.2 4 E.B.3 1 U.S.M.S. 4862; from which</p> <p>The $\frac{1}{4}$ sec. cor. of Secs. 1 and 6, T.12 N., Rs.1 and 2 W., G.& S.R.M., bears S.76°13'20"E., 2,722.86 ft. dist., hereinbefore described.</p> <p>Cor. No. 4, Gen. No. 173, Lot 45 DeVernon lode, bears S.50°06'26"W., 655.30 ft. dist.</p> <p>A wood post, 2 x 2 ins. in size, 4 ft. above ground, sets adjacent to the iron post.</p> <p>No local bearing objects or bearing trees available.</p> <p>Thence S.46°13'50"E.</p>
299.75	Lode line; discovery point bears S.38°30'57"W., 1,474.90 ft. dist.
599.50	Cor. No. 1, and place of beginning.
E.B. #3 LODE	
Beginning at Cor. No. 1 of the E.B. #3 lode, identical with Cor. No. 4 of the E.B. #2 lode of this survey.	
Thence S.38°30'57"W.	
170.	Center of unimproved dirt road, 12 ft. wide, bears N.10°W. and S.40°E.
1,499.90	<p>Cor. No. 2, identical with Cor. No. 3 of the E.B. #2 lode, Cor. No. 2 of the E.B. #5 lode and Cor. No. 4 of the E.B. #6 lode, all of this survey.</p> <p>Thence N.46°13'50"W.</p>
172.	Left bank of local drainage, 6 ft. wide, course S.55°W.
299.75	Lode line; discovery point bears N.38°30'57"E., 25.00 ft. dist.
599.50	Cor. No. 3, identical with Cor. No. 3 of the E.B. #6 lode of this survey.

Mineral Survey No. 4862

FEET	
	<p>Set an iron post, 30 ins. long, 3/4 in. diam., 12 ins. in the ground, in a concrete and rock base, with a brass cap firmly secured to the iron post, mkd. X E.B.3 3 E.B.6 3 U.S.M.S. 4862; from which</p> <p style="padding-left: 40px;">A wood post, 2 x 2 ins. in size, 4 ft. above ground, sets adjacent to the iron post.</p> <p>No local bearing objects or bearing trees available.</p> <p style="padding-left: 40px;">Thence N.38°30'57"E.</p>
867.88	Intersect line 3-4, Gen. No. 173, Lot 45 DeVernon lode, at a point from which Cor. No. 4 bears S.43°33'19"E., 469.80 ft. dist.
1,499.90	<p>True point for Cor. No. 4.</p> <p>This cor. falls on patented land where a permanent monument cannot be established.</p> <p style="padding-left: 40px;">Thence S.46°13'50"E.</p>
299.75	Lode line; discovery point bears S.38°30'57"W., 1,474.90 ft. dist.
375.	Center of unimproved dirt road, 12 ft. wide, bears N.15°W. and S.15°E.
572.01	<p>Witness cor. for Cor. No. 4, and intersect line 4-1, Gen. No. 173, Lot 45 DeVernon lode, at a point from which Cor. No. 4 bears S.47°42'32"W., 652.83 ft. dist.</p> <p>Set an iron post, 30 ins. long, 3/4 in. diam., 12 ins. in the ground, in a concrete and rock base, with a brass cap firmly secured to the iron post, mkd. X W.C. E.B.3 4 U.S.M.S. 4862; from which</p> <p style="padding-left: 40px;">A wood post, 2 x 2 ins. in size, 4 ft. above ground, sets adjacent to the iron post.</p> <p>No local bearing objects or bearing trees available.</p>
599.50	Cor. No. 1, and place of beginning.
	E.B. #6 LODE
	At Cor. No. 1 of the E.B. #6 lode, identical with Cor. No. 1 of the E.B. #5 lode of this survey.

Mineral Survey No. 4862

FEET	
	<p>Set an iron post, 30 ins. long, 3/4 in. diam., 12 ins. in the ground, in a concrete and rock base, with a brass cap firmly secured to the iron post, mkd. X E.B.6 1 E.B.5 1 U.S.M.S. 4862; from which</p> <p>The 1/4 sec. cor. of Secs. 1 and 12, T.12 N., R.2 W., G.& S.R.M., bears S.64°26'25"E., 1,888.92 ft. dist., monumented with an iron post, 2 1/2 in. diam., 12 ins. above ground, firmly set, with a brass cap properly mkd.</p> <p>A wood post, 2 x 2 ins. in size, 4 ft. above ground, sets adjacent to the iron post.</p> <p>No local bearing objects or bearing trees available.</p> <p style="text-align: center;">Thence N.46°13'50"W.</p>
230.	Left Bank of local drainage, 12 ft. wide, course S.35°W.
299.75	Lode line; discovery point bears N.30°36'14"E, 1,474.50 ft. dist.
599.50	Cor. No. 2.
	<p>Set an iron post, 30 ins. long, 3/4 in. diam., 12 ins. in the ground, in a concrete and rock base, with a brass cap firmly secured to the iron post, mkd. X E.B.6 2 U.S.M.S. 4862; from which</p> <p>A wood post, 2 x 2 ins. in size, 4 ft. above ground, sets adjacent to the iron post.</p> <p>No other local bearing objects or bearing trees available.</p> <p style="text-align: center;">Thence N.30°36'14"E.</p>
255.	Center of unimproved dirt road, 12 ft. wide, bears N.35°E. and S.75°W.
1,499.50	Cor. No. 3, identical with Cor. No. 3 of the E.B. #3 lode of this survey.
	Thence S.46°13'50"E.
299.75	Lode line; discovery point bears S.30°36'14"W., 25.00 ft. dist.
422.	Right Bank of local drainage, 6 ft. wide, course S.55°W.
599.50	Cor. No. 4, identical with Cor. No. 2 of the E.B. #3 lode, Cor. No. 3 of the E.B. #2 lode and Cor. No. 2 of the E.B. #5 lode, all of this survey.
	Thence S.30°36'14"W.

Mineral Survey No. 4862

FEET	
1,499.50	Cor. No. 1, and place of beginning.
	<p style="text-align: center;">E.B. #5 LODE</p> <p>Beginning at Cor. No. 1 of the E.B. #5 lode, identical with Cor. No. 1 of the E.B. #6 lode of this survey.</p> <p style="text-align: center;">Thence N.30°36'14"E.</p>
1,499.50	<p>Cor. No. 2, identical with Cor. No. 4 of the E.B. #6 lode, Cor. No. 2 of the E.B. #3 lode and Cor. No. 3 of the E.B. #2 lode, all of this survey.</p> <p style="text-align: center;">Thence S.46°13'50"E.</p>
299.75	Lode line; discovery point bears S.30°36'14"W., 25.00 ft. dist.
599.50	<p>Cor. No. 3, identical with Cor. No. 2 of the E.B. #2 lode, Cor. No. 4 of the E.B. #1 lode and Cor. No. 3 of the E.B. #4 lode, all of this survey.</p> <p style="text-align: center;">Thence S.30°36'14"W.</p>
1,485.	Right bank of local drainage, 8 ft. wide, course S.65°W.
1,499.50	<p>Cor. No. 4, identical with Cor. No. 2 of the E.B. #4 lode of this survey.</p> <p>Set an iron post, 30 ins. long, 3/4 in. diam., 12 ins. in the ground, in a concrete and rock base, with a brass cap firmly secured to the iron post, mkd. X E.B.5 4 E.B.4 2 U.S.M.S. 4862; from which</p> <p style="text-align: center;">A wood post, 2 x 2 ins. in size, 4 ft. above ground, sets adjacent to the iron post.</p> <p>No other local bearing objects or bearing trees available.</p> <p style="text-align: center;">Thence N.46°13'50"W.</p>
5.	Left bank of local drainage, 8 ft. wide, course S.75°W.
299.75	Lode line; discovery point bears N.30°36'14"E., 1,474.50 ft. dist.
599.50	Cor. No. 1, and place of beginning.

Mineral Survey No. 4862

FEET	
	E.B. #4 LODE
	At Cor. No. 1 of the E.B. #4 lode, on line 3-4 E.B. #8 lode of this survey.
	Set an iron post, 30 ins. long, 3/4 in. diam., 12 ins. in the ground, in a concrete and rock base, with a brass cap firmly secured to the iron post, mkd. X E.B.4 1 U.S.M.S. 4862; from which
	The $\frac{1}{4}$ sec. cor. of Secs. 1 and 12, T.12 N., R.2 W., G.& S.R.M., bears N.89°00'50"E., 838.35 ft. dist., hereinbefore described.
	A wood post, 2 x 2 ins. in size, 4 ft. above ground, sets adjacent to the iron post.
	No local bearing objects or bearing trees available.
	Thence N.46°13'50"W.
299.75	Lode line; discovery point bears N.30°36'14"E, 1,474.50 ft. dist.
599.50	Cor. No. 2, identical with Cor. No. 4 of the E.B. #5 lode of this survey.
	Thence N.30°36'14"E.
3.	Left Bank of local drainage, 8 ft. wide, course S.65°W.
1,499.50	Cor. No. 3, identical with Cor. No. 3 of the E.B. #5 lode, Cor. No. 2 of the E.B. #2 lode and Cor. No. 4 of the E.B. #1 lode, all of this survey.
	Thence S.46°13'50"E.
299.75	Lode line; discovery point bears S.30°36'14"W., 25.00 ft. dist.
575.	Center of unimproved dirt road, 12 ft. wide, bears N.30°E. and S.30°W.
599.50	Cor. No. 4, identical with Cor. No. 3 of the E.B. #1 lode of this survey, on line 4-1, M.S. No. 1588 Evergreen lode.
	Thence S.30°36'14"W.
3.94	Intersect line 3-4, M.S. No. 1588 Evergreen lode, common with line 1-2, M.S. No. 1588 Mexia lode, at a point from which Cor. No. 4 of the Evergreen lode, identical with Cor. No. 1 of the Mexia lode, bears N.46°26'31"W., 0.54 ft. dist.

Mineral Survey No. 4862

FEET	
64.	Center of unimproved dirt road, 12 ft. wide, bears N.5°W. and S.5°E.
864.11	Cor. No. 4, M.S. No. 1588 Mexia lode, identical with Cor. No. 4 of the E.B. #8 lode of this survey.
1,499.50	Cor. No. 1, and place of beginning.
E.B. #8 LODE	
At Cor. No. 1 of the E.B. #8 lode, identical with Cor. No. 3, M.S. No. 1588 Mexia lode.	
Found a mkd. stone 8 x 11 ins. in size, 8 ins. above ground, firmly set, properly mkd. I remove the stone and at the cor. point	
Set an iron post, 30 ins. long, 3/4 in. diam., 12 ins. in the ground, in a concrete and rock base, with a brass cap firmly secured to the iron post, mkd. X E.B.8 1 U.S.M.S. 4862 M.3 U.S.M.S. 1588; from which	
The $\frac{1}{4}$ sec. cor. of Secs. 1 and 12, T.12 N., R.2 W., G.& S.R.M., bears S.33°26'35"E., 144.07 ft. dist., hereinbefore described.	
A wood post, 2 x 2 ins. in size, 4 ft. above ground, sets adjacent to the iron post.	
The mkd. stone is buried alongside.	
No local bearing objects or bearing trees available.	
Thence S.30°36'14"W.	
1,260.	Center of unimproved dirt road, 12 ft. wide, bears N.85°W. and S.70°E.
1,340.	Left bank of Crooks Creek, 50 ft. wide, course S.40°E.
1,425.	Center of Senator Highway, an unimproved road, 20 ft. wide, bears N.60°W. and S.50°E.
1,474.31	Intersect line 3-4, E.B. #12 lode of this survey.
1,499.50	Cor. No. 2. Set an iron post, 30 ins. long, 3/4 in. diam., 12 ins. in the ground, in a concrete and rock base, with a brass cap firmly secured to the iron post, mkd. X E.B.8 2 U.S.M.S. 4862; from which

Mineral Survey No. 4862

FEET	
	<p>A wood post, 2 x 2 ins. in size, 4 ft. above ground, sets adjacent to the iron post.</p>
	<p>No local bearing objects or bearing trees available.</p>
	<p>Thence N.46°33'45"W.</p>
280.	<p>South edge of Senator Highway, an unimproved road, 20 ft. wide, bears N.25°W. and S.60°E.</p>
299.78	<p>Lode line; discovery point bears N.30°36'14"E., 1,474.50 ft. dist.</p>
599.56	<p>Cor. No. 3.</p>
	<p>Set an iron post, 30 ins. long, 3/4 in. diam., 12 ins. in the ground, in a concrete and rock base, with a brass cap firmly secured to the iron post, mkd. X E.B.8 3 U.S.M.S. 4862; from which</p>
	<p>A wood post, 2 x 2 ins. in size, 4 ft. above ground, sets adjacent to the iron post.</p>
	<p>No local bearing objects or bearing trees available.</p>
	<p>Thence N.30°36'14"E.</p>
80.	<p>Center of Senator Highway, an unimproved road, 20 ft. wide, bears N.55°W. and S.55°E.</p>
300.	<p>Right bank of Crooks Creek, 100 ft. wide, course S.85°E.</p>
864.11	<p>Cor. No. 1 of the E.B. #4 lode of this survey.</p>
1,499.50	<p>Cor. No. 4, identical with Cor. No. 4, M.S. No. 1588 Mexia lode.</p>
	<p>Found a mkd. stone 5 x 12 ins. in size, 12 ins. above ground, firmly set, properly mkd. I remove the stone and at the cor. point</p>
	<p>Set an iron post, 30 ins. long, 3/4 in. diam., 12 ins. in the ground, in a concrete and rock base, with a brass cap firmly secured to the iron post, mkd. X E.B.8 4 U.S.M.S. 4862; M.4 U.S.M.S. 1588; from which</p>
	<p>A wood post, 2 x 2 ins. in size, 4 ft. above ground, sets adjacent to the iron post.</p>
	<p>The mkd. stone is buried alongside.</p>
	<p>No other local bearing objects or bearing trees available.</p>
	<p>Thence S.46°33'45"E.</p>

Mineral Survey No. 4862

FEET	
299.78	Lode line; discovery point bears S.30°36'14"W., 25.00 ft. dist.
480.16	Intersect line 1-2, E.B. #9 lode of this survey.
560.22	Intersect line 4-1, E.B. #9 lode, common with line 1-2, E.B. #12 lode, both of this survey.
599.56	Cor. No. 1, and place of beginning.
<p>E.B. #9 LODE</p> <p>At Cor. No. 1 of the E.B. #9 lode, identical with Cor. No. 1 of the E.B. #12 lode of this survey.</p> <p>Set an iron post, 30 ins. long, 3/4 in. diam., 12 ins. in the ground, in a concrete and rock base, with a brass cap firmly secured to the iron post, mkd. X E.B.9 1 E.B.12 1 U.S.M.S. 4862; from which</p> <p>The ¼ sec. cor. of Secs. 1 and 12, T.12 N., R.2 W., G.& S.R.M., bears S.43°53'15"E., 258.19 ft. dist., hereinbefore described.</p> <p>Cor. No. 3, M.S. No. 1588 Mexia lode, identical with Cor. No. 1 of the E.B. #8 lode of this survey, bears S.56°31'20"E., 119.40 ft. dist.</p> <p>A wood post, 2 x 2 ins. in size, 4 ft. above ground, sets adjacent to the iron post.</p> <p>No local bearing objects or bearing trees available.</p> <p>Thence N.38°28'34"E.</p>	
20.73	Intersect line 4-1 of the E.B. #8 lode of this survey, common with line 3-4, M.S. No. 1588 Mexia lode, at a point from which Cor. No. 1, identical with Cor. No. 3 of the Mexia lode, bears S.46°33'45"E., 119.40 ft. dist.
861.30	Cor. No. 2, M.S. No. 1588 Mexia lode, identical with Cor. No. 3, M.S. No. 1588 Evergreen lode.
1,440.00	Cor. No. 2, identical with the point for Cor. No. 4, M.S. No. 1588 Par Value lode, on line 2-3, M.S. No. 1588 Evergreen lode.
	<p>Set an iron post, 30 ins. long, 3/4 in. diam., 12 ins. in the ground, in a concrete and rock base, with a brass cap firmly secured to the iron post, mkd. X E.B.9 2 U.S.M.S. 4862; P.V. 4 U.S.M.S. 1588; from which</p>

Mineral Survey No. 4862

FEET	
	<p>A wood post, 2 x 2 ins. in size, 4 ft. above ground, sets adjacent to the iron post.</p> <p>No local bearing objects or bearing trees available.</p> <p>Thence S.61°20'42"E.</p>
191.02	Intersect line 4-1, M.S. No. 1588 Blind Tom lode, at a point from which Cor. No. 4 bears S.29°46'27"W., 427.64 ft. dist., and point for Cor. No. 3, M.S. No. 1588 Par Value lode.
299.75	Lode line; discovery point bears S.38°28'34"W., 1,415.00 ft. dist.
460.	Right bank of local drainage, 8 ft. wide, course S.30°W.
599.50	<p>Cor. No. 3.</p> <p>Set an iron post, 30 ins. long, 3/4 in. diam., 12 ins. in the ground, in a concrete and rock base, with a brass cap firmly secured to the iron post, mkd. X E.B.9 3 U.S.M.S. 4862; from which</p> <p>Cor. No. 4, M.S. No. 1588 Blind Tom lode, bears S.72°55'43"W., 597.13 ft. dist.</p> <p>Cor. No. 1, M.S. No. 1588 Aligaitor lode, bears S.57°53'56"W., 723.56 ft. dist.</p> <p>A wood post, 2 x 2 ins. in size, 4 ft. above ground, sets adjacent to the iron post.</p> <p>No local bearing objects or bearing trees available.</p> <p>Thence S.38°28'34"W.</p>
396.69	Intersect line 1-2, M.S. No. 1588 Aligaitor lode, at a point from which Cor. No. 1 bears S.78°34'19"W., 373.48 ft. dist.
439.36	Intersect line 3-4, M.S. No. 1588 Blind Tom lode, at a point from which Cor. No. 4 bears N.60°26'43"W., 341.95 ft. dist.
905.	Left bank of local drainage, 8 ft. wide, course South.
1,016.76	Cor. No. 1 of the E.B. #11 lode of this survey and intersect line 4-1, M.S. No. 1588 Aligaitor lode, at a point from which Cor. No. 1 bears N.2°44'39"E., 411.89 ft. dist.
1,403.6	Intersect line 1-2, M.S. No. 1588 Diller C lode, at a point from which Cor. No. 2 bears S.74°56'26"E., 373.21 ft. dist.

Mineral Survey No. 4862

FEET	
1,440.00	<p>Cor. No. 4, identical with Cor. No. 4 of the E.B. #11 lode and Cor. No. 2 of the E.B. #12 lode, both of this survey.</p> <p>Set an iron post, 30 ins. long, 3/4 in. diam., 12 ins. in the ground, in a concrete and rock base, with a brass cap firmly secured to the iron post, mkd. X E.B.9 4 E.B.11 4 E.B.12 2 U.S.M.S. 4862; from which</p> <p style="padding-left: 40px;">Cor. No. 2, M.S. No. 1588 Diller C lode, bears S.79°51'55"E., 389.11 ft. dist.</p> <p style="padding-left: 40px;">A wood post, 2 x 2 ins. in size, 4 ft. above ground, sets adjacent to the iron post.</p> <p>No other local bearing objects or bearing trees available.</p> <p style="text-align: center;">Thence N.61°20'42"W.</p>
142.1	Intersect line 1-2, M.S. No. 1588 Diller C lode, at a point from which Cor. No. 2 bears S.74°56'26"E., 525.79 ft. dist.
299.75	Lode line; discovery point bears N.38°28'34"E., 25.00 ft. dist.
480.19	Intersect line 2-3, M.S. No. 1588 Mexia lode, at a point from which Cor. No. 2 bears N.30°31'06"E., 849.12 ft. dist.
518.56	Intersect line 3-4, M.S. No. 1588 Mexia lode, common with line 4-1, E.B. #8 lode of this survey, at a point from which Cor. No. 1, identical with Cor. No. 3 of the Mexia lode, bears S.46°33'45"E., 39.34 ft. dist.
599.50	Cor. No. 1, and place of beginning.
E.B. #11 LODE	
<p>At Cor. No. 1 of the E.B. #11 lode, at the intersection of line 3-4, E.B. #9 lode of this survey and line 4-1, M.S. No. 1588 Aligaitor lode.</p>	
<p>Set an iron post, 30 ins. long, 3/4 in. diam., 12 ins. in the ground, in a concrete and rock base, with a brass cap firmly secured to the iron post, mkd. X E.B.11 1 U.S.M.S. 4862; from which</p>	
<p style="padding-left: 40px;">The $\frac{1}{4}$ sec. cor. of Secs. 1 and 6, T.12 N., Rs.1 & 2 W., G.& S.R.M., bears N.40°10'53"E., 3,141.95 ft. dist., hereinbefore described.</p>	
<p style="padding-left: 40px;">Cor. No. 1, M.S. No. 1588 Aligaitor lode, bears N.2°44'39"E., 411.89 ft. dist.</p>	

Mineral Survey No. 4862

FEET	
	<p>A wood post, 2 x 2 ins. in size, 4 ft. above ground, sets adjacent to the iron post.</p> <p>No local bearing objects or bearing trees available.</p> <p>Thence S.61°20'42"E.</p>
40.	Right bank of local drainage, 8 ft. wide, course S.5°W.
150.00	Lode line; discovery point bears S.38°28'34"W., 323.24 ft. dist.
300.00	<p>Cor. No. 2.</p> <p>Set an iron post, 30 ins. long, 3/4 in. diam., 12 ins. in the ground, in a concrete and rock base, with a brass cap firmly secured to the iron post, mkd. X E.B.11 2 U.S.M.S. 4862; from which</p> <p>A wood post, 2 x 2 ins. in size, 4 ft. above ground, sets adjacent to the iron post.</p> <p>No local bearing objects or bearing trees available.</p> <p>Thence S.38°28'34"W.</p>
309.99	Intersect line 1-2, M.S. No. 1588 Diller C lode, at a point from which Cor. No. 2 bears S.74°56'26"E., 51.07 ft. dist.
423.24	<p>Cor. No. 3.</p> <p>Set an iron post, 30 ins. long, 3/4 in. diam., 12 ins. in the ground, in a concrete and rock base, with a brass cap firmly secured to the iron post, mkd. X E.B.11 3 U.S.M.S. 4862; from which</p> <p>A wood post, 2 x 2 ins. in size, 4 ft. above ground, sets adjacent to the iron post.</p> <p>No local bearing objects or bearing trees available.</p> <p>Thence N.61°20'42"W.</p>
25.20	Intersect line 4-1, M.S. No. 1588 Aligaitor lode, at a point from which Cor. No. 1 bears N.2°44'39"E., 875.53 ft. dist.
115.	Left Bank of local drainage, 10 ft. wide, course S.20°W.
150.00	Lode line; discovery point bears N.38°28'34"E., 100.00 ft. dist.
300.00	Cor. No. 4, identical with Cor. No. 2 of the E.B. #12 lode and Cor. No. 4 of the E.B. #9 lode, both of this survey.

Mineral Survey No. 4862

FEET	
	Thence N.38°28'34"E.
36.40	Intersect line 1-2, M.S. No. 1588 Diller C lode, at a point from which Cor. No. 2 bears S.74°56'26"E., 373.21 ft. dist.
423.24	Cor. No. 1, and place of beginning.
	E.B. #7 LODE
	At Cor. No. 1 of the E.B. #7 lode, identical with Cor. No. 2, M.S. No. 644 Tremont lode and Cor. No. 3, M.S. No. 646 Delaware lode.
	Found a mkd. stone 4 x 10 ins. in size, 8 ins. above ground, firmly set, markings partly legible. I remove the stone and at the cor. point
	Set an iron post, 30 ins. long, 3/4 in. diam., 12 ins. in the ground, in a concrete and rock base, with a brass cap firmly secured to the iron post, mkd. X E.B.7 1 U.S.M.S. 4862; T.2 U.S.M.S. 644; D.3 U.S.M.S. 646; from which
	The 1/4 sec. cor. of Secs. 1 and 6, T.12 N., Rs.1 & 2 W., G.& S.R.M., bears S.43°44'09"E., 1,208.18 ft. dist., hereinbefore described.
	Cor. No. 4, M.S. Nos. 1660 & 2109 Palmetto lode, identical with Cor. No. 3, M.S. Nos. 1660 & 2110 Trapezoid lode, bears N.73°56'14"W., 632.62 ft. dist.
	A wood post, 2 x 2 ins. in size, 4 ft. above ground, sets adjacent to the iron post.
	The mkd. stone is buried alongside.
	No local bearing objects or bearing trees available.
	Thence S.41°35'28"W.
975.	Power line bears N.50°W. and S.50°E.
1,080.	Center of unimproved dirt road, 12 ft. wide, bears N.40°W. and S.40°E.
1,224.80	Intersect line 4-1, E.B. #10 lode of this survey.
1,414.70	Cor. No. 2, identical with Cor. No. 2, M.S. No. 646 Delaware lode, on line 1-2, M.S. No. 1588 Evergreen lode.
	Found a mkd. stone 7 x 12 ins. in size, 18 ins. above ground, not firmly set. I remove the stone and at the cor. point

Mineral Survey No. 4862

FEET	
	<p>Set an iron post, 30 ins. long, 3/4 in. diam., 12 ins. in the ground, in a concrete and rock base, with a brass cap firmly secured to the iron post, mkd. X E.B.7 2 U.S.M.S. 4862; D.2 U.S.M.S. 646; from which</p> <p style="padding-left: 40px;">A wood post, 2 x 2 ins. in size, 4 ft. above ground, sets adjacent to the iron post.</p> <p style="padding-left: 40px;">The mkd. stone is buried alongside.</p> <p>No local bearing objects or bearing trees available.</p> <p style="text-align: center;">Thence N.46°13'50"W.</p>
6.00	Cor. No. 1, M.S. No. 1588 Evergreen lode, identical with Cor. No. 2 of the E.B. #1 lode of this survey.
80.28	Intersect line 3-4, E.B. #10 lode of this survey.
135.	Center of unimproved dirt road, 12 ft. wide, bears North and South.
299.75	Lode line; discovery point bears N.41°35'28"E., 25.00 ft. dist.
565.	Center of unimproved dirt road, 12 ft. wide, bears N.85°E. and S.85°W.
599.50	Cor. No. 3, on line 1-2, E.B. #1 lode of this survey.
	Thence N.41°35'28"E.
504.59	Intersect line 2-3, M.S. Nos. 1660 & 2109 Palmetto lode, at a point from which Cor. No. 3 bears S.49°46'43"E., 169.97 ft. dist.
1,085.	Power line bears North and South.
1,118.77	Intersect line 4-1, M.S. Nos. 1660 & 2109 Palmetto lode, in part common with line 3-4, M.S. Nos. 1660 & 2110 Trapezoid lode, at a point from which Cor. No. 4 of the Palmetto lode, identical with Cor. No. 3 of the Trapezoid lode, bears S.49°28'E., 28.22 ft. dist.
1,175.	Center of unimproved dirt road, 12 ft. wide, bears N.65°W. and S.65°E.
1,414.70	<p>Cor. No. 4.</p> <p>Set an iron post, 30 ins. long, 3/4 in. diam., 12 ins. in the ground, in a concrete and rock base, with a brass cap firmly secured to the iron post, mkd. X E.B.7 4 U.S.M.S. 4862; from which</p> <p style="padding-left: 40px;">A wood post, 2 x 2 ins. in size, 4 ft. above ground, sets adjacent to the iron post.</p>

Mineral Survey No. 4862

FEET	
	<p>No other local bearing objects or bearing trees available.</p> <p>Thence S.46°13'50"E.</p>
15.	Center of unimproved dirt road, 12 ft. wide, bears N.35°E. and S.35°W.
70.84	Intersect line 2-3, M.S. Nos. 1660 & 2110 Trapezoid lode, at a point from which Cor. No. 3, identical with Cor. No. 4, M.S. Nos. 1660 & 2109 Palmetto lode, bears S.49°52'W., 295.80 ft. dist.
299.75	Lode line; discovery point bears S.41°35'28"W., 1,389.70 ft. dist.
599.50	Cor. No. 1, and place of beginning.
<hr/> <p>E.B. #10 LODE</p>	
<p>At Cor. No. 1 of the E.B. #10 lode.</p>	
<p>Set an iron post, 30 ins. long, 3/4 in. diam., 12 ins. in the ground, in a concrete and rock base, with a brass cap firmly secured to the iron post, mkd. X E.B.10 1 U.S.M.S. 4862; from which</p>	
<p>The $\frac{1}{4}$ sec. cor. of Secs. 1 and 6, T.12 N., Rs.1 & 2 W., G.& S.R.M., bears N.73°13'59"E., 1,203.32 ft. dist., hereinbefore described.</p>	
<p>Cor. No. 4, M.S. No. 1588 Premium lode, bears S.35°32'50"W., 154.48 ft. dist.</p>	
<p>A wood post, 2 x 2 ins. in size, 4 ft. above ground, sets adjacent to the iron post.</p>	
<p>No local bearing objects or bearing trees available.</p>	
<p>Thence S.29°20'54"W.</p>	
77.75	Intersect line 4-1, M.S. No. 1588 Premium lode, in part common with line 5-6, M.S. No. 646 Delaware lode, at a point from which Cor. No. 4, bears S.41°45'15"W., 77.64 ft. dist.; thence S.41°58'30"W., 154.77 ft. to Cor. No. 6 of the Delaware lode.
149.01	Intersect line 3-4, M.S. No. 1588 Premium lode, in part common with line 1-2, M.S. No. 1588 Blind Tom lode, and point for Cor. No. 1 of the Blind Tom lode, at a point from which Cor. No. 4 bears N.75°56'54"W., 17.29 ft. dist.
299.75	Lode line; discovery point bears N.58°29'52"W., 25.00 ft. dist.

Mineral Survey No. 4862

FEET	
599.50	<p>Cor. No. 2, identical with Cor. No. 2, M.S. No. 1588 Par Value lode, on line 4-1, M.S. No. 1588 Blind Tom lode.</p> <p>Found a stone in place, 4 x 6 ft. in size, properly mkd. and witnessed. At the chiseled "X" mark, I</p> <p>Set an iron post, 30 ins. long, 3/4 in. diam., 12 ins. in the ground, in a concrete and rock base, with a brass cap firmly secured to the iron post, mkd. X E.B.10 2 U.S.M.S. 4862; P.V.2 U.S.M.S. 1588; from which</p> <p style="padding-left: 40px;">A wood post, 2 x 2 ins. in size, 4 ft. above ground, sets adjacent to the iron post.</p> <p>No local bearing objects or bearing trees available.</p> <p style="text-align: center;">Thence N.58°29'52"W.</p>
98.92	<p>Cor. No. 1, M.S No. 1588 Par Value lode and intersect line 2-3, M.S. No. 1588 Evergreen lode, at a point from which Cor. No. 2 bears N.39°26'44"E., 289.06 ft. dist.</p>
550.	<p>Center of unimproved dirt road, 12 ft. wide, bears North and South.</p>
694.40	<p>Intersect line 4-1, M.S. No. 1588 Evergreen lode, in part common with line 2-3, E.B. #1 lode of this survey, at a point from which Cor. No. 1 of the Evergreen lode, identical with Cor. No. 2 of the E.B. #1 lode, bears N.38°30'57"E., 416.51 ft. dist.</p>
700.00	<p>Cor. No. 3.</p> <p>Set an iron post, 30 ins. long, 3/4 in. diam., 12 ins. in the ground, in a concrete and rock base, with a brass cap firmly secured to the iron post, mkd. X E.B.10 3 U.S.M.S. 4862; from which</p> <p style="padding-left: 40px;">A wood post, 2 x 2 ins. in size, 4 ft. above ground, sets adjacent to the iron post.</p> <p>No local bearing objects or bearing trees available.</p> <p style="text-align: center;">Thence N.29°20'54"E.</p>
299.75	<p>Lode line; discovery point bears S.58°29'52"E., 675.00 ft. dist.</p>
380.	<p>Center of unimproved dirt road, 12 ft. wide, bears N.5°W. and South.</p>
429.48	<p>Intersect line 1-2, E.B. #1 lode of this survey, in part common with line 2-3, E.B. #7 lode of this survey.</p>

Mineral Survey No. 4862

FEET	
599.50	<p>Cor. No. 4.</p> <p>Set an iron post, 30 ins. long, 3/4 in. diam., 12 ins. in the ground, in a concrete and rock base, with a brass cap firmly secured to the iron post, mkd. X E.B.10 4 U.S.M.S. 4862; from which</p> <p>Cor. No. 2, M.S. No. 646 Delaware lode, identical with Cor. No. 2 of the E.B. #7 lode of this survey, bears S.7°05'36"W., 205.31 ft.</p> <p>Cor. No. 1, M.S. No. 1588 Evergreen lode, identical with Cor. No. 2 of the E.B. #1 lode of this survey, bears S.8°27'36"W., 201.78 ft.</p> <p>A wood post, 2 x 2 ins. in size, 4 ft. above ground, sets adjacent to the iron post.</p> <p>No local bearing objects or bearing trees available.</p> <p>Thence S.58°29'52"E.</p>
118.11	<p>Intersect line 2-3, M.S. No. 646 Delaware lode, common with line 1-2, E.B. #7 lode of this survey, at a point from which Cor. No. 2, identical with Cor. No. 2 of the E.B. #7 lode, bears S.41°35'28"W., 189.90 ft. dist.</p>
700.00	<p>Cor. No. 1, and place of beginning.</p> <hr/> <p>E.B. #12 LODE</p> <p>Beginning at Cor. No. 1 of the E.B. #12 lode, identical with Cor. No. 1 of the E.B. #9 lode of this survey.</p> <p>Thence S.61°20'42"E.</p>
80.94	<p>Intersect line 4-1, E.B. #8 lode of this survey, common with line 3-4, M.S. No. 1588 Mexia lode.</p>
119.31	<p>Intersect line 2-3, M.S. No. 1588 Mexia lode, at a point from which Cor. No. 3, identical with Cor. No. 1 of the E.B. #8 lode of this survey, bears S.30°31'06"W., 10.04 ft. dist.</p>
299.75	<p>Lode line; discovery point bears S.26°04'30"W., 25.00 ft. dist.</p>
457.40	<p>Intersect line 1-2, M.S. No. 1588 Diller C lode, at a point from which the point for Cor. No. 1 bears N.74°56'26"W., 87.01 ft. dist.</p>
599.50	<p>Cor. No. 2, identical with Cor. No. 4 of the E.B. #9 lode and Cor. No. 4 of the E.B. #11 lode, both of this survey.</p>

Mineral Survey No. 4862

FEET	
	Thence S.26°04'30"W.
1,110.	Center of unimproved dirt road, 12 ft. wide, bears N.75°E. and S.75°W.
1,461.81	Intersect line 3-4, M.S. No. 1588 Diller C lode, at a point from which the point for Cor. No. 4 bears N.74°56'26"W., 252.74 ft. dist.
1,485.19	Cor. No. 3. Set an iron post, 30 ins. long, 3/4 in. diam., 12 ins. in the ground, in a concrete and rock base, with a brass cap firmly secured to the iron post, mkd. X E.B.12 3 U.S.M.S. 4862; from which A wood post, 2 x 2 ins. in size, 4 ft. above ground, sets adjacent to the iron post. No local bearing objects or bearing trees available.
	Thence N.61°20'42"W.
97.63	Intersect line 3-4, M.S. No. 1588 Diller C lode, at a point from which the point for Cor. No. 4 bears N.74°56'26"E., 153.37 ft. dist.
175.	Left bank of Crooks Creek, 50 ft. wide, course S.13°E.
247.83	Intersect line 4-1, M.S. No. 1588 Diller C lode, at a point from which the point for Cor. No. 4 bears S.26°52'W., 36.08 ft. dist.
299.75	Lode line; discovery point bears N.26°04'30"E., 1,460.19 ft. dist.
400.	Center of unimproved dirt road, 12 ft. wide, bears N.57°W. and S.57°E.
597.52	Intersect line 1-2, E.B. #8 lode of this survey.
599.50	Cor. No. 4. Set an iron post, 30 ins. long, 3/4 in. diam., 12 ins. in the ground, in a concrete and rock base, with a brass cap firmly secured to the iron post, mkd. X E.B.12 4 U.S.M.S. 4862; from which A wood post, 2 x 2 ins. in size, 4 ft. above ground, sets adjacent to the iron post. No local bearing objects or bearing trees available.

Mineral Survey No. 4862

FEET	
	Thence N.26°04'30"E.
50.	Center of Senator Highway, an unimproved road, 20 ft. wide, bears N.85°W. and S.85°E.
90.	Right bank of Crooks Creek, 50 ft. wide, course S.40°E.
230.	Center of unimproved dirt road, 12 ft. wide, bears N.85°W. and S.85°E.
1,485.19	Cor. No. 1, and place of beginning.
	AREAS
	Acres
	Total area, E.B. #1 lode ----- 20.556
	Total area, E.B. #2 lode ----- 20.556
	Total area, E.B. #3 lode ----- 20.556
	Area in conflict with:
	Gen. No. 173 DeVernon lode ----- 7.652
	Total area, E.B. #4 lode ----- 20.095
	Area in conflict with:
	M.S. No. 1588 Mexia lode ----- 0.005
	M.S. No. 1588 Evergreen lode ----- 0.001
	Total area, E.B. #5 lode ----- 20.095
	Total area, E.B. #6 lode ----- 20.095
	Total area, E.B. #7 lode ----- 19.456
	Area in conflict with:
	M.S. Nos. 1660 & 2109 Palmetto lode ----- 1.397
	M.S. Nos. 1660 & 2110 Trapezoid lode ----- 0.335
	Total area, E.B. #8 lode ----- 20.124
	Total area, E.B. #9 lode ----- 19.528
	Area in conflict with:
	M.S. No. 1588 Aligaitor lode ----- 1.712
	M.S. No. 1588 Aligaitor lode, exclusive of its conflict with Blind Tom lode of the same survey ----- 1.692
	M.S. No. 1588 Blind Tom lode ----- 3.708
	M.S. No. 1588 Diller C lode ----- 0.059
	M.S. No. 1588 Mexia lode ----- 1.143
	E.B. #8 lode of this survey ----- 0.019

Mineral Survey No. 4862

FEET	AREAS	Acres
	Total area, E.B. #10 lode -----	9.627
	Area in conflict with:	
	M.S. No. 646 Delaware lode -----	3.373
	M.S. No. 1588 Evergreen lode -----	4.805
	M.S. No. 1588 Premium lode -----	0.014
	E.B. #1 lode of this survey -----	0.381
	E.B. #7 lode of this survey -----	0.405
	Total area, E.B. #11 lode -----	2.872
	Area in conflict with:	
	M.S. No. 1588 Aligaitor lode -----	1.557
	M.S. No. 1588 Aligaitor lode, exclusive of its conflict with Diller C lode of the same survey -----	1.422
	M.S. No. 1588 Diller C lode -----	0.508
	Total area, E.B. #12 lode -----	20.419
	Area in conflict with:	
	M.S. No. 1588 Diller C lode -----	8.046
	M.S. No. 1588 Mexia lode -----	0.004
	E.B. #8 lode of this survey -----	2.061
	LOCATION	
	This survey is located in the NE $\frac{1}{4}$, NW $\frac{1}{4}$, SE $\frac{1}{4}$ & SW $\frac{1}{4}$ Sec. 1, and NE $\frac{1}{4}$ & NW $\frac{1}{4}$ Sec. 12, T.12 N., R.2 W., G.& S.R.M.	
	The survey of the E.B. #s 1-12 lodes is identical with the locations or amended locations as marked on the ground.	
	EXPENDITURES	
	The improvements and the value of the labor and improvements made upon or for the benefit of each of the lode locations embraced in said mining claim by the claimant or its grantors are as follows:	
No. 1	The discovery point of the E.B. #1 lode is on the lode line, 25. ft. from a point on line 3-4, 299.75 ft. from Cor. No. 3, a post and notice. Value, None.	
No. 1	The discovery point of the E.B. #2 lode is on the lode line, 25. ft. from a point on line 2-3, 299.75 ft. from Cor. No. 2, a post and notice. Value, None.	

Mineral Survey No. 4862

FEET	
No. 1	The discovery point of the E.B. #3 lode is on the lode line, 25. ft. from a point on line 2-3, 299.75 ft. from Cor. No. 2, a post and notice. Value, None.
No. 1	The discovery point of the E.B. #4 lode is on the lode line, 25. ft. from a point on line 3-4, 299.75 ft. from Cor. No. 3, a post and notice. Value, None.
No. 1	The discovery point of the E.B. #5 lode is on the lode line, 25. ft. from a point on line 2-3, 299.75 ft. from Cor. No. 2, a post and notice. Value, None.
No. 1	The discovery point of the E.B. #6 lode is on the lode line, 25. ft. from a point on line 3-4, 299.75 ft. from Cor. No. 3, a post and notice. Value, None.
No. 1	The discovery point of the E.B. #7 lode is on the lode line, 25. ft. from a point on line 2-3, 299.75 ft. from Cor. No. 2, a post and notice. Value, None.
No. 1	The discovery point of the E.B. #8 lode is on the lode line, 25. ft. from a point on line 4-1, 299.78 ft. from Cor. No. 4, a post and notice. Value, None.
No. 1	The discovery point of the E.B. #9 lode is on the lode line, 25. ft. from a point on line 4-1, 299.75 ft. from Cor. No. 4, a post and notice. Value, None.
No. 1	The discovery point of the E.B. #10 lode is on the lode line, 25. ft. from a point on line 1-2, 299.75 ft. from Cor. No. 1, a post and notice. Value, None.
No. 1	The discovery point of the E.B. #11 lode is on the lode line, 100. ft. from a point on line 3-4, 150.00 ft. from Cor. No. 3, a post and notice. Value, None.
No. 1	The discovery point of the E.B. #12 lode is on the lode line, 25. ft. from a point on line 1-2, 299.75 ft. from Cor. No. 1, a post and notice. Value, None.

Mineral Survey No. 4862

FEET

OTHER IMPROVEMENTS

An adit (caved), the portal of which bears S.51°W., 760 ft. from Cor. No. 4 of the E.B. #6 lode.

Claimant unknown.

A cut with an adit at the north end. The south end of the cut bears N.10°W., 220 ft. from Cor. No. 2 of the E.B. #3 lode; 20 ft. wide, running N.20°E., 45 ft. to a face 8 ft. high and an adit 4 x 5 ft. in size running N.20°E., length unknown.

Claimant unknown.

A cut with an adit at the north end. The south end of the cut bears N.72°W., 150 ft. from Cor. No. 2 of the E.B. #3 lode; 10 ft. wide, running N.20°E., 75 ft. to a face 15 ft. high and an adit, 4 x 5 ft. in size, running N.25°E., length unknown, partially caved.

Claimant unknown.

A cut with an adit at the east end. The west end bears S.71°W., 180 ft. from Cor. No. 4 of the E.B. #6 lode; 6 ft. wide, running S.88°E., 18 ft. to a face 8 ft. high and an adit, 4 x 6 ft. in size, running S.88°E., 10 ft.

Claimant unknown.

An adit, partially caved and water filled, the portal of which bears N.31°W., 70 ft. from Cor. No. 3 of the E.B. #11 lode; approximately 4 x 5 ft. in size, running N.81°W., length unknown.

Claimant unknown.

OTHER CORNER DESCRIPTIONS
AND SUPPLEMENTAL DATA

Gen. No. 173, Lot No. 45 DeVernon lode: Cor. No. 1 could not be found. Cor. No. 2 is a granite stone 4 x 15 ins., 10 ins. above ground, firmly set, mkd. V., other markings illegible. Cor. No. 3 is a stone 9 x 7 ins., 7 ins. above ground, not firmly set, mkd. D.V., other markings illegible. Cor. No. 4 is a granite stone 6 x 14 ins., 9 ins. above ground, not firmly set, mkd. D.V., other markings illegible. Line 2-3 was found to be S.47°25'48"W., 1,468.86 ft. instead of S.46°30'W., 1,500.00 ft. as approved. Line 3-4 was found to be S.43°33'19"E., 580.20 ft. instead of S.43°30'E., 600.00 ft. as approved. Line 4-1 was determined by proportion and found to be N.47°42'32"E., 1,477.54 ft. instead of N.46°30'E., 1,500.00 ft. as approved.

M.S. No. 644 Tremont lode: Cor. No. 2, identical with Cor. No. 3, M.S. No. 646 Delaware lode and Cor. No. 1 of the E.B. #7 lode of this survey, described above. Line 1-2, common with line 3-4, M.S. No. 646 Delaware lode, and line 2-3 are shown as approved.

Mineral Survey No. 4862

FEET

M.S. No. 646 Delaware lode: Cor. No. 1 could not be found. Cor. No. 2, identical with Cor. No. 2 of the E.B. #7 lode of this survey, described above. Cor. No. 3, identical with Cor. No. 1 of the E.B. #7 lode of this survey, and Cor. No. 2, M.S. No. 644 Tremont lode, described above. Cor. No. 5 was a mkd. stone, not in place. Cor. No. 6 is a stone 3 x 5 ft., flush with the ground, mkd. D No. 6. Line 1-2 is based on the bearing from Cor. No. 6 to Cor. No. 2. Line 2-3 was found to be N.41°35'28"E., 1,414.70 ft. instead of N.41°12'E., 1,410.00 ft. as approved. Line 3-4, common with line 1-2, M.S. No. 644 Tremont lode, described above. Line 5-6, in part common with line 4-1, M.S. No. 1588 Premium lode, is described as follows: From Cor. No. 1 to Cor. No. 4 of the Premium lode was found to be S.41°45'15"W., 1,243.05 ft. instead of S.42°05'W., 1,243.00 ft. as approved. From Cor. No. 4 of the Premium lode to Cor. No. 6 was found to be S.41°58'30"W., 154.77 ft. instead of S.42°05'W., 157.20 ft. as approved. Line 6-1-2 was found to be N.46°47'49"W., 588.35 ft. instead of N.44°48'W., 600.00 ft. as approved.

M.S. Nos. 1660 & 2109 Palmetto lode: Cor. No. 2, identical with Cor. No. 3 of the Betsey Ann lode of the same survey could not be found. Cor. No. 3 is a stone 6 x 12 ins. 16 ins. above ground, not firmly set, properly mkd. Cor. No. 4, identical with Cor. No. 3, M.S. Nos. 1660 & 2110 Trapezoid lode is a stone 6 x 10 ins. 21 ins. above ground, not firmly set, properly mkd. The bearing of line 2-3 was determined from Cor. No. 4 of the Betsey Ann lode and Cor. No. 3 of the Palmetto lode. It was found to be S.49°46'43"E., instead of S.49°28'E., as approved. Line 3-4 was found to be N.28°31'34"E., 626.86 ft. instead of N.31°15'E., 580.00 ft. as approved. Line 4-1, in part common with line 3-4, M.S. No. 2110 Trapezoid lode is shown as approved.

M.S. Nos. 1660 & 2110 Trapezoid lode: Cor. No. 2 could not be found. Cor. No. 3, identical with Cor. No. 4, M.S. No. 2109 Palmetto lode, described above. Cor. No. 4, identical with Cor. No. 1, M.S. No. 38 Storm Cloud lode, could not be found. Line 2-3 is shown as approved. Line 3-4, in part common with line 4-1, M.S. No. 2109 Palmetto lode, described above.

M.S. No. 1588 Evergreen lode: Cor. No. 1, identical with Cor. No. 2 of the E.B. #1 lode of this survey, described above. Cor. No. 2 is a rebar with bearing tree. Cors. Nos. 3 and 4 are identical with Cors Nos. 2 and 1 respectively of the Mexia lode of the same survey. The points for these cors. were calculated by proportion. Cor. No. 4 was determined by proportion using Cor. No. 1 and Cor. No. 4 of the Mexia lode of the same survey. Cor. No. 3 was determined by proportion using Cor. No. 2 and Cor. No. 3 of the Mexia lode of the same survey. Line 1-2 was found to be S.46°13'50"E., 598.23 ft. instead of S.46°33'E., 600.00 ft. as approved. Line 2-3, in part common with line 4-1, Par Value lode of the same survey, was found as follows: From Cor. No. 2 to Cor.

Mineral Survey No. 4862

FEET

No. 1 of the Par Value lode of the same survey was found to be S.39°26'44"W., 289.06 ft. instead of S.38°42'W., 303.50 ft. as approved. From Cor. No. 1 to Cor. No. 4 of the Par Value lode was found to be S.38°02'01"W., 633.53 ft. instead of S.38°42'W., 617.80 ft. as approved. From Cor. No. 4 of the Par Value lode to Cor. No. 3 was found to be S.38°28'34"W., 578.70 ft. instead of S.38°42'W., 578.70 ft. as approved. Line 3-4, common with line 1-2, Mexia lode of the same survey, was found to be N.46°26'31"W., 599.08 ft. instead of N.46°33'W., 600.00 ft. as approved. Line 4-1, in part common with line 2-3 of the E.B. #1 lode of this survey, was found to be N.38°30'57"E., 1,503.36 ft. instead of N.38°42'E., 1,500.00 ft. as approved.

M.S. No. 1588 Mexia lode: Cors. Nos. 1 and 2, identical with Cors. Nos. 4 and 3 respectively of the Evergreen lode of the same survey, described above. Cors. Nos. 3 and 4, identical with Cors. Nos. 1 and 4 respectively of the E.B. #8 lode of this survey, described above. Line 1-2, common with line 3-4, Evergreen lode of the same survey, described above. Line 2-3 was found to be S.30°31'06"W., 859.16 ft. instead of S.30°44'W., 858.00 ft. as approved. Line 3-4, common with line 4-1 of the E.B. #8 lode of this survey, described above. Line 4-1 was found to be N.30°34'07"E., 860.29 ft. instead of N.30°44'E., 858.00 ft. as approved.

M.S. No. 1588 Premium lode: Cor. No. 1 is a granite stone 3 x 12 ins., 16 ins. above ground, not firmly set, markings partially legible. Cor. No. 3 could not be found. Cor. No. 4, on line 5-6, M.S. No. 646 Delaware lode, is a granite stone 5 x 12 ins., 24 ins. above ground, not firmly set, markings partially legible. Line 3-4, in part common with line 1-2, Blind Tom lode of the same survey, is described as follows: From Cor. No. 3 to Cor. No. 1 of the Blind Tom lode of the same survey is shown as calculated by proportion for line 1-2 of the Blind Tom lode. This was found to be S.60°19'14"E., 599.87 ft. instead of S.60°23'E., 600.00 ft. as approved. From Cor. No. 1 of the Blind Tom lode to Cor. No. 4 was found to be N.75°56'54"W., 17.29 ft. instead of N.60°23'W., 17.10 ft. as approved. Line 4-1 was found to be N.41°45'15"E., 1,243.05 ft. instead of N.42°05'E., 1,243.00 ft. as approved.

M.S. No. 1588 Blind Tom lode: Cors. Nos. 1, 3 and 4 could not be found. The point for Cor. No. 2 was established from a bearing rock. Lines 1-2, in part common with line 3-4, Premium lode of the same survey; 3-4 and 4-1, in part common with line 2-3, Par Value lode of the same survey, were calculated by proportion using Cor. No. 2 and Cor. No. 2 of the Diller C. lode of the same survey. No intermediate cors. of the Aligaitor lode of the same survey could be found. Line 1-2 was found to be S.60°19'14"E., 599.87 ft. instead of S.60°23'E., 600.00 ft. as approved. Line 3-4, shown from its intersection with line 1-2, Aligaitor lode of the same survey, to Cor. No. 4 was found to be N.60°26'43"W., 300.06 ft.

Mineral Survey No. 4862

FEET

instead of N.60°23'W., 300.00 ft. as approved. Line 4-1 is described as follows: From Cor. No. 4 to Cor. No. 3 of the Par Value lode of the same survey, was found to be N.29°46'27"E., 427.64 ft. instead of N.29°37'E., 436.00 ft. as approved. From Cor. No. 3 to Cor. No. 2, Par Value lode of the same survey, was found to be N.29°40'23"E., 620.25 ft. instead of N.29°37'E., 610.10 ft. as approved. From Cor. No. 2 of the Par Value lode to Cor. No. 1 of the Blind Tom lode, both of the same survey, was found to be N.29°20'54"E., 450.49 ft. instead of N.29°37'E., 453.90 ft. as approved.

M.S. No. 1588 Par Value lode: The point for Cor. No. 1 was established from a bearing rock. Cor. No. 2, identical with Cor. No. 2 of the E.B. #10 lode of this survey, and on line 4-1, M.S. No. 1588 Blind Tom lode, described above. Cors. Nos. 3 and 4 could not be found. The point for Cor. No. 4 was established at the record distance from Cor. No. 3, on line 2-3, Evergreen lode of the same survey. The point for Cor. No. 3 was then calculated by proportion between Cors. Nos. 2 and 4. Line 1-2 was found to be S.58°29'52"E., 98.92 ft. instead of S.60°23'E., 93.3 ft. as approved. Line 2-3, described above. Line 3-4 was found to be N.61°20'42"W., 191.02 ft. instead of N.60°23'W., 190.8 ft. as approved. Line 4-1, described above.

M.S. No. 1588 Aligaitor lode: Cors. Nos. 1, 2 and 4 could not be found. The point for Cor. No. 1, and the bearings of lines 1-2 and 4-1 were calculated by proportion from Cor. No. 2 of the Blind Tom lode of the same survey and Cor. No. 2 of the Diller C lode of the same survey. Line 1-2 was found to be N.78°34'19"E., 309.23 ft. from Cor. No. 1 to its intersection with line 3-4 of the Blind Tom lode of the same survey, instead of N.78°32'E., 309.54 ft. as approved. Line 4-1 was found to be N.2°44'39"E., 775.22 ft. from its intersection with line 1-2, Diller C lode of the same survey to Cor. No. 1, instead of N.2°47'E., 775.9 ft. as approved. Line 4-1, from the above intersection south to its intersection with line 3-4, E.B. #11 lode of this survey, is shown with the same bearing.

M.S. No. 1588 Diller C lode: Cor. No. 1, a marked stone, was found, but was loose on the surface of the ground and not in place, so I did not accept it as the point for the corner. The point for Cor. No. 2 was established from a bearing rock. Cors. Nos. 3 and 4 are completely lost. A diligent search was made for the corners and the bearing trees, but they no longer exist. The bearing of line 1-2 was calculated by proportion from Cor. No. 2 of the Blind Tom lode of the same survey and Cor. No. 2. The bearing of line 1-2 from its intersection with line 4-1, Aligaitor lode of the same survey, to Cor. No. 2, was found to be S.74°56'26"E., 141.97 ft. instead of S.74°53'E., 141.90 ft. as approved. From the above intersection to Cors. Nos. 1 and 2, line 1-2 is shown with the same bearing and a record distance of 612.80 ft. Lines 2-3 and 4-1 are

Mineral Survey No. 4862

FEET

shown as approved. Line 3-4 is shown as N.74°56'26"W., 612.80 ft. so that the end lines will be parallel.

MEMORANDUM

None

FIELD ASSISTANTS

Name	Capacity
Kent Miller	Assistant Instrumentman
Wayne Smith	Rodman-Chainman

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

CERTIFICATE OF SURVEYOR

Name of Mineral Surveyor

Date

Harvey W. Smith


January 25, 1996

I HEREBY CERTIFY That in pursuance of an order received from the Arizona State Office, Bureau of Land Management, at Phoenix, Arizona, dated October 31, 1986, I have carefully executed the survey of the claim of Eddie Basha, known as the E.B. #1, E.B. #2, E.B. #3, E.B. #4, E.B. #5, E.B. #6, E.B. #7, E.B. #8, E.B. #9, E.B. #10, E.B. #11 and E.B. #12, lodes, situated in surveyed sections 1 and 12, Township 12 North, Range 2 West, Gila and Salt River Meridian, in the State of Arizona.

This survey, designated as number 4862, has been executed by me and under my direction and has been made in strict conformity with said order, the Manual of Instructions for the Survey of Public Lands of the United States, and in specific manner described in the foregoing field notes.

I FURTHER CERTIFY That the labor expended and improvements made upon and for the benefit of the E.B. #1, E.B. #2, E.B. #3, E.B. #4, E.B. #5, E.B. #6, E.B. #7, E.B. #8, E.B. #9, E.B. #10, E.B. #11 and E.B. #12 lode locations embraced in the said mining claim by claimant or its grantors are fully stated in my report. The character, extent, location, and itemized value are specified in full detail. No portion of, or interest in, said labor and improvements so credited to this claim has been included in the estimate of expenditures upon any other claim.

Scottsdale, Arizona
(Location)


(Signature of Mineral Surveyor)

Title 18, U.S.C. section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious, or fraudulent statements or representations as to any matter within its jurisdiction.

CERTIFICATE OF APPROVAL

Arizona State Office
Phoenix, Arizona
January 31, 1996

The foregoing field notes of mineral survey number 4862, in surveyed sections 1 and 12, Township 12 North, Range 2 West, Gila and Salt River Meridian, in the State of Arizona, executed by Harvey W. Smith, Mineral Surveyor, under order dated October 31, 1986, having been critically examined and the necessary corrections made prior to their certification by the surveyor, the field notes and the survey therein described are hereby approved.

Debra K. McKay
(Authorized Signature)

Acting Chief Cadastral Surveyor of Arizona
(Title)

~~CERTIFICATE OF TRANSCRIPT~~

I HEREBY CERTIFY That the foregoing transcript of field notes of the above-described mineral survey number 4862 is a true copy of the original field notes.

~~_____
(Authorized Signature)~~

~~Acting Chief Cadastral Surveyor of Arizona
(Title)~~