

BOOK 122

SUBDIVISION

T 13 N R 11 E

CONTRACT NO 62

A. CONZEN

U. S. DEP SUR

No. 122

4-671

FIELD NOTES

GENERAL LAND OFFICE

122

No. 122

BOOK 122

BOOK

122

No - 122.

Field Notes
of the
Subdivision lines
of
Township 13 North Range 11 East
of the
Gila & Salt River Base & Meridian
in the
Territory of Arizona.
as surveyed by
Philip Coutzer
U.S. Deputy Surveyor
under his Contract No 62
Dated Dec. 21. 1899

Survey commenced Aug 17. 1900
Survey completed Sept. 6th 1900

IA.

^{BOOK}
NO - 122
¹²²

(4-674.)

Township 13. N. R. 11. E.

Index for Books 122, 123 and 124 ¹²²

137

6	133	5	97	4	72	3	49	2	25	1
131	—	129	—	95	—	69	—	47	—	23
7	126	8	92	9	67	10	45	11	20	12
124	—	123	—	90	—	65	—	43	—	18
18	121	17	88	16	63	15	41	14	15	13
118	—	116	—	85	—	61	—	38	—	13
19	113	20	83	21	60	22	36	23	11	24
112	—	109	—	81	—	57	—	34	—	8
30	106	29	79	28	56	27	31	26	6	25
104	—	102	—	77	—	54	—	30	—	3
31	99	32	74	33	51	34	27	35	1	36

Subdivision of T13N R11E

chains

a.m.

Aug 17, 1900. at $7^{\text{h}} 35^{\text{m}}$, L.M.T.
I set off $34^{\circ} 28'$ on the Lat. arc;
 $13^{\circ} 28' N$ on decl. arc and
determine a true meridian
with the solar at the
Cor. to secs. 35 and 36 on
the south boundary of the
Township 13 N. Range 11 E. as
heretofore described.
Thence I run
North, bet. secs. 35 and 36
on the sectional guide meridian.
Descent

- | | |
|-------|--|
| 16.00 | Draw 80'ks. wide, course N.E.
ascend |
| 23.00 | Top of ascent, bears N.E. and S.W. |
| 29.80 | Trail, bears N.E. and S.W. |
| 40.00 | Set a Quartzite stone $18 \times 14 \times 7$ ins.
12 ins. in the ground for $\frac{1}{4}$ sec.
Cor. marked $\frac{1}{4} S 35'$ on W |

Subdivision of T 13 N. R 11 E continued
chains

face. 36 on E. face. from which
a Pine 5 ins. diam. bears
 $N 17\frac{1}{2}^{\circ} E$ 20 lks. dist. marked.

1/4 S. 36. B.T.

a Pine 12 ins. diam. bears
 $S 85\frac{1}{2}^{\circ} W$ 12 lks. dist. marked

1/4 S 35 B.T.

61.00 Descend

65.00 Draw 100 lks. wide, course NE; ascend

68.10 Pine tree 20 ins. diam. on line
marked with 2 notches on N
and S

74.00 Top of ascent, bears NE and SW

80.00 Set a Quartzite stone 18x8x8 ins.
12 ins. in the ground for cor
to secs. 25, 26, 35 and 36
marked with 1 notch on S and
1 notch on E edges, from which
a Pine 6 ins. diam. bears

Subdivision of T 13 N. R 11 E. cou.
chains

N 59° E. 50 lks. dist. marked

T 13 N. R 11 E. S 25. BT.

a Pine 7 ins. diam. bears

S 76 $\frac{3}{4}$ ° E. 28 lks. dist. marked

T 13 N. R 11 E. S 36. BT.

a Pine 30 ins. diam. bears

S 21 $\frac{1}{4}$ ° W. 65 lks. dist. marked

T 13 N. R 11 E. S 35. BT.

a Pine 12 ins. diam. bears

N 67 $\frac{3}{4}$ ° W. 138 lks. dist. marked

T 13 N. R 11 E. S 26. BT.

Land rolling

Soil gravelly. 2nd rate

Timber. Pine. undergrowth

Pine.

Heavily timbered land 80, etc

East. bet secs. 25 and 36

on a true line

over rolling land

Subdivision of T13N.R11E. con't.
chains

2.20 Descend

11.00 Enter draw, course N N Westerly

13.10 Trail bears Northerly.

14.50 Spring 30 lbs, N.

15.00 Leave draw and ascend

28.00 Top of ascent

40.00 Set a Quartzite stone 18x10x6 ins.
12 ins. in the ground for $\frac{1}{4}$ sec.
Cor. marked $\frac{1}{4}S\ 25^\circ$ on N face.
 36 on S face. from which
a Pine 5 ins. diam. bears
 $N 1\frac{1}{2}^\circ E.$ 58 lbs. dist. marked
 $\frac{1}{4}S\ 25^\circ$ B.T.

A Pine 14 ins. diam. bears
 $S 82\frac{3}{4}^\circ E.$ 48 lbs. dist. marked

$\frac{1}{4}S\ 36^\circ$ B.T.

50.00 Descend

60.40 Deep cañon 40 lbs. wide, course N.
ascend

5

Sub-division of T 13 N. R 11 E. cou.
chains

- 69.00 Top of ascent
- 76.69 intersect East boundary of
Tfr. 51 eks. N $2^{\circ}33'$ W of cor.
secs. 30 and 31.
- Set a Sandstone 18x10x4 ins.
12 ins. in the ground for
closing cor. to secs 25 and 36
marked c.c. on W. face
with 1 groove on S. and 5
grooves on N face. from which
a Pine, 10 ins. diam. bears
 $N 58\frac{1}{2}^{\circ}$ W. 24 eks. dist. marked
T 13 N. R 11 E. S 25. BT.
- A Pine 16 ins. diam. bears
 $S 38^{\circ}$ W. 83 eks. dist. marked
T 13 N. R 11 E. S 36. BT.
- Land rolling.
- Dirt gravelly 2nd & 3rd rate
Timber, Pine.
- Heavily timbered land 76.69. chs.

Subdivision of T13N. R11E. con't
chains

North, bet. secs. 25 and 26
on the sectional guide meridian,
over rolling land.

13.35 Pine tree 15 ins. diam., on line
marked with 2 notches on N and S

19.50 Descend

26.10 Trail, bears N.Westerly

31.00 Cañon 20 eks. wide, course N.Easterly

33.00 along north bank of cañon.

40.00 Bet a Sand Stone $18 \times 2\frac{1}{2} \times 8$ ins. 12 ins.
in the ground for $\frac{1}{4}$ sec. cor.
marked $\frac{1}{4}S 26$ on W. face. 25 on
E face, from which.

A pine 10 ins. diam. bears
 $N 18\frac{3}{4}^{\circ} W.$ 54 eks. dist. marked

$\frac{1}{4}S 26$. B.T.

A pine 12 ins. diam. bears

$S 40\frac{3}{4}^{\circ} E.$ 53 eks. dist. marked

$\frac{1}{4}S 25$, B.T.

Subdivision of T13N. R11E. con.
chains

- 41.00 Bottom of cañon 40-eks. wide
course N.N.Westerly; ascend
- 46.00 Top of ascent. Thence along
east side of cañon
- 80.00 The point for sec. cor. falls
on steep bluff.
- 81.00 a sandstone in place 16x16x8
ins. above ground for witness
cor. to cor. of secs. 23, 24, 25 and
26. marked W.C. with 2 notches
on S. and 1 notch on E. ~~face~~ edges,
from which,
- a Pine 7 ins. diam. bears
 $N72^{\circ}E.$ 15 eks. dist. marked
W.C. T13N. R11E. S 24. B.T.
- a Pine 8 ins. diam. bears $S45^{\circ}E$
8 eks. dist. marked W.C. T13N. R11E.
S. 25 B.T.
- a Pine 10 ins. diam. bears

8

Subdivision of T 13 N. R 11 E. cor chains

876°W. 41 ects. dist. marked

WC. T 13 N. R 11 E. S 26 B.T.

A Pine 10 ins. diam. bears. N 25°W
13 ects. dist. marked WC. T 13 N. R 11 E.

S 23. B.T.

Land rolling and broken.

Soil, gravelly, 2nd & 3rd rate.

Timber. Pine.

Heavily timbered land 80. chs.

East on a true line between 24th, 25.
from cor. pt.

over rolling and broken land
ascending.

- | | |
|-------|--|
| 4.00 | Top of bank, bears N and S |
| 26.50 | Gulch 10 ects. wide, course southerly |
| 40.00 | Set a Sand Stone 18x14x6 ins.
12 ins. in the ground for $\frac{1}{4}$
sec. cor. marked $\frac{1}{4}S24$ on N |

Subdivision of T13 N. R11 E. cor.

chains

face, 25 on S face, from which

A Pine 16 ins. diam. bears

$N71^{\circ}W$. 52 lks. dist. marked

145.24 B.T.

A Pine 24 ins. diam. bears

$S16\frac{1}{2}^{\circ}W$. 55 lks. dist. marked

145.26 B.T.

48.50 Descend

58.00 Cañon walls wide, course N.
ascend

60.00 top of ascent

61.75 Trail bears N and S

70.15 Isolated quartz rock 2x3 ft. 5 ft high.
15 lks. N of line.

73.27 Intersect East boundary of
Twp. $N2^{\circ}33'W$. 1.27 chs. N of
cor. to secs. 19 and 30.

Get a Limestone 18 x 15 x 6 ins.
12 ins. in the ground for
closing cor. to secs. 24 and 25.

Sub-division of T 13 N. R 11 E. con.
chains

marked CC. on W. face, with
2 grooves on S and 4 grooves
on N faces, from which
A Pine 14 ins. diam. bears
N $85\frac{1}{4}^{\circ}$ W. 108 lks. dist. marked
T 13 N. R 11 E. S 24. B.T.

A Pine 8 ins. diam. bears
S $42\frac{1}{4}^{\circ}$ W. 48 lks. dist. marked
T 13 N. R 11 E. S 25. B.T.
Land rolling and broken
Soil, gravelly, 2nd & 3rd rate
Timber, Pine, some oak
Heavily timbered land 73.27 chs.

Aug 17. 1900.

Aug 18. 1900. at 8 a.m. L.M.T. I
set off $34^{\circ}29'$ on the lat. arc;
 $13^{\circ}08'$ N on the decl. arc, and
determine a true meridian
with the solar ^{point} at the cor₁ to

Subdivision of T 13 N. R 11 E. cont.
chains

secs. 23, 24, 25 and 26.

Thence I run

North, bet secs. 23 and 24
on the Sectional side meridian,
along east bank of cañon,
very rough.

40.00 a sandstone in place for
 $\frac{1}{4}$ sec. cor. 6 x 6 ft 4 ft. above
ground. marked $\frac{1}{4}S\ 23$ on
W face, 24 on E. face. from
which

a Pine 10 ins. diam. bears
 $N 61 \frac{3}{4}^{\circ} E.$ 62 eks. dist. marked
 $\frac{1}{4}S\ 24$ B.T.

a Pine 7 ins. diam. bears
 $S 83^{\circ} W.$ 58 eks. dist. marked
 $\frac{1}{4}S\ 23$ B.T.

Thence continue along east
bank of cañon.

Subdivision of T13N. R11E. con't.

chains

40.75 Gulch 10 lks. wide, course Westerly;
^{ascend}

58.00 Top of ascent, bears E and W

67.00 Descend

70.50 Draw 20 lks. wide, course W; ascend

72.00 Top of ascent

80.00 Set a sand stone 18x8x6 ins.

12 ins. in the ground for cor.
of secs. 13, 14, 23 and 24.marked with 3 notches on S
and 1 notch on E edges.

from which.

An Oak 6 ins. diam. bears

N 63 $\frac{1}{2}$ ° E. 28 lks. dist. marked

T13N R11E. S 13. B.T.

An Oak 6 ins. diam. bears S 10 $\frac{1}{2}$ ° E.

56 lks. dist. marked. T13N. R11E

S 24. B.T.

an oak 20 ins. diam. bears S 22° W

58 lks. dist. marked T13N. R11E.

S. 23. B.T.

Subdivision of T 13 N. R 11 E. con'
chains

a Pine 36 ins. diam. bears
 $N 84\frac{1}{2}^{\circ} W.$ 86 lks. dist. marked
 T 13 N. R 11 E. S 14 B T.

Land rolling and broken
 Soil, gravelly & stony. 2nd & 4th rate
 Timber, Pine, and some oak.
 Heavily timbered land 80. chs.

- | | |
|--------|--|
| | East. bet ^{Sheets} 13 and 24 |
| | over rolling land |
| 4. 50 | Descend |
| 9. 70 | Gulch rocks wide, course Westerly
ascend. |
| 12. 50 | Top of ascent |
| 14. 60 | Trail bears N and S |
| 23. 50 | Descend |
| 25. 70 | Draw rocks wide, course Northerly.
ascend |
| 28. 50 | Top of ascent bears N and S. |
| 31. 00 | Trail bears N and S |

Sub-division of T 13 N. R 11 E. con'

chains

40.00 Set a Limestone 18x8x6 ins.
12 ins. in the ground for
 $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}S\ 13$ on
N face, 24 on S face, from which
a Pine 20 ins. diam. bears
 $N 11\frac{1}{2}^{\circ} W.$ 14 eks. dist. marked
 $\frac{1}{4}S\ 13$ B.T.

A Pine 28 ins. diam. bears
 $S\ 22^{\circ} E$ 76 eks dist marked
 $\frac{1}{2}S\ 24$ B.T.

44.50 Descend

52.00 Canon 30 eks. wide, course N.
ascend

60.00 Top of ascent, bears N and S.

69.47 Intersect east boundary
of Rp. 1.50 chs. $N 2^{\circ} 33' W$ of
cor to secs. 18 and 19.

Set a Pine post 3 ft long
4 ins. sq. 18 ins. in the ground
for closing cor to secs 13

Subdivision of T13N. R11E. con.
 chains

and 24. marked CC. on
 w face. with 3 grooves on
 N and S faces. from which
 a Pine 12 ins. diam. bears
 $N 62\frac{1}{2}^{\circ} W.$ 50 lks. dist. marked

T13N. R11E. S. 13 BT.

A Pine 20 ins. diam. bears
 $S 77^{\circ} W.$ 158 lks. dist. marked

T13N. R11E. S 24 BT.

Land rolling

Dail. gravelly, 2nd & 3rd rate

Timber, Pine

Heavily timbered land 69.47 chs.

North, bet secs. 13 and 14
 sectional Guide meridian.
 over rolling land

Descending

3. 50 Draw 30 lks. wide, course Westly;
 ascend

Subdivision of T 13 N. R 11 E. con.
chains

- 7.50 Top of ascent, bears S and W.
- 18.40 Gulch rocks wide course, W
- 40.00 Set a Limestone 18x8x8 ins.
12 ins in the ground for
 $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ See¹⁴
on W. face 13 on E. face
from which
a Pine 10 ins. diam. bears
 $N 38\frac{1}{2}^{\circ} E.$ 22 lks. dist. marked
 $\frac{1}{4} S. 13. 13 T.$
- An oak 12 ins. diam. bears
 $N 35\frac{1}{2}^{\circ} W.$ 36 lks. dist. marked
 $\frac{1}{4} S. 14. 8 T.$
a pine
- 50.80 ~~Draw~~ 40 ins. diam. on line
marked with 2 notches on N & S.
- 55.00 Descend
- 56.80 Draw, course W; ascend
- 59.50 Top of ascent
- 74.00 Descend

Subdivision of T13N R11E. con.
chains

77.20 Draw, course N.

80.00 Set a Limestone 18x8x7 ins.
12 ins. in the ground for cor
of secs. 11, 12, 13 and 14 marked
with 4 notches on the S and
1 notch on E edges, from which
a Pine 26 ins. diam. bears
 $N73\frac{1}{4}^{\circ}$ E. 18 eks. dist. marked
T13N. R11E. S 12, B.T.

a Pine 20 ins. diam. bears
 $S30^{\circ}$ E. 50 eks. dist. marked
T13N. R11E. S 13, B.T.

a Pine 18 ins. diam. bears
 $S35\frac{1}{2}^{\circ}$ W. 90 eks. dist. marked
T13N. R11E. S 14, B.T.

a Pine 30 ins. diam. bears
 $N9\frac{3}{4}^{\circ}$ W. 87 eks. dist. marked
T13N. R11E. S 11, B.T.

Land rolling

Subdivision of T13N. R18E. con
chains

Dil. gravelly, 2nd & 3rd rate
Timber Pine, some oak
Heavily timbered land. 80. chs.

East bet secs. 12 and 13
on a true line
over rolling land

36.50 Descend

40.00 Set a Limestone 18 x 12 x 6 ins.
12 ins. in the ground for $\frac{1}{4}$ sec
cor. marked $\frac{1}{4}$ S. 12 on N
face, 13 on S face, from which
a Pine 12 ins. diam. bears
 $S 1\frac{3}{4}^{\circ} E.$ 28 lks. dist. marked
 $\frac{1}{4}$ S. 13. B.T.

a Pine 20 ins. diam. bears
 $N 81\frac{3}{4}^{\circ} W.$ 64 lks. dist. marked
 $\frac{1}{4}$ S. 12. B.T.

+1.00 Draw course northerly

Subdivision of T13N. R11E. con't.

chains

41.68 Trail

42.50 Leave draw; ascend

48.00 Top of ascent, bears N and S

65.81 Intersect East Boundary of
Tp. 1,44 chs. N 2°33' W. of cor
to secs. 7 and 18.

Put a Limestone 18x14x6 ins.
12 ins. in the ground for
closing cor to secs 12 and 13
marked CC. on W. face
with 4 grooves on S and 2
grooves on N faces, from which
a Pine 12 ins. diam. bears
 $S88^{\circ}W.$ 88 lks. dist. marked
T13N. R11E. S 13. BT.

A Pine 12 ins. diam. bears
 $N78^{\circ}W.$ 88 lks. dist. marked

T13N. R11E. S 12 BT.

Land rolling

Sub-division of T 13 N. R 11 E. Con.
chains

Soil gravelly, 2nd & 3rd rate.
Timber, Pine and some oak
Heavily timbered land 65.81 chs.

Aug. 18, 1900.

Aug. 20, 1900. at 7.55 am. l.m.t.
I set off $34^{\circ}31'$ on the sat. arc;
 $12^{\circ}29'$ N on the decl. arc and
determine a true meridian
with the solar at the cor.
to secs. 11, 12, 13 and 14.

Thence I run

North, bet. secs. 11 and 12.

Sectional guide meridian
over rolling land.

- 3.50 Enter draw, course N Easterly
- 7.50 Leave draw and ascend
- 14.00 a Pine 24 ins. diam. on line
marked with 2 notches on N and S.

Subdivision of T13N. R11E. Con'
 chains

- 14.50 Top of ascent, bears N E and SW
- 24.50 Descend
- 29.75 Draw, course N Westerly
- 31.00 along East side of draw
- 35.50 Enter draw, course N Easterly
- 40.00 Set a Limestone 18 x 12 x 6 ins.
 12 ins. in the ground for $\frac{1}{4}$ sec
 cor. marked $\frac{1}{4}S.11$ on W. face,
 12 on E. face. from which
 a Pine 24 ins. diam. bears
 $S7\frac{1}{4}^{\circ}E.$ 20 lks. dist. marked
 $\frac{1}{4}S.12, B.T.$
- a Pine 24 ins. diam. bears
 $S43\frac{1}{2}^{\circ}W.$ 88 lks. dist. marked
 $\frac{1}{4}S.11, B.T.$
- 44.80 Leave draw, course N Easterly
- 53.00 Top of ascent, bears N E and SW
- 80.00 a Limestone in place, 24 x 10 ins.
 5 ins. above ground. for cor

Sub-division of T13N. R11E. Con.
chains

of secs. 1, 2, 11 and 12, marked
with a \times at the exact cor. point,
with 5 notches on S. and 1 notch
on E edges, from which
a Pine 12 ins. diam. bears
 $N 52\frac{3}{4}^{\circ}$ E, 111 eks. dist. marked

T13N. R11E. S. 1. B.T.

A Pine 24 ins. diam. bears
 $S 16\frac{1}{2}^{\circ}$ E, 62 eks. dist. marked

T13N. R11E. S 12. B.T.

A Pine 24 ins. diam. bears
 $S 61^{\circ}$ W, 80 eks. dist. marked

T13N. R11E. S 14. B.T.

A Pine 30 ins. diam. bears
 $N 79^{\circ}$ W, 25 eks. dist. marked

T13N. R11E. S 2. B.T.

Land rolling

Dail, gravelly, 2nd & 3rd rate

Timber, Pine

Heavily timbered land 80. chs.

Sub-division of T 13 N. R 11 E. con' chains

East, on a true line betw. sec. 1 & 12
over rolling land

- | | |
|-------|--|
| 5.40 | descend |
| 9.80 | Enter draw, course N.E. |
| 10.65 | Trail course N.E. |
| 11.50 | Leave draw |
| 14.00 | Enter draw, course N.W. |
| 14.50 | Trail course N.W. |
| 15.50 | Leave draw and ascend |
| 23.00 | Top of ascent, bears N.W. and S.E. |
| 37.00 | Trail bears Northw. and S. |
| 37.30 | descend |
| 40.00 | a Limestone in place
18 x 18 ins. 6 ins above ground
for $\frac{1}{4}$ sec. cor. marked
with a x at the exact corner
point, and $\frac{1}{4}$ s.l. on N face
12 on S face, from which
a pine 30 ins. diam. bears |

Subdivision of T 13 N R 11 E. con
chains

N 12° E. 15 eks. dist. marked

1/4 S. 1. B.T.

A Pine 30 ins. diam. bears

S 34° W. 64 eks. dist. marked

1/4 S 1/2. B.T.

42.00 along S. side of draw.

52.20 Gulch 10 eks. wide, course Northerly.

60.35 Cañon 50 eks. wide, course

W W Westerly; ascend

63.50 Intersect the East Boundary
of Zp. 1.⁵⁷ chs N 2° 33' W of cor.
to secs. 6 and 7.

Set a Limestone 20 x 10 x 3 ins.
15 ins. in the ground for closing
cor. to secs. 1 and 12. marked
CC. on W face, with 5 grooves
on S and 1 groove on N faces
from which
A Pine 7 ins. diam. bears

Subdivision of T13N. R11E. Con't.
chains

N $63\frac{3}{4}^{\circ}$ W. 48 ecls. dist. marked

T13N. R11E. S. 1. 13T.

a Pine 10 ins. diam. bears

S 78° W. 35 ecls. dist. marked

T13N. R11E. S. 12. 13T.

Land rolling

Dirt gravelly, 2nd & 3rd rate

Timber, Pine and some oak.

Heavily timbered Land 63.50 chs.

North. bet. secs. 1 and 2.

Sectional guide meridian.

over rolling land

12.95 a Pine 3 ft. diam. on line

marked with 2 notches on N. S.

40.00 Set a Lime stone 18x12x4 ins.

12 ins. in the ground for

1/4 sec. cor. marked 1/4 S. 2.

on W. face, 1 on E. face

Subdivision of T13N. R11E. con't
chains

from which,

a Pine 12 ins. diam. bears
 $N 53^{\circ} E.$ 19 eks. dist. marked
 $\frac{1}{4} S. 1. 13.T.$

a Pine 30 ins. diam. bears
 $S 35\frac{1}{2}^{\circ} E.$ 32 eks. dist. marked
 $\frac{1}{4} S. 1. 13.T.$

55.00 Sheep Corral E of line

56.00 Descend

61.95 Cañon 20 eks, wide, course $N 85^{\circ} W$

68.90 Intersect N. Bdy. of 2d. 21.03 chs.
E of cor. 65 secs. 35 and 36.

Set a Limestone 20x10x6 ins.
15 ins. in the ground for closing
cor. 65 secs. 1 and 2. marked
C.C. on S. with 1 groove on E
and 5 grooves on W. faces
from which

a Pine 20 ins. diam. bears

Subdivision of T 13 N. R 11 E. Con' chains.

S 22° E. 61 eks. dist. marked

T 13 N. R 11 E. S. I. B.T.

A Pine 7 ins. diam. bears

S $45\frac{1}{2}$ ° W. 31 eks. dist. marked

T 13 N. R 11 E. ~~S. I.~~ B.T.

Land rolling

Soil gravelly & stony 3rd & 4th rate

Timber Pine, some oak

Heavily timbered land 68.90 chs.

Aug. 20. 1900

Aug 21. 1900. at 8.15 am. l.m.t.

I set off $34^{\circ}28'$ on the Lat. arc;

$12^{\circ}09'$ N on the decl. arc. and

determine a true meridian

with the solar at the corr to

secs 34 and 35 on the S. fdy of

The Zp.

Thence I run

N $0^{\circ}01'$ W. bet. secs. 34 and 35

Subdivision of T 13 N. R 11 E. Cont'd
chains

- 15.00 Descend
- 17.50 Draw course N Westerly; ascend
- 20.50 Top of ascent
- 28.00 ascend along E side of draw
- 40.00 Set a Sand Stone 18x10x6 ins.
12 ins. in the ground for $\frac{1}{4}$ sec
cor. marked $\frac{1}{4}S.34$ on W face
 35 on E face. from which
a Pine 10 ins. diam. bears $N65^{\circ}E$
21 lks. dist. marked $\frac{1}{4}S.35$. BT.
- a Pine 10 ins. diam. bears $N45\frac{1}{4}^{\circ}W$
76 lks. dist. marked $\frac{1}{4}S.34$. BT.
- 50.50 Top of ascent bears N Easterly
and S Westerly
- 56.00 Descend
- 64.00 Draw course N E
- 64.50 Trail. bears N E and S W?
- 68.50 along W side of draw
- 80.00 Set a Quartzite stone 18x14x6 ins.

Subdivision of T 13 N. R 11 E. Con.
chains

12 ins. in the ground for cor of
secs. 26, 27, 34 and 35, marked
with 1 notch on S. and 2 notches
on E. edges. from which
A Pine 10 ins. diam. bears N $55\frac{1}{2}^{\circ}$ E
40 lks. dist. marked T 13 N. R 11 E. S 26
B.T.

A Pine 10 ins. diam. bears S 34° E
28 lks. dist. marked T 13 N. R 11 E
S. 35 B.T.

A Pine 10 ins. diam. bears S $57\frac{1}{2}^{\circ}$ W
11 lks. dist. marked T 13 N. R 11 E
S 34. B.T

A Pine 10 ins. diam. bears N $47\frac{1}{4}^{\circ}$ W
5 lks dist. marked T 13 N. R 11 E.
S 27. B.T.

Land rolling

Dail gravelly. 2nd & 3rd rate
Timber Pine

Heavily timbered land so. chs

Subdivision of T 13 N. R 11 E. Cont.
chains

East on a random line bet. secs. 26 & 35

- 40.00 Det temp. $\frac{1}{4}$ sec cor.
- 80.10 intersect N and S line + take $\frac{1}{2}$
of cor. to secs. 25, 26, 35 and 36
Thence draw
- S $89^{\circ}58'W$ on a true line
bet. secs. 26 and 35
- 7.50 Descend
- 10.40 Draw course northerly; ascend
- 15.00 Top of ascent, bears N and S.
- 30.00 descend
- 40.00 The point for $\frac{1}{4}$ cor. falls on
steep canon bank.
- 41.00 Canon 20 eks. wide, course northerly;
ascend
- 45.00 A sandstone in place, 3 ft x 2 ft.
10 ins. above ground marked with
a cross at the exact cor. point
for witness corner. To $\frac{1}{4}$ sec cor.

Subdivision of T13 N. R11 E. Con.
chains

marked W.C. 1/4 S 26. on N face.
35 on S face. from which
a Pine 12 ins. diam. bears N 40° E
38 lks. dist. marked W.C. 1/4 S 26, BT.
a Pine 18 ins. diam. bears. S 8½° E.
16 lks. dist. marked W.C. 1/4 S. 35, BT.

57.50 Top of ascent

65.00 Descend

76.00 Enter draw, course N,

76.10 Trail bears N and S.

77.25 Leave draw.

80.10 The cor to secs. 26, 27, 34 and 35

Land rolling and broken

Soil gravelly and stony 3rd & 4th rate

Timber Pine and some oak.

Heavily timbered land 80.10 chs.

N. 0° 1' W. bet. secs. 26 and 27
over rolling land

Sub-division of T 13 N, R 11 E Cor
chains

35.10

- 40.00 Set a Sand stone 18x8x6 ins. 12 ins.
in the ground for $\frac{1}{4}$ sec. cor.
marked $\frac{1}{4} S. 27$ on W. face
26 on E. face, from which
a Pine 30 ins. diam. bears
 $S 42\frac{3}{4}^{\circ} E.$ 19 ecls. dist. marked
 $\frac{1}{4} S. 2\frac{7}{8}^{\circ} 37$
A Pine 30 ins. diam. bears
 $S 39^{\circ} W.$ 25 ecls. dist. marked
 $\frac{1}{4} S. 27. 13. T.$

53.00 Descend

- 58.30 Draw 50 ecls. wide, course N. Westerly
60.00 along E side of draw

63.25 Descend

- 65.25 Gulch 10 ecls. wide, course Westerly
69.00 Log fence bears E and W.
69.50 Top.
80.00 Set a Quartzite stone 18 x 12 x 6 ins.

Subdivision of T 13 N. R 11 E. On chains

12 ms. in the ground for cor. of
secs. 22, 23, 26 and 27, marked with
2 notches on S and E edges, from which
a Pine 20 ms. diam. bears $N 66\frac{3}{4}^{\circ} E$
55 lks. dist. marked T 13 N. R 11 E. S. 23 B.T.
A Pine 7 ms. diam. bears $S 49\frac{3}{4}^{\circ} E$
69 $\frac{1}{2}$ lks. dist. marked T 13 N. R 11 E. S 26 B.T.
A Pine 18 ms. diam. bears $S 45\frac{1}{2}^{\circ} W$
11 lks. dist. marked T 13 N. R 11 E. S 27 B.T.
A Pine 18 ms. diam. bears $N 32\frac{1}{4}^{\circ} W$
144 lks. dist. marked T 13 N. R 11 E. S 22 B.T.
Land rolling and even
Soil gravelly, 2nd rate
Timber Pine.
Heavily timbered land 80 ac.

Aug. 21, 1900.

Aug 22, 1900. at 7.30 am. L.M.T.
I set off $34^{\circ} 29'$ on the lat. arc;
 $11^{\circ} 50'$ on the decl. arc, and

Subdivision of T13N. R11E. Col.
chains

determine a true meridian at
the cor to secs 22, 23, 26 and 27
Thence I run N $89^{\circ}58' E$
on a random line bet secs.
23 and 26

- 40.00 Set traps. 4 sec. cor.
80.06 Intercept N and S line 4 lbs. N
of cor point to secs. 23, 24, 25
and 26.
Thence I run
West, on a true bet. secs. 23 and 26
over rolling land
\$ Descend steep canon bank
3.85 Bottom of canon rocks wide
course N $16^{\circ} W$; ascend
20.00 Top of ascent
28.40 Trail bears N and S
33.50 Gulch rocks wide, course NEasterly.
ascend

Sub-division of T 13 N. R 11 E Con.
chains

35.80 Trail bears N.

40.03 Set a Sandstone 20x14x8 ins.

15 ins. in the ground for $\frac{1}{4}$
sec. cor. marked $\frac{1}{4}5.23$ on
N face. 26 on S. face, from which
a Pine 6 ins. diam. bears
 $N 40^\circ W.$ 42 eks. dist. marked
 $\frac{1}{4}5.23$. B.T.

a Pine 30 ins. diam. bears
 $S 26^\circ W.$ 30 eks. dist. marked

$\frac{1}{4}5.26$. B.T.

42.50 Top of ascent bears NE and SW.

44.00 Log cabin, of W^c Clintocks, 5 chs.
South.

49.50 Descend

50.50 Draw 30 eks. S.; Sheep corral
6. chs. S.; ascend

54.50 Top of ascent bears N & S.

64.00 Descend

Subdivision of T 13 N R 1 E. con'

chains

- 68.50 Draw 50 chs. N; ascend
 71.25 Top of ascent
 73.40 Trail, bears N.Westerly and S.Easterly
 80.06 The cor. of secs. 22, 23, 26 and 27.
 Land rolling
 Soil, gravelly. 2nd + 3rd rate
 Timber, Pine
 Heavily timbered land. 80,06 chs.

N 0° 0' W. bet. secs. 22 and 23
 over rolling and broken land.

- 6.00 Trail, bears S.Easterly and N.Westerly
 30.00 descend

Set a Quartzite stone 18x10x6 ins.
 12 ins. in the ground for witness
 corner to $\frac{1}{4}$ sec cor. marked
 W.C. $\frac{1}{4}$ S 22 m N. face. 23 m E. face
 from which
 a Pine 30 ins. diam. bears S 61 $\frac{1}{4}$ E

Sub-division of T 13 N. R 11 E. Cou.
chains

45.eks. dist. marked W.C. $\frac{1}{4}$ s 23 BT.

A Pine 12 ins. diam. bears $549\frac{1}{2}^{\circ}$ W

42 eks. dist. marked W.C. $\frac{1}{4}$ s 22 BT.

40.00 Paint for $\frac{1}{4}$ sec. cor. falls in
McClintacks cañon, 50 eks. wide
course N Easterly; ascend

57.50 Top of ascent, bears NE and SW.

62.00 Draw, course S. Easterly

67.00 Top bears NW and SE

69.50 Descend

73.85 Draw, course S. Easterly; ascend

75.50 Top of ascent, bears NW and SE.

80.00 Set a limestone 18x14x10 ins.
12 ins. in the ground for cor
of secs. 14, 15, 22 and 23, marked
with 3 notches on S. and 2 notches
on E edges, from which
A Pine 8 ins. diam. bears
 148° E. 89 eks. dist. marked

Subdivision of T 13 N. R 11 E. Con'
claims

T 13 N. R 11 E. S 14 13 T.

a Pine 15 ins. diam. bears
 $S 85\frac{1}{2}^{\circ} E$ 178 eks. dist. marked

T 13 N. R 11 E. S. 23. BT.

a Pine 20 ins. diam. bears
 $S 1\frac{1}{4}^{\circ} W$. 162 eks dist. marked

T 13 N. R 11 E. S 22. 13 T.

a Pine 18 ins. diam. bears $N 54\frac{1}{2}^{\circ} W$
 67 eks. dist. marked T 13 N. R 11 E
 S. 15 BT.

Land rolling and broken
 Soil, gravelly stony 2nd & 4th rate
 Timber, Pine.

Heavily timbered land 80. chs.

From a point N. 10. chs from
 the cor. to sec. ~~14, 15, 23 & 23~~
~~14, 15, 23 and 24~~
 Draw East on ^{offset} random
 line.

Subdivision of T13N. R11E. Col.
chains

- over rolling and broken land
set temp point.
- 40.00 intersect N & S line 10. chs N
of cor. to secs. 13, 14, 23 and 24.
Thence S run West
- 46.50 on offset line
Thence S 10 chs back to true line
at foot of canon bank
A sandstone in place 15 x 10 ft.
3 ft. above ground for witness cor.
 $5\frac{1}{4}$ sec. cor. marked with a
cross at the exact cor. pt.
marked WC $\frac{1}{4}$ S 1/4 on N. 23 on S.
from which
an oak 8 ins. diam. bears
 $N 80^\circ W$ 135 chs. dist. marked
WC $\frac{1}{4}$ S 1/4 B.T.
an oak 10 ins. diam. bears
 $S 22^\circ E$ 18 chs. dist. marked
WC $\frac{1}{4}$ S 23, B.T.

Subdivision of T13N R11E, Con'.
chains

- 47.00 creek 20 fms. wide, course NNEasterly
 47.20 ascend W. bank of cañon
 50.00 Top of bank; descend
 52.00 Gulch 10 fms. wide, coarse S. Easterly;
 ascend
 58.00 Draw, course S. Easterly
 60.00 Top of ascent, bears NW and SE
 62.00 descend
 64.00 Gulch 10 fms. wide, course S.
 65.15 Gulch 10 fms. wide, course S.; ascend
 68.50 Top of ascent, bears N and S. descend
 76.35 Gulch 10 fms. wide, course S.
 80.00 The cor to secs. 14, 15, 22 and 23
 Land rolling and broken
 Soil, gravelly rocky, 2nd, 3rd & 4th rate
 Timber, Pine.
 Undergrowth, dense weeds in
 cañon
 Heavily timbered land 80. chs.

aug 22, 1900.

Subdivision of T 13 N. R 11 E. Con.
charts

No° 01' W. bet. secs. 14 and 15
 Aug. 23. 1900, at 7.54 A.M. LMT.
 I set off $34^{\circ} 30'$ on the lat. arc.
 $11^{\circ} 28' N$ on decl. arc. and determine
 a true meridian with the solar
 at the cor to secs. 14, 15, 22 and 23
 Thence I run

No° 01' W. bet. secs 14 and 15
 over rolling land

32.50 Descend along E side of canon
 40.00 Set a Lime stone 18x12x6 ins.
 12 ins in the ground for $\frac{1}{4}$ sec. cor.
 marked $\frac{1}{4} S 15$ on W. face, 14 on
 E face, from which

an oak 7 ins. diam. bears

$N 26^{\circ} E.$ 27 eks. dist. marked

$\frac{1}{4} S 14$ B.T.

a Pine 20 ins. diam. bears

$N 86^{\circ} 2' W.$ 17 eks. dist. marked

Sub-division of T13N.R11E. con-
chains

1/4 S. 15. B.T.

42.50 Bottom 20 ecls. wide, course N.E.;
ascend

51.00 Thence along W side of canon.

66.00 Top of ascent. bears N.E.; ascend

78.50 Canon 10 ecls. wide, course N.N.Easterly;
ascend.

80.00 Get a sandstone 18x8x6 ins.

12 ins. in the ground for cor.
of secs. 10, 11, 14 and 15 marked
with 4 notches on S. and 2 notches
on E edges. from which
a pine 14 ins. diam. bears
N 8° E. 20 ecls. dist. marked

T13N. R11E. S. 11 B.T.

An oak 6 ins. diam. bears S 22 1/2° E
45 ecls. dist. marked

T13N. R11E. S. 14 B.T.

An oak 10 ins. diam. bears

Subdivision of T 13 N. R 11 E. Cont.
 chains

S 30° 2' W. 43 lks. dist. marked

T 13 N. R 11 E. S 15. B.T.

An oak 5 ins. diam. bears

N 25° 4' W. 59 lks. dist. marked

T 13 N. R 11 E. S. 10. B.T.

Land rolling

Soil gravelly 2nd & 3rd rate

Timber, Pine

Heavily timbered land 80. chs.

East on a random line

bet. secs. 11 and 14

40.00 set temp. $\frac{1}{4}$ sec. cor.

80.12 Intersect N & S line at cor. to
secs. 11, 12, 13 and 14.

Thence down

West on a true line bet secs 11 & 14

over rolling and broken land;
descend.

1.90 Draw 30 lks. wide, coarse northwly
ascend.

Subdivision of T13 N. R11 E. Cou
chans

- 7.00 Top of ascent, bears N and S.
- 36.00 Descend towards ^{McClintock} canon.
- 40.06 Set a Limestone 18x8x8 ins., 12 ins.
in the ground for $\frac{1}{4}$ sec. cor.
marked $\frac{1}{4}$ sec 11 on N face
14 on S face, from which
An oak 8 ins. diam. bears
 $N 20\frac{1}{2}^{\circ} W$, 65 lbs. dist. marked
 $\frac{1}{4}$ sec 11 B.T.
- A Pine 20 ins. diam. bears
 $S 39\frac{1}{4}^{\circ} E$, 69 lbs. dist. marked
 $\frac{1}{4}$ sec 14 B.T.
- 42.00 Descend, steeper
- 53.50 Bottom of McClintock canon. 20 lbs. wide
course N; ascend steep bank
- 65.80 Top of ascent, bears N and S
- 75.00 Descend
- 79.50 Canon 20 lbs. wide, course NN Eastly
- 80.12 The cor. to secs. 10, 11, 14 and 15

Sub-division of T13N. R11E. con.
chains

Land rolling and broken

Dirt, gravelly rocky, 2nd & 4th rate

Timber, Pine.

Heavily Timbered Land 80, 12 chs.

Between 10 and 11
 owing to the rough steep
 canon banks on this line
 I offset 8 chs W. Thence I run
 N 0° 01' W. along steep bank
 of canon. at

40.00 8.00 chs. W. of corner point, set a
 Limestone 18 x 8 x 6 ins. 12 ins in
 the ground for witness corner
 to $\frac{1}{4}$ sec. cor. marked WC,
 $\frac{1}{4}$ S. 10. on W. face. 11 on E. face
 from which

A Pine 20 ins. diam. bears N 3 $\frac{1}{4}$ ° E
 53 chs. dist. marked WC. $\frac{1}{4}$ S 10 + 11. B.T.

A Pine 20 ins. diam. bears S 3 $\frac{1}{4}$ ° W

Subdivision of T13N. R11E. con't.
chains

50 lks. dist. marked N.C. $\frac{1}{4}$ S 104 11 B.T.

80,000 I offset back E. 8. chs. to true line
Set a Lime-stone $18 \times 12 \times 10$ ins.

12 ins. in the ground for cor of
secs. 2, 3, 10 and 11 marked
with 5 notches on S. and 2 notches
on E edges, from which
a Pine 30 ins. diam. bears
 $N 26^{\circ} E.$ 24 lks. dist. marked

T13N. R11E. S. 2 B.T.

A Pine 12 ins. diam. bears $S 61^{\circ} E$
57 lks. dist. marked T13N. R11E
S. 11, 13 T.

A Pine 26 ins. diam. bears
 $S 16^{\circ} W.$ 45 lks. dist. marked
T13N. R11E. S. 10, 13 T.

A Pine 18 ins. diam. bears
 $N 68^{\circ} W.$ 92 lks. dist. marked
T13N. R11E. S. 3, 13 T.

Sub-division of T 13 N. R 11 E. Col.
chains

Land broken,

Sail, stony & gravelly, 3rd rate worthless

Timber, Pine and some oak.

Heavily timbered land, mountainous, 80. chs.

East, on a random line

bet. secs. 2 and 11

40.00 Set temp $\frac{1}{4}$ sec. cor.

80.16 Intersect N and S line 5 chs. S
of cor to secs. 1, 2, 11 and 12

Thence S run

$589^{\circ} 58' W.$ on a true line

bet. secs. 2 and 11

over rolling land

13.60 a Pine 40 ins. diam. on line
marked with 2 notches on E and W

16.25 "Descent

23.50 Draw 100 chks wide, course Northly;
ascend

Sub-division of T13N. R11E. cont.
chains

37.00 Top of ascent bears N and S.

40.08 At a Sandstone 18x14x6 ins. 12 ins.
 in the ground for $\frac{1}{4}$ sec. cor.
 marked $\frac{1}{4} S 2$ on N face. 11 on
 S. face, from which
 a Pine 12 ins. diam. bears
 $S 34\frac{1}{4}^{\circ} E.$ 30 eks. dist. marked
 $\frac{1}{4} S 11. B.T.$

a Pine 18 ins. diam. bears
 $N 75\frac{1}{4}^{\circ} E.$ 17 eks. dist. marked
 $\frac{1}{4} S. I. B.T.$

68.00 Descend towards Mc Clintocks canon

72.00 Descend steep over large boulders

80.16 The cor to secs. 2, 3, 10 and 11.

Land rolling

Dale, gravelly and stony. 2nd & 4th rate.

Timber, Pine, some oak

Heavily timbered land 80¹⁶ eks.

Aug. 23. 1900

Subdivision of T13N. R11E. Con't.
chains

Aug. 24, 1900. at 9.30 am. L.M.T.
Set off $34^{\circ}32'$ on lat. arc;
 $11^{\circ}07' N$ on decl. arc, and determine
a true meridian with the solar
at the cor. to secs. 2, 3, 10 and 11.
owing to rough cañons I
offset E. 20. chs.

Hence I run

~~N. $\pm 0.14^{\circ}$~~ on offset line
bet secs 2 and 3.

40.00 at 40. chs. I offset $\frac{W}{E}$ 20. chs back
to true line.

A sandstone bluff 18×4 ft. 3 ft
above ground for $\frac{1}{4}$ sec. cor. I
mark with a cross at the
exact cor. point. marked

$\frac{1}{4}$ S. 3. on W. 2 on E. from which
an oak 5 ins. diam. bears
 $N48^{\circ}W.$ 25-lbs. dist. marked

Sub-division of T 13 N. R 11 E. cou'
chains

1/4 S. 3. B.T.

An oak 5 ins. diam. bears
 $S 55\frac{1}{2}^{\circ} E$, 25 chs. dist. marked

1/4 S. 2. B.T.

45.00 Top of ridge bears E and W;
descend

45.12 A Pine 18 ins. diam. on line, marked
with 2 notches on N and S

50.00 Mc Clintock Canon 50 chs. wide
course westerly; at this point it
offset N. 10 chs.

Thence $N 0^{\circ} 01' W$

65.00 Thence 1 offset E. 10 chs. to true line

69.12 Intersect N. Bdy. 21.60 chs. E of
cor 6 secs. 34 and 30.

Set a Sandstone 18 x 8 x 8 ins. 12 ins.
in the ground for closing corner
6 secs. 2 and 3. marked CC.
on S face, with 2 grooves on E

Subdivision of T13N. R11E. con.
chains

and 4 grooves on W. faces.
from which.

A Pine 16 ins. diam. bears
 $561\frac{3}{4}^{\circ}$ E. 37 lbs. dist. marked

T13N. R11E. S. 2. B.T.

A Pine 18 ins. diam. bears 547° W
43 lbs. dist. marked. T13N. R11E
S. 3 B.T.

Land broken

Soil worthless

Timber. Pine

Heavily timbered land. 69, 12 chs.

Aug 25, 1900 at 7:56 am. l.m.t.
I set off $34^{\circ}28'$ on the seat. arc;
 $10^{\circ}47'W$ on the decl. arc. and
determine a true meridian
with the solar. at the corr. to
secs. 33 and 34.

Subdivision of T18N R11E, con.
chains

Thence I run.

N. $0^{\circ}01'W.$ bet. secs. 33 and 34
Over rolling and broken land
ascend along E side of cañon.

- 9.95 Trail, bears NW and SE
- 23.15 Trail, bears SW and NE
- 40.00 Set a Sandstone $18 \times 6 \times 6$ ins.
12 ins. in the ground for $\frac{1}{4}$ sec. cor.
marked $\frac{1}{4}S. 33$ on W. face
 34 on E face, from which,
a Pine 14 ins. diam. bears
 $N 15^{\circ}E$. 74 lks. dist. marked
 ~~$\frac{1}{4}S. 34$~~ B.T.
a Pine 24 ins. diam. bears
 $N 89^{\circ}W.$ 87 lks. dist. marked
 ~~$\frac{1}{4}S. 33$~~ B.T.
- 44.00 Top of ascent, bears N WNWly
and S ESEly
- 48.50 Descend

Subdivision of T13N. R11E. Con.
chains

- 55.34 Trail, bears E and W.
- 67.75 Canon, flowing water, 20 eks. wide
course, easterly; ascend
- 79.50 Top of ascent, bears N Easterly
and S. Westerly.
- 80.00 Set a Sandstone 18x10x 6 ins.
12 ins. in the ground for cor.
of secs. 27, 28, 33 and 34.
marked with 1 notch on S
and 3 notches on E edges
from which,
an oak 8 ins. diam. bears
 $N 38\frac{1}{4}^{\circ} E$, 78 eks. dist. marked
T13N. R11E. S. 27. B.T.

A Pine 16 ins. diam. bears
 $S 36^{\circ} E$, 55 eks. dist. marked

T13N. R11E. S. 34. B.T.

A Pine 18 ins. diam. bears
 $S 84^{\circ} W$, 120 eks. dist. marked

Subdivision of T 13 N, R 11 E. Con't.
 chains

T 13 N, R 11 E, S 33, B.T.

a Pine 30 ins. diam. bears N 47 $\frac{1}{2}$ ° W
 84 lks. dist. marked T 13 N.
 R 11 E, S. 28, 13 T.

Land rolling and broken
 Soil, gravelly and stony, 2nd & 3rd rate.
 Timber, Pine and some oak.
 Heavily timbered land, 80. chs.

East on a random line
 bet. secs. 27 and 34
 over rolling land

40.00 Det temp., $\frac{1}{4}$ sec. cor.

80.09 Intersect N and S line 5 lks. S
 of cor. to secs. 26, 27, 34 and 35
 Thence S run

N 89° 58' W. on a true line
 bet. secs. 27 and 34.

37.50 Descend abruptly

Subdivision of T13N. R11E. Cou.
chains

- 39.50 Bottom of cañon 20eks. wide,
course N. ascend steep bank
- 40.0 4 $\frac{1}{2}$ The point for $\frac{1}{4}$ sec. cor. falls on
steep rocky point.
- 41.00 A sandstone in place 40 x 18 ft.
6 ins. above ground & mark with
a cross at the exact cor point
for witness corner to $\frac{1}{4}$ sec. cor.
marked $\frac{1}{4}S\ 27$, on N. 34 on S.
from which
an oak 6 ins. diam. bears
 $N 69^{\circ} E$ 32 eks. dist. marked
 $\frac{1}{4}S. 27. B.T.$
- a Pine 12 ins. diam. bears $S 25\frac{1}{2}^{\circ} E$
54 eks. dist. marked $\frac{1}{4}S 34. B.T.$
- 54.00 Top of ascent, bears N and S.
- 55.90 Trail, bears N and S
- 58.00 Descend
- 70.50 Bottom of cañon, 40eks. wide
course NEasterly; ascend

Subdivision of T 13 N. R 11 E. Cou.

chains

- 79.00 Top of ascent. bears NE and SW. stony
 80.09 The cor to secs. 27, 28, 33 and 34
 Land level and broken
 Soil, gravelly and stony 2nd & 4th rate
 Timber Pine and some oak.
 Heavily timbered land. 80.09 chs.

No ° of W. ret. secs. 27 and 28
 over-level and rolling land.

- 8.25 Descend
 12.00 Draw, 10 chs. wide, course E; ascend
 17.00 Top of ascent. bears E and W.
 27.75 Descend
 34.00 Draw, 1 ch wide, course E.
 34.25 Trail bears E and W; ascend
 40.00 Cut a Sandstone 18x8x8 ins
 12 ins. in the ground for $\frac{1}{4}$ s
 cor. marked $\frac{1}{4}$ S 28 on W
 face, 27 on E face.

Sub-division of T13N R11E con
tinues

from which

a Pine 17 ins. diam. bears
 $555\frac{1}{2}^{\circ}$ E. 52 $\frac{1}{2}$ lbs. dist. marked
 45.27. B.T.

a Pine 7 ins. diam. bears $588\frac{1}{2}^{\circ}$ W.
 35 lbs. dist. marked 45.28. B.T.

Top of ascent.

- 2.00 Descend
- 5.00 Draw 100 ft. wide, course E. ascend
- 8.50 Top of ascent bears E and W.
- 1.50 Descend
- 1.00 Draw 50 ft. wide, course Easterly; ascend
- 2.50 Top of ascent bears E and W.
- 1.00 Cut a Sand-stone 18 x 10 x 8 ins.
 12 ins. in the ground for cor. of
 sects. 21, 22, 27 and 28, marked
 with 2 notches on S and 2 notches
 on E edges. from which
- A Pine 12 ins. diam. bears N 38° E

Continued, Book 123.
Concluded, Book 124.

1902
BOOK 122