

BOOK 127 BOOK 127

1

BOOK 127 BOOK 127

No-127

Subdivisions

4-671

127

FIELD NOTES
GENERAL LAND OFFICE

Sp: 13 N. R. 12 E.

No-127

No-127

BOOK 127

Field-Notes.

1

of the Survey of the

Subdivision Lines.

of

Township 13. N. Range 12. East.

of the

Gila & Salt River Base

And Meridian

in the

Territory of Arizona

as surveyed by

Daniel Drummond

U. S. Deputy Surveyor

under his Contract. No. 28.

Dated February 21. 1893.

Survey Commenced Aug. 28. 1893.

Survey Completed Sept. 13. 1893.

(4-874.)

Township 13. N. R. 12. E.

Index for Books 127 and 125

6	104.	5	77.	4	56.	3	38.	2	18.	1
103.		101.		76.		54.		36.		16.
7	99.	8	73.	9	53.	10	34.	11	15.	12
97.		96.		72.		51.		32.		13.
18	94.	17	70.	16	49.	15	30.	14	11.	13
42.		91.		68.		48.		29.		10.
19	84.	20	66.	21	46.	22	27.	23	8.	24
87.		86.		65.		45.		25.		6.
30	84.	29	62.	28	43.	27	23.	26	4.	25
82.		81.		61.		42.		21.		3.
31	79.	32	57.	33	40.	34	19.	35	1.	36

Subdivisions T. 13, N. R. 12, E.

chs. From the Standard Cor.
to Secs. 35 & 36. Tp. 13, N.,
R. 12, E., heretofore described
I run.

N $0^{\circ} 1' W$. bet. Secs. 35 & 36
Va. $13^{\circ} 42' E$

- 40.00 Through heavy Pine & Oak timber
Set a sandstone $16 \times 12 \times 5$ ins
11 ins. in the ground. for $\frac{1}{4}$ Sec
Cor. marked $\frac{1}{4}$ on W face. Whence
A Cottonwood 5 ins. diam bears
 $S 37^{\circ} E$ 25 lks. dist. marked $\frac{1}{4}$
S. B.T. - A Cottonwood 6 ins.
diam. bears $S 29^{\circ} W$ 38 lks.,
dist. marked $\frac{1}{4}$ S. B.T.
- 41.50 Trail bears. N.E. & S.W.,
- 41.60 Gulch 10 lks. wide runs N.E.
- 45.85 Pine 24 ins. diam. on line marked
with 2 matches on N. & S. sides

Subdivisions T. 13. N. R. 12. E.

chs.	
72.00	Divide K trail bears. N.E. + S.W.
73.60	Pine 20 ins. diam. on line marked with 2 matches on N & S. sides
80.00	Set a Sandstone 20x10x8 ins. 15 ins. in the ground. for Cor. to Secs. 25, 26, 35 & 36. marked with 1 match on S. & E. edges, where A Pine 22 ins diam. bears. N 75° E 77 lks. dist. marked T. 13. N. R. 12. E. S. 25. B. T.
	A Pine 12 ins. diam. bears. S 74° E 152 lks. dist. marked T. 13. N. R. 12. E. S. 36. B. T.
	An Oak 6 ins. diam. bears. S 64° W 65 lks. dist. marked T. 13. N. R. 12. E. S. 35. B. T.
	A Pine 12 ins. diam bears. N 43° W 80 lks. dist. marked T. 13. N. R. 12. E. S. 26 B. T.

Subdivisions.

cha

Land level.

Soil alluvial 1st rate.

Timber heavy Pine & oak .80. cha

N $89^{\circ}39'E$ on a random line
bet. Secs. 25 & 36.

Va. $13^{\circ}42'E$.

40.00 Set. temporary $\frac{1}{4}$ Sec. Cor.

79.60 Int. E. boundary of Sp. 30 lks.

N. of the Cor. to Secs. 25, 30, 31
& 36. Hereinafter described.

Thence I run.

S $89^{\circ}52'W$ on a true line,
bet. Secs. 25 & 36.

Va. $13^{\circ}42'E$

Through heavy Pine & Oak timber.

2.30 Gulch 10 lks wide runs N.E.

10.60 Fir 24 ins. diam. on line marked

T. 13. N. R. 12. E.

- chs. with 2 watches on E. & W. sides.
- 39.80 Set. a Sandstone 18x10x6 ins.
13 ins. in the ground. for. $\frac{1}{4}$ Sec
Cor. Marked $\frac{1}{4}$ on N. face. whence
A Pine 8 ins. diam. bears, S50°W
8 lks. dist. marked $\frac{1}{4}$ S. B. J.
A Pine 6 ins. diam. bears, N37°E
75 lks. dist. marked $\frac{1}{4}$ S. B. J.
- 70.10 Divide & trail bears, N.E. & S.W.
- 79.60 The Cor. to Secs. 25, 26, 35 & 36.
Land rolling.
Soil Sandy 2^d rate.
✓ Timber heavy Pine & Oak. 79.60^{chs.}

N 0° 1' W. bet. Secs. 25 & 26.
Va. 13° 42' E

- 40.00 Through heavy Pine & Oak timber
Set. a Sandstone 16x10x8 ins

Subdivisions.

Chs. 11 ins. in the ground, for $\frac{1}{4}$ Sec
 Cor. marked $\frac{1}{4}$ on W. face, whence
 a Pine 10 ins. diam. bears $S72^{\circ}W$
 38 lks. dist. marked $\frac{1}{4}$ S. B. J. A
 Pine 20 ins. diam. bears $N58^{\circ}E$
 48 lks. dist. marked $\frac{1}{4}$ S. B. J.

76.00 Enta bottom

80.00 Sep. a Sandstone $16 \times 10 \times 6$ ins 11
 ins. in the ground, for Cor. to
 Secs. 23, 24, 25 & 26. marked
 with 2 notches on S. and 1 notch
 on E. edges, - whence

A Pine 22 ins. diam. bears
 $N65^{\circ}E$. 63 lks. dist. marked
 T. 13, N. R. 12, E. S. 24, B. J.

A Pine 12 ins. diam. bears
 $S82^{\circ}E$ 134 lks. dist. marked
 T. 13, N. R. 12, E. S. 25, B. J.

A Pine 25 ins. diam bears.

T. 13. N. R. 12. E.

chs. S62°W 121 lks. dist. marked
 T. 13. N. R. 12. E. S. 26. B. J.
 An Oak 4 ins. diam. bears,
 N3°30'W 127 lks. dist. marked
 T. 13. N. R. 12. E. S. 23 B. J.
 Land level
 Soil Alluvial 1st rate
 Timber Pine & Oak 80 chs.

N 89°52'E on a random line
 bet. Secs. 24 & 25
 Yu. 13°42'E

40.00 bet. temporary 1/4 Sec. Cor.
 79.56 Int. E. boundary of Sp. 7 lks.
 S. of the Cor. to Secs. 19, 24, 25 & 30
 Thence I run.
 S 89°49'W on a true line
 bet. Secs. 24 & 25,

Subdivisions.

Chs.

Ya. $13^{\circ}42'E$.

In heavy Pine & Oak timber

5.25 Entu bottom bars. N.E. & S.W.

6.30 Leam bottom bars. N.E. & S.W., ascend

39.78 Set. a sandstone $16 \times 12 \times 6$ ins.
 11 ins. in the ground. for. $\frac{1}{4}$ Sec.
 Cor. marked $\frac{1}{4}$ on N. face. Whence
 A Pine 14 ins. diam bars. $S40^{\circ}W$
 42 lks. dist. marked $\frac{1}{4}$ S. B.T.
 A Pine 15 ins. diam. bars. $N29^{\circ}E$
 36 lks. dist. marked $\frac{1}{4}$ S. B.T.

77.25 Entu bottom bars. NNW. & S.S.E.

78.00 Stream 20 lks wide Runs. N. by W.

79.56 The Cor. to Secs. 23. 24. 25 & 26.

Land nearly level

Soil sandy 2^d rate.

Timber heavy Pine & Oak 79.56 chs ✓

August. 28. 1893.

T. 13. N. R. 12. E.

- chs. N 0° 1' W. bat. Secs. 23 & 24
Va. 13° 42' E.
- In Heavy Pine timber
- 1.50 Stream 10 lks. wide runs N. by W.
- 6.40 Trail bears. Northely & Southely
- 18.10 Pine 36 ins. diam. on line. marked
with 2 notches on N. & S. sides
- 31.00 Enter bottom. bears. N. by E.
- 34.50 Recross stream bears. N. by E. ^{wide} 20 lks.
- 38.30 Trail bears. N. by E. & S. by W.
- 40.00 Set. a sandstone 18 x 12 x 5 ins.
13 ins. in the ground. for. 1/4 Sec
Cor. marked 1/4 on W. face. where
A Pine 4 ins. diam. bears. N 12° E
53 lks. dist. marked 1/4 S. B. I.
An Oak 5 ins. diam bears.
S 68 1/2° W 89 lks. dist. marked
1/4 S. B. I.
- 41.00 Leave bottom bears. N by E & S by W.

Subdivisions.

- chs.
60.60 Pine 30 ins. diam. on line marked with 2 notches on N. & S. sides
- 80.00 Set a sandstone 20x18x5 ins. 15 ins. in the ground, for Cor. to Secs. 13, 14, 23 & 24, marked with 3 notches on S. & 1 notch on W. E. edges. Whence -
A Pine 10 ins. diam. bears N69°E 40 lks. dist. marked T. 13, N. R. 12, E. S. 13 B. 4.
A Pine 11 ins. diam. bears S69°E 41 lks. dist. marked T. 13, N. R. 12, E. S. 24, B. 4.
A Pine 12 ins. diam. bears S70°W 135. lks. dist. marked T. 13, N. R. 12, E. S. 23, B. 4.
A Pine 8 ins. diam. bears N68°W. 70 lks. dist. marked T. 13, N. R. 12, E. S. 14, B. 4.

T. 13. N. R. 12. E.

chs. Land nearly level.
Soil sandy 2^d rate.
Timber Heavy Pine & Oak, 80 chs.

N 89° 49' E. on a random line
bet. Secs. 13 & 24.

Va. 13° 42' E.

40.00 Set. temporary 1/4 Sec. Cor.

79.50 Int. E boundary of Tp. 30 lks. S. of
Cor. to Secs. 13, 18, 19 & 24.

Thence I run S 89° 36' W
on a true line bet. Secs. 13 & 24.

Va. 13° 42' E.

In Heavy Pine and Oak timber

39.75 Set. a sandstone 15 x 10 x 6 ins 10
ins. in the ground. for 1/4 Sec. Cor.
Marked 1/4 on N. face, where an
Oak 5 ins. diam. bears. N 63° E

Sub divisions.

- Chs. 43 lks. dist. marked $\frac{1}{4}$ S. B.T.
 An Oak 4 ins. diam bears. $S 31^{\circ} W$
 9 lks. dist. marked $\frac{1}{4}$ S. B.T. -
 48.15 Gulch 10 lks. wide runs Northwaly
 66.70 Into bottom bears. N by E + S by W
 67.20 Trail bears. N.N.E. + S.S.W.
 67.40 Stream 20 lks. wide runs. N.N.E.
 69.30 Leave bottom bears. N.N.E. + S.S.W.
 79.50 The cor. to Secs. 13, 14, 23 + 24.
 Land level.
 Soil alluvial 1st rate.
 Timber Pine + Oak 79.50 Chains.
-

N $0^{\circ} 1' W$. bet. Secs. 13rd and 14.

Va. $13^{\circ} 42' E$.

In heavy Pine + Oak timber

- 40.00 Set a sandstone $22 \times 10 \times 7$ ins. 16 ins
 in the ground. for $\frac{1}{4}$ Sec. Cor. marked

T. 13. N. R. 12. E.

- chs. $\frac{1}{4}$ on N. face, whence a Pine 10 ins. diam. bears. $N 64^{\circ} W$ 60 lks. dist. marked $\frac{1}{4}$ S. B. T. — A Pine 20 ins. diam. bears. $S 13^{\circ} E$ 56. lks. dist. marked $\frac{1}{4}$ S. B. T.
- 63.50 Bank bears. $N. N. E.$ & $S. S. W.$ descend
- 64.20 Trail bears. $N. N. E.$ & $S. S. W.$
- 64.40 Dry bed of stream 10 lks. wide bears. $N. N. E.$
- 65.50 Leave bottom bears. $N. N. E.$ & $S. S. W.$ ascend
- 69.00 Opposite bank bears. $N. N. E.$ & $S. S. W.$
- 71.15 Pine 38 ins. diam. on line. marked with 2 notches on N. & S. sides
- 80.00 Bank bears. $N. by E.$ & $S. by W.$ sloping W. Set a sandstone $18 \times 11 \times 5$ ins. 13 ins. in the ground. for. Cr. to Secs. 11, 12, 13. $\frac{1}{4}$ 14. marked with 4 notches on S, and 1 notch on E. edges. whence A Pine 32 ins. diam. bears. $N 2^{\circ} E$. 86 lks. dist. marked T. 13. N. R. 12. E. S. 12. B. T.

Subdivisions.

chs. A Pine 34 ins. diam. bears.
 $S 63^{\circ} E$ 79 lks. dist. marked
 T. 13, N. R. 12 E. S. 13 B.T.

A Pine 12 ins. diam. bears.
 $S 57^{\circ} W$ 173 lks. dist. marked
 T. 13, N. R. 12 E. S. 14. B.T.

A Pine 22 ins. diam. bears.
 $N 35^{\circ} W$ 11 lks. dist. marked
 T. 13, N. R. 12 E. S. 11. B.T.

Land nearly level.

Soil sandy 2^d rate.

Timber heavy Pine & Oak, 80 chains.

$N 89^{\circ} 36' E$ on a random line
 bet. Secs. 12 & 13.

Va. $12^{\circ} 42' E$.

40.00 Sect. temporary $1/4$ Sec. Cor.

79.40 Int. E. boundary of Tp. 21 lks. N. of

T. 13. N. R. 12. E.

chs. Cor. to Secs. 7, 12, 13 & 18. Thence. Iron

S $89^{\circ}45'W$ on a true line.bet. Secs. 12nd & 13.Va. $13^{\circ}42'E$.

In heavy Pine & Oak timber.

31.20 Gulch 10 lks. wide runs N.N.E.

39.70 Set a sandstone $15 \times 11 \times 7$ ins. 10 ins.
in the ground. for $\frac{1}{4}$ Sec. Cor. marked
 $\frac{1}{4}$ on N. face. Whence A Pine 10 ins.
diam. bears N $31^{\circ}E$. 4-7 lks. dist. marked
 $\frac{1}{4}$ S. B. T. - An Oak 7 ins. diam. bears
S $10^{\circ}W$ 23 lks. dist. marked $\frac{1}{4}$ S. B. T.

69.70 Gulch. 20 lks. wide runs N.N.E.

79.40 The Cor. to Secs. 11, 12, 13 & 14.

Land rolling

Soil gravelly. 2^d & 3^d rateTimber. heavy Pine & Oak 79.4th chs.

August. 29. 1893.

Subdivisions.

- chs. N 0° 1' W. bet. Secs. 11 & 12.
Va. 13° 42' E.
- In heavy Pine & Oak timber
- 40.00 Set. a Sandstone 16x10x6 ins. 11 ins
in the ground. for. $\frac{1}{4}$ Sec. Cor. marked
 $\frac{1}{4}$ on W. face. whence. An Oak 4 ins.
diam. bears. N 65° W 49 lks. dist. marked
 $\frac{1}{4}$ S. B. J. - A Pine 12 ins. diam. bears
S 36° E 29 lks. dist. marked $\frac{1}{4}$ S. B. J.
- 63.30 Pine 30 ins. diam. on line marked
with 2 notches on N. & S. Sides.
- 80.00 Set. a Sandstone 18x12x6 ins. 13 ins
in the ground for. Cor. to Secs. 1, 2, 11 & 12.
Marked with 5 notches, on S, and
1 notch on E. edges. whence.
A Pine 10 ins. diam. bears.
N 47° E. 77 lks. dist. marked
J. 13. N. R. 12. E. S. 1. B. J.
A Pine 4 ins. diam. bears.

T. 13. N. R. 12. E.

- chs. S 11° E 71 lks. dist. marked
T. 13 N. R. 12. E. S. 12 B. T.
An Oak 6 ins. diam. bears.
S 2½° W 72 lks. dist. marked
T. 13, N. R. 12. E. S. 11, B. T.
A Pine 18 ins. diam. bears.
N 44° W 119 lks. dist. marked
T. 13, N. R. 12. E. S. 2 B. T.
Land broken.
Sail gravelly 3^d rate.
Timber Heavy Pine & Oak 80 chains.
-

N 89° 45' E on a random line
bet. Secs. 1 & 12.

Va. 13° 42' E.

- 40.00 Set. temporary ¼ Sec. Cor.
79.30 Int. E. boundary of Tp. 5 lks. N. of
Cor. to Secs. 1, 6, 7, & 12. Thence I run.

Subdivisions.

- chr. $S 89^{\circ} 47' W.$ on a true line
bet. Secs. 1 & 12.
Ta. $13^{\circ} 42' E.$
- In heavy Pine & Oak timber
- 20.30 Bank trans. $N, N.E. \& S.S.W.$ descend abrupt
- 21.40 Gulch. 20 lks wide runs $N, N.E.$ ascend
- 39.00 Bank trans. $N, N.E. \& S.S.W.$
- 39.65 Set a Sandstone $18 \times 12 \times 6$ ins 13
ins in the ground. for $\frac{1}{4}$ Sec. Cor.
marked $\frac{1}{4}$ on N. face. where an
Oak 7 ins. diam. trans. $S 25^{\circ} E$ 30 lks.
dist. marked $\frac{1}{4}$ S. B. I. - A Pine 4
ins. diam. trans. $N 76^{\circ} E$ 23 lks.
dist. marked $\frac{1}{4}$ S. B. I. -
- 73.00 Bank trans. $N, \& S.$
- 79.30 The Cor. to Secs. 1, 2, 11, & 12.
Land calling,
Soil gravelly 3^d rate,
Timber heavy Pine & Oak. 79.30 chr.

T. 13. N. R. 12. E.

- | | |
|-------|---|
| chs. | N 0° 1' W on a random line
bet. Secs. 1 and 2.
Va. 13° 42' E. |
| 40.00 | Set temporary 1/4 Sec. Cor. |
| 80.50 | Int. N. boundary of Sp. 3 lks. W. of
Cor. to Secs. 1, 2, 35 & 36. Thence I run
South, on a true line.
bet. Secs. 1 & 2.
Va. 13° 42' E. |
| | In heavy Pine & Oak timber |
| 11.90 | Bank from N.N.E. & S.S.W. descend |
| 14.86 | Enter bottom |
| 15.30 | Gulch, 30 lks. wide runs N.N. E. |
| 15.90 | Leave bottom & ascend, |
| 20.00 | Opposite bank from N.N.E. & S.S.W. |
| 40.50 | Set a Sandstone 16 x 10 x 6. ins. 11 ins
in the ground, for 1/4 Sec. Cor. -
Marked 1/4 on W. face. Whence a Pine
6 ins diam, trans. S 29. E. 30 lks. |

Subdivisions.

- chs. dist. marked $\frac{1}{4}$ S. B.T. An oak
 7 ins. diam. bears. $N 67^{\circ} E$ 35 lks.
 dist. marked $\frac{1}{4}$ S. B.T. —
- 59.86 Pine 32 ins. diam. on line marked
 with 2 notches. on N. & S. sides
- 68.00 Bank bears. N. by E. & S. by W. descend
- 74.00 descend abruptly
- 80.50 The Cor. to Secs. 1, 2, 11, & 12.
 Land broken.
 Sail stony 3^d rate.
 Timber heavy Pine & Oak 80.50 chs.
 August. 30. 1893.

From the Established Standard
 Cor. to Secs. 34 & 35. heretofore
 described. I run.

$N 0^{\circ} 1' W.$ bet. Secs. 34 & 35,
 $Va. 13^{\circ} 42' E.$

T. 13. N. R. 12. E.

- Chs. In heavy Pine & Oak timber
- 35.00 Enter bottom
- 35.10 Dry bed. 10 lks. wide runs E.
- 36.50 Trail bears. E & W.
- 37.00 N.W. Cor. of Cabin bears. $S 80^{\circ} E$ 12.10 chs.
- 38.00 Learn bottom & ascend
- 40.00 Set a Malpais Stone $22 \times 14 \times 8$ ins.
16 ins. in the ground. for. $\frac{1}{4}$ Sec Cor.
Marked $\frac{1}{4}$ on W. face. whence An Oak
8 ins. diam. bears. $N 69^{\circ} E$. 31. lks.
dist. Marked $\frac{1}{4}$ S. B. T. - A Pine 10
ins. diam. bears. $S 67^{\circ} W$ 54 lks. dist.
marked $\frac{1}{4}$ S. B. T.
- 80.00 Set a Sandstone $22 \times 14 \times 12$ ins. 16
ins. in the ground. for. Cor. to Secs.
26. 27. 34 & 35. marked with 1 notch
on S. and 2 notches. on E. edges. whence
A Pine 20 ins. diam. bears.
 $N 33^{\circ} E$. 66. lks. dist. marked

Subdivisions.

T. 13. N. R. 12. E. S. 26 B. J.

A Pine 18 ins. diam. trans.

S 14° E 53 lks. dist. marked

T. 13. N. R. 12. E. S. 35. B. J.

A Pine 18 ins. diam. trans.

S 42° W 12 lks. dist. marked

T. 13. N. R. 12. E. S. 34. B. J.

A Pine 8 ins. diam. trans

N 76° W 26 lks. dist. marked

T. 13. N. R. 12. E. S. 27 B. J.

Land level.

Soil sandy & gravelly 2^d & 3^d rates.

Timber Heavy Pine & Oak. 80 chains.

N 89° 34' E. on a random line.

cut. Secs. 26 & 35.

Ya. 13° 42' E.

40.00 Sect. Temporary 1/4 Sec. Cor.

T. 13. N. R. 12. E.

- chs.
79.90 Int. N. & S. line 16 lks. S. of Cor. to Secs.
25, 26, 35 & 36. Thence I run
S $89^{\circ}32'W$. on a true line
bet. Secs. 26. & 35.
Va $13^{\circ}42'E$.
- In Heavy Pine & Oak timber
17.60 Gulch 10 lks. wide runs Northwly.
36.00 Enter bottom. bears N.N.E. & S.S.W.
37.50 Trail bears N.N.E. & S.S.W.
37.85 Dry bed. 20 lks. wide runs N.N.E.
39.95 Set a Sandstone $15 \times 8 \times 6$ ins. 10 ins.
in the ground. for $\frac{1}{4}$ Sec. Cor. marked
 $\frac{1}{4}$ on W. face. Whence A Pine 12 ins.
diam. bears N $63^{\circ}W$ 62 lks. dist.
marked $\frac{1}{4}$ S. B. I. - A Pine 6 ins.
diam. bears S $73^{\circ}W$. 286. lks. dist.
marked $\frac{1}{4}$ S. B. I. -
- 46.40 Leave bottom & ascend
59.15 Fir 20 ins. diam. on line marked

Subdivisions.

- chs. with 2 notches on E. & W. sides.
- 61.70 Gulch 10 lks. wide runs Northw.,
- 79.90 The Cor. to Secs. 26, 27, 34 & 35.
Land nearly level.
Soil. Alluvial & Sandy 1st & 2^d rates.
Timber Pine & Oak. 79.90 chs.
-

N 0° 1' W. bet. Secs. 26 & 27.

Va. 13° 42' E.

Thin heavy Pine & Oak timber

- 8.75 Pine 20 ins diam. on line marked
with 2 notches on N. & S. sides
- 16.80 Pine 18 ins. diam. on line marked
with 2 notches on N. & S. sides
- 30.25 Pine 36 ins. diam. on line marked
with 2 notches on N. & S. sides
- 40.00 Set a sandstone 24x10x6 ins. 18 in.
in the ground. for 1/4 Sec. Cor.

J. 13. N. R. 12. E.

- cho. Marked $\frac{1}{4}$ on N. face. whence an Oak
12 ins. diam. trans. N 23° W 14 lks. dist.
Marked $\frac{1}{4}$ S. B. J. An. Oak 10 ins. diam.
trans. N 72° E 73 lks. dist. Marked $\frac{1}{4}$ S. B. J.
- 71.20 Entire bottom trans. N. E. & W.
- 72.60 Dry bed 10 lks wide runs. E & N. E.
- 74.50 Trail trans. N. N. E. & S. S. W.
- 75.70 Level bottom trans N. N. E. & S. S. W.
- 80.00 Set. a Sandstone $20 \times 12 \times 5$ ins. 15 ins.
in the ground. for. Cor. to Secs, 22,
23, 26 & 27 Marked with 2 notches
on S. & E. edges. Whence —
A Pine 5 ins. diam trans.
N 54° E 26 lks. dist. marked
J. 13. N. R. 12. E. S. 23 B. J.
A Pine 4 ins. diam. trans.
S 61° E 11 lks. dist. marked
J. 13. N. R. 12. E. S. 26 B. J.
A Pine 14 ins. diam. trans.

Subdivisions.

S 78° W 86. lks. dist. marked

T. 13, N. R. 12, E. S. 27. B.T.

A Pine 4 ins. diam. bears.

N 23° W. 89 lks. dist. marked

T. 13, N. R. 12, E. S. 22. B.T.

Land level.

Soil Sandy 2^d rate.

Timber Pine & Oak 80. chaus.

N 89° 32' E on a random line

bet. Secs. 23 & 26.

Va. 13° 42' E.

40.00 Set temporary 1/4 Sec. Cor.

79.53 Int. N. & S line 21 lks. N. of Cor. to

Secs. 23, 24, 25 & 26. Thence S. run

S 89° 41' W. on a true line

bet. Secs. 23 & 26.

Va. 13° 42' E.

T. 13. N. R. 12. E.

chs.	In heavy Pine & Oak timber
1.23	Trail bars Northernly & Southernly
2.50	Learn bottom & ascend bars. N by W. & S by E.
30.83	Pine 24 ins. diam. on line marked with 2 notches on E. & W. sides
39.77	Set. a Sandstone 22 x 15 x 6 ins. 16 ins in the ground. for. $\frac{1}{4}$ Sec. Cr. Marked $\frac{1}{4}$ on N. face. whence a Pine 8 ins. diam. bars. N 13° W 49 lks. dist. Marked $\frac{1}{4}$ S. B. T. - A Pine 11 ins diam. bars. S 8° E 67 lks. dist. Marked $\frac{1}{4}$ S. B. T.
49.00	Bank bars. N. & S. descend
52.00	Enter bottom bars. N. & S.
54.70	Gulch 20 lks. wide runs Northernly ^{descend}
54.90	Trail bars. N. & S.
57.00	Learn bottom & ascend
58.10	Pine 32 ins. diam. on line marked with 2 notches on E. & W. sides

Sub divisions.

chs.	
60.20	Opposite bank trans N. & S.
69.88	Pine 18 ins. diam. on line marked with 2 notches on E. & W. sides
72.30	Enter bottom
73.20	Dry bed 20 lks. wide runs N. N. E.
74.80	Trail trans. N. N. E. & S. S. W.
76.30	Leave bottom & ascend
79.53	The Cor. to Secs. 22, 23, 26. & 27. Land nearly level. Soil sandy & gravelly 2 ^d & 3 ^d rate. Timber heavy Pine & Oak. 79.53 chs. August 31. 1893.

N 0° 1' W bet. Secs. 22 & 23.

Pa 13° 42' E.

In heavy Pine & Oak timber

5.00 Gulch 20 lks wide runs East by

34.24 Gulch 10 lks wide runs N. E.

T. 13. N. R. 12. E.

- 40.00 Set. a Sandstone $18 \times 8 \times 7$ ins. 13. ins. in the ground. for. $\frac{1}{4}$ Sec. Cor. marked $\frac{1}{4}$ on N. face. Whence A Pine 20 ins. diam. bears. $S 61^{\circ} E$ 36 lks. dist marked $\frac{1}{4}$ S. B. T. — A Pine 28 ins. diam. bears. $N 57^{\circ} W$ 34 lks. dist marked $\frac{1}{4}$ S. B. T.
- 60.24 Pine 12 ins. diam. on line marked with 2 notches on N. & S. Sides
- 80.00 Set. a Sandstone $20 \times 9 \times 6$ ins. 15. ins. in the ground. for. Cor. to Secs. 14, 15, 22, & 23, marked with 3 notches on S. and 2 notches on E. edges. Whence A Pine 18 ins. diam. bears. $N 28^{\circ} E$. 60 lks. dist. marked T. 13, N. R. 12. E. S. 14. B. T. A Pine 10 ins. diam. bears. $S 22^{\circ} E$ 74 lks. dist. marked T. 13, N. R. 12, E. S. 23 B. T. A Pine 5 ins. diam. bears.

Subdivisions.

chs. S 30° W 68 lks. dist. marked
 T. 13, N. R. 12, E. S. 22 B. 1.
 A Pine 20 ins. diam. bears,
 N 6° W 60 lks. dist. marked
 T. 13, N. R. 12, E. S. 15 B. 1.
 Land level.
 Soil Sandy 2^d rate.
 Timber Heavy Pine & Oak. 80 chs.

N $89^{\circ} 41' E$ on a random line
 bet. Secs. 14 & 23.
 Va. $13^{\circ} 42' E$.

40.00 Sect. temporary $1/4$ Sec. Cor.
 79.60 Int. N. & S. line 5 lks. S of Cor. to
 Secs. 13, 14, 23, & 24. Thence I run
 S $89^{\circ} 39' W$ on a true line
 bet. Secs. 14 & 23.
 Va. $13^{\circ} 42' E$

T. 13. N. R. 12. E.

- Chs. In heavy Pine & Oak timber
- 16.00 Bank trans. N.N.E. & S.S.W. descend
- 26.40 Trail trans. N.N.E. & S.S.W.
- 27.30 Dry bed 20 lbs wide runs. N.N.E. ^{usual}
- 34.50 Opposite bank. trans. N.N.E. & S.S.W.
- 39.80 Sec. a Sandstone 18x10x8 ins. 13 ins
in the ground. for. $\frac{1}{4}$ Sec. Cor. marked
 $\frac{1}{4}$ on N. face. whence A Pine 8 ins. diam.
trans. N29°W 9 lks. dist. marked $\frac{1}{4}$ S.
B.S. - A Pine 14 ins. diam. trans.
S50°E 23 lks. dist. marked $\frac{1}{4}$ S. B.S.
- 79.60 The Cor. to Secs. 14, 15, 22 & 23.
Land broken.
Soil gravelly 2^d rate.
Timber heavy Pine & Oak. 79.60 chs.

N 0° 1' W. bet. Secs. 14 & 15.
Va. 13° 42' E.

Subdivisions.

- Chs. In Heavy Pine & Oak timber
- 40.00 Set a Sandstone $18 \times 14 \times 4$ ins. 13 ins
in the ground, for $\frac{1}{4}$ sec. Cr. marked
 $\frac{1}{4}$ on W. face. whence a Pine 12 ins.
diam. bears. $N 65^\circ W$ 63 lks. dist.
marked $\frac{1}{4}$ S. B. T. — Au. Oak, 6 ins
diam. bears. $S 40^\circ E$ 41 lks. dist.
marked $\frac{1}{4}$ S. B. T. —
- 49.00 Bank bears. N.E. & S.W. descent
- 51.00 Gulch. 20 lks. wide runs. N.E. ascend,
- 51.50 Trail bears. N.E. & S.W.
- 54.00 Opposite bank bears. N.E. & S.W.
- 80.00 Set a Sandstone $18 \times 10 \times 5$ ins. 13 ins
in the ground, for Cr. to Secs. 10, 11
14 & 15, marked with 4 notches on
S. and 2 notches on E. edges. whence
A Pine 12 ins. diam. bears.
 $N 48^\circ E$. 90. lks. dist. marked
T. 13, N. R. 12. E. S. 11 B. T.

T. 13. N. R. 12. E.

chs. A Pine 6 ins. diam. trans.
 S 20° E. 76 lks. dist. marked
 T. 13, N. R. 12, E. S. 14. B. T.

A Pine 5 ins. diam. trans.
 S 81° W 67 lks. dist. marked
 T. 13, N. R. 12, E. S. 15 B. T.

A Pine 6 ins. diam. trans.
 N 1° W 62 lks. dist. marked
 T. 13, N. R. 12, E. S. 10. B. T.

Land nearly level.
 Soil Sandy 2^d rate.
 Timber. Heavy Pine & Oak. 80 chs.

N 89° 39' E on a random line
 bet. Secs. 11, & 14.

Va 13° 42' E.

40.00 Sect. temporary 1/4 Sec. Cor.

79.60 Sect. N. & S. line, at Cor. to Secs.

Subdivisions.

- chs. 11, 12, 13 & 14. Thence I run.
 S $89^{\circ}39'$ W on a true line,
 bet. secs. 11 & 14,
 Va. $13^{\circ}42'$ E.
- In heavy Pine & Oak timber descend
- 6.20 Enter bottom trans. N. & S.,
- 6.90 Trail trans. N. & S.,
- 7.10 Gulch 20 lks. wide runs N.
- 8.10 Leave bottom & ascend
- 8.50 Ridge trans. N.E. & S.W. descend
- 12.50 Enter bottom
- 14.10 Gulch 20 lks. wide runs S.E.
- 14.60 Trail trans. S.E. & N.W.
- 14.75 Leave bottom & ascend
- 22.00 Bank trans. S.E. & N.W.
- 39.80 Set a sand stone $22 \times 10 \times 8$ ins. 16 ins
 in the ground for $\frac{1}{4}$ sec. Cor. marked
 $\frac{1}{4}$ on N. face. Whence A Pine 14 ins
 diam. trans. S 14° E. 49 lks. dist.

T. 13. N. R. 12. E.

- Chs. Marked $\frac{1}{4}$ S. 13, T. - A Pine 34 ins. diam
 trans. N 30° E 40 lks. dist marked $\frac{1}{4}$ S. 13, T.
- 45.00 Bank trans. N. E. & S. W. descend
- 47.50 Enter bottom
- 48.40 Gulch 10 lks. wide runs. N. E.
- 49.95 Gulch 10 lks wide runs. N. E.
- 52.00 Trail trans. N. E. & S. W.
- 52.50 Leave bottom & ascend
- 56.00 Opposite bank trans. N E & S. W.
- 79.60 The Cor. to Secs. 10, 11, 14 & 15.
 Land rough & broken,
 Soil stony. 4th rate.
 Timber Pine & Oak. 79.60 chs.
 September 1, 1893.
-

N 0° 1' W. bet. Secs. 10 & 11.Va. 13° 42' E.

In heavy Pine & Oak timber.

Subdivisions.

- chs.
 2.25 Bank trans. N.N.E. & S.S.W. descend
 3.00 Gulch. 20 lks. wide runs. N.N.E. ascend
 3.50 opposite Bank trans. N.N.E. & S.S.W.
 4.05 Pine 22 ins. diam. on line marked
 with 2 notches on N. & S. sides
 11.00 Enta mesa. trans. N.N.E. & S.S.W.
 40.00 Set. a Sandstone $20 \times 13 \times 3$ ins. 15 ins.
 in the ground. for. $\frac{1}{4}$ Sec Cor. marked
 $\frac{1}{4}$ on W. face. whence An Oak 6 ins.
 diam. trans. $N 53^\circ E$ 43 lks. dist.
 marked $\frac{1}{4}$ S. B. T. - A Pine 20 ins.
 diam. trans. $S 81^\circ W$ 66 lks. dist.
 marked $\frac{1}{4}$ S. B. T. -
 80.00 Sandstone in place $15 \times 10 \times 4$ ins.
 above ground. for. Cor. to Secs. 2
 3, 10 & 11. marked with 5 notches
 on S. and 2 notches on E. edges.
 Whence An Oak 6 ins diam. trans.
 $N 45^\circ E$ 27 lks. dist. marked.

T. 13. N. R. 12. E.

Chs. T. 13. N. R. 12. E. S. 2 B.S.

A Pine 10 ins. diam. trans.

S 20° E 66 lks. dist. marked

T. 13. N. R. 12. E. S. 11. B.S.

A Pine 6 ins. diam. trans.

S 40° W 14 lks. dist. marked

T. 13. N. R. 12. E. S. 10. B.S.

A Pine 12 ins. diam. trans.

N 65° W 114 lks. dist. marked

T. 13. N. R. 12. E. S. 3. B.S.

Land. Nearly level.

Soil. gravelly. 3^d rate.

Timber Heavy Pine + Oak 80 chs.

 N 89° 39' E on a random line
bet. Secs. 2nd & 11.

Va. 13° 42' E.

40.00 Sep. Temporary 1/4 Sec. Cor.

Subdivisions

chs. 79.54	Int. N + S line 25 lks. N. of Cor. to Secs. 1, 2, 11 & 12. Thence from S $89^{\circ}50'W$. on a true line bet. Secs. 2 & 11. Va. $13^{\circ}42' E$.
	In heavy Pine & Oak timber
1.25	Bank trans. N.E. + D.W. descend
4.20	Gulch 20 lks. wide runs N.E. ^{ward}
6.50	Ridge trans. N. + S. descend
10.50	Enter bottom
11.10	Recross. 20 lks wide runs S.E.
14.80	Leave bottom
19.20	Reenter bottom
19.60	Recross 20 lks. wide runs N.E.
20.90	Leave bottom
23.00	Bank trans. E. + W. steep
25.00	Bank trans. E. + W. steep
35.30	Bank trans. N.W. + S.E.
39.50	Recross Gulch 10 lks wide runs S.E. ascend

T. 13. N. R. 12. E.

- 39.77 Set. a Sandstone 18x12x5 ins 13 ins.
in the ground. for. $\frac{1}{4}$ Sec. Cor. marked
 $\frac{1}{4}$ on N. face, whence A Pine 6 in diam.
brans. N 61° E 12 lks. dist. marked $\frac{1}{4}$
S. B. J. — A Pine 4 ins. diam. brans.
S 56° E 15 lks. dist. marked $\frac{1}{4}$ S. B. J.
- 40.80 Bank brans. N. & S.
- 61.00 Gulch 20 lks. wide runs Eastly ^{W. side}
- 65.00 Bank brans. Eastly & Westly.
- 79.54 The Cor to Secs. 2, 3, 10 & 11.
Land. rough & broken.
Soil rocky 4th rate.
Timber Pine & Oak. 79.54 chs.
-

North. on a random line
bet. Secs. 2^d & 3.

Ya. $13^{\circ}42'$ E.

40.00 Set. temporary $\frac{1}{4}$ Sec Cor.

Subdivisions.

- chs.
80.96 Int. N. boundary of Tp. 40 lks.
W. of Cor. to Secs. 2, 3, 34, & 35.
Thence Iron
S $0^{\circ}17'$ W on a true line.
bet. Secs 2, & 3.
Va. $13^{\circ}42'$ E.
- 26.10 In heavy Pine & Oak timber
Pine 20 ins. diam. on line marked
with 2 notches on N. & S. sides
- 40.96 Set a Sandstone $20 \times 14 \times 6$ ins. 15
ins. in the ground. for $\frac{1}{4}$ Sec. Cor.
marked $\frac{1}{4}$ on W. face. whence
A Pine 8 ins. diam bears N 58° W
27 lks. dist. marked $\frac{1}{4}$ S. B. S.
A Pine 4 ins. diam. bears N 66° E
12 lks. dist. marked $\frac{1}{4}$ S. B. S.
- 80.96 The Cor. to Secs. 2, 3, 10 & 11
Land nearly level.
Soil gravelly 2^d rate.

T. 13. N. R. 12. E.

Timber Heavy Pine & Oak. 80.96 chs.
 September 2, 1893.

From the Standard Cor. to Secs.
 33 & 34. Hereinafter described.
 Iron. N $0^{\circ} 2' W$. bet. Secs. 33 & 34,
 Va. $13^{\circ} 42' E$.

In heavy Pine & Oak timber

- 12.35 Pine 36 ins. diam. on line marked
 with 2 notches on N. & S. sides
- 34.10 Pine 34 ins. diam. on line marked
 with 2 notches on N. & S. sides
- 40.00 Set a Sandstone $26 \times 14 \times 8$ ins. 19
 ins. in the ground. for $\frac{1}{4}$ Sec. Cor
 marked $\frac{1}{4}$ on W. face. whence a Pine
 22 ins. diam. bears. $N45^{\circ} E$. 10 lks.
 dist. marked $\frac{1}{4}$ S. B.T. - A Pine 20
 ins. diam. bears. $S50^{\circ} W$ 88 lks.

Subdivisions.

- chs. dist. marked $1/4$ S. B. T. —
- 80.00 Set a Sandstone $26 \times 12 \times 10$ ins. 19
ins. in the ground. for Cor. to Secs.
27, 28, 33, & 34, marked with 1 notch
on S. and 3 notches on E. edges. Whence
A Pine 18 ins. diam. bears.
N 30° E 3 lks. dist. marked
T. 13, N. R. 12, E. S. 27, B. T.
A Pine 17 ins. diam. bears.
S 54° E 124 lks. dist. marked
T. 13, N. R. 12, E. S. 34 B. T.
A Pine 20 ins diam. bears.
S 80° W. 44 lks. dist. marked
T. 13, N. R. 12 E. S. 33. B. T.
A Pine 10 ins. diam. bears.
N 30° W 11 lks. dist. marked
T. 13, N. R. 12, E. S. 28. B. T.
Land level.
Soil Sandy 2^d rate.
Timber Pine & Oak, 80 chains.

T. 13. N. R. 12. E.

chs. N $89^{\circ}39'E$ on a random line
bet. Secs. 27 & 34.
Ya. $13^{\circ}42'E$.

40.00 Set temporary $\frac{1}{4}$ Sec. Cor.

80.15 Int. N. & D. line. at Cor. to Secs. 26

27, 34 & 35. Thence I run

S $89^{\circ}39'W$ on a true line

bet. Secs. 27 & 34.

Ya. $13^{\circ}42'E$.

In heavy Pine & Oak timber.

30.30 Gulch 10 lks. wide runs N.W.

30.90 Trail bears N.W. & S.E.

37.90 Pine 20 ins. diam. on line. Marked
with 2 matches on E. & W. sides

40.07 Set a sandstone $20 \times 15 \times 3$ ins. 15
ins. in the ground. for $\frac{1}{4}$ Sec Cor.

Marked $\frac{1}{4}$ on N. face. whence an Oak
6 ins diam. bears N $34^{\circ}E$ 25 lks.
dist. marked $\frac{1}{4}$ S. B. Y. A. Fir 13.

Subdivisions.

- chs. ins. diam. bears S 60° W 26 lks.
 dist. marked $\frac{1}{4}$ S. B. I. -
- 61.00 Entire bottom bears. N. & S.
- 62.70 Trail bears. N. & S.
- 63.70 Dry bed 30 lks. wide runs. N.
- 64.10 Trail bears. N. & S.
- 65.50 Leaves bottom N. & S. ascend gently.
- 80.15 The Cor. to Secs. 27, 28, 33, & 34.
 Land nearly level.
 Soil sandy 2^d rate.
 Timber Heavy Pine & Oak. 80¹⁵ chs.
-

✓ N 0° 2' W. bet. ^{Secs.} 27 & 28.
 Va. 13° 42' E.

In Heavy Pine & Oak timber

- 40.00 Set a sandstone 18x14x6 ins. 13
 ins. in the ground. for $\frac{1}{4}$ Sec Cor.
 marked $\frac{1}{4}$ on W. face. whence

T. 13. N. R. 12. E.

Chs. A Pine 8 ins. diam. bears. $S59^{\circ}E$ 41
 lks. dist. marked $\frac{1}{4}$ S. B.T. —
 An Oak 10 ins. diam. bears. $S62^{\circ}W$ 57
 lks. dist. marked $\frac{1}{4}$ S. B.T. —

80.00 Set a Sandstone $22 \times 12 \times 5$ ins. 16 ins
 in the ground for Cor. to Secs. 21, 22,
 27 & 28, marked with 2 notches on S
 and 3 notches on E. edges. Whence
 A Pine 28 ins. diam. bears.
 $N45^{\circ}E$ 86 lks. dist. marked
 T. 13. N. R. 12. E. S. 22 B.T.
 A Pine 6 ins. diam. bears.
 $S33^{\circ}E$ 51 lks. dist. marked
 T. 13. N. R. 12 E. S. 27. B.T.
 A Pine 10 ins. diam. bears.
 $S81^{\circ}W$ 44 lks. dist. marked
 T. 13. N. R. 12 E. S. 28. B.T.
 An Oak 8 ins. diam. bears.
 $N42^{\circ}W$ 25 lks. dist. marked

Subdivisions.

T. 13, N. R. 12, E. S. 21. B.T.

Land level.

Soil Sandy 2^d rate.

Timber. Heavy Pine & Oak 80.15 Ch.

N 89° 39' E on a random line
bet. Secs. 22 & 27.

Va 13° 42' E.

40.00 Set. temporary 1/4 Sec. Cor.

80.00 Sub. N.T.S. line at Cor. to Secs.

22, 23, 26 & 27. Thence I run

S 89° 39' W. on a true line

bet. Secs. 22 & 27

Va 13° 42' E

In heavy Pine & Oak timber.

40.00 Set. a Sandstone 16 X 10 X 6 ins. 11 ins

in the ground. for 1/4 Sec. Cor. marked

1/4 on N. face. Whence. A line 8

ins. diam. brass. N 25° W 6 lbs. dist

T. 13. N. R. 12. E.

Chs. marked $\frac{1}{4}$ S. B. I. - A Pine 7 ins diam.
 bears. $S 4^{\circ} W$ 7 lks. dist. marked $\frac{1}{4}$ S. B. I.
 80.00 The Cor. to Secs. 21, 22, 27, & 28.
 Land. level.
 Soil Sandy 2^d rate.
 Timber heavy Pine & Oak. 80 chains.

$N 0^{\circ} 2' W$. bet. Secs. 21 & 22.
 Va. $13^{\circ} 42' E$.

In heavy Pine & Oak timber.

20.60 Gulch 10 lks. wide runs N. by E.
 35.40 Recross. gulch 20 lks wide runs N.W. ascend
 38.50 Bank bears. N.W. & S.E.
 40.00 Set a Sandstone $20 \times 8 \times 6$ ins. 15 ins.
 in the ground. for $\frac{1}{4}$ Sec. Cor. marked
 $\frac{1}{4}$ on W. face. whence An Oak. 5 ins. diam.
 bears. $N 42^{\circ} W$ 28 lks. dist. marked $\frac{1}{4}$
 S. B. I. - An Oak 4 ins. diam. bears.

Subdivisions.

- chs. S 36° E, 38 lks. dist. marked 1/4
S. B. I. —
- 80.00 Pine 24 ins. diam. which I mark
T. 13, N. S. 15 on N. E.
R. 12, E. S. 22 on S. E.
S. 21 on S. W. and
S. 16 on N. W. Sides. with 3 notches
on S. and E. Sides. for Cor. to Secs.
15, 16, 21 & 22. Whence
A Pine 26 ins. diam. bears
N 75° E 97 lks. dist. marked
T. 13, N. R. 12, E. S. 15. B. I.
A Pine 22 ins. diam. bears
S 70° E 36 lks. dist. marked
T. 13, N. R. 12, E. S. 22 B. I.
An Oak 8 ins. diam. bears
S 40° W 81 lks. dist. marked
T. 13, N. R. 12, E. S. 21 B. I.
A Pine 20 ins. diam. bears.

T. 13. N. R. 12. E.

chs. N 53° W 73 lks. dist. marked
T. 13. N. R. 12. E. S. 16 B. J.
Land. Nearly level.

Soil. Sandy 2^d rate.

Timber. Heavy Pine & Oak, 80. chs.

September 4. 1893.

N 89° 39' E. on a random line
bet. Secs. 15 & 22.

Va. 13° 42' E.

40.00 Set. temporary 1/4 Sec. Cor.

79.60 Sub. N. & S. line bet. Cor. to Secs. 14, 15, 22.

& 23. Thence I run

N 89° 39' E. on a true line

bet. Secs. 15 & 22

Va. 13° 42' E.

In heavy Pine & Oak timber

26.30 Gulch 10 lks. wide runs N. E.

Subdivisions.

- chs.
39.80 Set. a Sandstone 16x10x5 ins. 11
ins. in the ground. for $\frac{1}{4}$ Sec Cor.
marked $\frac{1}{4}$ on N. face where a Pine
22 ins. diam. bears. $N 85^{\circ} E 21$ lks.
dist. marked $\frac{1}{4}$ S. B. T. — A Pine 10 ins.
diam. bears. $S 47^{\circ} E 80$ lks. dist.
Marked $\frac{1}{4}$ S. B. T. —
- 79.60 The Cor. to Secs. 15, 16, 21 & 22.
Land level.
Soil. Sandy. 2^d rate.
Timber heavy Pine & Oak. 79.60 chs.
-
- $N 0^{\circ} 2' W$. bet. Secs. 15 & 16.
 $V a 13^{\circ} 42' E$.
- In heavy Pine & Oak timber
- 8.30 Pine 12 ins. diam. on line. Marked
with 2 notches on N. & S. sides
- 40.00 Set. a Sandstone 18x12x4 ins. 13

Chs. ins. in the ground. for $\frac{1}{4}$ Sec. Cor.
 marked $\frac{1}{4}$ on W. face, whence a Pine
 12 ins. diam. bears, $S33^{\circ}E$ 9 lks. dist.
 marked $\frac{1}{4}$ S. B.Y. — A Pine 14 ins. diam.
 bears $N17^{\circ}W$ 21 lks. dist. marked
 $\frac{1}{4}$ S. B.Y. —

80.00 Set a Sandstone $26 \times 10 \times 4$ ins. 19 ins
 in the ground. for Cor. to Secs. 9, 10,
 15 & 16, marked with 4 notches on S.
 and 3 notches on E. edges. Whence
 A Pine 26 ins. diam. bears
 $N18^{\circ}E$ 45 lks. dist. marked
 T. 13, N. R. 12, E. S 10 B.Y.

A Pine 20 ins. diam. bears.
 $S35^{\circ}E$ 10 lks. dist. marked
 T. 13, N. R. 12 E. S. 15. B.Y.

A Pine 16 ins. diam. bears.
 $S84^{\circ}W$ 30 lks. dist. marked
 T. 13, N. R. 12. E. S 16 B.Y.

Sub divisions.

Chs. An Oak 8 ins. diam. branch,
 N 30° W 85 lks. dist. marked
 J. 13. N. R. 12. E. S. 9 B. J.
 Land level.
 Soil sandy 2^d rate.
 Timber heavy Pine. 80. Chains.

N 89° 39' E on a random line
 bet. Secs. 10 & 15,
 Ya 13° 42' E.

40.00 Set temporary 1/4 sec. Cor.
 79.90 Int. N. & S. line at Cor. to Secs.
 10, 11, 14 & 15. Thence I run
 S 89° 39' W on a true line,
 bet. Secs. 10 & 15,
 Ya 13° 42' E

In heavy Pine & Oak timber
 0.30 Gulch - 10 lks. wide runs N. N. E.

- chs.
12.95 Pine 20 ins. diam. on line marked
with 2 notches on E. & W. Sides
- 20.05 Pine 26 ins. diam. on line. marked
with 2 notches on E. & W. Sides.
- 39.95 Set. a Sandstone 18x10x5 ins. 13 in
in the ground. for $\frac{1}{4}$ Sec. Cor. marked
 $\frac{1}{4}$ on N. face. Whence An Oak 10 ins.
diam. bears N 47° W 17 lks. dist.
marked $\frac{1}{4}$ S. B. T. — An Oak. 8 ins. diam.
bears S 4° W 78 lks. dist. marked
 $\frac{1}{4}$ S. B. T. —
- 64.50 Pine 12 ins. diam. on line. marked
with 2 notches on E. & W. Sides.
- 79.90 The Cor. to Secs. 9. 10. 15 & 16.
Land. level.
Soil Sandy 2^d rate.
Timber heavy Pine & Oak. 79.90 chs.
September 5, 1893.

Subdivisions.

Chs. No^o 2' W. but. Secs. 9 & 10.

Va 13° 42' E.

In heavy Pine & Oak timber

40.00 Sandstone in place 3x2x1/2 ft.
above ground. for. 1/4 Sec. Cor.
marked with Cross, thru (+), with
1/4 on W. side. Whence A Pine 20
ins. diam. bears S 70° E 53 lks.
dist. marked 1/4. S. - An Oak 6
ins. diam. bears, N 79° W 83 lks.
dist. marked 1/4. S. B.S. -

80.00 Set a Malpais Stone 22x10x8 ins
16 ins. in the ground. for. Cor. to
Secs. 3, 4, 9 & 10. Marked with
5 notches on S. and 3 notches on E.
Edges. Whence

A Cottonwood 5 ins. diam. bears,
N 11° E 109 lks. dist. marked
J. 13. N. R. 12. E. S. 3 B.S.

T. 13. N. R. 12. E.

chs. A Cottonwood 6 ins. diam. bears,
 $S 71^{\circ} E$ 52 lks. dist. marked
 T. 13. N. R. 12. E. S. 10. P. 1.

An Oak 14 ins diam. bears.
 $S 65^{\circ} W$ 60 lks. dist. marked
 T. 13. N. R. 12. E. S. 9 P. 1.

An Oak 8 ins. diam. bears.
 $N 42^{\circ} W$ 71 lks. dist. marked
 T. 13. N. R. 12. E. S. 4 P. 1. —

Land level.

Soil. Sandy & gravelly 2^d & 3^d rate
 Timber heavy Pine & Oak 80 chs.

$N 89^{\circ} 39' E$ on a random line
 Int. Secs. 3 & 10.
 $\gamma a 13^{\circ} 42' E$.

40.00 Sep. temporary $1/4$ sec. Cor.

79.70 Int. N. & S. line 21 lks. S. of Cor. to Secs.

Subdivisions.

- chs. 2, 3, 10 & 11, Thence I run
 S $89^{\circ}30'W$. on a true line
 bet. Secs. 3, & 10.
 Ta $13^{\circ}42'E$.
- In heavy Pine & Oak timber.
- 10.10 Divide & trail bears N.E. & S.W.
- 30.00 Pine 26 ins. diam. on line, marked
 with 2 notches on E. & W. sides
- 39.85 Set a Sandstone $15 \times 8 \times 4$ ins. 10 ins
 in the ground for $\frac{1}{4}$ sec. Or. marked
 $\frac{1}{4}$ on N. face, whence an Oak 4 ins.
 diam. bears N $68^{\circ}W$ 49 lks. dist,
 marked $\frac{1}{4}$ S. B.T. - an Oak 6 ins
 diam. bears S $70^{\circ}E$ 8 lks. dist,
 marked $\frac{1}{4}$ S. B.T. -
- 40.90 Gulch 10 lks. wide runs E. N.E.
- 79.40 Gulch 10 lks. wide runs N. by W.
- 79.70 The Cor. to Secs. 3, 4, 9 & 10.
 Land level.

T. 13. N. R. 12. E.

Soil Gravelly 3^d rate.

Timber, Heavy Pine & Oak 79.70 cts.

N^o 17' E on a random line
bet. Secs. 3 & 4.

Va. 13° 42' E.

40.00 Set temporary 1/4 Sec. Cor.

81.44 Int. N. boundary of Tp. 16 lks. E. of
Cor. to Secs. 3, 4, 33 & 34. Thence run.

S 0° 10' W on a true line

bet. Secs. 3 & 4,

Va. 13° 42' E

Ascend. along slope, West bank of
Leonard Cañon up stream41.44 Set a sandstone 20 x 10 x 7 ins. 15 ins
in the ground, for 1/4 Sec. Cor. marked
1/4 on W. face, and raised a mound
of stone 1 1/2 ft. high 2 ft. face.

Subdivisions.

Chs.	alongside. pits impracticable
48.20	Descend into Leonard Cañon
55.40	Leonard Cañon 50 lks. wide runs. N.E., ^{ascd}
67.00	End of abrupt ascent.
69.00	Right bank Leonard Cañon trans. N.E. + SW
80.40	Gulch 10 lks. wide runs. N. by W.
80.74	Fir 20 ins diam. on line marked with 2 matches on N. + S. Sides
81.44	The Cor. to Secs. 3, 4, 9 & 10. Land very rough rocky & precipitous. Soil rocky, 5 th rate. Timber Scattering Pine & Oak. September 6, 1893.

From the Standard Cor.
to Secs. 32, & 33, herein before
described. I. run.
N 0° 2' W. bet. Secs. 32 & 33.

J. 13. N. R. 12. E.

ch.

Va. $13^{\circ}42'E$.In heavy Pine & Oak timber. ^{descend}3.00 Leonards. Cañon 50 lks wide runs. N.W. ^{ascend}

10.00 Top of opposite bank trans. N.W. to S.E.

33.45 Pine 22 ins. diam. on line marked with 2 notches on N.W. sides

34.40 Bank trans N.N.E. & S.S.W. descend

37.20 Enter bottom

37.70 Recross Cañon 40 lks. wide runs. N.N.E.

39.90 Leave bottom & ascend

40.00 Set a sandstone $16 \times 11 \times 5$ ins. 11 ins in the ground. for $\frac{1}{4}$ Sec. Cr. marked $\frac{1}{4}$ on W. face. where a Pine 6 ins. diam. bears $N70^{\circ}E$ 96 lks. dist. marked $\frac{1}{4}$ S.B.T. A Pine 22 ins. diam. bears $N89^{\circ}W$ 100. lks dist. marked $\frac{1}{4}$ S.B.T.47.00 Recross. Cañon 40 lks. wide runs. N.N.W. ^{ascend}

53.50 Bank trans. N.N.W. & S.S.E.

Subdivisions.

chs.	
70.50	Bank trans. N.N.E. + S.S.W. descend
73.00	Ente bottom.
73.50	Reeras Cañon 50 lks. wide N by E.
74.50	Leard bottom + ascend
80.00	Set a Sandstone 18x10x4 ins. 13 ins. in the ground. for. Cor. to Secs. 28. 29. 32 & 33. marked with 12 match on and 4 matches on E. edges. whence A Pine 12 ins. diam. trans. N 7° E 163 lks. dist. marked T. 13, N, R. 12, E, S. 28. B. 9. A Pine 4 ins. diam. trans. S 12° E 156 lks. dist. marked T. 13, N, R. 12, E, S 33. B. 9. A Pine 26 ins. diam. trans. S 38° W 31 lks. dist. marked T. 13, N, R. 12, E, S. 32 B. 9. A Pine 6 ins. diam. trans. N 33° W 107 lks. dist. marked

T. 13. N. R. 12. E.

BOOK

127

T. 13. N. R. 12. E. S. 29 B. 1.

Land rough & broken.

Soil stony 4th rate.

Timber Pine & Oak. 80 chs.

~~Indexed, Book~~
Concluded, Book 125

BOOK 127