

BOOK 128

T 13 N R 13 E

No-128

BOOK 128

Subdivisions

4-671

128

FIELD NOTES

GENERAL LAND OFFICE

Sp. 13 N. R 13 E.

No-128

Field Notes.
of the Survey of the
Subdivision Lines
of
Township 13. N. Range 13. East.
of the
Gila & Salt River Base
And Meridian.
in the
Territory of Arizona
as surveyed by
Daniel Drummond
U.S. Deputy Surveyor
Under his Contract No. 28.
Dated February 21. 1893.
Survey Commenced. Sept. 14. 1893
Survey Completed. Oct. 13. 1893

(4-674.)

Township 13. N. R. 13. E.

Index for Books 128 and 129

6	113.	5	88.	4	73.	3	57.	2	40.	1
111.	109.		87		71.		55		38.	
7	107.	8	85.	9	69.	10	53.	11	36.	12
106.	104		83.		67.		52		34	
18	102.	17	82.	16	65	15	50.	14	32.	13
100.	98.		80		64		48		30.	
19	96.	20	78	21	62.	22	46	23	28.	24
94.	92.		76		60		44		26.	
30	90.	29	74	28	58.	27	42	26	24.	25
23.	9		15		12		9		4	
31	21.	32	17	33	14.	34	10.	35	7.	36

Subdivisions S. 13, N. R. 13, E.

I now proceed to the Cor. to Secs. 25, 30, 31 & 36. Sp. 13, N. R. 12 & 13, E. on the 3^d Auxiliary Meridian East. — herein before described. —

At the above Cor. in Latitude $34^{\circ}29'30''$ N. Longitude $111^{\circ}0'W$, I observe Polaris at its Eastern Elongation, this evening, Sept. 14, 1893. at $7^{\text{h}}50^{\text{m}}$ P.M. mean Solar time, by my watch, which is correct, and find its magnetic bearing to be $N 12^{\circ}12' W$

N. End of needle	$12^{\circ}12' E$
Azimuth for Lat.	$1^{\circ}32' E$
The Sun is the Va.	$13^{\circ}44' E$

I lay off the azimuth to the West. and mark the true

Subdivisions T. 13, N. R. 13, E.

Meridian so determined by driving
a peg. 5.00 chs. N. of the Cor.

September 14. 1893.

I now proceed to run an
auxiliary base line, through
T. 13, N. R. 13, E. and connect
corresponding corners, on the
E. & W. boundary, of the town-
ship, in accordance with
my instructions, to counteract
the error, in the survey of
the third standard parallel
N. through this Range. —

Subdivisions.

At 7 a. m. Sept. 15, ~~1893~~ I find the magnetic bearing of the line established last night to be $N 13^{\circ} 44' W$. The variation is therefore $13^{\circ} 44' E$. —

I begin at the established Cor. to Secs. 25, 30, 31, & 36. Sp. 13, N. R. 12, & 13, E. I run due East on a random line. Va

Va. $13^{\circ} 44' E$

I set temporary half mile and mile Corners, at each 40 + 80 chains, and at 495, 70 chains I intersect the Range line (run by Phillip Coutzen M. A., Deputy Surveyor, under his Contract No 27) 75, 62 chs. due North of the Standard Cor. to Sp. 13, N. R. 13, & 14, E.

T. 13. N. R. 13. E.

At said intersection, Deputy U.S. Surveyor Phillip Cortzen established the Cor. to Secs. 25, 30, 31 & 36, Tps. 13, N. R. 13, & 14, E.

The Correction for the true line will be 15.70 chs. East. per mile and its Course will be due West.

September 15, 1893.

From the Cor. to Secs. 25, 30, 31, & 36, a Stone firmly set, and properly marked, and Witnessed, as the Cor. to Secs. 25, 30, 31 & 36, Tps. 13, N. R. 13 & 14, E. Thence I run

West, on a true line
bet. Secs. 25 & 36,
Va. $13^{\circ}44'$ E.

Subdivisions.

chs.	In heavy Pine & Oak timber
2.00	Bank bears. N. & S.
5.50	Gulch 20 lks wide runs N.
8.00	Opposite bank bears. N. & S.
18.00	Right bank of West Chevalier Canyon bears. N.E. & S.W. descend
26.30	Pine 12 ins. diam. on line marked with 2 matches on E. & W. sides
30.25	Enter bottom
34.00	Stream 70 lks. wide. runs N.E. ^{ward}
35.65	Leave bottom & ascend
39.40	Opposite bank bears. N.E. & S.W.
40.00	Set a Sand Stone 24x16x5 ins. 18 ins. in the ground. for $\frac{1}{4}$ Sec. Cor. marked $\frac{1}{4}$ on N. face. whence A Pine 6 ins. diam. bears N50°W 40 lks. dist. marked $\frac{1}{4}$ S. B.S. A Pine 4 ins. diam. bears. S78 $\frac{1}{2}$ °W 33 lks. dist. marked $\frac{1}{4}$ S. B.S.

T. 13. N. R. 13. E.

- chs.
46.45 Pine 24 ins. diam. on line marked
with 2 notches on E. & W. Sides
- 78.25 Pine 25 ins. diam. on line marked
with 2 notches on E. & W. Sides.
- 80.00 Set a Sandstone 17x9x7 ins. 12
ins. in the ground for Cor. to Secs.
25, 26, 35 & 36, marked with 1
notch on E. & S. edges, whence
Pine 15 ins. diam. bears,
N 21° E 26 lks. dist marked
T. 13. N. R. 13. E. S. 25 B. S.
- A Pine 18 ins. diam. bears,
S 42° E 35 lks. dist. marked
T. 13. N. R. 13. E. S. 36 B. S.
- A Pine 19 ins diam. bears,
S 63° W 58 lks. dist. marked
T. 13. N. R. 13. E. S. 35 B. S.
- A Pine 5 ins. diam bears,
N 18° W 16 lks. dist. marked

Subdivisions.

Chs. • T. 13. N. R. 13. E. S. 26 13. S.
 Land rough & broken.
 Soil generally 3^d rate.
 Timber Heavy Pine & Oak 80 chs

South. on a random line
 bet. Secs. 35 & 36.

Va. $13^{\circ}44'E$

40.00 Set. temporary $\frac{1}{4}$ Sec. Cor.

46.35 Int. 3^d Standard parallel, N.
 and S. boundary of Tp. at the
 Standard Cor. to Secs. 35 & 36.

Hereinbefore described

Thence I run North on a
 true line bet. Secs. 35 & 36

Va. $13^{\circ}44'E$

In Heavy Pine & Oak timber

25.50 Banks cross N.E. & S.W. corner.

J. 13. N. R. 13. E.

chs. 27.50	Gulch 20 lks. wide runs N.E. ^{ascend}
30.50	Opposite bank bears N.E. + S.W.
36.35	Set a sandstone 18x8x6 ins. 13 ins. in the ground, for $\frac{1}{4}$ Sec Cor. marked $\frac{1}{4}$ on W. face. whence A Pine 8 ins. diam. bears N88°E 29 lks. dist. marked $\frac{1}{4}$ S. B.S. A Pine 8 ins. diam. bears S85°W 33 lks. dist. marked $\frac{1}{4}$ S. B.S.
36.00	Bank bears S.E. + N.W. descend
37.60	Gulch. 20 lks. wide runs S.E.
40.00	Opposite bank bears N.W. + S.E.
54.35	Pine 16 ins. diam. on line marked with 2 notches on N. + S. sides
69.90	Pine 30 ins. diam. on line marked with 2 notches on N. + S. sides
76.35	The Cor. to Secs. 25, 26, 35, + 36. Land broken, Soil generally 3 ^d rate, Timber heavy Pine + Oak. 76.35 chs

Subdivisions.

West. lot. Secs. 26 & 35,

Ta. $13^{\circ}44'E$.

In heavy Pine & Oak timber

18.70 Pine 14 ins diam. on line. marked
with 2 matches on E. & W. sides

22.05 Pine 17 ins. diam. on line. marked
with 2 matches on E. & W. sides

40.00 Set a Sandstone $40 \times 15 \times 3$ ins 25
ins in the ground. for $\frac{1}{4}$ Sec. Cor.
marked $\frac{1}{4}$ on N. face. whence

A Pine 22 ins diam. bears $S81^{\circ}E$
23 lks. dist. marked $\frac{1}{4}$ S. B.S.

A Pine 20 ins. diam. bears $N15^{\circ}E$
79 lks. dist. marked $\frac{1}{4}$ S. B.S.

80.00 Set a Sandstone $18 \times 6 \times 8$ ins 13
ins. in the ground. for. Cor. to
Secs. 26, 27, 34 & 35, marked
with 2 matches on E. and 1 match
on S. edges. Whence

T. 13. N. R. 13. E.

Chs.

A Pine 6 ins. diam. trees.

N 51° E 59 lks. dist. marked

T. 13. N. R. 13. E. S. 26. B. T.

A Pine 6 ins. diam. trees.

S 57° E 80 lks. dist. marked

T. 13. N. R. 13. E. S. 35. B. T.

A Pine 14 ins. diam. trees.

S 30° W 72 lks. dist. marked

T. 13. N. R. 13. E. S. 34 B. T.

A Pine 30 ins. diam. trees.

N 25° W 34 lks. dist. marked

T. 13. N. R. 13. E. S. 27 B. T.

Land level

Soil Sandy 2^d Mate

Timber Heavy Pine 80 chs.

South on a random line
bet. Secs. 34 & 35.

Subdivisions.

Yu. $13^{\circ}44'E$

- 40.00 Set temporary $\frac{1}{4}$ Sec Cor.
 77.10 Int. S. boundary of Sp 12 lks.
 N. of Standard Cor. to Secs. 34 & 35
 hereinbefore described. Thence Iron
 N $0^{\circ}5'W$ on a true line,
 bet. Secs. 34 & 35.

Yu. $13^{\circ}44'E$.

In heavy Pine timber

- 37.10 Set a Sandstone $16 \times 10 \times 5$ ins 11 ins
 in the ground for $\frac{1}{4}$ Sec. Cor.
 marked $\frac{1}{4}$ on W. face. Whence a
 Pine 5 ins. diam. bears $S70^{\circ}E$ 37
 lks. dist. marked $\frac{1}{4}$ S. B. S. -
 A Pine 18 ins. diam bears $N45^{\circ}W$
 45 lks. dist. marked $\frac{1}{4}$ S B. S.
 60.40 Pine 16 ins. diam. on line marked
 with 2 matches on N. & S. sides
 77.10 The Cor. to Secs. 26. 27. 34 & 35.

J. 13. N. R. 13. E.

Land. level

Soil. Sandy 2^d rate

Timber, heavy Pine 77.10 chs.

September. 16. 1893.

Nest. bet. Secs. 27 X 34.

Va. 13° 44' E.

- 40.00 Set. a Sandstone 18 X 12 X 4 ins. 13 ins
in the ground. for 1/4 Sec. Cr. marked
1/4 on N. face. Whence A Pine 12 ins.
diam. bears N 51° E 80 lks. dist.
marked 1/4 S. B. S. — A Pine 5 ins diam.
bears S 77° E 43 lks. dist. marked
1/4 S. B. S. —
- 41.15 Pine 50 ins. diam. on line marked
with 2 notches on E. & W. Sides
- 42.60 Gulch 10 lks wide runs Northward
- 64.80 Old Wagon Road bears N. N. E. & S. S. W

Subdivisions.

From Toronto Basin to Winslow.

80.00 Set a Sandstone 20x10x6 ins. 15 ins
in the ground. for. Cor. to Seas. 27, 28
33, & 34. Marked with 3 notches on
E. and 1 notch on S. edges. Whence
A Pine 14 ins. diam. Trans.

N 88° E 150 lks. dist. marked
T. 13. N. R. 13. E. S. 27 B. T.

A Pine 40 ins. diam. Trans.

S 25° E 31 lks. dist. marked
T. 13. N. R. 13. E. S. 34, B. T.

A Pine 18 ins. diam. Trans.

S 30° W 71 lks. dist. marked
T. 13. N. R. 13. E. S. 33 B. T.

A Pine 17 ins. diam. Trans

N 31° W 60 lks. dist. marked
T. 13. N. R. 13. E. S. 28 B. T.

Land rolling

Soil. gravelly & sandy 2^d + 3^d rate

Timber heavy Pine. 80 cts.

T. 13. N. R. 13. E.

- Chs. $S 0^{\circ} 5' E$ on a random line
bet. Secs. 33 & 34.
Va $13^{\circ} 44' E$
- 40.00 Set. temporary $\frac{1}{4}$ Sec. Cor.
- 77.80 Int. S. boundary of Sp. 6 lks. E.
of Standard Cor. to Secs. 33 & 34.
heretofore described. Thence Iron.
 $N 0^{\circ} 2' W$ on a true line
bet. Secs. 33 & 34.
Va $13^{\circ} 44' E$
- In heavy Pine timber
- 14.80 Pine 24 ins. diam. on line marked
with 2 notches on N. & S. Sides
- 35.00 Enter bottom brass. N.N.E. + S.S.W.
- 36.90 Wagon Road to Winslow brass. N.N.E. + S.S.W.
- 37.80 Set. a sandstone $16 \times 10 \times 8$ ins 11 ins in
the ground. for. $\frac{1}{4}$ Sec. Cor. marked
 $\frac{1}{4}$ on W. face. whence A Pine 10 ins
diam. brass. $S 69^{\circ} E$ 16 lks. dist marked

Subdivisions.

Chs.	$\frac{1}{4}$ S. B. 7. - A Pine 14 ins. diam. bears
	S 17° W 53 lks. dist. marked $\frac{1}{4}$ S. B. 7.
56.30	Enter Stream
58.10	Leave Stream runs N. N. E.
65.70	Stream 20 lks. wide runs N. W.
65.90	Leave bottom & ascend
77.80	The Cor. to Secs. 27, 28, 33 & 34.
	Land nearly level
	Soil sandy loam 1 st rate
	Timber Pine 77.80. Chs.

West. bot. Secs. 28 & 33.

Run. $13^{\circ} 44' E$

In heavy Pine timber descend

17.00	Bank bears N. W. & S. E. descend
21.40	Enter bottom
21.70	Stream 30 lks. wide flows N. W.
22.30	Trail bears N. W. & S. E.

J. 13. N. R. 13. E.

- chs.
23.50 Leaves bottom & ascend
- 26.00 Ridge trans. N. & S. descend
- 29.90 Gulch. 10 lks wide runs. N.E.
- 40.00 Set a Sandstone 24x10x5 ins. 18 ins
in the ground. for. $\frac{1}{4}$ Rec. Cor. marked
 $\frac{1}{4}$ on N. face. Whence A Pine. 7 ins.
diam. trans. N 1° E 29 lks. dist. mark
 $\frac{1}{4}$ S. B.S. - A_{Pine} 10 ins. diam. trans.
S 53° W 47 lks. dist. marked $\frac{1}{4}$ S. B.S.
- 55.00 Bank trans. N.N.E. & S.S.W descend
- 60.00 Entire bottom
- 62.40 Gulch 10 lks. wide runs. N.N.E.
- 64.00 Leaves bottom & ascend
- 67.00 Opposite bank. trans. N.N.E. & S.S.W.
- 80.00 Set a Sandstone 18x12x10 ins. 13 ins
in the ground. for. Cor. to Secs. 28, 29
32. & 33. marked with 4 notches on E.
and 1 notch on S. edges. Whence
A Pine 8 ins. diam. trans.

Subdivisions.

N 21° E 70 lks. dist, marked
I. 13, N. R. 13. E. S. 28 B. J.

A Pine 12 ins. diam. trees.

S 29° E 35 lks. dist, marked
I. 13, N. R. 13. E. S. 33 B. J.

A Pine 10 ins. diam. trees.

S 37° W. 27 lks. dist, marked
I. 13, N. R. 13. E. S. 32. B. J.

A Pine 7 ins. diam. trees.

N 50° W 11 lks. dist, marked,
I. 13, N. R. 13. E. S. 29 B. J.

Land rough & broken

Sail generally, 3^d rate

Timber, Heavy Pine 80, cho.

S 0° 2' E on a random line
bet Secs. 32 & 33.

Va. 13° 44' E

T. 13. N. R. 13. E.

- 40.00 Set. temporary $\frac{1}{4}$ Sec. Cor.
- 76.50 Int. S. boundary of Tp. at the
Standard Cor. to Secs. 32 & 33,
Hereinafter described. Thence Iron
 $N 0^{\circ} 2' W.$ on a true line
bet. Secs. 32 & 33.
Var. $13^{\circ} 44' E.$
In heavy Pine timber.
- 36.90 Pine 18 ins. diam. on line marked
with 2 notches on N. & S. Sides
- 38.50 Set. a Sandstone $16 \times 12 \times 5$ ins. 11
ins. in the ground. for $\frac{1}{4}$ Sec. Cor.
marked $\frac{1}{4}$ on W. face. whence a
Pine 8 ins. diam. bears. $N 82^{\circ} E 33$.
lks. dist. marked $\frac{1}{4}$ S. B. S. —
A Pine 8 ins. diam. bears. $S 75^{\circ} W$
40 lks. dist. marked $\frac{1}{4}$ S. B. S.
- 42.30 Pine 14 ins. diam. on line marked
with 2 notches on N. & S. Sides

Subdivisions.

- chs. 42.80 Pine 16 ins. diam. on line. marked with 2 notches on N. & S. Sides
 - 51.30 Bank trans. N.E. & S.W. descend
 - 54.00 Enter bottom
 - 56.30 Gulch 10 lks wide runs N.E.
 - 59.30 Leave bottom & ascend
 - 61.40 Opposite bank trans. N.E. & S.W.
 - 78.50 The Cr. to Secs 28, 29, 32 & 33. Land. Nearly level. Soil. Sandy 2^d rate. Timber. Heavy Pine 78.50. Chs.
- September 18. 1893.

Next bet. ^{secs.} 29 & 32.
 Va. 13° 44' E

SW heavy Pine timber

- 26.45 Gulch 10 lks. wide runs N.N.E.
- 32.40 Trail trans. N.E. & S.W.

S. 13. N. R. 13. E.

- chs.
37.25 Pipe 20 in. diam. on line marked with 2 notches on E. & W. sides
- 40.00 Set a Sandstone 18x12x5 ins. 18 in. in the ground. for $\frac{1}{4}$ Sec Cr. marked $\frac{1}{4}$ on N. face. Whence a Pipe 10 in. diam. bears S42°E 61 lks. dist. marked $\frac{1}{4}$ S. B. I. - A Pipe 10 in. diam. bears N14°W 39 lks. dist. marked $\frac{1}{4}$ S. B. I. -
- 46.00 Right bank. Willow Cañon bears N. N. E. & S. S. W. descend
- 53.10 Stream 50 lks. wide runs ^{upward} N. N. E.
- 58.60 Opposite bank. bears N. N. E. & S. S. W.
- 77.85 Gulch 10 lks. wide runs N. E.
- 80.00 Set a Sandstone 20x14x4 ins 15 in. in the ground. for Cr. to Secs. 29, 30, 31 & 32. marked with 5 notches on E. and 1 notch on S. edges. Whence.

Subdivisions

Chs. A Pine 10 ins. diam. trees
 $N 24^{\circ} E$ 62 lks. dist. marked
 T. 13, N. R. 13, E. S. 29, B. 1.

A Pine 30 ins. diam. trees,
 $S 62^{\circ} E$ 103 lks. dist. marked,
 T. 13, N. R. 13, E. S. 32, B. 1.

A Pine 28 ins. diam. trees,
 $S 75^{\circ} W$ 34 lks. dist. marked
 T. 13, N. R. 13, E. S. 31, B. 1.

A Pine 5 ins. diam. trees,
 $N 55^{\circ} W$ 80 lks. dist. marked
 T. 13, N. R. 13, E. S. 30, B. 1.

Land, rough & broken.

Soil, gravelly. 3^d Mate.

Timber, heavy Pine 80 chs.

$S 0^{\circ} 2' E$, on a random line
 bet. Secs. 31 & 32.

T. 13. N. R. 13. E.

chs.

Va. 13°44'E

- 40.00 Set. temporary 1/4 Sec. Cor.
 79.22 Int. S. boundary of Sp. 5 lks. E.
 of the ^{Standard} Cor. to Secs. 31 & 32.
 Hereinafter described. Thence I run
 North. on a true line.
 bet. Secs. 31 & 32.

Va. 13°44'E

In heavy Pine timber.

- 36.10 Gulch 10 lks. wide runs N.E.
 39.22 Set. a Sandstone 28x18x6 ins. 20
 ins. in the ground. for. 1/4 Sec. Cor.
 marked 1/4 on N. face. where a
 Pine 18 ins. diam. bears S32°E
 66 lks. dist. marked 1/4 S. B.T.
 A Pine 5 ins. diam. bears S88°W
 72 lks. dist. marked 1/4 S. B.T.
 52.07 Pine 30 ins. diam. on line. marked.
 with 2 notches on N. & S. Sides

Subdivisions.

chs.	
73.80	Gulch 10 lks. wide runs N.E.
79.22	The Cor. to Secs. 29, 30, 31 & 32 Land, nearly level. Soil sandy 2 ^d rate. Timber heavy Pine. 79.22 chs.

West bet. Secs. 30. and 31.

Va. 13° 44' E

In heavy Pine timber

14.70	Bank bears N.E. & S.W. descend
20.50	Entire bottom
21.60	Gulch 30 lks. wide runs N. then N.E.
22.50	Level bottom & ascend
31.70	Opposite bank bears N.W.
38.00	Bank bears S.E. & N.W. descend
38.08	Pine 24 ins diam. on line marked with 2 matches on E. & W. sides
40.00	Set a sandstone 24 x 18 x 5 ins 18 in in ground for 1/4 Sec Cor. marked 1/4 on N. side. where a

T. 13. N. R. 13. E.

chs.	Pine 8 ins diam, bears. N 23° E 45 lbs. dist. 2 1/4 d. 1/4 S. B. 1.
42.30	Pine 4 ins diam. bears. S 49° E 48 lbs. dist. 2 1/4 d. 1/4 S. B. 1.
62.20	Gulch 20 lks. wide, runs. S. E.
68.00	Banks bears. N. E. & S. W. descend
69.50	Gulch 20 lks. wide runs. N. E.
95.70	Opposite bank bears. N. E. & S. W.
	The Cor. to Secs. 25, 30, 31 & 36.
	Land rough & broken.
	Soil. Stony. 4 th rate.
	Timber. Heavy Pine. 95.70 chs.
	September 19. 1893.

I now return to the Cor.
to Secs. 25, 26, 35, & 36, as
recently established by me.
Thence I run.

N 0° 1' W. bet. Secs. 25 & 26
Va 13° 44' E

In Heavy Pine & Oak timber
14.00 Enta bottom.

Subdivisions.

- | | |
|-------|--|
| chs. | |
| 17.50 | Trail brass, N.W. + S.E. |
| 18.25 | Pine 22 ins. diam. one line marked with 2 notches on N. + S. sides |
| 20.20 | Gulch 20 lks. wide runs S.E. ^{ascend} |
| 28.50 | Opposite bank brass, N.W. + S.E. |
| 40.00 | Set a sandstone 22x16x7 ins. 16 ins in the ground. for. $\frac{1}{4}$ Sec. Cor. marked $\frac{1}{4}$ on W. face. whence A Pine 18 ins diam. brass. S61°W 94 lks. dist. marked $\frac{1}{4}$ S. B.L. - A Pine 18 ins. diam. brass N29°E 77 lks. dist marked $\frac{1}{4}$ S. B.L. - |
| 48.90 | Trail brass, N.W. + S.E. |
| 80.00 | Set a sandstone 20x11x8, ins. 15 ins in the ground. for. Cor. to Secs. 23, 24 25x26. marked with 2 notches on S. and 1 notch on E. edges whence A Pine 5 ins. diam. brass, N43°E 40 lks. dist. marked |

T. 13. N. R. 13. E.

Chs.

T. 13. N. R. 13. E. S. 24 B.T.

A Pine 5 ins. diam. bears

S 22° E 47 lks. dist. marked

T. 13. N. R. 13. E. S. 25. B.T. -

A double Pine 30 ins. diam. bears

S 38° W 86 lks. dist. marked

T. 13. N. R. 13. E. S. 26. B.T.

A Pine 16 ins. diam. bears.

N 22° W 39 lks. dist. marked

T. 13. N. R. 13. E. S. 23 B.T.

Land, rolling.

Soil, gravelly 2^d rate.

Timber Heavy Pine. 50 chains

East, on a random line.

bet. Secs. 24 & 25.

Ta 13° 44' E

In heavy Pine timber.

Subdivisions.

chs.	
40.00	Set temporary $\frac{1}{4}$ Sec. Cor.
80.00	Int. E. boundary of Sp. at Cor. to Secs. 19, 24, 25 & 30, as recently Established by Dep. U. S. Sur. Cortzen. Thence I run, West, on a true line. bet. Secs. 24 & 25, Pa. $13^{\circ}44'E$. In heavy Pine timber. ^{ascend}
2.80	W. bank W. fork. Cheylon brans. N. & S.
28.00	Bank brans. N. E. & S. W. descend
29.60	Pine 20 ins. diam. on line marked with 2 notches on E. & W. sides
31.35	Gulch 10 lks wide runs N. E. ascend
38.10	Opposite bank brans. N. E. & S. W.
40.00	Set a sandstone $16 \times 14 \times 5$ ins. 11 ins in the ground, for $\frac{1}{4}$ Sec. Cor. mark $\frac{1}{4}$ on N. face. whence a Pine 14 ins diam. brans $N1^{\circ}E$ 22 lks. dist.

J. 13. N. R. 13. E.

chs.	marked $\frac{1}{4}$ S. B. Y. - A Pine 5 ins. diam. trans. $S 38^{\circ} W$ 55 lks. dist. marked $\frac{1}{4}$ S. B. Y.
46.00	Bank trans. N.E. + S.W. descend
49.80	Gulch 10 lks. wide runs N.E. ascend
59.00	opposite bank trans N.E. + S.W.
73.00	Bank trans. N.E. + S.W. descend
80.00	The Cor. to Secs. 23, 24, 25 & 26. Land, rolling. Soil, gravelly. 2 ^d rate. Timber heavy Pine + Oak. 80 chains

No 1. W. bet. Secs. 23, & 24.
Va. $13^{\circ} 44' E$.

	In heavy Pine + Oak timber ^{ascend}
4.00	Gulch 20 lks wide runs N.N.E. ^{ascend}
10.27	Pine 22 ins. diam. on line marked with 2 notches on N + S. Sides
16.00	Bank, trans. N.N.E. + S. S.W.

Subdivisions.

- 39.80 Bank bears, N.E. & S.W. descend
- 40.00 Sandstone 4x3x2 ft. above ground in place
which I mark with cross thus + $\frac{1}{4}$
on W. face. Whence A Pine 18 ins
diam. bears. S60°W 22 lks. dist. marked
 $\frac{1}{4}$ S. B.S. - A Pine 20 ins. diam bears
S71°E 72 lks. dist. marked $\frac{1}{4}$ S. B.S.
- 50.15 Enter bottom
- 51.45 Gulch 10 lks wide runs N.E., ascend
- 51.95 Trail bears, N.E. & S.W.
- 52.50 Leave bottom & ascend
- 57.00 Opposite bank bears, N.E. & S.W.
- 73.70 Bank bears, N.E. & S.W. descend
- 80.00 ^{Set a} Sandstone 22x10x10 ins 16 ins. in
the ground. for. Cor. to Secs. 13, 14, 23 & 24
marked with 3 notches on S. and 1 notch
on E. edges. Whence
A Pine 20 ins. diam. bears
N67°E 8 lks. dist. marked

T. 13. N. R. 13. E.

chs. T. 13. N. R. 13. E. S. 13 B. T.

A Pine 5 ins. diam. trans
 S19°E 68 lks. dist. marked
 T. 13. N. R. 13. E. S. 24. B. T.

A Pine 22 ins. diam. trans.
 S73°W 9 lks. dist. marked
 T. 13. N. R. 13. E. S. 23 B. T.

A Pine 18 ins. diam. trans
 N60°W 64 lks. dist. marked
 T. 13. N. R. 13. E. S. 14. B. T.

Land, rolling.

Soil, gravelly. 3^d rate.

Timber heavy Pine 80 chams.

 East. on a random line

bet. Secs. 13 & 24.

Va. 13°44'E

40.00 bet. temporary 1/4 Sec. Cor.

Subdivisions.

- chs.
80.00 Int. E. boundary of Sp. at Cr.
to Secs. 13, 18, 19 & 24. A Stone
firmly set and properly marked
and witnessed. Thence I run
West on a true line
bet. Secs. 13 & 24,
Va $13^{\circ}44'E$.
In heavy Pine timber.
- 40.00 Set a Sandstone $18 \times 12 \times 5$ ins. 13.
ins. in the ground for $\frac{1}{4}$ Sec. Cr.
marked $\frac{1}{4}$ on N. face whence a
Pine 8 ins. diam. bears $S 10^{\circ}W 41$
lks. dist. Marked $\frac{1}{4}$ S. B.G. - A Pine
16 ins. diam. bears $N 52^{\circ}W 38$ lks.
dist. marked $\frac{1}{4}$ S. B.G.
- 48.65 Bank bears. N.E. & S.W. ascend
- 55.10 Entu bottom
- 55.80 Gulch 10 lks. wide runs N.E. ascend
- 56.00 Trail. bears. N.E. & S.W.

T. 13. N. R. 13. E.

chs.	
56.20	Leave bottom + ascend
64.50	Opposite bank trans. N.E. + S.W.
76.50	Banks trans N.E. + S.W. descend
80.00	The Cor. to Secs. 13, 14, 23 & 24.
	Land. rolling.
	Soil. gravelly 2 ^d rate.
	Timber. heavy Pine 80 chains

N 0° 1' W. bet. Secs. 13 & 14.

Va 13° 44' E

In heavy Pine timber descend

2.70	Enter bottom
3.10	Gulch 10 lks. wide runs N.E.
3.50	Trail trans. N.E. + S.W.
3.60	Leave bottom + ascend
10.00	Ridge trans. N.E. + S.W. descend
12.40	Gulch 20 lks. wide runs N.E. ascend
15.40	Pine 22 ins. diam. on line marked

Subdivisions.

- chs. with 2 matches on N.T.S. sides
- 19.00 Bank trans. N.E. & S.W.
- 40.00 Set a sandstone 18x12x4 ins. 13 ins
in the ground. for. $\frac{1}{4}$ Sec. Cor; marked
 $\frac{1}{4}$ on W. face. whence A Pine 5 ins
diam. trans. N 23° W. 8 lks. dist.
marked $\frac{1}{4}$ S. B.S. - A Pine 8 ins.
diam. trans. S 71° E. 24 lks.
dist. marked $\frac{1}{4}$ S. P.S. -
- 51.40 Gulch 10 lks wide trans. East ^{ward}
- 53.50 Bank trans. E & W
- 75.60 Wagon Road to Wainslow ls. N.N.E. & S.S.W.
- 80.00 Set a sandstone 18x10x5 ins. 13 ins
in the ground. for. Cor. to Secs. 11, 12, 13
& 14. Marked with 4 matches on S. and
1 notch on E. edges. whence
A Pine 5 ins. diam. trans
N 2° E. 15 lks. dist. marked
T 13, N, R 13, E, S 12, B.S.

J. 13. N. R. 13. E.

Chs. A Pine 5 ins. diam. brass

S 41° E 19 lks. dist. marked

J. 13. N. R. 13. E. S. 13. B. 1.

A Pine 5 ins. diam. brass.

S 39° W 15 lks. dist. marked

J. 13. N. R. 13. E. S. 14. B. 1. -

A Pine 6 ins. diam. brass.

N 74° W 13 lks. dist. marked

J. 13. N. R. 13. E. S. 11. B. 1. -

Land, rolling.

Soil, gravelly 2^d rate.

Timber heavy Pine 80 chains.

October 2, 1893.

East on a random line

bet. Secs. 12 & 13. -

Ta. 13° 44' E

40.00 Set temporary 1/4 Sec Cor.

Subdivisions.

80.36 Int. E boundary of Sp. 12 lks. N.
of Cor. to Secs. 7, 12, 13 & 18. a
stone firmly set, and properly
marked, and witnessed. Thence I run
N 89° 55' W on a true line
bet. Secs. 12 & 13.

Va. 13° 44' E.

In heavy Pine timber

26.80 Gulch. 20 lks. wide runs N.E.

27.05 Trail bears N.E. & S.W.

40.18 Set a sandstone. 18 x 10 x 6 ins. 13 ins. in
the ground. for 1/4 Sec. Cor. marked
1/4 on N. face. Whence A Pine 14 ins
diam. bears N 25° E. 101 lks. dist.
marked 1/4 S. B. S. - A Pine 12 ins
diam. bears S 12° W. 25 lks. dist.
marked 1/4 S. B. S. -

41.70 Bank bears N.E. & S.W. descend

46.20 Into bottom

J. 13. N. R. 13. E.

46.70	Chs. Gulch 15 lks. wide runs N.E.
47.00	Trail bears N.E. + S.W.
47.50	Leaves bottom + ascend
53.60	Pine 36 ins. diam. see on line marked with 2 notches on E. + W. sides.
63.70	Opposite bank bears N.E. + S.W.
74.50	Wagon Road to Winslow bears N.N.E. + S.S.W.
80.36	The Cor. to Secs. 11, 12, 13 & 14.
	✓ Land, rolling
	Soil. gravelly 2 ^d + 3 ^d rate.
	Timber heavy Pine 80. ³⁶ chains

N 0° 1' W. bet. Secs. 11 & 12,

Va. 13° 44' E

In heavy Pine timber

16.40	Pine 30 ins. diam. on line, marked with 2 notches on N. + S. sides
24.00	Entire Gulch bears N.E.

Subdivisions.

chs. 25.50	Leave gulch. runs. N.E.
27.80	Trail trans. N.E. & S.W.
30.50	Leave bottom & ascend
31.50	Ridge. trans. N.E. & S.W. descend
33.20	Gulch 10 lks wide runs. N.E.
40.00	Set a Sandstone 18x10x4 ins. 13 ins in the ground. for $\frac{1}{4}$ Sec. Cor. mark $\frac{1}{4}$ on W. face. Whence A Pine 15 ins. diam. trans S 84° W. 86 lks. dist marked $\frac{1}{4}$ S. B.T. - A Pine 14 ins diam trans S 21° E. 37 lks. dist. marked $\frac{1}{4}$ S. B.T. -
40.50	opposite Bank trans. N.E. & S.W.
80.00	Set a Sandstone 18x10x4 ins. 18 ins. in the ground. for Cor. to Secs. 1, 2, 11 & 12, marked with 5 notches on S. & 1 notch on E. edges. whence. A Pine 10 ins. diam. trans. N 40° E 40 lks. dist. marked

T. 13. N. R. 13. E.

Chs. T. 13. N. R. 13. E. S. 1. B. 1.

A Pine 6 ins. diam. trans.

S 13° E 18 lks. dist. marked

T. 13. N. R. 13. E. S. 12 B. 1. -

A Pine 11 ins. diam. trans.

S 79° W 40 lks. dist. marked

T. 13. N. R. 13. E. S. 11 B. 1. -

A Pine 8 ins. diam. trans.

N 30° W 13 lks. dist. marked

T. 13. N. R. 13. E. S. 2. B. 1.

Land. rolling.

Soil. gravelly 2^d rate.

Timber. heavy Pine 80 chains.

S 89° 55' E on a random line.

bet. Secs. 14, 12.

Va. 13° 44' E

40.00 Sub. temporary 1/4 Sec. Cor.

Subdivisions.

- | chs. | |
|-------|--|
| 80.26 | Ent. E. boundary of Sp. 12 lks. N. of Cor. to Secs. 1, 6, 7 & 12. A Stone firmly set and properly marked and witnessed. Thence I run $N 89^{\circ} 50' W$. on a true line, bet. Secs. 1 & 12, $\gamma a. 13^{\circ} 44' E$. |
| | In heavy Pine timber |
| 19.50 | Wagon Road to Winslow brans. NNE. & SSW. |
| 21.00 | Trail, parallel to Road |
| 36.50 | Bank brans NE. & SW. descend |
| 38.60 | Gulch 10 lks. wide runs NE. ^{ascend} |
| 40.13 | Set a Sandstone $16 \times 10 \times 4$ ins. 11 ins in the ground. for $\frac{1}{4}$ Sec. Cor. marked $\frac{1}{4}$ on N. face where a Pine 8 ins. diam. brans. $S 10^{\circ} E$ 43 lks. dist. marked $\frac{1}{4}$ A. B. S. A Pine 9 ins. diam. brans. $N 20^{\circ} E$ 56 lks. dist. marked $\frac{1}{4}$ A. B. S. |

T. 13. N. R. 13. E.

- 47.80 Divide trans. N.E. & S.W. descend
 48.15 Pine 24 ins. diam. on line marked
 with 2 notches on E. & W. sides
 55.10 Gulch 15 lks. wide runs N.E. ascend
 59.00 Bank opposite trans. N.E. & S.W.
 80.26 The Cor. to Sec. 1, 2, 11 & 12.
 Land. broken.
 Soil. Stony & gravelly. 2^d & 3^d rate.
 Timber heavy Pine. 80.26 chs.
-

N 0° 1' W. on a random line
 bet. Secs. 1 & 2,
 Va. 13° 44' E

- 40.00 Sect. temporary 1/4 Sec. Cor.
 80.10 Int. N. boundary of Tp. at. Cor. to
 Secs. 1, 2, 35 & 36. as recently
 established, by me Thence from
 S 0° 1' E on a true line

Subdivisions.

- chs. bet. Secs. 1 & 2.
Va 13°44'E.
- In heavy Pine timber
- 6.40 Pine 16 ins diam. on line marked with ² notches on N. & S. Sides
- 6.50 Pine 14 ins. diam. on line. marked with 2 notches on N. & S. Sides
- 40.10 Set a Sandstone 20x12x6 ins. 15 ins in the ground. for $\frac{1}{4}$ Sec Cor. marked $\frac{1}{4}$ on W face. whence A Pine 10 ins. diam. bears S32°W 10 lks. dist. marked $\frac{1}{4}$ S. B. S. - A Pine 8 ins. diam bears N61°E 4 lks. dist. marked $\frac{1}{4}$ S. B. S. -
- 50.50 Enter bottom
- 50.65 Gulch 10 lks. wide runs N.E. ^{ascend}
- 51.80 Trail bears N.E. & S.W.
- 53.50 Leave bottom & ascend
- 55.00 S.E. Bank bears N.E. & S.W.

T. 13. N. R. 13. E.

^{chs}
 80.10 The Cor. to Secs. 1, 2, 11, & 12. —
 Land, Nearly level,
 Soil, Sandy & gravelly 2^d rate.
 Timber Heavy Pine 80.10 chains.
 October 3, 1893.

From the Cor. to Secs. 26, 27, 34 & 35
 as recently established by me. Iron.
 N 0° 1' W. bet. Secs. 26 & 27,
 Va. 13° 44' E.

In heavy Pine timber

25.50 Trail bars. N.W. + S.E.
 39.00 Bank bars. N.W. + S.E. descend
 40.00 Set a sandstone 18 X 10 X 6 ins., 13.
 ins. in the ground, for $\frac{1}{4}$ Sec Cor
 marked $\frac{1}{4}$ on W. face. whence a
 Pine 18 ins. diam. bars S 69° W
 26 lks. dist. marked $\frac{1}{4}$ S. B. T.

Subdivisions.

chs.	A Pine 8 ins. diam. bears S53°E 81 lks. dist. Marked 1/4 S. B.T. -
42.50	Enter bottom
42.90	Pine 24 ins. diam. on line. Marked with 2 notches on N. & S. sides
44.15	Trail bears N.W. & S.E.
44.40	Gulch 20 lks. wide, runs N.W. ^{ascend}
47.60	Leave bottom & ascend
49.20	Descend
56.50	Enter bottom
57.60	Recross gulch 20 lks. wide runs N.E.
60.00	Leave bottom & ascend
78.50	Bank bears N.N.E. & S.S.W.
80.00	Set a Sandstone 24x14x8 ins. 18 ins in the ground. for Cor. to Secs. 22, 23, 26 & 27. Marked. with 2 notches on S. & E. edges. Whence A Pine 9 ins. diam. bears N74°E 45 lks. dist. marked

T. 13. N. R. 13. E.

Chs. T. 13. N. R. 13. E. S. 23. B.T. -
 A Pine 12 ins. diam. bears
 S 25° E 131 lks. dist. marked
 T. 13. N. R. 13. E. S. 26. B.T.
 A Pine 15 ins. diam. bears.
 S 8° W 57 lks. dist. marked
 T. 13. N. R. 13. E. S. 27. B.T.
 A Pine 6 ins. diam. bears.
 N 58° W 142 lks. dist. marked
 T. 13. N. R. 13. E. S. 22 B.T.
 Land. rolling.
 Soil. gravelly 3^d rate.
 Timber Heavy Pine 80 chs.

East. on a random line.

bet. Secs. 23 & 26.

Pa. 13° 44' E.

40.00 Set temporary 1/4 Sec Cor.

Subdivisions.

- 79.92 Int. N.T.S. line at Cor. to Secs. 23, 24 & 26. Thence I run West on a true line bet. Secs. 23 & 26. Pa. $13^{\circ}44'E$
- 1.10 In heavy Pine timber. descend Gulch 20 lks. wide runs N.E. ^{ascend}
- 31.80 Bank bears N.T.S., descend
- 33.20 Enter bottom
- 34.20 Gulch 10 lks. wide. runs Northerly
- 35.00 Leave bottom & ascend
- 37.55 Pine 30 ins. diam. on line marked with 2 notches on E. & W. sides
- 39.96 Set a sandstone $16 \times 10 \times 6$ ins 11 ins in the ground for $\frac{1}{4}$ Sec Cor. marked $\frac{1}{4}$ on N. face. Whence a Pine 4 ins diam. bears $S58^{\circ}E, 5$ lks. dist. marked $\frac{1}{4}$ S. B.T. - A Pine 5 ins diam. bears $N48^{\circ}W$

T. 13. N. R. 13. E.

- chs. 8 lks. dist. marked 1/4 S. B. I.
- 59.00 Bank bars N.E. + S.W. descend
- 63.00 Enter bottom
- 65.00 Gulch 20 lks. wide run. N.E.
- 66.20 Trail bars. N.E. + S.W.
- 67.70 Leave bottom & ascend
- 72.00 Opposite bank bars N.E. + S.W.
- 79.92 The Cor. to Secs. 22, 23, 26 & 27.
Land. broken.
Soil gravelly. 2^d & 3^d rate
Timber heavy Pine. 79.92 chs.
-

N 0° 1' W. bet. Secs. 22 & 23.

Va. 13° 44' E

In heavy Pine timber

- 19.50 Wagon Road to Winslow bars. NNE + SSW.
- 40.00 Set a sandstone 15 x 8 x 6 ins. 10 ins
in the ground. for 1/4 Sec Cor. marked

Subdivisions.

- Chs. $\frac{1}{4}$ on W. face whence a Pine 14 ins diam. bears. S 23° E 17 lks. dist. marked $\frac{1}{4}$ S. B.Y. — A Pine 28 ins. diam. bears. N 77° W 146 lks. dist. marked $\frac{1}{4}$ S. B.Y. —
- 59.30 Bank bears. N.E. + S.W. descend
- 65.00 Gulch 20 lks. wide runs N.E. ^{ward}
- 69.75 Bank Opposite bears. N.E. + S.W.
- 80.00 Set a Sandstone $18 \times 14 \times 6$ ins. 13 ins. in the ground. for. Cr. to Secs. 14, 15, 22, & 23. Marked with 3 notches on S. and 2 notches on E. edges. Whence
- A Pine 12 ins. diam. bears. N 73° E 101 lks. dist. marked J. 13. N. R. 13. E. S. 14. B.Y.
- A Pine 6 ins. diam. bears. S 45° E 12 lks. dist. marked J. 13. N. R. 13. E. S. 23 B.Y.

T. 13. N. R. 13. E.

Chs. A Pine 18 ins. diam. bears.
 S70°W 124 lks. dist. marked
 T. 13. N. R. 13. E. S. 22 B.S.
 An Oak 5 ins. diam. bears.
 N49°W 35 lks. dist. marked
 T. 13. N. R. 13. E. S. 15. B.S. —
 Land. Nearly level
 Soil. gravelly 2^d + 3^d rate
 Timber Heavy Pine + Oak 80 chs.

East on a random line
 Out. Secs. 14 x 23.
 Va. 13°44'E.

40.00 Set. temporary 1/4 Sec. Cor.
 79.96 Int. Nt. S. line at Cor. to Secs.
 13. 14. 23 x 24. Thence I run.
 West. on a true line.
 Out. Secs. 14 x 23.

Subdivisions.

chs.	Va. 13°44'E.
	In heavy Pine timber, descend.
2.30	Enter bottom
2.60	Gulch 20 lks. wide runs N.E.
2.80	Trail bears N.E. & S.W.
3.10	Leave bottom & ascend
8.70	Bank bears N.E. & S.W.
36.30	Wagon Road to Winslow bears N.E. & S.W.
39.98	Sandstone 14x12x6 in. above ground in place, marked 1/4 on N. face Where A Pine 6 ins. diam. bears S70°W 15 lks. dist. marked 1/4 S. B.S. - A Pine 7 ins. diam. bears N10°W 9 lks. dist. marked 1/4 S, B.S.
51.70	Pine 10 ins. diam. on line, marked with 2 notches on E. & W. Sides
61.00	Bank bears N.E. & S.W. descend
63.25	Gulch 20 lks. wide runs N.E. ^{ascend}
68.00	Opposite bank bears N.E. & S.W.

79.96 The Cor. to Secs. 14, 15, 22 & 23.
Land. rolling.
Soil. gravelly 2^d rate.
Timber. Heavy Pine 79.96 chs.

N 0° 1' W. bet. Secs. 14 & 15.
Va. 13° 44' E.

In heavy Pine timber

37.75 Pine 22 ins. diam. on line marked
with 2 matches on N. & S. Sides.

40.00 Set a Sandstone 16x10x5 ins. 11 ins. in
the ground. for 1/4 Sec. Cr. marked
1/4 on W. face, where a Pine 5 ins
diam. bears. N 76° W 21 lks. dist.
marked 1/4, S. B. T. - A Pine 4 ins.
diam. bears. N 9° E 14 lks. dist.
marked 1/4, S. B. T. -

80.00 Sandstone in place 30x15x4 ins.

Subdivisions.

chs. above ground, which I mark
 4 notches on S. and 2 notches on E
 faces, for. Co. to Recs. 10. 11. 14 & 15.
 When a Pine 6 ins. diam. bears,
 N 56° E 47 lks. dist, marked
 J. 13, N. R. 13, E. S. 11 B. J. -
 A Pine 8 ins. diam. bears
 S 10° E 25 lks. dist, marked,
 J. 13, N. R. 13, E. S 14 B. J.
 A Pine 14 ins. diam. bears.
 S 13° W 20 lks. dist, marked
 J. 13, N. R. 13 E. S. 15, B. J.
 A Pine 26 ins. diam. bears
 N 67° W 89 lks. dist, marked
 J. 13, N. R. 13, E. S. 10 B. J.
 Land.. level.
 Soil. Sandy 2^d rate.
 Timber. Heavy Pine 80 chs.
 October 4, 1893.

J. 13. N. R. 13. E.

Chs. East on a random line
bet. Secs. 11 & 14.
Va. $13^{\circ}44' E$.

40.00 Set temporary $\frac{1}{4}$ Sec. Cor.

79.90 Sub. N. & S. line 4 lks. N. of Cor. to
Secs. 11, 12, 13 & 14. Thence I run
 $N 89^{\circ}58' W$ on a true line
bet. Secs. 11 & 14.
Va. $13^{\circ}44' E$.

In heavy Pine timber.

8.50 Bank bears. N.E. & S.W. descend

16.30 Trail bears. N.E. & S.W.

16.65 Gulch 10 lks wide runs N.E. ^{ascend}

39.95 Set a Sandstone $18 \times 10 \times 5$ ins. 13 ins.
in the ground. from $\frac{1}{4}$ Sec. Cor. Marked
 $\frac{1}{4}$ on N. face, whence A Pine 14 ins.
diam. bears. $N 1^{\circ} E$ 68 lks. dist. mark
 $\frac{1}{4}$ S. B. J. - A Pine 26 ins. diam bears
 $S 36^{\circ} E$ 89 lks. dist. marked $\frac{1}{4}$ S. B. J.

Subdivisions.

cho.	
56.05	Trail bears N.W. & S.E.
64.30	Bank bears. N.W. & S.E. descent
71.00	Gulch 20 lks wide runs. NW ^{ground}
71.40	Trail bears. N.W. & S.E.
75.70	Opposite bank bears. NW & S.E.
79.90	The Cor. to Secs. 10. 11. 14 & 15 Land, rolling. Soil. Sandy & gravelly 2 ^d rate. Timber heavy Pine. 79.90 cho.

N 0° 1' W. bet. Secs. 10 & 11.

Va. 13° 44' E.

In heavy Pine timber.

1.30	Bank bears. N.W. & S.E. descent
10.50	Gulch 20 lks. wide runs. N.W. ^{ascent}
33.00	Opposite Bank bears. N.W. & S.E.
40.00	Set. a sandstone 16 x 10 x 5 ins. 11 ins in the ground. for 1/4 Sec. Cor. marked

J. 13. N. R. 13. E.

chs. $\frac{1}{4}$ on W. face. whence A Pine 14 ins
diam. trans. N40°W 48 lks. dist.
marked $\frac{1}{4}$ S. B. I. - A Pine 15 ins.
diam. trans. S46°E 75 lks. dist.
marked $\frac{1}{4}$ S. B. I. -

80.00 Set. a Sandstone 20x12x5 ins. 15 ins.
in the ground. for. Gr. to Recs. 2. 3.
10 & 11. marked with 5 notches on S.
and 2 notches on E. edges. whence
A Pine 10 ins. diam. trans.
N49°E. 37 lks. dist. marked
J. 13. N. R. 13 E. S. 2 B. I.
A Pine 14 ins. diam. trans.
S41°E 136 lks. dist. marked
J. 13. N. R. 13 E. S. 11. B. I.
A Pine. 16 ins. diam. trans.
S60°W 49 lks. dist. marked
J. 13. N. R. 13 E. S. 10. B. I.
A Pine 13 ins. diam. trans.

Subdivisions.

chs. N46°W 70 lks. dist. marked
 S. 13. N. R. 13. E. S. 3. B. 1. —
 Land. nearly level.
 Soil sandy & gravelly. 2^d + 3^d rate,
 Timber heavy Pine 80. chains.

S89°58'E on a random line,
 bet. Secs. 2 & 11.
 Va. 13°44'E.

40.00 Set. temporary 1/4 Sec. Cor.

79.76 Int. N. & S. line. 3 lks. N. of Cor. to
 Secs. 1, 2, 11 & 12. Thence I run
 N89°57'W. on a true line,
 bet. Secs. 2 & 11.
 Va. 13°44'E.

In heavy Pine timber

18.50 Bank trans. N.E. & S.W. descend

25.60 Enter bottom

- chs.
 26.55 Gulch. 10 lks wide, runs N. E.
 28.60 Leave bottom & ascend,
 39.88 Set a Sandstone 42. x 12 x 10 ins. 30 ins
 in the ground. for $\frac{1}{4}$ Sec. Cor. Marked
 $\frac{1}{4}$ on N. face, whence a Pine 4 ins.
 diam. bears N 12° E. 26 lks. dist.
 marked $\frac{1}{4}$ S. B. I. - An Oak. 5 ins. diam
 bears S. 20° W 36 lks. dist. marked $\frac{1}{4}$ S. B. I.
 43.50 Opposite bank, bears N. E. & S. W.
 67.50 Bank bears N. N. E. & D. A. W. descend
 70.90 Gulch. 10 lks. wide runs N. N. E. ascend
 74.50 Opposite bank, bears N. N. E. & S. S. W.
 79.76 The Cont. Secs. 2, 3, 10 & 11.
 Land, rolling.
 Soil, gravelly. 2^d rate.
 Timber. Heavy Pine 79.76 chs.
-

Subdivisions.

- Chs. $N 0^{\circ} 1' W.$ on a random line.
bet. Secs 2 & 3
 $\gamma a. 13^{\circ} 44' E.$
- 40.00 Set temporary $\frac{1}{4}$ Sec. Cor.
- 80.19 Sub. N. boundary of Sp. 7 lks. E of
Cor. to Secs. 2, 3, 34 & 35. Thence run
 $S 0^{\circ} 4' E$ on a true line
bet. Secs. 2 & 3.
 $\gamma a 13^{\circ} 44' E.$
- In heavy Pine timber.
- 18.00 Bank trans. N.W. + S.E. descend
- 21.90 Enter bottom.
- 22.40 Trail trans. N.W. + S.E.
- 23.30 Gulch 10 lks. wide runs N.W.
- 23.60 Leave bottom, & ascend ✓
- 40.19 Set a sandstone $18 \times 12 \times 5$ ins. 13 ins
in the ground, for $\frac{1}{4}$ Sec. Cor.
marked $\frac{1}{4}$ on W. face. when a
Pine 14 ins. diam. trans. $N 50^{\circ} W 5$
lks. dist. marked $\frac{1}{4}$ S. B.S. - A Pine

T. 13. N. R. 13. E.

- Chs. 10 ins. diam. bears. $S. 64^{\circ} E. 34$
 lts. dist. marked $\frac{1}{4}$ S. B. S. -
- 57.80 Pine 32 ins. diam. on line, marked
 with 2 notches on N. & S. sides.
- 80.19 The Cor. to Secs. 2, 3, 10 & 11.
 Land, nearly level.
 Soil, gravelly. 2^d rate.
 Timber Heavy Pine. 80.19 chs.
 October 5, 1893.
-

From the Cor. to Secs. 27, 28, 33 & 34.
 as recently established by me
 thence I run.

No^o 2' W. bet. Secs. 27 & 28.

Ya. $13^{\circ} 44' E.$

In heavy Pine timber.

- 15.65 Pine 28 ins. diam. on line, marked
 with 2 notches on N. & S. sides

Subdivisions.

- chs.
- 40.00 Set a Sandstone 18x10x5 ins. 13 ins
in the ground. for. $\frac{1}{4}$ Sec. Cor. marked
 $\frac{1}{4}$ on W. face. whence A Pine 12 ins
diam. bears. S 84° E 33 lks. dist,
marked $\frac{1}{4}$ S. B. J. - A Pine 40 ins
diam. bears. N 88° W 27 lks. dist,
marked $\frac{1}{4}$ S. B. J. -
- 48.00 Bank bears. N.W. + S.E. descend
- 48.90 Gulch 10 lks. wide. runs. NW ^{ward}
- 50.50 Opposite bank bears. NW. + S.E.
- 55.50 Pine 24 ins. diam. on line. marked
with 2 notches on N. + S. Sides
- 57.65 Pine 14 ins. diam. on line. marked
with 2 notches on N. + S. Sides
- 80.00 Set a Sandstone 22x12x6 ins. 16
ins. in the ground. for. Cor. to Secs.
21, 22, 27, + 28. marked with
2 notches on S. and 3 notches on
E. edges. whence -

T. 13. N. R. 13. E.

- Chs. A Pine 14 ins. diam. bears.
 N 36° E. 62 lks. dist. marked
 T. 13. N. R. 13. E. S. 22 B.S.
- A Pine 12 ins. diam. bears
 S 36° E 76 lks. dist. marked
 T. 13. N. R. 13. E. S. 27 B.S.
- A Pine 20 ins. diam. bears
 S 38° W 89 lks. dist. marked
 T. 13. N. R. 13. E. S. 28. B.S.
- A Pine 6 ins. diam. bears.
 N 59° W 27 lks. dist. marked
 T. 13. N. R. 13. E. S. 21. B.S. —
- Land. nearly level.
 Soil. gravelly. 2^d rate.
 Timber. Heavy Pine 80. Chains.

East. on a random line.

bet. ^{Secs.} 22 & 27.

Subdivisions T. 13. N. R. 13. E.

- chs. Va. $13^{\circ}44'E$
- 40.00 Set. temporary $\frac{1}{4}$ Sec. Cor.
- 80.40 Int. N. & S. line at Cor. to Secs. 22,
23, 26 + 27. Thence I run
West. on a true line
bet. Secs. 22 x 27.
Va $13^{\circ}44'E$.
- In Heavy Pine timber
- 18.30 Wagon Road to Winslow from N.W. $25^{\circ}55'W$
- 40.20 Set. a Sandstone $18 \times 11 \times 5$ ins. 13.
ins. in the ground, for $\frac{1}{4}$ Sec. Cor.
marked $\frac{1}{4}$ on N. face. where
A Pine 4 ins. diam. bears $S77^{\circ}E$
46. lks. dist. marked $\frac{1}{4}$ S. B. G.
A Pine 4 ins. diam. bears $N63^{\circ}W$
38 lks. dist. marked $\frac{1}{4}$ S. B. G.
- 52.20 Trail. bears. N.E. + S. W
- 80.40 The Cor. to Secs. 21, 22, 27, + 28.

Platt

BOOK

128

Concluded, Book 129.