

BOOK 129

T13NR18E

2.

P.60

No-129

BOOK 129

Subdivisions

4-671

129

FIELD NOTES
GENERAL LAND OFFICE.

Sp: 13 N. R 13 E.

No-129

Indexed, Book 128

BOOK 129

No-129

Township 13N R. 13E

6	113	5	88	4	73	3	2	1
111		109		87		71		
7	107	8	85	9	69	10	11	12
106		104		83		67		
18	102	17	82	16	65	15	14	13
100		98		80		64		
19	96	20	78	21	62	22	23	24
94		92		76				
30	90	29	74	28		27	26	25
31		32		33		34	35	36

Subdivision T. 13, N. R. 13, E.

chs. Land level.

Soil. gravelly + stony. 2^d + 3^d rate.
Timber heavy Pine. 80. 40 chs.

N 0° 2' W. bet. Secs. 21 + 22
Va 13° 44' E.

Few heavy Pine timber.

17.60 Trail bears. N.E. + S.W.

40.00 Set. a Sandstone 18x10x10 ins. 13 ins
in the ground. for 1/4 Sec. Cor. marked
1/4 on W. face. whence A Pine. 14 ins
diam. bears. S 89° W 72 lks. dist.

marked 1/4 S. B. T. - A Pine 12 ins.
diam. bears. N 63° E 100. lks. dist.
marked 1/4 S. B. T. -

77.50 Bank bears. N.E. + S.W. descend

79.50 Gulch 40 lks. wide runs N.E. ^{ward}

80.00 Set. a Sandstone 18x10x10 ins. 13 ins.

Subdivisions T. 13. N. R. 13. E.

chs. in the ground for Cor. to Secs. 15. 16
21 & 22. marked with 3 notches on S.
& E. edges. whence

A Pine 5 ins. diam. bears.

N 43° E 85 lks. dist. marked

T. 13. N. R. 13. E. S. 15. B. 1.

A Pine 4 ins. diam. bears.

S 6° E 60 lks. dist. marked

T. 13. N. R. 13. E. S. 22. B. 1.

A Pine 4 ins. diam. bears

S 6° W 70 lks. dist. marked

T. 13. N. R. 13. E. S. 21 B. 1.

A Pine 14 ins. diam. bears.

N 28° W 49 lks. dist. marked

T. 13. N. R. 13. E. S. 16. B. 1.

Land. level.

Soil. gravelly. 3^d rate.

Timber heavy Pine. 80. chains.

Subdivisions.

chs. East. on a random line.

bet. Secs. 15 & 22.

Va. $13^{\circ}44'E$

40.00 Set. temporary $\frac{1}{4}$ Sec. Cor.

80.40 Sub. N. & S. line 9 lks. S. of Cor. to
Secs. 14, 15, 22 & 23. Thence I run.

$S 89^{\circ}56'W$. on a true line.

bet. Secs. 15 & 22.

Va. $13^{\circ}44'E$.

In heavy Pine timber

10.90 Trail, bears N & S, W.

39.60 Trail, bears N. W. & S. E.

40.20 Set. a Sandstone $22 \times 12 \times 6$ ins. 16 in

in the ground. for $\frac{1}{4}$ Sec. Cor. marked

$\frac{1}{4}$ on N. face, whence A Pine 5 ins.

diam. bears $N 49^{\circ}W$ 31 lks. dist.

marked $\frac{1}{4}$ S. B. T. A Pine 20 ins.

diam. bears $S 47^{\circ}E$. 51 lks. dist

marked $\frac{1}{4}$ S. B. T. —

J. 13. N. R. 13. E.

chs.	
53.20	Bank bars. N. + S, descend
53.90	Gulch. 15 lks. wide runs. Northw ^{ard}
55.00	Opposite bank bars. N. + S.
74.00	Bank bars. N.E. + S.W, descend
80.10	Gulch. 20 lks. wide runs. N.E.
80.40	The Cor. to Secs. 15, 16, 21, + 22. Land. nearly level. Soil. gravelly 2 ^d rate. Timber. heavy Pine 80.40 chs.

N 0° 2' W, cut. Secs. 15 + 16,
Va, 13° 44' E

In heavy Pine timber, ^{ward}

3.50	Bank bars. N.E. + S.W,
40.00	Set a sandstone 15 x 12 x 5 ins. 10 ins. in the ground. for. 1/4 Sec Cor. marked 1/4 on W. face. whence A Pine 16 ins. diam. bars.

Subdivisions.

- chs. N 12° W. 23 lks. dist. marked
 1/4 S. B. J. - A Pine 5 ins. diam.
 trans. N 87° E 104 lks. dist.
 marked 1/4 S. B. J. -
- 61.50 Bank trans. N.E. & S.W. descend
- 67.50 Enter bottom
- 70.50 Gulch 10 lks. wide runs N.E.
- 71.80 Trail. trans. N.E. & S.W.
- 73.50 Leave bottom. & ascend
- 80.00 Set a Sandstone 18x11x6 ins. 13 ins
 in the ground. for Cor. to Secs.
 9, 10, 15 & 16. marked with 4 notches
 on S. and 3 notches on E. edges.
 whence A Pine 8 ins. diam. trans.
 N 32 1/2° E 77 lks. dist. marked
 J. 13, N. R. 13, E. S. 10, B. J.
 A Pine 20 ins. diam. trans.
 S 20° E 66 lks. dist. marked
 J. 13, N. R. 13, E. S. 15, B. J.

J. 13. N. 13. E.

chs. A Pine 32 ins. diam. bears
 $S 6^{\circ} W$ 84 lks. dist. marked
 J. 13, N. R. 13. E. S. 16, B. J.
 A Pine 14 ins. diam. bears
 $N 39^{\circ} W$ 44 lks. dist. marked
 J. 13, N. R. 13. E. S. 9 B. J. —
 Land. nearly level.
 Soil. gravelly 2^d rate.
 Timber Heavy Pine 80, chs.
 October 6, 1893.

$N 89^{\circ} 56' E$. on a random line
 bet. Sect. 10, & 15,
 Va $13^{\circ} 44' E$.

40.00 Sect. temporary $\frac{1}{4}$ Sec. Cor.
 80.45 Int. N. & S. line 5 lks. N. of Cor.
 to Secs. 10, 11, 14, & 15, Thence I run.
 $S 89^{\circ} 58' W$. on a true line.

Subdivisions.

Chs.	cut. Secs. 10. x 15.
	Ya $13^{\circ}44'E$
	In heavy Pine timber
5.00	Bank bears N.E. + S.W. descend
9.70	Enter bottom
10.20	Pine 18 ins. diam. on line marked with 2 notches on E. + W. Sides
10.60	Gulch 10 lks. wide runs N.E. ^{as a}
15.40	Opposite bank bears N.E. + S.W.
40.22	Set a Sandstone $20 \times 14 \times 5$ ins. 15 ins. in the ground. for $\frac{1}{4}$ Sec. Cor. Marked $\frac{1}{4}$ on N. face. when a Pine 20 ins. diam. bears. $S34^{\circ}W$ 10 lks. dist. marked $\frac{1}{4}$ S. B.S. - A Pine 18 ins. diam. bears. $N55^{\circ}W$ 105 lks. dist. marked $\frac{1}{4}$ S. B.S.
56.20	Enter bottom
57.80	Gulch 20 lks. wide. runs N.E.
58.80	Leave bottom + ascend

T. 13. N. R. 13. E.

chs.	
64.00	Opposite bank bears. N.E. + S.W.
72.30	Bank bears. N.E. + S.W. descend
78.10	Entire bottom
79.00	Trail. bears. N.E. + S.W.
79.75	Gulch 20 lks. wide runs. N.E.
80.45	The Cor. to Secs. 9, 10, 15 & 16 Land. nearly level. Soil. gravelly. 2 ^d rate. Timber heavy Pine. 80.45 chs.

N 0° 2' W. bet. Secs. 9 & 10.
Pa. 13° 44' E.

In heavy Pine timber, ascend

26.50	Bank bears. N.E. + S.W.
29.50	Bank bears. N.E. + S.W. descend
39.50	Entire bottom,
40.00	Set a Sandstone 18 x 10 x 6 ins. 13 ins in the ground. for. 1/4 Sec. Cor. marked

Subdivisions.

- Chs. $\frac{1}{4}$ on W. face, whence A Pine 18
 ins. diam. bears, $N68^{\circ}E$ 58 lks.,
 dist. marked $\frac{1}{4}$ S. B.Y. - A Pine 24
 ins. diam. bears, $N56^{\circ}W$ 51 lks.,
 dist. marked $\frac{1}{4}$ S. B.Y. -
- 40.60 Trail bears NE & SW .
- 40.85 Gulch 10 lks. wide runs NE .
- 41.00 Leave bottom & ascend
- 65.80 Opposite bank bears, NE & SW .
- 80.00 Set a Sandstone $18 \times 10 \times 8$ ins. 13 ins.
 in the ground. for. Cor. to Secs. 3. &
 9×10 , marked with 5 notches on S.
 and 3 notches on E. edges. whence
 A Pine 12 ins. diam. bears
 $N42^{\circ}E$ 43 lks. dist. marked
 Y. 13, N. R. 13. E. S. 3. B.Y.,
 A Pine 15 ins. diam. bears,
 $S50^{\circ}E$. 87 lks. dist. marked
 Y. 13, N. R. 13. E. S. 10 B.Y.

T. 13. N. R. 13. E.

Chs. A Pine 13 ins. diam. bears
 $S 16^{\circ} W$ 47 lks dist. marked
 T. 13. N. R. 13. E. S. 9 B. T. -
 A Pine 10 ins. diam. bears.
 $N 11^{\circ} W$ 35 lks. dist marked
 T. 13. N. R. 13. E. S. 4. B. T.
 Land. nearly level.
 Soil. gravelly 2^d rate.
 Timber Heavy Pine 80 chs.

$N 89^{\circ} 58' E$ on a random line
 bet. Secs. 3 & 10.
 $\gamma a. 13^{\circ} 44' E.$

40.00 Set. temporary $1/4$ Sec. Cr.
 80.24 Int. N. & D. line 10 lks. N. of Cor.
 to Secs. 2, 3, 10 & 11. Thence I run
 $N 89^{\circ} 58' W$ on a true line,
 bet. Secs. 3 & 10.

Subdivisions.

Chs.	Va. 13° 44' E
	In heavy Pine timber
12.40	Trail. bears. N.E. + S.W.
18.00	Bank bears. N.E. + S.W. descend
28.50	Entire bottom
34.90	Trail. bears. N.E. + S.W.
39.40	Gulch. 20 lks. wide. runs. N.E.
40.00	Leaves bottom + ascend.
40.12	Set. a Sandstone 16x12x4 ins. 11 ins in the ground. for 1/4 Sec. Cor. marked 1/4 on N. face. whence a Pine 18 ins. diam. bears. N5°E 54 lks. dist. marked 1/4. S. B.Y. - A Pine 6 ins. diam. bears. S48 1/2° E 129 lks. dist. marked 1/4. S. B.Y. -
50.30	opposite bank bears. N.E. + S.W.
80.24	The Cor. to Recs. 3, 4, 9 & 10. Land nearly level, Soil. gravelly 2 ^d rate. Timber heavy Pine. 80.24 chs.

J. 13. N. R. 13. E.

Chs. N 0° 4' W on a random line.
bet. Secs. 3 & 4.
Va. 13° 44' E.

40.00 Set temporary 1/4 Sec. Cor.

80.00 Int. N. boundary of Tp. 5 lks W. of
Cor. to Secs. 3, 4, 33, & 34, as recently
Established by me. Thence I run
S 0° 2' E on a true line,
bet. Secs. 3, & 4.
Va. 13° 44' E.

In heavy Pine timber

15.00 Bank trans. N, N.E. & S, S.W. descend

23.95 Gulch 10 lks. wide runs N, N.E. ^{Wood}

28.50 Opposite bank trans. N, N.E. & S, S.W.

40.00 Set a Sandstone 20 x 12 x 5 ins. 15 ins
in the ground, for 1/4 Sec. Cor. marked
1/4 on W. face. Whence a Pine 15 ins.
diam. trans. N 52° W 39 lks. dist,
marked 1/4 S. B. L. - An Oak. 6 ins.

Subdivisions.

- Chs. diam. bears. $S 85^{\circ} E$ 28 lks. dist.
 Marked $\frac{1}{4}$ S. B. I.
- 40.80 Pine 24 ins. diam. on line, marked
 with 2 notches on N. & S. Sides.
- 61.70 Pine 26 ins. diam. on line, marked
 with 2 notches on N & S. Sides.
- 80.00 The Cor. to Secs. 3, 4, 9 & 10.
 Land, nearly level.
 Soil, gravelly. 2^d rate.
 Timber Heavy Pine & Oak. 80. chs.

October 7, 1893.

From the Cor. to Secs. 28 & 29
 32 & 33. as recently Established
 by me. From
 $N 0^{\circ} 2' W.$ bet. Secs. 28 & 29
 $Va. 13^{\circ} 44' E$
 In heavy Pine timber

T. 13. N. R. 13 E.

- chs. over undulating surface,
 39.50 Entire bottom
 40.00 Set a Sandstone 18x12x4 ins
 13 ins. in the ground, for $\frac{1}{4}$ Sec
 Cor. Marked $\frac{1}{4}$ on W. face. whence
 A Pine 10 ins diam. bears, $S76^{\circ}E$
 8 lks. dist. Marked $\frac{1}{4}$ S. B. T.
 A Pine 5 ins. diam. bears. $N76^{\circ}W$
 15 lks. dist. marked $\frac{1}{4}$ S. B. T.
 41.10 Trail. bears. $N.E.$, + $S.W.$
 41.30 Gulch 10 lks. wide. runs $N.E.$
 42.26 Leave bottom + ascend.
 52.00 Bank bears. $N.E.$, + $S.W.$
 80.00 Set a Sandstone 18x10x6 ins, 13
 ins. in the ground. for. Cor. to
 Secs. 20, 21, 28 & 29. marked with
 2 notches on S. and 4 notches
 on E. edges. whence
 A Pine 10 ins. diam. bears.

Subdivisions.

- chs. N 35° E 84 lks. dist. marked
T. 13. N. R. 13. E. S. 21 B. T.
A Pine 34 ins. diam. trans.
- S 7° E 61 lks. dist. marked
T. 13. N. R. 13. E. S. 28 B. T.
A Pine 24 ins. diam. trans
- S 67° W 32 lks. dist. marked
T. 13. N. R. 13. E. S. 29 B. T.
A Pine 28 ins. diam. trans
- N 45° W 80 lks. dist. marked
T. 13. N. R. 13. E. S. 20 B. T.
Land. rolling,
Soil, gravelly, 2^d rate.
Timber, heavy Pine. 80 chs.
-

East on a random line,
bet. Secs. 21 & 28,
Ta. 13° 44' E.

J. 13. N. R. 13. E.

- chs.
40.00 Set. temporary $\frac{1}{4}$ Sec Cor.
- 80.00 Int. N. + S. line at Cor. to Secs.
21, 22, 27, + 28. Thence I run
West on a true line
but. sec. 21 X 28.
Ya. $13^{\circ}44^{\circ}E$.
- In heavy Pine timber.
- 14.25 Trail. bears. N.E. + S.W.
- 40.00 Set. a Sandstone $18 \times 12 \times 6$ ins. 13.
ins. in the ground. for $\frac{1}{4}$ Sec Cor.
marked $\frac{1}{4}$ on N. face. whence a
Pine 8 ins. diam. bears. $S 20^{\circ}W$
42 lks. dist. marked $\frac{1}{4}$ S. B. S.
A Pine 20 ins. diam. bears. $N 49^{\circ}W$
30 lks. dist. marked $\frac{1}{4}$ S. B. S.
- 44.20 Bank bears. N.W. + S.E. descend
- 45.05 Gulch 10 lks. wide runs. N.W. ^{ward}
- 46.00 Opposite bank bears. N.W. + S.E.
- 52.00 Bank bears. N.N.W. + S.S.E. descend

Subdivisions.

Chs.	
55.00	Entire bottom
55.40	Trail. brass. N + S.
55.70	Gulch, 20 lks. wide runs Northwly ^{asend}
57.00	Ridge brass. NNE, + S.S.W descend
58.00	Gulch 10 lks. wide runs N.E. ascend,
61.20	Opposite bank brass. N + S.
80.00	The Cor. to Secs. 20, 21, 28 & 29 Land. rough. Sail. Stony. 3 ^d rate. Timber heavy Pine 80. Chs.

N 0° 2' W. bat. 20 & 21.

Va 13° 44' E.

In heavy Pine timber.

- 40.00 Set a Sandstone 18 x 10 x 5 ins, 13
ins. in the ground for 1/4 Sec Cor.
marked 1/4 on W. face. Whence a Pin
14 ins. diam. brass. S 78° W 60

	lks. dist, marked $\frac{1}{4}$ S. B. T.
	A Pile 10 ins. diam. bears $N10^{\circ}E$
	37 lks. dist, marked $\frac{1}{4}$ S. B. T.
49.50	Bank bears. NW , & SE , descend
53.50	Enter bottom
55.20	Gulch. 20 lks. wide, runs NW ,
55.50	Leave bottom & ascend
69.80	Opposite bank bears. NW , & SE .
80.00	Set a Sandstone $20 \times 11 \times 10$ ins.
	15 ins. in the ground. for. Cr. to Seco
	16. 17. 20×21 . marked. with
	3 notches on S. and 4 notches
	on E. edges. whence
	A Pile 6 ins. diam. bears
	$N38^{\circ}E$ 78 lks. dist, marked
	T. 13. N. R. 13. E. S. 16. B. T.
	A Pile 5 ins. diam. bears
	$S84^{\circ}E$ 46 lks. dist, marked
	T. 13. N. R. 13. E. S. 21 B. T.

Subdivisions.

Chs. A Pine 14 ins. diam. bears
 S 10° W 128 lks. dist. marked
 J. 13, N. R. 13, E. S. 20 B. J.
 A Pine 26 ins. diam. bears
 N 27° W 64 lks. dist. marked
 J. 13, N. R. 13, E. S. 17. B. J.
 Land. rough & broken.
 Soil gravelly 3^d rate.
 Timber. heavy Pine 80 chs.

East on a random line
 bet. Secs. 16 & 21.
 Ya $13^{\circ} 44' E$

40.00 Set temporary $\frac{1}{4}$ Sec. Cr.
 80.00 Int. N. & S. line at Cr. to Secs.
 15, 16, 21 & 22. Thence I run
 West on a true line
 bet. Secs. 16 & 21.

T. 13. N. R. 13. E.

Chs.	Va 13°44'E
1.50	In heavy Pine timber, across Bank bars, NE. + S.W.
20.15	Divide & trail bars, NE. + S.W.
40.00	Set a Sandstone 18x10x8 ins. 13 ins. in the ground, for 1/4 Sec. Cor. Marked 1/4 on N. face, whence a Pine 6 ins. diam. bears S 83° W 50 lks. dist. marked 1/4 S. B.T. A Pine 5 ins. diam. bears N 6° W 20 lks. dist. marked 1/4 S. B.T.
52.30	Pine 30 ins. diam. on line marked with 2 notches on E. + W. Sides
54.60	Divide & trail bars, NW. + S.E.
80.00	The Cor. to Secs. 16. 17, 21 & 22 Land, nearly level, Soil, gravelly 2 ^d rate, Timber, heavy Pine, 80 chas.

Subdivisions.

- Chs. N $0^{\circ} 2' W$. bet. Secs. 16 & 17.
 Va $13^{\circ} 44' E$
- In heavy Pine timber as usual
- 39.45 Pine 20 ins. diam. on line marked
 with 2 notches on N. & S. Sides
- 40.00 Set a Sandstone $20 \times 8 \times 8$ ins. 15 ins
 in the ground. for $\frac{1}{4}$ Sec Cor
 marked $\frac{1}{4}$ on N. face. whence a
 Pine 24 ins. diam. bears N $72^{\circ} \frac{1}{2} W$
 74 lbs. dist. marked $\frac{1}{4}$ S. B. I.
 A Pine 7 ins. diam. bears S $81^{\circ} \frac{1}{2} E$
 64 lbs. dist. marked $\frac{1}{4}$ S. B. I.
- 69.10 Trail. bears N. W. & S. E.
- 80.00 Set a Sandstone $20 \times 12 \times 6$ ins. 15 ins
 in the ground. for. Cor. to Secs. 8, 9
 16, & 17, marked with 4 notches
 on S. & E. edges. whence.
 An Oak 5 ins. diam. bears
 N $78^{\circ} E$ 23 lbs. dist. marked,

T. 13. N. R. 13. E.

chs.

T. 13. N. R. 13. E. S. 9 B. S.

A Pine 5 ins. diam. trees

S 20° E 31 lks. dist. marked

T. 13. N. R. 13. E. S. 16. B. S.

A Pine 8 ins. diam. trees

S 52° W 33 lks. dist. marked

T. 13. N. R. 13. E. S. 17 B. S.

A Pine 7 ins. diam. trees.

N 38° W 18 lks. dist. marked

T. 13. N. R. 13. E. S. 8 B. S.

Land level.

Soil. gravelly 2^d rate.

Timber. heavy Pine 80 chs.

October 9. 1893.

East on a random line

bet. Acos. 9 & 16.

Va. 13° 44' E.

Subdivisions.

chs.	
40.00	Set. temporary $\frac{1}{4}$ sec. Cr.
80.00	Int. N. & S. line at Cor. to Secs. 9, 10, 15, & 16. Thence I run West, on a true line bet. Secs. 9 & 16, Pa. $13^{\circ}44'E$.
1.05	In heavy Pine timber, ascend Pine 36 ins. diam, on line, marked with 2 notches on E. & W. Sides
2.50	Bank bars. N.E. & S.W.
27.50	Bank bars N.E. & S.W. descend
31.35	Gulch 10 lks. wide runs N.E. ^{ascend}
36.50	Opposite bank bars. N.E. & S.W.
40.00	Set. a Sandstone $22 \times 10 \times 6$ ins, 16 ins. in the ground, for $\frac{1}{4}$ sec Cr. marked $\frac{1}{4}$ on N. face, whence a Pine 22 ins. diam. bears $S 16^{\circ} W$ 34 lks. dist., marked $\frac{1}{4}$ S. C. L. - A Pine 24 ins diam. bears. $N 20^{\circ} W$ 46 lks. dist.

T. 13. N. R. 13. E.

Chs.	Marked $\frac{1}{4}$ S. B. L. —
42.80	Divide $\frac{1}{2}$ trail trans. N.E. & S.W.
75.00	Bank trans. N.E. & S.W. descend
76.30	Gutch 10 lks. wide run. N.E., ascend
77.50	Opposite bank trans. N.E. & S.W.
80.00	The Cor. to Secs. 8, 9, 16 & 17.
	Land. nearly level,
	Soil. Sandy & gravelly 2 ^d rate.
	Timber heavy Pine. 80 chs.

N $0^{\circ} 2' W$. bet. Secs. 8 & 9.

Yu. $13^{\circ} 44' E$

In heavy Pine timber

40.00	Set a Sandstone $18 \times 10 \times 8$ ins. 13 ins. in the ground. for $\frac{1}{4}$ Sec Cor. marked $\frac{1}{4}$ on W. face. Whence A Pine 16 ins. diam. trans $S 40^{\circ} W$ 47 lks. dist. Marked $\frac{1}{4}$ S. B. L. — A Pine 20 ins.
-------	---

Subdivisions.

- chs. diam. bears $S 70^{\circ} E$ 36 lks. dist.
marked $\frac{1}{4}$ S. B. I. -
- 59.00 Bank bears. N.W. + S.E. descend
- 61.35 descend abruptly
- 61.75 Fir 24 ins. diam. on line marked
with 2 notches on N. + S. Sides
- 73.80 Gulch 20 lks. wide runs N.W. + N.W. ^{ascend}
- 77.50 Ridge bears. N.W. + S.E. descend
- 78.50 Gulch. 10 lks. wide runs NW ^{grad}
- 80.00 Set a Sandstone $18 \times 12 \times 4$ ins. 13 ins
in the ground. for. Cor. to Sees. 4, 5
8 & 9. marked with 5 notches on S.
and 4 notches on E. edges. whence
A Pine 18 ins. diam. bears
 $N 16^{\circ} E$. 128 lks. dist. marked
S. 13. N. R. 13. E. S. 4 B. I. -
A Pine 10 ins. diam. bears
 $S 74\frac{1}{2}^{\circ} E$ 109 lks. dist. marked
S. 13. N. R. 13. E. S. 9 B. I. -

T. 13. N. R. 13. E.

Chs. A Pine 8 ins. diam. bears
 S $52\frac{1}{2}$ W 97 lks. dist. marked
 T. 13, N., R. 13. E. S. 8, B. 1.

A Pine 10 ins. diam. bears
 N $78\frac{1}{2}$ W 94 lks. dist. marked
 T. 13, N., R. 13, E. S. 5, B. 1.

Laud. broken.

Soil. gravelly. 3^d rate.

Timber heavy Pine 80. chs.

East. on a random line
 bet. Secs. 4 & 9.

Va $13^{\circ}44'E$

40.00 Set. temporary $\frac{1}{4}$ Sec. Cor.

79.96 Sit. N. + S. line 15 lks. S. of Cor.
 to Secs. 3, 4, 9 & 10. Thence S run.
 S $89^{\circ}54'W$. on a true line
 bet. Secs. 4 & 9.

Subdivisions.

chs.

Va. $13^{\circ}44'E$

In heavy Pine timber

15.70 Trail. ~~trans.~~ N.E. & S.W.

39.98 Set a Sandstone 18x12x5 ins. 13 ins

in the ground. for $\frac{1}{4}$ Sec. Cor. marked $\frac{1}{4}$ on N. face. Whence, A Pine 12 ins,
diam. trans N $10^{\circ}W$ 15 lks. dist,
marked $\frac{1}{4}$ S. B.T. - A Juniper 5 insdiam. trans S $40^{\circ}E$ 2 lks. dist.54.00 Trail. ^{marked $\frac{1}{4}$ S. B.T.} trans. N.E. & S.W.

60.50 Bank. trans. N.E. & S.W. descend

79.96 The Cor. to Secs. 4, 5, 8 & 9.

Land, nearly level.

Soil, gravelly 2^d & 3^d rate.

Timber heavy Pine 79.96 chs.

on ~~any~~ random lineN $0^{\circ}2'W$. bet. Secs. 4, & 5,Va. $13^{\circ}44'E$.

T. 13. N. R. 13. E.

- | | |
|-------|---|
| 40.00 | Set temporary $\frac{1}{4}$ Sec. Cr. |
| 80.00 | Int. N. boundary of Tp. at Cor.
to Secs. 4, 5, 8 & 9, as recently
Established by me. - Thence I run
$S 0^{\circ} 2' E$ on a true line,
bet. Secs. 4 & 5,
Th. $13^{\circ} 44' E$. |
| 40.00 | Set a Sandstone $16 \times 10 \times 6$ ins. 11 ins
in the ground. for $\frac{1}{4}$ Sec. Cr. marked
$\frac{1}{4}$ on N. face, whence Pine 20 ins.
diam. bears $N 86^{\circ} E$ 57 lks. dist.
marked $\frac{1}{4}$ S. B. T. - A Pine 10 in
diam. bears $S 67^{\circ} W$ 61 lks.
dist. marked $\frac{1}{4}$ S. B. T. |
| 61.20 | Bank bears. N.E. & S.W. descend |
| 68.90 | Gulch 10 lks. wide runs S.W. ^{ascend} |
| 72.25 | Ridge bears. E. & W. descend |
| 80.00 | The Cor. to Secs. 4, 5, 8 & 9.
Land broken. |

Subdivisions.

Chs. Soil, gravelly 2^d & 3^d rate
 Timber Heavy Pine. 80. Chains
 October 10. 1893.

From the Cor. to Secs. 29, 30,
 31, & 32, as recently established
 by me. Iron.

N 0° 3' W. bet. Secs 29 & 30,
 Va. 13° 44' E.

In Heavy Pine timber

- 11.50 Bank bars. N.E. & S.W. descend
 24.70 Gulch 40 lks wide runs N.E. ^{ward}
 37.00 Opposite bank bars. N.E. & S.W.
 40.00 Set a sandstone 16 x 10 x 6 ins, 11 ins
 in the ground, for 1/4 Sec Cor,
 marked 1/4 on W. face. Whence a
 Pine 5 ins diam. bears S 39° W
 27 lks. dist. marked 1/4. A. B. J.

T. 13. N. R. 13. E.

- chs. A Pine 22 ins. diam. bears S37°E
29 lks. dist. marked 1/4 S. B.T.
- 48.40 Fruit bears. N. W. + S. E.
- 80.00 Set a Sandstone 18x12x5 ins. 13
ins. in the ground. for. Cor. to Secs.
19, 20, 29x30, marked with
2 notches on S. and 5 notches
on E. edges. Whence -
- A Pine 12 ins. diam. bears
N85°E 82 lks. dist. marked
T. 13. N. R. 13. E. S. 20. B.T.
- A Pine 8 ins. diam. bears
S40°E 67 lks. dist. marked
T. 13. N. R. 13. E. S. 29 B.T.
- A Pine 6 ins. diam. bears
S26°W 28 lks. dist. marked
T. 13. N. R. 13. E. S. 30. B.T.
- A Pine 5 ins. diam. bears.
N39°W 31 lks. dist. marked

Subdivisions.

Chs. T. 13, N. R. 13, E. S. 19 B. J.
 Land rough & broken.
 Soil. Stony & gravelly 3^d rate.
 Timber heavy Pine 80 chs.

East. on a random line
 bet. Secs. 20 & 29,
 Va. $13^{\circ}44'E$.

40.00 Set. temporary $1/4$ sec. Cor.
 80.10 Int. N. & S. line at Cor. to Secs
 20, 21, 28 & 29, Thence I run
 West. on a true line,
 bet. Secs. 20 & 29,
 Va. $13^{\circ}44'E$

In heavy Pine timber

14.20 Trail, bears N.W. & S.E.
 32.00 Right bank of Willow Cañon from
 Northerly & Southerly, descend

J. 13. N. R. 13. E.

cks,	
40.05	Set. as Sandstone 16x10x4 ins 11 ins. in the ground. for $\frac{1}{4}$ Sec Cr. marked $\frac{1}{4}$ on N. face. whence a Pine 6 ins. diam. bears. $N 84^{\circ} E$ 60 lks dist. marked $\frac{1}{4}$ S. B. J. A Pine 6 ins. diam. bears $S 17^{\circ} E$ 55 lks. dist. marked $\frac{1}{4}$ S. B. J.
40.50	Descend abruptly.
45.00	Enter bottom of Willow Cañon
46.00	Enter bed of Stream runs. Northley
49.00	Leaves bed. of Stream
49.75	Leaves bottom, & ascend abruptly
55.25	End of Steep ascent.
58.25	Opposite bank bears. N. & S.
67.50	Bank bears N.E. & S.W. descend
68.90	Gulch 10 lks. wide. runs. N.E. ascend
70.25	Opposite bank bears. N.E. & S.W.
80.10	The Cor. to Secs. 19, 20, 29 & 30. Land, rough & broken.

Subdivisions.

Sail. Stony 3^d + 4th rate
 Timber Pine. 80.10 cho.

Nest on a random line.

bet. Secs. 19 & 30.

Ya. 13°44' E.

In heavy Pine timber

40.00 Set temporary 1/4 Sec. Cor.

95.64 Int. W. boundary of Sp. 23 lks.

S. of Cor. to Secs. 19, 24, 25 + 30.

Thence I run,

S 89°50' E on a tree line

bet. Secs. 19 & 30.

Ya 13°44' E.

In heavy Pine Timber.

15.40 Enter bottom.

16.20 Gulch 10 lks wide runs Northw.

20.00 Leave bottom.

T. 13. N. R. 13. E.

- | | |
|-------|--|
| chs. | |
| 22.00 | Trail across N.W. + S.E. |
| 42.40 | Pine 4 ins. diam on line. marked with 2 notches on E. + W sides |
| 55.64 | Set a sandstone 16x12x4 ins. 11 ins. in the ground. for $\frac{1}{4}$ sec. Cr. man $\frac{1}{4}$ on N. face. whence A Pine 22 ins. diam. bears S. 80 W. 9 lks. dist. marked $\frac{1}{4}$ S. B.T. - A Pine 4 ins. diam. bears N 33° E 120. lks. dist. marked $\frac{1}{4}$ S. B.T. - |
| 58.40 | Bank bears N.E. + SW descend |
| 61.40 | Gulch 10 lks. wide runs N.S. then E ^{ascend} |
| 63.00 | Opposite bank bears S.W. + Easterly. |
| 95.64 | The Cor. to Secs. 19, 20, 29. + 30. Land. nearly level.
Soil. sandy 2 ^d rate.
Timber heavy Pine. 95.64 chs. |
-

Subdivisions.

- chs. No° 3' W. bat. Secs. 19, & 20.
 Va. 13° 44' E.
- In heavy Pine timber
- 2.00 Bank trans. N.E. & S.W. descend
- 5.55 Gulch 10 lks wide runs Northwesterly ^{bank}
- 6.50 Opposite bank trans. N.E. & S.W.
- 16.35 Pine 24 ins. diam. on line marked
 with 2 notches on N. & S. Sides
- 25.15 Pine 10 ins. diam. on line marked
 with 2 notches on N. & S. Sides
- 35.50 Pine 24 ins. diam. on line marked
 with 2 notches on N. & S. Sides
- 40.00 Set a Sandstone 20x12x4 ins. 15
 ins. in the ground. for 1/4 Sec. Cor.
 marked 44 on N. face. Whence a
 Pine 8 ins. diam. bears S 28° E
 52 lks. dist. marked 1/4. S. B.S.
 A Pine 4 ins. diam. bears N 8° W
 24 lks. dist. marked 1/4. S. B.S.

T. 13. N. R. 13. E.

Chs.
48.50

Bank beans N. W. + S. E. descend

80.00

Set a sandstone 18x12x5 ins. 13 ins
in the ground. for Cor. to Secs. 17, 18
19 & 20. marked with 3 notches on S.
and 5 notches on E. edges. whence

A Pine 5 ins. diam. beans

N 51° E 30 lks. dist. marked

T. 13. N. R. 13. E. S. 17. B. S.

A Pine 20 ins. diam. beans

S 59° E 91 lks. dist. marked

T. 13. N. R. 13. E. S. 20. B. S.

A Pine 22 ins. diam. beans.

S 63° W 44 lks. dist. marked

T. 13. N. R. 13. E. S. 19. B. S.

A Pine 16 ins. diam. beans.

N 68° W 66 lks dist. marked

T. 13. N. R. 13. E. S. 18. B. S.

Land level.

Soil. Sandy 2^d rate.

Timber Heavy Pine 80 chains

Subdivisions.

- | | |
|-------|--|
| chs. | East on a random line
bet. Secs. 17 & 20.
Va. $13^{\circ}44'E$. |
| 40.00 | Set temporary $\frac{1}{4}$ sec. Cor. |
| 80.15 | Int. N. & S. line at Cor. to Secs.
16, 17, 20 & 21. Thence I run
West on a true line,
bet. Secs. 17 & 20.
Va. $13^{\circ}44'E$. |
| | In heavy Pine timber |
| 15.50 | Bank bars, N.W. & S.E. descend. |
| 20.10 | Pine 16 ins. diam. on line. Marked
with 2 notches on E. & W. sides |
| 23.30 | Enter bottom |
| 24.40 | Enter bed run N.W. |
| 25.00 | Leave bed run N.W. |
| 25.30 | Leave bottom & ascend |
| 28.30 | Trail bars N.W. & S.E. |
| 35.15 | Pine 24 ins. diam. on line. Marked |

J. 13. N. R. 13. E.

- chs. with 2 notches on E. & W. sides
- 35.50 Ridge bars. N, N, W, + S, S, E. descend
- 40.08 Set a sandstone 22x12x6 ins. 16 ins
in the ground. for $\frac{1}{4}$ sec. Cor. Marked
 $\frac{1}{4}$ on N. face, where A Pine 4 ins
diam. bars N60°W 38 lks. dist.
Marked $\frac{1}{4}$ S. B.Y. — A Pine 30 ins.
diam. bars. S60°W 11 lks. dist.
Marked $\frac{1}{4}$ S. B.Y. —
- 48.50 Enter bed of Willow Cañon runs.
N, N, W, + bars. S, S, E,
- 51.50 Leave bed. runs. N, N, W,
- 52.00 Trail bars. N, N, W, + S, S, E,
- 53.00 Leave bottom + ascend
- 63.20 opposite bank bars N, N, W, + S, S, E,
- 67.80 Trail. bars W by N. + E by S.
- 68.15 Gulch 10 lks wide runs. E, S, E,
- 75.60 N.E. Cor. Log Cabin bars. S. 136, lks. dist.
- 78.25 Trail bars N, W, + S, E.

Subdivisions.

chs.
80.15 The Cor. to Secs. 17, 18, 19 & 20.
Land very rough & broken.
Soil stony & rocky 4th rate.
Timber Pine. 80.15 chs.

October 11, 1893.

N 89° 50' W. on a random line
bet. Secs. 18 & 19,
Va 13° 44' E

40.00 Set. temporary 1/4 Sec Cor.
95.55 Int. W. boundary of Tp. 23 lks.
S. of the Cor. to Secs. 13, 18, 19 & 24
as recently established by me,
Thurce Iron.

S 89° 40' E on a true line
bet. Secs. 18 & 19,
Va. 13° 44' E

In heavy Pine timber.

T. 13. N. R. 13. E.

chs.	
5.00	Bank trans. N.E. + S.W. descend.
17.80	Enter bottom
20.30	Gulch 20 lks wide. runs. N.E.
21.00	Trail. trans N.E. + S.W.
22.20	Leave bottom + ascend
28.10	Fence trans. N 80° E + S 80° W
43.00	Opposite bank trans. N.E. + S.W.
55.55	Set a Sandstone 18x12x5 ins. 13 ins in the ground. for. 1/4 Sec. Cor. marked 1/4 on N. face. where a Pine 22 ins. diam. trans N 74° W 87 lks. dist. A Pine 18 ins. diam. trans. S 60° E 100 lks. dist. marked 1/4 S 13. E.
69.40	Trail. trans. N.W. + S.E. ascend
70.62	Ridge trans. N.W. + S.E. descend
72.40	Enter bottom land trans N.W. + S.E.
82.10	Gulch 10 lks. wide runs. N.W.
83.00	Leave bottom + ascend.
85.10	Bank trans. N.W. + S.E.

Subdivisions.

chs.	
90.50	Trail brass. N.W. + S.E.
95.55	The Cor. to Secs. 17, 18, 19 + 20, Land nearly level. Soil. Sandy 1 st + 2 ^d rate, Timber Pine. 95.55 chs.
<hr/>	
	N 0° 3' W. bet. Secs. 17 + 18. Ta. 13° 44' E.
	In heavy Pine timber descend
2.30	Gulch 10 lbs wide runs. E. S. E. ^{ascend}
3.90	Trail brass. E. S. E. + W. N. W.
6.50	Bank brass. E. S. E. + W. N. W.
10.70	Pine 26 ins. diam. on line marked with 2 notches on N + S, Sides
20.00	Trail brass. N. E. + S. W.
40.00	Set a sand stone 18 x 10 x 5 ins. 18 ins. in the ground. for 1/4 Sec Cor, marked 1/4 on W. face. Whence a

T. 13. N. R. 13. E.

- Chs. Pine 14 ins. diam. bears $S 42^{\circ} W$
 69 lks. dist. marked $\frac{1}{4}$ S. B. J. -
 A Pine 7 ins. diam. bears $S 32^{\circ} E$
 52 lks. dist. marked $\frac{1}{4}$ S. B. J.
- 80.00 Set. a Sandstone $28 \times 10 \times 6$ ins
 20 ins. in the ground. for Gr. to
 Secs. 7, 8, 17 & 18, marked with
 4 notches on S. and 5 notches on
 E. edges. Whence
 A Pine 8 ins. diam. bears
 $N 59^{\circ} E$ 52 lks. dist. marked
 T. 13. N. R. 13. E. S. 8. B. J.
 A Pine 14 ins. diam. bears
 $S 78^{\circ} E$ 85 lks. dist. marked
 T. 13. N. R. 13. E. S. 17. B. J.
 A Pine 16 ins. diam. bears
 $S 38^{\circ} W$ 81 lks. dist. marked
 T. 13. N. R. 13. E. S. 18 B. J.
 A Pine 6 ins. diam. bears

Subdivisions.

chs. N 45° W 109 lks. dist. marked.
 T. 13. N. R. 13. E. S. 7 B. 1.
 Land level.
 Soil. gravelly 2^d + 3^d rate.
 Timber heavy Pine 80 chains.

East, on a random line.

bet. Secs. 8 & 17.

Va. 13° 44' E.

40.00 Set. temporary 1/4 Sec Cor.

80.07 Int. N. & S. line at Cor. to Secs. 8, 9,
 16 + 17. Thence Iron.

West, on a true line.

bet. Secs. 8 & 17.

Va. 13° 44' E

In heavy Pine timber

15.00 Trail. bears, N. W. & S. E.

28.30 Bank of Willow Cañon bears, N. N. E. & S. S. W.

Ascend

- chs.
35.15 Willow Cañon 50 lks. wide runs N.N.E.,
- 37.40 Leave bottom & ascend
- 40.04 Sec. a Sandstone 20x10x4 ins. 15 ins
in the ground. for 1/4 Sec. Cr.
marked 1/4 on N. face. where a
Pine 5 ins. diam. bears N48°W
50 lks. dist. marked 1/4 A. B. J. -
A Pine 12 ins. diam. bears S26°W
89 lks. dist. marked 1/4 A. B. J.
- 47.10 Opposite bank bears N.E. & S.W.
- 51.50 Bank bears N.E. & S.W. descend
- 55.55 Gulch 20 lks. wide runs N.E. ^{ascend}
- 64.00 Opposite bank bears N.E. & S.W.
- 80.07 The Cor. to Secs. 7, 8, 17 & 18.
Land rough & broken.
Soil. Stony 4th rate,
Timber Pine. 80.07 chs.

Subdivisions.

- cho. $N 89^{\circ} 40' W$. on a random line
bet. Secs. 7 & 18.
Ya. $13^{\circ} 44' E$.
- 40.00 Set. temporary $\frac{1}{4}$ Sec. Cor.
- 95.32 Int. W. boundary of Sp. 28 lks.
N. of Cor. to Secs. 7, 12, 13 & 18.
Thence I run.
 $S 89^{\circ} 50' E$ on a true line,
bet. Secs. 7 & 18.
Ya. $13^{\circ} 44' E$
In heavy Pine timber.
- 44.50 Bank trans. N. by E. & S. by W, descend
- 51.00 Enter bottom
- 53.60 Trail. trans. North by & South by
- 54.80 Gulch 20 lks. wide runs N. by, E. ^{ward}
- 55.32 Set. a Sandstone $18 \times 12 \times 3$ ins. 13 ins
in the ground. for $\frac{1}{4}$ Sec. Cor. Marked
 $\frac{1}{4}$ on N. face. whence a Pine 12
ins. diam. trans. $S 51^{\circ} E$. 56 lks

- Chs. 1 dist. marked $\frac{1}{4}$ S. B. T. —
 A Pine 20 ins. diam. bears N24°W
 51 lks. dist. marked $\frac{1}{4}$ S. B. T.
 6394 Pine 36 ins. diam. on line. marked
 with 2 notches on E. & W. sides.
 76.60 Opposite bank bears. N. & S.
 95.32 The Cor. to Secs. 7, 8, 17, & 18.
 Land. broken.
 Soil, gravelly 2^d & 3^d rate.
 Timber heavy Pine 95.32 chs.
 October 12, 1893.

N 0° 3' W. bet. Secs. 7 & 8.
 Ta 13° 44' E

In heavy Pine timber

- 33.80 Pine 28 ins. diam. on line. marked
 with 2 notches on N. & S. sides.
 40.00 Set a sandstone, 20x12x3 ins, 15 ins.

Subdivisions.

- Chs. in the ground. for $\frac{1}{4}$ Sec. Cor. marked
 $\frac{1}{4}$ on W. face. Whence a Pine 22 ins.
 diam. bears. $S77^{\circ}W$ 35 lks. dist.
 marked $\frac{1}{4}$ S. B. J. - A Pine 18 ins
 diam. bears. $N63^{\circ}E$ 54 lks. dist.
 marked $\frac{1}{4}$ S. B. J. -
- 64.90 Pine 30 ins. diam. on line. marked
 with 2 notches on N. & S. Sides.
- 74.50 Bank bears. N. by. E. & S. by. W. descend
- 80.00 Set. a Sandstone $24 \times 14 \times 4$ ins. 18 ins in
 the ground. for Cor. to Secs. 5, 6, 7 & 8.
 marked with 5 notches on S. N. E. edges
 whence A Pine 6 ins. diam. bears
 $N20^{\circ}E$ 49 lks. dist. marked
 S. 13. N. R. 13. E. S. 5. B. J.
 A Pine 20 ins. diam. bears
 $S15^{\circ}E$ 14 lks. dist. marked
 S. 13. N. R. 13. E. S. 8. B. J.
 A Pine 22 ins. diam. bears.

T. 13. N. R. 13. E.

Chs. S 54° W 146 lks. dist. marked
 T. 13. N. R. 13. E. S. 7. B. 4. —
 A Pine 12 ins. diam. trans.
 N 29° W 74 lks. dist. marked
 T. 13. N. R. 13. E. S. 6. B. 4. —
 Land nearly level.
 Soil gravelly 2^d rate.
 Timber heavy Pine 80 chains.

East. on a random line.

bet. Secs. 5 & 8.

Pa. 13° 44' E.

40.00 bet. temporary 1/4 Sec. Cor.

80.07 Int. N. & S. line at Cor. to Secs.

4, 5, 8 & 9. Thence Iron.

West. on a true line.

bet. Secs. 5 & 8.

Pa. 13° 44' E.

Subdivisions.

Chs.	In heavy Pine timber, descend
2.90	Gulch 20 lks. wide runs N.W. ^{ward}
7.50	Opposite bank trans. N.W. + S.E.
22.65	Right bank Willow Cañon trans N + S. ^{descend}
31.30	^{descend abruptly}
34.20	Willow Cañon 60 lks. wide runs N by W ^{ward}
40.03	Sandstone in place 36x24x18 ins. above ground. which I mark with Cross thus (+) 1/4 on N. face for 1/4 Sec Cor. Whence A Pine 20 ins. diam. trans. S. 5 lks. dist, marked 1/4 S. B.S. - A Pine 8 ins. diam. trans N 16° W 60 lks. dist, marked 1/4 S. B.S.
41.10	Opposite bank Willow Cañon trans N by W.
63.00	Bank trans. N.E. + S.W. descend
66.75	Gulch 10 lks. wide runs N.E. ^{ward}
68.50	Opposite bank trans. N.E. + S.W.
78.50	Bank trans. N by E. + S. by W. descend
80.07	The Cor. to Secs. 5, 6, 7 + 8, Land very rough + broken

T. 13. N. R. 13. E.

Chs. Soil. rocky 4th rate.
 Timber Pine. 80.09 chs.

N 89° 50' W on a random line
 bet. Secs. 6 & 7.

40.00 Va. 13° 44' E.

40.00 Set. temporary 1/4 Sec. Cor.

95.27 Int. W. boundary of Sp. at. Cor. to
 Secs. 1, 6, 7 & 12, as recently
 Established by me. Thence I run
 S 89° 50' E. on a true line
 bet. Secs. 6 & 7.
 Va 13° 44' E.

In heavy Pine timber

6.00 Bank trans. N.E. & S.W. descend

16.00 Descend abruptly.

18.00 Gulch 20 cks. wide. runs N.E. ^{ascend}

21.05 Pine 24 ins. diam. on line. marked

Subdivisions.

- Cho. with 2 notches on E. & W. Sides
 25.90 Opposite bank bears N.E. & S.W.
 27.25 Bank bears N.E. & S.W. descend.
 30.40 Gulch 10 lks. wide runs N.E. ^{and}
 40.50 Opposite bank bears N.E. & S.W.
 55.27 Set a sandstone 18x10x4 ins. 13
 ins. in the ground. for $\frac{1}{4}$ Sec Cor.
 marked $\frac{1}{4}$ on N. face, whence a
 Pipe 14 ins. diam. bears S 15° E
 64 lks. dist. Marked $\frac{1}{4}$ S. B.Y.
 An Oak 8 ins. diam. bears N 10° W
 26 lks. dist. marked $\frac{1}{4}$ S. B.Y. -
 64.00 Bank bears N.N.E. & S.S.W. descend
 69.20 Enter bottom.
 69.60 Gulch 20 lks. wide runs N.N.E.
 70.00 Trail bears N.N.E. & S.S.W.
 70.10 Leave bottom & ascend.
 76.20 Opposite bank bears N.N.E. & S.S.W.
 95.27 The Cor. to Secs. 5, 6, 7, & 8.

T. 13. N. R. 13. E.

chs. Land broken.
Soil. Sandy & gravelly 3^d & 4th rate.
Timber Heavy Pine 95.27 chs.

N^o 2' W. on a random line.
bet. Secs. 5 & 6.
Va. 13° 44' E.

40.00 Set. temporary 1/4 Sec. Cr.
80.08 Int. N. boundary of Sp. 7 lks W.
of Cor. to Secs. 5, 6, 31 & 32 as
recently established by me
Thence Iron.

S 0° 1' W on a true line.
bet. Secs. 5, & 6.
Va. 13° 44' E.

3.00 Leaves bottom & ascend
7.25 Ridge runs N.E. & S.W. descend
9.00 Gulch 20 lks. wide runs N.E.

Subdivisions T. 13. N. R. 13. E.

- 15.00 Recross same 20 lks. wide runs. N.W.
- 19.60 Recross same 20 lks wide runs. N.E
- 24.80 Recross same 20 lks wide runs. N.W
- 29.30 Recross same 20 lks wide runs N.E, ^{and}
- 34.50 End of abrupt ascent.
- 38.00 Bank bears. N.E. & S. by W.
- 40.08 Set a Sandstone 18x8x8 ins. 13 ins
in the ground. for 1/4 sec Cr. marked
1/4 on W. face. whence a Pine 10
ins. diam. bears. N83°W 13 lks.
dist. marked 1/4 S. B.T. - An Oak
8 ins. diam. bears. S 22° E 54
lks. dist. marked 1/4 S. B.T. -
- 55.35 Pine 20 ins. diam. on line marked
with 2 notches on N & S. sides.
- 80.08 The Cor. to Secs. 5, 6, 7, & 8.
Land very rough & broken
Soil. gravelly & rocky 3^d & 4th rate
Timber Pine & Oak. 80.08 chs.
October 13. 1893.

The whole of this township is covered by heavy Pine & oak timber, and 60. miles 68 chains and 75 links. run through the same.

General Description.

This township consist in the main of level land except where the Cañons traverse the same. the soil is of a gravelly sandy nature. producing an enormous growth of heavy Pine timber.

Willow Cañon of immense proportions. with rough and precipitous sides. traverses this Tp. in a northerly direction

Containing water at all seasons.
Native grasses thrive, and
Cattle Horses & Sheep, graze
over this Tp. -

There is one Cabin in Sec. 20.
No Settlers in the Tp.

The mean declination
for the plat. the average
of 5 observations is $13^{\circ}44'E$

David Drummond
U.S. Deputy Surveyor.

U. S. Surveyor -General's Office.

Tucson, A. T. October 9th. 1895.

The foregoing field-notes of the Surveys of the Subdivisions of Township No, 13, N, Range No 13 East, Gila and Salt River Meridian in Arizona, executed by

DANIEL DRUMMOND

U. S. Deputy Surveyor, under his Contract dated Febry, 21st, 1893, having been critically examined, the necessary corrections and explanations made, the said Field Notes and the surveys they describe are hereby approved.

Levi H. Manning

U. S. Surveyor-General,

for the Territory of Arizona.