

No-149

P. 1

# Field Notes

OF THE SURVEY OF THE

*SUBDIVISION LINES*

—OF—

*Township 14 North Range 10 East*

*Gila and Salt River Base and Meridian*

**ARIZONA.**

By *Thos. F. White* D. S.

*under contract dated Aug 27, 1880.*

*Survey commenced Aug 8, 1881.*

*Survey completed Aug 13, 1881.*

No-149

149

Copies

Field Notes  
of L.

1B

INDEX DIAGRAM.

Township 14 N

BOOK 149

1A

Range 10 E

68	70	5	52	4	40	3	27	2	14	1
69		68		57		38		26		13
7	67	8	50	9	37	10	24	11	11	12
66		65		49		36		23		10
18	64	17	48	16	35	15	22	14	9	13
63		61		47		34		21		8
19	60	20	45	21	32	22	20	23	6	24
59		58		44		31		19		5
30	57	29	43	28	30	27	17	26	4	25
56		55		42		29		16		3
31	53	32	41	33	28	34	15	35	1	36

Gila and Salt River Meridian.

ARIZONA.

10

# Preliminary Oaths of Assistants.

We, *J. H. McElure*

and *H. J. Bargmann*

do solemnly swear that we will faithfully execute the duties of Chain Carriers; that we will level the chain upon uneven ground, and plumb the tally pins, whether by sticking or dropping the same; that we will report the true distance to all notable objects, and the true length of all lines that we assist in measuring, to the best of our skill and ability.

*J. H. McElure*  
*H. J. Bargmann*

Sworn to and subscribed before me, this *1<sup>st</sup>*

day of *Aug.*, 18*81*

*William J. Osburn*  
Notary Public  
*Irma Co., N.Y.*

We, *John Blake*  
*Hugh Dobbinis* and *L. J. Bargmann*

do solemnly swear that we will well and truly perform the duties of *Assessors*

*Mountain & Hagman* respectively

according to instructions given us, and to the best of our skill and ability.

*John Blake*  
*Hugh Dobbinis*

*L. J. Bargmann*

Sworn to and subscribed before me this *1st*

day of *August*, 18*87*

*William A. Sherman*  
Notary Public  
Pima Co., Ariz.



T. 14. N. R. 10. E. G. & S. R. M.

cks

build mound of earth 2 ft high.  
with pile, 18 x 18 x 12 ins as per  
instructions for 1/4 sec. cor,  
from which bears a  
Pile 37 ins. dia. S. 30° E 12 lbs dist.  
a Pile 10 ins. dia. N. 40° W. 50 lbs dist.

67.70 Rocky Gulch 50 lbs wide course S. W.

80.00 Set a post marked & notched 4 ft long  
4 ins. sq. with marked stone 12 ins.  
in the ground and build a mound  
of stone 2 ft high. as per instructions  
for cor. to secs. 25. 26. 35 & 36.

from which bears a  
Pile 12 ins. dia. S. 35° E 43 lbs dist.  
a Pile 22 ins. dia. N. 40° E. 23 lbs dist.  
a Pile 12 ins. dia. N. 41° W. 105 lbs dist.  
a Pile 24 ins. dia. S. 39° W. 127 lbs dist.

Very broken, Soil 3<sup>d</sup> rate  
Heavy pine timber, some  
spruce & oak.

N. 14. N. R. 10. E. G. & S. R. M.

class

East on a random line bet. Secs. 25 & 36.

Var  $14^{\circ} 15' E$ .

- 19.00 Rocky gulch 30 lbs wide course S. W.  
 29.20 Enter high table land.  
 40.00 Set temporary  $\frac{1}{4}$  sec cor.  
 80.26 Intersect E. B. of T<sub>p</sub>. 19 lbs S. of the  
 cor. to Secs. 25. 30. 31 & 36, which  
 was recently established by me, and  
 is here before fully described in my  
 field notes. from this cor. I run  
 $S 89^{\circ} 52' W$ . on true line bet. Sec 25 & 36.

Var.  $14^{\circ} 15' E$ .

- 40.13 Set a post marked  $\frac{1}{4}$  S. 4 ft long  
 flattened 3 ins. wide, with marked  
 stone, 12 ins. in the ground and  
 build up of stone 2 ft high as  
 per instructions for  $\frac{1}{4}$  sec. cor.  
 from which bears a  
 Pin 24 ins. dia. N.  $45^{\circ} W$ . 2 lbs dist.  
 a Pin 25 ins. dia. S.  $50^{\circ} W$ . 19 lbs dist.

P. 14. N. R. 10. E. G. x S. R. M.

chs

80.26 Cor to Secs. 25.26. 35 & 36.

Broken, Soil 3<sup>d</sup> rate  
Thick pine timber, throughout  
with some oak and under growth.

North between Secs. 25 & 26.

Var. 14° 15' E.

6.50 Enter high table land

40.00 Set a post marked  $\frac{1}{4}$  S. 4 ft  
long flattened 3 ins. wide, with  
marked stone, 12 ins. in the  
ground & build mound of stone  
2 ft high, as per instructions.  
for  $\frac{1}{4}$  sec. cor.

from which bears.

a Pine 16 ins. dia. East. 10 lks dist

a Pine 23. ins. dia. S. 48° W. 12 lks dist.

80.00 Set a post marked & notched  $\frac{1}{2}$   
long 4 ins. sq. with marked stone  
12 ins. in the ground and build,

N. 14. N. R. 10. E. G. & S. R. M.

Chs

mound of stone 2 ft high, as per  
instructions for cor. to Secs. 24, 25, 23 & 26,  
from which bears a

Pine 8 ins. dia. S. 74° E. 67 lks dist

a Pine 15 ins. dia. S. 72° W. 61 lks dist.

a Pine 13 ins. dia. N. 9° W. 72 lks dist

a Pine 30 ins. dia. N. 33° E. 171 lks dist.

Mostly flat table land Soil 3<sup>d</sup> rate.  
Thick Pine timber throughout,  
and undergrowth.

East on random bet. Secs. 24 & 25.

Var. 14° 15' E.

4000 Set a temporary 1/4 Sec. cor.

80.12 Intersect E. B. of Tp. 22 lks N. of  
the cor. to Secs. 19, 24, 25 & 30.

from which cor. I run,

N. 89° 51' W. on true line bet.

Secs. 24 & 25,

Var. 14° 15' E.



S. 14. <sup>BOOK 149</sup> N. R. 10. E. G & S. R. M.

chs

40.06 Set a post marked  $\frac{1}{4}$  S. 4 ft long flattened 3 ins. wide, with marked stone, 12 ins. in the ground, and build and set stone off high, esp. instructions for  $\frac{1}{4}$  sec. cor.

from which bear a  
Pine 24 ins. dia. S. 55° W. 88 lbs dist  
a Pine 26 ins. dia. N. 45° W. 42 lbs dist.

80.12 Cor to Secs. 23, 24, 25, 26.

Plot or slightly undulating  
Thick pine throughout, with  
undergrowth.

North bet. <sup>Secs</sup> 23 & 24

Var. 14° 15' E.

40.00 Set a post marked  $\frac{1}{4}$  S. 4 ft long flattened 3 ins. wide, with marked stone, 12 ins. in the ground and build and

S. 14. N. R. 10. E. G. & S. P. M.

Obs

of stones 2 ft high, as per instruction for 1/4 Sec. cor.

from which bears

a Pine 39 ins. dia. S 53° W. 12 lbs dist.

a Pine 10 ins. dia. N. 47° E. 138 lbs dist.

8000 Set a post marked & notched, 4 ft long 4 ins. sq. with marked stone, 12 ins. in the ground, and build end of stone 2 ft high, as per instructions for cor to Secs. 13, 14, 23, 24.

from which bears.

a Pine 12 ins. dia. S. 50° W. 3 lbs dist.

a Pine 13 ins. dia. N. 31° W. 14 lbs dist.

a Pine 11 ins. dia. N. 32° E. 30 lbs dist.

a Pine 16 ins. dia. S. 42½° E. 134 lbs dist.

Undulating Soil 2<sup>d</sup> rate  
Heavy pine & undergrowth.

S. 14 N. <sup>BOOK 149</sup> 10. E. G. & S. R. M.

Chs

East on random line bet. Secs 13 & 24  
Per.  $14^{\circ} 15' E.$

15.00 Leave high table land & descend.

39.80 Head of ravine course N. E.

~~40.00~~ Set a temporary  $\frac{1}{4}$  Sec cor.

80.04 Intersect E. B. of Tp. 11 lbs N. of  
the cor. to Secs. 13. 18. 19. 24.

from this cor. Run  
N.  $89^{\circ} 55' W.$  on true line  
bet. Secs. 13 & 24.

Per.  $14^{\circ} 15' E.$

40.02 Set a post marked  $\frac{1}{4}$  S. 4 ft  
long flattened 3 ins. wide, with  
marked stone, 12 ins. in the  
ground & build end of stone  
1 ft high as permanent for  $\frac{1}{4}$  Sec. <sup>see Plan</sup>  
from which bears.

a Pine 26 ins. dia. N.  $57^{\circ} E.$  23 lbs dist

a Pine 12 ins. dia. S.  $32^{\circ} E.$  37 lbs dist.

80.04 Cor to Secs. 13. 14. 23 & 24

S. 14. N. R. 10. E. G. & S. P. M.

Chs

Broken, Soil 3<sup>d</sup> rate.

Heavy pine timber, Some  
oak & fir. Dense undergrowth.

North between Secs. 13 & 14.

Cor.  $14^{\circ} 15' E$ .

39.00 Descend from table land,

40.00 Set a post marked  $1/4 S$ , 4 ft  
long flattened 3 ins. wide, with  
marked star, 12 ins in the ground  
and build end of star 2 ft high,  
as per instructions for 14 Sec. Cor.  
from which bears.

An Oak 8 ins. d.i.e. West 3 Chs dist

An Oak 10 ins. d.i.e.  $S. 21^{\circ} E$ . 10 Chs dist.

65.00 Ascend to table land again.

80.00 Set a post marked & notched, 4 ft  
long 4 ins sq. with marked star  
12 ins. in the ground and build end  
of star 2 ft high, as per instructions.

BOOK 149

S. 14. N. R. 10. E. G. &amp; S. R. M.

Chs

for cor. to Secs. 11. 12. 13 & 14.  
from which bears.

a Pine 18 ins. dia. S. 20° W. 64 lbs dist

a Pine 16 ins. dia. S. 52½° E. 107 lbs dist

a Pine 12 ins. dia. N. 22° E. 171 lbs dist.

a Pine 12 ins. dia. N. 60° W. 116 lbs dist.

Broken Soil 3<sup>d</sup> rateHeavy pine timber, and thick  
undergrowth.

East on random line bet. Secs 12 &amp; 13.

Var. 14° 15' E.

4000

Set a temporary 1/4 Sec. cor.

Descend from table land.

52.00

79.90

Intersect E. B. of Tp. 21 lbs N. of  
the cor. to Secs. 7. 12. 13. & 18.

From this cor. I run.

N. 89. 57' W. on true line bet. Secs 12 &amp; 13.

Var. 14° 15' E.

39.95 Set a post marked 1/4 S. 4 ft long  
flattened 3 ins. wide, with

S. 14. N. R. 10. E. G. & S. R. M.

chs

marked stone, 12 ins. in the ground, and build end of stone 4ft high, as per instruction ins for 1/4 sec. cor.

from which bears a  
a Pine 14. ins. dia. N. 71° E. 55 lbs. dist.  
a Pine 18. ins. dia. S. 53° E. 131 lbs. dist.

79.90 Cor. to Secs. 11, 12, 13 & 14. ✓

Broken Soil 3<sup>d</sup> rate

Heavy pine and thick undergrowth.

North between Secs. 11 & 12.

Var 14° 15' E.

5.00 Descend from table land,

40.00 Set a post marked 1/4 S. 4ft long flattened 3 ins. wide, with marked stone, 12 ins. in the ground, and build end of cart 4ft high, with pits 18x18x12 ins as per instructions for 1/4 sec. cor. ✓

S. 14. N. R. 10. E. G. & L. R. M.

chs

from which bears.

a Pine 8 ins. dia. S. 45° W. 10 lbs dist

a. Pine 10 ins. dia. S. 31° E. 6 lbs. dist

45.00 Dry Wash 20 lbs wide come N. E.

80.00 Set a post marked & watched 4ft  
long 4 ins. sq. with marked stone  
12 ins. in the ground, and build  
mound of earth 2ft high, with  
pits 18x18x12 ins. as per instructions  
for Cor. to Secs. 1. 2. 11 & 12.

from which bears.

a Pine 30 ins. dia. S. 24° E. 11 lbs dist.

a. Pine 8 ins. dia. S. 71° W. 13 lbs. dist.

a Juniper 27 ins. dia. N. 66° E. 22 lbs dist.

a Pine 10 ins. dia. N. 44° W. 54 lbs dist.

Broken Descending N & E.

Soil 3d rate Heavy pine,

Undergrowth

August 8. 1881.

BOOK 149

S. 14 N. R. 10 E. G. &amp; S. R. M.

chs

East on random line bet. Secs. 14 &amp; 12

Var.  $14^{\circ} 15' E.$ 40.00 Set a temporary  $1/4$  Sec. cor.50.50 Gully in ravine 20 lbs wide corner N. W.  
thence N. E.80.12 Intersect the E. B. of Sp. 22 Chs N.  
of the cor. to Secs. 1. 6. 7. & 12  
from this cor. I own.N.  $89^{\circ} 51' W.$  on true line bet Secs. 14 & 12Var  $14^{\circ} 15' E.$ 

31.40 a Pine 40 ins. dia

40.06 Set a post marked  $1/4$  S. 4 ft long  
flattened 3 ins. wide, with marked  
stone, 12 ins. in the ground, and brick  
end of stone 4 ft high, as per inst  
sections for  $1/4$  sec. cor.

from which bears.

a Pine 15 ins. dia.  $S 74^{\circ} E.$  25 lbs dist.a Pine 18 ins. dia. N.  $87^{\circ} E.$  38 lbs dist.

80.12 Cor to Secs. 1. 2. 11 &amp; 12.

Rolling & broken soil 3<sup>d</sup> rate ✓



T. 14 N. R. 10. E. G. & S. R. M.

chs

Heavy pine timber; & brush.

North on a random line bet Secs. 1 & 2  
 Var.  $14^{\circ} 15' E.$

40.00 Set temporary  $\frac{1}{4}$  sec. cor.

55.00 Run 100 lks wide course N. E.

79.89 Intersect N. boundary 15 lks W.  
 of cor. to Secs. 1 & 2. <sup>35936</sup> from  
 which cor. I run.

S. 0.6' W. on true line bet Secs. 1 & 2.  
 Var.  $14^{\circ} 15' E.$

39.89 Set a Post marked  $\frac{1}{4}$  S. 4 ft long  
 flattened 3 ins. wide, with marked  
 stone, 12 ins. in the ground and build  
 mound of stone 2 ft high, as per  
 instructions for  $\frac{1}{4}$  sec. cor.  
 from which bear.

a Pine 16 ins. dia. S.  $19^{\circ}$  W. 40 lks dist

a Pine 26 ins. dia. S.  $33^{\circ}$  E. 48 lks dist.

79.89 Cor to Secs 1, 2, 11 & 12.

S. 14 N. R. 10. E. G. & S. R. M.

chs

Rolling & broken Soil 3<sup>d</sup> rate  
Heavy pine timber throughout  
Thick undergrowth.

From the cor. to Secs. 34 & 35  
2 x 3. on S. B. of Sp. 9 run  
North between Secs. 34 & 35.

Var.  $14^{\circ} 15'$  E.

26.00 Enter high table land.

40.00 Set a post, marked  $\frac{1}{4}$  S. 4 ft  
long flattened 3 ins. wide, with  
marked stone, 12 ins. in the ground  
and build mound of stone 2 ft high  
as per instructions for  $\frac{1}{4}$  sec cor.  
from which bears.

A Pine 21 ins. dia. N.  $24\frac{1}{2}^{\circ}$  E. 87 lbs dist  
An Oak 10 ins. dia. S.  $18^{\circ}$  W. 66 lbs dist.

42.36 A Pine 20 ins. dia.

80.00 Set a post marked & notched 4 ft long  
4 ins. sq. with marked stone, 12 ins. in.

BOOK 149

S. 14. N. R. 10. E. G. &amp; S. R. M.

chs

the ground, build md of earth 4 ft  
high, with pits 18x18x12 ins. each  
instructions for cor to Secs.

26. 27. 34 &amp; 35.

from which bears.

An Oak 10 ins. dia. N.  $87^{\circ}$  E. 75 lks dist

A Pine 12 ins. dia. S.  $80^{\circ}$  E. 106 lks dist.

A Pine 16 ins. dia N.  $77^{\circ}$  W. 54 lks dist

A Pine 11 ins. dia. S.  $72^{\circ}$  W. 58 lks dist.

Ascending N. Soil 3<sup>d</sup> rate  
Heavy pine throughout.

East on a random line bet. Secs 26 & 35.

Var  $14^{\circ} 15' E.$

40.00 Set a temporary  $1/4$  sec cor.

80.22 Intersect the N. & S. line 18 lks N.  
of the cor. to Secs. 25, 26, 35 & 36.

from which I run.

N.  $89^{\circ} 52' W.$  on true line bet. Secs 26 & 35.

Var.  $14^{\circ} 15' E.$

S. 14. N. R. 10. E. of S. S. R. M.

Chs.

40.11 Set a post marked  $\frac{1}{4}$  S. 4 ft long flattened 3 ins. wide, with marked stone, 12 ins. in the ground and build end of center 2 ft high, with pits  $18 \times 18 \times 12$  ins. as per instruction for  $\frac{1}{4}$  sec. cor.

from which bears.

a. Pine 20 ins. dia. N.  $12^\circ$  W. 39 lbs dist  
 a Pine 18 ins. dia. S.  $24^\circ$  E. 143 lbs dist.

80.22. Cor. to Secs. 26, 27, 34 & 35,

Plat on W. broken on E.

Heavy pine timber throughout with undergrowth.

North bet. Secs 26 & 27.

Var.  $14^\circ 15'$  E.

40.00 Set a post marked  $\frac{1}{4}$  S. 4 ft long, flattened 3 ins. wide, with marked stone, 12 ins. in the ground, and build end of stone

BOOK 149

S. 14 N. R. 10 E. G. &amp; S. R. M.

chs

4 ft high, as per instructions  
for 1/4 sec. cor.

from which bears.

a Pine 14 ins. dia. N. 38° E. 122 lbs dist.

a Pine 28 ins. dia. N. 43° W. 94 lbs dist.

43.44 a Pine 22 ins. dia.

55.81 a Pine 27 ins. dia.

80.00 Set a post in marked & notched 4 ft  
long 4 in. sq. with marked stones  
12 ins. in the ground, and build  
end of stone, 4 ft high, as per  
instructions for cor. to Secs.

22. 23. 26. & 27.

from which bears.

a Pine 16 ins. dia N. 24° W. 181 lbs dist

a Pine 39 ins. dia. S. 16° W. 240 lbs dist

a Pine 40 ins. dia. S. 63 1/2° E. 98 lbs dist.

a Pine 10 ins dia. S. 34° E. 77 lbs dist.

Plat Soil 3<sup>d</sup> rate Heavy pine  
timber, and undergrowth of oak & blue.

S. 14. N. R. 10. E. G. & S. R. M.

chs.

East on a random line bet Secs. 26 & 23.

Var.  $14^{\circ} 15' E$ .

40.00 Set a temporary  $1/4$  Sec. cor.

80.10 Intersect the N & S. line 18 lks S.  
of the cor. to Secs. 23, 24, 25 & 26  
from which I run.

S.  $89^{\circ} 52' W$ . on true line bet Secs. 23 & 26.

Var  $14^{\circ} 15' E$ .

40.05 Set a post marked  $1/4$  S. 4 ft long  
flattened 3 ins. wide, with marked  
stap, 12 ins. in the ground and 1/2 in.  
end of stap 2 ft. high, as per inst  
section for  $1/4$  sec. cor.

from which bears.

a Pine 16 ins. dia. S.  $58^{\circ} W$ . 60 lks dist

a Pine 28 ins. dia. N.  $60^{\circ} W$ . 17 lks dist.

80.10 Cor to Secs. 22, 23, 26 & 27.

Plat. Soil 3<sup>d</sup> rate

Heavy Pine timber throughout.  
and undergrowth.

BOOK 149

S. 14 N. R. 10. E. G. &amp; S. R. M.

chs

North bet. Secs. 22 &amp; 23.

Var.  $14^{\circ} 15' E.$ 

4000 Set a post marked  $\frac{1}{4}$  S. 4 ft long  
flattened 3 ins. wide, with marked  
stone, 12 ins. in the ground and  
built mid of stone 2 ft high,  
as per instructions for  $\frac{1}{4}$  Sec cor.  
from which bears.

A Pin 10 ins. dia. N.  $46^{\circ} W.$  60 lbs dist.A Pin 25 ins. dia. N.  $70^{\circ} E.$  123 lbs dist.

8000 Set a post marked & notched 4 ft long  
4 ins. sq. with marked stone, 12 ins. in  
the ground and built mid of stone  
2 ft high, as per instructions for cor. to Secs.  
14. 15. 22 & 23

from which bears.

A Pin 30 ins. dia. S.  $62^{\circ} W.$  43 lbs dist.A Pin 16 ins. dia. S.  $30^{\circ} E.$  6 lbs dist.A Pin 24 ins. dia. N.  $28^{\circ} E.$  14 lbs dist.A Pin 26 ins. dia. N.  $65^{\circ} W.$  8 lbs dist.

S. 14 N. R. 10 E. G. & S. P. M.

chs

Undulating, Soil 2<sup>d</sup> rate  
Heavy pine timber all along.

East on a random line, bet. Secs 14 & 23.

Var.  $14^{\circ} 15' E.$

4000 Set a temporary  $\frac{1}{4}$  sec. cor.

79.95 Intersect the N & S line 10 lks S.  
of the cor. to Secs. 13, 14, 23 & 24.  
from which I run.

S.  $89^{\circ} 56' N.$  on a true line bet. Sec 14 & 23

Var.  $14^{\circ} 15' E.$

39.98 Set a post marked  $\frac{1}{4}$  S.  $4\frac{1}{2}$  long  
flattened 3 ins. wide, with  
marked stone, 12 ins. in the ground  
and build mound of stones off high  
as per instructions for  $\frac{1}{4}$  sec. cor.  
from which bears.

a Pine 18 ins. dia. South, 63 lks dist

a Pine 16 ins. dia. N.  $43^{\circ} N.$  96 lks dist.

79.95 Cor to Secs. 14, 15, 22 & 23. ✓



BOOK 149  
 T. 14 N. R. 10. E. G. & S. P. M.

chs

Undulating, high table land,  
 soil 2<sup>d</sup> rate  
 Heavy pine timber, and  
 undergrowth.

North bet. Secs. 14 & 15.

Var 14° 15' E.

40.00 Set a post marked  $\frac{1}{4}$  Sec. 4 ft long  
 flattened 3 ins. wide, with marked  
 stone 12 ins. in the ground, and  
 build out of stone 2 ft high,  
 as per instructions for  $\frac{1}{4}$  sec cor.  
 from which bears.

a Pine 20 ins. dia. N. 38 $\frac{1}{2}$ ° E. 44 lbs dist.

a Pine 36 ins. dia. N. 23 $\frac{1}{2}$ ° W. 119 lbs dist.

51.00 Cross head of gulch 20 lbs course N. W.

80.00 Set a post marked & watched 4 ft  
 long 4 ins sq. with marked stone 12 ins.  
 in the ground, and build out of  
 stone 2 ft high, as per inst. for cor.

S. 14 N. R. 10 E. of S. R. M

chs

to Secs. 10, 11, 14 & 15,

from which bears.

An Oak 8 ins. dia. N.  $36^{\circ}$  E. 105 lks dist

A Pine 16 ins. dia. N.  $42^{\circ}$  W. 17 lks dist

A Pine 28 ins. dia. S.  $20^{\circ}$  E. 74 lks dist

A Pine 24 ins. dia. S.  $37^{\circ}$  W. 98 lks dist.

Rolling Soil 3d rate

Heavy pine timber throughout.

August 9, 1881.

East on random line bet. Secs. 11 & 14

Var.  $14^{\circ} 15' E.$

37.00 Ravine 10 lks wide course N. E.

40.00 Set temporary  $\frac{1}{4}$  Sec cor.

49.00 Ravine 10 lks wide course N.

80.13 Intersect the N & S. line 18 lks N. of  
cor. to Secs. 11, 12, 13 & 14.

from which I run.

N  $89^{\circ} 52' W.$  on true line bet. Secs. 11 & 14.

Var.  $14^{\circ} 15' E.$  ✓

N. 14 N. R. 10. E. G. & S. R. M.

chs

40.06 Set a post marked  $\frac{1}{4}$  S. 4 ft long, flattened 3 ins. wide, with marked stone, 12 ins. in the ground and build mound of stone 2 ft high, see instructions for ~~the~~ bee. cor. from which bears.

An Oak 8 ins. dia. N.  $75^{\circ}$  E. 15 lbs dist.

a Pine 26 ins. dia. S.  $50^{\circ}$  W. 43 lbs dist.

80.13. Cor to Secs. 10. 11. 14 & 15.

Broken Soil 3<sup>d</sup> rate

Heavy pine timber, some oak and undergrowth.

North bet. Secs. 10 & 11.

Var.  $14^{\circ} 15' E$ .

18.00 Ravine 200 lbs wide course N.E.

40.00 Set a post marked  $\frac{1}{4}$  S., 4 ft long flattened 3 ins. wide, with marked stone, 12 ins. in the ground and build mound of stone 2 ft high

N. 14 N. R. 10. E. G. & S. R. M.

chs

as per instructions for 1/4 sec. cor  
from which bears.

a Pine 10 ins. dia. N. 50° W. 52 lks dist.

An Oak 12 ins. dia. N. 35° E. 45 lks dist.

45.00 Ascend top of high table land

56.00 Descend from table land

80.00 Set a post marked & notched 4 ft  
long 4 ins. sq. with marked stem  
12 ins. in the ground, and build  
mound of earth, with pits 18 x 18 x 12  
ins. as per instructions for Cor to Secs.  
2, 3, 10 & 11.

from which bears.

a Pine 16 ins. dia. S 40° W. 119 lks dist

An Oak 10 ins. dia. N. 68° E. 45 lks dist

a Pine 30 ins. dia. S. 43° E. 62 lks dist.

a Pine 28 ins. dia. N. 21° W. 246 lks dist.

Rolling soil 3<sup>d</sup> rate

Heavy pine timber, all along

BOOK 149

v. 14 N. R. 10. E. G. &amp; S. R. M.

Chs.

East on a random line bet. Secs 2 &amp; 11.

Var.  $14^{\circ} 15' E$ .40.00 Set a temporary  $\frac{1}{4}$  sec cor.

42.00 Ascend to top of N. slope of hill.

80.17 Intersect the N. & S. line 30 lks S.  
of cor. to Secs. 1, 2, 11, & 12.

from which I run.

 $S 89^{\circ} 47' W$ . on true line bet Secs 2 & 11.Var.  $14^{\circ} 15' E$ .40.08 Set a post marked  $\frac{1}{4}$  S. 4 ft long  
flattened 3 ins. wide with marked  
stone, 12 ins. in the ground, and  
build end of stone 2 ft high, as per  
instruction for  $\frac{1}{4}$  sec cor.

from which bear.

an Oak 8 ins. dia. N.  $64^{\circ} E$ . 57 lks dist.a Pine 30 ins. dia. S.  $28^{\circ} E$ . 80 lks dist.

80.17 Cor. to Secs. 2, 3, 10 &amp; 11.

Hilly & broken, Soil 3<sup>d</sup> rate

Heavy pine timber &amp; brush.

S. 14 N. R. 10 E. G & S. R. M.

Chs.

North on random line bet Secs. 2 & 3.

Var  $14^{\circ} 15' E.$

46.00 Set temporary  $\frac{1}{4}$  sec. cor.

44.00 Dry wash 20 lbs wide in little valley cor. N. E.

80.07 Intersect N. B. 9 lbs. E. of cor. to Secs.  
2 & 3, <sup>34 & 35</sup> from which cor. I run.

S.  $0^{\circ} 4' E.$  on true line bet. Secs. 2 & 3.

Var.  $14^{\circ} 15' E.$

40.07 Set a post marked  $\frac{1}{4}$  S.  $4\frac{1}{2}$  long  
flattened 3 ins. wide, with marked  
stone, 12 ins. in the ground, and  
build mid of earth 2 ft high, with pits  
 $18 \times 18 \times 12$  ins as per instructions for  
 $\frac{1}{4}$  sec cor.

from which bears.

a. Post 25 ins. dia. S.  $10^{\circ} W.$  128 lbs dist.

a. Post 10. ins. dia. S.  $28^{\circ} E.$  112 lbs dist.

80.07 Cor. to Secs. 2. 3. 10 & 11.

Rolling soil good along little  
Valley, heavy pine timber, all along. ✓

C. 14 N. R. 10 E. G. & S. R. M.

Chs.

From the cor. to Secs. 33 & 34. 3 & 4  
on S. B. of Tp. 2 run  
North between Secs. 33 & 34  
Var.  $14^{\circ}15' E$

40.00 Set a post marked  $\frac{1}{4}$  S. 4 ft  
long, flattened 3 ins. wide, with  
marked stone, 12 ins. in the  
ground and build end of stone  
2 ft high, as per instruction for  $\frac{1}{4}$  sec. cor.  
from which bears.

a. Pine 17 ins. dia. S.  $17^{\circ} E$ . 76 lks dist.

a. Pine 18 ins. dia. S.  $45^{\circ} W$ . 50 lks dist.

80.00 Set a post marked & notched 4 ft long  
4 ins. sq. with marked stone 12 ins.  
in the ground, and build end of  
stone 2 ft high, as per instruction for  
Cor. to Secs. 27, 28, 33 & 34.  
from which bears.

a. Pine 18 ins. dia. N.  $40^{\circ} W$ . 140 lks dist.

a. Pine 24 ins. dia. N.  $83^{\circ} E$ . 121 lks dist.

T. 14 N. R. 10 E. G. & S. R. M.

Chs

a Pine 28 ins. dia. S.  $24^{\circ}$  W. 48 lks dist.

a Pine 27 ins. dia. S.  $53^{\circ}$  E. 46 lks dist.

Undulating Soil 2<sup>d</sup> rate

Heavy pine timber, throughout

East on a random line bet.

Secs. 27 & 34

Var.  $14^{\circ} 15'$  E.

40.00 Set a temporary  $\frac{1}{4}$  sec. cor.

80.16. Intersect the N & S. line 9 lks N. of the cor. to Secs. 26, 27, 34 & 35. from which I run.

N. 89.56' W. on true line bet. Secs 27, 34.

Var.  $14^{\circ} 15'$  E.

40.08 Set a post marked  $\frac{1}{4}$  S. 4 ft long flattened 3 ins. wide with marked stone, 12 ins in the ground, and build mid of stone 2 ft high as per instructions for  $\frac{1}{4}$  sec. cor. from which bears.



S. 14 <sup>7<sup>th</sup> 149</sup> R. 10 E. G. & S. R. M.

chs

a. Pine 10 ins. dia. S. 35° E. 102 lks dist.  
 An Oak 8 in dia N. 32° W. 41 lks dist.

80.16 Cor to Secs. 27. 28. 33 & 34.

Flat Soil 3<sup>d</sup> rate

Thick pine timber throughout  
 Some Oak.

North between Secs. 27 & 28.

Var 14° 15' E.

4000 Set a post marked  $\frac{1}{4}$  S. 4 ft long  
 flattened 3 ins. wide, with  
 marked stone, 12 ins. in the  
 ground, and build end of stone  
 2 ft high as per instructions for  $\frac{1}{4}$  sec cor.  
 from which bears.

a. Pine 12 ins. dia. S. 63° E. 28 lks dist.

a. Pine 29 ins. dia. N. 22° W. 57 lks dist.

80.00 Set a post marked & notched  $\frac{1}{4}$  ft  
 long 4 ins. sq. with marked stone  
 12 ins. in the ground and build

BJJK 149

S. 4 N. R. 10 E. G &amp; S. R. M.

cho

mid of stone left high, esp.  
 instructions for. cor. to Secs.  
 21. 22. 27 & 28.

from which bears.

An Oak 8 ins. dia. S.  $64^{\circ}$  E. 107 lks dist

An Oak 12 ins. dia. S.  $23^{\circ}$  W. 78 lks dist.

A Pine 13 ins. dia. N.  $77\frac{1}{2}^{\circ}$  E. 100 lks dist

A Pine 50 ins. dia. N.  $43^{\circ}$  W. 102 lks dist.

Rolling Soil 2<sup>d</sup> rate

Thick pine timber, throughout  
 some oak.

East on random line bet. Secs 22 & 27  
 Var  $14^{\circ} 15' E.$

40.00 Set temporary  $\frac{1}{4}$  sec. cor.

79.84 Intersect the N & S. line 21 lks N.  
 of the cor. to Secs. 22. 23. 26 & 27.  
 from which I run.

N.  $89^{\circ} 51'$  W on true line bet. Secs 22 & 27  
 Var.  $14^{\circ} 15' E.$  ✓

BOOK 149

S. 14 N. R. 10. E. G. &amp; S. P. M

chs

39.92

Set a post marked  $\frac{1}{4}$  sec. 4 ft long flattened 3 ins. wide, with marked stone, 12 ins. in the ground, and build end of stone 2 ft high, as per instructions for  $\frac{1}{4}$  sec. cor. from which bears.

a Pine 24 ins. dia. N.  $70^{\circ}$  E. 44 lks dist.

a Pine 26 ins. dia. S.  $65^{\circ}$  W. 9 lks dist.

79.84

Cor to secs. 21, 22, 27 & 28.

Rolling soil 2<sup>d</sup> rate  
Heavy pine timber, some  
Oak & undergrowth.

North bet. Secs. 21 & 22.

Cor.  $14^{\circ} 15' E.$

40.00

Set a post marked  $\frac{1}{4}$  S. 4 ft long flattened 3 ins. wide, with marked stone, 12 ins. in the ground, and build end of stone 2 ft high, as per instructions

B. 149

S. 14 N. R. 10. E. G. &amp; S. R. M.

cho

for 1/4 sec cor.

from which bears.

a Pine 28 ins. dia. N. 57° E. 61 lbs dist.

a Pine 27 ins. dia. N. 58° W. 57 lbs dist.

80.00

Set a post marked & notched  
4 ft long 4 ins. sq. with marked  
stone 12 ins. in the ground and  
build end of stone 2 ft high, as  
per instructions for Cor to Sec.  
15. 16. 21 x 22.

from which bears

a Pine 12 ins. dia. S. 48 1/2° W. 109 lbs dist.

a Pine 16 ins. dia. N. 42° W. 118 lbs dist.

a Pine 24 ins. dia. S. 53° E. 74 lbs dist.

a Pine 19 ins. dia. N. 68° E. 45 lbs dist.

Undulating soil 2<sup>d</sup> rate  
Heavy pine timber, some  
Oak & undergrowth.

BOOK 149

N. 14 N. R. 10 E. G. &amp; S. R. M

chs

East on a random line bet Secs. 15 &amp; 22.

Var  $14^{\circ} 15' E$ .4600 Set temporary  $\frac{1}{4}$  sec cor.79.93 Intersect the N. & S. line 12 lks S.  
of the cor. to Secs. 14, 15, 22, & 23,  
from which I run.S.  $89^{\circ} 55' W$ , on true line bet. Secs. 15 & 22Var.  $14^{\circ} 15' E$ .39.96 Set a post marked  $\frac{1}{4}$  S. 4 ft long  
flattened 3 ins. wide, with marked  
stone, 12 ins. in the ground, and with  
end of stone 2 ft high, as per  
instructions for  $\frac{1}{4}$  sec. cor.  
from which bears.a. Pine 20 ins. dia. N.  $20^{\circ} W$ . 66 lks dista Pine 24 ins. dia. S.  $83^{\circ} E$ . 63 lks dist.

Water in pond 100 yds S. E.

79.93 Cor to Secs. 15, 16, 21 &amp; 22

Undulating soil 2<sup>d</sup> rateHeavy pine timber throughout  
August 10, 1881.

B.L.A. 149

## S. 14 N. R. 10 E. G. 8 S. P. M.

chs

North between Secs. 15 &amp; 16.

Var.  $14^{\circ} 15' E.$ 

as verified by observation with Solar Compass.

11.49 a Pine 30 ins. dia.

33.11 a Pine 28 ins. dia.

36.00 Top of little hill 75 ft. high.

40.00 Set a post marked  $\frac{1}{4}$  S. 4 ft long  
flattened 3 ins. wide, with marked  
stone, 12 ins. in the ground, and  
build end of stone, 2 ft high as per  
instructions for  $\frac{1}{4}$  sec. cor.  
from which bears.a Pine 30 ins. dia. S.  $35^{\circ} W.$  25 lks dista Pine 18 ins. dia. S.  $15^{\circ} E.$  29 lks dist.80.00 Set a post marked & notched 4 ft long  
4 ins. sq. with marked stone, 12 ins.  
in the ground, and build end of  
stone 2 ft high, as per instructions  
for cor. to Secs. 9. 10. 15 & 16.  
from which bears. ✓

N. 14. N. R. 10. E. G. & S. R. M.

chs

a Pine 8 ins. dia. N.  $70^{\circ}$  E. 14 lbs dist.

a Pine 8 ins. dia. N.  $72^{\circ}$  W. 41 lbs dist.

a Pine 10 ins. dia. S.  $34^{\circ}$  E. 61 lbs dist.

a Pine 12 ins. dia. S.  $36^{\circ}$  W. 79 lbs dist.

Rolling Soil 2<sup>d</sup> rate

Heavy pine timber throughout  
East on random line bet Secs. 10 & 15.

Var  $14^{\circ} 15'$  E.

30.50 Descend from high table land.

40.00 Set a temporary  $1/4$  sec. cor.

45.00 Rocky gulch 50 lbs wide course N. W.

79.87 Intersect the N & S. Pine 17 lbs N.

of the cor. to Secs. 10. 11. 14 & 15.

from which I run.

N.  $89^{\circ} 53'$  W. on true line bet Secs 10. & 15.

Var.  $14^{\circ} 15'$  E.

39.93 Set a post marked  $1/4$  S. 4 ft long  
flattened 3 ins. wide, with marked  
stone, 12 ins. in the ground, & buried  
mid of stone, 2 ft high, as per instructions

BOOK 149

S. N. R. 10 E. G. &amp; S. R. M.

Chs

for 1/4 sec. cor.

from which bears.

a Pine 30 ins. dia. N. 70° W. 17 lks dist ✓

a Pine 20 ins. dia. S. 20° E. 23 lks dist.

79.87. Cor. to Secs. 9, 10, 15 &amp; 16.

Rolling & descending E. soil  
2<sup>d</sup> rate Heavy pine timber  
throughout.

North between Secs. 9 &amp; 10.

Bor. 14° 16' E.

33.00 Descend from high table land

40.00 Set a post marked 1/4 S. 4 ft long  
flattened 3 ins. wide, with marked  
stone, 12 ins. in the ground, &  
build m d of stone 2 ft high, as per  
instructions for 1/4 sec. cor.

from which bears.

a Pine 18 ins. dia S. 24° E. 97 lks dist

a Pine 16 ins. dia. S. 33° W. 32 lks dist. ✓



N. 14. N. R. 10. E. G. & S. R. M.

Chs

78.04 a Pine 48 ins. dia.

80.00 Set apart, marked & notched, 4 ft long 4 ins. sq. with marked above 12 ins. in the ground, and build mound of earth 2 ft high, with pits 18+18+12 ins. as per instructions for cor to Secs 3, 4, 9 & 10. from which

a Pine 36 ins. dia. S. 27° W. 109 lbs dist

a Pine 40 ins. dia. S. 16° E. 75 lbs dist

a Pine 24 ins. dia. N. 55° W. 179 lbs. dist

a Pine 36 ins. dia. N. 14° E. 94 lbs. dist.

Descending N. Soil good on N. End. Heavy pine timber and undergrowth throughout

---

East on random line bet. Secs. 3 & 10.

Cor. 14° 15' E.

37.00 Dry wash 30 lbs wide course N. E.

40.00 Set temporary 1/4 sec. cor.

79.90 Intersect the N & S. line 21 lbs. N.

J. 14. N. R. 10. E. G. & S. R. M.

cho

of cor to Secs. 2, 3, 10, 11.  
from which I run.

N.  $89^{\circ} 51' W.$  on true line bet Secs. 3 & 10.  
Var  $14^{\circ} 15' E.$

39.95 Set a post marked  $1/4 S.$  4 ft long  
flattened 3 ins. wide, with marked  
spore, 12 ins. in the ground and build  
mid of earth 2 ft high with pits 18 x 18 x 2  
ins. as per instructions for  $1/4 sec.$  cor.  
from which bears.

A. Pine 24 ins. dia. N.  $70^{\circ} W.$  84 lks dist

A Pine 36 ins. dia. S.  $83^{\circ} W.$  177 lks dist.

79.90 Cor to Secs. 3, 4, 9 & 10.

Rolling Soil good Very heavy  
pine timber and undergrowth  
throughout

North on random line bet. Sec 3 & 4  
Var  $14^{\circ} 15' E.$

40.00 Set temporary  $1/4 sec.$  cor. ✓

S. 14 N. R. 10. E. G. & S. R. M.

chs

45.00 Prairie 100 lks wide course N. E.

80.17 Intersect the N. B. 20 lks E. of  
of cor. to Sec 33 & 34. 3 & 4.  
from which cor I run.

S.  $0^{\circ} 9'$  E on true line bet Secs. 3 & 4  
Var  $14^{\circ} 15'$  E.

40.27 Set a post marked  $1/4$  S. 4 ft long  
flattened 3 ins wide with marked  
stone, 12 ins. in the ground and  
build end of earth 2 ft high, with  
pits 18 + 18 + 12 ins. as per instructions  
for  $1/4$  sec. cor.

from which bears.

a Pine 10 ins. dia. S.  $30^{\circ}$  E. 66 lks dist

a Pine 40 ins. dia. S.  $31^{\circ}$  W. 117 lks dist

80.17 Cor. to Secs. 3, 4, 9 & 10

Rolling Soil 2<sup>d</sup> rate

Heavy pine timber throughout

S. 14. N. R. 10. E. G. & S. R. M.

chs

From Cor. to Secs. 32 & 33. 4 & 5  
on S. B. of Sp. From north bet.  
Secs. 32 & 33. Var.  $14^{\circ} 15' E.$

4.30 A Pine 36 ins. dia.

20.40. A Pine 25 ins. dia.

40.00 Set a post marked  $\frac{1}{4}$  S. 4 ft long  
flattened 3 ins. wide, with marked  
stone, 12 ins. in the ground and  
build end of stone, 2 ft high as per  
instructions. for  $\frac{1}{4}$  Sec. cor.

from which bears a  
Pine 28 ins. dia. N.  $15^{\circ} E.$  100 lks dist  
A Pine 20 ins. dia. S.  $84^{\circ} W.$  118 lks dist.

54.00 Dry wash 30 lks wide come N. W in little valley

80.00 Set a post marked & notched 4 ft long  
4 ins. sq. with marked stone, 12 ins. in  
the ground, and build end of stone  
2 ft high as per instructions for Cor to  
Secs. 28. 29. 32 & 33.

from which bears. ✓

BOOK 149  
S. 14 N. R 10 E. G. & S. R. M.

Chs

a Pine 22 ins. dia. N. 26° E. 98 lks dist.

An Oak 24 ins. dia S. 66° E. 94 lks dist

a Pine 11 ins. dia. S. 19° W. 34 lks dist

a Pine 20 ins. dia. N. 41° W. 89 lks dist.

Rolling Heavy pine timber  
& undergrowth.

East on random line bet. Secs 28 & 33.

Var 14° 15' E.

40.00 Set a temporary 1/4 sec. cor.

61.00 Gulch 40 lks wide course N. W.

80.06 Intersect the N & S. line 13 lks N.  
of the cor. to Secs. 27, 28, 33 & 34  
from which I run.

N. 89° 54' W. on true line bet Secs 28 & 33.

Var 14° 15' E.

40.03. Set a post marked 1/4 s. 4 ft long  
flattened 3 ins. wide, with marked  
stone, 12 ins. in the ground and build  
mid of stone 2 ft high, as per instructions

N. 14 N. R. 10. E. G. & S. R. M

for  $\frac{1}{4}$  Sec. Cor.

from which bears.

a. Pine 27 ins. dia. N.  $40^{\circ}$  E. 83 lks dist

An Oak 9 ins. dia. S.  $87^{\circ}$  W. 81 lks dist.

80.06 Cor. to Secs. 28. 29. 32 & 33.

Rolling & broken  
Heavy pine timber &  
undergrowth.

North bet. Secs. 28 & 29.  $\text{Var. } 14^{\circ} 15' \text{ E.}$

39. 40 Dry Wash 50 lks wide course N. W.  
in little Valley.

40.00 Set a post marked  $\frac{1}{4}$  S. 4 ft long  
flattened 3 ins. wide, with marked  
stone, 12 ins. in the ground and  
built mid of earth 2 ft high, with  
pits 18 x 18 x 12 ins. as per instructions  
for  $\frac{1}{4}$  sec. cor.

from which bears.

a Pine, 18 ins. dia. N.  $56^{\circ}$  E. 156 lks dist &

BOOK 149

S. 14 N. R. 10. E. G. &amp; S. R. M

Chs.

80.00 a Pine 20 ins. dia. N.  $81^{\circ}$  W. 281 lbs dist.  
 Set a post marked & notched  
 4 ft long 4 ins. sq. with marked stone  
 12 ins. in the ground, and build  
 mid of stone 4 ft high, as pt in structure  
 for cor. to Secs 20, 21, 28 & 29.

from which bear.

a Pine 30 ins. dia. N.  $37^{\circ}$  E. 58 lbs dist

a Pine 19 ins. dia. S.  $54^{\circ}$  E. 83 lbs dist

a Pine 16 ins. dia. S.  $46^{\circ}$  W. 11 lbs dist

a Pine 18 ins. dia. N.  $30^{\circ}$  W. 123 lbs dist.

Rolling Heavy pine timber.

East on a random line bet. Secs 21 & 28.

Var  $14^{\circ} 15'$  E.

40.00 Set temporary 1/4 sec. cor.  
 80.20 Intersect the N. & S. line 11 N. of  
 cor. to Secs. 21, 22, 27 & 28.

from which I run

N.  $89^{\circ} 55'$  W. on true line bet. Secs 21 & 28

N. 14 N. P. 10 E. 1/4 G. & S. P. M.

chs

Var. 14° 15' E.

40.10

Set a post marked 1/4 S. 4 ft long flattened 3 ins. wide, with marked stone, 12 ins. in the ground and build up of stone 2 ft high, as per instructions for 1/4 Sec. cor. from which bears.

A. Pine 18 ins. dia. N. 58° E. 82 lks dist.

A. Pine 20 ins. dia. S. 55° W. 52 lks dist.

80.20

Cor. to Secs. 20. 21. 28. & 29.

Rolling & descending East Soil 2<sup>d</sup> rate

Heavy pine timber throughout.

North bet. Secs. 20 & 21.

Var 14° 15' E

40.00

Set a post marked 1/4 S. 4 ft long flattened 3 ins. wide, with marked stone, 12 ins. in the ground, and build up of stone, 2 ft high, as per



BLK 149

N. 14 N. R. 10. E. G. &amp; S. R. M.

chs

instructions for 1/4 Sec. cor.  
from which bears.

An oak 20 ins. dia N. 25° E. 68 lps dist

A Pine 30 ins. dia S. 38° W. 11 lps dist.

8000 Set a post marked & notched 4 ft  
long 4 ins. sq. with marked stone  
12 ins. in the ground, and build  
md of stone 2 ft high, as per inst.  
instructions for cor. to Secs. 16, 17, 20 & 21,  
from which bears.

A Pine 33 ins. dia. N. 32 1/2° W. 70 lps dist

An Oak 10 ins. dia. N. 57° E. 82 lps dist

An Oak 8 ins. dia. S. 70° W. 25 lps dist

A Pine 20 ins. dia S. 79° E. 250 lps dist.

Rolling somewhat broken  
Soil 3<sup>d</sup> rate Heavy pine  
timber.

Aug 11. 1881

N. 14 N. R. 10 E. G. & S. R. M.

chs

East on random line bet Secs 16 & 21.  
Var  $14^{\circ} 15' E$ .

Ascend

- 20.00 Top of high table land
- 40.00 Set temporary  $1/4$  Sec. Cor.
- 80.05 Intersect the N. & S. line 14 lbs S.  
of cor. to Secs. 15. 16. 21. & 22.  
from which I run.  
S.  $89^{\circ} 54' W$ . on true line bet Secs. 16 & 21  
Var  $14^{\circ} 15' E$ .
- 40.02 Set a post marked  $1/4$  S. 4 ft long  
flattened 3 ins. wide, with  
marked stone, 12 ins in the ground  
and build mid of stone, 2 ft high,  
as per instructions for  $1/4$  Sec. Cor  
from which bears.  
A Pin 29 ins. dia. N.  $30^{\circ} W$ . 31 lbs dist  
A Pin 20 ins. dia. S.  $56^{\circ} W$ . 109 lbs dist.
- 80.05 Cor to Secs. 16. 17. 20. & 21.  
Undulating & high table land

T. 14 N. R. 10 E. G. & S. R. M.

cho

Soil 3<sup>d</sup> rate

Heavy pine & undergrowth

North bet. Secs. 16 & 17

Var  $14^{\circ} 15' E$ ,

4000 Set a post marked  $1/4$  S. 4 ft long  
flattened 3 ins. wide, with  
marked stone, 12 ins. in the ground  
and build end of stone 2 ft high  
as per instructions for  $1/4$  sec. cor.  
from which bears.

a. Pine 13 ins. dia. N.  $40^{\circ} W$ , 55 lbs dist

✓ a Pine 18 ins. dia. S.  $35^{\circ} E$ , 62 lbs dist.

8000 Set a post marked & notched, 4 ft long  
4 ins. sq. with marked stone, 12 ins.  
in the ground and build end of  
stone 2 ft high, as per instructions  
for cor. to Secs. 8, 9, 16, & 17.  
from which bears.

a Pine 25 ins. dia. N.  $60^{\circ} W$ , 30 lbs dist

T. 74 N. R. 10 E. G. & S. R. M.

chs

A Pine 26 in. dia. S.  $48^{\circ}$  E. 8 lks dist

A Pine 18 ins dia. S.  $58^{\circ}$  W, 23 lks dist

A Pine 24 ins dia. S  $26^{\circ}$  E. 71 lks dist.

Ascending S. Soil 2<sup>d</sup> rate  
Heavy pine timber & thick  
undergrowth.

East on random line bet. Secs 9 & 16.

Var.  $14^{\circ} 15'$  E.

30.00 Descend from high table land

40.00 Set temporary  $\frac{1}{4}$  Sec. cor.

41.00 Ravine 200 lks wide course N.

79.83. Intersect the N & S. line 18 lks S.  
of cor. to Sec. 9, 10, 15, & 16,  
from which I run.

S  $89^{\circ} 52'$  W. on true line bet. Secs. 9 & 16.

Var.  $14^{\circ} 15'$  E.

39.91 Set a post marked  $\frac{1}{4}$  S. 4 ft long  
flattened 3 ins. wide, with marked  
stone, 12 ins. in the ground, and

N. 14. N. R. 10. E. G. x S. R. M

chs.

build end of stone, 2 ft high, as  
per instructions for  $\frac{1}{4}$  sec. cor.  
from which bears.

A Pine 30 ins. dia. S.  $45^{\circ}$  E. 56 lks dist.

An Oak 8 ins. dia N.  $47^{\circ}$  W. 23 lks dist

79.83 Cor. to Secs. 8, 9, 16 & 17

Land Descending East x N. Soil  
2<sup>d</sup> rate Heavy pine timber throughout  
with some oak & undergrowth.

North bet. Secs. 8 & 9.

Var.  $14^{\circ} 15' E.$

40.00 Set a post marked  $\frac{1}{4}$  S. 4 ft long  
flattened 3 ins. wide, with marked  
stone, 12 ins. in the ground and  
build end of stone 2 ft high, as per  
instructions for  $\frac{1}{4}$  sec. cor.  
from which bears.

A Pine 20 ins. dia. S.  $40^{\circ}$  E. 5 lks dist

A Pine 18 ins. dia. S.  $32^{\circ}$  W. 18 lks dist.

N. 14. N. R. 10. E. G. & S. R. M.

chs  
80.00 Set a post marked & notched 4 ft  
long 4 ins. sq. with marked stone  
12 ins. in the ground, and build  
rod of stone 2 ft high, as per west  
sections for cor. to Secs. 4, 5, 8, & 9.  
from which bears,  
a Pine 10 ins. dia. S. 38° W. 25 lks dist  
a Pine 15 ins. dia. S. 57° E. 28 lks dist.  
a Pine 16 ins. dia. N 84° E. 27 lks dist  
an Oak 16 ins. dia. N. 33° W. 82 lks dist.  
High rolling Soil 2<sup>d</sup> rate  
Heavy pine timber some oak  
& brush,

East on random line bet. Secs. 4 & 9.  
Var. 14° 15' E.

21.00 Range 20 lks wide course N. E.

40.00 Set temporary 1/4 sec. cor.

79.84 Intersect N & S. line 16 lks S. of cor.  
to secs. 3, 4, 9 & 10. from which I run

S. 14. N. R. 10. E. G. & S. R. M

chs

S.  $89^{\circ}53'W$ . on true line bet. Secs. 4 & 9.

Var.  $14^{\circ}15' E$ .

39.92 Set a post marked  $1/4$  S. 4 ft long flattened 3 ins. wide, with marked stone. 12 ins. in. the ground, and build mid of stone 2 ft high, as per instructions for  $1/4$  sec. cor.

from which bears.

a Pine 14 ins. dia. S.  $72^{\circ}W$ . 37 lks dist

a Pine 18 ins. dia. N.  $21^{\circ}E$ . 161 lks dist.

79.84 Cor. to Secs. 4, 5, 8 & 9.

High & rolling, Soil 3<sup>d</sup> rate  
Heavy pine timber, throughout  
Thick m. d. growth.

North on random line bet. Secs. 4 & 5.

Var.  $14^{\circ}15' E$ .

40.00 Set a temporary  $1/4$  sec. cor.

80.18 Intersect N. B. 25 lks. E. of cor. to  
secs. 4 & 5; <sup>32 & 33</sup> from which cor. I. run

BOOK 149

S. 14 N. R. 10 E. G. &amp; S. R. M.

Chs

S.  $0^{\circ} 11' E$ , on true line bet. Secs. 4 & 5.Var.  $14^{\circ} 15' E$ .

40.19 Set a post marked  $1/4 S$ , 4 ft long flattened 3 ins. wide, with marked stone, 12 ins. in the ground, and build md of stone 2 ft high, as per instructions for  $1/4$  Sec. Cor. from which bears.

a Post 28 ins. dia. S.  $83^{\circ} E$ , 36 lks dista. Pine 14 ins. dia. S.  $84^{\circ} W$ , 44 lks dist.

80.18. Cor. to Secs. 4, 5, 8 &amp; 9.

Rolling Soil 2<sup>d</sup> rate

Heavy pine timber throughout

North bet. Secs. 31 &amp; 32.

Var.  $14^{\circ} 15' E$ .

21.07 " Monson Road " to Pinto Basin corner S. M.

40.00 Set a post marked  $1/4 S$ , 4 ft long flattened 3 ins. wide, with marked stone, 12 ins. in the ground and



T. 14 N. R. 10. E. G. & S. R. M.

chs.

Build mid of stone 2 ft high, as per instructions for ~~44~~ Sec. cor, from which bears.

A Pine 29 ins. dia. N. 53° E. 16 lks dist

A Pine 12 ins. dia. N. 36° W. 50 lks dist.

80.00 Set a post marked & notched 4 ft long 4 ins. sq. with marked stone 12 ins. in the ground, and build mid of earth 2 ft high, with pits 18 x 18 x 12 ins.

as instructions for Cor to Seco.

29. 30. 31 & 32.

from which bears.

A Pine 22 ins. dia. N. 68° E. 46 lks dist

A Pine 23 ins. dia. S. 48 1/2° E. 63 lks dist

A Pine 16 ins. dia. S. 27° W. 64 lks dist

A Pine 24 ins. dia. N. 73° W. 110 lks dist.

Rolling, Heavy pine timber Undergrowth with pine & oak

S. 14 N. R. 10 E. G. & S. R. M.

Chs

East on random line bet. Secs. 29 & 32.

" " Var.  $14^{\circ} 15' E$ .

23.30 "Mormon Road" course South

23.38

Set a temporary  $\frac{1}{4}$  sec. cor.

40.00

67.50 Wash 30 lbs wide course N. in little Valley.

80.13.

Intersect N & S. line 8 lbs. S. of cor. to Secs. 28. 29. 32 & 33.

from which I run

S.  $89^{\circ} 57' W$ . on true line bet Secs. 29 & 32.

Var.  $14^{\circ} 15' E$ .

40.06

Set a post. marked  $\frac{1}{4}$  S. 4 ft long flattened 3 ins. wide, with marked stone, 12 ins. in the ground, and build mid of earth 2 ft high, as per instructions for  $\frac{1}{4}$  sec. cor.

from which bears.

a Pine 29 ins. dia. S.  $48^{\circ} E$ . 44 lbs dist

a Pine 36 ins. dia. N.  $28^{\circ} W$ . 8 lbs dist.

80.13

Cor. to Secs 29. 30. 31. 32

Rolling, Heavy pine timber, mording with

BOOK 149

T. 14 N. R. 10. E. G. &amp; S. R. M.

chs

- 4000 West on random line bet. Secs. 30 & 31  
 Set a temporary <sup>Var. 14° 15' E.</sup> 1/4 Sec cor.
- 79.48 Intersect W. B. of Tps 12 lbs N. of cor  
 to Secs. <sup>25</sup> 30. <sup>36</sup> 31 from which I run  
 N. 89° 55' E. on true line bet. Secs. 30 & 31.  
 Var. 14° 15' E.
- 39.48 Set a post marked 1/4 S. 4 ft long  
 flattened 3 ins. wide, with marked  
 stone, 12 ins. in the ground, and  
 build mud of earth 2 ft high, with  
 pits 18 x 18 x 12 ins. as per instructions  
 for 1/4 Sec. Cor.  
 from which bears  
 a Pine 10 ins. dia. N. 41° E. 30 lbs dist  
 a Pine 12 ins. dia. S. 22° E. 130 lbs dist.
- 79.48 Cor. to Secs. 29. 30. 31 & 32.  
 Rolling, Heavy pine timber
-

B. K. 149

N. 14 N. R. 10. E. G. & S. R. M.

chs

North between Secs. 29 & 30.

Var.  $14^{\circ}15' E.$

40.00 Set a post, marked  $\frac{1}{4}$  S. 4 ft long flattened 3 ins. wide with marked stone, 12 ins. in the ground and build end of stone 2 ft high, as per instructions for  $\frac{1}{4}$  sec. cor. from which bears.

A. Pine 13 ins. dia. East 50 lks. dist

A. Pine 12 ins. dia. S.  $24^{\circ} N.$  69 lks. dist.

41.60 Monson Road br. N. W.

80.00 Set a post marked & notched 4 ft long 4 ins. sq. with marked stone 12 ins. in the ground, and build end of earth 2 ft high, with pits  $18 \times 18 \times 12$  ins. as per instructions for cor. to Secs. 19. 20. 29 & 30. from which bears.

A. Pine 24 ins. dia. N.  $57^{\circ} E.$  145 lks. dist

A. Pine 14 ins. dia. S.  $68^{\circ} E.$  40 lks. dist ✓

S. 14 N. R. 10 E. G & S. R. M

chs

A Pine 10 ins. dia. S. 32° W. 119 lks dist.

A Pine 45. ins. dia. N. 29° W. 60 lks dist.

Rolling Heavy pine timber  
Undergrowth with Pine & Oak.

East on random line bet Secs. 20. & 29.

Var. 14° 15' E

40.00 Set temporary 1/4 Sec. cor.

68.00 Wash 50 lks wide course N. in little valley

80.22 Intersect N & S. line 10 lks N. of cor.  
to Secs. 20. 21. 28. 29.

from which I run

N. 89° 56' W. on true line bet Secs. 20 & 29

Var. 14° 15' E

40.11 Set a post marked 1/4 S. 4 ft long  
flattened 3 ins. wide, with  
marked stone, 12 ins. in the ground  
and build mid of stone 2 ft high,  
as per instructions for 1/4 sec. cor.

from which bears.

S. 14. N. P. 10. E. G. & S. P. M.

Chs

a Pine 20 ins. dia. north 134 lks dist  
a Pine 16 ins. dia. S. 46° W. 28 lks dist.

80.22

Cor. to Secs. 19. 20. 29. & 30.

Rolling Soil 3<sup>d</sup> rate

Heavy pine timber throughout  
Undergrowth.

August 12, 1881

Went on random line bet. Secs. 19 & 30.

Var. 14° 15' E.

as verified by observation with Solar Compass.

19.44

"Mormon Road" N. E. & S. W.

40.00

Set temporary 1/4 Sec. cor.

79.40.

Intersect W. B. of Tp. 17 lks N. of cor.  
to Secs. 19 & 30. <sup>24, 25 & 8.</sup> from which cor. from

N. 89° 53' E. on true line bet. sec. 19 & 30.

Var 14° 15' E.

89.40.

Set a post marked 1/4 S. 4 ft long  
flattened 3 ins. wide, with marked  
stone, 12 ins. in the ground, and

S. 14 N. R. 10. E. G. & S. R. M.

Chs

build mid of stone 2 ft high, as per  
instruction for  $\frac{1}{4}$  sec. cor.

from which bears.

a Pine 19 ins. dia. N.  $48^{\circ}$  E. 32 lbs dist

a Pine 26 ins. dia. S.  $67^{\circ}$  W. 71 lbs dist.

72.00 Pine 40 ins. dia.

79.40 Cor. to Secs. 19. 20. 29 & 30.

Rolling, Heavy pine timber  
Oak & Pine undergrowth.

<sup>Secs</sup>  
North bet 19 & 20.

For  $14^{\circ} 15' E$ .

2.88 a Pine 16 ins. dia.

4.00 Set a post marked  $\frac{1}{4}$  S. 4 ft long  
flattened 3 ins. wide, with marked  
stone, 12 ins. in the ground, and build  
mid of stone 2 ft high, as per inst.  
ructions for  $\frac{1}{4}$  sec. cor from which  
a Pine 22 ins. dia. br. S.  $20^{\circ}$  E. 61 lbs dist  
a Pine 12 ins. dia. br. N.  $18^{\circ}$  W. 96 lbs dist.

T. 14 N. R. 10. E. G. & S. R. M.

Chs  
 40.40 Mormon Road to Pinto Basin S. W.  
 80.00 Set a post marked & notched 4 ft long  
 4 ins. sq. with marked stone, 12 ins.  
 in the ground and build end of  
 stone 2 ft high as per instruction  
 for cor. to Secs. 17, 18, 19 & 20  
 from which bears.  
 a Pine 30 ins. dia. S. 70° W. 53 lks dist  
 a Pine 16 ins. dia. S. 22½° E. 40 lks dist  
 a Pine 28 ins. dia. N. 85° W. 35 lks dist  
 a Pine 24 ins. dia. N. 61° E. 167 lks dist.  
 Rolling Heavy pine timber  
 Oak & pine under growth

East on random line bet. Secs 17 & 20.  
 Var 14° 15' E.

8.67 Mormon Road to Pinto Basin corner  
 34.00 Ravine 100 lks wide, course N. W.  
 40.00 Set a temporary ¼ sec. cor.  
 80.00 Intersect N. & S. line 11 lks S. of cor



S. 14 N. R. 10. E. G. & S. R. M.

chs.

to Sec. <sup>16</sup>17. 20 & 21. from which corner  
 S 89° 55' N. on true line bet. Sec. 17 & 20.  
 Var. 14° 15' E.

40.03 Set a post marked 1/4 S. 4 ft long  
 flattened 3 ins. wide, with marked  
 stone, 12 ins. in the ground, and  
 build end of stone 2 ft high, as per  
 instructions for 1/4 Sec. cor.  
 from which bears.

a Pine 29 ins. dia. S. 39° N. 44 lbs dist.

a Pine 12 ins. dia. N. 27° E. 80 lbs dist.

80.07 Cor to Secs. 17, 18, 19 & 20.

Rolling & broken Soil 3' deep  
 Heavy pine timber and  
 some oak.

---

To by Copied

BOOK 149

S. 14. N. R. 10. E. G. & S. R. M.

Chs

Meet on random bet. Secs. 18 & 19.  
Var. 14° 15' E.

40.00 Set temporary 1/4 sec. cor.

52.00 Prairie 100 lks wide course N. E.

79.43 Intersect W. B. of Tp. 12 lks S. of cor.  
to Secs. <sup>13</sup> 18 & <sup>324</sup> 19, from which I run  
S. 89° 55' E. on true line bet. Secs. 18 & 19.  
Var. 14° 15' E.

39.43 Set a post marked 1/4 S. 4 ft long  
flattened 3 ins. wide, with marked  
stone, 12 ins. in the ground, and  
build m d of earth 2 ft high, with  
pits 18 x 18 x 12 ins. as per structure  
for 1/4 sec. cor.

from which bears  
a Pine 16 ins. dia. S. 7° E. 22 lks dist  
an Oak 6 ins. dia. S. 47 W. 2 lks dist.

79.43 cor to Secs. 17, 18, 19, & 20.

Rolling, Soil 3d rate  
Heavy pine timber throughout

BOOK 149

T. 14 N. R. 10. E. G. &amp; S. R. W.

Chs

North bet. Secs. 17 &amp; 18.

Var.  $14^{\circ} 15' E$ .

22.00 Ravine 100 lbs wide course N.

40.00 Set a post marked  $1/4 S$ . 4 ft long  
flattened 3 ins. wide, with marked  
stone, 12 ins. in the ground, and  
build wd of stone 2 ft high, as per  
instructions for  $1/4 sec. cor.$ 

from which bears

a Pine 18 ins. dia. N.  $16^{\circ} W$ . 52 lbs dist.a Pine 27 ins. dia. S.  $25\frac{1}{2}^{\circ} E$ . 73 lbs dist.80.00 Set a post marked & watched 4 ft long  
4 ins. sq. with marked stone 12 ins.  
in the ground, and build wd of  
stone 2 ft high, as per instructions  
for cor. to Secs. 7, 8, 17 & 18.

from which bears

a Pine 10 ins. dia. S.  $57\frac{1}{2}^{\circ} E$ . 108 lbs dist.a Pine 12 ins. dia. N.  $38^{\circ} E$ . 224 lbs dist.a Pine 26 ins. dia. N.  $25^{\circ} W$ . 310 lbs dist.

S. 14 N. R. 10. E. G. & S. R. M.

Chs

none near S. W.

High rolling & broken, Soil 2<sup>d</sup> rate  
Heavy pine timber all along  
Undergrowth pine & oak.

---

East on random line bet. Secs. 8 & 17  
Var.  $14^{\circ} 15' E$ .

27.00 Gully 30 lks wide course S. E.

27.50 "Mormon Road" to Pointe D'acier S. E.

40.00 Set temporary  $1/4$  Sec. Cor.

80.12 Intersect N. & S. line 17 lks S. of cor.  
to Secs. 8, 9, 16 & 17, from which I run  
S.  $89^{\circ} 53' W$ , on true line bet sec. 8, 17  
Var.  $14^{\circ} 15' E$ ,

40.06 Set a post marked  $1/4$  S. 4 ft long  
flattened 3 ins. wide, with marked  
stone, 12 ins. in the ground, and  
build end of stone left high, as per  
instructions for  $1/4$  sec. cor.  
from which bear

✓

S. 14 N. R. 10. E. G. & S. P. M.

chs

a. Pine 18 ins. dia. N.  $75^{\circ}$  E. 32 lbs dist  
An Oak 8 ins. dia. S.  $88^{\circ}$  W. 30 lbs dist.

80.12 Cor. to Secs. 7, 8, 17 & 18.

High & rolling some broken  
Soil 3<sup>d</sup> rate Heavy pine timber  
throughout Some oak and  
thick undergrowth.

West on random line bet. Secs 7 & 18  
Var.  $14^{\circ} 15' E.$

40.00 Set temporary  $1/4$  sec. cor.

65.00 Ravine 100 lbs wide course N.W.

79.28 Intersect W. B. of Tp. 15 lbs S. of  
cor. to Secs. 7<sub>n</sub> & 18<sub>12,13</sub>, from which I run  
S.  $89^{\circ} 54' E.$  on true line bet. Secs. 7 & 18  
Var.  $14^{\circ} 15' E.$

39.28 Set a post marked  $1/4$  S. 4 ft long  
flattened 3 ins. wide, with marked  
stone, 12 ins. in the ground, and  
build end of stone 2 ft high,

## S. 14 N. R. 10. E. G. &amp; S. R. M.

Chs

as per instructions for 1/4 Sec. cor.  
from which bears.

a Pine 20 ins. dia. N.  $22\frac{1}{2}^{\circ}$  E. 88 lbs dist  
an Oak 12 ins. dia. S.  $83^{\circ}$  E. 123 lbs dist.

79.28 cor. to Secs. 7. 8. 17. 18

Ascending E. Soil 2<sup>d</sup> rate  
Heavy pine timber with Oak  
& undergrowth.

North bet. Secs. 7 & 8.

Per.  $14^{\circ} 15' E.$

40.00 Set a post marked 1/4 S. 4 ft long  
flattened 3 ins. wide, with marked  
stone, 12 ins. in the ground, and  
build end of stone 2 ft high, as per  
instructions for 1/4 sec. cor.

from which bears.

a. Pine. 8 ins. dia. S.  $18^{\circ}$  E. 67 lbs dist

a Pine 24 ins. dia. S.  $53\frac{1}{2}^{\circ}$  W. 213 lbs dist.

80.00 Set a post marked & notched ✓

N. 14 N. R. 10. E. G. & S. R. M

chs

4 ft long 4 ins. sq. with marked  
stone 12 ins. in the ground and  
build end of stone 2 ft high, as  
per instructions for cor to Secs  
5, 6, 7 & 8. from which bears  
a. Pine 29 ins. dia. N. 25° E. 10 lks dist  
a. Pine 14 ins. dia. S. 58° W. 165 lks dist  
a. Pine 30 ins. dia. N. 55° W. 200 lks dist.  
a. Pine 12 ins. dia. S. 85° E. 137 lks dist.  
Ascending N. Soil 2<sup>d</sup> rate  
Pine timber throughout  
& brush.

East on random line bet. Secs. 5 & 8.

Var. 14° 15' E.

24.77 "Mormon Road" to Pinto Basin S.  
40.00 Set temporary 1/4 sec cor.  
46.00 Top of ridge extends N. W.  
57.50 Descend steeply to lower table land  
80.16 Intersect N & S. line 20 lks N. of

T. 14 N. R. 10. E. G. & S. R. M.

Chs

cor. to Secs. 4, 5, 8 & 9 from which Iron  
N. 89° 51' W. on true line bet. secs. 5 & 8.

Var. 14° 15' E.

40.08 Set a post marked  $\frac{1}{4}$  S. 4 ft long  
flattened 3 ins. wide, with marked  
stone .12 ins. in the ground, and build  
end of stone  $2\frac{1}{4}$  high as per instructions  
for  $\frac{1}{4}$  Sec. cor.

from which bears.

An <sup>Oak</sup> 10 ins. dia. N. 63° E. 30 lks dist

a Pine 27 ins. dia. S. 7° E. 74 lks dist.

80.16 Cor. to Secs. 5, 6, 7 & 8.

Rolling Soil 3<sup>d</sup> rate  
Heavy pine timber and oak  
and undergrowth.

West on random line bet. Secs. 6 & 7

Var 14° 15' E.

40.00 Set temporary  $\frac{1}{4}$  Sec. Cor.

79.22 Intersect N. B. of T. 19 lks S. of ✓



S. 14. N. R. 10. E. G. & S. R. M.

Cho

cor. to Secs. <sup>11</sup>6 & <sup>12</sup>7. from which Iron  
S.  $89^{\circ}52'E$ . on true line bet. secs. 6 & 7.

Var  $14^{\circ}15'E$ .

39.22 Set a post. marked  $\frac{1}{4}$  S. 4 ft long  
flattened 3 ins. wide, with marked  
stone, 12 ins. in the ground, and  
build end of stone 2 ft high as per  
instructions for  $\frac{1}{4}$  sec. cor.

from which bears.

a Pin 20 ins. dia. N.  $28^{\circ}W$ . 9 lks dist.

a Pin 22 ins. dia. S.  $17^{\circ}W$ . 110 lks dist.

79.22 Cor. to Secs. 5, 6, 7 & 8.

High & rolling Soil 3<sup>d</sup> rate

Thick pine timber and  
undergrowth.

North on random line bet Secs. 5 & 6.

Var  $14^{\circ}15'E$ .

40.00 Set temporary  $\frac{1}{4}$  sec. cor.

80.13 Intersect N. B. 21 lks E of

S. 14. N. R. 10 E. G. & S. R. M.

3832  
 cor. to secs. 5 & 6, from which run  
 S. 0° 9' E. on true line bet. Secs. 5 & 6.  
 9 or 14° 15' E.

10.13 Set a post marked  $\frac{1}{4}$  S. 4 ft long  
 flattened 3 ins. wide, with  
 marked stone, 12 ins. in the  
 ground and build up of stone  
 2 ft high, as per instructions for  $\frac{1}{4}$  Sec. Cor.  
 from which bears  
 a Pine 16 ins. dia. S. 65 $\frac{1}{2}$ ° E. 60 lks dist.  
 a Pine 33 ins. dia. N. 69° W. 93 lks dist.

10.13 Cor to Secs. 5, 6, 7 & 8.

Rolling Soil 3<sup>d</sup> rate  
 Pine timber throughout.

August 13. 1881.

---

## General Description.

Township 14 N. Range 10 E has a rolling and broken surface with a portion of it along the center and thence to the S. E. flat. It lies along the summit of the Mogollon Mts. Lines of drainage commence in it and run N. E. & E. into the Little Colorado and N. W. & W. into the Verde Rivers.

There is some good tillable land along a little valley in the S. W. part of the township. Water is found in tanks in a number of places during the dry portion of the year. There is heavy pine timber throughout the township, with some oak fir and aspen. Theodore J. W.  
U.S. Deputy Surveyor

## List of Names.

A List of the Names of Individuals employed to assist  
in running, measuring or marking the lines and corners  
described in the foregoing Field Notes of the survey of

The subdivision lines of Township  
14 N. Range 10 E. of the Gila  
and Salt River Meridian and  
Base lines

Showing the respective capacities in which they acted.

J. H. McClure Chainman.

H. J. Bargmann Chainman.

John Blake Axeman.

L. J. Bargmann Flagman.

Hugh Dobbins, Moundman.




Final Oath of Assistants.

We hereby certify that we assisted *Theodore*  
*H. White* U. S. Deputy Surveyor, in surveying  
 the subdivision lines of Township  
 14 N. Range 10 E. of the Gila and  
 Salt River Meridian and Base  
 lines

and that said Survey has been in all respects, to the best of our  
 knowledge and belief, well and faithfully executed, and the  
 boundary monuments planted according to the instructions  
 furnished by the Surveyor-General.

- J. H. McClure* Chainman.
- H. J. Bergmann* Chainman.
- J. J. Plake* Axeman.
- L. J. Bergmann* Flagman.
- Hugh Dobbins* Moundman

Sworn to and subscribed before me, this *eight*  
 day of *September* 188*6*.



*William Osburn*  
 Notary Public  
 Pima Co. A. T.

Final Oath of Deputy Surveyor.

75

I, *Theodore H. White*

United States Deputy Surveyor, do solemnly swear that I have, in my own proper person and with the necessary assistants, well, truly and faithfully executed the survey of

*the subdivision lines of Township 14 N. Range 10 E. of the Gila and Salt River Meridian and Base lines*

under my contract with John Wasson, United States Surveyor General for Arizona, bearing date the *27<sup>th</sup>* day of

*August* 1880; that in making the said Survey I have used only such instruments as were approved by the said Surveyor-General, exercising due care in the preservation of adjustments of the same; that in using the solar compass I have at no time projected established lines depending for alignment upon the magnetic needle; that I have in all respects complied with the laws of the United States governing public-land

surveys, the surveying manual, and such additional instructions as have been furnished me by and through the said Surveyor-General relating to the aforesaid Survey; that I have thoroughly acquainted my assistants in the field with the nature of their duties under the laws and instructions above mentioned; that to the best of my knowledge and belief all assistants so employed have likewise obeyed the aforesaid laws and instructions, and that the annexed field-notes are the original, true, and correct returns of the said Surveys.

*Theodore J. White*  
 U.S. Deputy Surveyor

Subscribed and sworn to before me this *eight*  
 day of *September* 1881

*William J. O'Connell*  
 Notary Public  
 Platte Co., A.T.



# U. S. Surveyor General's Office,

TUCSON, ARIZONA, Dec 14 - 1881

The foregoing Field Notes of the Survey of the  
 Subdivisions of Tp. 14 ct. R. 10. E.

Of the Gila and Salt River Base and Meridian, Arizona, execu-  
 ted by Thos. A. White

Deputy Surveyor, under his contract of the 27<sup>th</sup>  
 day of August, 1880, having been  
 critically examined and the necessary corrections and explan-  
 ations made, the said Field Notes and the surveys they describe  
 are hereby approved.

John Mason  
 Surveyor General.