

No-155

Subdivisions

4-671

15

FIELD NOTES
GENERAL LAND OFFICE.

Sp: 14 N. R. 12 E.

No-155

61. 31. 66

Indexed, Book 154.

B17K 155

Subdivisions T. 14. N. R. 12. E.

- chs. From the Cor to Secs. 4, 5, 32, & 33,
on S. boundary of the Township.
Hereinafter described. From
N $0^{\circ}2'$ W. bet. Secs. 32 & 33,
Va. 13 $^{\circ}42'$ E
- In heavy Pine & Oak timber.
- .20 Pine 20 ins. diam. on line, marked
with 2 notches on N. & S. Sides
- 28.90 Pine 18 ins. diam. on line marked
with 2 notches on N. & S. Sides.
- 40.00 Set a Sandstone 16x14x5 ins. 11 in
in the ground, for $\frac{1}{4}$ Sec. Cor. marked
 $\frac{1}{4}$ on W. face, whence a Pine 6 ins
diam. bears N 81° E 52 lks. dist.
marked $\frac{1}{4}$ S. B. T. - An Oak 5 ins
diam. bears S 48° W 46 lks. dist.
marked $\frac{1}{4}$ S. B. T. -
- 80.00 Set a Sandstone 18x10x8 ins. 13 ins.
in the ground, for Cor. to Secs. 28, 29

Subdivisions T. 14. N. R. 12. E.

chs. 32 x 33, marked with 1 notch on S.
and 4 notches on E. edges. Whence -

A Pine 20 ins. diam. bears
N 7° E 29 lks. dist. marked
T. 14. N. R. 12. E. S. 28. B. I. -

A Pine 15 ins. diam. bears
S 53° E 32 lks. dist. marked
T. 14. N. R. 12. E. S. 33. B. I. -

A Pine 14 ins. diam. bears
S 75° W 62 lks. dist. marked
T. 14. N. R. 12. E. S. 32. B. I. -

A Pine 16 ins. diam. bears
N 17° W 43 lks. dist. marked
T. 14. N. R. 12. E. S. 29 B. I. -

Land. level.

Soil. Sandy & gravelly, 1st & 2^d rate
Timber, heavy Pine & Oak. 80. chs.

Subdivisions.

- | | |
|-------|--|
| chs. | East on a random line.
bet. Secs. 28 & 33.
Ya. $13^{\circ}42'E$ |
| 40.00 | Set temporary $\frac{1}{4}$ Sec Cor. |
| 80.14 | Int. N. & S. line 10 lks. S. of Cor to
Secs. 27, 28, 33 & 34. Thence I run
$189^{\circ}56'W$. on a true line
bet. Secs. 28 & 33.
Ya. $13^{\circ}42'E$. |
| | In heavy Pine & Oak timber as usual |
| 34.50 | Bank bears N.E. & S.W. |
| 36.00 | Trail bears N.E. & S.W. |
| 40.07 | Set a Sandstone $16 \times 10 \times 5$ ins. 11 ins
in the ground. for $\frac{1}{4}$ Sec Cor. Marked
$\frac{1}{4}$ on N. face. Whence A Pine 12 ins
diam. bears $N 20^{\circ}E$ 23 lks. dist
marked $\frac{1}{4}$. S. B.T. - A Pine 11
ins. diam bears $18^{\circ}W$ 29 lks.
dist. marked $\frac{1}{4}$. S. B.T. - |

J. 14. N. R. 12. E.

- chs.
73.15 Pine 30 ins diam. on line marked
with 2 notches on E. & W. Sides.
- 80.14 The Cor. to Secs. 28, 29, 32 & 33,
Land. Nearly level.
Soil. Sandy 2^d rate.
Timber. Heavy Pine & Oak. 80.14 chs.
-

N^o 2' W. bet. Secs. 28 & 29.
Va. 13^o 42' E.

In heavy Pine & Oak timber

- 40.00 Set a Sandstone 18x10x8 ins. 13. ins
in the ground, for $\frac{1}{4}$ Sec. Cor. marked
 $\frac{1}{4}$ on N. face. Whence A Pine 5 ins.
diam. bears S 18^o E 10 lks. dist.
marked $\frac{1}{4}$ A. B. I. - An Oak. 5 ins
diam. bears N 8^o W 28 lks. dist.
marked $\frac{1}{4}$ A. B. I. -
- 64.50 Bank bears N.E. & S.W. descend

Subdivisions.

cho. 69.60	Gulch 20 lks. wide. runs N.E. and
80.00	Set a Sandstone 16x11x6 ins. 11 ins in the ground. for. Cor. to Secs. 20, 21. 28 & 29, marked with 2 notches on S. and 4 notches on E. edges. whence A Pine 20 ins. diam. bears N62°E 38 lks. dist. marked T. 14, N. R. 12, E. S. 21, B. 4. An Oak 8 ins. diam. bears S80°E 20 lks. dist marked T. 14, N. R. 12, E. S. 28, B. 4. - A Pine 5 ins. diam. bears S71°W 57 lks. dist. marked T. 14, N. R. 12, E. S. 29, B. 4. - An Oak 5 ins. diam. bears N44°W 63 lks. dist. marked T. 14, N. R. 12, E. S. 20, B. 4. - Land. nearly level. Soil. Sandy 2 ^d rate.

T. 14. N. R. 12. E.

Chs. Timber. Heavy Pine & Oak, 80. Chs.

N 89° 56' E. on a random line
 bet. Secs. 21 & 28.
 Va. 13° 42' E.

40.00 Sect. temporary 1/4 Sec. Cor.

79.74 Int. N. & S. line 5 lks. N. of Cor to
 Secs. 21, 22, 27 & 28. Thence I run
 S 89° 58' W. on a true line.
 bet. Secs. 21 & 28.
 Va. 13° 42' E.

In heavy Pine & Oak timber descend

5.30 Gulch 20 lks. wide, runs N.E. ascend

9.32 Pine 26 in diam. on line marked
 with 2 notches on E. & W. sides

12.75 Bank, trans. N.E. & S.W.

14.15 Divide & Trail trans. N.E. & S.W.

18.25 Bank trans. N.E. & S.W. descend

24.90 Gulch 10 lks. wide, runs N.E. ascend

Subdivisions.

- | | |
|---------------|--|
| chs.
27.15 | Opposite bank bears, N.E. & S.W. |
| 34.12 | Pine 30 ins. diam. on line, marked with 2 notches on E. & W. Sides |
| 36.75 | Bank bears N.E. & S.W. descend |
| 38.75 | Gulch 10 lks. wide, runs N.E. ^{ascend} |
| 39.87 | Set a sandstone 18X11X6 ins 13 ins in the ground, for 1/4 Sec. Cor. marked 1/4 on N. face, whence a Pine 12 ins diam. bears S67°E 69 lks. dist. marked 1/4 S. B.T. - An Oak 14 ins diam bears N68°E 40 lks. dist, marked 1/4 S. B.T. - |
| 42.75 | opposite bank bears, N.E. & S.W. |
| 57.57 | Pine 18 ins. diam. on line, marked with 2 notches on E. & W. Sides |
| 55.02 | Pine 20 ins. diam. on line, marked with 2 notches on E. & W. Sides |
| 73.25 | Bank bears N.E. & S.W. descend |
| 76.60 | Gulch 20 lks. wide, runs N.E. |

T. 14. N. R. 12. E.

- Chs.
76.72 Trail. trans. N.W. & S.E.
79.74 The Cor. to Secs. 20, 21, 28 & 29. —
Land rolling.
Soil. gravelly, 3^d rate.
Timber. Heavy Pine & Oak 79.74 chs.
November, 6, 1893.

No° 2' W. bet. Secs. 20, & 21.
Ta. 13° 42' E

In heavy Pine & Oak timber

- 17.65 Pine 16 ins. diam. on line. marked
with 2 notches on N. & S. sides
27.80 Trail. trans. N.E. & S.W.
40.00 Set a sandstone 18x10x6 ins. 13 ins.
in the ground. for $\frac{1}{4}$ Sec. Cor. marked
 $\frac{1}{4}$ on W. face. Whence A Pine 24 ins
diam. bears. S 89° E 37 lks. dist.
marked $\frac{1}{4}$ S. B. I. — A Pine 22 ins.
diam. bears. S 53° W 6.0 lks. dist. marked

Subdivisions

- Chs. $\frac{1}{4}$ S. B.S. -
- 73.00 Banks bears. N.W. + S.E. descend
- 80.00 Set a Sandstone $20 \times 12 \times 8$ ins. 15 ins
in the ground. for. Cr. to Seas. 16, 17, 20 +
21. Marked with 3 notches on S. &
4 notches on E. edges. whence
A Pine 8 ins. diam. bears
N 87° E 34 lks. dist. marked
S. 14. N. R. 12. E. S. 16 B.S. -
- An Oak 4 ins. diam. bears
S 52° E 86 lks. dist. marked
S. 14. N. R. 12. E. S. 21 B.S. -
- An Oak 5 ins. diam. bears.
S 13° W 32 lks. dist. marked
S. 14. N. R. 12. E. S. 20, B.S.
- A Double Oak 10 ins. diam. bears
N 40° W 67 lks. dist. marked
S. 14. N. R. 12. E. S. 17 B.S. -
- Land level.

T. 14. N. R. 12. E.

Chs. Soil, gravelly, 2^d rate.
 Timber Heavy Pine & Oak, 80. Chs.

N 89° 58' E. on a random line
 bet. Secs. 16 & 21.
 Va. 13° 42' E.

40.00 Set temporary 1/4 Sec. Cor.

79.64 Int. N. & D. line 7 lks. S. of Cor. to Secs.
 15, 16, 21 & 22. Thence Iron
 S 89° 55' W, on a true line.
 bet. Secs. 16 & 21.
 Va. 13° 42' E.

In heavy Pine & Oak timber

8.90 Trail. trans. N.E. & D.W.

9.00 Gulch 20 lks wide, runs N.E. as usual

20.50 Back bears N.E. & D.W.

39.82 Set a Sandstone 16x14x5 ins. 11 ins. in
 the ground, for 1/4 Sec. Cor. marked
 1/4 on N. face. where a Pine 8 ins. diam.

Subdivisions.

chs. bears S 35° W 20 lks. dist. marked
 1/4 S. B.Y. - A Pine 6 ins. diam. bears
 N 20° W 30 lks. dist. marked
 1/4 S. B.Y. -

71.00 Bank bears N.W. & S.E. descend
 76.30 Gulch 10 lks wide. runs. N.W. ascend
 79.64 The Cor. to Secs. 16, 17, 20 & 21.
 Land. nearly level
 Soil. gravelly 2^d rate
 Timber heavy Pine & Oak. 79.64 chs

N 0° 2' W. bet. Secs. 16 & 17.

Via 13° 42' E.

In heavy Pine & Oak timber, descend

3.60 Gulch 10 lks wide. runs. N.W. ascend
 10.80 Bank bears, N.W. & S.E.
 40.00 Set. a Sandstone 18 X 10 X 6 ins. 13 ins
 in the ground. for 1/4 Sec. Cor. marked
 1/4 on W. face. whence A Pine 10 ins.

J. 14, N. R. 12, E.

- Chs. diam brass $S53^{\circ}W$ 15 lks. dist
 marked $\frac{1}{4}$ S. B. J. — A Juniper 10 ins
 diam. brass $S85^{\circ}E$ 27 lks. dist. marked
 $\frac{1}{4}$ S. B. J. —
- 72.25 Pine 12 ins. diam. on line. marked
 with 2 matches on N. & S. sides.
- 74.50 Descend gently.
- 80.00 Set a Sandstone $16 \times 10 \times 7$ ins. 11 ins in
 the ground. for Cor. to Secs. 8, 9, 16 & 17.
 marked with 4 matches on S. & E.
 edges. Whence —
- A Pine 5 ins. diam. brass
 $N12^{\circ}E$ 13 lks. dist. marked
 J. 14, N. R. 12, E. S. 9 B. J. —
- An Oak 5 ins. diam. brass
 $S14^{\circ}E$. 24 lks. dist. marked
 J. 14, N. R. 12, E. S. 16 B. J. —
- An Oak 6 ins. diam. brass
 $S56^{\circ}W$ 35 lks. dist. marked

Subdivisions.

- Chs. T. 14, N. R. 12, E. S. 17. B.T. -
 A Pine 5 ins. diam bears.
 N 53° W. 38 eks. dist. marked
 T. 14, N. R. 12, E. S. 8. B.T. -
 Land. ralling.
 Soil. gravelly. 2^d + 3^d rate,
 Timber. heavy Pine + Oak. 80 chs.

N $89^{\circ} 55'$ E on a random line
 bet. Secs. 9 & 16.

Va. $13^{\circ} 42'$ E.

- 40.00 Set temporary $\frac{1}{4}$ Sec. Cor.
 80.00 Int. N. + S. line. 14 eks. N. of Cor to
 Secs. 9, 10, 15 & 16. Then I run
 N $89^{\circ} 59'$ W. on a true line.
 bet. Secs. 9 + 16.
 Va $13^{\circ} 42'$ E.

In heavy Pine + Oak timber

- 2.00 Bank bears. N. + S. descend

T. 14. N. R. 12. E.

chs.	
7.50	Gulch 20 lks wide. runs northerly. ^{ascend}
10.00	Opposite bank trans. N.T.D.
12.90	Bank trans. N.T.D. descend
16.80	Gulch 10 lks. wide. runs northerly ^{ascend}
24.00	Opposite bank trans. N.T.D.
27.00	Bank trans. N.E. & S.W. descend
40.00	Set a sandstone 18x8x6 ins. 13 ins. in the ground. for 1/4 Sec. Cor. marked 1/4 on N. face. whence An Oak 5 ins. diam. trans S 82° W 13 lks. dist. marked 1/4 S. B.L. - A Pine 14 ins. diam. trans N 39° E 23. lks. dist. marked 1/4 S. B.L. -
40.90	Gulch 10 lks. wide. runs N.E. ascend
50.50	Opposite bank trans. N.E. & S.W.
66.50	Bank trans. N.W. & S.E. descend
74.80	Gulch 10 lks wide. runs N.W. ascend
80.00	The Cor. to Secs. 8, 9, 16 & 17. - Land. rolling.

Subdivisions.

Chs. Soil, gravelly, 2^d + 3^d rate.
 Timber. Heavy Pine + Oak 80 chs.
 November 7, 1893.

No^o 2' W. bet. Secs. 8. & 9.

Ta. 13° 42' E.

In heavy Pine + Oak timber

- .90 Bank ~~beams~~ N.E. + S.W. descend
 2.30 Descend 15 ft.
 8.20 Gulch 20 lks. wide runs N.E. ascend
 21.40 Ridge bears N.E. + S.W. descend
 24.00 Right bank Clear Creek Cañon bears E. + W.
 descend + leave timber
 38.90 Clear Creek Cañon 80 lks. wide runs ^{ascend} E.
 40.00 Set a sandstone 20 x 11 x 6 ins. 15
 ins in the ground. for $\frac{1}{4}$ Sec Cor,
 marked $\frac{1}{4}$ on N. face. and raised
 a mound of stone $1\frac{1}{2}$ ft. high, 2
 ft. base. alongside.

T. 14. N. R. 12. E.

- Chs. Pits impracticable. - No trees near
 60.60 Left bank of Clear Creek Cañon
 trans. Easterly & Westerly. E. side timber
 80.00 Set a Sandstone 20x16x8 ins. 15 ins in
 the ground. for. Cor. to Secs. 4, 5, 8 & 9,
 marked with 5 notches on S. and 4
 notches on E. edges. Whence -
 A Pine 20 ins. diam. trans
 N 61° E 53 lks. dist. marked
 T. 14. N. R. 12. E. S. 4. B. S.
 A Juniper 42 ins. diam. trans
 S 58° E 48 lks. dist. marked
 T. 14 N. R. 12. E. S. 9 B. S. -
 An Oak 5 ins. diam. trans
 S 70° W 62 lks. dist. marked
 T. 14. N. R. 12. E. S. 8. B. S. -
 An Oak 4 ins. diam. trans
 N 47° W. 94 lks. dist. marked
 T. 14. N. R. 12. E. S. 5. B. S. -

Subdivisions.

chs. Land, very rough & broken.
 Soil, rocky, 4th rate.
 Timber, Pine Oak & Juniper 43.40 chs.

189°59'E. on a random line
 bet. Secs. 4 & 9.
 Va 13°42'E.

40.00 Set temporary 1/4 Sec Cor.

79.94 Int. N. & S. line 3 lks. S. of Cor.
 to Secs. 3, 4, 9 & 10. Thence I run
 West, on a true line,
 bet. Secs. 4 & 9.
 Va 13°42'E.

Along N Slope of Clear Creek Cañon

18.80 Gulch 10 lks. wide runs S.E. ascend
 34.94 Enter timber.
 35.80 end of abrupt ascend

36.75 Left bank Clear Creek Cañon bears NE & SW.

39.97 Set a Sandstone 18x11x5 ins. 13 ins
 in the ground. for 1/4 Sec. Cor.

Chs.	Marked $\frac{1}{4}$ on N. face. Whence a Pine 4 ins. diam. bears. S 28° E. 47 lks. dist. marked $\frac{1}{4}$ S. B. J. — A Pine 5 ins. diam. bears. N 10° W 55 lks. dist. marked $\frac{1}{4}$ S. B. J. —
48.00	Enter gulch
48.50	Leave gulch runs. S. E. ascend
52.75	Trail, bears. N. W. + S. E.
57.00	S. W. Bank bears. N. W. + S. E.
57.20	Pole fence bears. N. W. + S. E.
60.00	Bank bears N. W. + S. E. descend
63.00	Enter Cedar
65.50	Leave Cedar
70.30	Gulch 10 lks. wide runs. S. E. ascend
78.50	opposite bank bears. N. W. + S. E.
79.94	The Cor. to Secs. 4 + 5, 8 + 9. — Land, rough + broken Soil. Stony 3' + 4' rate Timber Pine + Cedar 45. chans.

Subdivisions.

- cha No^o 2' E on a random line
 Art. Secs. 4 & 5.
 Va. 13° 42' E.
- 40.00 Set temporary 1/4 Sec Cor.
- 79.60 Int. N. boundary of Tp. 5 lks. E.
 of Cor. to Secs. 4, 5, 32, & 33. herein-
 before described. Thence I run
 South, on a true line.
 bet. Secs. 4 & 5,
 Va 13° 42' E.
- In heavy Pine & Oak timber
- 7.75 Wagon Road to Winslow, bears N.E. & S.W.
- 31.30 Wagon Road to Winslow bears N.N.E. & S.S.W.
- 35.80 Brush fence bears E. & W.
- 39.00 Trail bears N.E. & S.W.
- 39.60 Set a Sandstone 18x11x6 ins 13 ins in
 the ground. for 1/4 Sec. Cor. marked
 1/4 on W. face. whence An Oak 6
 ins. diam. bears N 48° E 48 lks dist.
 marked 1/4 S. B. I. - A Pine 5 ins.

J. 14. N. R. 12. E.

chs.	diam. bears $S 60^{\circ} W$ 77 lks. dist, marked $\frac{1}{4}$ S. B. J. —
45.00	Pine 32 ins. diam. on line marked with 2 notches on N. & S. sides.
58.10	Trail. bears. N. W. & S. E.
60.50	Log fence bears. N $70^{\circ} W$ & $S 70^{\circ} E$
66.80	Wagon Road. bears. E. & W.
67.00	S. W. Cor. Log House bears. N $80^{\circ} E$ 13.90 chs.
79.60	The Cor. to Secs. 4, 5, 8 & 9, Land. rolling. Soil. gravelly, 2 ^d & 3 ^d rate Timber, Pine Oak & Juniper, 79.60 chs.
	November 8. 1893.

From the Cor. to Secs. 5, 6, 31 & 32, on the S. boundary of township heretofore described, I run. N $0^{\circ} 3' W$. bet. Secs. 31 & 32.
Ra. $13^{\circ} 42' E$

Subdivisions.

- chs. In heavy Pine & Oak timber
- 40.00 Set a Sandstone 16x10x5 ins 11
ins. in the ground. for $\frac{1}{4}$ Sec. Cor,
marked on N. face. $\frac{1}{4}$. whence
A Pine 14 ins. diam. bears N 73° E
39 lks. dist. marked $\frac{1}{4}$ S. B.T. -
A Pine 20 ins. diam. bears
N 70° W 30 lks. dist. marked
 $\frac{1}{4}$ S. B.T. -
- 80.00 Set a Sandstone 18x11x5 ins. 13 ins
in the ground. for. Cor. to Secs. 29,
30, 31 & 32, marked with 1 notch
on S. and 5 notches E. edges. whence
A Pine 40 ins. diam. bears
N 74° E 30 lks. dist. marked
S. 14, N. R. 12, E. S. 29 B.T.
A Pine 28 ins. diam. bears
S 44° E 67 lks. dist. marked
S. 14, N. R. 12, E. S. 32, B.T. -

T. 14. N. R. 12. E.

chs. A Pine 27 ins. diam. bears
 $S 63^{\circ} W$ 66 lks. dist. marked
 T. 14. N. R. 12. E. S. 31. B. T. —
 A Pine 20 ins. diam. bears
 $N 70^{\circ} W$ 36 lks. dist. marked
 T. 14. N. R. 12. E. S. 30. B. T. —
 Land level.
 Soil. Sandy. 1st rate.
 Timber. Heavy Pine & Oak 80, chs.

East. on a random line
 bet. Secs. 29 & 32.
 Va. $13^{\circ} 42' E$.

40.00 Set. temporary $\frac{1}{4}$ Sec. Cr.
 79.90 Int. N. & S. line. 10 lks. S. of Cor. to
 Secs. 28. 29 32 & 33. Thence I run
 $S 89^{\circ} 56' W$. on a true line.
 bet. Secs. 29 & 32.
 Va. $13^{\circ} 42' E$.

Subdivisions.

- chs. In heavy Pine & Oak timber
- 39.50 Bank bears N.T.S. descend
- 39.95 Set a sandstone 18x10x6 ins. 13 ins
in the ground. for 1/4 Sec Cor. marked
1/4 on N. face. whence. An Oak 6 ins
diam. bears. S 40° E 59 lks. dist,
marked 1/4 S. B.S. - A Pine 10 ins.
diam. bears. N 40° 30' W 14 3 lks. dist,
marked 1/4 S. B.S. -
- 40.50 Pine 24 ins. diam. on line marked
with 2 notches on E. & W sides.
- 47.25 Gulch 20 lks wide. runs. northw^{ard}
- 49.00 Opposite bank bears N.T.S. and
Pine 22 ins. diam on line marked
with 2 notches on E. & W. sides
- 63.50 Bank bears N.E. & S.W. descend
- 68.25 Gulch. 20 lks wide runs N.E. ^{ascend}
- 69.80 Pine 24 ins. diam. on line. mark
with 2 notches on E. & W. sides.

T. 14. N. R. 12. E.

chs.	
74.00	Opposite bank bears N.E. & S.W.
79.90	The Cr. to Secs. 29, 30, 31, & 32, Land, rolling. Soil, gravelly 2 ^d rate. Timber, heavy Pine & Oak 79.90 chs.

West bet. Secs. 30 & 31 on a true line
Va. 13° 42' E.

In heavy Pine & Oak timber

1.50	Bank bears N.E. & S.W. descend
6.00	Gulch 20 lks wide. runs N.E. ascend
13.00	Opposite bank bears N.E. & S.W.
40.00	Set a Sandstone 18 x 12 x 8 ins, 13 ins in the ground, for 1/4 Sec. Cr. mark 1/4 on N. face, whence A Pine 15 ins diam bears S 17° E. 19 lks. dist. marked 1/4 A. B. T. - A Pine 4 ins. diam. bears N 40 1/2 W 48

Subdivisions.

Chs.	lks. dist. marked $\frac{1}{4}$ S. B.S.
42.20	Circle 20 ins. diam. on line, marked with 2 notches on E. & W. Sides
49.00	Bank brass. N.E. & S.W. descend
55.40	Gulch 10 lks wide. runs N.E. ^{ascend}
57.85	Circle 32 ins. diam. on line Marked with 2 notches on E & W, Sides
58.50	Opposite bank brass N.E. & S.W.
83.00	Bank brass. N & S, descend
85.55	Gulch 10 lks wide. runs N. ascend
92.00	Bank brass. N & S,
93.00	Trail. brass. N.E. & S.W.
102.30	Intersect. W. boundary of Sp. 1220 chs. N. of Cor. to Secs. 25, 30, 31 & 36. a post. firmly set. and properly marked & Witnessed as described in the field notes furnished by the Surveyor Genl I obliterate the marks on the

T. 14. N. R. 12. E.

Chs. Past, and witness trees, referring
to T_p on the East. —

At above intersection I
set a Sandstone 18x12x8 ins. 13.
ins. in the ground. for Closing
Sec. Cor. to Secs. 30+31. Marked
C.C. on E. with 1 notch on S.
and 5 notches on N. faces. Whence
A Pine 8 ins. diam. bears.

N 55° E 31 lks. dist. marked
T. 14. N. R. 12. E. S. 30 B. T.

A Pine 9 ins. diam. bears
S 60° E 32 lks. dist. marked
T. 14. N. R. 12 E. S. 31 B. T.

A Pine 8 ins. diam. bears.
S 62° W 43 lks. dist. marked
T. 14. N. R. 12. E. C. C. S. 30, X 31. B. T.

Land, nearly level

Soil, sandy & gravelly 2^d rate
Timber heavy Pine & Oak 102.30 chs.

Subdivisions.

chs. No° 3'W. bet. Secs. 29. & 30.
Ta 13°42'E.

In heavy Pine & oak timber.

- 4.40 Bank bears N.E. & S.W. descend
11.10 Enter gulch
12.00 Leave gulch runs N.E.
16.00 Re-enter gulch
17.25 Leave gulch runs N.W.
40.00 Set a Sandstone 16x11x4 in. 11 in
in the ground for 1/4 sec. Cor marked
1/4 on W. face. whence A Pine 26 in
diam. bears N40°E 4 lks. dist,
marked 1/4 S. B. I. - A Pine 24.
in. diam bears S27°W 50 lks dist,
marked 1/4 S. B. I. -
41.40 Re-enter gulch
43.00 Leave gulch runs N.N.E. ascend
43.50 Ridge bears N.E. & S.W. descend
45.90 Gulch 10 lks wide, runs N.E. ascend

T. 14. N. R. 12. E.

- chs.
 62.50 Opposite bank trans. N.E. + S.W.
 73.60 Gulch 10 lks wide, runs N.E. and
 77.75 Bank trans. N.E. + S.W.
 80.00 Set a Sandstone 16x12x10 ins //
 ins. in the ground. for Cor to Secs.
 19, 20, 29 + 30. Marked with 2
 notches on S. and 5 notches on E. edges
 whence A Pine 26 ins. diam trans
 N 26° E 20 lks. dist. marked
 T. 14, N. R. 12, E, S. 20 B.S.
 A Pine 22 ins. diam. trans
 S 87° E 26 lks. dist. marked
 T. 14, N. R. 12, E, S. 29 B.S. -
 A Pine 20 ins. diam. trans
 S 29° W 40 lks. dist. marked
 T. 14, N. R. 12, E, S. 30. B.S.
 A Pine 19 ins. diam. trans
 N 77° W 101 lks. dist. marked
 T. 14, N. R. 12, E, S. 19 B.S. -

Subdivisions.

chs. Land rollings
 Soil. Sandy & gravelly 2^d & 3^d rds
 Timber. Heavy Pine & Oak. 80 chs.
 November 9. 1893.

N 89° 56' E on a random line
 bet Secs. 20 & 29,
 Va. 13° 42' E

40.00 Set. temporary 1/4 Sec. Cor.

79.90 Int. N & S. line 5 Mrs. S. of Cor to
 Secs. 20. 21. 28 & 29. Thence I run
 S 89° 54' W on a true line
 bet. Secs. 20 & 29,
 Va 13° 42' E

In heavy Pine & Oak timber ^{around}

3.80 Bank cross N.E. & S.W.

39.95 Set a Sandstone 16x12x9 ins. 11 in
 in the ground. for 1/4 Sec Cor. marked
 1/4 on N. face. whence A Pine 10 in

T. 14. N. R. 12. E.

- Chs. diam. bears. N74°E 39 lks. dist.
marked 1/4 S. B.L. - A Pine 11
ins diam. bears S53°W 34 lks.
dist. marked 1/4 S. B.L. -
- 56.80 Bank bears. N.E. & S.W. descend
- 69.85 J. rail. bears. N.E. & S.W.
- 70.45 Gulch 20 lks wide. runs N.E. ^{ascend}
- 76.70 Opposite bank bears. N.E. & S.W.
- 79.90 The Cor. to Secs. 19, 20, 29 & 30.
Land rolling.
Soil. gravelly 2^d & 3^d rate
Timber. Pine & Oak, 79.90 chs.

West on a true line.

bet. Secs. 19 & 30.

9 in heavy ^{Timber} Var 13°42'E.

- 40.00 Set a Sandstone 18X10X4 ins. B is
in the ground. for 1/4 Sec. Cor. marked
1/4 on N. face. where A Pine 10 ins.

Subdivisions.

- chs. diam. bears S52°E 20 lks. dist.
marked 1/4 S. B. I. - A Pine 11 ins.
diam. bears N77°E 28 lks. dist.
marked 1/4 S. B. I. -
- 62.00 Bank bears N. & S. descend
- 63.90 Gulch 10 lks. wide runs northerly ^{and}
- 67.00 Ridge bears N.N.E. & S.S.W. descend
- 70.60 Gulch 20 lks wide runs N.N.E. ^{and}
- 74.00 Opposite bank bears N.N.E. & S.S.W.
- 102.70 Intersect W. boundary of Sp. 12, 50
chs. N. of Cor. to Secs. 19, 24, 25 & 30
A. Post. firmly set, and properly
marked & witnessed, as described
in the field notes furnished by
the Surveyor General. -
I obliterate the marks on the
Post. and witness trees, referring
to Sp. on the East. -
At the above intersection I

T. 14. N. R. 12. E.

chs. Set a Sandstone 24x12x6 ins. 18
 ins in the ground. for Closing Cor.
 to Secs. 19 & 30. marked C.C. on
 E. with 2 matches on S. and 4
 matches on N. faces. Whence
 A Pine 30 ins. diam. bears
 N 26° E 57 lks. dist. marked
 T. 14. N. R. 12. E. S. 19 B.T. -
 A Pine 28 ins. diam. bears
 S 32° E 17 lks dist. marked
 T. 14. N. R. 12. E. S. 30. B.T. -
 A Pine 10 ins. diam. bears
 S 25° W 16 lks. dist. marked
 T. 14. N. R. 12. E. C.C. Ss 19 & 30 B.T.
 Land. nearly level.
 Soil. Sandy & gravelly 2^d & 3^d rate
 Timber Heavy Pine oak 102.70 chs.

Subdivisions.

- chs. No° 3' W. bet. Secs. 19, & 20.
Va 13° 42' E
- In heavy Pine & Oak timber ^{ascend}
- .35 Pine 22 ins. diam. on line, marked
with 2 notches on N. & S. sides
- 16.50 Bank bars N.E. & S.W. onto main.
- 39.65 Bank bars. N.E. & S.W. descend
- 40.00 Set a Sandstone 20 x 15 x 10 ins. 15
ins. in the ground, for 1/4 Sec. Cor.
marked 1/4 on W. face. whence a Pine
10 ins. diam. bars N 15° E 24
lks. dist. marked 1/4 S. B.S.
- A Pine 14 ins. diam. bars S 50° W
38 lks. dist. marked 1/4 S. B.S.
- 52.30 Gulch 20 lks. wide. runs N.E. ^{ascend}
- 68.00 Opposite bank bars N.E. & S.W.
- 80.00 Set a Sandstone 24 x 15 x 5 ins. 18.
ins. in the ground. for. Cor. to Secs
17, 18, 19, & 20. marked with 3

J. 14. N. R. 12. E.

Chs. Notches on S. and 5 notches on E. edges. Whence

A Pine 14 ins. diam. bears
N 18° E. 71 lks. dist, marked
J. 14, N. R. 12, E. S. 17 B. T. —

A Pine 5 ins. diam. bears
S 41½° E 63 lks. dist, marked
J. 14, N. R. 12, E. S. 20 B. T. —

A Pine 7 ins. diam. bears
S 47° W 46 lks. dist, marked
J. 14, N. R. 12, E. S. 19 B. T. —

A Pine 15 ins. diam. bears
N 52° W 38 lks. dist, marked
J. 14, N. R. 12, E. S. 18 B. T. —

Land, nearly level,

Soil, Sandy & gravelly, $\frac{2}{3}$ & $\frac{1}{3}$ shale,
Timber, Heavy Pine & Oak, 80. chs.

Subdivisions.

- chs. $N 89^{\circ} 54' E$ on a random line
 bet. sees. 17 & 20,
 Va. $13^{\circ} 42' E$,
- 40.00 Set temporary $\frac{1}{4}$ Sec. Cr.
- 79.80 Int. N. & S. line 14 lks. N. of
 Cor. to sees. 16, 17, 20, & 21. I run
 West. on a true line,
 bet. sees. 17 & 20,
 Va $13^{\circ} 42' E$.
- In heavy Pine & Oak timber ^{ascend}
- 5.30 Bank trans N.W. & S.E. entire mesa
- 9.80 Bank trans N.E. & S.W. descend
- 14.30 Gulch 10 lks wide. runs N.E. ascend
- 21.30 Bank trans N.E. & S.W. Entire mesa
- 39.90 Set a Sandstone $18 \times 10 \times 6$ ins. 13 ins,
 in the ground. for $\frac{1}{4}$ Sec. Cr. marked
 $\frac{1}{4}$ on N. face. Whence a Pine 16 ins,
 diam. trans $S 58^{\circ} W$ 67 lks. dist.
 marked $\frac{1}{4}$ S. B. S. - a Pine 18 ins

T. 14. N. R. 12. E.

chs.	diam, beans N72°W 43 lks. dist. marked 1/4 S. B. L. —
58.30	Bank beans. N.W. to S.E. descend
60.40	Gulch 10 lks. wide, runs. N.W. ascend
69.30	Ridge beans N. to S. descend
71.90	Gulch 20 lks. wide runs. northerty
72.60	Leaved bottom & ascend
79.80	The Cor. to Secs. 17, 18, 19, & 20. Land, rolling, Soil, gravelly, 2 ^d rate. Timber. Heavy Pine & Oak 79.80 chs. November 10, 1893.

West. on a true line
bet. Secs. 18 & 19.
Va. 13°42'E

In Heavy Pine timber

12.00	Bank beans N. to S. descend
19.80	Gulch 10 lks wide, runs, northerty ^{ascend}

Subdivisions.

Cho.	
25.00	Opposite bank bears. N + S, Enter mesa
25.75	Right bank Clear Creek Cañon bears. N.E. + S.W. and leave timber
27.00	Descend abruptly.
32.20	Clear Creek Cañon 100 lks wide ^{and} runs N.E.
38.60	Ridge bears N.E. + S.W descend
40.00	Set a Sandstone 18 X 10 X 8 ins. 13.
	ins. in the ground; for 1/4 Sec Cor.
	marked 1/4 on N. face, and raised
	a mound of stone 1 1/2 ft. high 2 ft.
	base, alongside. pits impracticable
	No trees within limits.
44.70	Begin ascent of Left bank
72.50	Left bank Clear Creek Cañon bears.
	S.W. E. N.E. then E. and enter timber
75.50	Fence bears S 40° W + N.
76.50	S.E. Cor. Log house bears. N. 40 lks dist.
83.00	Trail bears N.E. + S.W.
102.48	Entered N. boundary of the Sp.
	12.54 Cho. N. of Cor. 1/8 Secs.

T. 14. N. R. 12. E.

Chs. 13, 18, 19 & 24. A post firmly set and properly marked and witnessed as described in the field notes furnished by the Surveyor General. I obliterate the marks on the Post and Witness trees, referring to Sp on the East.

At foregoing intersection I set a Sandstone $18 \times 13 \times 8$ ins. 13 ins in the ground, for Closing Cor. to Secs. 18 & 19, marked C.C. on E. with 3 notches on N. & S. faces, whence

A Pine 14 ins. diam. bears $N 19^\circ E$ 109 lks. dist. marked T. 14. N. R. 12. E. S. 18. B. S.

A Pine 10 ins. diam. bears $S 60^\circ E$ 62 lks. dist. marked T. 14. N. R. 12. E. S. 19 B. S. —

A Pine 8 ins. diam. bears

BOOK 155
Subdivisions.

chs. S44° W 31 lks. dist. marked
T. 14, N. R. 12, E., C.C. S. 18 & 19, B.S.
Land. Very rough & broken,
Soil. gravelly & rocky. 2^d & 4th rate
Timber. Pine & Oak 55. ¹³chs.

N 0° 3' W. but. Secs. 17 & 18,
T. 13° 42' E.

In heavy Pine & Oak timber

- 25.50 Bank bears E. & W. descend
- 29.70 Gulch 10 lks wide runs ^{used} westerly
- 33.50 Opposite bank bears E & W.
- 34.80 Pine 20 ins. diam. on line marked
with 2 notches on N. & S. side
- 40.00 Pine 12 ins. diam. which I mark
1/4 S. on N. side for 1/4 Sec Cor.
Whence A Pine 13 ins. diam. bears
S 34° W 15 lks. dist marked 1/4 S. B.S.
A Pine 14 ins. diam. bears.

T. 14. N. R. 12. E.

- Chs. N 3° E 15 lks. dist marked 1/4 S. B. J.
- 41.70 Bank trans. N.W. + SE. descend
- 45.80 Gulch 10 lks wide runs N.W. ^{ascend}
- 50.00 Opposite bank trans. N.W. + SE.
- 63.50 Right bank Clear Creek Cañon from N.E. ^{descend} + S.W. ^X
and leave timber
- 65.25 Descend abruptly.
- 74.20 Clear Creek Cañon 80 lks. wide runs N.E. ^{ascend}
- 80.00 Set a sandstone 17x10x5 ins. 12 ins.
in the ground. for Cor. to Secs. 7, 8,
17, & 18. marked with 4 notches on S.
and 5 notches on E. edges, and raised
a mound of stone 1 1/2 ft. high 2 ft.
base alongside. pits impracticable
No trees within limits
Land. rough & broken.
Soil. Stony. 4th rate.
Timber. Pine & Oak. 63.50 chs.

Subdivisions.

- chs. East, on a random line
bet. Secs. 8 & 17.
Va. $13^{\circ}42'E$.
- 40.00 Set temporary $\frac{1}{4}$ Sec Cor.
80.06 Int. N & S. line at Cor. to Secs. 8, 9,
16, & 17. Thence I run.
West, on a true line
bet. Secs. 8 & 17.
Va $13^{\circ}42'E$.
- 1.00 In pine timber
Bank bears N.E. & S.W.
- 2.50 Descend abruptly 18 feet.
- 6.20 Gulch 20 lks wide runs N.E. ^{about}
- 20.30 Bank opposite bears N.E. & S.W. Enters mesa
- 40.03 Set a Sandstone $16 \times 11 \times 7$ in 11 in
in the ground. for $\frac{1}{4}$ Sec Cor. marked
 $\frac{1}{4}$ on N. face. When a Pine 8 in
diam, bears N 10° W. 42 lks dist.
marked $\frac{1}{4}$ S. B. S. - A Pine 12 in diam
bears S 46° W 18 lks. dist. marked $\frac{1}{4}$ S. B. S.

T. 14. N. R. 12. E.

- 66.80 Right bank Clear Creek Cañon bears N. + S,
and leave timber ^{dead}
- 76.90 Clear Creek Cañon. 80 lks wide runs. N. by S, ^{West}
- 80.06 The Cor. to Secs. 7, 8, 17 + 18,
Land. rough + broken.
Soil. Stony. 3^d + 4th rate.
Timber. Scattering Pine. 66^{so} lks

West on a true line.

bet. Secs. 7 + 18.

In Cedars
Bearing $13^{\circ} 42' E$

- 2.70 Trail. bears N.W. + S.E. ascend
- 20.20 Left bank Clear Creek Cañon bears N.E. + S.W.
- 23.20 Leave Cedars and enter Pines
- 40.00 Set a Sandstone 16 x 10 x 5 ins. 11 ins
in the ground. for $\frac{1}{4}$ Sec. Cor. marked
 $\frac{1}{4}$ on N. face. whence An Oak 4 ins
diam. bears. N $46^{\circ} W$ 48 lks. dist.
marked $\frac{1}{4}$ S. B. T. - An Oak 5 ins.
diam. bears. S $24^{\circ} E$ 90 lks. dist.

Subdivisions.

- Chs. marked $1/4$ S. B. T. -
- 51.40 Pine 20 ins. diam. on line marked with 2 notches on E. & W. Sides
- 66.70 Bank trans. N.E. & S.W. descend
- 72.60 Gulch 10 lks wide. runs N.E. ascend
- 72.75 Trail. trans. N.E. & S.W.
- 84.70 Opposite bank trans. N.E. & S.W.
- 94.60 Pine 16 ins. diam. on line. marked with 2 notches on E. & W. Sides
- 98.50 Pine 40 ins. diam. on line. marked with 2 notches on E. & W. Sides.
- 102.60 Intersect. N. boundary of Sp. 13.04
Chs. N. of Cor. to Secs. 7, 12, 13 & 18.
A Post. firmly set. properly marked and witnessed as described in the field notes furnished by the Surveyor General.
I obliterate the marks on the Post. and witness trees referring

T. 14. N. R. 12. E.

Chs. to Sp. on the E. —

At the foregoing intersection I set a Sandstone 16x10x6 ins. 11 ins in the ground, for Closing Cor. to Sec. 7x18. Marked C.C. on E. with 4 notches on S. and 2 notches on N. faces
Whence A Pine 10 ins. diam. bears,

N 71° E 42 lks. dist. marked
T. 14. N. R. 12. E. S. 7. B.T. —

A Pine 18 ins. diam. bears.

S 15° E. 35 lks. dist. marked
T. 14. N. R. 12. E. S. 18. B.T.

A Pine 17 ins. diam. bears.

S 25° W 43 lks. dist. marked
T. 14. N. R. 12. E. C.C. Ss 7x18. B.T. —

Land. broken.

Soil. gravelly 2^d + 3^d rate,

Timber. Pine + Cedar 102.60 chains.

November 11. 1893.

Subdivisions.

Chs.	No ^o 3' W. bet. Secs. 7 & 8. Va 13° 42' E
	Along W. Slope of Clear Creek Canon
31.50	Gulch 20 lks wide runs. Eastward ^{and}
40.00	Set a Sand stone 16x10x8 ins. 11 ins in the ground. for 1/4 Sec Cor. Marked 1/4 on W. face. and raised a mound of Stone 1 1/2 ft. high. 2 ft. base along side. pits impracticable. No trees within limits. -
48.70	Left bank of Clear Creek Canon trans. N.E. + S.W.
55.00	Enter Pine & Juniper timber
57.30	Bank trans N.W. + S.E. descend
61.60	Gulch 20 lks. wide runs. S.E. ^{and}
71.50	Opposite bank. trans. N.W. + S.E.
80.00	Set a Sand stone 17x11x8 ins 12 ins in the ground. for Cor. to Secs. 5, 6, 7 & 8. Marked with 5 notches on S. + E edges whence. A Pine 14 ins. diam. trans N 15° E 7 lks. dist. marked.

T. 14. N. R. 12. E.

Chs. T. 14. N. R. 12. E. S. 5. B. J. -

A Pine 10 ins. diam. trans

S 75° E 43 lks. dist. marked

T. 14. N. R. 12. E. S. 8. B. J. -

A Juniper 10 ins. diam. trans

S 41° W 22 lks. dist. marked

T. 14. N. R. 12. E. S. 7. B. J. -

A Pine 9 ins. diam. trans.

N 89 1/2° W 45 lks. dist. marked

T. 14. N. R. 12. E. S. 6 B. J. -

Land, Very rough & broken.

Soil, rocky. 4th rate.

Timber, Pine & Juniper, 25.00 chs.

East on a random line

bet. Secs. 5 & 8.

Va 13° 42' E.

40.00 Set. Temporary 1/4 Sec. Cor.

80.42 Int. N. & S. line 12 lks. S. of

Subdivisions.

- Chs. Cor. to Secs. 4, 5, 8 & 9. Thence I run
 $S 89^{\circ} 55' W.$ on a true line
 bet. Secs. 5 & 8,
 To $13^{\circ} 42' E.$
 over rolling ground, in pines & cedars.
- 40.21 Set a Sandstone $18 \times 10 \times 5$ ins, 13
 ins. in the ground, for $\frac{1}{4}$ sec cor
 marked $\frac{1}{4}$ on N. face, whence
 A Pine 15 ins. diam. bears $N 50^{\circ} W$
 8 lks. dist. marked $\frac{1}{4}$ S. B.S. -
 A Cedar 5 ins. diam, bears $S 27^{\circ} E$
 42 lks. dist. marked $\frac{1}{4}$ S. B.S.
- 49.30 Bank bears N.W. & S.E. descend
- 65.40 Leave Cedar
- 66.70 Gulch 10 lks. wide runs S.E. ^{ascend}
- 74.90 Opposite bank bears N.W. & S.E.
- 80.42 The Cor. to Secs. 5, 6, 7, & 8.
 Land broken,
 Soil, gravelly & stony 3^d & 4th rate

Chs. Timber Scattering Pine & Cedar 80⁴² Chs.

West on a true line.

bet. Secs. 6 & 7.

7a. 13°42'E.

In heavy Pine timber descend

10.45 Gulch 10 lks. wide runs S.E. ^{ascend}

31.50 Opposite banks bears N.W. & S.E.

40.00 Set a Sandstone 17x10x5 ins. 12 ins
in the ground. for $\frac{1}{4}$ Sec. Cor. -

Marked $\frac{1}{4}$ on N. face. whence

A Pine 14 ins. diam. bears N29°E

34 lks. dist. marked $\frac{1}{4}$ S. B.S. -

A Pine 6 ins. diam. bears S86°E

8 lks. dist. marked $\frac{1}{4}$ S. B.S. -

81.40 Trail, bears N.W. & S.E.:

102.52 Intersect. W. boundary of Township,

12.60 chs. N. of Cor. to Secs. 1. 6. 7

+ 12. A Post. firmly set. properly

Subdivisions.

Chs. Marked and witnessed, as described in the field notes furnished by the Surveyor General. —

I obliterate the marks, on the Post, and witness trees, referring to T. on the E. —

At the foregoing intersection I set a Sandstone $20 \times 11 \times 5$ ins. 15 ins. in the ground, for Closing Cor. to Secs 6 & 7, marked C.C. on E. with 5 notches on S. and 1 notch on N. faces. Whence

An Oak 5 ins. diam. bears
 $N 62^\circ E$ 66 lks. dist. marked
 T. 14, N. R. 12, E. S. 6, B. S. —

An Oak 4 ins. diam. bears
 $S 75^\circ E$ 28 lks. dist. marked
 T. 14, N. R. 12, E. S. 7, B. S.

A Pine 20 ins. diam. bears

T. 14. N. R. 12. E.

cho. S 85° W 33 lks dist. marked
 T. 14. N. R. 12. E. C.C. As 6, & 7, B.S.
 Land, nearly level.
 Soil, gravelly. 2^d rate
 Timber, heavy Pine & Oak 102.52 chs.

North, on a random line.

bet. Secs. 5 & 6.

Va. 13° 42' E.

40.00 Set. temporary 1/4 Sec Cor.

79.92 Int. N. boundary of Sp. 7 lks. E. of
 the Cor. to Secs. 5, 6, 31 & 32. Hereinbefore
 described. Thence True.

S 0° 3' E on a true line

bet. Secs. 5 & 6.

Va. 13° 42' E.

In heavy Pine & Oak timber

33.70 Wagon Road to Winslow bears E. N. E. & W. S. W.

39.92 Set. a Sandstone 18 X 11 X 7 ins 13.

BICK 155

Subdivisions S. 14, N. R. 12, E.

chs. ins in the ground for $\frac{1}{4}$ Sec. Cor.
marked $\frac{1}{4}$ on W. face. whence

A Pine 12 ins. diam. bears $N 37^{\circ} E$

23 lks. dist. marked $\frac{1}{4}$ S. B.C. -

A Juniper 16 ins. diam. bears $S 60^{\circ} W$

18 lks. dist. marked $\frac{1}{4}$ S. B.C.

50.90 Wagon Road to Winston bears E. by S. + W. by N.

79.92 The Cor. to Secs. 5, 6, 7, & 8.

Land. nearly level

Soil. Sandy & gravelly 2^d rate

Timber heavy Pine Oak & Juniper 79.92 chs

November 13, 1893.

45 miles, 12 chains, and 58 lks.
run through heavy Pine and
Oak timber.

General Description.

This township contains some very rough land. Cut by immense cañons. the soil is gravelly. of a fair quality. producing some magnificent pine timber. also fine native grasses. affording abundant pasturage. for the cattle horses & sheep that roam over its surface.

Clear Creek Cañon. contains abundant water. at all seasons of the year. There are two houses. one in Secs. 4, 7, 18. The mean declination for the plat. the mean of five observations is $13^{\circ}42'E$.

Daniel Drummond
U. S. Deputy Surveyor

U.S. Surveyor-General's Office,

Tucson, A.T. October 9th, 1895.

The foregoing Field Notes of the Surveys
of the Subdivisions of Township No. 14 N.
Range No. 12 East, Gila & Salt River
Meridian in Arizona, executed by

DANIEL DRUMMOND

U.S. Deputy Surveyor, under his Contract
dated Febry, 21st 1893, having been
critically examined, the necessary
corrections and explanations made, the
said Field notes and the Surveys they
describe are hereby approved.

Levi H. Manning
U.S. Surveyor General.

for the Territory of Arizona.