

T. 14 N. R. 13. E

No-157

Subdivisions

4-671

157

FIELD NOTES
GENERAL LAND OFFICE.

Sp. 14 N. R. 13 E.

No-157

60.56.04

Indexed, Book 156,

No-137

Township 14 N R. 13 E

6	108	5	80	4	603	2	1
107		105		78			
7	103	8	76	9	10	11	12
101		100		75			
18	98	17	73	16	15	14	13
96		94		71			
19	93	20	69	21	22	23	24
91		90		67			
30	88	29	65	28	27	26	25
86		84		63			
31	82	32	61	33	34	35	36

Subdivisions T. 14. N. R. 13. E.

- chs. North. on a random line.
bet. Secs. 3, 4.
- Va $13^{\circ}44' E$
- 10.00 Set temporary $\frac{1}{4}$ Sec. Cor.
- 18.04 Int. N. boundary of Tp. 46 lks.
N. of Cor. to Secs. 3, 4, 33 & 34. From
Thence Iron.
- $S 0^{\circ}20' W$ on a true line.
bet. Secs. 3 & 4.
- Va. $13^{\circ}44' E$.
- In Cedars and Pinon
- 18.04 Set a sandstone $18 \times 11 \times 4$ ins. 13 ins.
in the ground. for $\frac{1}{4}$ Sec. Cor. marked
 $\frac{1}{4}$ on N. face. whence A Pin 5 ins. diam.
trans $N 31\frac{1}{2} E$ 40 lks. dist. marked
 $\frac{1}{4}$ S. B. I. - A Pin 5 ins. diam.
trans. $N 76^{\circ} W$ 9 lks. dist. marked
 $\frac{1}{4}$ S. B. I. -
Fruit trans. N.E. & S.W.
- 53.00
- 75.30 Bank trans. N.E. & S.W. descent
- 18.04 The Cor. to Secs. 3, 4, 9 & 10.

Subdivisions. S. 14. N. R. 13. E.

Chs. Land. nearly level
 Soil. gravelly. 2^d + 3^d rate
 Timber. Piñon & Cedar, 78.04 chs.
 October 20. 1893.

From the Cor. to Secs. 4. 5. 32. & 33.
 on the S. boundary of the Township.
 Hereinafter described. From
 $N 0^{\circ} 2' W.$ bet. Secs. 32. & 33.
 $7/8$ Va. $13^{\circ} 44' E.$

In heavy Pine & oak timber

- 2.40 Pine 14 ins. diam. on line, marked
 with 2 notches on N. & S. Sides.
- 18.80 Pine 20 ins. diam. on line, marked
 with 2 notches on N. & S. Sides.
- 40.00 Set a Sandstone $18 \times 14 \times 4$ ins. 13 ins.
 in the ground. for $1/4$ Sec. Cor. marked
 $1/4$ on W. face. whence a Pine 22 ins.

Subdivisions.

- Chs. diam. bears $N 79^{\circ} E$ 95. lks. dist.
marked $\frac{1}{4}$ A. B. J. - A Pine 6 ins. diam.
bears. $S 50^{\circ} W$ 86 lks. dist. marked $\frac{1}{4}$ S. B. J.
- 56.45 Pine 12 ins. diam. on line. marked
with 2 notches on N. & S. Sides.
- 80.00 Set a Sandstone $16 \times 14 \times 5$ ins. 11 ins.
in the ground. for Cor. to Secs. 28, 29
32, & 33. Marked with 1 notch on S.
and 4 notches on E. edges. whence
An Oak 4 ins. diam. bears
 $N 10^{\circ} E$. 51 lks. dist. marked
T. 14. N. R. 13. E. S. 28 B. J.
A Pine 5 ins. diam. bears
 $S 45^{\circ} E$ 82 lks. dist. marked
T. 14. N. R. 13. E. S. 33. B. J.
An Oak 5 ins. diam. bears.
 $S 79^{\circ} W$ 81 lks. dist. marked
T. 14. N. R. 13. E. S. 32. B. J.
An Oak 4 ins. diam. bears.

T. 14. N. R. 13. E.

Chs. N 34° W 56 lks. dist. marked
 T. 14. N. R. 13. E. S. 29 B.S. —
 Land. level.
 Soil. Sandy & gravelly 2^d rate.
 Timber Heavy Pine & Oak. 80. chs.

S 89° 59' E. on a random line
 bet. Secs. 28 & 33.
 Va. 13° 44' E

40.00 Set temporary 1/4 Sec. Cor.

80.07 Int. N. + S. line. 10 lks. S. of Cor. to
 Secs. 27, 28, 33 & 34. Thence I run
 S 89° 57' W. on a true line.
 bet. Secs. 28 & 33.

Va. 13° 44' E

In heavy Pine & Oak timber

18.10 Trail. bears N. E. + S. W.

25.00 Bank bears N. W. + S. E. descend

BOOK 157, 64.
 Sub divisions.

31.90	Chs. Gulch 15 lks wide, runs N.W. ascend
32.30	Trail bears N.W. + S.E.
34.00	Opposite bank bears N.W. + S.E.
40.03	Set a Sandstone 18x10x6 ins. 13 ins in the ground. for. $\frac{1}{4}$ Sec. Cor. marked $\frac{1}{4}$ on N. face. whence. A Pine 24 ins diam. bears N 20° E 60 lks. dist. marked $\frac{1}{4}$ S. B. L. - An Oak 8 ins, diam. bears S 25° W 90 lks dist. marked $\frac{1}{4}$ S. B. L. -
41.00	Bank bears N.E. + S.W. descend
43.70	Gulch 10 lks wide, runs N.E. ascend
48.50	Opposite bank bears N.E. + S.W.
55.00	Bank bears N by E. + S by W, descend
61.50	Pine 12 ins. diam. on line marked with 2 notches on E. + W. Sides.
62.60	Gulch 20 lks. wide runs N. by E. ^{ascend}
66.50	Opposite bank bears N by E. + S by W
80.07	The Cor. to Secs. 28, 29, 32, + 33.

T. 14. N. R. 13. E.

chs. Land, nearly level.
 Soil Gravelly, 2^d rate.
 Timber heavy Pine & Oak, 80.07 chs

N 0° 2' W. bet. Secs. 28 & 29
 Ta 13° 44' E

In heavy Pine & Oak timber

- 37.55 Pine 24 ins. diam. on line, marked
 with 2 notches on N. & S. Sides.
- 40.00 Sep. a Sandstone 16x10x8 ins. 11
 ins. in the ground. for 1/4 Sec. Cor.
 marked 1/4 on W. face. whence a Pine
 8 ins. diam. bears. S 18° W 34 lks.
 dist. marked 1/4 S. B.L. - An oak
 6 ins. diam. bears. S 82° E 12 lks
 dist. marked 1/4 S. B.L. -
- 61.85 Bank bears. NNE. + S.S.W. descends
- 63.50. Entu bottom.

Subdivisions.

- chs.
67.45 Gulch 10 lks. wide runs N.N.E.
- 69.65 Learn bottom. & ascends
- 72.50 Opposite bank bears N.N.E. & S.S.W
- 80.00 Set a Sandstone 18x12x5 ins. 13.
ins. in the ground. for Cor. to Secs.
20, 21, 28 & 29. Marked with 2
natches on S, and 4 natches on
E. edges. Whence —
- A Pine 12 ins. diam bears
N 86° E. 78 lks. dist. marked
T. 14, N. R. 13, E. S. 21. B. J.
- A Pine 10 ins. diam. bears
S 52° E 74 lks. dist. marked
T. 14, N. R. 13, E. S. 28. B. J.
- A Pine 4 ins. diam. bears
S 30° W 56. lks. dist. marked
T. 14, N. R. 13, E. S. 29 B. J.
- An Oak 4 ins. diam. bears
N 16° W 26 lks. dist. marked

T. 14. N. R. 13. E.

chs. T. 14. N. R. 13. E. S. 20 B. T.

Land. level.

Soil. gravelly. 2^d rate

Timber. Heavy Pine & Oak, 80. chs.

N $89^{\circ}57'E$ on a random line

bet. Secs. 21 & 28.

Va. $13^{\circ}44'E$ 40.00 Set temporary $\frac{1}{4}$ Sec. Cor.

80.10 Int. N. & S. line 7 lks. N. of Cor. to

Secs. 21, 22, 27 & 28. Thence I run.

West on a true line

bet. Secs. 21 & 28.

Va. $13^{\circ}44'E$

In heavy Pine & Oak timber

8.45 Pine 24 ins. diam. on line, marked
with 2 notches on E. & W. sides.

22.80 Bank bears N.E. & S.W. descend

Subdivisions.

chs. 27.00	Pine 22 ins. diam. on line, marked with 2 notches on E. & W. sides.
33.00	Enter bottom.
33.30	Trail. bears. N.E. & S.W.
33.75	Gulch 10 lks. wide. runs N.E., ascend
37.00	Ridge bears. N.E. & S.W. descend
40.05	Set a sandstone 22 x 14 x 6 ins. 16 ins. in the ground. for $\frac{1}{4}$ Sec. Cr. marked $\frac{1}{4}$ on N. face. whence A Pine 10 ins diam. bears S 38 W 20 lks. dist. marked $\frac{1}{4}$ S. B. T. - A Pine 26 ins. diam. bears. N 70° W 13 lks. dist. marked $\frac{1}{4}$ S. B. T. -
41.50	Gulch 10 lks. wide. runs N.E., ^{ascend}
54.00	Opposite bank bears. N.E. & S.W.
69.00	Bank bears. N.E. & S.W. descend
74.85	Gulch 10 lks wide runs N.E., ascend
75.00	Trail. bears. N.E. & S.W.
78.50	Opposite bank bears. N.E. & S.W.

chs.
80.10

The Cor. to Secs. 20, 21, 28 & 29

Land rolling

Soil, gravelly, 3^d + 4th rate

Timber heavy Pine & Oak, 80.10 chs.

N 0° 2' W. bet. Secs. 20 & 21.

Ta. 13° 44' E

In heavy Pine & Oak timber.

11.20 Pine 14 ins. diam. on line, marked
with 2 notches on N. & S. sides.17.55 Pine 28 ins. diam. on line, marked
with 2 notches on N. & S. sides.

20.50 Banks, trans. N.E. & S.W. descend

22.00 Enter bottom

25.00 Gulch 20 ft. wide, runs N.E. ^{ascend}

26.00 Leave bottom & ascend

40.00 Set a sandstone 20 x 11 x 5 ins. 15
ins. in the ground, for 1/4 Sec. Cor

Subdivisions.

- Chs. $\frac{1}{4}$ on W. face, whence A Pine
10 ins. diam. bears. N80°W 12
lks. dist. marked $\frac{1}{4}$ S. B.S.
- An Oak 5 ins. diam. bears N73°E
70 lks. dist. marked $\frac{1}{4}$ S. B.S.
- 42.50 Opposite bank bears. N.E. & S.W.
- 80.00 Set a sandstone 30x10x8 ins. 22
ins. in the ground. for. Cor. to Sec
16, 17, 20, 21. Marked with 3
notches on S. and 4 notches on
E. edges. Whence
- An Oak 4 ins. diam. bears.
N28 $\frac{1}{2}$ °E 104 lks. dist. marked
S. 14. N. R. 13. E. S. 16. B.S.
- A Pine 15 ins. diam. bears.
S10°E 74 lks. dist. marked
S. 14. N. R. 13. E. S. 21. B.S.
- An Oak 7 ins. diam. bears.
S43°W 5 lks. dist. marked

T. 14. N. R. 13. E.

Chs. T. 14. N. R. 13. E. S. 20. B. 4.

An Oak 5 ins. diam. bears N 55° W
11 lks. dist. marked.

T. 14. N. R. 13. E. S. 17. B. 1.

Land. nearly level.

Soil. gravelly 2^d rate.

Timber heavy Pine & Oak, 80. chs.

East. on a random line

bet. Secs. 16 & 21.

Va. 13° 44' E.

40.00 Set. temporary 1/4 Sec. Cor.

80.42 Int. N. & S. line 5 lks. S. of Cor. to

Secs. 15, 16, 21 & 22, thence I run

S 89° 58' W. on a true line

bet. Secs. 16 & 21.

Va. 13° 44' E.

In heavy Pine & Oak timber ^{as usual}

.20 Oak bears N.E. & S.W.

Subdivisions.

- chs.
14.00 Bank trans. N.E. + S.W. descend
24.15 Entu bottom
24.35 Trail. trans. N.E. + S.W.
25.00 Gulch 10 lks wide. runs N.E. ^{ascend}
40.00 opposite bank trans. N.E. + S.W.
40.21 Set a Sandstone 18x12x4 ins. 13
ins. in the ground for $\frac{1}{4}$ Sec Cor.
marked $\frac{1}{4}$ on N. face. whence a
A Pine 16 ins. diam trans S45°E
63 lks. dist marked $\frac{1}{4}$ S. B.S.
A Pine 10 ins diam. trans N76°E
50 lks. dist. marked $\frac{1}{4}$ S. B.S.
67.80 Bank trans. N.W. + S.E. descend
72.75 Gulch 10 lks wide runs N.W. ^{ascend}
80.42 The Cor. to Secs. 16, 17, 20 & 21
Land. nearly level
Soil. gravelly 2^d rate
Timber Heavy Pine + Oak 80.42 ^{ch}
October 21, 1893.

S. 14. N. R. 13. E.

chs. No° 2' W. bet Secs. 16 & 17.

Va. 13° 44' E

In Heavy Pine timber.

- 8.05 Pine 26 ins. diam. on line marked with 2 notches on N. & S. Sides.
- 29.50 Bank bars. N. by W + S. by E. descend
- 33.60 Gulch 20 lks. wide. runs N. by W, ascend
- 37.20 Ridge bars. E. & W, descend
- 40.00 Pine 5 ins. diam. which I blaze and mark $\frac{1}{4}$ S. on N. Side, for $\frac{1}{4}$ Sec Cor. whence A Pinon 5 ins. diam. bears S 85° E 17 lks. dist. marked $\frac{1}{4}$ S. B. S. - A Pine 5 ins. diam. bears S 63° W 30 lks. dist. marked $\frac{1}{4}$ S. B. S.
- 44.20 Willow Cañon 80 lks. wide runs N. E. ^{ascend}
- 51.23 End of abrupt. ascent.
- 57.50 Top of Left. bank Willow Cañon bears N. E. + S. ^{ascend}
- 80.00 Set a Sandstone 22 x 12 x 8 ins. 16 ins. in the ground. for Cor. to Secs. 8, 9, 16 & 17.

Subdivisions.

- cho. marked with 4 notches on S. and E. edges. Whence —
- A Pine 14 ins. diam. bears
 $N 50^{\circ} E$ 90 lks. dist. marked
 S. 14. N. R. 13. E. S. 9 B.S. —
- A Pine 18 ins. diam. bears
 $S 38^{\circ} E$ 57 lks. dist. marked
 S. 14. N. R. 13. E. S. 16. B.S. —
- A Pine 15 ins. diam. bears
 $S 72^{\circ} W$ 99 lks. dist. marked
 S. 14. N. R. 13. E. S. 17. B.S. —
- A Juniper 14 ins. diam. bears.
 $N 78^{\circ} W$ 99 lks. dist. marked
 S. 14. N. R. 13. E. S. 8. B.S. —
- Land. Very rough & broken,
 Soil, rocky 4th rate,
 Timber, Pine & Juniper. 80 cho.
-

T. 14. N. R. 13. E.

Chs. N 89° 58' E. on a random line

bet. Secs. 9 & 16.

Va. 13° 44' E

40.00 Set temporary 1/4 Sec Cor.

80.36 Int. N.T.S. line 5 lks. N. of Cor. to Secs.

9, 10, 15 & 16. Thence I run.

West on a true line

bet. Secs. 9 & 16.

Va. 13° 44' E

Descend.

7.20 Willow Cañon 80 lks. wide runs E. N. E. ^{ward}

16.80 Descend, along slope Willow Cañon

26.10 Revers Willow Cañon 90 lks wide runs E. by S. ^{ward}

33.40 Along slope Willow Cañon, descend

40.18 Set a Sandstone 20 X 11 X 7 ins. 15 ins

in the ground. for 1/4 Sec. Cor.

marked 1/4 on N. face. and raised

a mound of stone 1 1/2 ft. high 2
ft. base. alongside. pits impracticable

Subdivisions.

- Chs. No trees within limits, -
- 41.65 Recross Willow Cañon 70 lbs wide runs.
E. N.E. ascend abruptly
- 52.07 Left bank Willow Cañon trans. E, N.E. & W.S.W.
and enter *Pinus* and *Cedars*
- 57.90 Trail. trans N.E. & S.W.
- 61.75 Pine 12 ins. diam on line. marked
with 2 notches on E. & W. Sides.
- 80.36 The Cor. to Secs. 8, 9, 16, & 17.
Land very rough & broken.
Soil. gravelly & rocky 3^d & 4th rate
Timber. Pine & Cedar. 28. ²⁹ Chs.

N 0° 2' W. bet. Secs. 8 & 9.

Va. 13° 44' E

In heavy Pine timber

28.50 Trail. trans. N.E. & S.W.

40.00 Set a sandstone 18x8x6 ins. 13 in
in the ground. for 1/4 Sec Cor. marked

T. 14. N. R. 13. E.

- chs. $\frac{1}{4}$ on W. face, Whence A Pine 18 ins. diam.
 brass N50°W 81 lbs. dist. marked
 $\frac{1}{4}$ S. B. J. - A Pine 6 ins. diam. brass
 S88°E 31 lbs. dist. marked
 $\frac{1}{4}$ S. B. J. -
- 63.00 Bank brass. NNE. & S.S.W. descend
- 66.40 Gulch 10 lbs. wide, runs. NNE, ascend
- 72.00 Opposite bank brass. NNE. & S.S.W.
- 80.00 Set. a sandstone 18X10X6 ins. 13 ins.
 in the ground. for Cor. to Secs. 4, 5, 8 & 9.
 marked with 5 notches on S. and 4
 notches on E. edges, Whence
 A Cedar 4 ins. diam. brass
 N66°E 162 lbs. dist. marked
 T. 14. N. R. 13. E. S. 4, B. J.
 A Pine 7 ins. diam. brass
 S43°E 34 lbs. dist. marked
 T. 14. N. R. 13. E. S. 9 B. J.
 A Pine 4 ins. diam. brass.

Subdivisions.

- chs. S74°W 31 lks. dist. marked
 T. 14. N. R. 13. E. S. 8. B. 1. -
 A Pine 8 ins. diam. bears
 N45°W 29 lks. dist. marked
 T. 14. N. R. 13. E. S. 5 B. 1. -
 Land. newly level
 Soil. gravelly 2^d rate
 Timber Pine & Cedar. 80. chs.
-

East. on a random line
 bet. Secs. 4 & 9.

Va. 13°44'E

40.00 bet. temporary 1/4 Sec Cor.

80.18 Int. N. & S. line, 28 lks. S. of Cor.
 to Secs. 3, 4, 9 & 10. Thence I run
 S89°48'W on a true line
 bet. Secs. 4 & 9.

Va. 13°44'E.

In Pines and Cedars

- | | |
|-------|--|
| Chs. | Ascend |
| 4.00 | Bank brans. N.E. + S.W. |
| 5.50 | Trail brans. N.W. + S.E. |
| 19.50 | Right bank Willow Cañon brans. N.W. + S.E. descend
and leave timber |
| 20.00 | Descend abruptly |
| 38.90 | Willow Cañon 90 lks wide runs. N.W. ascend |
| 40.09 | Set. a sandstone 24 x 11 x 8 ins. 18 ins.
in the ground. for $\frac{1}{4}$ Sec. Cr. marked
$\frac{1}{4}$ on N. face. and raised a mound
of stone $1\frac{1}{2}$ ft. high. 2 ft. base
alongside. pits impracticable
No trees within limits.— |
| 52.40 | ascend abruptly |
| 55.00 | Top Left bank Willow Cañon brans.
N.W. & S.E. and enter Pines & Cedars. |
| 64.00 | Bank brans N.N.W. + S.S.E. descend |
| 67.35 | Gulch 10 lks. wide. runs. N.W.W. ascend |
| 70.00 | Ridge brans. N. + S. descend |
| 73.00 | Gulch 10 lks. wide. runs. N.N.E. ascend |

Subdivisions.

- chn.
78.50 Opposite bank bears N. NE. + S. S. W.
80.18 The Cor. to Secs. 4, 5, 8 & 9.
Land very rough & broken
Soil, rocky. 4th rate
Timber Pine & Cedar 45 ¹⁸/₁₀₀ chs.
-

N 0° 20' E on a random line

bet. Secs. 4 & 5.

Va 13° 44' E

- 40.00 Sect. temporary 1/4 Sec Cor.
78.42 Int. N. boundary of Sp. 18 lks. E.
of Cor. to Secs. 4, 5, 32 & 33, here-
inbefore described, Thence I run
S 0° 12' W on a true line.

bet. Secs. 4 & 5.

Va. 13° 44' E

In Pines and Cedars

- 1.50 Bank bears N. E. + S. W. descend

- 5.80 Gulch 20 lks. wide runs S. W. ^{and}

J. 14. N. R. 13. E.

- chs.
10.00 Opposite bank trans. N.E. + D.W.
21.20 Right bank Willow Cañon trans.
N.W. by W. + S.E. by E. descend abruptly
and leave timber
34.80 Willow Cañon 70 lbs wide runs. Westly ^{and}
38.42 Set a Sandstone 22 x 12 x 8 ins. 16 ins.
in the ground. for $\frac{1}{4}$ Sec. Cor. marked
 $\frac{1}{4}$ on W. face. and raised a mound
of stones $1\frac{1}{2}$ ft. high. 2 ft. base
alongside. pits impracticable
44.80 Left bank Willow Cañon trans. Eastly + Westly
46.10 Into timber + mesa
78.42 The Cor. to Secs. 4, 5, 8, 9.
Land very rough & broken
Soil rocky. 4th rate.
Timber Pine + Cedar 53.52 chs.

October 23, 1893.

Subdivisions.

- chs. From the Cor. to Secs. 5, 6, 31 & 32
on S. boundary of Sp. hereinbefore
described. I run
N $0^{\circ} 3' W$. bet. Secs. 31 & 32.
Va $13^{\circ} 44' E$
- Along East slope of Willow Cañon
26.20 Willow Cañon 80 lks wide runs N by E
40.00 Set a Sandstone $18 \times 10 \times 7$ ins., 13.
ins. in the ground. for $\frac{1}{4}$ Sec. Cor.
Marked $\frac{1}{4}$ on W. face, and raised
a mound of Stone $1\frac{1}{2}$ ft. high
2 ft. base alongside
pits impracticable.
No trees within limits
Thence along West Slope Willow Cañon
56.40 Recross Willow Cañon 60 lks
wide runs. N.W. ascend.
66.50 Right bank Willow Cañon Cross NW, SE, and
67.00 enter Pine and Oak Timber
Ridge Cross N.W. & S.E. descent

T. 14, N. R. 13, E.

- 67.80 Bank brass. N.W. + S.E. descent
- 69.50 Gulch 10 lks wide runs N.W. then ^{east} west.
- 69.80 Pine 18 ins. diam. on line, marked
with 2 matches on N. + S. Sides
- 72.30 Opposite bank brass. N.W. + S.E.
- 80.00 Set a Sandstone 18x12x5 ins, 13 ins
in the ground. for Cor. to Secs. 29, 30
31 & 32, marked with 1 match on
S. and 5 matches on E. edges. Whence
A Pine 18 ins. diam. brass
N 34° E 72 lks. dist. marked
T. 14, N. R. 13, E. S. 29 B.S. -
A Pine 14 ins. diam. brass
S 12° E 80 lks. dist. marked
T. 14, N. R. 13, E. S. 32, B.S. -
A Pine 16 ins. diam. brass
N 66½° W 725 lks. dist. marked
T. 14, N. R. 13, E. S. 31 B.S. -
A Pine 12 ins. diam. brass.

Subdivisions.

chs. N82°W 98 lks. dist, marked
 T. 14. N. R. 13. E. S. 30. B. 1. -
 Land. Very rough & broken
 Soil. Stony. 3^d & 4th rate
 Timber Pine & Oak 13.50 chs.

S 89°59' E on a random line.
 bet. Secs. 29 & 32.
 Va. 13°44' E

40.00 Sect. temporary 1/4 Sec Cor.
 80.40 Int. N. & S, line at Cor. to Secs
 28, 29, 32 & 33, Thence I run
 N89°59' W on a true line
 bet. Secs. 29 & 32
 Va. 13°44' E

In heavy Pine & Oak timber

7.60 Pine 30 ins. diam. on line, marked
 with 2 notches on E. & W. sides

T. 14. N. R. 13. E.

- | | |
|-------|--|
| 13.00 | Trail, trans. N.E. & S.W. |
| 25.90 | Trail, trans. N.W. & S.E. |
| 35.00 | Bank trans. N.W. & S.E. descend |
| 40.20 | Set a Sandstone 18x15x6 ins. 13 ins
in the ground. for 1/4 Sec. Cr. marked
1/4 on N. face. Whence a Pine 18 ins
diam. trans N18°W 11 lks. dist.
A Pine 6 ins. diam. trans S70°W
71 lks. dist. marked 1/4 S, B, J. - |
| 42.95 | Gulch 10 lks wide runs N.W. ascend |
| 45.70 | Opposite bank trans. N.W. & S.E. |
| 51.35 | Pine 38 ins. diam. on line marked
with 2 notches on E. & W. Sides |
| 57.00 | Bank trans. N.E. & S.W. descend |
| 59.65 | Gulch 10 lks. wide runs N.E. |
| 62.20 | Opposite bank trans. N.E. & S.W. |
| 63.70 | Pine 16 ins. diam. on line marked
with 2 notches on E. & W. Sides. |
| 64.50 | Trail trans. N. & S. |

Subdivisions.

80.40 The Cor. to Secs. 29, 30, 31 & 32.
 Land, nearly level
 Soil, gravelly 2^d rate
 Timber heavy Pine 80.⁴⁰ chains

N 89° 59' W. on a random line
 bet. Secs. 30 & 31.
 Va. 13° 44' E.

40.00 Set. temporary 1/4 Sec. Cor.

95.00 Int. W. boundary of Sp. 30 Sta. N.
 of Cor. to Secs. 25, 30, 31 & 36. as
 hereinbefore described. Thence run

N 89° 50' E on a true line
 bet. Secs. 30 & 31.
 Va. 13° 44' E

In heavy Pine timber

28.40 Pine 36 ins. diam. on line marked
 with 2 notches on E. & W. sides

T. 14. N. R. 13. E.

37.00	Bank bars, northward & southward descend
38.75	Gulch 10 lks wide runs northward ^{ward}
45.80	Opposite bank bars. N. & S.
54.05	Trail bars. N. & S.
55.00	Set a sandstone 18x15x4 ins. 13 ins in the ground for $\frac{1}{4}$ Sec. Cor. marked $\frac{1}{4}$ on N. face. Whence a Pine 14 ins. diam. bars. $N41^{\circ}E$. 41 lks dist. marked $\frac{1}{4}$ S B. Y. - An Oak 5 ins. diam. bars $N4^{\circ}W$ 61 lks. dist. marked $\frac{1}{4}$ S B. Y. -
62.50	Left bank Willow Cañon bars. N. & S. descend
66.00	Descend abruptly.
71.20	Willow Cañon 80 lks. wide runs northward ^{ward}
89.10	Right bank Willow Cañon bars. SE & NE.
95.00	The Cor. to Secs. 29, 30, 31 & 36. Land. very rough & broken Soil. gravelly & rocky 2 ^d & 4 th rate. Timber Heavy Pine. 95.00 chs.

Subdivisions.

chs.	No ^o 3 'W. bet. 29 & 30. Va. 13°44' E
	In heavy Pine timber
6.00	Right bank Willow Cañon. trans. N.E. & S.W. ^{descend}
13.80	Willow Cañon 80 lks. wide runs N.E.
19.50	Reeras Cañon 70 lks. wide runs N.W. ^{ascend}
28.00	Right bank Willow Cañon trans. N.W. & S.E. ascend
37.00	Enta Mesa. trans. N.W. & S.E.
40.00	Set a sandstone 24 x 15 x 8 ins. 18 ins. in the ground. for 1/4 Sec. Cor. marked 1/4 on W. face. whence a Pine 14 ins. diam trans. S 15° E 25 lks. dist. marked 1/4 S.B.S. A Pine 10 ins. diam. trans. S 80° W 23 lks. dist. marked 1/4 S.B.S.
44.50	Bank trans. N.W. & S.E. descend
48.70	Gulch 20 lks wide. runs N.W. ^{ascend}
55.95	Pine 8 ins. diam. on line marked with 2 notches on N. & S. sides.
57.50	Opposite bank trans. N.W. & S.E.

chs.
80.00

Set a sandstone 18x10x5 ins. 13 ins.
in the ground, for Cor. to Secs. 19, 20
29 & 30, marked with 2 notches on
S. and 5 notches on E. edges. Whence
A Pine 14 ins. diam. bears
N 4° E 59 lks. dist. marked
T. 14, N. R. 13, E. S. 20 B. T. —

A Pine 12 ins. diam. bears

S 72° E. 20 lks. dist. marked
T. 14, N. R. 13, E. S. 29 B. T. —

A Pine 8 ins. diam. bears

S 12° W 79 lks. dist. marked
T. 14, N. R. 13, E. S. 30 B. T.

A Pine 16 ins. diam. bears

N 33° W 47 lks. dist. marked
T. 14, N. R. 13, E. S. 19, B. T.

Land, broken

Soil gravelly 2^d + 3^d rate

Timber heavy Pine, 80 chs.

Subdivisions.

- cha. S $89^{\circ}59'E$ on a random line
bet. Secs. 20 & 29
Va $13^{\circ}44'E$.
- 40.00 Set temporary $\frac{1}{4}$ Sec. Cor.
80.32 Int. N.T.S. line 3 lks. S. of Cor. to
Secs. 20, 21, 28 & 29, thence I run
West on a true line,
bet. Secs. 20 & 29.
Va. $13^{\circ}44'E$.
- In heavy Pine timber, ascend
- 4.40 Bank bears N.E. & S.W.
31.75 Trail, bears N.E. & S.W.
37.40 Bank bears N.T.S., descend
40.16 Set a Sandstone $20 \times 10 \times 10$ ins, 15 ins.
in the ground, for $\frac{1}{4}$ Sec. Cor. marked
 $\frac{1}{4}$ on N. face whence a Pine 30 ins
diam. bears $N56^{\circ}E$ 38 lks. dist,
marked $\frac{1}{4}$ S. B.T. - A Juniper
14 ins. diam. bears $S70^{\circ}E$ 26

T. 14. N. R. 13. E.

- Chs. lks. dist. marked $\frac{1}{4}$ S. B. L.
- 48.20 Gulch 40 lks. wide, runs. northerly ^{ascend}
- 53.50 Bank trans. N. & S.
- 60.00 Ridge trans. N. & S.
- 63.00 Bank trans N.N.W. + S.S.E. descend
- 71.90 Gulch 20 lks. wide. runs. N.N.W. ^{ascend}
- 78.50 Bank trans, N.N.W. + S.S.E.
- 80.32 The Cor. to Secs. 19, 20, 29 & 30.

Land broken.

Soil. Stony, 3^d rateTimber Heavy Pine 80³² chs.

October 24, 1893.

S $89^{\circ}50'W$. on a random line

bet Secs. 19 & 30.

Va $13^{\circ}44'E$

- 40.00 Set temporary $\frac{1}{4}$ Sec. Cor.
- 94.86 Int. W boundary of Tp 29 lks.

Subdivisions.

chs. N. of Cor. to Secs. 19, 24, 25 & 30
as hereinbefore described. I run
N 89° 39' E on a true line
bet. Secs. 19 & 30.
Ta 13° 44' E.

In heavy Pine timber

- 13.00 Bank bars N.E. & S.W. descend
30.50 Gulch 30 lks wide, runs N.E. ascend
36.50 Bank Opposite bars, N.E. & S.W.
43.50 Bank bars N.E. & S.W. descend
47.85 Trail bars N.N.E. & S.S.W.
54.00 Opposite bank bars N.E. & S.W.
54.86 Set a Sandstone 18x9x7 ins. 13 ins.
in the ground, for $\frac{1}{4}$ Sec Cor. marked
 $\frac{1}{4}$ on N. face, whence a Pine 8 ins
diam. bars N 4° W 14 lks. dist,
marked $\frac{1}{4}$ S. B. L. - A Pine 4 ins,
diam. bars S 38° W 48 lks dist,
marked $\frac{1}{4}$ S. B. L. —

T. 14. N. R. 13. E.

chn.	
57.05	Trail from Northely & Southely
61.00	Left bank Willow Cañon from N. & S. descend and leave timber
75.40	Willow Cañon 80 lks. wide runs N. then N.E. ^{about}
92.00	Right bank Willow Cañon from N & N.N.E. and enter timber
94.86	The Cor. to Secs. 19, 20, 29 & 30. Land very rough & broken Soil gravelly & stony. 3 ^d & 4 th rate Timber heavy Pine 63 ⁰⁰ chaus

N 0° 3' W. bet. Secs. 19 & 20.

Va 13° 44' E

By Pine timber ^{about}Right bank Willow Cañon from N.N.E & S.S.W.
and leave Pine timber

17.80 Willow Cañon 80 lks wide runs N.E. about

Along west slope willow Cañon

38.90 Recross Willow Cañon 80 lks wide runs N.W. ^{about}40.00 Set a sandstone 22 x 12 x 6 ins. 16 ins
in the ground. for 1/4. Sec. Cor. marked
1/4 on W. face, and raised a mound of

Subdivisions.

- Chs. $1\frac{1}{2}$ ft. high, 2 ft. base, alongside
Pits impracticable.
No trees within limits -
Thence along E. Slope of Willow Cañon
- 72.80 Recross Willow Cañon, 70 lks. wide near N.E. ⁴⁵⁰⁰ end
- 80.00 Set a Sandstone $18 \times 11 \times 9$ ins 13 ins
in the ground, for Cor to Secs.
17, 18, 19 & 20, marked with 3
notches on S. and 5 notches on
E. edges, and raised a mound
of Stone 2 ft. high $4\frac{1}{2}$ ft. base
alongside. Pits impracticable
No trees within limits,
Land, Very rough & broken
Soil, gravelly & stony 2^d & 4th rate
Timber Pine 450 Chs.

East, on a random line
bet. Secs. 17 & 20.

T. 14. N. R. 13. E.

Chs.	Va 13°44'E
40.00	Set. temporary $\frac{1}{4}$ Sec. Cor.
80.32	Int. N. & S. line at. Cor. to Secs. 16, 17, 20, & 21. Thence I run West. on a true line, bet. Secs. 17 & 20. Va. 13°44'
	In heavy Pine timber
6.95	Pine 20 ins. diam. on line marked with 2 notches on E. & W Sides
12.00	Ridge bears N.N.E. & S.S.W. descend
18.30	Gulch 10 lks wide runs N.N.E. ascend
26.70	Opposite bank bears N.N.E. S.S.W.
40.16	Set. a Sandstone 22x15x10 ins. 16 ins. in the ground, marked $\frac{1}{4}$ on N. face. for $\frac{1}{4}$ Sec. Cor. Whence an Oak 6 ins. diam. bears S12°E 75 lks. dist. A Pine 16 ins diam bears N60°E 15 lks dist. marked $\frac{1}{4}$ S. B. S.

Subdivisions.

- 46.20 Right bank Willow Cañon bears N.S.W. & N. by E. ^{dead}
and leave same timber
- 55.70 Into bed Willow Cañon.
- 63.40 Leave bed Willow Cañon runs E. by N. ^{used}
- 80.32 The Cor. to Secs. 17, 18, 19 & 20.
Land rough & broken
Soil, gravelly & rocky 3^d & 4th rate
Timber heavy Pine 46, 20 chs.

S 89° 39' W. on a random line bet. ^{Sec 18 & 19}
Va. 13° 44' E.

- 40.00 Sect. temporary 1/4 Sec Cor.
- 94.80 Sth. W. boundary of Tp 31 ths. N. of
Cor. to Secs. 13, 18, 19 & 24. herein before
described Thence I run
N 89° 28' E. on a true line
bet. Secs. 18 & 19
Va 13° 44' E
In heavy Pine timber

chs. 16.50	Bank trans. N. + S. descend
22.30	Gulch 20 lks. wide, runs Northerly. ^{Wind}
24.00	Opposite bank trans N. + S.
25.00	Ridge trans. N by W + S. by E. descend
36.95	Trail N.W. + S.E.
39.10	Gulch 20 lks wide runs, NW, ascend
45.00	Opposite bank trans. NW, + S.E.
54.80	Set a Sandstone 20 x 8 x 6 ins. 15 ins in the ground. for 1/4 Sec. Cor. Marked 1/4 on N face, whence a Pine 15 ins diam. trans. S 70° W 40 lks dist Marked 1/4 S. B. Y. A Pine 18 ins diam. trans N 27° E 37 lks. dist. marked 1/4 N. B. Y.
59.70	Trail trans. Northerly + southerly
68.10	Trail trans N.E. + S.W.
81.00	Bank willow ^{Cotton} trans N.E. + S.W. descend ^{and}
83.50	Descend abruptly. ^{leave pine timber}
94.80	The Cor to Secs. 17, 18, 19 + 20.

Subdivisions.

chs. Land, rough & broken
 Soil, gravelly & stony 3^d & 4th rate
 Timber heavy Pine, 81.00 chains
 October 25, 1893.

N 0° 3' W. but. Secs. 17 & 18,
 Va 13° 44' E

Within banks of Willow Cañon ^{and}

8.61 End of abrupt ascent, and enter heavy
 Pine timber

9.90 Pine 24 ins. diam. on line marked
 with 2 notches on N. & S. sides

10.50 Left bank Willow Cañon trans. N.E. & S.W.

16.55 Trail trans. N.E. & S.W.

40.00 Set a sandstone 16 x 10 x 4 ins 11 ins
 in the ground for 1/4 Sec. Cor. marked
 1/4 on W. face, whence a Pine
 19 ins. diam. trans. S 17° E 44.
 lks. dist. marked 1/4 S. B. L.

T. 14. N. R. 13. E.

- Chs. A Juniper 5 ins. diam bears.
S 82° W 29 lks. dist. marked
1/4 S. B. I. —
- 40.10 Pine 24 ins. diam. on line. marked
with 2 notches on N. & S. Sides.
- 80.00 Set a Sandstone $18 \times 11 \times 5$ ins. 13 ins.
in the ground. for Co. to Rees. 7, 8, 17+18
Marked with 4 notches on S. and 5
notches on E. edges. Whence
A Pine 26 ins. diam. bears
N 82° E 77 lks. dist. marked
T. 14, N. R. 13. E. S. 8 B. I.
- A Pine 20 ins. diam. bears
S 86° E 56 lks. dist. marked
T. 14, N. R. 13. E. S. 17. B. I.
- An Oak 6 ins. diam. bears
S 27° W 34 lks. dist. marked
T. 14, N. R. 13. E. S. 18 B. I.
- An Oak 4 ins. diam. bears

BOOK 157
Subdivisions.

Chs. N 48 1/2 W 44 lks. dist. marked
 T. 14. N. R. 13. E. S. 7. B. 1.
 Land nearly level.
 Soil. gravelly 2^d rate
 Timber. Heavy Pine 71.39 chs.

East, on a random line
 bet. Secs. 8 & 17.
 Va 13° 44' E

40.00 Set temporary 1/4 Sec. Cor.
 80.28 Int. N. S. line at ^{Cor 16} Secs. 8, 9, 16 & 17.
 Thence Iron

West, on a true line
 bet. Secs. 8 & 17.
 Va 13° 44' E

In heavy Pine timber
 17.85 Pine 16 ins. diam. on line. marked
 with 2 notches on E. & W. sides

T. 14. N. R. 13. E.

- chs.
 19.30 Bank bars NNE. & SSW, descent
 21.50 Gulch 10 lks. wide, runs, NNE, and
 22.65 Trail bars, NNE. & SSW,
 24.10 Opposite bank bars NNE, & SSW.
 40.14 Set a Sandstone 18x11x5 ins, 13 ins
 in the ground, for $\frac{1}{4}$ Sec Cor. marked
 $\frac{1}{4}$ on N. face, where a Pine 13 ins
 diam. bars, N30°E 36 lks. dist.
 marked $\frac{1}{4}$ S. B.T. — A Pine 12 ins,
 diam. bars, S35°E 26 lks. dist.
 marked $\frac{1}{4}$ S. B.T. —
 80.28 The Cor. to Secs. 7, 8, 17 & 18,
 Land level.
 Soil. Sandy & gravelly 2^d rate
 Timber heavy Pine. 80.28 chs.

October 25, 1893.

S 89° 28' W. on a random line
 bet. Secs. 7 & 18.

Subdivisions.

chs.

Va 13°44'E

40.00 Set temporary 1/4 Sec Cor.

94.74 Int. W. boundary of Sp. 29 lks.

N. of Cor. to Secs. 7, 12, 13 & 18.

Thence I run

N 89°17'E on a true line

bet. Secs. 7 & 18.

Va 13°44'E.

In heavy Pine timber

9.50 Bank bars. Northerly & Southerly ^{descend}15.10 Gulch 10 lks wide. runs. Northerly ^{ascend}

17.50 Opposite bank bars. Northerly & Southerly.

19.00 Bank bars. N. & S. descend

26.10 Gulch 60 lks. wide. runs. Northerly ^{ascend}

33.50 Opposite bank bars. N. & S.

54.74 Set a Sandstone 17x10x5 ins. 12 ins
in the ground. for 1/4 Sec Cor. Marked
1/4 on N. face, where A Pine 14 ins
diam. bars N 12° W 20 lks. dist.

T. 14. N. R. 13. E.

- Chs. marked $\frac{1}{4}$ S. B. I. - An Oak 4 ins,
diam. bears $S36^{\circ}W$ 11 lks. dist.
Marked $\frac{1}{4}$ S. B. I. -
- 60.25 Gulch 10 lks. wide runs N.E.
- 70.00 Bank bears N.T.S. descend
- 73.80 Gulch 10 lks. wide, runs Northw^{ard}
- 78.00 Opposite bank bears N.T.S.
- 94.74 The Cor. to Secs. 7, 8, 17 & 18.
Land level
Soil gravelly 2^d rate
Timber Heavy Pine. 94.74 chs.

$N0^{\circ}3'W$. bet Secs. 7 & 8,
Va $13^{\circ}44'E$

In Heavy Pine timber

- 40.00 Set a Sandstone $16 \times 11 \times 5$ ins, 11 ins,
in the ground, for $\frac{1}{4}$ Sec. Cr. Marked
 $\frac{1}{4}$ on W. face. Whence A Pine 16 ins,

Subdivisions.

- Chs. diam. brass $S 88^{\circ} E$ 34 lks.
 dist. marked $\frac{1}{4}$ S. B. I. - A Pine
 14 ins. diam. brass. $N 67^{\circ} W$ 22
 lks. dist. marked $\frac{1}{4}$ S. B. I. -
- 61.00 Trail brass. N.E. & S.W.
- 70.70 Trail brass. N.E. & S.W.
- 80.00 Set a Sandstone $18 \times 12 \times 4$ ins. 13 in
 in the ground. for Cor. to Secs. 5, 6,
 7 & 8. marked with 5 notches on S,
 and E. edges. Whence
 A Pine 10 ins. diam. brass.
 $N 19^{\circ} E$ 89 lks. dist. marked
 T. 14, N. R. 13. E. S. 5. B. I.
 A Pine 13 ins. diam. brass
 $S 75^{\circ} E$ 110 lks. dist. marked
 T. 14, N. R. 13. E. S. 8 B. I.
 A Pine 20 ins. diam. brass
 $S 55^{\circ} W$ 45 lks. dist. marked
 T. 14, N. R. 13. E. S. 7. B. I.

T. 14. N. R. 13. E.

Chs. A Pine 16 ins. diam. bears
 N $22\frac{1}{2}^{\circ}$ W 134 lks. dist. marked
 T. 14. N. R. 13. E. S. 6. B. I. —
 Land. level.
 Soil sandy & gravelly 2^d rate
 Timber heavy Pine. 80 chains.

East, on a random line
 bet. Secs. 5, & 8.
 Ya $13^{\circ}44'E$

46.00 Set temporary $\frac{1}{4}$ Sec Cor.
 80.24 Int. N. & S. line. at Cor. to Secs. 4, 5
 & 9. Thence I run
 West, on a true line
 bet. Secs. 5 & 8.
 Ya. $13^{\circ}44'E$.
 Any heavy Pine timber
 11.45 Trail bears. N. W. & S. E.
 18.00 Enter Cedar and leave Pine

Subdivisions.

- 29.50 Bank trans. N. & S, descend
- 33.80 Gulch 20 lks. wide, runs northw^{ast}ly ^{ascend}
- 37.50 Opposite bank trans. N. & S,
- 40.12 Set a Sandstone 17x10x6 ins. 12
ins. in the ground. for $\frac{1}{4}$ Sec. Cor.
Marked $\frac{1}{4}$ on N. face. Whence a
Pine 5 ins. diam. trans N19°W
63 lks. dist. marked $\frac{1}{4}$ S. B.S.
A Pine 5 ins. diam. trans. S29°W
47 lks. dist. marked $\frac{1}{4}$ S. B.S. -
- 45.00 Bank trans. N.E. & S.W. Live Cedar, descend
- 51.50 Gulch 30 lks wide. runs. N.E. ascend
- 55.00 Ridge trans N.E. & S.W, descend
- 59.00 Gulch 20 lks. wide runs. N.E. ^{ascend}
- 69.00 Opposite bank trans. N.E. & S.W,
- 76.35 Trail, trans N. & S,
- 80.24 The Cor. to Secs. 5, 6, 7, 8,
Land. rolling.
Soil gravelly 3^d rate
Timber Pine & Cedar, 80.24 Chs.

T. 14. N. R. 13. E.

Chs. S $89^{\circ}17'W$ on a random line
bet. Secs. 6 & 7.
Va $13^{\circ}44'E$

40.00 Set. temporary $\frac{1}{4}$ Sec Cor.

94.60 Int. W. boundary of Sp. at Cor. to
Secs. 1, 6, 7 & 12. Thence I run
N $89^{\circ}17'E$. on a true line
bet. Secs. 6 & 7.

5.50 In heavy cedar timber
Va. $13^{\circ}44'E$
Bank trans. N.E. & S.W. descend

10.70 Gulch 10 lks. wide. runs N.E. ascend

15.00 Opposite bank trans. N.E. & S.W.

25.00 Bank trans N.N.W. & S.S.E. descend

24.90 Gulch 10 lks wide. runs N.N.W.

35.00 Bank trans. N. & S. descend abruptly

43.80 Gulch 50 lks. wide. runs Northw. ^{ascend}

53.50 Opposite bank trans. N. & S.

54.60 Set. a Sandstone $17 \times 11 \times 4$ ins 12
ins. in the ground. for $\frac{1}{4}$ Sec Cor.

BOOK 157

Subdivisions J. 14, N. R. 13. E.

- Chs. Marked 1/4 on N. face, whence a
Pine 7 ins. diam. bears S 52° W
11 lks. dist. Marked 1/4 S B. J.
A Pine 6 ins. diam. bears N 45° E
42 lks. dist. marked 1/4 A. B. J. -
- 58.00 Bank bears, N.W. + S.E. descend
- 67.10 Gulch 10 lks wide, runs N.W. ^{ascend}
- 80.00 Opposite bank bears, N.W. + S.E.
- 84.50 Leave Cedars, and enter Pines
- 94.60 The Cor. to Secs. 5, 6, 7, + 8.
Land broken,
Soil. Stony. 4¢ rate
Timber Pine + Cedar, 94.60 chs.

N 0° 12' E on a random line
bet. Secs. 5, + 6,
Va. 13° 44' E

40.00 Set temporary 1/4 Sec. Cor.

Subdivisions T₁₄, N. R. 13, E.

78.76 Int. N. boundary of Tp. 20 lks. E.
of Cor. to Secs. 5, 6, 31 & 32. Iron
S $0^{\circ} 3' W$. on a true line.

bet. Secs. 6th & 7.

Va. $13^{\circ} 44' E$.

In heavy pines and cedars
2525 Trail. bears N.W. & S.E.

38.76 Set a Sandstone 18x10x6 ins, 13 ins
in the ground. for $\frac{1}{4}$ Sec. Cr. mark
 $\frac{1}{4}$ on W. face. whence A Pine 10 ins,
diam. bears N $65^{\circ} E$ 24 lks. dist.

Marked $\frac{1}{4}$ S. B.T. - A Pine 5
ins. diam. bears N $65^{\circ} \frac{1}{2} W$ 10 lks.
dist. marked $\frac{1}{4}$ S. B.T. -

66.90 Pine 8 ins. diam. on line marked
with 2 notches on N & S. sides.

78.76 The Cor. to Secs. 5, 6, 7 & 8. -
Land. level.

Soil. gravelly 2^d rate.

Timber. Pine & Cedar. 78.76. 'chs.

October, 26. 1893.

47 miles. 67 chs. & 19 lks. runs thro' heavy Pine timber

General Description.

This township contains rough & rugged land, cut by many cañons, of which Willow Cañon is the largest. It contains water at all seasons, the land between the banks of the cañons is level mesa, the soil is gravelly, producing a fine growth of pine timber, and good native grasses. Cattle horses & sheep roam over its surface, wild game is abundant, the fish in the large cañons is of a poor quality, there is one house in Sec. 25. Not visible from the section lines, the timber in the N.E. portion consist of Piñon

and Cedar. Very dense.

The mean declination for the
flat. the mean of five

observations is $13^{\circ}44'E$.

Daniel Drummond
U.S. Deputy Surveyor

U.S. Surveyor- General's Office,

Tucson, A.T. October 9th, 1895.

The foregoing field notes of the Surveys of the Subdivisions of Township No, 14, N. Range No, 13 East, Gila and Salt River Meridian in Arizona, executed by

DANIEL DRUMMOND

U.S. Deputy Surveyor, under his Contract dated Febry, 21st, 1893, having been critically examined, the necessary corrections and explanations made, the said Field notes and the surveys they describe are hereby approved.

Geo. H. Manning

U, S, Surveyor General.

for the Territory of Arizona.