

BOOK 331

No 331

4-671 BOOK 331

331

FIELD NOTES

GENERAL LAND OFFICE.

Subdivision

Township 20. N. R. 2. E.

No 331

Index

(4-674.)

Township *20 N.* R. *2 E.*

BOOK 331 and

BOOK 332
BOOK 333

6	153	5	109	4	81	3	52	2	27	1	-
150	148			107	78		50		270		
7	146	8	104	9	75	10	48	11	23	12	
143	141			101	74		46		21		
18	138	17	99	16	71	15	43	14	18	13	
134	132			96	69		41		16		
19	129	20	93	21	65	22	38	23	13	24	
126	124			91	63		36		11		
30	120	29	89	28	60	27	34	26	9	25	
117	115			86	58		32		7		
31	112	32	84	33	55	34	29	35	4	36	

No-331

BOOK

2

331

Field Notes
of the survey of the
Sub-division Lines
of
Township No 20 N. Range No 2 East
of the
Gila & Salt River Base Meridian
in the
Territory of Arizona
as surveyed by
Francis W. Oury
U. S. Deputy Surveyor
Charles E. Perkins
Compassman & U. S. Deputy Surveyor
Under Contract No 31
Dated June 21. 1893.

Survey commenced October 24. 1894
Survey completed. October 31. 1894.

Chains Subdivisions

Survey commenced Oct 24
1894 with a W + L. E. Gurley
solar transit.

At the cor to sec. 1. 2. 35 + 36
I verify the adjustments of
the transit and find
them correct.

I set off $11^{\circ} 58'$ S. on the
decl. arc, and at $11^{\text{h}} 44'$ A.M.
I observe the sun
on the meridian; the
resulting lat. is $35^{\circ} 02' N$
the true lat., nearly.

From the cor to sec
1. 2. 35 + 36 on S. side of Tp.
as per survey on Des Moines
I run

N $00^{\circ} 1'$ W. 700 sec. 35 E 36
Va $13^{\circ} 51'$ E

Chains To N. B. 2. E. (Cont)

Over rolling heavily timbered
land.

- 7.00 Descend gradually 30 ft.
21.00 Foot of descent.
40.00 Set a malpais. Stone 20x16x14
ins. 16 ins. in the ground
for 14 sec. cor. marked 14 N. W
face and raised a mound of
stone 1 1/2 ft. high 2 ft. face
alongside from which
an oak 8 in diam. br. S. 65° 11' E
19 1/2 ms. dist. marked 14 S. B. T.
a pine 40 in diam. br. N. 15° 20' W
105 ms. dist. marked 14 S. B. T.
56.00 Ascend 60 ft.
63.00 Top of ascended descend 45 ft.
69.00 Foot of descent.
80.00 Set a malpais. Stone 26x12x8
ins. 18 ins. in the ground for

Trains Subdivisions

Cor to Secs. 25, 26, 35 + 36. Marked
with 1 meter on S. + E. edges and
raised a mound of stone $1\frac{1}{2}$ ft.
high 2 ft. base alongside, from which
A pine 15 in. diam. W. N. $32^{\circ} 01' E$
14 W. dist. marked T. 20 N. R. 2 E
S. 25. T. 3.

A pine 16 in. diam. W. S. $32^{\circ} 11' E$
24 W. dist. marked T. 20 N. R. 2 E
S. 36. T. 3.

A pine 16 in. diam. W. S. $45^{\circ} 25' W$
38 W. dist. marked T. 20 N. R. 2 E
S. 35. T. 3.

A pine 18 in. diam. W. N. $45^{\circ} 31' W$
25 W. dist. marked. T. 20 N. R. 2 E
S. 26. T. 3.

Land, broken + rolling
Soil, rocky 4th rate.
Timber, pine

Chains T 20 N R 26. (Contd)

Heavily timbered land. 50 chs.

East on a random line bet
secs. 25 E / 36

$Ta 13^{\circ} 51' E.$

4000 Set temporary 1/4 sec. cor.

7990 Intersect. E. vdy. of T_p-19 W_s. S.
of cor to secs. 25.30.31 E / 36. as
bearing for described

Thence down

S. $89^{\circ} 52' W.$ on a true line bet. secs.
25 E / 36.

$Ta 13^{\circ} 51' E.$

Over wooden heavily timbered land.

Descend 40 ft.

365 Foot of descent, west. 4 ft. deep-
course S. E.

Ascend 40 ft.

Chains. Surveys

- 8.00 Top of ascent.
- 32.00 Descend gradually 30 ft.
- 39.95 Set a trap for stone 18x16x14
ins. 12 ins. in the ground
for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on
N. Face and raised a mound
of stone $1\frac{1}{2}$ ft. high. 2 ft
base alongside, found which
is over 8 in diam. Tr. S. $9^{\circ}03'W$.
7 Ws. dist. marked $\frac{1}{4}$ S. B. S.
A pine 14 in diam. Tr. S. $61^{\circ}37'W$.
16 Ws. dist. marked $\frac{1}{4}$ S. B. S.
- 43.00 Foot of descent.
- 49.00 Ascend. 30 ft.
- 56.00 Top of ascent.
- 71.00 Descend. 150 ft. into cañon
- 75.50 Bed of cañon course S.
- 79.90 The cor. to sec. 25. 26. 35 + 36.
Land, broken

Chain. T. 2. N. R. 2 E (Contd)

Soil, very 4th rate

Timber, pine

Heavily timbered land 79.90 chs.

N. 0.1 W. Gr. sec. 25th 26.

Ta 13.51 E.

Over mountains. Sparsely timbered
land.

Descend 10 ft.

2.00 Bed of cañon, course S. 60° E.

Ascend 300 ft.

14.00 Top of ascent, thence over rolling
land.

40.00 Set a malpais. Stone 18 x 16 x 10
ins. 12 ins. in the ground
For 1/4 sec. cor. marked 1/4 on W
face and raised a mound of
stone 1 1/2 ft. high 2 ft. base

Chains Subdivisions

alongside, from which

A pin 12 in diam. Tr. N. 61° E.

19. No. dist. marked 1/4 S. B. J.

An oak 8 in diam. Tr. N. 22° E

83 No. dist. marked 1/4 S. B. J.

80.00 Set a malpais stone 14 x 14 x 12
ins. 9 ins in the ground for
corn to sec. 23, 24, 25 and 26.

marked with 2 notches on S.
and 1 notch on E. edges and
raised a mound of stone 1 1/2
ft. high 2 ft. from alongside
from which.

An oak 6 in diam. Tr. N. 2° 36' E

45 No. dist. marked T. 20 N. B. 2
E. S. 24. B. J.

An oak 6 in diam. Tr. S. 37° 41' E

34 No. dist. marked T. 20 N. B. 2 E
S. 25. B. J.

chains. T. 20 N. R. 2 E (Contd)

An cor. 8 in diam. $\text{Tr. S. } 61^{\circ} 57' \text{ W.}$
 113 $\text{Wrs. dist. marked T. 20 N. R. 2 E}$
 S. 26. B. T.

An cor. 8 in diam. $\text{Tr. N. } 22^{\circ} \text{ W.}$
 38 $\text{Wrs. dist. marked T. 20 N. R. 2 E}$
 S. 23. B. T.

Land, mountains. E falling
 Soil, very 4th rate

Timber, pine, some scrub. oak.
 Mountains or heavily timbered
 land. 80 chs.

$\text{N. } 89^{\circ} 52' \text{ E}$ on a random line
 bet sec. 24 & 25
 $\text{Ta } 13^{\circ} 51' \text{ E.}$

4000 Ser. temporary $\frac{1}{4}$ sec. cor.
 79.85 Intersect E. bdy of Sp. 9 Wrs.
 Ref. cor to sec. 19. 24. 25 + 30

Chains. Subdivisions

as Transit from described
Thence True.

S. 89° 56' W. on a true line for
sec. 24 Ed 25

Ta 13° 51' E.

Over broken heavily timbered land

Ascend 40 ft.

10.50 Top of ascent

12.00 Descend 100 ft.

20.00 Foot of descent

33.00 Ascend 175 ft.

39.92 Set a mark pair. Stone 26 x 14 x 10

ins. 18 ins. in the ground

For 1/4 sec. cor. marked 1/4 on

N. face and raised a mound
of Stone 1 1/2 ft. high. 2 ft. base
alongside, from which

A pine 6 in. diam. to S. 46° 28' W.

40 Wa. Dist. marked 1/4 S. T. B. T.

Chains T. 20 N. R. 2 E (Contd)

A pine 4 in diam. $N. 70^{\circ} 11' E$
74 hrs. Dist. marked $\frac{1}{4}$ S. B. J.

45.00 Top of ascuer.

49.00 Descend 75 Ft.

72.00 Foot of ascuer.

79.85 The cor to secs. 23, 24, 25 + 26.

Land, broken

Soil, rocky 4th rate

Timber, pine.

Heavily timbered land. 79.85 chs.

$N. 0^{\circ} 1' W.$ bet. secs. 23 E / 24
Ta $18^{\circ} 51' E.$

Over rolling heavily timbered land

14.00 Ascend. 250 Ft.

26.00 Top of rocky ridge, course E + N.

Descend. 250 Ft.

40.00 Set a malpais. $18 \times 16 \times 6$

Chains Subdivisions

ins 12 ins. in the ground
 For $\frac{1}{4}$ sec cor marked $\frac{1}{4}$ on
 W. Face and raised a mound
 of stone $1\frac{1}{2}$ ft. high 2 ft. base
 along side, From which
 a pine 18 in diam. br. N. $50^{\circ}10'E$
 61 chs. dist. marked $\frac{1}{4}$ S. B. T.
 A pine 26 in diam. br. N. $44^{\circ}12'E$
 76 chs. dist. marked $\frac{1}{4}$ S. B. T.
 From this cor a small spring
 br. N. $7^{\circ}45'E$ 16 chs. dist.

42.00 Leave timber

44.11 Foot of descent, ravine 5 ft.
 dup, course. S. W.
 Ascend 50 ft.

54.00 Top of ascent, a point on
 E. slope of a small round butte
 Descend 60 ft.

57.70 Foot of descent, ravine 10 ft.

Chains. T. 20 N. R. 2 E (Contd)

deep, course S. E.

66.00 Enter heavy timber

68.42 A pine 30 in diam. on line I
marked with 2 notches on N. & S.
sides.

80.00 Set a sandstone 13 x 12 x 10
ins. 8 ins. in the ground.
For cor to sec. 13. 14 23 + 24.
marked with 3 notches on S.
and 1 notch on E. edges
and raised a mound of tom
1 1/2 ft. high 2 ft. base
alongside, from which
A pine 46 in. diam. trs. N. 64° 28' E.
118 Ms. dist. marked. T. 20 N
R. 2 E. S. 13. B. T.

A pine 51 in diam trs. S. 46° 32' E.
179 Ms. dist. marked. T. 20 N
R. 2 E. S. 24. B. T.

Chains Subdivisions.

A pine 40 in diam. $N. 22^{\circ} 52' W.$
 121 Ms. dist. marked T. 20 N
 R. 2 E. S. 23. T. 3.

A pine 20 in diam. $N. 68^{\circ} 08' W.$
 83 Ms. dist. marked T. 20 N. R. 2
 E. S. 14. T. 3.

Land, mountainous & broken
 Soil, very 4th rate
 Timber, pine
 Mountainous or heavily timbered
 land. 80 chs.

$N. 89^{\circ} 56' E$ on a random line
 br. sec. 13 & 24.
 Ta $13^{\circ} 51' E$.

4000 Set temporary $\frac{1}{4}$ sec. cor.
 7992 Intersect E. ldy of T. 13 Ms.
 S of cor & sec. 13. 18. 19 + 24

Chains. To N. B. 2 E (Contd)

as previously described
Thence down

S. 89° 50' W. on a true line for
secs. 13 & 24

To 13° 51' E.

Over rolling heavily timbered land.

25.00 Descend. 35 ft.

27.30 Foot of descent, thence
along broken slope of hill

38.00 Descend. 250 ft.

39.96 Set a malpais. Stone 14 x 12 x 10
ins. 9 ins. in the ground.

For 1/4 sec. cor. marked 1/4 on
N. face and raised a mound
of stone 1 1/2 ft. high 2 ft.
face alongside, from which
a pine 10 in diam. br. N. 79° 03' W.

37 Ws. dist. marked 1/4 S. B. T.

A pine 14 in diam. br. S. 19° 11' W.

Chains. Subdivisions

- 107 hrs. dist. marked $\frac{1}{4}$ S. B. T.
- 57.00 Foot of descent. Thence
over rolling land.
- 79.92 Thence to sec. 13, 14, 23 + 24.
Land rolling & mountainous.
Soil, rocky 3rd rate
Timber, pine
Mountainous or heavily timbered
land. 79.92. chs.
-

N. $0^{\circ} 1' W$. for sec. 13 & 14
Ta $13^{\circ} 51' E$.

Over rolling heavily timbered
land.

24.50 Cross ledge, 10 ft. high
course E & W.

38.00 Ascend. 100 ft.

40.00 Top of rocky ridge. course E & W.

Chains To N. R. 2 E (Contd)

A flag limestone in place
 which I mark with a cross
 (4) at exact cor. point. For
 $\frac{1}{4}$ sec. cor. with $\frac{1}{4}$ on W. of cross
 and raised a mound of Tm
 $1\frac{1}{2}$ ft. high 2 ft. base
 along side, from which
 all bearings in diam. W. S. $70^{\circ}42'$ E.
 52 Ws. Dist. marked $\frac{1}{4}$ S. B. T.
 A pine 16 in diam. W. N. $84^{\circ}12'$ E.
 60 Ws. Dist. marked $\frac{1}{4}$ S. B. T.
 Descend 100 ft.

42.00 Foot of descent, various
 course. S. 30° W.

Ascend 200 ft.

50.00 Top of ascent.

Descend 150 ft.

52.00 A pine 10 in diam on line I
 mark with 2 notches on N. S.

Chains. Subdivisions.

Sides

66.00

Foot of descent, ravine 5 ft.
Deep, course @ $27^{\circ} E$
Rec'd 100 ft. N.

80.00

Set a malpais stone $25 \times 4 \times 10$
ins. 18 ins. in the ground for
cor to sec. 11. 12. 13. $\frac{3}{4}$ marked
with 4 notches on S and 1
notch on E. edges and raised
a mound of stone $1\frac{1}{2}$ ft. high
2 ft. base alongside from which
An ear 6 in diam. W. N $1^{\circ} 48' E$
71 Ms. dist. marked T. 20 N. R. 2
E. S. 12. B. T.

An ear 6 in diam W. S. $45^{\circ} 10' E$
63 Ms. dist. marked T. 20 N.
R. 2 E. S. 13. B. T.

An ear 8 in diam W. S. $67^{\circ} 45' W$
59 Ms. dist. marked T. 20 N.

Chains T. 20 N. B. 2. E. (Contd)

B. 2 E. S. 14 T. 3. J.

A pine 24 in diam. W. N. $13^{\circ} 56' W.$

107 Ws. dist. marked T. 20 N

B. 2 E. S. 11 T. 3. J.

Land, rolling Ed. broken

Soil, very 3rd rate

Timber, Pine

Heavily timbered land. 80 chs.

S. $89^{\circ} 50' E.$ on a random line

W. sec. 12^{Ed} 13.

Ta $13^{\circ} 51' E.$

4000 Ac temporary 1/4 Sec. cor.

79.96 Interest E. Edy of Tp. 11

W. N. of cor to sec. 7, 12, 13 & 18

as. for timber for disced
These I own

N. $89^{\circ} 45' W.$ on a true line W.

Chains. Subdivisions

secs. 12 & 13.

Ta $13^{\circ} 51' E$.Over rolling heavily timbered
land.

Descend gradually 55 ft.

20.00 Foot of descent

3998 Set a malpais. $Tom 18 \times 12 \times 10$ ins. 12 ins. in the ground
for $\frac{1}{4}$ sec. cor marked $\frac{1}{4}$ on N. Face and raised a
mound of $Tom 1 \frac{1}{2}$ ft. high
2 ft. Face alongside, from
which.A pine 16 in diam. $Trs. N. 27^{\circ} 15' E$
4100. dist. marked $\frac{1}{4}$ S. B. J.A pine 8 in diam. $Trs. S. 65^{\circ} E$.63. 700. dist. marked $\frac{1}{4}$ S. B. J.

51.00 Descend. 20 ft.

55.00 Foot of descent.

Chains. T. 20 N. R. 2. E. (Contd)

59.00 Ascend 75 ft.

73.00 Top of ascent

Descend 80 ft. to.

79.96 The cor to secs. 11, 12, 13 & 14.

Land broken & rolling

Soil, rocky 4th grade

Timber, pine

Heavily timbered land. 79.96. chs.

N 0° 1' W. Cr. sec. 11 & 12

Ta 13° 51' E.

Overgrown heavily timbered
land.

Ascend 100 ft.

10.00 Top of ascent, ridge, course
E + W.

Descend 100 ft.

22.00 Foot of descent, same course S. W.

Chains. Subdivisions.

Cross. S.W. cor of log fence
which encloses Summit
Spring, Spring Trs. N 91° E
5.40 chs. dist.

27.40 A pine 32 in diam. on line
I made with 2 notches on
N + S. sides.

From this point a small
unoccupied cabin Trs. E.
1.50 chs. dist.

28.00 Top of ascent. E descend 60 ft.

28.66 A pine 22 in diam. on line I
made with 2 notches on N + S.
sides.

30.00 Foot of descent

37.17 A pine 16 in diam on line I
made with 2 notches on N + S.
sides.

40.00 Set a sandstone 30 x 22 x 16

Chains. To N. B. 2. E. (Contd)

ins. 21 ins. in the ground
for 14 sec. cor. marked 1/4 on
W. face and raised a mound
of Torr 1 1/2 ft. high 2 ft.
base alongside, from which
An Obs. 10 in diam. Tr. S. 40° 8' E.

32 Ws. Dist. marked 1/4 S. B. T.
An obs 6 in diam. Tr. N. 83° 30' E.

57 Ws. Dist. marked 1/4 S. B. T.

40.68 An. Obs 40 in diam. on line I.
mark with 2 notches on N. + S.
sides.

8000 Set a malpais. Torr 14 X 11 X 9
ins. 9 ins. in the ground
for cor to sec. 1. 2. 11 & 12.
marked with 5 notches on S.
and 1 notch on E. edges. and
raised a mound of Torr 1 1/2 ft.
high 2 ft. base alongside

Chains. Sub-divisions

From which

A pine 22 in diam. No. N. 39° 34' E
 133 Ms. dist. marked T. 20 N
 R. 2 E. S. 1 T. 3. T.

An oak 8 in diam. No. S. 69° 17' E.
 82 Ms. dist. marked T. 20 N R
 2 E. S. 12. T. 3. T.

A pine 8 in diam. No. N. 68° 08' W
 121 Ms. dist. marked T. 20 N
 R. 2 E. S. 11 T. 3. T.

An aspen 8 in diam. No. N. 48° 2' W
 145 Ms. dist. marked T. 20 N.
 R. 2 E. S. 2. T. 3. T.

Land, broken + rolling

Soil, rocky 4th rate

Timber, pine

Heavily timbered land 80 chs.

October 24. 1894

Chains. T 20 N. B. 2 E. (Cont'd)

S. $89^{\circ}45' E$ on a random line
for sec. 1 of 12

Ta $13^{\circ}51' E$

40.00 Set temporary 1/4 sec. cor.

79.90 Intersect the E. bdy of Twp.
11 N. S. of cor to sec.
1. 6. 7. of 12. as hereinbefore
described

Thence I run

N. $89^{\circ}50' W$ on a true line for
sec. 1 of 12

Ta $13^{\circ}51' E$

Over broken land.

1.70 A pine 14 ins diam. on true
line I run with 2 notches on
E + W sides

15.00 A pine 46 in diam on
true line I run with 2
notches on E + W sides.

chains Subdivisions

Ascend gradually 80 ft.

28.00 Bench and pole fence
across line course
N. W. + S. E.

39.95 Clear Wagoners pasture
A masonry cross in place
4 x 3 x 2 ft. stone ground
which I mark with a
cross (+) at exact cor point
for $\frac{1}{4}$ sec cor. with $\frac{1}{4}$ on
N. of cross. and raised
a mound of stone $1\frac{1}{2}$ ft.
high 2 ft. base alongside
fence which

A pine 16 in. diam. W. S.
N. $67^{\circ}23'$ W. 19 Mo. dist.
marked $\frac{1}{4}$ S. B. T.

A pine 20 in. diam. W. S.
S $33^{\circ}26'$ E. 30 Mo. dist.

chains. T 20 N. R. 2 E. (Contd)

marked 14 A. B. T

53.00 Top of ascent

Descend 65 ft.

61.00 Foot of descent

65.00 Ascent 125 ft.

70.00 Top of ascent

Descend 140 ft. to

79.90 The cor to sec.

1. 2. 11 and 12.

Land, timber

Soil, very 3rd rate

Timber, pine

Heavily timbered land

79.90 chs.

27. c.

BOOK 331

Chains. Subdivisions

Chains Tgs N. B. 2. E. (Contd)

No 1st W. br. sec 1 & 2
 Va 13° 57' E.

Over rolling heavily timbered
 land.

21.00 Wash 3 ft. deep, course N 60° E.

23.00 Ascend 25 ft.

27.00 Top of ascent & descend
 20 ft.

30.00 Foot of descent

40.00 Set a mark. Two 14 x 12 x 10
 ins. 9 ins. in the ground
 for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on
 W. face and raised a
 mound of two 1 $\frac{1}{2}$ ft. high
 2 ft. base alongside, from
 which.

An oak 12 in. diam. W. N. 79° 13' E.

17. ins. dist. marked $\frac{1}{4}$ S. B. T.

A pine 30 in. diam. W. S. 87° 03' W.

Chains. Subdivisions

- 31 Ms. dist. marked $\frac{1}{4}$ S. T. B. T.
- 46.50 West 2 ft. deep, course S. 30° W
- 80.46 Intersect the 5th Standard
parallel North at a point
3.96 chs. W. of Standard
cor to sec. 35 + 36. T. 21. N. R. 2 E.
at which point I set a
malpais stone 18 x 14 x 10 ins.
12 ins. in the ground for
closing cor to sec. 1 and 2
marked C. C. on S. face with
1 notch on E. and 3 notches on
W. face. and raised a
mound of stone $1\frac{1}{2}$ ft. high
2 ft. face alongside of same
which.
- A pine 8 in diam. W. S. 40° 05' E
45 Ms. dist. marked T. 20 N
R. 2 E. S. 1 T. B. T.

Chains. T. 20. N. R. 2. E. (Contd)

A pine 8 in diam. trs. S. $81^{\circ}20'W$.

39 Ws. Dist. marked T. 20 N.

R. 2 E. S. 2. T. 3. T.

A pine 8 in diam. trs. N. $16^{\circ}14'W$

42 Ws. Dist. marked T. 20 N.

R. 2 E. C. C. S. 1 + 2 T. 3. T.

Land, gently rolling

Soil, very 3rd rate

Timber, pine

Heavily timbered land. 80.46. chs.

From the cor. to secs. 2, 3, 34 + 35
on S. vdy of T. p. as herein
before described Town.

N. $0^{\circ}1'W$. Cor. secs. 34 & 35

T. $13^{\circ}51'E$.

Over rolling heavily timbered
land.

Chains. Subdivisions

- Ascend. 30 ft.
- 6.00 Top of ascen.
- 37.93 A pine 18 in. diam on line I
mark with 2 notches on N + S
sides.
- 38.88 A pine 16 in diam. on line I mark
with 2 notches on N + S sides
- 38.99 A pine 12 in diam. on line I mark
with 2 notches on N + S sides.
- 40.00 Set a malpais stone 18x18x14
ins. 12 ins in the ground
for 1/4 sec. cor marked 1/4 on
W. face and raised a mound
of stone 1 1/2 ft. high 2 ft
face alongside, from which
A pine 12 in diam. to S. 61° 20' E
24 ins. dist. marked 1/4 S. T. B. J.
A pine 16 in diam. to N. 20° E
47 ins. dist. marked 1/4 S. T. B. J.

Chains T. 20 N. R. 2. E. (Contd)

- 49.96 A pine 30 in diam on line Iron
with 2 notches on N. + S. sides.
- 71.00 Small ravine, Course S. E.
- 73.35 A pine 18 in diam. on line Iron
with 2 notches on N. + S. sides.
- 80.00 Set a malpais. Tom 18x18x6
ins. 12 ins. in the ground
for cor to sec. 26, 27, 34 + 35
marked with 1 notch on S.
and 2 notches on E. edges
and raised a mound of
Tom 1 1/2 ft. high. 2 ft. base
alongside, from which
A pine 30 in diam. br. N 24° 14' E
8000. dist. marked T. 20 N
R. 2. E. S. 26. B. T.
- A juniper 12 in diam. br. S. 56° 22' E.
7300. dist. marked T. 20 N
R. 2. E. S. 35. B. T.

Chains Subdivisions

A pine 14 in diam. Trs. S. 60° 05' W.

140 Ms. dist. marked T. 20 N

R. 2 E. S. 34. T. 3. T.

A pine 10 in. diam. Trs. N. 76° 15' W.

93 Ms. dist. marked. T. 20 N

R. 2 E. S. 27. T. 3. T.

Land, rolling

Soil, very 4th rate

Timber, pine

Heavily timbered land. 80 chs.

East on a random line bet

secs 26 E of 35

Ta 13° 51' E.

40.00

Set temporary 1/4 sec. cor.

79.91

Intersect N & S line 17 W. S.

S. of cor to secs 25, 26, 35 & 36

Thence S. run

Chains T. 20 N. R. 2. E. (Contd.)

S. $89^{\circ}53'W$ on a true line over
secs. 26 $E/35$

To $13^{\circ}51'E$.

Over mountainous heavily
timbered land.

Ascend 200 ft.

6.00

Top of ascent. Thence over
rolling land.

39.95

Set a malpais. Tom. $14 \times 12 \times 10$
ins. 9 ins. in the ground
for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on
N. face and raised a mound
of tom. $1\frac{1}{2}$ ft. high 2 ft.
base alongside, from which
a pine 14 in diam. W. $N5^{\circ}38'E$
68 Ws. Dist. marked $\frac{1}{4}$ S. B. T.
A juniper 10 in diam. W. $S2^{\circ}28'E$
23 Ws. Dist. marked $\frac{1}{4}$ S. B. T.

40.51

A pine 26 in diam. on true S. tom.

chains. Subdivisions

with 2 notches on E & W sides.

79.91 The cor & sec. 26, 27, 34 & 35-

Land, mountainous & rolling

Soil, rocky & of rate

Timber, pine

Mountainous or heavily

timbered land. 79.91 chs

N^o 1' W. cor sec. 26 & 27.

Ta. 13^o 51' E.

Over rolling heavily timbered
land.

40.00 Set a mark. Stone 18 x 14 x 8
ins. 12 ins. in the ground.

For 1/4 sec. cor marked 1/4 on
W. face and raised a mound
of stone 1 1/2 ft. high. 2 ft.
base alongside, from which

Trains. T₂₀ N. B. 2. E. (Cont'd)

A pine 10 in diam. Tr. N. 13° W.
dist. marked 1/4 S. B. T.

An oak 8 in diam. Tr. N. 24° 15' W.
27 Ws. dist. marked 1/4 S. B. T.

69.00 Descend 175 ft. into cañon

75.30 Bed of cañon, course N. W.
Ascend 50 ft. to.

80.00 Set a caud. stone 12 x 12 x 10
ins. 8 ins. in the ground
for cor to sec. 22, 23, 26 + 27.
marked with 2 notches on S.
& E. edges. and raised a mound

of stone 1 1/2 ft. high 2 ft.
base alongside, from which.

A pine 8 in diam. Tr. N. 52° E
29 Ws. dist. marked T₂₀ N
B. 2. E. 23. B. T.

An oak. 4 in diam. Tr. S. 12° 47' E
36 Ws. dist. marked T₂₀ N

Chains. Subdivisions

B. 2. E. S. 26. T. 20. N.

An oak 4 in diam. W. S. $35^{\circ}10'N$.

88 W. dist. marked T. 20. N.

B. 2. E. S. 27. T. 20. N.

A pine 18 in diam. W. N. $34^{\circ}16'N$.

78 W. dist. marked T. 20. N.

B. 2. E. S. 22. T. 20. N.

Land, rolling Ed. Brown

Soil, very 3rd rate

Timber, pine, some scrub oak

Heavily timbered land, 80 chs.

N. $89^{\circ}53'E$ on a random line

to sec. 23 + 26.

To a $13^{\circ}51'E$.

40.00 Set temporary 1/4 sec. cor

79.95 Intersect N + S line a W. cor

of cor to sec. 23. 24. 25 + 26.

Chains. T. 20 N. R. 2. E. (Contd.)

Thence Town

S. $89^{\circ}49'W$. on a true line

for sec. 23 Ed 26.

Ta $13^{\circ}57'E$.

Over-broken brackly timberland land.

6.00 Ascend 20 ft.

10.00 Top of ascent

Descend 30 ft.

23.00 Foot of descent

3997 Set a malpais. stone $14 \times 12 \times 8$
ins. 9 ins. in the ground

for $\frac{1}{4}$ sec. cor marked $\frac{1}{4}$ on

N. face and raised a mound
of stone $1\frac{1}{2}$ ft. high. 2 ft.

face alongside, from which
Azimut 10 in diam. to N $91^{\circ}22'E$.

27 ins. dist. marked $\frac{1}{4}$ S. B. T.

A pine 14 in diam. to S. $87^{\circ}13'W$.

93 ins. dist. marked $\frac{1}{4}$ S. B. T.

Chains. Subdivisions.

59.00 Descend 25 ft.

63.00 Foot of descent
Ascend 100 ft.77.00 Top of ascent, ridge course
N + S.

Descend 150 ft. to

79.95 - The cor to sec. 22, 23, 26 + 27.

Land, broken

Soil, rocky 4" rate

Timber, pine

Heavily timbered land 79.95 Cha.

N 0° 1' W. to sec. 22 + 23

Ta 13° 51' E.

Over mountains heavily
timbered land.

Ascend 200 ft.

11.00 Top of ascent, thence over

chains To N. B. 2. E. (Contd)

- high rolling mesa
- 40.00 Set a mark. Stone 14 x 11 x 9
ins. 9 ins. in the ground
For 1/4 sec. cor marked 1/4 on
W face and raised a mound
of stone 1 1/2 ft. high 2 ft.
base alongside, from which
a pin 16 in diam. W. N. 61° E
78 Ws. dist. marked 1/4 A. B. T.
Apine 22 in diam. W. S. 16° W
103 Ws. dist. marked 1/4 A. B. T.
- 62.50 Descend 75 ft.
- 65.00 Foot of descent, ravine, course
W.
- Ascend. 65 ft.
- 67.00 Top of ascent.
- 75.00 Descend 100 ft. S.
- 80.00 Set a mark. Stone 20 x 14 x 10
ins. 15 ins. in the ground for

Chains Subdivisions

- Cor to ces. 14. 15. 22 E/23
 marked with 3 notches on S
 and 2 notches on E. edges.
 and raised a mound of Torr
 1 1/2 Ft. high 2 Ft. base
 along side, from which
 An oak 6 in diam. br. N. 28° 38' E.
 17 Ms. dist. marked T. 20 N
 B. 2. E. S. 14. B. T.
- An oak 6 in diam. br. S. 65° 11' E.
 56 Ms. dist. marked T. 20 N
 B. 2. E. S. 23. B. T.
- An oak 6 in diam. br. S. 61° 21' W
 44 Ms. dist. marked T. 20 N
 B. 2. E. S. 22. B. T.
- An oak 8 in diam. br. N. 68° 27' W.
 36 Ms. dist. marked T. 20 N
 B. 2. E. S. 15. B. T.
- Note. From this cor Stewart

Crains.

T. 20 N. R. 2. E. (Contd)

Spring Trs. N. 72° E. 17 chs. dist

All old corral Trs. N. 37° 21' E

11 chs. dist.

All old corral Trs. N. 16° W. 4.50

chs. dist

Level, mountainous, soil stony 4-5' with
Timber, pine. Some Cent. Oak

Mountainous or heavily timbered
land. 80 chs.

N. 89° 49' E. on a random line

Trs. secs. 14 E. 23

To 13° 51' E.

40.00

Set temporary 1/4 sec. cor

79.85

Intersect N + S. line 22 W.

N of cor to secs. 13. 14. 23 E. 24.

Thence down

S. 89° 58' W. on a true line Trs

secs. 14 E. 23.

Chains. Subdivisions

To $13^{\circ} 51' E$.

Over rolling heavily timbered land.

- 13.00 West, 4 ft. deep, course S.
- 21.00 Ascend gradually 100 ft.
- 39.92 Set a trap for mice. $20 \times 14 \times 10$ ins. 15 ins. in the ground for $\frac{1}{4}$ sec. cor marked $\frac{1}{4}$ on N face and raised a mound of $20 \times 14 \times 10$ ft. high. 2 ft. face alongside. From which
An oak 6 in diam. $70^{\circ} S. 23^{\circ} 40' W.$
21 No. dist. marked $\frac{1}{4}$ S. B. T.
- Apine 40 in diam. $70^{\circ} N. 27^{\circ} 31' E$
95 No. dist. marked $\frac{1}{4}$ S. B. T.
- 42.00 Ravine 25 ft. deep, course S.
 $15^{\circ} W.$
- 51.00 Top of ascent, thence over rolling land.

Chains. T 20 N. B. 2 E (Contd)

63.00 Descend 200 ft. to
 79.85 The cor to sec. 14, 15, 22, & 23
 Land, rolling & mountainous
 Soil, Tong 4th rate
 Timber, pine, comm. scrub. Oak
 Mountains or Gravity timbered
 land. 79.85 chs.

N 0° 1' W. br sec. 14 & 15
 T a 13° 51' E.

Over mountainous. Gravity
 timbered land.

Descend gradually 20 ft.

9.00 Foot of descent, west 3 ft.
 deep, course W.

19.00 Ascend E. slope of butte.
 40 ft.

27.00 Top of ascent.

Chains. Subdivisions.

- Descend 35 Ft.
- 40.00 Top of descent
Set a mark. Tom. 14x9x8
ins. 9 ins. in the ground for
1/4 sec. cor marked 1/4 on W.
Face and raised a mound of
Tom 1 1/2 Ft high. 2 Ft. base
alongside, from which
A pine 50 in diam. to N 41° 11' E.
28 Ws. dist. marked 1/4 S. B. T.
- A pine 10 in diam. to N. 87° 03' W.
65 Ws. dist. marked 1/4 S. B. T.
- 46.50 Ascend. 250 Ft.
- 65.00 Top of ascent, thence over
rolling mesa
- 87.00 Set a mark. Tom 24x16x9
ins. 18 ins. in the ground
for cor & sec. 10. 11. 14 & 15-
marked with 4 notches on S. and

Chains. T. 20 N. R. 2. E. (Contd)

2 notches on E. edges and
raised a mound of Torr
1 1/2 ft. high 2 ft. base
alongside. From which
An oak 6 in diam. tr. N. 48° 23' E
42 Ws. dist. marked. T. 20 N
R. 2. E. S. 11. T. T.

An oak 6 in diam. tr. S. 54° E.
74 Ws. dist. marked. T. 20 N
R. 2. E. S. 14. T. T.

An oak 6 in. diam. tr. S. 46° 58' W.
128 Ws. dist. marked. T. 20 N
R. 2. E. S. 15. T. T.

A pine 10 in diam. tr. N. 44° 13' W.
93 Ws. dist. marked. T. 20 N
R. 2. E. S. 10 T. T.

Land, broken Ed mountains.
Soil, Stony 4th date
Timber, pine, from south east

Chaus. Subdivisions

Mountainous or heavily
timbered land. 80 chs.

A. $89^{\circ}58'E$ on a random line
 Wt sec. 11 Ed 14
 Ta $13^{\circ}51'E$.

4000 Set temporary $\frac{1}{4}$ sec. cor.
 7990 Intersect N. + S. line. 18 W. S.
 of cor to sec. 11. 12. 13 Ed 14.
 Thence down

A. $89^{\circ}50'W$ on a true line Wt
 sec. 11 Ed 14
 Ta $13^{\circ}51'E$.

Over broken heavily timbered land.
 Descend 25 ft. along S. slope
 of hill.

10.50 Foot of descent, wash 3 ft.
 deep, course S. E.

Chains To N B. 2. E. (Contd)

Ascend 35 Ft.

14.00 Top of ascent

15.00 Descend gradually 20 Ft.

21.00 Foot of descent

39.95 Set a malpais. Stone 14x12x10
ins. 9 ins in the ground for
1/4 Sec. cor marked 1/4 on N
Face and raised a mound
of stone 1 1/2 Ft. high. 2 Ft.
Face alongside, from which
a pine 20 in diam. br. N. 7° 09' W
13 Ms. dist. marked 1/4 S. B. T.
A pine 40 in diam. br. S. 21° 33' W.
87 Ms. dist. marked 1/4 S. B. T.

49.00 Ascend 30 Ft.

53.00 Top of ascent. Thence over
rolling land.

76.00 Rain 3 Ft. deep, course S.

79.90 The cor to secs. 10. 11. 14 & 15

Chains Subdivisions

Land, broken Ed rolling
 Soil, very 4th rate
 Timber, pine, com. cor. case.
 Heavily timbered land, 79.90 chs.
 October 25, 1894

N 0° 1' W. Tr. sec. 10 Ed 11
 Ta 13° 51' E.

Over-rolling heavily timbered land.
 4000 Set a walpole. Tr. 14x10x10
 ins. 9 ins. in the ground for
 1/4 sec. cor marked 1/4 on W. face
 and raised a mound of Tr. 1
 1 1/2 ft. high 2 ft. base
 along side, from which
 an case 8 in. diam. Tr. N. 39° 17' W.
 63 Ms. dist marked 1/4 S. B. T.
 A pin 14 in diam. Tr. S 76° 31' E.
 27 Ms. dist marked 1/4 S. B. T.

Chains T. 20 N R. 2 E. (Contd)

50.00 Ascend 200 Ft.

71.00 Top of ascent

80.00 Set a malpais stone 14 x 10 x 10
ins. 9 ins. in the ground for
cor to sec. 2, 3, 10 E 11. marked
with 5 notches on S. and 2
notches on E. edges and
raised a mound of stone 1 1/2
Ft. high 2 Ft. base alongside
from which

A pine 16 in diam. brs. N. 46° 51' E.
18 Ms. dist. marked T. 20 N
R. 2 E. S. 2. B. T.

An oak 6 in diam. brs. S. 81° 28' E.
13 Ms. dist. marked T. 20 N
R. 2 E. S. 11 B. T.

An oak 8 in diam. brs. S. 22° 39' W.
25 Ms. dist. marked T. 20 N
R. 2 E. S. 10 B. T.

chains. Subdivisions

An case 6 in diam. Trs. N. 69° 09' W.

46 Ms. Dist. marked T. 20 N

R. 2 E. S. 3 T. 3.

Land, rolling Ed. mountains

Soil, very 4th rate.

Timber, piney, some scrub oak

Mountains or heavily timbered

land. 80 chs.

N. 89° 50' E. on a random line

Trs. sec. 2 E. 11

Ta 13° 51' E

4000 Set temporary 1/4 sec cor

7991 Intersect - N + S line 11 Ms N
of cor to sec. 1. 2. 11 E. 12

Thence Iron

S. 89° 55' W on a true line Trs

sec. 2 E. 11

Chains T. 20 N. B. 2 E. (Contd)

T a $13^{\circ} 51' E$

Over rolling heavily timbered land.

- 2.43 A pine 46 in diam. on line I mark
with 2 notches on E + W. sides.
- 4.30 West. 2 ft. deep, course. N.
- 8.00 Ascend. 20 ft.
- 12.00 Top of ascent
- 28.00 Ascend. 45 ft.
- 30.15 A pine 12 in diam. on line I mark
with 2 notches on E + W. sides.
- 39.95 Set a mark. Stone $18 \times 12 \times 10$
ins. 12 ins. in the ground. For
 $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on N.
face and raised a mound of
stone $1\frac{1}{2}$ ft. high 2 ft.
base alongside, from which
A pine 16 in diam. Trs. N. $48^{\circ} 09' E$.
1100. Dist. marked $\frac{1}{4}$ S. B. L.

Chain. Subdivisions

- an oak 10 in diam. Tr. $S 62^{\circ} 42' W$.
 31 Ms. dist. marked $\frac{1}{4}$ S. B. T.
 48.00 Top. of ascent
 60.00 Descend 25 ft.
 65.50 Foot of descent
 73.05 A pine 36 in diam on line I
 mark with 2 notches on E & W. sides
 79.91 The cor to sec. 2, 3, 10 & 11
 Land, rolling
 Soil, very 4th rate
 Timber, pine, some scrub oak
 Heavily timbered land. 79.91 chs.
-

$S 0^{\circ} 1' W$. Tr sec. 2 & 3.
 Ta $13^{\circ} 51' E$.

Our rolling heavily timbered
 land.

7.00 Ascend 100 ft

Chains T. 20. N. B. 26. (Contd)

- 11.00 Top of ascent,
Descend 110 ft.
- 25.00 Foot of descent.
- 40.00 Set a malpais. Stone 18x12x10
ins. 12 ins. in the ground for
 $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on W
Face and raised a mound of
Stone $1\frac{1}{2}$ Ft. high 2 ft. base
along side, from which
An obs. 12 in diam. Trs. S. $57^{\circ}18'$
5.7. 200. dist. marked $\frac{1}{4}$ S. B. I.
A pine 40 in diam. Trs. S. $73^{\circ}09'$ E.
2100. dist. marked $\frac{1}{4}$ S. B. I.
- 41.00 Ascend gradually 25 ft.
- 47.00 Top of ascent, and descend 30 ft.
- 51.00 Foot of descent, small west
course. E.
Ascend 35 ft.
- 59.00 Top of ascent.

Chains. Subdivisions.

73.00 Descend 25 ft. to

80.33 Intersect the 5th Standard
parallel *N* at a point 4.08^{ths}.
W of Standard cor to sec.
34 + 35. T. 21 N. R. 2 E
At which point I set a
sandstone 10 x 10 x 10 ins. block
in the ground for closing
cor. to sec. 2^d & 3^d marked
C.C. on *N* face with 2 notches
on *E* and 4 notches on *W*
faces. and raised a mound
of stone 1 1/2 ft high 2 ft.
Face alongside, from which
A pine 18 in diam. W. S. 64° E
86 W. dist. marked T. 20 N
R. 2 E. S. 2. T. B. T.
A pine 18 in diam. W. S. 41° 15' N.
96 W. dist. marked T. 20 N.

Chavis. T. 20 N. R. 2 E. (Contd).

R. 2 E. S 3 T. 2.

A pine 16 in diam. to N. $31^{\circ}28'$ E.

22 Ws dist. marked. T. 20 N. R. 2.

E. C. C. S. 2 + 3. T. 2.

Land, timber

Soil, 3rd rate

Timber, pine, scrub oak.

Heavily timbered land. 80.33 chs.

From the cor to sec. 34, 33 E 34
on S. E. of Tp. as previously
described. True.

N. $2^{\circ}2'$ W. to sec. 33 E 34
Ta $13^{\circ}51'$ E.

Over rolling heavily timbered
land.

Descend gradually 40 ft.

4000 A malpais rock in place

Chains. Subdivisions -

2 x 3 x 1 1/2 ft. above ground.
 which I mark with a cross
 (+) at exact cor point. For 1/4
 sec. cor. with 1/4 on W of
 cross and raised a mound of
 stone 1 1/2 ft. high 2 ft. face
 along side, from which
 A pine 12 in diam. brs. N 63° 13' W.
 95 Ma. dist. marked 1/4 S. B. S.
 A pine 14 in diam. brs. S. 82° 07' E
 101 Ma. dist. marked 1/4 S. B. S.

- 54.00 Foot of descent
 West. 4 ft. deep, course S. W.
 Ascend. 200 ft.
- 60.00 Top of ascent.
 Descend 100 ft.
- 65.00 Foot of descent
 Ascend 200 ft.
- 73.00 Top of ascent.

Chains. T₂₀ N. R. 2 E. (Contd)

Lean heavy timber, with
scattering pine & Juniper

80.00 Set a trapline. Truss 18x16x15
ins. 12 ins in the ground for
corn to sec. 27, 28, 33 & 34 with 1 notch on S
and 3 notches on E

edges, and raised a mound of
truss 1 1/2 ft. high 2 ft. base
along side, from which:

A juniper 10 in diam. W. S.
39° E. 197 Ws. dist. marked

T₂₀ N. R. 2 E. S. 34. T. S.

A juniper 40 in diam. W. S.
69° 57' E. 160 Ws. dist. marked

T₂₀ N. R. 2 E. S. 34. T. S.

A juniper 24 in diam. W. S.
40° 33' E. 218 Ws. dist. marked

T₂₀ N. R. 2 E. S. 34. T. S.

A juniper 20 in diam. W. S.
70° 19' N. 237 Ws. dist. marked.

Chains Sub-divisions

T. 20 N. R. 2 E. S. 33. B. T.
 Land, trees + mountains
 Soil, rocky 4th rate
 Timber, pine
 Mountains or heavily timbered
 land. 73. chs.

East on a random line to
 Secs. 27 E. 34
 Ta 13° 51' E.

40.00 Set temporary 1/4 Sec. cor.
 79.87 Intersect N + S line 18 W. A.
 of cor to secs. 26. 27. 34 E. 35
 Thence True
 S. 89° 52' W on a true line to
 Secs. 27 E. 34
 Ta 13° 51' E.
 Over rolling heavily timbered

Chains. T. 20 N. R. 2. E. (Contd)

land

- 39.93 Set a mark. Stone 14 x 12 x 10
ins. 9 in in the ground for
1/4 sec. cor. marked 1/4 on N
face and raised a mound of
stone 1 1/2 ft. high 2 ft. face
alongside, from which
A pine 16 in. diam. br. S. 86° 15' W.
23 No. dist. marked 1/4 S. B. T.
A pine 20 in. diam. br. N. 3° 19' E
17 No. dist. marked 1/4 S. B. T.
- 45.00 Descend 100 ft. into Cañon
- 49.00 Bed of cañon. Course S. W.
Ascend 150 ft.
- 55.00 Top of ascent.
- 75.00 Clear heavy timber
- 79.87 The cor. to Secs. 27. 28. 33 & 34
Land, from
Soil, from 3rd rate

Chains. Subdivisions

Timber, pine

Heavily timbered land. 75 chs.

N $0^{\circ} 2' W$. 75 sec. 27 E of 28.Ta $13^{\circ} 51' E$.

Over rolling land.

- 7.00 Descend. 200 ft. into Cañon
- 16.00 Foot of descent, thence along
toward E. slope of Cañon
- 27.15 Bed of Cañon, Course $S. 8^{\circ} W$.
Ascend W slope of Cañon
300 ft.
- 40.00 Set a mark as stone $16 \times 14 \times 12$
ins. 11 ins in the ground
for $\frac{1}{4}$ sec. cor marked $\frac{1}{4}$
on N. face and raised
a mound of stone $1\frac{1}{2}$ ft. high
2 ft. face alongside, from which

Trains To N. B. 2 E. (Contd)

A pine 24 in diam. Trs. S. 26° 17' E

32 hrs. dist. marked 1/4 N. B. T.

An oak 12 in diam. Trs. S. 53° 28' W.

28 hrs. dist. marked 1/4 N. B. T.

42.00 Top of ascent.

Enter heavy timber

Descend. 300 ft. into cañon

49.00 Bed of cañon course. S. 3° E.

Thence along general course
of cañon

73.00 Ascend 250 ft. out of cañon

79.50 Top of ascent.

80.00 A sandstone in place 6x6x6
ft. above ground, which I
mark with a cross (+) at
exact cor point. For cor to sec.
21. 22. 27 E of 28 with 2 notches
on S and 3 notches on E of cross
and raised a mound of stone

Chains. Subdivisions.

1 1/2 ft. high. 2 ft. base
 along side, from which.
 An oak. 6 in diam. W. N. 17° 22' E
 23 Ws. dist. marked. T. 20 N
 R. 2 E. S. 22. T. T.

An oak. 8 in. diam. W. S. 14° 22' E
 16. Ws. dist. marked. T. 20 N
 R. 2 E. S. 27. T. T.

A pine 21 in diam. W. S. 60° 21' W
 49. Ws. dist. marked. T. 20 N
 R. 2 E. S. 28. T. T.

A pine 23 in diam. W. N. 14° 04' W
 57 Ws. dist. marked. T. 20 N
 R. 2 E. S. 21. T. T.

Land, rolling & mountainous
 Soil, very 4th rate
 Timber, pine
 Mountainous or heavily
 timbered land. 73. chs.

chains. To N. B. 2. E. (Contd)

Note In sec 28 about 1/2 mile
S + W westerly from this cor is
a large spring known as
Bear Spring

N. $89^{\circ}52'E$ on a random line
bet. sec. 22 E & 27
Ta $13^{\circ}51'E$.

4000 Set temporary 1/4 sec. cor.

7990 Intersect N + S. line 9 W. S.
of cor to sec. 22, 23, 26 E & 27.

Thence Town

S. $89^{\circ}48'W$ on a true line bet
sec. 22 E & 27.

Ta $13^{\circ}51'E$.

Corr town heavily timbered
land.

Descend 50 ft. into cañon

Chains Subs. T. 20 N. B. 2. E. (Contd.)

2.84 Bed of cañon, course N. W.
Ascend 100 ft.

5.00 Top of ascent, ridge, course
N. + S.

Descend 200 ft. into Cañon
17.89 Foot of descent, in the Cañon
course. S. W.

Ascend abruptly 150 ft
23.00 Top of ascent. Thence over
high mesa.

39.95 Set a malpais. Stone 12x12x12
ins. 8 ins. in the ground.
For $\frac{1}{4}$ sec cor marked $\frac{1}{4}$
on N. Face and raised a
mound of Stone $1\frac{1}{2}$ ft. high
2 ft. base alongside, from
which

A pine 18 in diam. to N 70° 4' E
50 Ms. dist marked $\frac{1}{4}$ S. B. T.

Notes continued in Book 332.

BOOK 331