

3

No. 455

BOOK 455

Subdivision

4-671

455

FIELD NOTES

GENERAL LAND OFFICE.

Township 23 N. R. 5. E

Indexed Book 453.

128

Township 23N R. 5E

6	144	5	4	3	2	1
142	140					
7	138	8	9	10	11	12
135	133					
18	130	17	16	15	14	13
129						
19	20	21	22	23	24	
30	29	28	27	26	25	
31	32	33	34	35	36	

Subs. T. 23 N. R. 5 E. (cont)

chs 3, 8, 19 and 24, which is a
stone firmly set and prop-
erly marked and witnessed
as described in the field
notes furnished by the
Surveyor General.
I obliterate all marks
which refer to surveys on
the East.
at the point of intersection
I set a malpais stone 18 x
18 x 12 ins. 12 ins. in the
ground for closing cor. C.
sec. 18 and 19, marked C.C.
on E. face, with 3 notches
on N. and S. faces, and
raised a mound of stone
2 ft high, 3 ft base,
alongside, from which

Subdivisions

- chs. a Pine 8 mis. diam. hrs.
 $\$ 330^{\circ} 40' E.$ 64 lks. dist.
 marked T. 23 N. R. 5 E. S. 19 B.T.
- a Pine 8 mis. diam. hrs.
 $\$ 50^{\circ} 25' E.$ 71 lks. dist.
 marked T. 23 N. R. 5 E. S. 19 B.T.
- c Pine 16 mis. diam. hrs.
 $\$ 160^{\circ} 55' W.$ 47 lks. dist.
 marked T. 23 N. R. 5 E. C. C. S. 18-19
 B.T.

Land, mountainous and
 rolling.

Soil, stony, 2^o and 3^o rate
 Timber, pine.

mountainous, or heavily
 timbered land 60.46 chs.

N. 0^o 3' W. bet. sees 17 and 18.

Var. $130^{\circ} 45' East.$

T. 23 N. R. 5 E. (cont)

chs ever rolling broken heavily
timbered land.

ascend gradually 50 ft.

12.00 Top of ridge, course E, and N.
descent 100 ft.

23.00 Foot of descent, ascend 50 ft

38.00 Top of ridge, course E and
N. descent 20 ft.

40.00 Set a malpais stone 14x10
x10 ins. 10 ins in the
ground for $\frac{1}{4}$ sec. cor. marker
 $\frac{1}{4}$ on N-face, and raise a
mound of stone 2 ft high,
3 ft. base, alongside. from
which

a pine 8 ins. diam. has
N. 79° 50' E. 13 chs. dist.

marker $\frac{1}{4}$ B. B. T.

a pine 10 ins. diam. has

Subdivisions

- chs S. 2^o 36' N. 19 lks. dist.
marked 1/4 S. B.T.
- 42.00 Road, course N. W. and S. E.
- 46.00 ascends 40 ft.
- 52.00 Top of ascent and descends
50 ft.
- 55.00 Foot of descent, and leave
timber, enter open park.
- 70.00 ascends 150 ft.
- 80.00 Set a malpais stone 20 x
12 x 12 mic. 15 mic. in the
ground for cor to sec.
2, 8, 17 and 8, marked with
4 notches on S. and 5 notches
on E. edges, and raised
a mound of stone 2 ft.
high, 3 ft. base, along-
side, from which
a Puni 36 mic. diam. has

T. 23 N. R. 5 E. (cont)

cho N. $56^{\circ} 15' E$. 42 lks. dist.
 marked T. 23 N. R. 5 E. S. 8 - B.T.
 a Pine 30 mis. diam. hrs.
 S. $42^{\circ} 05' E$. 105 lks. dist.
 marked T. 23 N. R. 5 E. S. 17 - B.T.
 a Pine 10 mis. diam hrs
 S. $13^{\circ} 10' W$. 202 lks. dist. marked
 T. 23 N. R. 5 E. S. 18 - B.T.
 a Pine 35 mis. diam. hrs. N.
 $60^{\circ} 46' W$. 120 lks. dist. marked
 T. 23 N. R. 5 E. S. 7 - B.T.
 Land, rolling and mountain-
 ous.
 Soil, stony, 3^d rate.
 Timber, pine.
 Heavily timbered on moun-
 tainous land, 55 lks.
 S. $19^{\circ} 47' E$. on a random line

Subdivisions

chs. bet. secs. 8 and 17.

Var. $13^{\circ}45'$ East.

40.00 Set temporary $\frac{1}{4}$ sec. cor.

79.90 Intersect N. and S. line 29
chs. S. of cor. to secs. 8, 9,
16 and 17.

Thence Drive

N. 89° 59' W. on a true line
bet. secs. 8 and 17.

Var. $13^{\circ}45'$ East.

over rolling land.

12.00 Leave open, enter heavily
timbered land.

36.00 Road. Course N. W. + S. E

39.95 Set a malpais stone $16 \times$

12×12 ins. 11 ins. in the
ground for $\frac{1}{4}$ sec. cor.

marked $\frac{1}{4}$ on N. face,
and raised a mound of
stone $1\frac{1}{2}$ ft high, 3 ft.

+ 23 N. R. 5 E. (cont)

chs. base, alongside, from
which

a Pine 14 ins. diam. tree
N. $30^{\circ} 11'$ E. 27 lks. dist.

marked 1/4 S. B. T.

a Pine 16 ins. diam. tree
N. $63^{\circ} 40'$ W. 31 lks. dist.

marked 1/4 S. B. T.

57.00 Leave heavily timbered land,
enter open park

79.90 The cor. to secs. 7, 8, 17 and 18.

Land, ralling.

Soil, stony. 3^d rate.

Timber, pine.

Heavily timbered land 44.91 chs.

West on a true line

bet. secs. 7 and 18.

Var. $13^{\circ} 45'$ East.

Subdivisions

- chs over rolling land, through
 scattering timber.
 ascend 50 ft.
- 7.00 Top of ascent and descent
 150 ft.
- 22.00 Foot of descent, thence
 over rolling land,
- 40.00 Set a malpais stone 12×12
 $\times 8$ ins. 8 ins in the ground
 for $\frac{1}{4}$ sec. cor. marker
 $\frac{1}{4}$ on N. face, and raised
 a mound of stone $1\frac{1}{2}$ ft.
 high, 2 ft base, along
 side. Pts impracticable
- 59.00 Leave scattering timber,
 enter heavily timbered,
- 68.32 Intersect w. bdy of Sp. 14.10
 chs. N. of cor. Co. sec. 7, 12,
 13 and 18, which is a

T. 23 N. R. 5 E (cont.)

the stone firmly set and properly marked and witnessed as described in the field notes furnished by the Surveyor General.

I obliterate all marks which refer to surveys on the East

at the point of intersection I set a malpais stone 16 x 11 x 11 ins. in the ground for closing cor to sec 7 and 18, marked C. C. on E. face, with 2 notches on N. and 4 notches on S. faces, and raised a mound of stone $\frac{1}{2}$ ft. high, 2 ft. base, alongside, from which

Subdivisions

chs. a Pine 12 ins. diam. hrs.
N. $16^{\circ} 20'$ E. 42 chs. dist.

marked T. 23 N. R. 5 E. S. 7 B.T.

a Pine 12 ins. diam. hrs.

S $11^{\circ} 10'$ E. 16 chs. dist. mark-

ed T. 23 N. R. 5 E. S. 18 B.T.

a Pine 16 ins. diam. hrs.

S $19^{\circ} 40'$ E. 51 chs. dist.

marked T. 23 N. R. 5 E. S. 15 B.T.

Land, rolling.

Soil, stony. 3^d rate.

Timber, pine.

Heavily timbered land

9.32 chs.

N. $0^{\circ} 3'$ W. bet. secs. 7 and 8.

Var. $13^{\circ} 45'$ East.

Over rolling land.

40-00

Set a malpais stone 18x16

T. 23 N. R. 5 E. (cont)

- chs 7 8 mis. 12 mis. in the ground
 for $\frac{1}{4}$ sec. cor. marker
 $\frac{1}{4}$ on N. face, and raise
 a mound of stone $1\frac{1}{2}$ ft.
 high, 3 ft. base, alongside.
 Pits impracticable.
- 51.00 Road course N. W. and S. E.
- 80.00 Get a malpais stone $20 \times$
 20×12 mis. 15 mis. in the
 ground for cor. to sec.
 5, 6, 7 and 8, marker with
 5 notches on S. and E. edges,
 and raise a mound of
 stone 2 ft high, 3 ft base,
 alongside, from which
 a Pine 25 mis. drain. hrs.
 N. 38° / S. E. 120 chs. dist.
 marker T. 23 N. R. 5 E S. 5 T. T.
 a Pine 12 mis. drain. hrs.

Subdivision

chs N. 43° 25' W. 10' lks. dist.
 marked T. 23 N. R. 5 E. S. 6 DT
 No other trees within limits
 Land, level, and rolling
 Soil, stony, 2° and 3° rate.
 No timber.

S 89° 59' E. on a random line
 bet. secs. 5 and 8.

Var. 130° 45' East.

40.00 Set temporary 1/4 sec. cor.

Pd. 29 Intersect N. and S. line 39
 lks. N. of cor to secs 4, 5, 8
 and 9.

Thence I run

N. 89° 42' W. on a true line
 bet. secs 5 and 8.

Var. 130° 45' East.

Over mountains heavily

T. 23 N. R. 5 E. (cont)

- chs. Timbered land.
ascend 200 ft.
- 11.00 Top of ascent, ridge,
course S. E. and N.
Thence along ridge,
descent 700 ft.
- 40.15 Set a red cedar stone
14x14x6 ins. 10 ins. in
the ground for 1/4 sec. ear-
marked 1/4 on N. face, and
raised a marker of stone
2 ft high, 3 ft. base, along-
side, from which,
a Fri 11 ins. diam. bs.
S. 76° 20' E. 42 lks. dist.
marked 1/4 S. S.T.
- a Fri 9 ins. diam. bs.
S. 87° 10' W. 31 lks. dist.
marked 1/4 S. S.T.

Subsidiaries

chs	
54.00	Beane heavily timbered land, with open park.
61.00	Foot of descent, thence over rolling land,
80.29	The cor to sec. 5, 6, 7 and 8. Land, mountainous and rolling. Gail, stony, 20 rate. Timber, fir, pine and aspen. mountainous or heavily tim- bered land, 61 chs.

West on a true line
bet. sec. 6 and 7.

Var. $13^{\circ}45'$ East.

Over level land.

24.00 Road, course N. W. and S. E.

40.00 Get a sand stone, $2 \times 10 \times 10$

T. 23 N. R. 5 E. (cont)

chs 8 ins. in the ground for
 $\frac{1}{4}$ sec. cor. marker $\frac{1}{4}$ on
 N. face, and dug pits $18 \times$
 18×12 ins E. and W. of
 stone $3\frac{1}{2}$ ft dist. and
 raised a mound of stone
 covered with earth $3\frac{1}{2}$ ft.
 high, $4\frac{1}{2}$ ft base, alongside.

68.80 Intersect W. bdy of Sp.
 14.20 chs. N. of cor to sec.
 1, 6, 7 and 12, which is a
 post firmly set and prop-
 erly marked and intersected
 as described in the field
 notes furnished by the
 Surveyor General
 I obliterate all marks
 which refer to surveys
 on the East.

Subdivisions

cho

at the point of intersection I set a malpais stone $20 \times 20 \times 10$ ins. 15 ins. in the ground for closing run to sec. 6 and 7, marked c. c. on E. face, with 1 notch on N. and 5 notches on S. faces and raised a mound of stone 2 ft high, 3 ft. base, alongside.

Puts impracticable.

Land, level.

Soil, stony, 3^d rate

No timber.

N. $0^{\circ} 3' W.$ on a random line
bet. sec 5 and 6

Var. $13^{\circ} 45'$ East.

T. 23 N. R. 5 E. (cont)

40.00	Set temporary $1/4$ sec. cor-
80.26	Intersect N. edge of Tp. 18 also N. of cor to secs. 5, 6, 31 and 32, Thence 9 mi S 0° 5' W. on a true line bet. secs. 5 and 6. Var. 130° 45' East. over mountains heavily timbered land.
7.00	Descent 300 ft.
21.40	Bed canon, course S. W. and ascent 250 ft.
33.00	Top of ridge, course E and W. Descent 150 ft.
39.00	N. edge of deep, canon, with perpendicular rocky sides, descent 150 ft.
40.26	Bed of canon, course W.

Subdivisions

chs Note - It is impossible
to set a corner in this
cañon, therefore,
ascend 150 ft. to

43.00 Set a limestone $18 \times 10 \times$
9 ins. 12 ins. in the
ground for witness cor
to $\frac{1}{4}$ sec. cor. marker
N.C. $\frac{1}{4}$ on N. face, and
raise a monument of stone
 $1\frac{1}{2}$ ft high, 3 ft base,
along side, from which
a Pine 13 ins. diam base
S. $22^{\circ} 11' W.$ 110 lbs. dist.
marker N.C. $\frac{1}{4}$ S.B.T.
a Pine 16 ins. diam base
N. 112 lbs. dist. marker
N.C. $\frac{1}{4}$ S.B.T.
ascend 100 ft.

T. 23 N. R. 5 E. (cont)

cha

51.00 Top of ridge, course E and
W, and descent 150 ft.

72.60 Leave heavily timbered land,
enter open park

80.26 Foot of descent. The cor. to
secs. 5, 6, 7 and 8,

Land, mountainous.

Soil, stony, 3^d rate.

Timber, pine, fir and
aspen, and juniper bush.
Mountainous or heavily
timbered land, 80.26 chs.

June 5, 1894.

General Description.

The northern portion of
this township is broken
and mountainous, forming
a part of Kendrick Peak;

Subs. T. 23 N. R. 5 E (contd)

cls the southern and eastern parts are rolling and more open in character, but nearly all of the township is covered with a heavy growth of merchantable pine and fir timber. Grass grows abundantly during the rainy seasons.

There is one settler in Section 22

Charles E. Perkins
Compassman^{and}
U.S. Deputy Surveyor

U. S. Surveyor-General's Office,

TUCSON, A. T., July 13, 1895.

The foregoing Field Notes of the Surveys of
the Subdivisions of
Tp: 23 N. R 5 E.

Gila and Salt River Meridian
in Arizona executed by
F. W. Oury

U. S. Deputy Surveyor, under his contract dated
June 21st 1893
having been critically examined, the necessary correc-
tions and explanations made, the said Field Notes and
the surveys they describe are hereby approved.

Geo. A. Manning

U. S. Surveyor-General
for the Territory of Arizona.