

2

No. 484

BOOK 484

4-671

484

FIELD NOTES

GENERAL LAND OFFICE.

*subdivision*

*Township 24 N. R. 5. E*

64

Indexed Book 483

Township 24N R. SE

6	5	107	4	80	3	2	1	
			105	78				
7	8	103	9	76	10	11	12	
			101	73				
18	17	98	16	70	15	14	13	
			96	68				
19	126	20	93	21	66	22	23	24
123		121		90		65		
30	117	29	87	28	27	26	25	
114		112		85				
31	109	32	82	33	34	35	36	

## Subdivisions T. 24 N. R. 5 E

Chs. 780 15' W. 11 lbs. dist. marked  
14 S.B.T.

a pine 18 ins diam. tree.

N. 81° W. 9 lbs. dist. marked

14 S.B.T.

43.00 Foot of descent.

ascent 100 ft.

49.00 Top of ascent.

Descent 80 ft.

67.45 Ravine, 3 ft. deep, course N.

68.00 Foot of descent.

75.00 Ravine, 15 ft deep, course N.

79.85 The cor. to sec's 21, 22, 27 and  
28.

Land, broken.

Soil, rocky, & thrate.

Timber, pine and fir.

Heavily timbered land 79.85 chs

## Subdivisions

- Chs. N. 00 2' W.  
 bet. secs. 21 and 22.  
 Var. 15° 38' East.
- over broken land,  
 through timber,
- 19.00 ascent 65 ft
- 32.00 Top of ascent thence  
 along E slope of hill
- 40.00 a malpais rock in  
 place 5 x 4 x 3 feet above  
 ground, which I mark  
 with a cross (+) at  
 exact cor. point for  
 1/4 sec cor. with 1/4 on  
 W. face, and raised a  
 mound of stone 1/2 ft.  
 high, 2 ft. base, along-  
 side, from which  
 a pine 8 ins. diam. has

T. 24 N. R. 5 E. (contd)

Shs. S  $79^{\circ}30'$  E 65 lks. dist.  
marked  $\frac{1}{4}$  S.C.T.

a pine 6 mis. diam. hrs.

N.  $86^{\circ}$  W. 71 lks. dist.

marked  $\frac{1}{4}$  S.C.T.

80.00 Set a malpais stone  $18 \times$

$16 \times 12$  mis. 12 mis. in the  
ground for cor to see.

15, 16, 21 and 22, marked  
with 3 notches on S and  
E. edges, and raised a

monument of stone  $1\frac{1}{2}$  ft.  
high, 2 ft. base, along side  
from which

a pine 14 mis. diam. hrs.

N.  $20^{\circ}30'$  E. 31 lks. dist.

marked T. 24 N. R. 5 E. S. 15 B.T.

a pine 16 mis. diam. hrs.

S  $90^{\circ}45'$  E. 68 lks. dist.

## Subdivisions

Chs.

marked T. 24 N. R. 5 E. S. 22 B.T.

a pine 18 ins. diam chs

S. 17 1/2' N. 18 lbs. dist.

marked, T. 24 N. R. 5 E. S. 21 B.T.

a pine 14 ins. diam. chs.

N. 89° 15' W. 73 lbs. dist.

marked T. 24 N. R. 5 E. S. 16 B.T.

Land, rolling.

Soil, rocky, 4 strata.

Timber, pine.

Heavily timbered land

50 chs.

N. 89° 53' E. on a random line  
bet sees 15 and 22.

Var. 15° 30' East.

40.00

Get temporary 1/4 sec. cor.

79.90

Intersect Rand B line

16 chs. S. of cor to sees.

T. 24 N. R. 5 E. (contd)

Chs. 14, 15, 22 and 23.

Thence I run

S.  $89^{\circ}46'$  W. on a true line

bet sees. 15 and 22.

Var.  $15^{\circ}30'$  East.over rolling land through  
timber.

16.45 Ramble, 3 ft. deep, course N.

38.00 Ramble, 4 ft. deep, course N.

39.95 Get a malpais stone  $15 \times 12 \times 12$  mis. 12 mis in the ground for  $\frac{1}{4}$  see in marker  $\frac{1}{4}$  on N. face and raised a mound of stone  $1\frac{1}{2}$  ft. high, 2 ft base, alongside, from which a pine 36 mis. diam. has N.  $130^{\circ}30'$  W. 61 chs. dist. marker  $\frac{1}{4}$  S.B.T. a pine 40 mis. diam. has

## Subdivisions

Chs.	S 71° 15' E. 57 lks. dist. marked 1/4 k. B.T.
58.00	ascend 200 ft.
79.00	Top of ascent
79.90	The cor to secs. 15, 16, 21, and 22.
	Land, rolling and broken. Soil, rocky, 4th rate. Timber, pine. Heavily timbered land, 79.90 chs.

---

N. 0° 2' W. bet. secs. 15 and 16

Var. 15° 38' East.

	over broken land along E. slope of hill
13.00	ascend 60 ft.
19.00	Top of ascent and descent 150 ft.



## T 24 N. R. 5 E. (contd)

chs.

40.00

Set a malpais stone 20" x 14 x 10 ins. 15 ins. in the ground for  $\frac{1}{4}$  sec. corner - marked  $\frac{1}{4}$  on W. face, and raised a mound of stone  $1\frac{1}{2}$  ft high, 2 ft base, alongside, from which

a pine 14 ins. diam. hrs. N.  $70^{\circ}15'$  E. 19 lbs dist. marked  $\frac{1}{4}$  E.B.T.

a pine 12 ins. diam. hrs. S  $130^{\circ}45'$  E. 23 lbs dist. marked  $\frac{1}{4}$  E.B.T.

42.90

Foot of descent - ascent 80 ft.

64.00

Top of ascent.  
Ridge, course E and W.  
Thence along ridge

## Subdivisions

Obs.

80.00

Get a sand stone 19 x 14 x  
 11 ins. 12 ins. in the  
 ground for cor. to secos.  
 9, 10, 15 and 16, marked  
 with 4 notches on S  
 and 3 notches on E. edge  
 and raised a mound of  
 stone 1 1/2 ft high, 2 ft  
 base, alongside,  
 from which  
 a pine 16 ins. diam. has  
 N. 37° 15' E. 100 lbs. dist.  
 marked T. 24 N. R. 5 E. S. 10-D.T.  
 a pine 12 ins. diam. has  
 S 72° 30' E. 47 lbs. dist.  
 marked T. 24 N. R. 5 E. S. 15-D.T.  
 a pine 14 ins. diam. has  
 S 87° 30' W. 73 lbs. dist.  
 marked T. 24 N. R. 5 E. S. 16-D.T.

T. 24 N. R. 5 E. (cont'd)

Obs.

a fine 12 mile diam. hole.

S.  $45^{\circ} 45'$  N. 102 chs. dist.

marked T. 24 N. R. 5 E. S. 16 - P. T.

Land, broken.

Soil, rocky, 4<sup>th</sup> rate.

Heavily timbered land 80 chs.

at this cor. I verify the  
adjustments of the transit  
and find them correct.

I then set off  $27^{\circ} 52' 00''$  N.  
on the decl. arc, and at  
12<sup>h</sup> 01<sup>m</sup> p.m. L.M.T. observe  
the Sun on the meridian  
the resulting latitude is  
 $35^{\circ} 27' N.$ , the true latitude  
nearly.

N.  $89^{\circ} 46'$  E. on a random line

## Subdivisions

- |       |   |
|-------|---|
| Chs.  | bet. secs 10 and 15.<br>Var. $15^{\circ}38'$ East.  |
| 40.00 | Set temporary $\frac{1}{4}$ sec. cor.   |
| 79.82 | Intersect N and S line<br>21 lks N of cor. to secs.<br>10, 11, 14 and 15.<br>Thence I run<br>S. $89^{\circ}55'$ W. on a true line<br>bet secs. 10 and 15.<br>Var. $15^{\circ}38'$ East.<br>over rolling land. |
| 2.09  | Road, bet. N.W. and S.E.  |
| 8.00  | Descent 20 ft.  |
| 9.00  | Foot of descent, ravine<br>3 ft deep, course N.W.   |
| 27.00 | Descent 35 ft.  |
| 33.00 | Foot of descent   |
| 39.91 | Get a malpais stone 18"<br>14 x 10 ins. 12 ins. in  |

## T24 N.R. 5 E. (cont'd)

Obs. the ground for  $\frac{1}{4}$  sec. sur-  
 marked  $\frac{1}{4}$  on N face, and  
 raised a mound of stone  
 $\frac{1}{2}$  ft high, 2 ft base along-  
 side, from which  
 a juniper 40 ins. diam.  
 hrs. N.  $73^{\circ}$  E. 165 lbs. dist.  
 marked  $\frac{1}{4}$  S.D.T.

a pine 16 ins. diam. hrs.  
 S.  $67^{\circ} 45'$  W. 212 lbs. dist.  
 marked  $\frac{1}{4}$  S.D.T.

~~a pine 16 ins. diam. hrs.  
 S.  $67^{\circ} 45'$  W. 212 lbs. dist.  
 marked  $\frac{1}{4}$  S.D.T.~~

57.00 Descent 65 ft.  
 54.00 Ravine, 20 ft. deep, course N.  
 56.00 ascent 100 ft.  
 65.45 Top of ascent.  
 Descent 85 ft.

## Subdivisions

Chs.

72.50

Foot of descent.

ascend 100 ft.

79.82

The cor. to secs. 9, 10, 15 and  
16.

Land, rolling and broken.

Soil, rocky, 4th rate.

Timber, pine.

---

N. 0° 2' W. bet. secs. 9 and 10.

Var. 15° 38' East

Over mountainous land

Descent 150 ft.

12.00

Foot of descent.

Ravine, 5 ft. deep, course

N.W.

ascend 80 ft.

17.00

Top of ascent, ridge,

course E and W.

Descent 100 ft.

T. 24 N. R. 5 E. (cont'd)

Chs.	
28.00	Foot of descent, thence over rolling land.
40.00	Set a sand stone $20 \times 14 \times 9$ ins. 15 ins. in the ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on W. face, and raised a mound of stone $\frac{1}{2}$ ft. high, 2 ft. base, alongside, from which a pine 16 ins diam. has N. $47^{\circ} 15'$ W. 62 lks dist. marked $\frac{1}{4}$ S.B.T.
	a pine 22 ins. diam. has N. $29^{\circ} 30'$ E. 41 lks. dist. marked $\frac{1}{4}$ S.B.T.
61.00	Leave heavy timber, enter small scattering pine
71.00	Road, course E and W.
80.00	Set a malpais stone 18x

## Subdivisions

Chs. 14 x 12 rods, 12 rods. in the ground for cor. to sec.  
 3, 4, 9 and 10, marked with 5 notches on S. and 3 notches on E. edges, dug pits 10 x 15 x 12 in in each cor. 5 1/2 ft. dist. and raised a mound of earth 2 ft high, 4 1/2 ft. base, along side.  
 Land, mountainous and rolling.  
 Soil, rocky <sup>2 1/2</sup> 4 ch rate.  
 Timber, pine.  
 Heavily timbered land  
 61 chs.

N. 89° 55' E. on a random line  
 bet sec. 3 and 10.

Var. 15° 38' East.



## T24 N. R. 5 E (cont'd)

40.00	Get temporary 1/4 sec. cor.
79.80	Intersect N. and S. line 16 lks. N. of cor. to secs. 2, 3, 10 and 11. Thence I run N. $89^{\circ}58'$ W. on a true line bet secs. 3 and 10. Var. $15^{\circ}35'$ East Over mountainous land. ascend 150 ft.
5.00	Top of ascent. Descent 300 ft.
32.00	Foot of descent. Thence on, <sup>rallying</sup> nearly level land.
39.33	Road course N. W. & S. E.
39.90	Get a malpais stone 207 16 x 12 ins. 15 ins. in the ground for 1/4 sec cor

## Subdivisions

- Chs. marked  $\frac{1}{4}$  on N. face,  
 dug pits  $1.5 \times 1.8 \times 1.2$  nis.  
 E. and W. of stone  $5 \frac{1}{2}$   
 ft. dist. and raised a  
 mound of stone covered  
 with earth  $1 \frac{1}{2}$  ft. high  
 $3 \frac{1}{2}$  ft. base, along side.
- 79.80 The cor to secs. 3, 4, 9 and 10.  
 Land, mountainous and  
 rolling.  
 Rail. stony, 30 rate.  
 Timber scattering pine and fir on  
 mountainous land 32 chs.
- 
- N.  $0^{\circ} 2'$  W. bet. secs. 3 and 4.  
 Var.  $15^{\circ} 30'$  East.  
 even gently rolling land.
- 40.00 Get a malpais stone  
 $1.5 \times 1.4 \times 1.2$  nis. 10 nis in

T. 24 N. R. 5 East. Contd

Shs

the ground for  $\frac{1}{4}$  sec. cor.  
marked  $\frac{1}{4}$  on W. face,  
and raised a mound  
of stone  $1\frac{1}{2}$  ft high, 2 ft  
base, along side, Pitt's  
impracticable

61. 31

I intersect the Birch Stand-  
and Parallel North at  
a point 10.60 chs S.  $89^{\circ}37'$  E. of  
the standard  $\frac{1}{4}$  sec. cor. on  
the S. ldy of sec. 33 T.  
25 N. R. 5 E. at which point  
I set a malpais stone  $15 \times$   
 $14 \times 10$  ins. 12 ins in the  
ground for closing cor-  
to secs. 3 and 4, marked  
C. C. on S. with 3 notches  
on E. and W. faces, and  
raised a mound of stone

## Subdivisions

Chs. 1 1/2 ft. high, 2 ft. base,  
alongside. Pits unprac-  
ticable.

Land, rolling; Soil, stony, ~~not~~ No timber.

June 9<sup>th</sup>, 1894.

From the cor. to secs

4, 5, 32 and 33, on the  
S. hdy of the Tp. as herein-  
before described

From

N. 0° 2' W. bet. secs. 32 and 33.

Var. 15° 38' East.

Over mountainous land,  
through dense aspen  
bush

ascend 300 ft.

22.00

Top of ascent.

Descend 300 ft.

40.00

Get a sandstone 18 x 14 x 10

## T 24 N. R. 5 E. (contd)

- Shs. 12 ins. in the ground  
for  $\frac{1}{4}$  sec. cor. marked  $\frac{1}{4}$   
on W. face, and raised a  
mound of stone  $1\frac{1}{2}$  ft.  
high, 2 ft. base, alongside  
from which  
a fir 6 ins. diam. hrs. S.  
67° 45' W. 28 lbs. dist. marked  
 $\frac{1}{4}$  S. B. T.
- An aspen 6 ins. diam. hrs  
N. 44° 30' E. 4 lbs. dist. marked  
 $\frac{1}{4}$  S. B. T.
- 40.50 Ravine, 10 ft. deep, course W.
- 48.00 Ravine, 12 ft. deep, course W.  
Leave dense brush, enter  
heavy timber.
- 78.00 Foot of descent.
- 80.00 Get a sandstone  $16 \times 12 \times 10$   
ins. 8 ins. in the ground

## Subdivisions

- Chs. for cor. to sees. 28, 29, 32  
and 33, marked with 1  
notch on S and 4 notches  
on E. edges, and raised  
a mound of stone  $1\frac{1}{2}$  ft.  
high, 2 ft. base, along  
side, from which  
a pine 10 ins. diam. has  
N.  $77^{\circ}$  E. 73 lks. dist. marked  
T. 24 N. R. 5 E. S. 28 B.T.
- a pine 10 ins. diam. has  
S  $63^{\circ}$  E. 111 lks. dist. marked  
T. 24 N. R. 5 E. S. 33 B.T.
- a pine 6 ins. diam. has  
S  $71^{\circ} 30'$  W. 112 lks. dist.  
marked T. 24 N. R. 5 E. S. 32 B.T.
- a pine 34 ins. diam. has  
N.  $32^{\circ} 15'$  W. 28 lks. dist.  
marked T. 24 N. R. 5 E. S. 29 B.T.

## T 24 N. R. 5 E. (contd)

chs. Land, mountainous.  
Soil, rocky, 4<sup>th</sup> rate  
Timber, some scattering  
pine,  
mountainous or heavily  
timbered land 80 chs.

---

East on a random line  
bet secs. 28 and 33.

Var.  $15^{\circ}38'$  East.

40.00 Set temporary 1/4 sec cor

79.85 Intersect Kant S. line  
15 chs. S. of cor to secs.

27, 28, 33 and 34.

Thence 9 run

S.  $89^{\circ}54'$  W. on a true line  
bet secs. 28 and 33.

Var.  $15^{\circ}38'$  East.

Over rolling land, through

## Subdivisions

Chs.	Timber.
6.00	Descent 160 ft.
39.92	<p>a malpais rock in place 2x1x1 ft. above ground which I mark with a cross (+) at exact cor. point for <math>\frac{1}{4}</math> sec. cor. with <math>\frac{1}{4}</math> on N. face, and raise a mound of stone <math>1\frac{1}{2}</math> ft. high, 2 ft base, alongside, from which</p> <p>a pine 6 ins. diam. has <math>S 86^{\circ} W. 27</math> lks. dist. marked <math>\frac{1}{4}</math> S.B.T.</p> <p>a pine 8 ins. diam. has <math>S 27^{\circ} 30' E. 38</math> lks. dist. marked <math>\frac{1}{4}</math> S.B.T.</p>
43.00	Foot of descent.



T. 24 N. R. 5 E. (cont'd)

0.00	Leave timber, enter open park.
50.00	ascend 150 ft. Leave park enter scat- tering pine
64.45	Top of ridge, course N. and S.
	Enter heavy timber - Descent 65 ft.
69.00	Foot of descent
76.00	ascend 40 ft.
79.85	Therco. to secs. 28, 29, 32 and 33.
	Land, rolling Soil, 3 <sup>rd</sup> rate. Timber, pine. Heavily timbered land 58.20 chs
	<hr/> N. 002' W. bet. secs. 28 and 29.

## Intermissions

- |       |   |
|-------|---|
| chs.  | Var. $150^{\circ} 38'$ East<br>over rolling land.<br>ascend 30 ft.  |
| 3.00  | Top of ascent.  |
| 16.00 | Road to Munderbach's<br>ranch, course SW & NE.<br>ascend 200 ft.  |
| 34.00 | Top of ascent.<br>Descend 150 ft.   |
| 40.00 | Get a sandstone $16 \times 14 \times$<br>$10$ ins. $11$ ins. in the<br>ground for $\frac{1}{4}$ sec. cor.<br>marked $\frac{1}{4}$ on W. face, and<br>raised a mound of stone<br>$1\frac{1}{2}$ ft high, 2 ft. base,<br>alongside, from which<br>a pile 36 ins. diam. has<br>N. $86^{\circ}$ W. $75$ lbs. dist. marked<br>$\frac{1}{4}$ B.B.T. |

## T. 24 N. R. 5 E. (cont'd)

- lbs. a pine 20 ins. diam. hrs.  
S.  $67^{\circ}30'$  E. 93 lbs. dist.  
marked  $\frac{1}{4}$  S.B.T.
- 69.00 Foot of descent
- 73.00 Enter heavy timber
- 80.00 Set a malpais stone  $20 \times$   
 $16 \times 12$  ins. 15 ins. in the  
ground for cor to sec  
20, 21, 28 and 29, marked  
with 2 notches on S.  
and 4 notches on E. edges  
dug pits  $18 \times 18 \times 12$  ins  
in each sec.  $5\frac{1}{2}$  ft. dist.  
and raised a mound of  
earth 2 ft. high,  $4\frac{1}{2}$  ft  
base, alongside, from  
which  
a pine 6 ins. diam. hrs.  
N.  $44^{\circ}45'$  E. 62 lbs. marked

## Subdivisions

Obs.

T. 24 N. R. 5 E. S. 21 - B.T.

a pine 30 mis. diam. hrs.

S. 37° 15' E. 112 lks. dist.

marked T. 24 N. R. 5 E. S. 28 B.T.

a pine 15 mis. diam. hrs.

S. 240, 15' W. 6 lks. dist.

marked T. 24 N. R. 5 E. S. 29 B.T.

a pine 6 mis. diam. hrs.

N. 50, 15' W. 84 lks. dist.

marked T. 24 N. R. 5 E. S. 20 B.T.

Land, rolling.

Soil, alluvial and stony.

20 and 4<sup>th</sup> rate.

Timber, pine.

Heavily timbered land

7 lks.

N. 89° 54' E. on a random line

bet. secs. 21 and 28.

## T. 24 N. R. 5 E. (contd)

Obs.

Var.  $15^{\circ}38'$  East.40.00 Set temporary  $\frac{1}{4}$  sec. cor.79.80 Intersect the N. and S. line  
16 lbs. N. of em to secs.

21, 22, 27 and 28.

Thence I run

N.  $89^{\circ}59'$  W. on a true line  
bet. secs 21 and 28.Var.  $15^{\circ}38'$  East.over rolling land, through  
timber.

5.00 Leave timber

11.00 Enter timber  
ascend 250 ft39.90 Set a malpais stone  $14 \times$   
 $10 \times 10$  ins. 9 ins. in the  
ground for  $\frac{1}{4}$  sec. cor.  
marked  $\frac{1}{4}$  on N. face,  
and raised a mound

## Subdivisions

- Chs. of stone  $1\frac{1}{2}$  ft high, 2 ft base, along side, from which
- a fine 8 mis diam. hrs. N.  $86^{\circ}$  W. 40 lbs. dist. marked  $\frac{1}{4}$  S.B.T.
- a fine 8 mis diam. hrs. S  $21^{\circ}$  W. 37 lbs. dist. marked  $\frac{1}{4}$  S.B.T.
- 43.00 Top of ascent and descent 250 ft.
- 70.00 Foot of descent. Thence on rolling land to
- 79.80 The cor to sees. 20, 21, 28 and 29. Land, rolling and mountainous. Soil, alluvial and stony 20 and 4 ch. rate.

T. 24 N. R. 5 E. (cont'd)

Chs. Timber, pine.  
 maintains a heavy timber  
 belt east, 73. 80 chs.

---

 N. 0° 2' W.

bet secs. 20 and 21.

Var. 15° 38' East.

over rolling land, through  
 timber.

7.00 ascent 30 ft.

10.00 Top of ascent, leave  
 heavy timber.

38.00 ascent 85 ft. gradually.

40.00 Get a malpais stone 17 x  
 14 x 11 ins. 12 ins in the  
 ground for 1/4 sec cor.  
 marked 1/4 on W. face, and  
 raised a mound of stone  
 1 1/2 ft high, 2 ft. base,

## Subdivisions

- Chs. alongside, from which  
a pine 8 ins. diam. hts.  
N.  $66^{\circ}$  W. 40 lbs. dist.  
marked  $\frac{1}{4}$  S.B.T.
- a pine 30 ins diam. hts.  
S.  $71^{\circ}$  E. 51 lbs. dist. marked  
as  $\frac{1}{4}$  S.B.T.
- 66.00 Top of ascent, ridge,  
course N.W. & S.E.  
Descent 100 ft.  
Enter heavy timber.
- 80.00 Get a malpais stone  
20 x 16 x 10 ins. 12 ins. in  
the ground for cor to  
sees. 16, 17, 20 and 21,  
marked with 3 notches  
on S. and 4 notches on  
E. edges, and raised  
a mound of stone  $1\frac{1}{2}$



T 24 N. R. 5 E. (contd)

Chs.

ft. high, 2 ft base, along-  
side, from which

a pine 14 ins. diam. hrs.

N.  $10^{\circ} 30'$  E. 17 lks. dist.

marked T 24 N. R. 5 E. S. 16 B.T.

a pine 18 ins. diam. hrs.

S  $72^{\circ} 45'$  E. 45 lks. dist.

marked T 24 N. R. 5 E. S. 21 B.T.

a pine 14 ins. diam. hrs.

S  $60^{\circ} 30'$  W. 116 lks. dist.

marked T 24 N. R. 5 E. S. 20 B.T.

a pine 14 ins. diam. hrs.

N.  $57^{\circ} 45'$  W. 60 lks. dist.

marked T 24 N. R. 5 E. S. 17 B.T.

Land, rolling.

Soil, alluvial, and stony

2' and 4' rate.

Timber, pine.

Heavily timbered land <sup>24</sup> 34 chs.

## Subdivisions

Chs

June 9, 1894.

S.  $89^{\circ}59'$  E. on a random line  
bet sees. 16 and 21.

Var.  $15^{\circ}38'$  East.

40.00 Set temporary 14 see. cor.

79.75 Intersect N. and S. line  
15 chs S. of cor to sees  
15, 16, 21 and 22,

Thence Drive

S.  $89^{\circ}55'$  W. on a true line  
bet sees. 16 and 21.

Var.  $15^{\circ}38'$  East.

Over mountainous land  
ascend 300 ft.

17.20 at this point an old  
log cabin bet. S. of line  
about 4 chs. dist.

18.00 avoys, 10 ft. deep, course

## T 24 N. R. 5 E. (cont'd)

- | Obs.  | N.  |
|-------|---|
| 39.87 | <p>Set a malpais stone 15 x 14 x 10 ins 10 ins. in the ground for 1/4 sec. cor. marked 1/4 on N. face, and raised a mound of stone 1 1/2 ft high, 2 ft. base, alongside, from which</p> |
|       | <p>a pine 12 ins. diam. hrs. S 73° 45' W. 37 lks. dist. marked 1/4 S.B.T.</p>   |
|       | <p>a pine 6 ins. diam. hrs. N. 60° 30' W. 34 lks. dist. marked 1/4 S.B.T.</p>   |
| 43.00 | <p>Top of ascent, ridge, course N and S. Descent 140 ft.</p>  |
| 72.00 | Foot of descent   |

## Subdivisions

Chs. ascent 100 ft to

79.75 The cor to secs. 16, 17,  
20 and 21.

Land mountainous.

Soil, stony, 4 th rate.

Timber, pine.

mountainous, or heavily

timbered land, 79.75 chs.

N.  $0^{\circ} 2'$  W. bet. secs. 16 and 17.

Var.  $15^{\circ} 38'$  East

Over mountainous land.

Descent gradually 250 ft  
through timber.

40.00 Set a sandstone  $17 \times 14 \times$   
9 ins. 12 ins in the  
ground for  $\frac{1}{4}$  sec. cor.  
marked  $\frac{1}{4}$  on W. face,  
and raised a monument

## T24 N.R. 5 E. (contd)

- Chs. of stone  $1\frac{1}{2}$  ft. high, 2 ft base, alongside, from which
- a pine 8 ins. diam. hrs.  
N.  $61^{\circ}$  E. 67 lks. dist. marked  $\frac{1}{4}$  E.B.T.
- a pine 6 ins. diam hrs.  
N.  $47^{\circ}$  W  $93$  lks. dist. marked  $\frac{1}{4}$  E.B.T.
- 49.00 Foot of descent, ravine 4 ft. deep, course NW. ascends 25 ft.
- 62.00 Top of ascent, and descent 35 ft.
- 71.00 Foot of descent.
- 80.00 Set a sand stone  $16 \times 12 \times 10$  ins. 11 ins in the ground for cor to sus. 8, 9, 16 and mark with 4 notches

## Subdivisions

- Chs. on S. and E. edges, and raised a mound of stone  $1\frac{1}{2}$  ft high, 2 ft. base, alongside, from which a pine 10 mis. diam. has. N.  $37^{\circ} 15'$  E. 46 lbs. dist. marked T. 24 N. R. 5 E. S. 9 B.T.
- a pine 13 mis. diam. has. S.  $73^{\circ} 30'$  E. 116 lbs. dist. marked T. 24 N. R. 5 E. S. 16 B.T.
- a pine 12 mis. diam. has. S.  $60^{\circ} 45'$  W. 19 lbs. dist. marked T. 24 N. R. 5 E. S. 17 B.T.
- a pine 10 mis. diam. has. N.  $64^{\circ} 45'$  W. 82 lbs. dist., marked T. 24 N. R. 5 E. S. 8 B.T.

T. 24 N. R. 5 E. (contd)

Shs. From this cor. a cabin  
 bears N.  $24^{\circ}15'$  W, and  
 a small spring bears N.  $30^{\circ}$   
 $55'$  W, about 7 chs. dist.  
 Land, mountainous.  
 Soil, rocky, 4<sup>th</sup> rate.  
 Timber, pine.  
 mountainous or heavily  
 timbered land, 80 chs.

---

N.  $89^{\circ}55'$  E. on a random line  
 bet sec. 9 and 16.

Var.  $15^{\circ}38'$  East.

40.00 Set temporary N sec. cor.  
 79.90 Intersect N. and S. line 5  
 chs. S. of cor. to sec. 9, 10,  
 15 and 16.

Thence I run

S.  $89^{\circ}53'$  W, on a true line

## Subdivisions

- Chs. bet sees 9 and 16.  
 Var. 15038' East.  
 one broken land.  
 Descent 150 ft.  
 7.00 Foot of descent  
 ascent 175 ft.  
 15.00 Top of ascent.  
 34.00 Descent 100 ft.  
 39.95 Set a limestone 15 x 12 x 9  
 inc 10 inc. in the ground  
 for  $\frac{1}{4}$  sec-co marked  $\frac{1}{4}$   
 on N. face, and raised  
 a mound of stones  $1\frac{1}{2}$   
 ft high, 2 ft. base, along  
 side, from which  
 a pine 8 inc. diam. has  
 N. 47° 30' W. 19 lbs. dist.  
 marked  $\frac{1}{4}$  S.B.T.  
 a pine 30 inc. diam.



## T 24 N. R. 5 E. (cont'd)

chs.	hs. S. 27° W. 85 lks dist. marked 1/4 S.B.T.
42.00	Foot of descent. ascend 100 ft.
51.00	Top of ascent, and descent 150 ft.
64.50	Foot of descent, small ravine, course N.
79.90	The car, to secs. 8, 9, 16 and 17. Land, broken. Soil, rocky, 4th rate. Timber, pine. Heavily timbered land, 79.90 chs.

N. 00 2' W. bet. secs. 8 and 9.

Var. 15° 38' East.

over rolling land, through  
timber.

## Subdivisions

- |       |  |
|-------|--|
| 3.00  | Small ramme, course NE.  |
| 34.00 | Small ramme, course NW.  |
| 40.00 | Get a sand stone $1' 9" \times 14" \times$<br>$10$ ins. $12$ ins in the<br>ground for $\frac{1}{4}$ sec. con.<br>marked $\frac{1}{4}$ on W. face,<br>and raised a mound<br>of stone $1\frac{1}{2}$ ft. high,<br>$2$ ft. base, alongside,<br>from which<br>a pine $36$ ins. diam. has<br>N. $43^\circ$ W. $56$ lks. dist.<br>marked $\frac{1}{4}$ E.B.T.<br>a pine $24$ ins. diam. has<br>N. $29^\circ$ E. $67$ lks. dist.<br>marked $\frac{1}{4}$ E.B.T. |
| 60.00 | Leave timber   |
| 70.15 | Road, course E and W.  |
| 80.00 | Get a malpais stone  |

T 24 N. R 5 E. (contd)

Obs.

17 x 16 x 14 ins 12 ins in  
 the ground for cor to  
 see 4, 5, 8 and 9 marked  
 with 5 notches on S.  
 and 4 notches on E edge  
 and raised a mound of  
 stone 1 1/2 ft high, 2 ft  
 base, alongside. Pits  
 impracticable  
 Land, rolling.  
 Soil, stony, 3' and 4' rate.  
 Timber, scattering pine

---

N. 89° 53' E. on a random line  
 bet. sees. 4 and 9.

Var. 15° 38' East.

40.00 Set temporary 1/4 sec. cor.

79.85 Intersect the N. and S. line

## Subdivisions

Chs. 16 lks. N. of cor. to secs

3, 4, 9 and 10.

Thence I run

west on a true line

bet secs. 4 and 9.

Var.  $15^{\circ} 38'$  East.

evenly rolling land.

39.92 Set a malpais stone

$18 \times 14 \times 11$  ins.  $12$  ins. in

the ground for  $\frac{1}{4}$  sec.

cor. marked  $\frac{1}{4}$  on N.

face, and raised a

mound of stone  $1\frac{1}{2}$  ft.

high, 2 ft. base, along-

side. Pits unprac-

ticable.

79.85 The cor. to secs. 4, 5, 8 and

9.

Land, gently rolling.

T. 24 N. R. 5 E. (contd)

Chs. Soil, stony 2<sup>o</sup> and 3<sup>o</sup> rate.  
No timber.

N. 0° 2' W. bet. secs. 4 and 5.

Var. 15° 38' East.

38.00 One gently rolling land.  
40.00 <sup>Logansburg Williams Cedar Ranch</sup>  
<sup>Course E 4 1/2 W</sup>  
Set a malpais stone 20 x

18 x 16 ins. 15 ins in the  
ground for 1/4 sec cor

marked 1/4 on W. face,  
and raised a mound of  
stone 1 1/2 ft high, 2 ft  
base, alongside, from  
which

a juniper 10 ins diam-  
ber. S. 45° W. 193 lbs.

dist. marked 1/4 G.P.T.

no other trees within limits

6184 Intersect the Sixth Stand.

## Subdivisions

Chs. and Parallel North at  
 a point 11.78 chs.  $N. 89^{\circ} 20' E.$   
 of the Standard  $1/4$  sec.  
 cor. on the S. hdy of  
 sec. 32, T. 25 N. R. 5 E.  
 at which point  
 I set a malpais stone  
 $16 \times 12 \times 10$  ins. 11 ins. in the  
 ground for closing cor.  
 to secs 4 and 5, marked  
 c.c. on S. with 4 notches  
 on E. and 2 notches  
 on W. faces, and raised  
 a mound of stone  
 $1\frac{1}{2}$  ft high, 2 ft. base  
 alongside. Pits im-  
 practicable.  
 Land, gently rolling,  
 Soil, stony, 3' and 4' rate

T24 N.R. 56 Contd

Obs. No timber.

From the cor. to sec.  
56, 31 and 32, on the S.  
bdy of Tp. as hereinbefore  
described

From

N.  $0^{\circ} 3' W.$  bet. sec. 31 and 32.Var.  $15^{\circ} 38' East.$ 

over mountainous land.  
ascend 300 ft.

21.00 Top of ascent, and descent  
250 ft.

40.00 Set a sand stone  $18 \times 12 \times 9$   
ins. 12 ins. in the ground  
for  $\frac{1}{4}$  sec. cor. mark  
off on W. face, and raised  
a mound of stone  $1\frac{1}{2}$   
ft high, 2 ft base, along -

## Subdivisions

- chs. side, from which  
 a pine 8 ins diam. hrs.  
 $S 67^{\circ} E$  19 lbs. dist.  
 marked 74 S.B.T.
- a pine 10 ins diam. hrs.  
 $N. 21^{\circ} W.$  33 lbs. dist.  
 marked 74 S.B.T.
- 46.00 Foot of descent  
 ascent 100 ft.
- 73.00 Top of ascent.  
 Road, course  $N 80^{\circ} W.$  and  
 $S 80^{\circ} E.$
- 79.00 Ravine, 5 ft. deep, course  
 $W.$
- 80.00 Set a sand stone  $18 \times 12 \times$   
 8 ins. 12 ins. in the ground  
 for cor to secs. 29. 30. 31  
 and 32, marked with 1  
 notch on S. and 5 notches



T. 24 N. R. 5 E. (contd)

Shs.

on E. edge, and raises  
a mound of stone  $1\frac{1}{2}$  ft  
high 2 ft base, along-  
side, from which  
a pine 10 ins. diam. has.  
N.  $77^{\circ}$  E. 73 lbs. dist. marker

T. 24 N. R. 5 E. S. 29 - B.T.

a pine 10 ins diam. has.  
S.  $63^{\circ}$  E. 111 lbs. dist marker

T. 24 N. R. 5 E. S. 32 - B.T.

a pine 6 ins diam. has.  
S.  $71^{\circ} 30'$  W. 112 lbs. dist.  
marker T. 24 N. R. 5 E. S. 31 - B.T.

a pine 34 ins diam. has.  
N.  $32^{\circ} 15'$  W. 78 lbs. dist.  
marker T. 24 N. R. 5 E. S. 30 - B.T.

Land, mountainous  
Soil, rocky, 4<sup>th</sup> rate.  
Timber, pine

## Subdivisions

Chs. mountains on Timberus  
land 80 chs.

---

at this cor. I verify the  
adjustments of my instru-  
ment and find them  
correct.

I set off  $23^{\circ} 04' N.$  on  
the decl. arc, and at  
12 h 01 m. p.m. l. in A.  
observe the Sun on  
the meridian, the  
resulting lat. is  $35^{\circ}$   
 $23' N$  the true lat.  
nearly.

---

East. on a random line  
let sec 29 and 32

Var.  $15^{\circ} 38' East$

## T 24 N. R. 5 E. (contd)

40.00	Set temporary $\frac{1}{4}$ sec cor.
79.90	Intersect N and S line 15 chs. S of cor to secs. 28, 29, 32 and 33. Thence I run S $89^{\circ}54'W$ . on a true line bet secs. 29 and 32. Var. $150^{\circ}38'$ East. over broken land, through timber. Descend 60 ft. 5.00 Foot of descent. 31.00 Leave timber 35.85 Road, course N.E. & S.W. 39.95 Set a malpais stone 17x 14x11 ins. 12 in in the ground for $\frac{1}{4}$ sec cor marked $\frac{1}{4}$ on N face, and raised a mound

## Subdivisions

Chs. of staves  $1\frac{1}{2}$  ft high, 2 ft base alongside.

Puto impracticable.

49.00 Descent 300 ft.

72.00 Foot of descent. ravine course NW.

ascend 175 ft.

79.00 Top of ascent.

79.90 The cor. to secs. 29, 30, 31 and 32.

Land broken.

Soil, rocky, 30 rate.

Timber, pine.

mountainous or heavily timbered land, 31 chs.

---

West. on a true line

bet. secs. 30 and 31.

Var.  $15^{\circ} 38'$  East

## T 24 N. R 5 E. (cont'd)

- shs. Over mountains land.  
 Descent 200 ft.  
 13.00 Enter timber.  
 40.00 Get a limestone  $20 \times 18 \times 12$   
 ins. 15 ins. in the ground  
 for  $\frac{1}{4}$  sec. cor. marker  
 $\frac{1}{4}$  on N. face and raise it  
 a mound of stone  $1\frac{1}{2}$   
 ft high, 2 ft. base,  
 alongside. from  
 which  
 a pine 8 ins. diam. has  
 $\text{S } 67^{\circ} 45'$  W. 9 lbs dist.  
 marker  $\frac{1}{4}$  S.B.T.  
 a pine 8 ins. diam. has  
 $\text{S } 61^{\circ} \text{ E. } 63$  lbs. dist.  
 marker  $\frac{1}{4}$  S.B.T.  
 51.00 Foot of descent.  
 65.00 Leave timber.

## Subdivisions

chs.  
68.90

Intersect the N. hdy of  
Tp. 15.00 chs. N. of cor-  
to sees. 25, 30, 31 and 36,  
as heretofore described  
I obliterate all marks  
which refer to surveys  
on the E.

at point of intersection  
I set a sand stone  $20 \times 12 \times$   
9 ins. 15 ins in the  
ground for closing cor.  
to sees 30 and 31, marked  
C.C. on E. with 5 notches  
on N. and 1 notch on  
S faces dug pits  $18 \times 18$   
 $\times 12$  ins. N., S., and E. of  
post,  $5 \frac{1}{2}$  ft. dist. marked  
raised a mound of earth  
2 ft high  $4 \frac{1}{2}$  ft base

T. 24 N. R. 5 E. (contd)

chs.

alongside, from which  
a pine 20 ins. diam. has  
N.  $71^{\circ} 45'$  E. 193 chs. dist.

marked T. 24 N. R. 5 E. S. 30 B. T.

a pine 20 ins. diam. has  
N.  $60^{\circ} 15'$  E. 194 chs. dist.

marked T. 24 N. R. 5 E. S. 30 B. T.

a pine 16 ins. diam. has  
N.  $53^{\circ} 30'$  E. 178 chs. dist.

marked T. 24 N. R. 5 E. S. 30 B. T.

Land, mountainous and  
rolling.

Soil, stony, 2<sup>o</sup> and 4<sup>th</sup> rate.

Timber, pine.

mountainous or heavily  
land 52 chs.

---

N.  $0^{\circ} 3'$  W. bet. secs. 29 and 30.

Var.  $15^{\circ} 38'$  East.

## Subdivisions

- Chs. over broken land.
- 1.45 Descent 150 ft.
- 5.40 Foot of descent, ravine,  
course W.  
ascend 160 ft.
- 8.00 Top of ascent, ridge  
course E and W.  
Descent 100 ft.
- 22.00 Foot of descent, ravine  
6 ft. deep, course S.W.  
ascend 300 ft.
- 40.00 Set a syenite stone  
16 x 14 x 12 ins., 11 ins.  
in the ground for  
1/4 sec. cor. marked 1/4  
on W. face, and raised  
a mound of stone 1 1/2  
ft high, 2 ft. base,  
alongside from which



T. 24 N. R. 5 E. Cont'd

Chs. a pine 9 ins. diam. hro.  
N.  $61^{\circ} 15'$  E. 47 lbs. dist.  
marked 14 B.B.T.

a pine 16 ins. diam. hro.  
S  $79^{\circ}$  W. 63 lbs. dist.  
marked 14 B.B.T.

49.00 Top of ascent.  
Descent 180 ft.

73.00 Foot of descent.

80.00 Set a malpais stone  
17 x 15 x 11 ins. 12 ins.  
in the ground for cor-  
to secs. 19, 20, 29 and 30,  
marked with 2 notches  
on S and 5 notches on  
E. edges, and raised a  
mound of stone  $1\frac{1}{2}$  ft.  
2 ft. base, along side.  
from which

## Subdivisions

- Chs. a pine 16 ins diam. hrs.  
N. 16° 15' E. 93 lbs. dist.  
marked T. 24 N. R. 5 E. S. 20 B.T.
- a pine 14 ins diam. hrs  
S. 42° 30' E. 110 lbs. dist.  
marked T. 24 N. R. 5 E. S. 29 B.T.
- a pine 19 ins diam. hrs  
S. 63° 30' W. 42 lbs. dist.  
marked T. 24 N. R. 5 E. S. 30 B.T.
- a pine 16 ins diam. hrs.  
N. 17° 15' W. 16 lbs. dist.  
marked T. 24 N. R. 5 E. S. 19 B.T.
- Land broken and mountainous.
- Soil, rocky, 4<sup>th</sup> rate.
- Timber, pine.
- mountainous land 71 chs
- June 10, 1894.

T. 24 N. R. 5 E. Cont'd

Chs. N.  $89^{\circ}54'$  E. on a random line  
bet sees. 20 and 29.

Var.  $15^{\circ}38'$  East.

40.00 Set temporary 1/4 sec. cor.

79.87 Intersect N and S. line  
17 lbs. S. of cor to sees.  
20, 21, 28 and 29.

Thence I run

S.  $89^{\circ}47'$  W. on a true line  
bet. sees. 20 and 29.

Var.  $15^{\circ}38'$  East.

Over rolling land, through  
timber.

11.00 ascent 50 ft.

14.00 Top of ascent.

21.00 Leave timber.

35.00 Enter timber

36.00 ascent 75 ft.

39.00 Top of ascent.

## Subdivisions

- Chs.  
39.93 Set a lime stone  $18 \times 12$   
+ 9 ins. 12 ins. in the  
ground for  $\frac{1}{4}$  sec. cor.  
marked  $\frac{1}{4}$  on N. face,  
and raised a mound  
of stone  $1\frac{1}{2}$  ft. high, 2  
ft. base, alongside,  
from which  
a pine 16 ins. diam.  
hrs. S. 480 W. 72 lbs. dist.  
marked  $\frac{1}{4}$  S.B.T.
- a pine 20 ins. diam. hrs  
S. 68° E. 24 lbs. dist. marked  
 $\frac{1}{4}$  S.B.T.
- 41.00 Descent 75 ft.
- 54.00 Foot of descent.
- 57.00 ascent 100 ft.
- 73.00 Top of ascent.  
Leave timber

## T 24 N. R. 5 E. (contd)

chs  
79.87

The cor to secs. 19, 20, 29  
and 30.

Land, rolling.

Soil, stony, 2<sup>o</sup> and 3<sup>o</sup> rate.

Timber, pine.

Heavily timbered land  
59 chs.

West on a true line  
bet secs. 19 and 30.

Var. 15038' East.

Over broken land.

4.00 Descent 500 ft. into  
cañon.

22.00 Bottom of cañon, cause  
b.w.

ascend 500 ft.

29.50 Top of ascent and W. edge  
of cañon, thence on

## Subdivisions

- chs. rolling sand, through  
timber.
- 40.00 Set a limestone  $16 \times 10 \times 8$   
ins. 11 ins in the ground  
for  $\frac{1}{4}$  sec. cor. marker  
 $\frac{1}{4}$  on N. face, and  
raised a mound of  
stone  $1\frac{1}{2}$  ft high, 2 ft  
base, alongside, from  
which  
a pine 8 ins. diam. has  
N.  $71^{\circ}$  W. 43 chs. dist.  
marker  $\frac{1}{4}$  C.B.T.  
a pine 6 ins. diam. has  
N.  $67^{\circ}$  E. 31 chs. dist.  
marker  $\frac{1}{4}$  C.B.T.
- 57.00 Leave timber.
- 68.85 Intersect W. hdy of Sp.  
14.89 chs. N. of en. to

T 24 N. R. 5 E. (contd)

chs.

secs 19, 24, 25 and 30  
 as herein before described.  
 I obliterate all marks  
 which refer to surveys  
 on the E.  
 At the point of intersection  
 I set a sand stone  $20 \times 14$   
 $\times 8$  ins. 15 ins. in the  
 ground for clearing ear  
 to secs 19 and 30, marked  
 C.C. on E. face, with  
 4 notches on N. and 2  
 notches on S. faces,  
 and raised a mound of  
 stone  $1\frac{1}{2}$  ft high, 2 ft  
 base, alongside, from  
 which  
 a pine 20 ins. diam. has  
 N  $23^{\circ} 15'$  E 50 lks dist,

## Subdivisions

chs. marked T. 24 N. R. 5 E. S. 19 S. T.  
 a pine 20 mis. diam. chs.  
 S.  $77^{\circ}30'$  E. 83 chs. dist.  
 marked T. 24 N. R. 5 E. S. 30 S. T.  
 a pine 24 mis. diam. chs.  
 N.  $88^{\circ}15'$  W. 45 chs. dist.  
 marked C. T. 24 N. R. 5 E. S. 19 & 30 S. T.  
 Land mountainous and  
 rolling.  
 Soil, stony, 3<sup>d</sup> and 4<sup>th</sup> rate.  
 Timber, pine.  
 mountainous or heavily  
 timbered land 22 chs.

N.  $0^{\circ}3'$  W. bet. secs. 19 and 20.

Var.  $15^{\circ}38'$  East.

one high rolling land.

40.00 Get a malpais stone

18 x 10 x 8 mis. 12 mis in



T 24 N.R. 5 E. (cont'd)

Chs.

the ground for  $\frac{1}{4}$  sec. con  
marked  $\frac{1}{4}$  on W. face,  
and raised a mound of  
stone  $1\frac{1}{2}$  ft. high, 2 ft.  
base, along side, from  
which

a pine 16 ins. diam. hrs.  
N.  $110^{\circ}$  W. 16 lbs. dist.

marked  $\frac{1}{4}$  B.P.T.

a pine 14 ins. diam. hrs.  
N.  $16^{\circ}$   $45^{\circ}$  E. 19 lbs. dist.

marked  $\frac{1}{4}$  B.P.T.

71.00 Descend 90 ft. through timber

80.00 Set a limestone  $16 \times 14 \times 9$   
ins.  $11$  ins. in the ground  
for con to sec. 17, 18, 19  
and 20, marked with 3  
notches on S and 5 notches  
on E. edges, and raised a

## Subdivisions T24 N. R. 5 E.

Chs.

mass of stone  $1\frac{1}{2}$  ft high,  
2 ft base, alongside,  
from which

a pine 18 ins. diam. has.

N.  $86^{\circ}$  E. 61 lbs. dist. marker

T. 24 N. R. 5 E. S. 17 B.T.

a pine 6 ins. diam. has.

S.  $67^{\circ}$  45' E. 24 lbs. dist.

marker T. 24 N. R. 5 E. S. 20 B.T.

a pine 10 ins. diam. has.

S.  $43^{\circ}$  W. 29 lbs. dist. marker

T. 24 N. R. 5 E. S. 19 B.T.

a pine 19 ins. diam. has.

N.  $37^{\circ}$  30' W. 36 lbs. dist.

marker T. 24 N. R. 5 E. S. 18 B.T.

Land, rolling

Soil, stony. 3<sup>d</sup> rate.

Timber, pine.

Heavily timbered land 9 chs.

Concluded Book 480

BOOK 484