

3.

No. 485.

Subdivision

lines of

T. 24 N. - R. 6 E.

BOOK 485

4-671

FIELD NOTES
GENERAL LAND OFFICE.

485

128

Begin
Indexed Book 486.

Township 24N R. 6E

6	137	5	4	3	2	1
136	134					
7	132	8	9	10	11	12
130	129					
18	17	16	15	14	13	
19	20	21	22	23	24	
30	29	28	27	26	25	
31	32	33	34	35	36	

No. 485 ^{BOOK} 129

485

Subdivisions T. 24 N. R. 6 E. (etc)

Obs. Var. $14^{\circ} 43'$ East.

40.00 Get temporary $\frac{1}{4}$ sec. cor.

80.96 intersect the N and S line

13 lks. N. of cor. to sec.

8, 9, 16 and 17. as herein-
before described.

Thence I run

N. $59^{\circ} 47'$ W. on a true line

bet. sec. 8 and 17.

Var. $14^{\circ} 43'$ East.

over broken land through
timber.

Descent 45 ft.

7.00 Foot of descent.

Ravine 5 ft. deep, course
S.W.

13.00 Leave timber.

36.00 Enter scattering pine.

40.48 Set a malpais stone 17×15

Sub divisions

lbs. ticable.

81.07 The cor. to secs. 7, 8, 17 and
18.
Land, rolling.
Soil, stony, 4th rate.
No timber.

N. 0° 3' W. bet secs. 7 and 8.

Var. 14° 43' East.

even rolling land.

40.00 Set a malpais stone 17.
15 x 12 ins. 12 ins. in the
ground for 1/4 sec cor
marked 1/4 on W. face,
and raised a mound of
stone 1/2 ft. high, with
base, along side. Pits
impracticable.

76.00 Enter scattering pine

T 24 N. R. 6 E. (contd)

lbs.
80.00

Set a sandstone $16 \times 14 \times 9$
 ins. 11 ins. in the ground
 for cor to sec. 5, 6, 7 and
 8, marked with 5 notches
 on S and E. edges, and
 raised a mound of stone
 $1\frac{1}{2}$ ft high, 2 ft. base,
 alongside, from which
 a pine 20 ins. diam. has
 N. 140° E. 76 lbs. dit. marked
 T. 24 N. R. 6 E. S. 5 B.T.

a pine 30 ins. diam. has. S.
 $64^{\circ} 30'$ E. 37 lbs. dit. marked
 T. 24 N. R. 6 E. S. 8 B.T.

a pine 14 ins. diam. has.
 S. $83^{\circ} 45'$ W. 44 lbs. dit.
 marked T. 24 N. R. 6 E. S. 7 B.T.

a pine 6 ins. diam. has.
 N. 46° $15'$ W. 91 lbs. dit.

Subdivision

Chs. marked T. 24 N. R. 6 E. S. 6 B.T.
 Lands, rolling.
 Soil, rocky, 4th rate.
 Timber, some scattering
 pine.

S. $89^{\circ}47'$ E. on a random line
 bet. secs. 5 and 8.

Var. $140^{\circ}43'$ East.

40.00 Set temporary $\frac{1}{4}$ sec. cor.

80.80 Intersect the N. and S.
 line 10 lbs S of cor. to
 secs. 4, 5, 8, and 9.

Thence I run

N. $89^{\circ}55'$ W. on a true line
 bet. secs. 5 and 8.

Var. $140^{\circ}43'$ East.

Over rolling land.

1.00 Descend gradually 75 ft.

T-24 N.R. 6 E. (contd)

- chs.
22.00 Foot of descent.
- 23.00 Ravine 7 ft. deep, course S.
- 40.40 Set a malpais stone $20 \times 16 \times 12$ ins. 15 ins. in the ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on N. face, and raised a mound of stone $1\frac{1}{2}$ ft. high. 2 ft. base, alongside, from which a pine 6 ins. diam. hrs. S 70° E. 47 lbs. dist. marked $\frac{1}{4}$ C.S.T.
- a pine 16 ins. diam. hrs. N. 60° E. 38 lbs. dist. marked $\frac{1}{4}$ C.S.T.
- 41.00 Enter scattering pine.
Descent 70 ft.
- 53.00 Foot of descent.
Ravine 10 ft. deep, course

Subdivisions

Chs.

N. W

ascend 50 ft.

80.80

Top of ascent.

The cor. to secs. 5, 6, 7 and 8.

Land, rolling.

Soil, stony, 3^d rate.

Timber, scattering pine

N. $89^{\circ}55'$ W. on a random line
bet. secs. 6 and 7.

Var. $14043'$ East.40.00 Set temporary $\frac{1}{4}$ sec. cor.80.95 intersect the W. bdy of the
Sp 7 lks. N. of cor to secs.
6, 7 and 12, as heretofore
described.

Thence I run

S. $89^{\circ}58'$ E. on a true line
bet. secs. 6 and 7.

T 24 N. R. 6 E. (contd)

Sho

Var. 14043 East.

over rolling land.

40.95

Set a malpais stone 20 x 18 x 12 ins. 15 ins. in the ground for 1/4 sec. corner marked 1/4 on N. face, and raised a mound of stone 1 1/2 ft. high, 2 ft. base, alongside. Pits impracticable.

80.95

The cor. to secs. 5, 6, 7 and 8. Land, rolling. Soil, rocky, 4th rate. No timber.

N. 003' W. bet. secs. 5 and 6.

Var. 14043 East.

over rolling land.

Dissent 100 ft.

11.00

Foot of descent.

Gibbarivision

- Chs. Ravine, 8 ft. deep, course
N. W.
- Ascend 85 ft.
- 29.00 Top of ascent.
- 40.00 Set a malpais stone 16 x
14 x 10 vis 11 vis. in the
ground for 1/4 sec. cor.
marked 1/4 on W. face,
and raised a mound of
stone 1 1/2 ft high, 2 ft
base, alongside. Pits
impracticable.
- 60.64 Intersect Sixth Standard
and Parallel North at a
point 1070 ch. S 89° 39' E. of
Standard 1/4 sec. cor. on
S. bdy of sec. 31, T. 25 N. R.
6 E., at which point I
set a malpais stone 20 x 1

T24 N.R. 6 E. (contd)

shs. 14x10 mis. 15 mis. in the
ground for clearing cor. to
secs. 5 and 6, marked C.C. on
S. face, with 5 notches on
E. and 1 notch on W. faces,
and raised a mound of
stone $1\frac{1}{2}$ ft. high, 2 ft.
base, alongside. Pits
impracticable.

Land, rolling.

Soil, rocky, 4th rate.

No timber.

June 18th, 1894.

General description.

This T^h. contains nearly
every variety of land, from
level prairie to moun-
tains, and the soil

Sub-division T. 24 N. R. 6 E. (contd)

Chs.

ranges from worthless rock to rich loam.

The soil on the extreme southern portion of the Tp. is a rich black loam, capable of producing abundant crops without irrigation. The soil of the greater portion of the Tp. can be classed as stony, 3rd and 4th rate. About one half of this Township is covered with marketable pine timber.

There is no water in this Township.

Charles E. Perkins

Compassman
U.S. Deputy Surveyor

No. 485

BOOK 485

141

U. S. Surveyor-General's Office,

TUCSON, A. T., July 13th 1895.

The foregoing Field Notes of the Surveys of
the Subdivisions of
Tp: 24 N. R. 6. E.

Gila and Salt River Meridian
in Arizona executed by
F. W. Oury

U. S. Deputy Surveyor, under his contract dated
June 21st 1893
having been critically examined, the necessary correc-
tions and explanations made, the said Field Notes and
the surveys they describe are hereby approved.

Geo. A. Manning
U. S. Surveyor-General
for the Territory of Arizona.