

No. 486

*Subdivision*

*lines of*

T. 24 N. R. 6 E.

BOOK 486

4-671

486

FIELD NOTES  
GENERAL LAND OFFICE.

1  
 BOOK 486 and BOOK 485 and BOOK 484  
 BOOK 487  
*Index*  
 (4-674.)  
 Township 24 N R. 6 E.

6	137	5	105	4	81	3	58	2	32	1
136	134		104		80		56		30	
7	132	8	101	9	78	10	53	11	27	12
130	128		100		77		52		25	
18	127	17	98	16	74	15	49	14	22	13
125	123		96		72		47		20	
19	121	20	94	21	70	22	45	23	17	24
119	117		91		68		43		15	
30	115	29	89	28	65	27	39	26	12	25
112	111		87		63		37		9	
31	107	32	84	33	60	34	34	35	6	36

No. 486

BOOK 486

1A

Field Notes  
of the survey of the  
Subdivision Lines  
of  
Township No. 24 N. R. 6 East.  
of the  
Gila and Salt River Basins and mountain  
in the  
Territory of Arizona  
as surveyed by,  
Francis W. Croy,  
U. S. Deputy Surveyor.  
Charles F. Perkins,  
comparisons by U. S. Deputy Surveyor  
under contract No. 31.  
Dated June 21, 1893.

Survey commences June 18, 1894.  
Survey completed June 18th, 1894.

pp 2+3  
blank

BOOK 486

## Subdivisions

chs. Survey commenced June  
18, 1894, with a W and  
L. E. Gurley Solar transit  
June 14<sup>th</sup> at the cor to Tps.  
23 and 24 N. Rs. 6 and 7 E.  
I verify the adjustments  
of my transit and find  
them correct.

~~I set off  $18^{\circ}46'$  N. on the  
suel. arc, and at 11<sup>56</sup><sup>m</sup>  
a.m. I m. t. observe the  
Sun on the meridian,  
the resulting lat is  $35^{\circ}$   
 $25'$ , the true latitude  
nearly.~~

at 7<sup>h</sup> a.m.

I. m. t. I set off  $35^{\circ}23'$  on  
the lat. arc;  $23^{\circ}15'$  N on the  
suel. arc, and determine

T. 24 N. R. 6 E.

cho a true meridian with  
the solar, the resulting  
mean variation of the needle is  
140° 43' E.

From the Sp. cor.

I run

N. on E. body of sec. 36.

Var. 140° 43' East.

at 40.03 cho. find 1/4 sec. cor.  
3 eko. E. of my line, and at  
79.97 find the cor. to sec.  
25 and 36, 2 eko. W. of my line  
The bearing of the range  
line is, therefore, North,  
agreeing with the field  
notes furnished by the  
Surveyor General.

The S. body of the Sp. bearing  
been recently established by

## Subdivisions

cho. me, the course being  
 N.  $89^{\circ} 57'$  W., and the distance  
 for the first mile being  
 80.89 cho., therefore  
 From the cor. to sec.

1, 2, 35 and 36 on the S.  
 body of the Tp. as herein-  
 before described,

I run

N.  $80^{\circ} 1'$  W. bet secs. 35 and 36.

Var.  $14^{\circ} 43'$  East.

over rolling land, through  
 timber.

12.00 Ravine, 10 ft. deep, course W.

27.00 ascend gradually 85 ft.

40.00. Set a post 3 ft long .3  
 mis square, with marker  
 stone 12 mis. in the  
 ground for  $\frac{1}{4}$  sec. cor.

## T. 24 N. R. 6 E. (cont)

chs marked  $\frac{1}{4}$  S on W. face,  
 dug pits  $18 \times 18 \times 12$  ins. N.  
 and S of post.  $5\frac{1}{2}$  ft.  
 dist. and raised a mound  
 of earth  $1\frac{1}{2}$  ft high,  $3\frac{1}{2}$   
 ft base, around post,  
 from which

a pine 16 ins. diam. has  
 N.  $85^\circ$  W. 47 chs dist.

marked  $\frac{1}{4}$  S. B. T.

a pine 8 ins. diam. has  
 N.  $69^\circ$  E. 97 chs dist. marked  
 $\frac{1}{4}$  S. B. T.

con. on S. slope of a red  
 hill.

58.00 Top of ascent, and descent  
 100 ft.

77.00 Foot of descent.

50.00 Set a post 4 ft long, 4 ins

## Subdivisions

chs. square, with marked  
 stone 12 vis in. the ground  
 for cor to sec. 25, 26, 35  
 and 36, marked  
 T. 24 N. B. 25 on N. E.,  
 R. 6 E. S. 36 on S. E.,  
 S. 35 on S. W. and  
 S. 26 on N. W. faces, with  
 a notch on S. and E. edges  
 dug pits 18 x 18 x 12 vis.  
 in each sec. 5 1/2 ft. dist.  
 and raised a mound of  
 earth 2 ft high, 4 1/2 ft.  
 base, around post,  
 from which  
 a pine 8 vis. diam. has  
 N. 46° 23' W. 13 chs. dist.  
 marked T. 24 N. R. 6 E. S. 26 B. T.  
 a pine 28 vis. diam. has.



24 N.R. 6 E. (cont)

chs. S. 42° 30' W. 96 lbs. dist.  
 marked T. 24 N.R. 6 E. S. 35 B.T.  
 a pine 32 ins. diam. hrs. S.  
 62° E. 97 lbs. dist. marked  
 T. 24 N.R. 6 E. S. 36 B.T.  
 a pine 30 ins. diam. hrs.  
 N. 81° 36' E. 97 lbs. dist. marked  
 T. 24 N.R. 6 E. S. 25 B.T.  
 No other trees within limits  
 land, calling.  
 Soil, alluvial, 2<sup>d</sup> rate.  
 Timber, pine.  
 Heavily timbered land.  
 80 chs.

S. 89° 57' E. on a random line  
 bet sec. 25 and 36.

Var. 140 43 East.

40.00 Set temporary 1/4 sec. cor.

80.90 Interest E body of Sp. 14 lbs

## Subdivisions

- ch<sup>s</sup> N. of cor to sec. 25, 30, 3~~1~~  
and 36, which is a  
post firmly set and properly  
marked and witnessed  
as described in the field  
notes furnished by the  
Surveyor General  
Thence I run  
N.  $89^{\circ}51'$  W. on a true line  
bet. sec. 25 and 36.  
Var.  $14^{\circ}45'$  East.  
ascend 60 ft.  
16.00 Top of ascent, and descend  
150 ft.  
35.00 Foot of descent.  
40.45 Set a post, 3 ft long, 3  
ins. square, with marked  
stone or ins. in the ground  
for  $\frac{1}{4}$  sec. cor. marked  $\frac{1}{4}$  S.

## T. 24 N. R. 6 E. (cont)

chs on N. face, dug pits 18x  
18x 12 ins. E. and W. of  
post 5 1/2 ft. dist, and  
raised a mound of earth  
1 1/2 ft high, 3 1/2 ft base,  
around post from which  
a pine 30 ins diam. has  
I 28° E. 104 lks. dist. marked  
1/4 S.B.T.

a pine 28 ins. diam. has  
N. 67° E. 108 lks. dist  
marked 1/4 S.B.T.

52.00 Leave timber, enter open  
flat.

72.00 Leave flat, enter timber.

80.21 The cor. to secs. 25, 26, 35  
and 36.

Land, 35 chs. hilly, 45 chs.  
level.

## Subdivisions

chs Soil, partly alluvial, 1st  
and 3<sup>d</sup> rate.

Timber, pine  
Heavily timbered land  
90 chs.

N. 0° 1' W. bet. secs. 25 and 26.

Var. 140 43' East.

over rolling land

4000 Set a post 3 ft long  
3 ins. square, with  
marker stone 12 ins  
in the ground for  $\frac{1}{4}$   
sec. cor. marker  $\frac{1}{4}$  from W.  
face, dug pits 10 x 10 x 12  
ins. N. and S. of post.  $5\frac{1}{2}$   
ft dist. and raised a  
mound of earth  $1\frac{1}{2}$  ft  
high.  $3\frac{1}{2}$  ft base, around

## T 24 N. R. 6 E. (cont)

- chs post, from which  
 a pine 16 ins. diam. bro.  
 N. 46° E. 9 lks. dist. marked  
 14 S.B.T.
- a pine 10 ins. diam. bro.  
 S 54° W. 54 lks. dist. marked  
 14 S.B.T.
- 57.00 ascent 160 ft.
- 71.00 Top of ridge, course W.  
 and descent 100 ft. to
- 80.00 Set a post 4 ft. long, 4  
 ins. square, with marked  
 stone 12 ins. in the  
 ground for cor to sec.  
 23, 24, 25 and 26, marked  
 T. 24 N. S. 24 and N. E.  
 R. 6 E. S 25 on S E  
 S 26 on S W., and  
 S 23 on N. W. faces, with

Subdivisions

cho. 2 notches on S and 1 notch on E. edges. dug pits 18 x 18 x 12 ins. in each sec. 5 1/2 ft. dist, and raised a mound of earth 2 ft high, 4 1/2 ft base, around post, from which

a pine 18 ins. diam. bearing N. 63° 61' W. 235 lks. dist. marked T 24 N. R. 6 E S. 23 B.T.

a pine 23 ins. diam. bearing S 11° 30' E. 161 lks. dist. marked T. 24 N. R. 6 E. S. 25 BT

No other trees within limits

Land, mountainous

Soil, rocky, 30 and 4<sup>th</sup> rate.

Timber, pine

T. 24 N. R. 6 E. (cont)

chs. mountainous land, 23 chs.

---

S.  $89^{\circ} 51' E.$  on a random line  
bet sees. 24 and 25.

Var.  $14^{\circ} 43' East.$ 

40.00 Set temporary  $\frac{1}{4}$  sec. cor  
80.85 intersect E. body of Tp. 9 S.  
N. of cor to sees. 19. 24. 25  
and 30, which is a post  
firmly set and properly  
marked and witnessed as  
described in the field  
notes furnished by the  
Surveyor General.

Thence I run

N.  $89^{\circ} 47' W.$  on a true line  
bet sees. 24 and 25.

Var.  $14^{\circ} 43' East.$ 

Over mountainous land.

## Subdivisions

- chs ascent along N. slope of -  
mountain.
- 40.42 Set a post 3 ft. long 3  
ins. square, with marker  
stone 12 ins. in the  
ground for  $\frac{1}{4}$  sec. cor.  
marked  $\frac{1}{4}$  S on N. face,  
dug pits 18 x 18 x 12 ins. <sup>E. N. post</sup>  
5  $\frac{1}{2}$  ft. dist. and raised  
a mound of earth 1  $\frac{1}{2}$  ft.  
high, 3  $\frac{1}{2}$  ft. base, around  
post, from which  
a pine 17 ins. diam. has  
N. 46° 43' E. 63 lks. dist.  
marked  $\frac{1}{4}$  S.O.T.
- a pine 29 ins. diam. has  
S 71° 30' W. 107 lks. dist  
marked  $\frac{1}{4}$  S.O.T.
- 46.00 Top of ascent and



## T. 24 NR 6 E. 3 (cont)

- cho descent 300 ft to  
 80.85 cor to secs. 23, 24, 25 and  
 26.  
 Land mountainous  
 Soil, rocky, 2<sup>d</sup> and 3<sup>d</sup> rate.  
 Timber pine.  
 mountainous or heavily  
 timbered land 80.85 cho.
- 
- N. 001' W. bet. secs. 23 and 24.  
 Var. 140 + 3' East.  
 Over mountainous land.  
 Descent 50 ft.  
 9.00 Foot of descent and  
 ascent 300 ft.  
 40.00 Get a malpais stone 14 x 12  
 x 11 ins. 9 ins in the  
 ground for 1/4 sec. cor.  
 marked 1/4 on W. face,

## Subdivisions

chs

and raised a mound of  
stone  $1\frac{1}{2}$  ft high - 2 ft base,  
alongside, from which  
a pine 8 ins. diam. has  
N.  $61^{\circ}45'$  E. 27 lbs. dist.  
marked  $\frac{1}{4}$  S.B.T.

a pine 6 ins. diam. has  
S  $23^{\circ}30'$  E. 13 lbs. dist.  
marked  $\frac{1}{4}$  S.B.T.

cor. on S slope of  
mountain.

68.00 Top of ascent and descent  
150 ft. to

80.00 Set a malpais stone  $18 \times$   
 $13 \times 9$  ins. 12 ins. in the  
ground for cor to recs.  
13, 14, 23 and 24 marked  
with 3 matches on S.  
and 1 match on E.

## T. 24 N. R. 6 E. (cont)

chs. edge and raised a  
 mound of stone  $1\frac{1}{2}$  ft.  
 high. 2 ft. base, along-  
 side. from which  
 a pine 16 ins. diam. has  
 N.  $40^{\circ} 30'$  W. 64 lks. dist.

marked T. 24 N. R. 6 E. S.  
 14 B.T.

a pine 16 ins. diam. has  
 S  $55^{\circ}$  W. 40 lks. dist. marked  
 T. 24 N. R. 6 E. S. 23 B.T.

a pine 8 ins. diam. has  
 S  $38^{\circ}$  E. 47 lks. dist.

marked T. 24 N. R. 6 E. S. 24 B.T.

a pine 6 ins. diam. has  
 N.  $48^{\circ} 30'$  E. 47 lks. dist.

marked T. 24 N. R. 6 E. S. 13 B.T.

Land, mountainous  
 Soil, rocky, 4th rate.

## Subdivisions

lbs Timber, small scattering  
pine  
mountainous land, 80 lbs.

---

$S 89^{\circ} 47' E.$  on a random line  
bet sees. 13 and 24.

Var.  $140^{\circ} 43' East.$

40.00 Set temporary  $1/4$  sec. cor.

80.92 Intersect E hdy of the  
2<sup>d</sup>. 5 lbs  $S$  of cor to  
sees. 13, 18, 19 and 24,  
which is a post firmly  
set and properly marked  
and witnessed as describ-  
ed in the field notes  
furnished by the Sur-  
veyor General.

Thence I run

$N. 89^{\circ} 49' W.$  on a true line

T. 24 N. R. 6 E. (cont)

Chs. bet secs. 13 and 24.  
 Var. 140 43' East.  
 ascent gradually 125 ft.  
 along N slope of mt.  
 40.46 Set a post 3 ft long, 3  
 ins. square, with marker  
 stone 12 ins. in the  
 ground for  $\frac{1}{4}$  sec. cor-  
 marker  $\frac{1}{4}$  S. on N. face,  
 dug pits 10 x 10 x 12 ins.  
 E and W. of post, 5  $\frac{1}{2}$  ft-  
 dist. and raised a mound  
 of earth 1  $\frac{1}{2}$  ft high, 2  
 ft base, around post,  
 from which  
 a pine 8 ins diam.  
 hrs. N. 61° 45' E. 13 lbs  
 dist. marked  $\frac{1}{4}$  S.B.T.  
 a pine 11 ins. diam.

## Subdivisions

chs	brs. S. $42^{\circ}$ W. 19 lks dist. marker $\frac{1}{4}$ . S.B.T.
47.00	Top of ascent and descent 110 ft. to
80.92	The cor. to secs. 13, 14, 23 and 24.
	Land, mountainous Soil, stony, 20 rate. Timber, pine. mountainous or heavily timbered land, 80.90 chs.
	<hr/>
	N. $0^{\circ}1'$ W. bet. secs. 13 and 14 Var. $14^{\circ}43'$ East. Over mountainous land, Descent 50 ft.
6.00	Ravine 20 ft. deep, course N.E. Ascent 50 ft.
10.00	Top of ascent, and descent

## T. 24 N. R. 6 E. (cont)

- |       |  |
|-------|--|
| chs   | 65 ft.   |
| 13.00 | Foot of descent and ascent, 450 ft. along E slope of mountain  |
| 40.00 | a pine 8 ins diam. which I marked 1/4 S. on W. side for 1/4 sec cor. from which<br>a pine 10 ins diam. has S 16° 47' W. 45 lbs. dist. marked 1/4 S.P.T.<br>a pine 8 ins. diam. has N. 19° W. 27 lbs. dist. marked 1/4 S.P.T.<br>cor. on SW. slope of mountain. |
| 43.00 | Canon 150 ft. deep, course E   |
| 50.00 | Top of ascent and descent.   |

## Subdivisions

chs 250 ft. to

80.00 Get a malpais stone 16 x  
13 x 11 ins. 11 ins in the  
ground for cor. to sec.

" 12, 13 and 14 marked  
with 4 notches on S.  
and 1 notch on E edge  
and raised a mound  
of stone 1/2 ft high. 2 ft  
base, alongside, from  
which

a pine 26 ins. diam. hrs.

S 67° 13' E. 60 lbs dist

marked T. 24 N. R. 6 E. S. 13-BT.

a pine 12 ins. diam. hrs.

S 81° W. 105 lbs. dist

marked T. 24 N. R. 6 E. S. 14-BT.

a pine 14 ins. diam. hrs.

N. 79° 46' W. 70 lbs dist.



T. 24 N. R. 6 E. (cont)

chs. marked T24 N. R. 6 E. S. 11 - D.T.  
 No other trees within limits  
 cor on N. slope of mountain  
 land, mountains.  
 Soil, stony, 2° and 3° rate.  
 Timber, pine.

---

S. 89° 49' E. on a random line  
 bet secs. 12 and 13.

Var. 140 43' East.

40.00 Set Temporary 1/4 sec. cor.

80.80 Intersect E. ldy of the  
 sp. 13 lds. S. of cor. to  
 secs. 7, 12, 13, and 18, which  
 is a post firmly set and  
 properly marked and suit-  
 ness as described in  
 the field notes furnished

## Subdivisions

Chs. by the Surveyor General  
Thence I run

N.  $89^{\circ} 55'$  W. on a true line  
bet secs. 12 and 13.

Var.  $14^{\circ} 43'$  East,  
over rolling land.

31.00 ascend 500 ft.

40.40 Set a malpais stone  $12 \times$   
 $9 \times 8$  ins. 8 ins. in the  
ground for  $\frac{1}{4}$  sec. cor.  
marked  $\frac{1}{4}$  on N. face, and  
raised a mound of stone  
 $1\frac{1}{2}$  ft high, 2 ft base,  
along side. from which  
a pine 30 ins. diam. has,  
 $S 61^{\circ} 09'$  E. 73 lks dist.  
marked  $\frac{1}{4}$  S.B.T.  
a pine 13 ins. diam. has  
N.  $13^{\circ} 31'$  W. 109 lks dist.

Tring 4 N. R. 6 E. (cont)

- chs. marked  $\frac{1}{4}$  E.O.T.
- 80.80 The cor to sees. 11, 12, 13  
and 14.  
Land, 31 chs. level, 49.80 chs  
mountainous.  
Soil, alluvial and rocky  
1st and 4<sup>th</sup> rate.  
Timber, scattering pine,  
mountainous land 49.50  
chs.
- 
- N.  $0^{\circ} 1'$  W. bet. sees. 11 and 12.  
Var. 140 43' East.  
Over broken land.  
Descent 45 ft.
- 1.45 Foot of descent, and ascent  
130 ft.
- 11.00 Top of ascent, and descent  
200 ft.

## Subdivisions

chs

27.00

Foot of descent.

40.00

Get a malpais stone

16 x 14 x 9 ins. 11 ins. in

the ground for  $\frac{1}{4}$  sec.cor. marked  $\frac{1}{4}$  on W face,

and raised a mound of

stone  $1\frac{1}{2}$  ft high. 2 ft base

along side, from which

a pine 13 ins. diam. has

N. 230 31' E. 109 lbs. dist.

marked  $\frac{1}{4}$  S.B.T.

a pinon 9 ins. diam. has

S. 16° 15' W. 187 lbs. dist

marked  $\frac{1}{4}$  S.B.T.

thence descent gradually to

80.00

Get a post 4 ft long 4

ins. square, with marked

stone 12 ins. in the

ground for cor to secs.

## S. 24 N. R. 6 E. (cont)

chs.

1, 2, 11 and 12, marked  
 T. 24 N. S. 1 on N.E.,  
 R. 6 E. S. 12 on S.E.,  
 S. 11 on S.W., and  
 S. 2 on NW. faces, dug  
 pits  $18 \times 18 \times 12$  ins in  
 each sec.  $5\frac{1}{2}$  ft. dist. and  
 raised a mound of earth  
 2 ft high.  $4\frac{1}{2}$  ft base,  
 around post, from  
 which  
 a pine 24 ins. diam. has  
 S.  $52^{\circ} 09'$  E. 80 lks. dist.  
 marked T. 24 N. R. 6 E. S. 12 B.T.  
 a pine 16 ins. diam. has  
 S.  $84^{\circ} 15'$  W. 236 lks. dist  
 marked T. 24 N. R. 6 E. S. 11 B.T.  
 a pine 40 ins. diam. has  
 N.  $20^{\circ} 03'$  E. 75 chs. dist.

## Subdivisions

chs. marked T. 24 N. R. 6 E. S. 1 B.T.  
No other trees within limits  
Land, broken and rolling.

Soil, stony, 3 land 4th rate.  
Timber, scattering pine.

---

S 89° 55' E. on a random line  
bet secs. 1 and 12.

Var. 14° 43' East.

40.00 Set temporary 1/4 sec. cor.

80.83 Intersect E. bdy of Sp. 7 lbs  
S. of cor to secs. 1, 6, 7 and  
12, which is a post  
firmly set and properly  
marked and witnessed  
as described in the

## T. 24 N. R. 6 E. (cont)

chs

field notes furnished by  
the Surveyor General.

Thence I run

N. 89° 58' W. on a true line  
bet. sec. 1 and 2.

Var. 140° 43' East.

over rolling land.

40.41

Set a malpais stone 12 x  
10 x 9 ins. 8 ins. in the  
ground for  $\frac{1}{4}$  sec. cor.  
marked  $\frac{1}{4}$  on N. face,

and raised a mound of  
stone  $\frac{1}{2}$  ft high. 2  
ft base, alongside.

From which

a cedar 8 ins. diam. has

$\angle$  43° 01' W. 27 lbs. dist.  
marked  $\frac{1}{4}$  S.B.T.

a juniper 10 ins. diam. has

## Subdivisions

- In. A  $24^{\circ} 45'$  E. 31 lks. dist.  
 marked  $\frac{1}{4}$  S.B.T.
- 60.21 Road from Flagstaff  
 to Grand Canyon, course  
 N.W. and S.E.
- 80.83 The cor to secs. 1, 2, 11 and  
 12.  
 Land rolling.  
 Soil, stony, 3<sup>d</sup> and 4<sup>th</sup> rate.  
 Timber, pine, cedar and  
 pines.

---

N.  $0^{\circ} 1'$  W. bet. secs. 1 and 2.

Var.  $14^{\circ} 43'$  East.

over rolling land, descend-  
 ing gradually.

- 40.00 Get a malpais stone,  $16 \times 14$   
 $\times 12$  ins. 11 ins. in the  
 ground for  $\frac{1}{4}$  sec. cor.



T. 24 N. R. 6 E. cont'd

chs. marked 14 on W. face,  
and raised a mound of  
stone  $1\frac{1}{2}$  ft. high, 2 ft  
base, alongside. Pits  
impracticable.

59.54

I intersect Sixth Standard  
and Parcel North at a  
point 9.25 chs  $S 89^{\circ}45' E$  of standard  
and  $\frac{1}{4}$  sec. cor. on the S.  
bdy of sec. 35, T. 25 N. R. 6  
E. at which point I  
set a malpais stone  
 $12 \times 10 \times 6$  ins. 8 ins in  
the ground for closing  
cor to secs. 1 and 2,  
marker c.c. on S face,  
with 1 notch on E.  
and 5 notches on W.  
faces, and raised a mound

## Subdivisions -

chs of stone  $1\frac{1}{2}$  ft high  
 2 ft base, along side  
 from which  
 a pine 8 ins. diam. has  
 S  $25^{\circ}45'$  W. 185 lbs dit.  
 marked T. 24 N. R. 6 E. S. 2 B.T.  
 a pine 16 ins diam has S.  
 $2^{\circ}30'$  W. 249 lbs dit.  
 marked T. 24 N. R. 6 E. S. 2 B.T.  
 a pine 24 ins. diam. has N.  
 $40^{\circ}30'$  E. 96 lbs. dit. marked  
 T. 24 N. R. 6 E. C. C. S. 142 B.T.  
 sand, rolling.

Soil, rocky. 4<sup>th</sup> rate.

Timber, Pine  
 June 14, 1894

From the cor to sees  
 2, 3, 34 and 35 on S. body  
 of the Sp.

T. 24 N. R. 6 E. (cont)

- |       |  |
|-------|--|
| 40.00 | <p>Drum<br/> N. 0° 1' W. bet. sec. 34 and 35.<br/> Var. 14° 43' East.<br/> over open level land.<br/> Set a post 3 ft long, 3<br/> ins. square with marked<br/> stone 12 ins in the ground<br/> for 1/4 sec. cor. marked<br/> 1/4 on W. face, dug pits<br/> 15 x 15 x 12 ins. N and S<br/> of post 5 1/2 ft dist and<br/> raised a mound of earth<br/> 1 1/2 ft high, 3 1/2 ft base,<br/> around post.</p> |
| 51.00 | <p>Enter scattering pine<br/> and ascend 200 ft. to</p>  |
| 80.00 | <p>Set a post 4 ft. long, 4<br/> ins square, with marked<br/> stone 12 ins. in the ground</p>  |

## Subdivisions

chs.

for cor. to secs. 26, 27,  
 34 and 35, marked  
 T. 24 N. S. 26 on N E.  
 R. 6 E. S. 35 on S E  
 S. 34 on SW, and  
 S. 27 on N.W. faces, with  
 1 notch on S and 2 notches  
 on E. edges, dug pits 18 x  
 18 x 12 ins. In each sec.  
 5 1/2 ft dist. and raised  
 a mound of earth 1 1/2 ft  
 high, 3 1/2 ft base, around  
 post, from which  
 a pine 10 ins. diam. has  
 N. 60° E. 88 lbs dist.  
 marked T. 24 N. R. 6 E. S. 26 BT.  
 a pine 16 ins diam has  
 S. 21° 09' E. 201 lbs dist.  
 marked T. 24 N. R. 6 E. S. 35 BT.

T. 24 N. R. 6 E. (cont)

chs. a pine 14 ins diam hts.  
 S. 80° 15' W. 40 chs. dist  
 marked T. 24 N. R. 6 E. S. 34 B.T.

a pine 12 ins. diam hts.  
 N. 80° 15' W. 53 chs dist  
 marked T. 24 N. R. 6 E. S. 27 B.T.

Land, level and main-  
 tainable.

Soil, alluvial, and alkali  
 at and 3' rate.

Timber, scattering pine 29  
 chs.

mountainous land 29 chs.

---

S. 89° 57' E. on a random line  
 bet. secs 26 and 35.

Var. 140 43' East.

40.00 Set Temporary 1/4 sec. cor

80.95 Set intersect N. and S. line 5

## Birmingham

40.38

lbs. N of cor. to sec. 25,  
26, 35 and 36.  
Thence I run  
N. 89° 59' W. on a true line  
bet sec. 26 and 35.

Var. 14° 43' East.

8.00

ascend 85 ft. along N.  
slope of mountain

40.47

a pine 30 ins. diam. which  
I marked 1/4 S. on N.  
side, for 1/4 sec. cor.  
from which

a pine 28 ins. diam. has  
S. 27° 31' E. 67 lbs. dist.  
marked 1/4 S.B.T.

a pine 6 ins. diam. has  
N. 11° 07' E. 59 lbs. dist.  
marked 1/4 S.B.T.

40.79

Top of ascent and descent

## Tp. 24 N. R. 6 E. (cont)

chs.	
	65 ft.
54.00	Foot of descent.
61.00	ascend 75 ft.
67.00	Top of ascent and descent 60 ft to
80.95	The cor. to secs. 26, 27, 34 and 35.
	Land, mountainous.
	Soil, stony, 2 <sup>d</sup> and 3 <sup>d</sup> rate.
	Timber, scattering pine.
	mountainous land, 80-95 chs.

N. 0° 1' W. bet secs. 26 and 27.

Var. 140 43' East.

Over broken land.

ascend 50 ft.

6.00 Top of ridge, course E.  
and W.

Descent 200 ft to

## Subdivisions

khs.

11.00 Ravine, 15 ft. deep, course  
N.

ascend ridge, 60 ft high,

19.00 Top of ridge, course  
E and N.

Descent 100 ft.

30.00 Ravine, 12 ft. deep, course  
N. N.

ascend along N. slope of  
a black cinder moun-  
tain, 400 ft.

40.00 Get a post 3 ft. long, 3  
ins. square, with marked  
stone 12 ins. in the  
ground for 1/4 sec. cor.  
marked 1/4 S. on N. face,  
dug pits 18 x 18 x 12 ins.  
N. and S. of post 5 1/2 ft.  
dist. and raised a mound



T 24 N. R. 6 E. (contd)

of earth  $1\frac{1}{2}$  ft high  $3\frac{1}{2}$  ft  
base, around post,  
from which

a pinion 20 ins diam. has  
S. 88° 30' E. 37 lks dist.  
marked  $\frac{1}{4}$  S.B.T.

No other trees within limits  
Cor. on W. slope of mountain  
about  $\frac{1}{4}$  mile from top.

43.00 Top of ascent and descent  
400 ft. to

80.00 Set a malpais stone 16  
 $\times 14 \times 12$  ins. 11 ins in the  
ground for cor to see.  
22, 23, 26 and 27, marked  
with 2 notches on S.  
and E. edges, and  
raised a mound of  
stone  $1\frac{1}{2}$  ft high 2 ft

## Subdivisions

chs. base, alongside, from  
 which

a fir 28 mis. diam. chs.  
 N.  $17^{\circ}31'$  E. 30 lks. dist.  
 marked T. 24 N. R. 6 E. S. 23 B.T.

a fir 16 mis. diam. chs.  
 S.  $6^{\circ}33'$  E. 94 lks. dist.  
 marked T. 24 N. R. 6 E. S. 26 B.T.

a pine 10 mis. diam. chs.  
 S.  $21^{\circ}00'$  W. 73 lks. dist. marked  
 T. 24 N. R. 6 E. S. 27 B.T.

a pine 6 mis. diam.  
 chs. N.  $87^{\circ}15'$  W. 34 lks.  
 dist. marked T. 24 N. R. 6 E.  
 S. 22 B.T.

Land, mountainous and  
 broken.

Soil, stony, 2<sup>d</sup> rate.

Timber, scattering pine

T 24 N. R. 6 E. (contd)

chs. and fir, and pinon  
mountainous land 80 chs.

$S 89^{\circ} 59' E.$  on a random line  
bet. secs. 23 and 26.

Var.  $14^{\circ} 43' East.$

40.00 Set temporary  $\frac{1}{4}$  sec. cor.

50.90 9 intersect N. and S. line

7 chs N. of cor to secs.

23, 24, 25 and 26,

Thence I run

N.  $89^{\circ} 56' W.$  on a true line

bet. secs. 23 and 26.

Var.  $14^{\circ} 43' East.$

over mountainous land.

Descent 30 ft.

4.00 Foot of descent.

30.00 ascent 650 ft.

40.45 Set a malpais stone

## Subdivisions

chs.

11 x 9 x 8 mis. 7 mis. in  
the ground for  $\frac{1}{4}$  sec.  
marked  $\frac{1}{4}$  on N. face,  
and raised a mound  
of stone  $\frac{1}{2}$  ft high, 2  
ft base, alongside  
from which:

a pine 10 mis diam.

Des N.  $63^{\circ} 45'$  N. 67 lks.

dist marked  $\frac{1}{4}$ . B.P.T.

a pine 19 mis diam. chs.

S.  $77^{\circ}$  E. 109 lks. dist.

marked  $\frac{1}{4}$  B.P.T.

car on E. slope of moun-  
tain.

69.00 Top of ascent and des-  
cent 200 ft to

80.90 The car. to secs. 22, 23,  
26, and 27.

## T24 N.R. 6 E. (contd)

Chs.

Land, mountainous  
Soil, rocky, 4<sup>th</sup> rate.  
Timber, pine and fir.  
mountainous or heavily  
timbered land 80.90 chs.

---

N. 00° 1' W. bet. secs. 22 and 23.

Var. 140° 43' East.

Over broken land.

Descent 45 ft.

17.00 Foot of descent

40.00 Set a malpais stone 13x11  
x 9 ins. 8 ins. in the ground  
for 1/4 sec. cor. marked 1/4  
on W. face, and raised a  
mound of stone 1 1/2 ft.  
high, 2 ft. base, along-  
side, from which  
a pine 10 ins. diam. has.

## Subdivisions

- 6hs. S. 43° 31' W. 71 chs dist.  
marked 1/4 S. D. T.  
a pine, 9 ins. diam. hcs.  
S. 21° 17' W. 73 chs. dist.  
marked 1/4 S. D. T.
- 49.00 Descent 200 ft.
- 64.00 Foot of descent, Ravine  
4 ft. deep, course W.
- 69.00 ascent 25 ft.
- 71.00 Top of ascent.
- 80.00 Beta malpais stone  
18 x 16 x 12 ins. 11 ins in  
the ground for cor to  
secs. 14, 15, 22 and 23,  
marked with 3 notches  
on S. and 2 notches on  
E. edges, and raised a  
mound of stone 1 1/2 ft.  
high, 2 ft. base, alongside

## T24 N.R. 6 E. (contd)

chs.

from which

a pine 26 mis. diam. hrs.  
 N. 65° 45' E. 57 lks. dist.

marked T. 24 N. R. 6 E. S. 14 B.T.

a pine 10 mis. diam. hrs.

S. 25° 43' E. 68 lks. dist.

marked T24 N. R. 6 E. S. 23 B.T.

a pine 16 mis. diam. hrs.

S. 13° 17' W. 72 lks. dist.

marked T. 24 N. R. 6 E. S. 22 B.T.

a pine 15 mis. diam. hrs.

N. 52° 41' W. 111 lks. dist.

marked T. 24 N. R. 6 E. S. 15 B.T.

Land, rolling hills.

Soil rocky, 3<sup>d</sup> rate.

Timber, heavy pine.

Heavily timbered land 80 chs.

---

S. 89° 56' E. on a random line

## Subdivisions

- Chs. bet. sees. 14 and 23.  
 Var.  $14^{\circ}43'$  East.
- 40.00 Bet temporary 14 sec. cor.  
 80.85 Intersect N. and S. line  
 of Chs. N. of cor. to sees.  
 13, 14, 23 and 24.  
 Thence I run  
 N.  $89^{\circ}52'$  W. on a true line  
 bet. sees. 14 and 23.  
 Var.  $14^{\circ}43'$  East.  
 Over rolling land,  
 along N. slope of main  
 can.
- 21.00 Descent 60 ft.  
 27.33 Foot of descent.  
 33.00 Ravine, 5 ft. deep, course  
 N. W.
- 40.42 Set a malpais stone  $11 \times$   
 $9 \times 8$  ins.  $7$  ins. in the



T24 N.R. 6 E. Contd

Chs.

ground for  $\frac{1}{4}$  sec. cor.  
 marked  $\frac{1}{4}$  on N face,  
 and raised a mound of  
 stone  $1\frac{1}{2}$  ft. high. 2 ft.  
 base, alongside, from  
 which

a pine 16 ins. diam. bes.  
 N. 61° 30' E. 73 lks. dist.  
 marked  $\frac{1}{4}$  E.B.T.

a pine 23 ins. diam. bes.  
 S. 80° 15' W. 9 lks. dist.  
 marked  $\frac{1}{4}$  S. B.T.

80.85 The cor. to secs. 14, 15, 22  
 and 23.

Land, rolling.

Soil, stony, 3<sup>d</sup> rate.

Timber, small pine.

---

N. 0° 1' W. bet. secs. 14 and 15.

## Subdivisions

Chs.

Var. 140 43' East,

over calling land.

- 40.00 Set a malpais stone  
 13 x 9 x 7 ins. 8 ins. in  
 the ground for 1/4 sec.  
 cor. marked 1/4 on N.  
 face, and raise a  
 mound of stone 1 1/2 ft  
 high. 2 ft. base, along  
 side. from which  
 a pine 20 ins. diam.  
 hrs. S 90 17' E. 42 lbs.  
 dist. marked 1/4 S.B.T.  
 a pine 6 ins. diam. hrs.  
 N. 41 30' E. 118 lbs. dist.  
 marked 1/4 S.B.T.

- 80.00 Set a malpais stone 14 x  
 12 x 10 ins. 9 ins. in  
 the ground for cor to

T. 24 N. R. 6 E. (contd)

Chs.

secs. 10, 11, 14 and 15, marked  
 with 4 notches on S. and  
 2 notches on E. edges and  
 raised a mound of stone  
 1 1/2 ft high, 2 ft base,  
 alongside, from which  
 a pine 20 ins. diam. hrs.  
 N. 76° 31' W. 124 lks. dist.  
 marked T. 24 N. R. 6 E. S. 10 B.T.  
 a pine 21 ins. diam. hrs.  
 S. 31° 29' W. 95 lks. dist.  
 marked T. 24 N. R. 6 E. S. 15 B.T.  
 a pine 24 ins. diam. hrs  
 S. 51° E. 220 lks. dist.  
 marked T. 24 N. R. 6 E. S. 14 B.T.  
 No other trees within limits.  
 Land gently rolling.  
 Soil, stony, 2<sup>d</sup> and 3<sup>d</sup> rate.  
 Timber, scattering pine

## Subdivisions

Chs.  $S. 89^{\circ} 52' E.$  on a random line  
bet. secs. 11 and 14.

Var.  $14^{\circ} 43' East.$

40.00 Set temporary  $\frac{1}{4}$  sec. cor.

80.62 Intersect N. and S. line  
11 lbs S of cor to secs.

11, 12, 13 and 14.

Thence I run

$N. 89^{\circ} 57' W.$  on a true line  
bet. secs. 11 and 14.

Var.  $14^{\circ} 43' East.$

5.25 Over rolling broken land.  
Rauml, 10 ft. deep, course S. W.  
ascend 160 ft.

8.00 Top of ascent, and line  
descends over broken ridges.

35.00 Foot of descent.

40.31 Set a malpais stone

$13 \times 11 \times 7$  ins. 9 ins. in

the ground for  $\frac{1}{4}$  sec.

## T24 N. R. 6 E. (contd)

Chs. cor. marked  $\frac{1}{4}$  on N face,  
and raised a mound of  
stone  $1\frac{1}{2}$  ft high, 2 ft  
base, alongside, from  
which

a pine 20 ins. diam. hrs.  
S  $67^{\circ} 03'$  W. 60 lks. dist.  
marked  $\frac{1}{4}$  S.B.T.

a pine 24 ins. diam.  
hrs. S.  $64^{\circ} 45'$  E. 70 lks. dist.  
marked  $\frac{1}{4}$  S.B.T.

+7.00 Descent 130 ft. to

Fo. B2 The cor. to secs. 10, 11, 14  
and 15.

Land, rolling and broken  
Soil, stony, 2<sup>d</sup> and 3<sup>d</sup> rate.  
Timber, scattering pine

---

N. 00' W bet. secs. 10 and 11.

## Subdivisions

Obs.

Var. 140 43' East.

Over rolling land.

ascend gradually 40 ft.

18.00 Top of ascent.

23.00 Descent 30 ft.

25.00 Foot of descent, and  
ascend 100 ft.37.00 Top of ascent and  
descent 150 ft.

40.00 Get a malpais stone

18 x 15 x 13 ins. 12 ins.

in the ground for 1/4

sec. cor. marked 1/4 on

W. face, and raised a

mound of stone 1/2 ft.

high. 2 ft. base, along

side, from which

a pile 30 ins. diam. lies

S 67° 41' W. 48 lbs. dist.

## T24 N.R. 6 E. (contd)

- lbs. marker 1/4 S. B.T.  
a pine 24 ins. diam. hrs.  
S. 23 01' E. 124 lbs. dist.  
marker 1/4 S.B.T.
- 61.00 Foot of descent
- 80.00 Set a malpais stone 16  
x 11 x 9 ins. 11 ins. in the  
ground for cor. to sec.  
2, 3, 10 and 11, marker with  
5 notches on S. and 2  
notches on E. edge, and  
raise a mound of stone  
1 1/2 ft high, 2 ft base,  
alongside, from which  
a pine 30 ins. diam. hrs.  
N. 14° 5' E. 120 lbs. dist.  
marker T24 N.R. 6 E. S. 2 B.T.  
a pine 30 ins. diam. hrs.  
N 34° 47' W 66 lbs. dist.

## Subdivisions

Chs.

marked T. 24 N. R. 6 E. S. 3 - B.T.

No other trees within limits

Land, rolling,

Soil, stony, 3<sup>d</sup> and 4<sup>th</sup> rate.

Timber, scattering pine

---

 S. 89° 57' E. on a random line  
bet sees. 2 and 11.

Var. 14° 43' East.

40.00 Set temporary 1/4 sec cor.

80.80 Intersect N and S. line.

9 ebs. S. of cor to sees.

1, 2, 11 and 12.

Thence I run

S. 89° 59' W. on a true line.

bet. sees. 2 and 11.

Var. 14° 43' East.

over nearly level land.

40.40 Set a malpais stone 1/4



## T24 N.R. 6 E. (contd)

Obs.  $\times 11 \times 9$  ins. 9 ins in the  
ground for  $\frac{1}{4}$  sec. cor.  
marked  $\frac{1}{4}$  on N. face,  
and raised a mound  
of stone  $1\frac{1}{2}$  ft. high. 2 ft  
base, alongside, from  
which

a pine 11 ins. diam. has  
N.  $61^{\circ} 15'$  E 73 lks. dist.  
marked  $\frac{1}{4}$  B.B.T.

a pinon 8 ins. diam. has  
S.  $33^{\circ} 07'$  W. 107 lks. dist.  
marked  $\frac{1}{4}$  B.B.T.

80.80 The cor. to secs. 2, 3, 10, and 11.

Land, gently rolling.

Soil, stony, 2<sup>o</sup> and 3<sup>o</sup> rate.

Timber, scattering pine  
and pinon

## Subdivisions

- Chd. N. 0° 1' W. bet. secs. 2 and 3.  
 Var. 140 43' East.  
 over mountainous land.  
 ascent 250 ft.
- 38.00 Top of ascent.  
 descent 200 ft.  
 Enter timber
- 40.00 Set a malpais stone 18 x  
 10 x 10 ins. 12 ins. in the  
 ground for 1/4 sec. con  
 marked 1/4 on W. face,  
 and raised a mound  
 of stone 1 1/2 ft. high  
 2 ft base, alongside.  
 from which  
 a pine 30 ins diam has  
 N. 87° 30' W. 63 lbs. dist.  
 marked 1/4 S.B.T.  
 a pine 26 ins. diam

## T24 N.R. 6 E. (contd)

- Chs. 190.5' E. 27 lbs.  
 dist. marked  $\frac{1}{4}$  S.B.T.
- 52.00 Foot of descent  
 ascends 50 ft.
- 55.00 Top of ascent.
- 59.87 Intersect the Sixth Stand-  
 and Parallel North at a  
 point 9.35 chs.  $S 89^{\circ} 45' E$  of the  
 Standard  $\frac{1}{4}$  sec. cor. on E. bdy of sec 34.  
 T. 25 N.R. 6 E., at which  
 point I set a masonry  
 stone  $16 \times 10 \times 9$  ins. 11 ins.  
 in the ground for closing  
 cor. to secs. 2 and 3, marked  
 C.C. on N. face, with  
 2 notches on E. and 4  
 notches on W. faces,  
 and raised a mound of  
 stone  $1\frac{1}{2}$  ft. high, 2 ft

## Subdivisions

Chs.

base, along side, from  
which,

a pine 30 ins. diam. hrs.

S. 60° 45' W. 110 lbs. dist.

marked T. 24 N. R. 6 E. S. 3-B.T.

a pine 24 ins. diam. hrs.

S. 66° 15' E. 75 lbs. dist.

marked T. 24 N. R. 6 E. S. 2-B.T.

a pine 10 ins. diam. hrs.

N. 50° 30' E. 155 lbs. dist.

marked T. 24 N. R. 6 E.

C.C. S. 2 and 3-B.T.

Sands, rolling and  
broken.

Incl. stony, 30 ratt.

Trunk, scattering pine

---

From the cor to see

3, 4, 33 and 34 on S. body

## T24 N. R. 6 E. (contd)

Chs. of the Tp. as hereinbefore described

From

N. 002' W. bet. sec. 33 and 34.

Var. 14043' East

over level land.

40.00 Set a malpais stone 14  
x 12 x 10 ins. 9 ins. in the  
ground for  $\frac{1}{4}$  sec. cor.  
marker  $\frac{1}{4}$  on W. face,  
and raised a mound of  
stone  $1\frac{1}{2}$  ft. high, 2 ft.  
base, alongside. Pits  
impracticable.

50.00 ascent 50 ft.

60.00 Enter pine timber

62.00 Top of ascent.

80.00 Set a malpais stone

20 x 14 x 12 ins. 15 ins. in

## Subdivisions

- Chs. the ground for cor.  
to secs. 27, 28, 33 and  
34, marked with  
notch on S and 3 notches  
on E. edges, and raised  
a mound of stone  $1\frac{1}{2}$   
ft high, 2 ft base,  
along side, from  
which
- a pile 22 ins. diam.  
hrs. N.  $25^{\circ}$ , 5' E. 13 lbs.  
dist. marked T. 24 N.  
R. 6 E. S. 27 B.T.
- a pile 17 ins. diam. hrs.  
S.  $75^{\circ}$  31' E. 53 lbs dist.  
marked T. 24 N. R. 6 E. S. 34 B.T.
- a pile 29 ins. diam. hrs.  
S.  $42^{\circ}$  31' N. 216 lbs. dist.  
marked T. 24 N. R. 6 E. S. 33 B.T.

T 24 N.R. 6 E. (cont'd)

Chs. a pine 29 mis. diam bro. N.  $83^{\circ}$   
 17' W. 84 lbs. drift marker  
 T. 24 N.R. 6 E. S. 28 B.T.  
 Land, level and rolling  
 Soil, alluvial, 1st & 4th rate.  
 Timber, pine.  
 Heavily timbered land, 20 chs.

S.  $89^{\circ} 57'$  E. on a random line  
 bet secs. 27 and 34.

Var.  $14^{\circ} 43'$  East.

40.00 Set temporary  $\frac{1}{4}$  sec. cor.  
 81.00 Intersect N. and S. line 8 lbs  
 S of the cor. To secs. 26, 27,  
 34, and 35.  
 Thence run  
 W. on a true line  
 hit secs. 27 and 34.  
 Var.  $14^{\circ} 43'$  East.

## Subdivisions T24N.R.6 E (cont.)

- Chs. over rolling land.  
Descent 125 ft.
- 39.00 Foot of descent
- 40.50 a pine 34 mis. diam.  
which I marked 14 B.  
on N. face, and raised  
a mound of stone, 2 ft. <sup>3/4</sup> high  
around tree. Pits  
impracticable.  
ascend 40 ft.
- 53.00 Top of ascent, and  
descent gradually 60 ft. to
- 81.00 The cor. to secs. 27, 28, 33  
and 34.  
Land, rolling and broken.  
Soil, stony, 3<sup>d</sup> rate.  
Timber, scattering pine.
- June 15<sup>th</sup>, 1894.



Continued Book 487.  
Concluded Book 485.

BOOK 486