59

Ⅱ

Subdivisions

T. 29 N, R 1 E

Jacobs, D.S.

BOOK 582

4–671

FIELD NOTES

GENERAL LAND OFFICE.

No. 582

60

Indexed, Book 581

Township _29N_ R. _1E_

6 *98*	5 *77*	4 *62*	3	2	1
94	*95*	*74* *61*			
7 *93*	8 *74*	9	10	11	12
92	*91*	*73*			
18 *89*	17 *71*	16	15	14	13
88	*87*	*70*			
19 *85*	20 *69*	21	22	23	24
84	*83*	*67*			
30 *82*	29 *66*	28	27	26	25
81	*79*	*65*			
31 *78*	32 *64*	33	34	35	36

	S. 89° 45' W. on a random line bet. secs. 3 and 10.
40.00	Set temp. 1/4 sec. cor.
80.13	Intersect N. and S. line, 33 lks S of cor. of secs. 2, 3, 10 and 11.
	Thence I run.
	N. 89° 59' W. on a true line bet. secs. 3 and 10.
	Over rough rolling land — Through dense undergrowth. Ascend to mesa.
33.00	Descend.
38.00	Cañon, 150 ft deep. course N. E.
40.06½	Set a sandstone 20×12×4 ins 14 ins in the ground for 1/4 sec. cor marked 1/4 on N. face; raise a mound of stone 2 ft. base 1½ ft. high N. of cor. Pits impracticable.
40.22	Wagon road to Anita Junction bears N. E. and S. W.

62

46.08	Wagon road to Anita Junction bears E. and W.
49.00	Ascend to ridge.
52.00	Top of ridge. 150 ft. high.
54.00	Descent.
59.00	Cañon, 150 ft. deep. curve,
59.00	Road to Anita Junction bears N.E. and S.W.
67.60	Leave cañon, ascend to mesa.
73.50	Top of mesa.
80.13	The cor. of secs. 3, 4, 9, and 10. Land, rolling cut by cañons Soil, 4th rate. Timber cedar and pine Dense undergrowth 80 chs.
	N. 0° 3' W. on a random line bet. secs. 3 and 4.
40.00	Set temp 1/4 sec. cor.
80.50	Intersect N. bdy. of Tp.

24 lks E of cor. of secs. 3,4, 33 and 34.
Thence I run

S. 0° 13' E. on a true line bet.
secs. 3 and 4.

Over ascending land.
heavily timbered

40.50   Set a sandstone 16×16×4 ins.
12 ins in the ground, for 1/4 sec.
cor. marked 1/4 on W. face; from which,

A cedar 8 ins. diam. bears N. 70 1/2
E. 180 lks. dist., marked 1/4 S. 3. B.
T.

A pine 10 ins. diam. bears
N. 58 1/2° W. 87 lks. dist. marked
1/4 S. 4 B. T.

80.50   The cor. of secs. 3, 4, 9 and 10
Land, rolling
Soil, 4th rate.
Timber cedar and pine.
Heavily timbered 80.50 chs.
September 18th 1900

From the S. C. of secs. 32, 33,4
and 5 on S. Bdy. of Tp. which is
a sandstone 6×6×18 ins. above
ground, firmly set, marked
and witnessed as described
by the surveyor general, I run
N. 0°4' W. bet. secs. 32 and 33

Through Over land descending to N.
dense undergrowth.

40.00	Set a limestone 15×12×8 ins

10 ins in the ground for 1/4 sec.
cor. marked 1/4 on W. face; and
raise a mound of stone 2 ft. base
1½ ft. high W. of cor, Pits impracticable

40.20	Wash 15 chs wide bears E and W.
40.88	Road from Grands camp to

Anita Junction bears S.E and N.W.

65.20	Leave Wash brs. E and W.
80.00	Set a limestone 30×14×6 ins.

22 ins. in the ground for cor. of
secs 28, 29, 32 and 33, marked

with 1 notch on S. and 4 notches
on E. edges; and raised a mound
of stone 2 ft. base 1½ ft. high W.
of cor. Pits impracticable.

Land, rolling.

Soil, 2ᵃⁿᵈ and 4ᵗʰ rate.

Timber cedar and pine

Dense undergrowth 80 chs.

_____

E. on a random line bet. secs.
28 and 33.

40.00   Set temp. ¼ sec. cor.

80.19   Intersect N. and S. line, 24 lks
S. of cor. of secs. 27, 28, 33 and 34.

Thence I run

S. 89°50' W. on a true line bet. secs.
28 and 33.

Over rolling land, through
~~Dense undergrowth~~

40.09½   Set a sandstone 18 X 12 X 8 ins. 12
ins. in the ground, for ¼ sec. cor.

marked 1/4 on N. face. from which
a cedar 8 ins. diam. bears
S. 28 1/4° W. 110 lks. dist., marked
1/4 S. 33 B.T. - No more trees within
limits.

Raise a mound of stone 2 ft.
base 1 1/2 ft. high N. of cor.
Pits impracticable.

80.19   The cor. of secs. 28, 29, 32 and 33.
Land, rolling.
Soil, 4th rate.
Timber, cedar and pine.
Dense undergrowth   80.19 chs.

N. 0° 4' W. bet. secs. 28 and 29.
Over rolling land.
heavily Timbered
40.00   Set a limestone 18×16×6 ins.
12 ins in the ground for 1/4 sec.
cor. marked 1/4 on W. face, and
raise a mound of stone. 2 ft.

	base 1½ ft. high W. of cor. Pits
	impracticable. 2nd leave Timber
78.50	Wash. 40 chs. wide, course S.W.
80.00	Set a limestone 18×8×6 ins. 12
	ins. in the ground for cor. of secs.
	20, 21, 28 and 29. marked with
	2 notches on S and 4 notches on
	E. idges; and raise a mound of
	stone 2 ft. base, 1½ ft. high W.
	of cor. Pits impracticable.
	Land, rolling.
	Soil, 4th rate.
	Timber, cedar and pine.
(80)	Heavily timbered 40. chs.

	N. 89°50' E. on a random line
	bet. secs. 21 and 28
40.00	Set temp. ¼ sec. cor.
80.13	Intersect N. and S. line. 17 lks.
	S. of cor. of secs 21, 22, 27 and 28

	Thence I run
	S 89°44' W. on a true line
	bet. secs. 21 and 28.
Through	Over rolling land.
37.56	~~dense undergrowth~~
	Begin descent.
40.06½	Set a sandstone 18×10×6 ins.
	12 ins. in the ground for ¼ sec.
	cor. marked ¼ on N. face. from which
	A cedar 8 ins. diam. bears
	S. 89° E. 218 lks dist. marked
	¼ S. 28 B.T.
	A cedar 12 ins. diam. bears
	N. 76½° E. 272 lks. dist. marked
	¼ S. 21 B.T.
✓ 62.50	Wash course S.W.
80.13	The cor. of secs. 20, 21, 28 and 29.
	Land, rolling.
	Soil, 4th rate.
	Timber, cedar and pine.
	Dense undergrowth 80.13 chs

September 19th 1900.

N. 0° 4' W. bet. secs 20 and 21.

Over rolling land, Through
Dense Undergrowth.

40.00 Set a limestone 20×12×6 ins. 15
ins. in the ground, for 1/4 sec. cor.
marked 1/4 on W. face; dig pits
18×18×12 ins. N. and S. of stone 3 ft.
dist. and raise a mound of earth
3½ ft. base 1½ ft. high W. of cor.

43.00 Leave wash, Begin ascent.

56.60 Road to Anita Junction bears E and W.

80.00 Set a limestone 20× 8×6 ins. 15 ins.
in the ground; for cor. of secs
16, 17, 20 and 21 marked with 3
notches on S and 4 notches on E edges
from which

A pine 12 ins. diam. bears S
74¾° E. 248 lks. dist. marked T. 29
N., R. 1 E., S. 21, B.T.

No more trees within limits.
Raise a mound of stone 2 ft. base,
1½ ft. high N. of cor. Pits impracticable.
Land, rolling.
Soil 2nd and 4th rate.
Timber, cedar and pine.
Dense undergrowth 80 chs.

N. 89°44' E. on a random line
bet. secs. 16 and 21.

40.00	Set temp. ¼ sec. cor.
80.02	Intersect N. and S. line, 1 alks

N. of cor. of secs. 15, 16, 21 and 22.
Thence I run.

S. 89° 47' W. on a true line bet.
secs 16 and 21

crooked	Over rolling land with dense undergrowth
36.60.	Wash 10 chs. wide course S.W.
37.60	Wagon road to Anita Junction

bears N.E. and S.W.

40.01	Set a limestone 22 x 12 x 4 ins 16 ins in the ground, for 1/4 sec. cor. marked 1/4 on N. face, raise a mound of stone 2 ft. base 1½ ft. high N. of cor.
46.60	Leave wash, ascend.
62.00	Top of ridge, descend.
80.02	The cor of secs. 16, 17, 20 and 21. Land, rough and rolling. Soil, 2nd and 4th rate. Timber cedar and pine. Dense undergrowth 80.02 chs.

N. 0°4' W. bet. secs. 16 and 17.

Over ground ascending to N.

Heavily Timbered

30.00	Top of ascent, thence over mesa.
40.00	Set a limestone 24 x 14 x 3 ins 6 ins in the ground to bedrock surrounded by mound of stone fa 1/4 sec. cor. marked 1/4 on N face from which

A cedar 12 ins. diam. bears
S. 79½° E. 86 lks. dist. marked
1/4 S. 16 B.T.

A cedar 16 ins. diam. bears
N. 55° W., 142 lks. dist. marked
1/4 S. 17 B.T.

80.00   Set a limestone 20×6×6 ins 8
ins. in the ground to bedrock sur-
rounded by mound of stone for cor.
of secs. 8, 9, 16 and 17, marked with
4 notches on S. and E. edges from
which.

A cedar 12 ins. diam. bears
N. 27° E. 42 lks. dist. marked
T. 29 N., R. 1 E., S. 9, B.T.

A pine 14 ins. diam. bears
S. 53/4° E., 101 lks. dist. marked
T. 29 N., R. 1 E., S. 16, B.T.

A cedar 10 ins. diam. bears
S. 14½° W. 143 lks. dist. marked

T. 29 N., R. 1 E., S. 17, B.T.

   A cedar 12 ins. diam. bears
N. 87½° W., 144 lks. dist. marked.
   T. 29 N., R. 1 E., S. 8, B.T.
   Land, rolling.
   Soil, rocky 4th rate.
   Timber, cedar and pine.
   Heavily timbered 80 chs.

_____

   N. 89°47′ E. on a random line bet.
secs. 9 and 16.

40.00	Set temp. ¼ sec. cor.
79.92	Intersect N. and S. line, 18 lks

S. of cor. of secs. 9, 10, 15 and 16
   Thence I run,
   S. 89° 39′ W. on a true line bet. secs.
9 and 16, Through dense
Timber
   Over ascending land.

5.00	Leave wash course S.W.
19.00	Top of ascent.
39.96	Set a limestone 20×14×4 ins. 10

ins. in the ground, for 1/4 sec. cor.
marked 1/4 on N. face. from which.

A pine 12 ins. diam. bears
N. 47° E., 160 lks. dist, marked
1/4 S. 9 B.T.

A cedar 16 ins. diam. bears
S. 12 1/2° E. 138 lks. dist masked.
1/4 S. 16 B.T.

50.00	Begin descent.
59.00	Cañon 100 ft. deep course S., ascent
	to mesa.
79.92.	The cor of secs. 8, 9, 16 and 17.

Land rolling.

Soil, rocky 4th rate.

Timber cedar and pine.

Heavily timbered, 79.92 chs.

September 20th 1900

N. 0° 4' W. bet. secs. 8 and 9.
Over rough land descending

northward in
Over heavily Timbered Land.
40.00 Set a limestone 18×16×6 ins 12 ins
in the ground for ¼ sec. cor. marked
¼ on W. face, from which,

A cedar 14 ins. diam. bears S.
27¾° E. 180 lks dist. marked ¼ S.
9 B. T.

A pine 12 ins. diam. bears S.
58¾° W, 185 lks. dist. marked
¼ S. 8 B T.

80.00 Set a limestone 20×10×6 ins 10
ins. in the ground for cor. of secs.
4, 5, 8 and 9 marked with 5 notches
on S and 4 notches on E edges;
dig pits 18×18×12 ins. in each sec.
5½ ft. dist., and raise a mound of
earth 4 ft. base 2 ft. high W. of cor.
Land, rolling.
Soil, rocky 4th rate.
Timber, cedar and pine

	Heavily timbered 80. chs.
✗	
	N. 89° 39' E on a random line
	bet. secs 4 and 9
40.00	Set temp. 1/4 sec. cor.
80.03	Intersect N. and S line 45 lks.
	N. of cor of secs. 3 4, 9 and 10.
	Thence I run
	S. 89° 58' W. on a true line bet.
	secs. 4 and 9.
	~~Heavily Timbered~~ Over rolling land
40.01 1/2	Set a limestone 20x12x6 ins 10
	ins. in the ground for 1/4 sec. cor.
	marked 1/4 on N. face. from which
	A pine 20 ins. diam. bears
	S. 30° W. 227 lks. dist. marked
	1/4 S. 9 B.T.
	A cedar 12 ins. diam. bears
	N. 28 1/4° W. 159 lks. dist. marked
	1/4 S. 4 B.T.

80.03	The cor. of secs. 4, 5, 8 and 9.
	Land, rough and rolling.
	Soil, rocky; 4th. rate.
	Timber, cedar and pine
	Heavily timbered 80.03 chs.

N. 0° 4' W. on a random line bet.
secs. 4 and 5.

40.00	Set temp. 1/4 sec. cor.
80.46	Intersect N. bdy of Tp. 2 lks E.

of cor. of secs. 4, 5, 32, and 33.

Thence I run

S. 0° 5' E. on a true line bet.
secs. 4 and 5.

Over rolling land.

Heavily Timbered	
40.46	Set a limestone 16 x 10 x 6 ins 10

ins. in the ground for 1/4 sec. cor.
marked 1/4 on N. face, from which.

A cedar 6 ins. diam. bears
S. 63° E. 87 lks. dist. marked

¼ S. 4 B.T.

A cedar 8 ins. diam. bears
S. 33° W. 145 lks. dist. marked
¼ S. 5 B.T.

80.46   The cor. of secs. 4 5, 8 and 9.

Land rolling.

Soil, 3rd rate.

Timber, cedar and pine.

Heavily timbered 80.46 chs.

September 21st 1900.

From the S.C. of secs. 31, 32, 5 and
6 on the S. bdy. of Tp. which is a
limestone 5″×8×7 ins. above ground
marked and witnessed as described
by the surveyor general I run
N. 0°5′ W. bet. secs. 31 and 32.

Over rolling land. ——

Through ~~dense undergrowth.~~

40.00   Set a limestone 24×10×8 ins
18 ins in the ground for ¼ sec. cor.

marked 1/4 on W. face. dig pits 18×18×12
ins. N. and S. of stone 3 ft. dist., and
raise a mound of earth, 3½ ft base
1½ ft. high W. of cor.

68.53   Wagon road from Grands camp
to Anita Junction bears E and W.

80.00   Set a limestone 24 × 8×6 ins 18 ins
in the ground for cor. of secs. 29, 30,
31 and 32. marked with 1 notch
on S and 6 notches on E edges; dig
pits 18 × 18 × 12 ins., in each sec. 5½
ft. dist and raise a mound of earth
4 ft. base, 2 ft. high W. of cor.

    Land, rolling.

    Soil, 2nd rate.

    Timber, cedar.

    Dense undergrowth 80 chs.

    E. on a random line bet. secs.
29 and 32.

80

40.00	Set temp. 1/4 sec. cor.
80.06	Intersect N. and S. line at cor. of secs. 28, 29, 32 and 33.
*	Thence I run
	West on a true line bet. secs. 29 and 32.
Through 5.00	Over rolling land. ~~Dense undergrowth~~ Top of S. face of rocky ridge, descent
25.00	Bottom of slope.
40.03	Set a limestone 24 x 12 x 6 ins. 18 ins in the ground, for 1/4 sec. cor. marked 1/4 on N. face; dig pits 18 x 18 x 12 ins. E and W. of stone 3 ft. dist. and raise a mound of earth, 3½ ft. base 1½ ft. high, N. of cor.
80.06	The cor. of secs. 29, 30, 31 and 32.
	Land rolling
	Soil 2nd and 4th rate.
	Timber, cedar.
	Dense undergrowth 80.06 chs.

W. on a random line bet. secs. 30 and 31.

40.00   Set temp. 1/4 sec. cor.

79.89   Intersect Principal Meridian

22 lks S. of cor of secs. 25, 30, 31 and

36. which is a limestone 15 x 13 x 5 ins

above ground marked and witnessed

as described by the surveyor general.

    Thence I run

    S. 89° 51'E. on a true line bet.

Through dense undergrowth

secs. 30 and 31.

39.89   Set a limestone 18 x 10 x 6 ins. 12 ins.

in the ground for 1/4 sec. cor. mark-

ed 1/4 on N. face; dig pits 18 x 18 x 12 ins.

E and W. of stone 3 ft. dist. and

raise a mound of earth 3½ ft base

1½ ft. high N of cor.

79.89   The cor. of secs. 29, 30, 31 and 32.

    Land, rolling.

    Soil, 2nd and 4th rate.

82

Timber, cedar.

Dense undergrowth 79.89 chs.

N. 0° 5' W. bet. secs. 29 and 30.

Over rolling land.

Through ~~Dense undergrowth.~~

22.00 Dim road bears E. and W.

40.00 Set a limestone 18 X 10 X 6 ins. 12 ins. in the ground for 1/4 sec. cor. marked 1/4 on W. face; dig pits 18 x 18 X 12 ins. N. and S. of stone, 3 ft. dist.; and raise a mound of earth, 3 1/2 ft. base 1 1/2 ft. high, W. of cor.

44.00 Ascend a rocky ridge.

48.00 Top of ridge bears N.E. and S.W.

80.00 Set a limestone 20 X 12 X 6 ins. 15 ins. in the ground for cor. of secs. 19, 20, 29 and 30, marked with 2 notches on S. and 5 notches on E edges; dig pits, 18 X 18 X 12 ins. in each sec., 5 1/2 ft. dist.; and raise

a mound of earth 4 ft. base, 2 ft.
high, N. of cor.

Land rolling.

Soil, 2nd and 4th rate.

Timber, cedar.

Dense undergrowth. 80 cha.

September 22nd 1900

_____

E. on a random line bet secs 20 and
29.

40.00   Set temp. 1/4 sec. cor.
80.19   Intersect N. and S. line 38 lks
N. of cor. of secs. 20, 21, 28 and 29.

Thence I run.

N. 89° 44' W. on a true line bet
secs. 20 and 29.

Through   Over rolling land ~~Dense undergrowth.~~
40.09½   Set a limestone 24 × 10 × 6 ins
18 ins in the ground for 1/4 sec.
cor. marked 1/4 on N. face; dig pits

	18×18×12 ins. E. and W. of stone,
	3 ft. dist. and raise a mound
	of earth 3½ ft. base 1½ ft. high
	N. of cor.
45.00	Ascent to rocky ridge.
49.00	Top of ridge bears N. 20° E and
	S. 20 W.
80.19	The cor. of secs. 19, 20, 29 and 30.
	Land, rolling.
	Soil. 2 nd. and 4 th rate.
	Timber, cedar
	Dense undergrowth 80.19 chs.

	N. 89° 51′ W. on a random line
	bet. secs 19 and 30.
40.00	Set temp ¼ sec. cor.
79.98	Intersect Principal Meridian
	at the cor. of secs. 19, 24, 25, and 30.
	which is a limestone 15×8×8
	ins above ground in a mound

of stone, marked and witnessed
as described by the surveyor
general.

Thence I run

S. 89° 51' E. on a true line bet.
secs. 19 and 30.

Over rolling land.

Through ~~Dense Undergrowth~~

39.98   Set a limestone 24×10×6 ins.
18 ins in the ground for 1/4 sec. cor.
marked 1/4 on N. face; dig pits 18×18×12
E. and W. of stone 3 ft. dist. and raise
a mound of earth 3½ ft. base 1½ ft.
high. N. of cor.

79.98   The cor of secs 19, 20, 29 and 30

Land, rolling.

Soil 2nd and 4th rate.

Timber cedar

Dense undergrowth 79.98 chs.

_____

N. 0° 5' W. bet secs. 19 and 20.

Over rolling land.

Through Dense Undergrowth.

40.00 Set a limestone 20x8x6 ins.
15 ins in the ground, for 1/4 sec.
cor. marked 1/4 on W. face, dig
pits 18x18x12 ins. N. and S. of
stone 3 ft. dist., and raise a mound
of earth, 3½ ft base 1½ ft high W.
of cor.

80.00 Set a limestone 24x8x6 ins 18
ins. in the ground for cor. of secs.
17, 18, 19, and 20 marked with 3
notches on S and 5 notches on E
edges; dig pits 18x18x12 ins. in
each sec. 5½ ft. dist., and raise a
mound of earth 4 ft. base, 2 ft.
high W. of cor.
Land, rolling.
Soil, 3rd and 4th rate.
Timber. cedar.
Dense undergrowth 80. chs.

	S. 89° 44' E. on a random line
	bet. secs. 17 and 20.
40.00	Set temp. 1/4 sec. cor.
80.14	Intersect N. and S. line 10 lks. S.
	of cor. of secs 16, 17, 20 and 21
	Thence I run.
	N. 89° 48' W. on a true line bet.
	secs. 17 and 20.
	Over rough rocky ground
Through	~~dense tenders growth~~.
40.07	Set a limestone 24 × 8 × 3 ins.
	6 ins. in the ground to bedrock
	surrounded by mound of stone.
	for 1/4 sec. cor. marked 1/4 on N.
	face. and raise a mound of
	stone 2 ft. base 1½ ft. high N.g.
	cor. Pits impracticable.
72.09	Road bears S.E. and N.W.
80.14	The cor. of secs. 17, 18, 19 and 20.
	Land rough and rolling.

Soil, rocky; 4th rate.

Timber, cedar.

Dense undergrowth 80.14 chs.

September 24, 1900.

N. 89° 51' W. on a random line bet. secs. 18 and 19.

40.00   Set temp. 1/4 sec. cor.

79.64   Intersect Principal Meridian 22 lks. N. of cor. of secs 13, 18, 19 and 24, which is a limestone 6×12×6 ins. above ground marked and witnessed as described by the surveyor general.

Thence I run.

East. on a true line bet secs 18 and 19.

Through   Over rolling land. ~~Dense undergrowth.~~

39.64   Set a limestone 18×16×6 ins, 12 ins in the ground for 1/4 sec. cor.

marked 1/4 on N. face, raise a
mound of stone. 2 ft. base, 1½ ft.
high N. of cor. Pits impracticable.

79.64 | The cor. of secs. 17, 18, 19 and 20.
Land, rolling.
Soil, 2nd and 4th rate.
Timber, cedar.
Dense undergrowth 79.64 cha.

N 0°5' W. bet. secs. 17 and 18.
Over ascending ground.
heavily | ~~timber~~
3.25 | Road bears S.E. and N W.
40.00 | Set a limestone 18×12×8 ins 12 ins
in the ground for 1/4 sec. cor. mark
ed 1/4 on W. face, from which,
A cedar 10 ins. diam. bears
S. 40¼° E. 145 lks. dist. marked
1/4 S. 17 B.T.
A cedar 12 ins. diam. bears
N. 49° W. 37 lks. dist. marked

	1/4 S. 18 B. T.
	Ascend
46.00	Top of mesa.
75.00	Descend
80.00	Set a limestone 24 x 12 x 6 ins

4 ins. in the ground to bedrock surrounded by mound of stone for cor. of secs. 7, 8, 17 and 18 marked with 4 notches on S and 5 notches on E edges, from which,

A cedar 10 ins. diam. bears N. 26 3/4° E., 229 lks. dist. marked T. 29 N., R. 1 E., S. 8, B. T.

A cedar 10 ins. diam. bears N 17 1/2° W. 70 lks. dist. marked T. 29 N., R. 1 E., S. 7, B. T. - no more trees within limits.

Raise a mound of stone 7 ft. base 1 1/2 ft. high N. of cor. Pits impracticable.

Land rough and rolling.
Timber cedar and pine.
Soil, 4th rate.

Heavily timbered 80 chs.

_____

S 89° 48' E. on a random line
bet. secs. 8 and 17.

40.00 Set temp. 1/4 sec. cor.
80.10 Intersect N. and S. line 28 lks.
N. of cor. of secs. 8, 9, 16 and 17.
     Thence I run.
N. 89° 36' W. on a true line bet. secs.
8 and 17.
     Over rough rolling land.

~~Heavily~~ ~~Timbered~~
40.05 Set a limestone 18 x 12 x 6 ins.
12 ins in the ground for 1/4 sec.
cor. marked 1/4 on N. face, from which
a pine 18 ins. diam. bears
N. 33° E. 132 lks dist. marked.
1/4 S. 8 B.T.

A cedar 12 ins. diam. bears
S. 74¾° W., 38 lks. dist. marked
¼ S. 17. B.T.

79.30   Descent to gulch course N.

80.10   The cor. of secs. 7, 8, 17 and 18.
Land, rough and rolling.
Soil, rocky 4th rate.
Timber cedar and pine.
Heavily timbered 80.10 chs.

N. on a random line bet. secs.
7 and 18.

40.00   Set temp ¼ sec. cor.

79.60   Intersect Principal Meridian
at the cor. of secs. 7, 12, 13 and 18.
which is a limestone 6 × 10 × 8
ins. above ground marked and
witnessed as described by the
surveyor general.
Thence I run.

	E. on a true line bet. secs. 7 and 18.
Through	Over rolling land
39.60	~~Dense Undergrowth~~
	Set a limestone 24×12×4 ins
	18 ins in the ground for 1/4 sec.
	cor. marked 1/4 on N. face and
	raise a mound of stone 2 ft. base,
	1½ ft. high N. of cor.
40.10	Ascend.
62.00	Top of rocky ridge, bears S. 60° W.
78.50	Descend.
79.60	The cor. of secs. 7, 8, 17, and 18.
	Land, rolling.
	Soil, 2nd and 4th rate.
	Timber, cedar and pine.
	Dense undergrowth 79.60 chs.
	September 20th 1900

	N. 0° 5' W. bet secs. 7 and 8
Over heavily ~~Timbered Land~~	
2.00	Descend to cañon, course S. 79° W.
14.00	Bottom of cañon 150 ft. below

	sec. cor. Ascend.
18.50	Top of rim of cañon.
40.00	Set a limestone 18×12×6 ins. 12 ins. in the ground for ¼ sec. cor. marked ¼ on W face, from which.

A cedar 10 ins diam bears S. 89¾° E. 106 lks. dist. marked ¼ S. 8 B.T.

A pine 12 ins. diam. bears S. 37° W. 60 lks. dist. marked ¼ S. 7 B.T.

| 80.00 | Set a limestone 20×12×8 ins 15 ins. in the ground for cor of sees. 5, 6, 7, and 8. marked with 5 notches on S. and E. edges, from which. |

A pine 12 ins. diam. bears N. 30° E., 213 lks. dist. marked T. 29 N., R. 1 E., S. 5, B.T.

A pine 18 ins. diam. bears

S 71¼° E., 101 lks. dist. marked
T. 29 N., R. 1 E., S. 8, B.T.

A pine 18 ins. diam. bears
S. 10½° W. 217 lks. dist. marked
T. 29 N., R. 1 E., S. 7, B.T.

A pine 14 ins. diam. bears
N. 71¾° W. 242 lks. dist. marked
T. 29 N., R. 1 E., S. 6, B.T.

Land, rolling.

Soil, rocky 4th. rate.

Timber cedar and pine.

Heavily timbered 80. chs.

_____

S. 89° 36' E. on a random line
bet. secs 5 and 8.

40.00   Set temp ¼ sec. cor.

80.00   Intersect N. and S. line 2 lks.
S. of cor. of secs. 4, 5, 8 and 9.

Thence Irun

N. 89° 41' W. on a true line

	bet. secs. 5 and 8.
Over heavily Timbered Land.	
40.00	Set a limestone 20x12x8 ins
	15 ins. in the ground for 1/4 sec.
	cor. marked 1/4 on N. face, from which
	A cedar 14 ins. diam. bears
	S. 40° E. 40 lks. dist. marked
	1/4 S. 8 B.T.
	A cedar 10 ins. diam. bears
	N. 32¾° W. 159 lks. dist. marked
	1/4 S. 5 B.T.
80.00	The cor. of secs. 5, 6, 7 and 8.
	Land rolling.
	Soil, 4th rate.
	Timber, cedar and pine.
	Heavily timbered 80 chs.
	N. on a random line bet. secs.
	6 and 7.
40.00	Set temp. 1/4 sec. cor.
79.84	Intersect Principal Meridian

at the cor of secs 1, 6, 7 and 12.
which is a sandstone 24 x 9 x 8
ins above the ground surrounded
by a mound of stone, marked
and witnessed as described by
the surveyor general.

    Thence I run.

    E. on a true line bet. secs.
6 and 7, land heavily Timberd

16.00   hs and mesa course S 10° E
and N. 10° W.

3984   Set a limestone 30 x 16 x 6 ins
22 ins. in the ground for 1/4
sec. cor, marked 1/4 on N. face;
from which,

    A pine 8 ins. diam. bears
S 88 1/2° E. 10 lks dist. marked
1/4 S. 7 B.T.

    A pine 16 ins. diam. bears
N 84 1/4° W. 86 lks. dist. marked

98

	¼ S. 6 B.T.
79.84	The cor. of secs 1. 5, 6, 7 and 8.
	Land, rolling.
	Soil, 4th rate.
	Timber, cedar and pine.
	Heavily timbered 79.84 chs.

	N. 0° 5" W., on a random
	line bet. secs. 5 and 6.
40.00	Set temp. ¼ sec. cor.
80.43	Intersect N. bdy of Tp. 14
	lks. E. of cor. of secs. 5, 6, 31 and
	32.
	Thence I run
	S. 0° 11' E on a true line bet.
	secs. 5 and 6.
and heavily	Over ridges and cañons.
40.43	Set a limestone 18 X 12 X 6 ins.
	12 ins. in the ground for ¼ sec.
	cor. marked ¼ on W. face from

which

A pine 12 ins. diam. bears
S. 30 1/4° E lks. dist marked
1/4 S. 5 B.T. — no other trees
within limits.

Raise a mound of stone
2 ft. base 1 1/2 ft. high N. of
cor.

Ascend to ridge.

41.68	Top of ridge. brs.
48.60	Begin descent.
52.80	Bottom of cañon, course S.W. 125 ft. deep. Ascend.
57.50	Top of ascent.
68.10	Begin descent.
70.80	Gulch, course N.W. 75 ft. deep. Ascend.
74.30	Top of ascent.
80.43	The cor. of secs. 5, 6, 7 and 8.

Land rough and rolling.
Soil, rocky 4th rate.
Timber cedar and pine
Heavily timbered 80.43 chs.

September 26th 1900

The 27th day of September I
discharge Mark Marsh
chainman and Fred Ferst
axeman. and change J.
William Donnelly from
axeman to chainman and
employ Harry H. Tompson
and James Hughes to perform
the duties of axemen.

No officer authorized to administer
oaths other than my self being available
without great inconvenience, delay and expense
I administer the required preliminary
and final oaths as a notary public.

Francis B Jacobs
U.S. Deputy Surveyor

General Description.

This Township some good
rich land along the southern
boundary, but for the most
part is very rocky and is
entirely destitute of water.

The southern portion has
scattering cedar while the
northern is covered with a
heavy growth of scrub pine
and cedar.

The Grand Cañon and
Santa Fé Railroad enters the
Tp. near the 1/4 sec. cor. on S.
boundary of sec. 35ᵗ and on secs.
26 and 35 have a Y and
material yards and the
Junction where track branches
off to Anita Mining Camp.
There are no settlers or

known mines on the Tp.

Francis B. Jacobs

U.S. Deputy Surveyor

September 26th 1900

(Final oaths will be found in
notes of last 17th ship of the
five)

OFFICE OF UNITED STATES SURVEYOR GENERAL,

Tucson, Arizona, *Mar 1.* 1901.

The foregoing field notes of the sur-

vey of *The Subdivisions of T*

29 N R 1 E

Gila and Salt River Meridian,

executed by *Francis B. Jacobs*

under his contract No. *73*, dated *6/3. 1900,*

having ~~examined~~ been critically examined,

and the necessary corrections and expla-

nations made, the said field notes, and

the surveys they describe, are hereby ap-

proved.

George Christ

U. S. Surveyor General for Arizona.