

No. 2.

SUBDIVISIONS. BOOK 585

T. 29 N. R. 2 E.

JACOBS.

4-671

**FIELD NOTES**  
GENERAL LAND OFFICE.

585

No. 585

Township 29N R. 2E

6	106	5	76	4	3	2	1
104		103		74			
7	106	8	72	9	10	11	12
98		97		70			
18	95	17	68	16	15	14	13
93		92		67			
19	88	20	65	21	22	23	24
87		85		64			
30	83	29	62	28	27	26	25
81		80					
31	77	32		33	34	35	36

62

## Subdivision # 29

- 110° 3' N. bet Secs. 28 and 29  
 over rolling land <sup>heavily</sup> timbered  
 4.00 Top of ridge bears S.E. and N.W.  
 Descend  
 15.00 Ravine course S.W. Ascend  
 23.00 Top of ridge bears S.E. and N.W.  
 A Stone Monument, the E. side  
 center of the "Ella" Mining Claim  
 bears N. 8 lks. dist.  
 28.00 Descend  
 40.00 Center of Dutch course S.W.  
 Set a limestone 24 x 10 x 6 ins. 18 ins.  
 in the ground for 1/4 Sec. cor.  
 Marked 1/4 on W face. from which  
 A Pine 10 ins. in diam. bears S 27 1/2° E  
 162 lks. dist. Marked 1/4 S 28 B.T.  
 A Pine 6 ins. in diam bears N 85 3/4° W  
 95 lks. dist. Marked 1/4 S 29 B.T.  
 40.75 Ascend  
 65.00 Top of ridge bears N.E. and S.W.

N. R. 2 East.

63

- 67-45 Center of shaft 10 ft. deep on  
the Nellie mining claim
- 69-17 4 Cedar 12 ins. in diam. on line I mark  
with 2 notches on N and S sides
- 80 00 Set a limestone 24x18x6 ins. 10 ins.  
in the ground (rock prevented  
setting deeper) surrounded by  
mound of stone for cor. of secs.  
20+21-28 and 29 marked with 2  
notches on S and 4 notches on E <sup>edges</sup> ~~face~~  
from which
- A Cedar 12 ins. in diam. bears N  $13\frac{1}{4}^{\circ}$  E  
55 lks. dist. marked T29N R2 E S 21 B.T.
- A Pine 14 ins. in diam. bears S  $43^{\circ}$  E  
11 lks. dist. marked T29N-R2 E S 28 B.T.
- A Pine 12 ins. in diam. bears S  $53^{\circ}$  W
- 63 lks. dist marked T29N R2 E S 29 B.T.
- A Pine 12 ins in diam. bears N  $80\frac{1}{2}^{\circ}$  W
- 61 lks. dist. marked T29N-R2 E S 20 B.T.

Lance Kelly

## Subdivision T.

Soil rocky 4<sup>th</sup> rate  
 Timber Pine and cedar  
 Heavily timbered land 80. abs.

---

N 89° 56' E on a random line bet.  
 Secs 21 and 28.

40 00 Set temp. 1/4 Sec. cor.

80 19 Intersect N. and S. line 12 lbs. N. of  
 cor. of Secs 21-22 27 and 28  
 thence I run

N 89° 59' W on true line bet Secs. 21 and 28  
 over rising land, heavily timbered

40 09 1/2 Set a limestone 30 x 20 x 4 ins. 21 ins in  
 the ground for 1/4 Sec. cor. marked 1/4 on  
 N face, from which  
 A cedar 16 ins. in diam. bears N 1/4° E  
 34 lbs. dist. marked 1/4 S 21 B.T.  
 A cedar 10 ins. in diam. bears S 40° W  
 34 lbs. dist marked 1/4 S 28 B.T.

80, 19 The cor. of Secs. 20-21 28 and 29

29 N. R. 2 East.

65

Land rolling

Soil rocky 4<sup>th</sup> rate

Timber Pine and cedar

Heavily timbered land 80 19 chs.  
 August 27<sup>th</sup> 1900

---

N. 3' N. bet. Secs 20 and 21

over rough land, heavily timbered

Ascend

19.00 Top of ridge bears E and W

Descend

30.00 Gulch course N. Ascend

35.00 Top of flat ridge bears E and W.

40.00 At a limestone 18 x 12 x 6 ins. 12 ins.

in the ground for 1/4 sec cor.

marked 1/4 on N. face from which

A pine 10 ins. in diam. bears N 38 1/2° E

10 lbs dist marked 1/4 S 21 B.T.

A pine 12 ins. in diam. bears S 76° W

72 lbs. dist. marked 1/4 S 20 B.T.

42.00 Descend

66

## Subdivision I

47.00 Gulch course N. 12.5 ft below cor.  
Ascend

51.00 Top of ridge bears E and N Descend

53.00 Gulch course S 60° W. Ascend

58.00 Top of ridge bears N. 60° and S. W.

70.00 Set a limestone 30x10x6 ins. 15 ins. in  
the ground (rock prevented setting  
deeper) surrounded by mound of  
stone, for cor. of secs. 16-17-20 and  
21. Marked with 3 notches <sup>on</sup> S and 4  
notches on E edges.

from which

A Cedar 12 ins. in diam. bears N 16 1/2° E

25 lks. dist. marked T29-N R 2 E S 16 B.T.

A Pine 10 ins. in diam. bears S 24° E

22 lks. dist. marked T29-N R 2 E S 21 B.T.

A Pine 10 ins. in diam. bears S 73° W

52 lks. dist. marked T29-N-R. 2 E S 20 B.T.

A Cedar 16 ins. in diam. bears N 72° W

47 lks. dist. marked T29-N R 2 E S 17 B.T.

29 N. R. 2 East.

67

Sand mountains  
 Soil rocky with rate  
 Timber Pine and cedar  
 Heavily timbered land 80. chs.

---

S 89° 39' E. on a ran down line bet.

secs 16. and 21

40.00 Set temp 1/4 Sec. cor.

80.04 Intersect N and S line 1/4 Sec. S of  
 cor. of <sup>secs.</sup> 15-16-21 and 22.

Thence I run,

S. 89° 55' W. on a true line bet.

secs. 16 and 21, thro. heavy timber

over rolling rocky land

15-75 Gulch course S.W. Ascend

20.00 Top of mesa. -

40.04 1/2 Set limestone 18x8x8 ins. 6 ins. in

the ground (rock prevented setting  
 deeper) surrounded by mound of  
 stone for 1/4 Sec. cor. marked



68

## Subdivision 7c

1/4 on n face from which  
A cedar 30 ins. in diam. bears  $S 85^{\circ} E$

8 lbs. dist. marked "4 S 21 B.T.

A cedar 10 ins. in diam bears  $N 56\frac{1}{2}^{\circ} W$

49 lbs. dist. marked "4 S 16 B.T.

80.09 The cor. of Secs 16-17-20 and 21

Land rolling

Soil rocky + <sup>th</sup> rate

Timber Pine and cedar

Heavily timbered land 80,09 obs.

$N 0^{\circ} 3' N$  bet. Secs - 16 and 17

over broken land, heavily timbered

3.20 Descend

6.75 Gulch and Road course S.  $60^{\circ} W$ .

Ascend

11.60 Top of bank

14.00 Descend

17.17 Gulch course S. W.

Ascend

29. N. R 2 East.

69

- 20.50 Top of bank
- 38.75 A cedar 12 ins. in diam., on line I mark  
with 2 notches on N and S sides
- 40.00 Set a limestone 20 x 14 x 6 ins., 15 ins  
in its ground for  $\frac{1}{4}$  sec. cor  
marked  $\frac{1}{4}$  on W face, from which  
A Pine 10 ins. in diam., bears S  $84\frac{1}{2}^{\circ}$  E  
32 lbs. dist. marked  $\frac{1}{4}$  S 16 B.T.  
A Pine 10 ins. in diam., bears S  $37^{\circ}$  W.  
25 lbs. dist. marked  $\frac{1}{4}$  S 17 B.T.
- 43.00 Descend
- 45.40 Gulch course S.W. ascend
- 47.00 Top of bank ascend
- 53.00 Top of mesa
- 70.00 Descend
- 74.00 Gulch course S.W. ascend
- 80.00 A cedar, 10 ins. diam., for cor. of Secs.  
8-9-16 and 17. I mark  
T 29 N., S 9 on N E  
R 2 E. S 16 on S E

## Subdivisions of

S 17 on S. W. end

S 8 on N. W. side; with 4  
notches on S and E edges.

from which

4 Pine 12 ins. diam. bears  $N 71\frac{3}{4}^{\circ} E$

73 lbs. dist. marked T 29 N. - R 2 E - S 9 B.T.

A Pine 10 ins. diam. bears  $S 42^{\circ} E$

24 lbs. dist. marked T 29 N. - R 2 E. - S 16 B.T.

A Pine 8 ins. diam. bears  $S 3^{\circ} W$

11 lbs. dist. marked T 29 N. - R 2 E. - S 17 B.T.

A Cedar 8 ins. diam. bears  $N 69\frac{1}{2}^{\circ} W$

22 lbs. dist. marked T 29 N. - R 2 E. - S 8 B.T.

Land mountainous

Soil rocky at the rate

Timber Pine and Cedar

Heavily timbered land 80.00

$N 89^{\circ} 55' E$  on a random line  
bet. Secs. 9 and 16

40.00 Set temp  $\frac{1}{4}$  Sec. cor

## 29 N. R 2 East. 71

- 80.46 Intersect N. and S. line 18 lks. S.  
of the cor. of secs. 9-10-15 and 16  
Hence I run  
S 89° 47' W on a true line bet. Secs.  
9 and 16  
over broken land, heavily timbered
- 31.75 Descend
- 34.50 Gulch course S 60° W Ascend
- 37.50 Top of bank
- 40.73 A talcum stone 18 x 12 x 6 ins. 4 ins. in  
the ground (rock prevented setting  
deeper) surrounded by mound of  
stone, for 1/4 sec. cor. marked 1/4 on  
n face from which.  
A Pin 1/6 ins diam. bears N 35° E  
44 lks. dist. marked 1/4 S 9 B.T.  
A Cedar 10 ins. diam. bears S 64 1/2° E  
4 lks. dist. marked 1/4 S 16 B.T.
- 52.75 At S. E. cor. "Gauoshonter"  
mining claim bears S. 2 lks. dist.

72

## Subdivisions

80.46 The cor of sec 8-9-16 and 17  
Land broken

Soil rocky & <sup>th</sup> rate

Timber Pine and cedar

heavily timbered land 80.46 ch

August 28<sup>th</sup> 1900

---

N. 3' x bot sec. 8 and 9

over broken land, heavily timbered

2.00 Top of mesa

9.86 Cedar 18 ins. diam on line & mark  
with 2 notches on N and S sides

15.50 Descend

25.00 Gulch course N., Ascend

30.00 Top of ridge bears E and N  
Descend very abruptly 30° Vert.

32.30 Gulch course N. - 150 ft deep  
Ascend

40.00 Top of mesa

Set a lime stone 20 x 8 x 4 ins.

T 29 N. R. 2 East 73

15 ins. in the ground for  $\frac{1}{4}$  sec cor  
marked  $\frac{1}{4}$  on W face. - from which  
A Pine 10 ins. diam bears  $S 37 \frac{3}{4}^{\circ} E$ .

31 lks dist marked  $\frac{1}{4}$  S 9 B.T.

A Pine 10 ins. diam. bears  $S 79 \frac{1}{4}^{\circ} W$ .

36 lks. dist marked  $\frac{1}{4}$  S 8 B.T.

45.04 A cedar 18 ins diam on line I marked  
with 2 notches on N. and S. sides

75 50 Descend

80 00 Set a limestone  $30 \times 20 \times 6$  ins. 22 ins.  
in the ground for cor of lines 4-5-8  
and 9. marked with 5 notches on S  
and 4 notches on E edges.  
from which.

A Pine 8 ins. diam. bears  $N 61 \frac{3}{4}^{\circ} E$

50 lks dist marked T 29 N-R 2 E-S 4 B.T.

A Pine 14 ins. diam bears  $S 22 \frac{3}{4}^{\circ} E$

37 lks. dist. marked T 29 N-R 2 E-S 9 B.T.

A Pine 14 ins. diam. bears  $S 34 \frac{1}{2}^{\circ} W$

59 lks dist marked T 29 N-R 2 E-S 8 B.T.

74

## Subdivisions

A line 10000 diam bears  $N 25 \frac{1}{2}^{\circ} W$ 

13 lks. dist marked T29N-R2E S 5137.

Land mountainous

Soil rocky,  $\frac{1}{4}$   $\frac{1}{2}$  rate

Timber Pine and cedar

Heavily timbered land 80. chs

 $N 89^{\circ} 47' E$  on a random line

bet secs 4 and 9

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

80.44 Intersect N. and S. line 8 lks. S. of

cor of secs 3-4-9 and 10

Thence I run

 $S 89^{\circ} 44' N$  on a true line bet.

secs. 4 and 9.

cor. broken ground heavily timbered

75.50. Descend

30.00 Bottom of hill Ascend

33.00 Top of mesa

40.77 set a lime stone  $18 \times 14 \times 4$  ins. 6 ins.

T 29 N. R. 2 East

75

in the ground (rock prevented setting  
deeper) surrounded with mound of  
stones for  $\frac{1}{4}$  Sec. cor. marked  $\frac{1}{4}$  on N face  
from which

A Pine 6 ins. diam. bears S  $44^{\circ}$  E

26 lbs. dist. marked  $\frac{1}{4}$  S. 9 B.T.

A Pine 10 ins. diam. bears N  $37^{\circ}$  W

21 lbs. dist. marked  $\frac{1}{4}$  S 4 B.T.

50.00 Descend

53.00 Gulch course S  $12^{\circ}$  <sup>ft deep</sup> Ascend.

56.00 Top of flat ridge

65.50 Descend.

75-85 Gulch course N. W 100 ft deep

80.44 The cor. of Secs 4-5-8 and 9

Land broken ~~in~~

Soil rocky at <sup>the</sup> rate

Timber Pine and cedar

Heavily timbered land 80.44 obs



76

## Subdivision

No 3' N on a random line  
bet Secs 4 and 5-

40.00 Set temp.  $\frac{1}{4}$  Sec. cor.

80.41 Intersect N. bdy of Tp. 37 lks. N.  
of cor of Secs 4-5-32 and 33  
Thence I run

$30^{\circ} 13' W.$  on a true line bet. Secs.  
4 and 5-

a heavily timbered  
over mountainous land

40.41 set a line stone  $30 \times 18 \times 6$  ins. H ins. in  
the ground (rock prevented setting  
deeper) surrounded by mound  
of stones. for  $\frac{1}{4}$  Sec. cor. marked  
 $\frac{1}{4}$  on N. face. from which  
a Pine 18 ins. diam bears  $N 52^{\circ} E$   
51 lks. dist. marked  $\frac{1}{4} S 4$  B.T.  
A Pine 18 ins. diam bears  $N 87^{\circ} W.$   
39 lks. dist. marked  $\frac{1}{4} S 5$  B.T.  
Descend

51.00 Enter Rain Tank Wash

T 29 N., R 2 East 77

course S 75° W.

52.75 Road follows road

55.00 Limestone bluff 15 ft high  
ascend

80.41 The corners 4-5 8 and 9.

Land mountainous

Soil rocky 4<sup>th</sup> rate

Timber Pine and cedar

Heavily timbered land 80.41 obs.

August 29<sup>th</sup> 1900

August 30<sup>th</sup> At 7<sup>h</sup> 30<sup>m</sup> a.m.  
l.m.t. I set off 35-47' on the  
lat. arc; 9° 05' N. on the decl  
arc; and determine a true  
meridian with the solar at the  
standard cor. of Secs 31 and 32  
which is a limestone 20 x 16 x 4  
ins set in a mound of stone and  
marked and witnessed as

## Subdivision

described by the Surveyor  
General

Thence I run

N 0° 3' W bet Secs 31 and 32.

Over rolling land & dense <sup>undergrowth</sup>

1.50 Descend

26.00 Ascend

34.00 Top of ridge bears E and W

38.50 Descend

40.00 Set a limestone 24 x 12 x 8 ins  
18 ins in the ground for 1/4 Sec  
cor. marked 1/4 on W face  
from which

A Cedar 10 ins. diam. bears S 50° E

136 lks. dist. marked 1/4 S 32 - B.T.

A Cedar 10 ins. diam. bears N 85 1/2° W

23 lks. dist. marked 1/4 S 31 B.T.

43.45 Road bears E and W

48.75 Gulch course S 70° W

Ascend

T29N, R2 East 79

50.50 Limestone ledge bears  $N70^{\circ}E + S.70^{\circ}W$ 80.00 Set a limestone  $20 \times 12 \times 6$  ins. 15 ins

in the ground for cor of sec

29-30-31 and 32 marked

with one notch on S and 5

notches on E edges from which

A Pine 8 ins. diam. bears  $N23^{\circ}\frac{1}{2}^{\circ}E$ 

22 lks. dist. marked T29N-R2ES29BT.

A Pine 10 ins. diam. bears  $S39^{\circ}\frac{3}{4}^{\circ}E$ 

40 lks. dist. marked T29N-R2ES32BT.

A Pine 8 ins. diam. bears  $S.22^{\circ}\frac{1}{2}^{\circ}W.$ 

13 lks. dist. marked T29N-R2ES31BT.

A Pine 12 ins diam bears  $N16^{\circ}\frac{1}{4}^{\circ}W$ 

75 lks. dist. marked T29N-R2ES30BT.

Land rolling

Soil 3<sup>d</sup> rate

Timber Cedar and Pine

Dense undergrowth &amp; rocks

## Subdivision

East on a random line bet.

Secs 29 and 32

40-00 Set temp  $\frac{1}{4}$  Sec. cor.

80.17 Intersect N and S line 14 lds S. of  
Cor. of secs 28-29-32 and 33  
Thence I run

$S89^{\circ}54'W$  on a true line bet Secs  
29 and 32 thro dense undergrowth  
over rough hilly land

4.00 Descend

79-00 Ravine course S. ascend

40 08 $\frac{1}{2}$  set a limestone  $24 \times 12 \times 6$  ins. 4  
ins. in the ground (rock prevented  
setting deeper) surrounded  
by mound of stone for  $\frac{1}{4}$  ft.  
Sec. cor. Marked  $\frac{1}{4}$  on N face  
from which

A cedar 8 ins. diam. bears  $N49^{\circ}E$

19 lds. dist. marked  $\frac{1}{4}$  S 29 B.T.

A pine 6 ins. diam. bears  $S38\frac{1}{2}^{\circ}W$

7<sup>th</sup> 29 N R 2 East 81

10 hrs. dist. marked  $\frac{1}{4}$  S 32 B.T.

43.00 Top of ridge bears N and S  
Descend

45.00 Ravine course S Ascend

45-80 Road bears N and S

44.60 Top of rocky ridge ends  
75 hrs. S.

69.00 Descend

80.17 The cor. of secs. 29-30-31 and 32  
Land hilly and rocky  
Soil 4<sup>th</sup> rate  
Timber Cedar and Pine  
Dense undergrowth 80.17 hrs.

---

West on a random line but sec  
30 and 31

40.00 Sit temp  $\frac{1}{4}$  Sec. cor.

80.38 Intersect N. bdy 2 hrs. N of cor  
of Secs 25-30-31 and 36  
which is a limestone

8.2

## Subdivision

12 x 12 x 6 ins above ground  
 surrounded by mound of stone  
 previously set, marked and  
 witnessed by me.

Since I ran

$789^{\circ}59' E$  on a true line bet.

secs 30 and 31, since underground  
 over rolling land  
 ascend

13-40 Top of mesa

20-00 Rocky rim here  $S75^{\circ}E + N75^{\circ}W$   
 Descend

75-00 Ascend

40.38 set a limestone  $20 \times 8 \times 6$  ins, 8 ins.  
 in the ground. (rock prevented  
 setting deeper) Surrounded by  
 mound of stone for  $1/4$  sec, cor.  
 marked  $1/4$  on N face  
 from which  
 Cedar 10 ins in diam bears

BOOK 585  
T 29 A, R 2 East 83

N72 $\frac{1}{2}$ °E 88 yds, dist. marked 14530 B.T.

A cedar 12 ins. diam. bears S 14 $\frac{1}{2}$ ° N

130 yds, dist. marked 14531 B.T.

61-00 Descend

63.50 Ravine course S. ascend

80.38 The corners 29-30-31 and 32

Land rolling

Soil 3<sup>d</sup> and of 1<sup>st</sup> rate

Timber Cedar and Pine

Dense undergrowth 80.35 chs

August 30<sup>th</sup> 1900

---

N0°3' N. bet. lines 29 and 30

over rough land, dense undergrowth

ascend

1.80 Rock bluff 10 ft high

1.90 Top of rock bluff 750 ft.  
above Gulch -

40.00 Set a limestone 24 x 12 x 4 ins.  
6 ins. in the ground. (rock



F.4

## Subdivision

prevented sitting dupes.)  
 surrounded by mound of  
 stone. for  $1/4$  sec. cor.

marked  $1/4$  on W face

from which

A Pine 10 ins. diam. bears  $N 57 \frac{1}{2}^{\circ} E$

20 lbs. dist. marked  $1/4 S 29-13 T.$

A Pine 10 ins. diam. bears  $N 57 \frac{1}{4} W$

56 lbs. dist. marked  $1/4 S 30 13 T.$

80,00 set a limestone  $20 \times 12 \times 6$  ins.

15 ins. in the ground for cor. of

secs 19-20-29 and 30

marked with 2 notches on S

and 5 notches on E edges

from which

A Pine 12 ins. diam. bears  $N 46^{\circ} E$

61 lbs. dist. marked  $T 29 N - R 2 E S 20 R T.$

A Pine 14 ins. diam. bears  $S 33 \frac{1}{2} E$

48 lbs. dist. marked  $T 29 N - R 2 E S 29 R T.$

A Pine 12 ins. diam. bears  $S 27 \frac{1}{2} W$

T 29 N R 2 East 85

36 lks. dist. marked T29NR2ES 30 B.T.

A Pine 16 ins. diam. bears N79 $\frac{1}{2}$ W

50 lks. dist. marked T29-N-726319 B.T.

Land rough and rocky

Soil  $\frac{1}{2}$  rate

Timber Pine and cedar

Dense undergrowth 80. chsN 89° 54' E on a random line  
bet. Secs. 20 and 29.40.00 Set temp  $\frac{1}{4}$  sec cor79.97 Intersect 76 and 3 line 12 lks N. of  
cor. of Secs. 20-21-28 and 29  
thence I runS 89° 59' W on a true line  
bet. Secs. 20 and 29, <sup>in undergrowth</sup> this dense,  
over broken rocky land39.98 $\frac{1}{2}$  Set limestone 18 x 10 x 4 ins.4 ins. in the ground (rocks prevented  
setting deeper) surrounded with

## Subdivision

- Mound of stone for  $\frac{1}{4}$  sec ~~cor~~  
 marked  $\frac{1}{4}$  on N face  
 from which
- A Pine 9 ins diam. bears  $N 75^{\circ} \frac{1}{2} E$   
 21 lks. dist. marked  $\frac{1}{4} S 20 B.T.$
- A Pine 6 ins diam bears  $S 29^{\circ} E$   
 4 lks dist marked  $\frac{1}{4} S 29 B.T.$
- 46.10 A mining shaft 15 ft deep  
 bears N. 18 lks. dist. - also  
 considerable excavating  
 N-E of shaft and large dumps  
 of waste north of this line. -
- 51.67 Road bears N and S
- 57.17 Road from Anita camp to the  
 Hoist on Sec. 29 -
- 79.97 The cor of Secs. 19-20-29 and 30  
 Land rough  
 Soil rocky & the rate  
 Timber Pine and cedar  
 Dense undergrowth 79.97 cks

T 29 N. R 2 East 87

S 89° 59' N on a random line  
bet. Secs 19 and 30-

H 0.00 Sit. temp.  $\frac{1}{4}$  Sec cor

8 0.45 Intersect W body of Sp. 20 lvs  
N of cor. of Secs 19-24-25 and 30  
which is a lime stone 5 x 14 x 6  
ins above ground - previously  
set; marked and witnessed by  
me. -

Thence I run

N 89° 50' E on a true line bet.  
Secs. 19 and 30 thro dense <sup>undergrowth</sup>  
over broken land  
ascend

H. 50 Top of mesa

40-45 Sit a limestone 20 x 12 x 6 ins.  
15 ins. in the ground for  $\frac{1}{4}$  Sec. cor,  
marked  $\frac{1}{4}$  on n face  
from which  
A Pine 8 ins diam bears S 15  $\frac{1}{4}$  E!

88

## Subdivision

89 lks. dist. marked '45 30 - B.T.

A cedar 8 ins. diam. bears  $N 5^{\circ} W$ 

33 lks. dist marked '45 19 B.T.

80.45 The cor of secs 19-20-29 and 30  
Land roughSoil rocky & <sup>the</sup> rats

Timber Pine and cedar

Dense Undergrowth 80.45 chs

August 31<sup>st</sup> 1900N 0° 3' W bet Secs 19 and 20  
over mountainous land, heavily timbered

2.00 Descend

18 00 Road bears E. and W.

20 00 Gulch course W.

Ascend

23-00 Ridge bears E. and W.

24-00 Descend

30-00 Gulch course W. - Ascend.

32-30 A Point in Anita Camp

T 29 N. R 2 East 89

from which buildings bear  
as follows

A Lumber house 14 x 20 ft the  
S.E. cor. bears N 53 $\frac{1}{2}$ ° W 97 lks. dist.

A Log house 14 x 20 ft the S.E. cor  
bears N 81° W 291 lks. dist.

A Log "Boarding house" the S. E.  
cor. bears N 90 $\frac{1}{4}$ ° W. 377 lks. dist

The Store and office building, the S. E.  
cor. bears N 90° W. 500 lks. dist.

assay office, the S. E. cor. bears  
S 89° W. 605 lks. dist.

A Building the S. E. cor bears  
N 61° W 243 lks dist

A Building the N. E. cor. bears  
S 49 $\frac{1}{4}$ ° W 128 lks dist

A Building the N. E. cor.  
bears S 11° W 100 lks dist.

37.71 Porch of building

37.77 Building, 27 ft. front

## Subdivision

In order to get around  
this building I offset  
from the point at 37.30  
chs. West 50 lks. -

Thence  $N 0^{\circ} 3' W$  2.00 chs

Thence East 50 lks to line.

34.76 A Pine 12 ins. diam. on line I mark  
with 7 notches on N and S sides

36.00 Top of N. slope of ridge  
Descend

39.15 Road bears E. and S. W.

40.00 Set a lime stone  $20 \times 16 \times 6$  ins. 15  
ins. in the ground for  $\frac{1}{4}$  Sec. cor.  
marked  $\frac{1}{4}$  on N face  
from which

A Pine 10 ins. diam. bears  $N 43^{\circ} E$

53 lks dist marked  $\frac{1}{4} S 20$  B.T.

A Pine 18 ins. diam. bears  $N 13^{\circ} W$ .

56 lks. dist. marked  $\frac{1}{4} S 19$  B.T.

40.29 Road bears  $NE$  and  $S. W.$

T<sup>h</sup> 29 N R 2 East 91

40.83 Gulch course S 60° W

Ascend

46.00 Top of mesa

80.00 Sit a limestone 30 x 8 x 6 ins. on  
 rock. Surrounded by mound of  
 stone 3 ft. base 2 ft high for con-  
 of secs. 17-18-19 and 20  
 marked with 3 notches on S  
 and 5 notches on E edges  
 from which

A Pine 6 ins. diam. bears N 89<sup>3</sup>/<sub>4</sub>° E

38 lks. dist. marked T 29 N R 2 E S 17 B.T.

A Pine 12 ins. diam. bears S 59<sup>1</sup>/<sub>2</sub>° E

36 lks. dist. marked T 29 N R 2 E S 20 B.T.

A Pine 8 ins. diam. bears S 1<sup>1</sup>/<sub>2</sub>° W

44 lks. dist. marked T 29 N R 2 E S 19 B.T.

A Pine 10 ins. diam. bears N 66<sup>1</sup>/<sub>2</sub>° W

55 lks. dist. marked T 29 N R 2 E S 18 B.T.

Land mountainous

Soil rocky at <sup>the</sup> rate



92

## Subdivision

Timber Pine and Cedar  
Heavily timbered land 80. chs.

---

$N 89^{\circ} 59' E$  on a random line  
bet Secs. 17 and 20

40.00 Set temp  $\frac{1}{4}$  Sec. cor.

80.04 Intersect N and S line 34 chs. N. of  
cor. of Secs. 16-17-20 and 21.

Thence I run

$N 89^{\circ} 46' W$  on a true line bet. Secs  
17 and 20.

over rough land heavily timbered

9.20 Road bears N. E. and S. W.

22.98 A cedar post 5x5 ins diam. 2 ft  
above ground marked with pencil  
N. W. cor. Nellis

40.02 Set a limestone 16x10x6 ins 11 ins.  
in the ground for  $\frac{1}{4}$  Sec. cor.  
marked  $\frac{1}{4}$  on N face  
from which

F 29 N R 2 East 93

A cedar 1 1/2 ins. diam. bears N 7 1/4 ° E

57 lks. dist. marked 1/4 S 17 B.T.

A Pine 8 ins. diam. bears S 24 1/2 ° E

75 lks. dist. marked 1/4 S 20 B.T.

80.04 The cor. of secs 17-18-19 and 20

Land rough

Soil rocky & the rate

Timber Pine and cedar

Heavily timbered land 80.04, chs

---

S 89° 50' W on a random line

bet. secs 18 and 19.

40.00 Set temp 1/4 sec. cor.

80.38 Intersect N. bdy 11 lks. S of the cor

of secs. 13-18-19 and 24 which is  
a limestone 20 x 12 x 6 <sup>in.</sup> set in a

mound of stone previously set  
marked and witnessed by

me—

Thence I run

94

## Subdivision

- N 89° 55' E on a true line  
 bet Secs. 18 and 19.  
 over hilly land, heavily timbered
- 13.50 Enters Rain Falls wash  
 course South
- 15-15 Road bears N. E and S. W.
- 18.50 Road bears N. and S.
- 21-00 Leaves Rain Falls wash
- 40.38 Set a line stone 16 x 12 x 6 ins.  
 11 ins in the ground for  $\frac{1}{4}$  sec  
 cor marked  $\frac{1}{4}$  on N face  
 from which  
 A Pine 16 ins. diam. bears S 61 $\frac{1}{4}$ ° W.  
 12 yds. dist. marked  $\frac{1}{4}$  S 19 B.T.  
 A Pine 10 ins. diam. bears N 75 $\frac{1}{4}$ ° W  
 41 yds. dist. marked  $\frac{1}{4}$  S 18 B.T.
- 80.38 The cor. of Secs. 17-18-19 and 20  
 Land hilly  
 Soil 3 $\frac{1}{2}$  and 4 $\frac{1}{2}$  in rate  
 Timber Pine and cedar

T 29 N., R. 2 East 95

Heavily Timbered land 80.38 chs.

September 1<sup>st</sup> 1900N 0° 3' W bet. Secs 17 and 18  
over <sup>heavily timbered</sup> mountainous land

1.50 Descend steep rocky ridge

6.75 Gulch 125 ft below cor. course W.  
Ascend10.60 Ridge bears E and W  
Descend15.40 Gulch 150 ft deep course S, W.  
Ascend

24.00 Top of bank bears N, E, and S, W.

40.00 Set a limestone 18 x 12 x 6 ins,  
12 ins in the ground for 1/4 Sec.  
cor. marked 1/4 on W face  
from which

A cedar 10 ins diam. bears N 89 3/4° E

32 lbs, dist. marked 1/4 S 17 B. T.

A cedar 16 ins. diam. bears S 22 1/2° W

96

## Subdivision

- 35 lbs, dist, marked N S 18 B.T.
- 42 00 Descend
- 51-00 Gulch 150 ft deep course S, W.  
Ascend
- 58.40 Top of bank bears N. 90, and S W
- 63-00 Descend
- 70.00 Set a limestone 24 x 14 x 6 ins,  
18 ins in the ground for cor. of sec.  
7-8-17 and 18 marked with  
4 notches on S and 5 notches on  
E edges from which  
A Pine 14 ins. diam. bears N 42° E  
57 lbs dist marked T 29 N-R 2 E S 8 B.T.  
A Pine 12 ins. diam. bears S 45° E  
19 lbs. dist marked T 29 N-R 2 E S 17 B.T.  
A Pine 12 ins. diam. bears S 75° W.  
48 lbs, dist, marked T 29 N-R 2 E S 18 B.T.  
A Cedar 10 ins. diam. bears N 9 1/2° W  
48 lbs, dist marked T 29 N-R 2 E S 7 B.T.  
Land mountainous

T<sup>h</sup> 29 N., R 2 East 97Soils H<sup>g</sup> rate

Timber Pine and Cedar

Heavily timbered land 80. Chs

S 89° 46' E on a random line  
bet Sec 8 and 17

40.00 Set temp. 1/4 Sec. cor

80.10 Intersect N and S line 14 Chs

S of cor. of Secs 8-9-16 and 17

Thence I run

N 89° 52' W on a true line

bet Secs 8 and 17

over mountainous land <sup>heavily timbered</sup>

73.00 Descend

30.50 Gulch course N.W.

Ascend

35.00 Top of bank

37.00 Descend along South  
side of Gulch

40.05 Set a limestone 18 x 10 x 8 ins.

## Subdivision

12 ins in the ground for  $\frac{1}{4}$  Sec. cor.  
marked  $\frac{1}{4}$  on N. face  
from which

A Pine 14 ins. diam bears  $N44^{\circ}E$

43 lks. dist. marked  $\frac{1}{4} S 8 B.T.$

A Pine 10 ins. diam. bears  $S63^{\circ}E$

8 lks. dist. marked  $\frac{1}{4} S 17 B.T.$

46.55 A Log cabin  $16 \times 24$  ft. bears  
 $N 92^{\circ} W$  350 lks dist.

51.55 Road bears  $N 90^{\circ} E$  and  $S 80^{\circ} W$ .

63.75 Same Road bears  $S E.$  and  $N. W.$

80.10 The cor. of secs. 7-8-17 and 18.

Land mountainous

Soil  $\frac{1}{2}$  rate

Timber Pine and cedar

Heavily timbered land  $80.10$  cfs

---

$S 89.55^{\circ} W.$  on a random line

bet. Secs 7 and 18-

40.00 Set temp  $\frac{1}{4}$  Sec. cor.

- 80-12 Intersect the N. bdy. of the Sp.  
 15 1/2 W of the cor. of Sec 7-12-13  
 and 18 which is a limestone  
 10x12x8 ins. above ground previously  
 set marked and witnessed by me.  
 Thence I run  
 N 89°-49' E on a true line bet.  
 Sec. 7 and 18.  
 over rough land heavily timbered  
 Descend
- 1.90 Gulch course S 70° E  
 Ascend
- 4.00 Top of bank
- 11-75 Descend
- 17 00 Gulch 75 ft deep course S 25° N  
 Ascend
- 20-00 Top of bank
- 40.12 Set a limestone 24x9x5 ins.  
 18 ins in the ground for 1/4 Sec. cor.  
 marked 1/4 on N face



## Subdivision

from which

A Pine 12 ins. diam. bears  $N 34 \frac{1}{2}^{\circ} E$ ,  
 43 lks. dist. marked  $\frac{1}{4} S 7$  B, T.

A cedar 27 ins. diam. bears  $S 66^{\circ} W$ .  
 2 lks. dist. marked  $\frac{1}{4} S 18$  - B, T.

59.00 Enter Rain Tank Wash

60.40 Road bears N, and S,

67.00 Leave Rain Tank Wash  
 course S. -

90.12 The cor. of Secs 7-8-17 and 18  
 Land Rough broken

Soil 2<sup>d</sup> and of the rate  
 Timber Pine and cedar

Heavily timbered land 90.12 obs

---

$N 0^{\circ} 3' N$  bet Secs 7 and 8.

over mountainous land heavily timbered

Descend

350 Gulch and Road 100<sup>lks</sup> below ca,  
 cor. course W

29 N. R. 2 East

BOOK 585

101

Ascend

6.50 Ridge bears E, and N.

21-00 Descend

24-00 Enter Rainland cross L  
course S. W.

24-60 Road bears N. E. and S. W.

28-00 Leave Wash ascend

40.00 Set a limestone  $30 \times 16 \times 6$  ins,  
22 ins in the ground for  $\frac{1}{4}$  sec. cor.  
marked  $\frac{1}{4}$  on N face  
from which

A Pine 14 ins. diam. bears  $S 64^\circ E$

3 lds. dist. marked  $\frac{1}{4}$  S 8 B.T.

A cedar 12 ins. diam. bears  $S 22 \frac{1}{2}^\circ W$ .

43 lds. dist marked  $\frac{1}{4}$  S 7 B.T.

44. No A cedar 9 ins. diam. on line I mark  
with 2 notches on N and S sides

48-00 Descend

58-90 Gulch course S. E. Ascend

77-00 Gulch course  $S 10^\circ W$  ascend

## Subdivision

90.00 set a limestone 30 x 10 x 8 ins.  
 27 ins in the ground for cor. of  
 Secs 5-6-7 and 8 marked with  
 5 notches on S and E edges  
 from which  
 A cedar 9 ins. diam. bears N  $70^{\circ} \frac{1}{2}$  E  
 133 lks. dist. marked T29N-R2E S 5 B.T.  
 A Pine 10 ins. diam. bears S  $48^{\circ} \frac{1}{2}$  E  
 50 lks. dist. marked T29N-R2E S 8 B.T.  
 A Pine 12 ins. diam. bears S  $57^{\circ}$  W  
 157 lks. dist. marked T29N-R2E S 7 B.T.  
 A Pine 10 ins. diam. bears N  $44^{\circ} \frac{1}{2}$  W  
 106 lks. dist. marked T29N-R2E S 6 B.T.  
 Land mountainous  
 Soil 4<sup>th</sup> rate  
 Timber Pine and cedar  
 Heavily timbered land 80 chs  
 September 3<sup>d</sup> 1900

L 29 N., R 2 East. 103

- S.  $89^{\circ}52'$  E. on a random line  
bet. Secs. 5 and 8
- 40.00 Set temp  $\frac{1}{4}$  sec. cor.
- 80.76 Intersect N and S line 12 1/2  
S. of cor. of Secs 4-5-8 and 9  
Thence True  
N  $89^{\circ}57'$  W. on a true line bet.  
Secs. 5 and 8  
over rough broken land <sup>timbered</sup> heavily.
- 9.00 Descend
- 13.00 Gulch course N, W. Ascend
- 15.35 Top of ridge bears S E and N, W.
- 25.38 Descend
- 32.00 Run Dam wash and Road  
course S  $70^{\circ}$  W.
- 33.50 Ascend
- 36.00 Ridge bears N and S
- 40.13 Set a lime stone  $18 \times 12 \times 4$  ins.  
12 ins in the ground for  $\frac{1}{4}$  sec. cor.  
marked  $\frac{1}{4}$  on N face

104

## Subdivision

from which

A cedar 18 ins diam. bears  $S 74^{\circ} 34' E$   
15 lks. dist, marked  $\frac{1}{4}$  S 8 B, T.

A cedar 18 ins. diam bears  $N 36^{\circ} 14' W$   
27 lks. dist marked  $\frac{1}{4}$  S-5 B, T.

74- Descend

79.75 Gulch course  $S 10^{\circ} W$  ascend

80.76 The cor. of secs 5-6-7 and 8

Land rough and rocky

Dirt at the rate

Timber Pine and cedar

Heavily timbered land 80.76 do

$S 89^{\circ} 49' W$  on a random line  
bet. Secs. 6 and 7

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

80.19 Intersect the N. bdy. of the Twp.  
4 lks. S of the cor. of secs. 1-6-7  
and 12 which is a limestone  
6 x 18 x 6 ins above ground

T 29 N R 2 East 105

previously set marked and  
witnessed by me  
Thence I run

N 89° 51' E on a true line bet Secs.  
6 and 7

over rolling land heavily timbered

27.87 Grand Canon and Santa Fe  
Railway bears S. 17° 35' E  
and 3° Curve to R. - N. E. 1

23.60 Road parallel to railroad

40-19 Set a limestone 18x12x6 ins. 12  
ins. in the ground for 1/4 Sec. cor.  
marked 1/4 on n. face  
from which

A Cedar 3 ins. diam. bears S 9 1/2° E  
5 lds. dist marked 1/4 S 7 T. T.

A Pine 10 ins. diam. bears N 74 1/2° W  
32 lds. dist. marked 1/4 S. 6 T. T.

53.00 Descend

64.00 Gulch course S. E.

106

## Subdivision

ascend

69.80 top of mesa

76.75 descend

80-19 The cor. of <sup>secs.</sup> 5-6-7- and 8

Land rolling

Soil rocky & <sup>sh.</sup> rate

Tumble Pine and cedar

Heavily timbered land. 80-19 chs.

N0-3' W on a random line

but secs 5 and 6

40.00 Set temp 1/4 Sec cor

80.15' Intersect N bdy of the Sp. 32

lts. E. of the cor. of secs 5-6-31  
and 32. which is a limestone

5x10x6 ins. above ground

previously set marked and  
witnessed by me

thence I run.

S0°17'E on a true line

T 29 N., R 2 East. BOOK 585  
107

Art. Secs. 5 and 6 thro dense timber

over rolling rocky land

32.15 G.C. and S.F. Railway bears

$N 57^{\circ} 10' E$  and  $S 57^{\circ} 10' W$

40-15 Sit limestone  $24 \times 18 \times 6$  ins. 18 ins.

in the ground for  $\frac{1}{4}$  sec, cor.

marked  $\frac{1}{4}$  on N face

from which

A cedar 14 ins. diam. bears  $N 5^{\circ} E$

3 lbs. diet. marked  $\frac{1}{4}$  S 5 B.T.

A Pine 8 ins. diam. bears  $S 80^{\circ} \frac{1}{2} W$

14 lbs. diet. marked  $\frac{1}{4}$  S 6 B.T.

80.15 the cor of Secs 5-6-7 and 8

Land rolling

Soil rocky  $\frac{1}{4}$  to 1 mile

Timber Pine and cedar

Heavily timbered land 80.15

September 4<sup>th</sup> 1900

---



## Subdivision

## General Description

This township contains very little good land almost the entire surface is covered by limestone.

There is a dense growth of scrub pine and cedar covering the entire township.

There are copper mines on Secs. 20 and 29 claimed and being worked by the Anita Consolidated Copper Co. of Swampscott Mass. There is no water on the township.

Anita Mining Camp contains about 10 buildings and a number of tents is situated on Sec 19.-

Francis B. Jacobs  
U.S. Deputy Surveyor

BOOK 585

L 29 N. R 2 East 109

number of <sup>h</sup> 1900

170  
Ann

Preliminary & Final Caths.

See

North & East Bdys

T. 30, N. R. 1, E.

BOOK 585

BOOK 111  
585

APPROVAL.

OFFICE OF U. S. SURVEYOR GENERAL,

TUCSON, ARIZONA, *Feb'y 28*, 1901.

The foregoing field notes of the sur-

vey of *The Subdivisional Lines*  
*of T. 29 N. R. 28 E.*

Gila & Salt River Meridian,

executed by *Francis B. Jacobs*.

under his contract No. *73*, dated *6/13 1900*.

having been critically examined, and the

necessary corrections and explanations

made, the said field notes, and the sur-

veys they describe, are hereby approved.

*George Christ*

U. S. Surveyor General for Arizona.