

Copied  
Comptrol  
Indication

Sent to Com. G. L. O. Feb 27<sup>th</sup> 1892  
Approved March 18 1892  
Ed.

BOOK 594

No. 594

594

4-671

## FIELD NOTES

GENERAL LAND OFFICE.

of the survey  
of the

Subdivision Lines of  
Township 29 N. Range 15 E  
Surveyed by John C. Smith  
U.S. Dep. Sur

Under his contract No 16  
Dated Nov. 1<sup>st</sup> 1890

Survey commenced June 1891  
completed

Township No. 29 N.

Range No. 15 E. & S.R.R. Mer.

1A

BOOK 594

|    |    |    |    |    |    |
|----|----|----|----|----|----|
| 6  | 5  | 4  | 3  | 2  | 1  |
| 7  | 8  | 9  | 10 | 11 | 12 |
| 18 | 17 | 16 | 15 | 14 | 13 |
| 19 | 20 | 21 | 22 | 23 | 24 |
| 30 | 29 | 28 | 27 | 26 | 25 |
| 31 | 32 | 33 | 34 | 35 | 36 |

BOOK 594

4  
3  
2  
1  
1  
1  
1

True Meridian

For preliminary talks see  
BOOKS 1 and 12

No. 594

BOOK 594

18

AINS, Subdivisions T. 29 N

R. 15 E.

From the  $\frac{1}{16}$  sec. Standard cor.  
on the south boundary of sec.  
36. west of the  $\frac{1}{4}$  sec. Standard  
cor. T. 29 N. R. 15 E. I run  
North through west  $\frac{1}{2}$  of  
sec. 36.

7 $\frac{1}{2}$  13° E.

over rough country.

20.00

Deposited a marked stone 12 ins. in the ground,  
for  $\frac{1}{16}$  Sec. Cor., dug pits 18X18X12 ins.  $\frac{1}{16}$  on  $\frac{1}{16}$  and  
 $\frac{1}{16}$  W. of corner 5 1-2 ft. dist., and raised a mound of  
earth 1 1-2 ft. high, 3 1-2 ft. base over it.

In  $\frac{1}{16}$  pit drove a stake 2 ft. long, 2 ins. square,  
12 ins. in the ground, marked  $\frac{1}{16}$  S, on  $\frac{1}{16}$  N. face,

28.25

Trail bears N. E. and S. W.

40.00

Set a sandstone  $\frac{1}{16}$  X  $\frac{1}{4}$  X  $\frac{1}{4}$  ins.,  $\frac{1}{16}$  ins.  
in the ground, for  $\frac{1}{16}$  Sec. Cor., marked  $\frac{1}{16}$  on  $\frac{1}{16}$  N...  
face, dug pits 18x18x12 ins.,  $\frac{1}{16}$  E. and  $\frac{1}{16}$  W. of stone  
5 1-2 ft. dist., and raised a mound of earth 1 1-2 ft.  
high, 3 1-2 ft. base, alongside,

60.00

Set a sandstone  $\frac{1}{16}$  X  $\frac{1}{4}$  X  $\frac{1}{4}$  ins.,  $\frac{1}{16}$  ins.  
in the ground, for  $\frac{1}{16}$  Sec. Cor., marked  $\frac{1}{16}$  on  $\frac{1}{16}$  N...  
face, dug pits 18x18x12 ins.,  $\frac{1}{16}$  E. and  $\frac{1}{16}$  W. of stone  
5 1-2 ft. dist., and raised a mound of earth 1 1-2 ft.  
high, 3 1-2 ft. base, alongside,

## CHAINS. Subdivisions T. 29 N R. 15 E.

61.00

Trail bears N. W. and S. E.

80.00

Set a sandstone  $10 \times 10 \times 10$  ins.,  $7$  ins. in the ground, for  $\frac{1}{16}$  Sec. Cor., marked  $\frac{1}{16}$  on N. face, dug pits  $18 \times 18 \times 12$  ins., E. and W. of stone  $5$  1-2 ft. dist., and raised a mound of earth  $1$  1-2 ft. high,  $3$  1-2 ft. base, alongside,

Surface rough

Soil 3rd. rate.

Grass. fair

---

Think I run west on a  
 but line bet. sec. 25 and 36  
 $\frac{1}{4}$  13° E.

18.10

Trail bears N. W. and S. E.

20.00

Set a sandstone  $15 \times 8 \times 7$  ins.,  $11$  ins. in the ground for Cor. to Secs. 25, 26, 35 and 36. marked with  $1$  notch on S. and  $1$  notch on E. edges, dug pits  $18 \times 18 \times 12$  ins. in each Sec.  $5$  1-2 ft. dist. and raised a mound of earth  $2$  ft. high,  $4$  1-2 ft. base, alongside.

Surface rough

Soil 3rd. rate

Some grass.

---

## HAINS. Subdivisions T. 29 N R. 15 E.

Thence I run west on a bearing  
line bet. secs. 26 and 27.  
70. 13° E.

1360 Trail bears N. E. and S. W.

16.00 " " " " "

20.00 Set a sandstone 18 X 16 X 3 ins., 12 ins.  
in the ground, for 1/6 Sec. Cor., marked 1/6 on N...  
face, dug pits 18x18x12 ins., E... and W... of stone  
5 1-2 ft. dist., and raised a mound of earth 1 1-2 ft.  
high, 3 1-2 ft. base, alongside,

Surface rough and broken.

Only 3rd rate

Grass poor.

Thence I run 70° 13' N. through  
East 1/2 sec. 26.

70. 13° E.

20.00 Set a sandstone 18 X 16 X 6 ins., 12 ins.  
in the ground, for 1/6 Sec. Cor., marked 1/6 on N...  
face, dug pits 18x18x12 ins., E... and W... of stone  
5 1-2 ft. dist., and raised a mound of earth 1 1-2 ft.  
high, 3 1-2 ft. base, alongside,

Surface rough

Only 3rd rate.

Grass coarse

## CHAINS. Subdivisions T. 29 N R. 15 E.

Found 1 iron east on a true  
line from the center of SE 14  
on 26.

7a. 13° E

10.00 Spring bears N. 10° W. 776 chains

11.10 Trail bears N. E. and S. W.

19.40 Trail bears N. W. and S. E.

20.00 - Set a sandstone... 13... X... 10... X... 4... ins... 8...  
ins. in the ground, for... Sec. Cor., marked... on  
... W... face, and raised a mound of stone 1 1-2 ft. high  
2 ft. base, alongside. Pits impracticable.

Surface rough  
Soil 3rd. rate.

No Grass.

---

No. 594

BOOK 594 ✓

Subdivisions T. 29... N

R. 15... E.

### General Description.

This is a mountainous township  
therefore I only surveyed enough  
to locate the water; it is  
very rough and broken near  
the springs, and impossible  
to set corners or run  
lines around the spring in  
N.E. 14 of S.E. 14 sec. 26.

The other spring is located  
in the center of S.E. 14  
of S.E. 14 sec. 26.

These springs are said  
to be the only water  
failing water for the  
Ojibwe Indians, in the  
vicinity.

John C. Smith  
U.S. D.S.

June 8<sup>th</sup> 1891

For final notes see Book 47



U. S. Surveyor-General's Office,

TUCSON, A. T., Feb 6<sup>th</sup> 1882

The foregoing Field Notes of the Surveys of  
 Subdivisions of T<sup>h</sup>. 2921  
 R. 15 E. of the

..... Gila and Salt River Meridian  
 in Arizona .....

..... executed by  
 John B. Smith

U. S. Deputy Surveyor, under his contract dated  
 November 1<sup>st</sup> 1898

.....  
 having been critically examined, the necessary correc-  
 tions and explanations made, the said Field Notes and  
 the surveys they describe are hereby approved.

.....  
 Royal C. Johnson  
 U. S. Surveyor-General  
 for the Territory of Arizona.